



US009974982B2

(12) **United States Patent**
Slayton et al.

(10) **Patent No.:** **US 9,974,982 B2**
(45) **Date of Patent:** ***May 22, 2018**

(54) **SYSTEM AND METHOD FOR NONINVASIVE SKIN TIGHTENING**

(71) Applicant: **Guided Therapy Systems, LLC**, Mesa, AZ (US)

(72) Inventors: **Michael H. Slayton**, Tempe, AZ (US);
Peter G. Barthe, Phoenix, AZ (US);
Inder Raj S. Makin, Mesa, AZ (US);
Brian D. O'Connor, Phoenix, AZ (US)

(73) Assignee: **Guided Therapy Systems, LLC**, Mesa, AZ (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 136 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/098,139**

(22) Filed: **Apr. 13, 2016**

(65) **Prior Publication Data**
US 2016/0228729 A1 Aug. 11, 2016

Related U.S. Application Data

(63) Continuation of application No. 13/964,820, filed on Aug. 12, 2013, now Pat. No. 9,320,537, which is a (Continued)

(51) **Int. Cl.**
A61B 7/02 (2006.01)
A61N 7/02 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61N 7/02** (2013.01); **A61B 5/682** (2013.01); **A61B 5/6842** (2013.01); **A61B 8/08** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC A61N 2007/027; A61N 2007/025; A61N 7/02

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,427,348 A 9/1947 Bond et al.
3,913,386 A 10/1975 Saglio
(Continued)

FOREIGN PATENT DOCUMENTS

CN 104027893 9/2014
DE 4029175 3/1992
(Continued)

OTHER PUBLICATIONS


Alam, M., "The future of noninvasive procedural dermatology". *Semin Cutan Med Surg.* Mar. 2013; 32(1):59-61.
(Continued)

Primary Examiner — Ronald Hupczey, Jr.
(74) *Attorney, Agent, or Firm* — Knobbe Martens Olson & Bear LLP

(57) **ABSTRACT**

A method and system for noninvasive face lifts and deep tissue tightening are disclosed. An exemplary method and treatment system are configured for the imaging, monitoring, and thermal injury to treat the SMAS region. In accordance with an exemplary embodiment, the exemplary method and system are configured for treating the SMAS region by first, imaging of the region of interest for localization of the treatment area and surrounding structures, second, delivery of ultrasound energy at a depth, distribution, timing, and energy level to achieve the desired therapeutic effect, and third to monitor the treatment area before, during, and after therapy to plan and assess the results and/or provide feedback.

20 Claims, 28 Drawing Sheets



Related U.S. Application Data

	continuation of application No. 12/028,636, filed on Feb. 8, 2008, now Pat. No. 8,535,228, which is a continuation-in-part of application No. 11/163,151, filed on Oct. 6, 2005, and a continuation-in-part of application No. 11/163,148, filed on Oct. 6, 2005.	4,646,756 A	3/1987	Watmough
		4,663,358 A	5/1987	Hyon
		4,668,516 A	5/1987	Duraffourd et al.
		4,672,591 A	6/1987	Breimesser et al.
		4,680,499 A	7/1987	Umemura et al.
		4,697,588 A	10/1987	Reichenberger
		4,754,760 A	7/1988	Fukukita et al.
		4,757,820 A	7/1988	Itoh
		4,771,205 A	9/1988	Mequio
(60)	Provisional application No. 60/616,755, filed on Oct. 6, 2004, provisional application No. 60/616,754, filed on Oct. 6, 2004.	4,801,459 A	1/1989	Liburdy
		4,803,625 A	2/1989	Fu et al.
		4,807,633 A	2/1989	Fry
		4,817,615 A	4/1989	Fukukita et al.
		4,858,613 A	8/1989	Fry
(51)	Int. Cl.	4,860,732 A	8/1989	Hasegawa et al.
	<i>A61B 5/00</i> (2006.01)	4,865,041 A	9/1989	Hassler
	<i>A61B 8/08</i> (2006.01)	4,865,042 A	9/1989	Umemura
	<i>A61B 8/12</i> (2006.01)	4,867,169 A	9/1989	Machida
	<i>A61H 23/02</i> (2006.01)	4,874,562 A	10/1989	Hyon
	<i>A61N 7/00</i> (2006.01)	4,875,487 A	10/1989	Seppi
	<i>G01S 15/89</i> (2006.01)	4,881,212 A	11/1989	Takeuchi
	<i>A61B 17/32</i> (2006.01)	4,891,043 A	1/1990	Zeimer et al.
	<i>A61B 8/00</i> (2006.01)	4,893,624 A	1/1990	Lele
		4,896,673 A	1/1990	Rose
(52)	U.S. Cl.	4,900,540 A	2/1990	Ryan et al.
	CPC <i>A61B 8/0858</i> (2013.01); <i>A61B 8/12</i> (2013.01); <i>A61B 8/4483</i> (2013.01); <i>A61B 8/483</i> (2013.01); <i>A61B 8/546</i> (2013.01); <i>A61B 17/320068</i> (2013.01); <i>A61H 23/0245</i> (2013.01); <i>A61N 7/00</i> (2013.01); <i>G01S 15/8909</i> (2013.01); <i>A61B 8/4281</i> (2013.01); <i>A61B 8/4455</i> (2013.01); <i>A61H 2201/5007</i> (2013.01); <i>A61H 2230/50</i> (2013.01); <i>A61N 2007/0008</i> (2013.01); <i>A61N 2007/0034</i> (2013.01); <i>G01S 15/899</i> (2013.01)	4,901,729 A	2/1990	Saitoh
		4,917,096 A	4/1990	Englehart
		4,932,414 A	6/1990	Coleman et al.
		4,938,216 A	7/1990	Lele
		4,938,217 A	7/1990	Lele
		4,947,046 A	8/1990	Kawabata et al.
		4,951,653 A	8/1990	Fry
		4,955,365 A	9/1990	Fry
		4,958,626 A	9/1990	Nambu
		4,976,709 A	12/1990	Sand
		4,979,501 A	12/1990	Valchanov
		4,992,989 A	2/1991	Watanabe et al.
		5,012,797 A	5/1991	Liang
		5,018,508 A	5/1991	Fry et al.
		5,030,874 A	7/1991	Saito et al.
		5,036,855 A	8/1991	Fry
		5,040,537 A	8/1991	Katakura
		5,054,310 A	10/1991	Flynn
		5,054,470 A	10/1991	Fry
		5,054,491 A	10/1991	Saito et al.
		5,070,879 A	12/1991	Herres
		5,088,495 A	2/1992	Miyagawa
		5,115,814 A	5/1992	Griffith
		5,117,832 A	6/1992	Sanghvi
		5,123,418 A	6/1992	Saurel
		5,142,511 A	8/1992	Kanai et al.
		5,143,063 A	9/1992	Fellner
		5,143,074 A	9/1992	Dory
		5,149,319 A	9/1992	Unger
		5,150,711 A	9/1992	Dory
		5,150,714 A	9/1992	Green
		5,152,294 A	10/1992	Mochizuki et al.
		5,156,144 A	10/1992	Iwasaki
		5,158,536 A	10/1992	Sekins
		5,159,931 A	11/1992	Pini
		5,163,421 A	11/1992	Bernstein
		5,163,436 A	11/1992	Saitoh et al.
		5,178,135 A	1/1993	Uchiyama et al.
		5,190,518 A	3/1993	Takasu
		5,190,766 A	3/1993	Ishihara
		5,191,880 A	3/1993	McLeod
		5,205,287 A	4/1993	Erbel et al.
		5,209,720 A	5/1993	Unger
		5,212,671 A	5/1993	Fujii et al.
		5,215,680 A	6/1993	D'Arrigo
		5,224,467 A	7/1993	Oku
		5,230,334 A	7/1993	Klopotek
		5,230,338 A	7/1993	Allen et al.
		5,247,924 A	9/1993	Suzuki et al.
		5,255,681 A	10/1993	Ishimura et al.
		5,257,970 A	11/1993	Dougherty
		5,265,614 A	11/1993	Hayakawa
		5,267,985 A	12/1993	Shimada
		5,269,297 A	12/1993	Weng

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,965,455 A	6/1976	Hurwitz
3,992,925 A	11/1976	Perilhou
4,039,312 A	8/1977	Patru
4,059,098 A	11/1977	Murdock
4,101,795 A	7/1978	Fukumoto
4,151,834 A	5/1979	Sato et al.
4,166,967 A	9/1979	Benes et al.
4,211,948 A	7/1980	Smith et al.
4,211,949 A	7/1980	Brisken et al.
4,213,344 A	7/1980	Rose
4,276,491 A	6/1981	Daniel
4,315,514 A	2/1982	Drewes et al.
4,325,381 A	4/1982	Glenn
4,343,301 A	8/1982	Indech
4,372,296 A	2/1983	Fahim
4,379,145 A	4/1983	Masuhō et al.
4,381,007 A	4/1983	Doss
4,381,787 A	5/1983	Hottinger
4,397,314 A	8/1983	Vaguine
4,409,839 A	10/1983	Taenzer
4,431,008 A	2/1984	Wanner et al.
4,441,486 A	4/1984	Pounds
4,452,084 A	6/1984	Taenzer
4,484,569 A	11/1984	Driller
4,507,582 A	3/1985	Glenn
4,513,749 A	4/1985	Kino
4,513,750 A	4/1985	Heyman et al.
4,527,550 A	7/1985	Ruggera et al.
4,528,979 A	7/1985	Marchenko
4,534,221 A	8/1985	Fife et al.
4,566,459 A	1/1986	Umemura et al.
4,567,895 A	2/1986	Putzke
4,586,512 A	5/1986	Do-Huu
4,601,296 A	7/1986	Yerushalmi
4,620,546 A	11/1986	Aida et al.
4,637,256 A	1/1987	Sugiyama et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

5,282,797 A	2/1994	Chess	5,622,175 A	4/1997	Sudol et al.
5,295,484 A	3/1994	Marcus	5,617,858 A	5/1997	Taverna et al.
5,295,486 A	3/1994	Wollschlager et al.	5,638,819 A	6/1997	Manwaring et al.
5,304,169 A	4/1994	Sand	5,644,085 A	7/1997	Lorraine et al.
5,305,756 A	4/1994	Entrekin et al.	5,647,373 A	7/1997	Paltieli
5,321,520 A	6/1994	Inga et al.	5,655,535 A	8/1997	Frlemel et al.
5,323,779 A	6/1994	Hardy et al.	5,655,538 A	8/1997	Lorraine
5,327,895 A	7/1994	Hashimoto et al.	5,657,760 A	8/1997	Ying
5,329,202 A	7/1994	Garlick et al.	5,658,328 A	8/1997	Johnson
5,348,016 A	9/1994	Unger et al.	5,660,836 A	8/1997	Knowlton
5,358,466 A	10/1994	Aida et al.	5,662,116 A	9/1997	Kondo
5,360,268 A	11/1994	Hayashi	5,665,053 A	9/1997	Jacobs
5,370,121 A	12/1994	Reichenberger	5,665,141 A	9/1997	Vago
5,370,122 A	12/1994	Kunig et al.	5,671,746 A	9/1997	Dreschel et al.
5,371,483 A	12/1994	Bhardwaj	5,673,699 A	10/1997	Trahey et al.
5,375,602 A	12/1994	Lancee et al.	5,676,692 A	10/1997	Sanghvi
5,379,773 A	1/1995	Hornsby	5,685,820 A	11/1997	Riek et al.
5,380,280 A	1/1995	Peterson	5,690,608 A	11/1997	Watanabe
5,380,519 A	1/1995	Schneider et al.	5,694,936 A	12/1997	Fujimoto
5,383,917 A	1/1995	Desai et al.	5,697,897 A	12/1997	Buchholtz
5,391,140 A	2/1995	Schaetzle et al.	5,701,900 A	12/1997	Shehada et al.
5,391,197 A	2/1995	Burdette et al.	5,704,361 A	1/1998	Seward et al.
5,392,259 A	2/1995	Bolorforosh	5,706,252 A	1/1998	Le Verrier et al.
5,396,143 A	3/1995	Seyed-Bolorforosh et al.	5,706,564 A	1/1998	Rhyne
5,398,689 A	3/1995	Connor et al.	5,715,823 A	2/1998	Wood et al.
5,406,503 A	4/1995	Williams	5,720,287 A	2/1998	Chapelon et al.
5,413,550 A	5/1995	Castel	5,722,411 A	3/1998	Suzuki
5,417,216 A	5/1995	Tanaka	5,727,554 A	3/1998	Kalend et al.
5,419,327 A	5/1995	Rohwedder	5,735,280 A	4/1998	Sherman et al.
5,423,220 A	6/1995	Finsterwald et al.	5,743,863 A	4/1998	Chapelon
5,435,311 A	7/1995	Umemura	5,746,005 A	5/1998	Steinberg
5,438,998 A	8/1995	Hanafy	5,746,762 A	5/1998	Bass
5,443,068 A	8/1995	Cline et al.	5,748,767 A	5/1998	Raab
5,458,596 A	10/1995	Lax	5,749,364 A	5/1998	Sliwa et al.
5,460,179 A	10/1995	Okunuki et al.	5,755,228 A	5/1998	Wilson et al.
5,460,595 A	10/1995	Hall et al.	5,755,753 A	5/1998	Knowlton
5,469,854 A	11/1995	Unger et al.	5,762,066 A	6/1998	Law
5,471,488 A	12/1995	Fujio	5,763,886 A	6/1998	Schulte
5,472,405 A	12/1995	Buchholtz et al.	5,769,790 A	6/1998	Watkins
5,487,388 A	1/1996	Rello et al.	5,779,644 A	7/1998	Eberle et al.
5,492,126 A	2/1996	Hennige	5,792,058 A	8/1998	Lee
5,496,256 A	3/1996	Bock	5,795,297 A	8/1998	Daigle
5,501,655 A	3/1996	Rolt	5,795,311 A	8/1998	Wess
5,503,152 A	4/1996	Oakley et al.	5,810,009 A	9/1998	Mine et al.
5,503,320 A	4/1996	Webster et al.	5,810,888 A	9/1998	Fenn
5,507,790 A	4/1996	Weiss	5,814,599 A	9/1998	Mitragotri et al.
5,511,296 A	4/1996	Dias et al.	5,817,013 A	10/1998	Ginn et al.
5,520,188 A	5/1996	Hennige	5,817,021 A	10/1998	Reichenberger
5,522,869 A	6/1996	Burdette	5,820,564 A	10/1998	Slayton
5,523,058 A	6/1996	Umemura et al.	5,823,962 A	10/1998	Schaetzle
5,524,620 A	6/1996	Rosenchein	5,827,204 A	10/1998	Grandia et al.
5,524,624 A	6/1996	Tepper	5,840,032 A	11/1998	Hatfield et al.
5,524,625 A	6/1996	Okazaki	5,844,140 A	12/1998	Seale
5,526,624 A	6/1996	Berg	5,853,367 A	12/1998	Chalek et al.
5,526,812 A	6/1996	Dumoulin et al.	5,869,751 A	2/1999	Bonin
5,526,814 A	6/1996	Cline et al.	5,871,524 A	2/1999	Knowlton
5,526,815 A	6/1996	Granz	5,873,902 A	2/1999	Sanghvi
5,529,070 A	6/1996	Augustine et al.	5,876,341 A	3/1999	Wang et al.
5,540,235 A	7/1996	Wilson	5,879,303 A	3/1999	Averkiou et al.
5,558,092 A	9/1996	Unger	5,882,557 A	3/1999	Hayakawa
5,560,362 A	10/1996	Sliwa et al.	5,891,034 A	4/1999	Bucholz
5,575,291 A	11/1996	Hayakawa	5,895,356 A	4/1999	Andrus et al.
5,575,807 A	11/1996	Faller	5,899,861 A	5/1999	Friemel et al.
5,577,502 A	11/1996	Darrow et al.	5,904,659 A	5/1999	Duarte
5,577,507 A	11/1996	Snyder et al.	5,919,219 A	7/1999	Knowlton
5,577,991 A	11/1996	Akui et al.	5,923,099 A	7/1999	Bilir
5,580,575 A	12/1996	Unger et al.	5,924,989 A	7/1999	Polz
5,643,179 A	1/1997	Fujimoto	5,928,169 A	7/1999	Schatzle et al.
5,601,526 A	2/1997	Chapelon	5,931,805 A	8/1999	Brisken
5,603,323 A	2/1997	Pflugrath et al.	5,938,606 A	8/1999	Bonnefous
5,605,154 A	2/1997	Ries et al.	5,938,612 A	8/1999	Kline-Schoder
5,609,562 A	3/1997	Kaali	5,948,011 A	9/1999	Knowlton
5,615,091 A	3/1997	Palatnik	5,957,844 A	9/1999	Dekel
5,618,275 A	4/1997	Bock	5,957,882 A	9/1999	Nita et al.
5,620,479 A	4/1997	Diederich	5,957,941 A	9/1999	Ream
			5,964,707 A	10/1999	Fenster et al.
			5,967,980 A	10/1999	Ferre et al.
			5,968,034 A	10/1999	Fullmer
			5,971,949 A	10/1999	Levin

(56)

References Cited

U.S. PATENT DOCUMENTS

5,977,538	A	11/1999	Unger et al.	6,350,276	B1	2/2002	Knowlton
5,984,881	A	11/1999	Ishibashi et al.	6,356,780	B1	3/2002	Licato et al.
5,984,882	A	11/1999	Rosenchein	6,361,531	B1	3/2002	Hissong
5,990,598	A	11/1999	Sudol et al.	6,370,411	B1	4/2002	Osadchy et al.
5,997,471	A	12/1999	Gumb et al.	6,375,672	B1	4/2002	Aksan
5,997,497	A	12/1999	Nita et al.	6,377,854	B1	4/2002	Knowlton
5,999,843	A	12/1999	Anbar	6,377,855	B1	4/2002	Knowlton
6,004,262	A	12/1999	Putz et al.	6,381,497	B1	4/2002	Knowlton
6,007,499	A	12/1999	Martin et al.	6,381,498	B1	4/2002	Knowlton
6,013,032	A	1/2000	Savord	6,387,380	B1	5/2002	Knowlton
6,014,473	A	1/2000	Hossack et al.	6,390,982	B1	5/2002	Bova et al.
6,016,255	A	1/2000	Bolan et al.	6,405,090	B1	6/2002	Knowlton
6,019,724	A	2/2000	Gronningsaeter et al.	6,409,720	B1	6/2002	Hissong
6,022,308	A	2/2000	Williams	6,413,216	B1	7/2002	Cain et al.
6,022,327	A	2/2000	Chang	6,413,253	B1	7/2002	Koop
6,030,374	A	2/2000	McDaniel	6,413,254	B1	7/2002	Hissong
6,036,646	A	3/2000	Barthe	6,419,648	B1	7/2002	Vitek
6,039,048	A	3/2000	Silberg	6,423,007	B2	7/2002	Lizzi et al.
6,039,689	A	3/2000	Lizzi	6,425,865	B1	7/2002	Salcudean
6,042,556	A	3/2000	Beach	6,425,867	B1	7/2002	Vaezy
6,049,159	A	4/2000	Barthe	6,425,912	B1	7/2002	Knowlton
6,050,943	A	4/2000	Slayton	6,428,477	B1	8/2002	Mason
6,059,727	A	5/2000	Fowlkes	6,428,532	B1	8/2002	Doukas
6,071,239	A	6/2000	Cribbs	6,430,446	B1	8/2002	Knowlton
6,080,108	A	6/2000	Dunham	6,432,057	B1	8/2002	Mazess et al.
6,083,148	A	7/2000	Williams	6,432,067	B1	8/2002	Martin
6,086,535	A	7/2000	Ishibashi	6,432,101	B1	8/2002	Weber
6,086,580	A	7/2000	Mordon et al.	6,436,061	B1	8/2002	Costantino
6,090,054	A	7/2000	Tagishi	6,438,424	B1	8/2002	Knowlton
6,093,148	A	7/2000	Fujimoto	6,440,071	B1	8/2002	Slayton
6,093,883	A	7/2000	Sanghvi	6,440,121	B1	8/2002	Weber
6,101,407	A	8/2000	Groezienger	6,443,914	B1	9/2002	Costantino
6,106,469	A	8/2000	Suzuki et al.	6,451,013	B1	9/2002	Bays et al.
6,113,558	A	9/2000	Rosenchein	6,453,202	B1	9/2002	Knowlton
6,113,559	A	9/2000	Klopotek	6,461,304	B1	10/2002	Tanaka et al.
6,120,452	A	9/2000	Barthe	6,461,378	B1	10/2002	Knowlton
6,123,081	A	9/2000	Durette	6,470,216	B1	10/2002	Knowlton
6,126,619	A	10/2000	Peterson et al.	6,338,716	B1	11/2002	Hossack
6,135,971	A	10/2000	Hutchinson	6,488,626	B1	12/2002	Lizzi
6,139,499	A	10/2000	Wilk	6,491,657	B2	12/2002	Rowe
6,159,150	A	12/2000	Yale et al.	6,500,121	B1	12/2002	Slayton
6,171,244	B1	1/2001	Finger et al.	6,500,141	B1	12/2002	Irian
6,176,840	B1	1/2001	Nishimura	6,508,774	B1	1/2003	Acker
6,183,426	B1	2/2001	Akisada	6,511,427	B1	1/2003	Sliwa, Jr. et al.
6,183,502	B1	2/2001	Takeuchi	6,511,428	B1	1/2003	Azuma
6,183,773	B1	2/2001	Anderson	6,514,244	B2	2/2003	Pope
6,190,323	B1	2/2001	Dias	6,517,484	B1	2/2003	Wilk
6,190,336	B1	2/2001	Duarte	6,524,250	B1	2/2003	Weber
6,193,658	B1	2/2001	Wendelken	6,666,835	B2	3/2003	Martin
6,210,327	B1	4/2001	Brackett et al.	6,540,679	B2	4/2003	Slayton
6,213,948	B1	4/2001	Barthe	6,540,685	B1	4/2003	Rhoads et al.
6,216,029	B1	4/2001	Paltieli	6,540,700	B1	4/2003	Fujimoto et al.
6,233,476	B1	5/2001	Strommer et al.	6,547,788	B1	4/2003	Maguire et al.
6,234,990	B1	5/2001	Rowe et al.	6,554,771	B1	4/2003	Buil et al.
6,241,753	B1	6/2001	Knowlton	6,569,099	B1	5/2003	Babaev
6,246,898	B1	6/2001	Vesely et al.	6,569,108	B2	5/2003	Sarvazyan et al.
6,251,074	B1	6/2001	Averkiou et al.	6,572,552	B2	6/2003	Fukukita
6,251,088	B1	6/2001	Kaufman et al.	6,575,956	B1	6/2003	Brisken et al.
6,268,405	B1	7/2001	Yao	6,595,934	B1	7/2003	Hissong
6,273,864	B1	8/2001	Duarte	6,599,256	B1	7/2003	Acker
6,280,402	B1	8/2001	Ishibashi et al.	6,605,080	B1	8/2003	Altshuler et al.
6,287,257	B1	9/2001	Matichek	6,607,498	B2	8/2003	Eshel
6,287,304	B1	9/2001	Eggers et al.	6,618,620	B1	9/2003	Freundlich et al.
6,296,619	B1	10/2001	Brisken	6,623,430	B1	9/2003	Slayton
6,301,989	B1	10/2001	Brown et al.	6,626,854	B2	9/2003	Friedman
6,307,302	B1	10/2001	Toda	6,626,855	B1	9/2003	Weng
6,309,355	B1	10/2001	Cain et al.	6,638,226	B2	10/2003	He et al.
6,311,090	B1	10/2001	Knowlton	6,645,150	B2	11/2003	Angelsen et al.
6,315,741	B1	11/2001	Martin	6,645,162	B2	11/2003	Friedman
6,322,509	B1	11/2001	Pan et al.	6,662,054	B2	12/2003	Kreindel
6,322,532	B1	11/2001	D'Sa	6,663,627	B2	12/2003	Francischelli
6,325,540	B1	12/2001	Lounsberry et al.	6,665,806	B1	12/2003	Shimizu
6,325,758	B1	12/2001	Carol et al.	6,669,638	B1	12/2003	Miller
6,325,769	B1	12/2001	Klopotek	6,685,639	B1	2/2004	Wang et al.
6,325,798	B1	12/2001	Edwards et al.	6,685,640	B1	2/2004	Fry
				6,692,450	B1	2/2004	Coleman
				6,699,237	B2	3/2004	Weber
				6,716,184	B2	4/2004	Vaezy et al.
				6,719,449	B1	4/2004	Laughlin

(56)

References Cited

U.S. PATENT DOCUMENTS

6,719,694 B2	4/2004	Weng	7,615,015 B2	11/2009	Coleman
6,726,627 B1	4/2004	Lizzi et al.	7,615,016 B2	11/2009	Barthe
6,733,449 B1	5/2004	Krishnamurthy et al.	7,631,611 B1	12/2009	Dick et al.
6,749,624 B2	6/2004	Knowlton	7,686,763 B2	3/2010	Vaezy et al.
6,772,490 B2	8/2004	Toda	7,694,406 B2	4/2010	Wildes et al.
6,773,409 B2	8/2004	Truckai et al.	7,695,437 B2	4/2010	Quistgaard et al.
6,775,404 B1	8/2004	Pagoulatos et al.	7,727,156 B2	6/2010	Angelsen et al.
6,790,187 B2	9/2004	Thompson et al.	7,758,524 B2	7/2010	Barthe
6,824,516 B2	11/2004	Batten et al.	7,766,848 B2	8/2010	Desilets et al.
6,825,176 B2	11/2004	White et al.	7,789,841 B2	9/2010	Huckle et al.
6,835,940 B2	12/2004	Morikawa et al.	7,819,826 B2	10/2010	Diederich et al.
6,846,290 B2*	1/2005	Lizzi A61B 8/0858 600/439	7,819,826 B2	10/2010	Azhari et al.
			7,828,734 B2	10/2010	Barthe
			7,824,348 B2	11/2010	Hasegawa et al.
			7,833,162 B2	11/2010	Cribbs et al.
			7,841,984 B2	11/2010	Mast et al.
			7,846,096 B2	12/2010	Desilets et al.
			7,857,773 B2	12/2010	Desilets et al.
6,875,176 B2	4/2005	Mourad et al.	7,875,023 B2	1/2011	Eshel et al.
6,882,884 B1	4/2005	Mosk et al.	7,901,359 B2	3/2011	Mandrusov et al.
6,887,239 B2	5/2005	Elstrom	7,905,007 B2	3/2011	Calisti et al.
6,889,089 B2	5/2005	Behl	7,905,844 B2	3/2011	Desilets et al.
6,896,657 B2	5/2005	Willis	7,914,453 B2	3/2011	Slayton et al.
6,902,536 B2	6/2005	Manna	7,914,469 B2	3/2011	Torbati
6,905,466 B2	6/2005	Salgo	7,955,281 B2	6/2011	Pedersen et al.
6,918,907 B2	7/2005	Kelly	7,967,764 B2	6/2011	Lidgren et al.
6,920,883 B2	7/2005	Besette	7,967,839 B2	6/2011	Flock et al.
6,921,371 B2	7/2005	Wilson	7,955,262 B2	7/2011	Rosenberg
6,932,771 B2	8/2005	Whitmore	7,993,289 B2	8/2011	Quistgaard et al.
6,932,814 B2	8/2005	Wood	8,057,465 B2	9/2011	Sliwa, Jr. et al.
6,936,044 B2	8/2005	McDaniel	8,057,389 B2	11/2011	Barthe et al.
6,936,046 B2	8/2005	Hissong	8,066,641 B2	11/2011	Barthe et al.
6,945,937 B2	9/2005	Culp et al.	8,123,707 B2	2/2012	Huckle et al.
6,948,843 B2	9/2005	Laugham et al.	8,128,618 B2	3/2012	Gliklich et al.
6,953,941 B2	10/2005	Nakano et al.	8,133,180 B2	3/2012	Slayton et al.
6,958,043 B2	10/2005	Hissong	8,133,191 B2	3/2012	Rosenberg et al.
6,971,994 B1	12/2005	Young et al.	8,142,200 B2	3/2012	Crunkilton et al.
6,974,417 B2	12/2005	Lockwood	8,152,904 B2	4/2012	Slobodzian et al.
6,976,492 B2	12/2005	Ingle	8,166,332 B2	4/2012	Barthe et al.
6,992,305 B2	1/2006	Maezawa et al.	8,182,428 B2	5/2012	Angelsen et al.
6,997,923 B2	2/2006	Anderson	8,197,409 B2	6/2012	Foley et al.
7,006,874 B2	2/2006	Knowlton	8,206,299 B2	6/2012	Foley et al.
7,020,528 B2	3/2006	Neev	8,208,346 B2	6/2012	Crunkilton
7,022,089 B2	4/2006	Ooba	8,211,017 B2	7/2012	Foley et al.
7,058,440 B2	6/2006	Heuscher et al.	8,262,591 B2	9/2012	Pedersen et al.
7,063,666 B2	6/2006	Weng	8,262,650 B2	9/2012	Zanelli et al.
7,070,565 B2	7/2006	Vaezy et al.	8,264,126 B2	9/2012	Toda et al.
7,074,218 B2	7/2006	Washington et al.	8,273,037 B2	9/2012	Kreindel et al.
7,094,252 B2	8/2006	Koop	8,282,554 B2	10/2012	Makin et al.
7,108,663 B2	9/2006	Talish et al.	8,333,700 B1	12/2012	Barthe et al.
7,115,123 B2	10/2006	Knowlton	8,337,407 B2	12/2012	Quistgaard et al.
7,122,029 B2	10/2006	Koop et al.	8,343,051 B2	1/2013	Desilets et al.
7,142,905 B2	11/2006	Slayton	8,366,622 B2	2/2013	Slayton et al.
7,165,451 B1	1/2007	Brooks et al.	8,398,549 B2	3/2013	Palmeri et al.
7,179,238 B2	2/2007	Hissong	8,409,097 B2	4/2013	Slayton et al.
7,189,230 B2	3/2007	Knowlton	8,425,435 B2	4/2013	Wing et al.
7,229,411 B2	6/2007	Slayton	8,388,535 B2	5/2013	Weng et al.
7,235,592 B2	6/2007	Muratoglu	8,444,562 B2	5/2013	Barthe et al.
7,258,674 B2	8/2007	Cribbs	8,460,193 B2	6/2013	Barthe et al.
7,273,459 B2	9/2007	Desilets	8,480,585 B2	7/2013	Slayton et al.
7,294,125 B2	11/2007	Phalen et al.	8,506,486 B2	8/2013	Slayton et al.
7,297,117 B2	11/2007	Trucco	8,523,775 B2	9/2013	Barthe et al.
7,303,555 B2	12/2007	Makin et al.	8,535,228 B2	9/2013	Slayton et al.
7,311,679 B2	12/2007	Desilets et al.	8,570,837 B2	10/2013	Toda et al.
7,327,071 B2	2/2008	Nishiyama et al.	8,573,392 B2	11/2013	Bennett et al.
7,331,951 B2	2/2008	Eshel et al.	8,585,618 B2	11/2013	Hunziker et al.
7,332,985 B2	2/2008	Larson et al.	8,604,672 B2	12/2013	Toda et al.
7,347,855 B2	3/2008	Eshel	8,622,937 B2	1/2014	Weng et al.
RE40,403 E	6/2008	Cho et al.	8,636,665 B2	1/2014	Slayton et al.
7,393,325 B2	7/2008	Barthe	8,640,193 B2	1/2014	Shigeeda
7,398,116 B2	7/2008	Edwards	8,641,622 B2	2/2014	Barthe et al.
7,399,279 B2	7/2008	Abend et al.	8,663,112 B2	3/2014	Slayton et al.
7,491,171 B2	2/2009	Barthe et al.	8,672,848 B2	3/2014	Slayton et al.
7,510,536 B2	3/2009	Foley et al.	8,690,778 B2	4/2014	Slayton et al.
7,517,315 B2	4/2009	Willis	8,690,779 B2	4/2014	Slayton et al.
7,530,356 B2	5/2009	Slayton	8,690,780 B2	4/2014	Slayton et al.
7,530,958 B2	5/2009	Slayton	8,708,935 B2	4/2014	Barthe et al.
7,532,201 B2	5/2009	Quistgaard et al.	8,715,186 B2	5/2014	Slayton et al.
7,571,336 B2	8/2009	Barthe	8,726,781 B2	5/2014	Eckhoff et al.
7,601,120 B2	10/2009	Moilanen et al.	8,728,071 B2	5/2014	Lischinsky et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,753,295 B2	6/2014	Thierman	2003/0065313 A1	4/2003	Koop
8,758,253 B2	6/2014	Sano et al.	2003/0066708 A1	4/2003	Allison et al.
8,836,203 B2	9/2014	Nobles et al.	2003/0073907 A1	4/2003	Taylor
8,857,438 B2	10/2014	Barthe et al.	2003/0074023 A1	4/2003	Kaplan
8,858,471 B2	10/2014	Barthe et al.	2003/0083536 A1	5/2003	Eshel
8,915,853 B2	12/2014	Barthe et al.	2003/0092988 A1	5/2003	Makin
8,915,854 B2	12/2014	Slayton et al.	2003/0097071 A1	5/2003	Halmann et al.
8,915,870 B2	12/2014	Barthe et al.	2003/0099383 A1	5/2003	Lefebvre
8,920,320 B2	12/2014	Barthe et al.	2003/0125629 A1	7/2003	Ustuner
8,920,324 B2	12/2014	Slayton et al.	2003/0135135 A1	7/2003	Miwa et al.
8,926,533 B2	1/2015	Bockenstedt et al.	2003/0139790 A1	7/2003	Ingle et al.
8,932,224 B2	1/2015	Barthe et al.	2003/0153961 A1	8/2003	Babaev
8,932,238 B2	1/2015	Wing et al.	2003/0171678 A1	9/2003	Batten et al.
9,011,336 B2	4/2015	Slayton et al.	2003/0171701 A1	9/2003	Babaev
9,039,617 B2	5/2015	Slayton et al.	2003/0176790 A1	9/2003	Slayton
9,039,619 B2	5/2015	Barthe et al.	2003/0191396 A1	10/2003	Sanghvi
9,095,697 B2	8/2015	Barthe et al.	2003/0200481 A1	10/2003	Stanley
9,114,247 B2	8/2015	Barthe et al.	2003/0212129 A1	11/2003	Liu et al.
9,272,162 B2	3/2016	Slayton et al.	2003/0212351 A1	11/2003	Hissong
9,283,409 B2	3/2016	Slayton et al.	2003/0212393 A1	11/2003	Knowlton
9,283,410 B2	3/2016	Slayton et al.	2003/0216648 A1	11/2003	Lizzi et al.
9,320,537 B2	4/2016	Slayton et al.	2003/0216795 A1	11/2003	Harth
9,421,029 B2	8/2016	Barthe et al.	2003/0220536 A1	11/2003	Hissong
9,427,600 B2	8/2016	Barthe et al.	2003/0220585 A1	11/2003	Hissong
9,427,601 B2	8/2016	Barthe et al.	2003/0229331 A1	12/2003	Brisken et al.
9,440,096 B2	9/2016	Barthe et al.	2003/0233085 A1	12/2003	Giammarusti
9,510,802 B2	12/2016	Barthe et al.	2003/0236487 A1	12/2003	Knowlton
9,522,290 B2	12/2016	Slayton et al.	2004/0000316 A1	1/2004	Knowlton
9,533,175 B2	1/2017	Slayton et al.	2004/0001809 A1	1/2004	Brisken
2001/0009997 A1	7/2001	Pope	2004/0002658 A1	1/2004	Marian, Jr.
2001/0009999 A1	7/2001	Kaufman et al.	2004/0002705 A1	1/2004	Knowlton
2001/0014780 A1	8/2001	Martin	2004/0010222 A1	1/2004	Nunomura et al.
2001/0014819 A1	8/2001	Ingle	2004/0015079 A1	1/2004	Berger et al.
2001/0031922 A1	10/2001	Weng	2004/0015106 A1	1/2004	Coleman
2001/0039380 A1	11/2001	Larson et al.	2004/0030227 A1	2/2004	Littrup
2001/0041880 A1	11/2001	Brisken	2004/0039312 A1	2/2004	Hillstead
2002/0000763 A1	1/2002	Jones	2004/0039418 A1	2/2004	Elstrom
2002/0002345 A1	1/2002	Marlinghaus	2004/0041563 A1	3/2004	Lewin et al.
2002/0040199 A1	4/2002	Klopotek	2004/0041880 A1	3/2004	Ikeda et al.
2002/0040442 A1	4/2002	Ishidera	2004/0042168 A1	3/2004	Yang et al.
2002/0055702 A1	5/2002	Atala	2004/0044375 A1	3/2004	Diederich et al.
2002/0062077 A1	5/2002	Emmenegger	2004/0049134 A1	3/2004	Tosaya et al.
2002/0062142 A1	5/2002	Knowlton	2004/0049734 A1	3/2004	Tosaya et al.
2002/0072691 A1	6/2002	Thompson et al.	2004/0059266 A1	3/2004	Fry
2002/0082528 A1	6/2002	Friedman	2004/0068186 A1	4/2004	Ishida et al.
2002/0082529 A1	6/2002	Suorsa et al.	2004/0073079 A1	4/2004	Altshuler et al.
2002/0082589 A1	6/2002	Friedman	2004/0073113 A1	4/2004	Salgo
2002/0087080 A1	7/2002	Slayton	2004/0073115 A1	4/2004	Horzewski et al.
2002/0095143 A1	7/2002	Key	2004/0073116 A1	4/2004	Smith
2002/0099094 A1	7/2002	Anderson	2004/0073204 A1	4/2004	Ryan et al.
2002/0115917 A1	8/2002	Honda et al.	2004/0077977 A1	4/2004	Ella et al.
2002/0128648 A1	9/2002	Weber	2004/0082857 A1	4/2004	Schonenberger
2002/0143252 A1	10/2002	Dunne et al.	2004/0082859 A1	4/2004	Schaer
2002/0156400 A1	10/2002	Babaev	2004/0102697 A1	5/2004	Evron
2002/0161357 A1	10/2002	Anderson	2004/0105559 A1	6/2004	Aylward et al.
2002/0165529 A1	11/2002	Danek	2004/0122323 A1	6/2004	Vortman et al.
2002/0168049 A1	11/2002	Schriever	2004/0122493 A1	6/2004	Ishibashi et al.
2002/0169394 A1	11/2002	Eppstein et al.	2004/0143297 A1	7/2004	Ramsey
2002/0169442 A1	11/2002	Neev	2004/0152982 A1	8/2004	Hwang et al.
2002/0173721 A1	11/2002	Grunwald et al.	2004/0158150 A1	8/2004	Rabiner et al.
2002/0193784 A1	12/2002	McHale et al.	2004/0186535 A1	9/2004	Knowlton
2002/0193831 A1	12/2002	Smith	2004/0189155 A1	9/2004	Funakubo
2003/0009153 A1	1/2003	Brisken et al.	2004/0206365 A1	10/2004	Knowlton
2003/0014039 A1	1/2003	Barzell et al.	2004/0210214 A1	10/2004	Knowlton
2003/0018255 A1	1/2003	Martin	2004/0217675 A1	11/2004	Desilets
2003/0018270 A1	1/2003	Makin et al.	2004/0249318 A1	12/2004	Tanaka
2003/0023283 A1	1/2003	McDaniel	2004/0254620 A1	12/2004	Lacoste
2003/0028111 A1	2/2003	Vaezy et al.	2004/0267252 A1	12/2004	Washington et al.
2003/0028113 A1	2/2003	Gilbert et al.	2005/0033201 A1	2/2005	Takahashi
2003/0032900 A1	2/2003	Ella	2005/0033316 A1	2/2005	Kertz
2003/0036706 A1	2/2003	Slayton et al.	2005/0038340 A1	2/2005	Vaezy et al.
2003/0040739 A1	2/2003	Koop	2005/0055018 A1	3/2005	Kreindel
2003/0050678 A1	3/2003	Sierra	2005/0055073 A1	3/2005	Weber
2003/0055417 A1	3/2003	Truckai et al.	2005/0061834 A1	3/2005	Garcia et al.
2003/0060736 A1	3/2003	Martin et al.	2005/0070961 A1	3/2005	Maki
			2005/0074407 A1	4/2005	Smith
			2005/0080469 A1	4/2005	Larson
			2005/0091770 A1	5/2005	Mourad et al.
			2005/0096542 A1	5/2005	Weng

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0104690 A1	5/2005	Larson et al.	2007/0219605 A1	9/2007	Yaroslasky et al.
2005/0113689 A1	5/2005	Gritzky	2007/0238994 A1	10/2007	Stecco et al.
2005/0131302 A1	6/2005	Poland	2007/0239075 A1	10/2007	Rosenberg
2005/0137656 A1	6/2005	Malak	2007/0239077 A1	10/2007	Azhari et al.
2005/0143677 A1	6/2005	Young et al.	2007/0239079 A1	10/2007	Manstein et al.
2005/0154313 A1	7/2005	Desilets	2007/0239142 A1	10/2007	Altshuler
2005/0154314 A1	7/2005	Quistgaard	2008/0015435 A1	1/2008	Cribbs et al.
2005/0154332 A1	7/2005	Zanelli	2008/0027328 A1	1/2008	Klopotek
2005/0154431 A1	7/2005	Quistgaard	2008/0039724 A1	2/2008	Seip et al.
2005/0187495 A1	8/2005	Quistgaard	2008/0071255 A1	3/2008	Barthe
2005/0191252 A1	9/2005	Mitsui	2008/0086054 A1	4/2008	Slayton
2005/0193451 A1	9/2005	Quistgaard	2008/0086056 A1	4/2008	Chang et al.
2005/0193820 A1	9/2005	Sheljaskow et al.	2008/0097214 A1	4/2008	Meyers et al.
2005/0197681 A1	9/2005	Barolet et al.	2008/0097253 A1	4/2008	Pedersen et al.
2005/0228281 A1	10/2005	Nefos	2008/0114251 A1	5/2008	Weymer
2005/0240127 A1	10/2005	Seip et al.	2008/0139974 A1	6/2008	Da Silva
2005/0240170 A1	10/2005	Zhang et al.	2008/0146970 A1	6/2008	Litman et al.
2005/0251120 A1	11/2005	Anderson et al.	2008/0167556 A1	7/2008	Thompson
2005/0256406 A1	11/2005	Barthe	2008/0183077 A1	7/2008	Moreau-Gobard et al.
2005/0261584 A1	11/2005	Eshel	2008/0183110 A1	7/2008	Davenport et al.
2005/0261585 A1	11/2005	Makin et al.	2008/0188745 A1	8/2008	Chen et al.
2005/0267454 A1	12/2005	Hissong	2008/0194964 A1	8/2008	Randall et al.
2005/0288748 A1	12/2005	Li et al.	2008/0195000 A1	8/2008	Spooner et al.
2006/0004306 A1	1/2006	Altshuler	2008/0200810 A1	8/2008	Buchalter
2006/0020260 A1	1/2006	Dover et al.	2008/0200813 A1	8/2008	Quistgaard
2006/0025756 A1	2/2006	Francischelli	2008/0214966 A1	9/2008	Slayton
2006/0042201 A1	3/2006	Curry	2008/0214988 A1	9/2008	Altshuler et al.
2006/0058664 A1	3/2006	Barthe	2008/0221491 A1	9/2008	Slayton
2006/0058671 A1	3/2006	Vitek et al.	2008/0223379 A1	9/2008	Stuker et al.
2006/0058707 A1	3/2006	Barthe	2008/0242991 A1	10/2008	Moon et al.
2006/0058712 A1	3/2006	Altshuler et al.	2008/0243035 A1	10/2008	Crunkilton
2006/0074309 A1	4/2006	Bonnefous	2008/0269608 A1	10/2008	Anderson et al.
2006/0074313 A1	4/2006	Slayton et al.	2008/0275342 A1	11/2008	Barthe
2006/0074314 A1	4/2006	Slayton	2008/0281206 A1	11/2008	Bartlett et al.
2006/0074355 A1	4/2006	Slayton	2008/0281236 A1	11/2008	Eshel et al.
2006/0079816 A1	4/2006	Barthe	2008/0281237 A1	11/2008	Slayton
2006/0079868 A1	4/2006	Makin	2008/0281255 A1	11/2008	Slayton
2006/0084891 A1	4/2006	Barthe	2008/0294073 A1	11/2008	Barthe
2006/0089632 A1	4/2006	Barthe	2008/0319356 A1	12/2008	Cain
2006/0089688 A1	4/2006	Panescu	2009/0005680 A1	1/2009	Jones et al.
2006/0094988 A1	5/2006	Tosaya	2009/0012394 A1	1/2009	Hobelsberger et al.
2006/0111744 A1	5/2006	Makin	2009/0043198 A1	2/2009	Milner et al.
2006/0116583 A1	6/2006	Ogasawara et al.	2009/0043293 A1	2/2009	Pankratov et al.
2006/0116671 A1	6/2006	Slayton	2009/0048514 A1	2/2009	Azhari et al.
2006/0122508 A1	6/2006	Slayton	2009/0069677 A1	3/2009	Chen et al.
2006/0122509 A1	6/2006	Desilets	2009/0093737 A1	4/2009	Chomas et al.
2006/0161062 A1	7/2006	Arditi et al.	2009/0156969 A1	6/2009	Santangelo
2006/0184069 A1	8/2006	Vaitekunas	2009/0163807 A1	6/2009	Sliwa
2006/0184071 A1	8/2006	Klopotek	2009/0171252 A1	7/2009	Bockenstedt et al.
2006/0189972 A1	8/2006	Grossman	2009/0177122 A1	7/2009	Peterson
2006/0206105 A1	9/2006	Chopra	2009/0177123 A1	7/2009	Peterson
2006/0224090 A1	10/2006	Ostrovsky et al.	2009/0182231 A1	7/2009	Barthe et al.
2006/0229514 A1	10/2006	Wiener	2009/0216159 A1	8/2009	Slayton et al.
2006/0241440 A1	10/2006	Eshel	2009/0226424 A1	9/2009	Hsu
2006/0241442 A1	10/2006	Barthe	2009/0227910 A1	9/2009	Pedersen et al.
2006/0241470 A1	10/2006	Novak et al.	2009/0230823 A1	9/2009	Kushculey et al.
2006/0241576 A1	10/2006	Diederich et al.	2009/0253988 A1	10/2009	Slayton et al.
2006/0250046 A1	11/2006	Koizumi et al.	2009/0312693 A1	12/2009	Thapliyal et al.
2006/0282691 A1	12/2006	Barthe	2009/0318909 A1	12/2009	Debenedictis et al.
2006/0291710 A1	12/2006	Wang et al.	2009/0326420 A1	12/2009	Moonen et al.
2007/0032784 A1	2/2007	Gliklich et al.	2010/0011236 A1	1/2010	Barthe et al.
2007/0035201 A1	2/2007	Desilets	2010/0022919 A1	1/2010	Peterson
2007/0055154 A1	3/2007	Torbati	2010/0022922 A1	1/2010	Barthe et al.
2007/0055155 A1	3/2007	Owen et al.	2010/0042020 A1	2/2010	Ben-Ezra
2007/0055156 A1	3/2007	Desilets et al.	2010/0049178 A1	2/2010	Deem et al.
2007/0065420 A1	3/2007	Johnson	2010/0113983 A1	5/2010	Heckerman et al.
2007/0083120 A1	4/2007	Cain et al.	2010/0130891 A1	5/2010	Taggart et al.
2007/0087060 A1	4/2007	Dietrich	2010/0160782 A1	6/2010	Slayton et al.
2007/0088245 A1	4/2007	Babaev et al.	2010/0160837 A1	6/2010	Hunziker et al.
2007/0088346 A1	4/2007	Mirizzi et al.	2010/0168576 A1	7/2010	Poland et al.
2007/0161902 A1	7/2007	Dan	2010/0191120 A1	7/2010	Kraus et al.
2007/0166357 A1	7/2007	Shaffer et al.	2010/0241035 A1	9/2010	Barthe et al.
2007/0167709 A1	7/2007	Slayton	2010/0249602 A1	9/2010	Buckley et al.
2007/0208253 A1	9/2007	Slayton	2010/0249669 A1	9/2010	Ulric et al.
2007/0219604 A1	9/2007	Yaroslasky et al.	2010/0256489 A1	10/2010	Pedersen et al.
			2010/0274161 A1	10/2010	Azhari et al.
			2010/0280420 A1	11/2010	Barthe et al.
			2010/0286518 A1	11/2010	Lee et al.
			2011/0040171 A1	2/2011	Foley et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2011/0040190 A1 2/2011 Jahnke et al.
 2011/0087099 A1 4/2011 Eshel et al.
 2011/0087255 A1 4/2011 McCormack et al.
 2011/0112405 A1 5/2011 Barthe et al.
 2011/0178444 A1 7/2011 Slayton et al.
 2011/0190745 A1 8/2011 Uebelhoer et al.
 2011/0251527 A1 10/2011 Kushculey et al.
 2012/0004549 A1 1/2012 Barthe et al.
 2012/0016239 A1 1/2012 Barthe et al.
 2012/0029353 A1 2/2012 Slayton et al.
 2012/0035473 A1 2/2012 Sanghvi et al.
 2012/0035475 A1 2/2012 Barthe et al.
 2012/0035476 A1 2/2012 Barthe et al.
 2012/0046547 A1 2/2012 Barthe et al.
 2012/0053458 A1 3/2012 Barthe et al.
 2012/0111339 A1 5/2012 Barthe et al.
 2012/0143056 A1 6/2012 Slayton et al.
 2012/0165668 A1 6/2012 Slayton et al.
 2012/0165848 A1 6/2012 Slayton et al.
 2012/0191020 A1 7/2012 Vitek et al.
 2012/0197120 A1 8/2012 Makin et al.
 2012/0197121 A1 8/2012 Slayton et al.
 2012/0215105 A1 8/2012 Slayton et al.
 2012/0271294 A1 10/2012 Barthe et al.
 2012/0296240 A1 11/2012 Azhari et al.
 2012/0316426 A1 12/2012 Foley et al.
 2012/0330197 A1 12/2012 Makin et al.
 2012/0330222 A1 12/2012 Makin et al.
 2012/0330223 A1 12/2012 Makin et al.
 2013/0012755 A1 1/2013 Slayton
 2013/0012816 A1 1/2013 Slayton et al.
 2013/0012838 A1 1/2013 Jaeger et al.
 2013/0012842 A1 1/2013 Barthe
 2013/0018286 A1 1/2013 Slayton et al.
 2013/0046209 A1 2/2013 Slayton et al.
 2013/0066208 A1 3/2013 Barthe et al.
 2013/0066237 A1 3/2013 Smotrich et al.
 2013/0072826 A1 3/2013 Slayton et al.
 2013/0096471 A1 4/2013 Slayton et al.
 2013/0190659 A1 7/2013 Slayton et al.
 2013/0268032 A1 10/2013 Neev
 2013/0274603 A1 10/2013 Barthe et al.
 2013/0281853 A1 10/2013 Slayton et al.
 2013/0281891 A1 10/2013 Slayton et al.
 2013/0296697 A1 11/2013 Slayton et al.
 2013/0296700 A1 11/2013 Slayton et al.
 2013/0303904 A1 11/2013 Barthe et al.
 2013/0303905 A1 11/2013 Barthe et al.
 2013/0310863 A1 11/2013 Makin et al.
 2013/0345562 A1 12/2013 Barthe et al.
 2014/0024974 A1 1/2014 Slayton et al.
 2014/0050054 A1 2/2014 Toda et al.
 2014/0082907 A1 3/2014 Barthe et al.
 2014/0117814 A1 5/2014 Toda et al.
 2014/0142430 A1 5/2014 Slayton et al.
 2014/0148834 A1 5/2014 Barthe et al.
 2014/0180174 A1 6/2014 Slayton et al.
 2014/0187944 A1 7/2014 Slayton et al.
 2014/0188015 A1 7/2014 Slayton et al.
 2014/0188145 A1 7/2014 Slayton et al.
 2014/0194723 A1 7/2014 Herzog et al.
 2014/0208856 A1 7/2014 Schmid
 2014/0236049 A1 8/2014 Barthe et al.
 2014/0243713 A1 8/2014 Slayton et al.
 2014/0257145 A1 9/2014 Emery
 2014/0276055 A1 9/2014 Barthe et al.
 2015/0000674 A1 1/2015 Barthe et al.
 2015/0080723 A1 3/2015 Barthe et al.
 2015/0080771 A1 3/2015 Barthe et al.
 2015/0080874 A1 3/2015 Slayton et al.
 2015/0088182 A1 3/2015 Slayton et al.
 2015/0164734 A1 6/2015 Slayton et al.
 2015/0165238 A1 6/2015 Slayton et al.
 2015/0165243 A1 6/2015 Slayton et al.
 2015/0174388 A1 6/2015 Slayton

2015/0202468 A1 7/2015 Slayton et al.
 2015/0217141 A1 8/2015 Barthe et al.
 2015/0360058 A1 12/2015 Barthe et al.
 2015/0374333 A1 12/2015 Barthe et al.
 2015/0375014 A1 12/2015 Slayton et al.
 2016/0027994 A1 1/2016 Toda et al.
 2016/0175619 A1 6/2016 Lee et al.
 2016/0206335 A1 7/2016 Slayton
 2016/0206341 A1 7/2016 Slayton
 2016/0256675 A1 9/2016 Slayton
 2016/0296769 A1 10/2016 Barthe et al.

FOREIGN PATENT DOCUMENTS

DE 10140064 3/2003
 DE 10219297 11/2003
 DE 10219217 12/2004
 DE 20314479 12/2004
 EP 0142215 5/1984
 EP 0344773 12/1989
 EP 1479412 11/1991
 EP 0473553 4/1992
 EP 670147 2/1995
 EP 0661029 7/1995
 EP 724894 2/1996
 EP 763371 11/1996
 EP 1044038 10/2000
 EP 1050322 11/2000
 EP 1234566 8/2002
 EP 1262160 12/2002
 EP 0659387 4/2003
 EP 1374944 1/2004
 EP 1874241 1/2008
 EP 1811901 4/2009
 EP 1785164 8/2009
 EP 2230904 9/2010
 EP 1501331 6/2011
 EP 2066405 11/2011
 EP 2474050 7/2012
 FR 2532851 9/1983
 FR 2685872 1/1992
 FR 2672486 8/1992
 FR 2703254 3/1994
 GB 2113099 8/1983
 IL 102516 1/1996
 IL 112369 8/1999
 IL 120079 3/2001
 JP 63036171 2/1988
 JP 03048299 3/1991
 JP 3123559 5/1991
 JP 03136642 6/1991
 JP 4089058 3/1992
 JP 04150847 5/1992
 JP 7080087 3/1995
 JP 07505793 6/1995
 JP 7184907 7/1995
 JP 7222782 8/1995
 JP 09047458 2/1997
 JP 9108288 4/1997
 JP 9503926 4/1997
 JP 11123226 5/1999
 JP 11505440 5/1999
 JP 11506636 6/1999
 JP 10248850 9/1999
 JP 2000126310 5/2000
 JP 2000166940 6/2000
 JP 2000233009 8/2000
 JP 2001170068 6/2001
 JP 2002505596 2/2002
 JP 2002078764 3/2002
 JP 2002515786 5/2002
 JP 2002521118 7/2002
 JP 2002537939 11/2002
 JP 2003050298 7/2003
 JP 2003204982 7/2003
 JP 2004-504898 2/2004
 JP 2004-507280 3/2004
 JP 2004-509671 4/2004
 JP 2004-512856 4/2004

(56)

References Cited

FOREIGN PATENT DOCUMENTS

JP	2004147719	5/2004
JP	2005503388	2/2005
JP	2005527336	9/2005
JP	2005323213	11/2005
JP	2006520247	9/2006
JP	2008515559	5/2008
JP	2009518126	5/2009
JP	2010517695	5/2010
KR	1020010024871	3/2001
KR	100400870	10/2003
KR	1020060113930	11/2006
KR	1020070065332	6/2007
KR	1020070070161	7/2007
KR	1020070098856	10/2007
KR	1020070104878	10/2007
KR	1020070114105	11/2007
KR	1020000059516	4/2012
KR	10-2013-0124598	11/2013
KR	10-1365946	2/2014
WO	WO93/12742	7/1993
WO	WO95/24159	9/1995
WO	WO96/25888	8/1996
WO	WO96/34568	11/1996
WO	WO96/39079	12/1996
WO	WO97/35518	10/1997
WO	WO98/32379	7/1998
WO	WO98/52465	11/1998
WO	WO99/33520	7/1999
WO	WO99/49788	10/1999
WO	WO2000/06032	2/2000
WO	WO00/15300	3/2000
WO	WO00/21612	4/2000
WO	WO00/53113	9/2000
WO	WO01/28623	4/2001
WO	WO01/045550	6/2001
WO	WO01/080709	11/2001
WO	WO01/82777	11/2001
WO	WO01/82778	11/2001
WO	WO01/87161	11/2001
WO	WO 02/09812	2/2002
WO	WO02/09813	2/2002
WO	WO02/015768	2/2002
WO	WO02/24050	3/2002
WO	WO02/092168	11/2002
WO	WO03/053266	7/2003
WO	WO03/065347	8/2003
WO	WO03/070105	8/2003
WO	WO03/077833	9/2003
WO	WO03/086215	10/2003
WO	WO03096883	11/2003
WO	WO03/099177	12/2003
WO	WO03/099382	12/2003
WO	WO03/101530	12/2003
WO	WO2004/000116	12/2003
WO	WO2004/080147	9/2004
WO	WO2004/110558	12/2004
WO	WO2005/011804	2/2005
WO	WO2005/065408	7/2005
WO	WO2005/090978	9/2005
WO	WO2006/036870	4/2006
WO	WO2006/042163	4/2006
WO	WO2006/042168	4/2006
WO	WO2006/042201	4/2006
WO	WO2006/065671	6/2006
WO	WO2006/082573	8/2006
WO	WO2006104568	10/2006
WO	WO2007/067563	6/2007
WO	WO2008/036622	3/2008
WO	WO2009/013729	1/2009

WO WO2009/149390 10/2009
 WO WO2014/055708 4/2014

OTHER PUBLICATIONS

- Alam, M., et al., "Ultrasound tightening of facial and neck skin: a rater-blinded prospective cohort study". *J Am Acad Dermatol*, 2010. 62(2): p. 262-269.
- Alexiades-Armenakas, M., "Ultrasound Technologies for Dermatologic Techniques". *J Drugs Derm*. 2014. 12 (11): p. 1305.
- Alster, T.S., et. al., "Noninvasive lifting of arm, thigh, and knee skin with transcutaneous intense focused ultrasound". *Dermatol Surg*, 2012. 38(5): p. 754-759.
- Arosarena, O., "Options and Challenges for Facial Rejuvenation in Patients With Higher Fitzpatrick Skin Phototypes". *JAMA Facial Plastic Surgery*, 2015.
- Brobst, R.W., et. al., "Noninvasive Treatment of the Neck". *Facial Plast Surg Clin North Am*, 2014. 22(2): p. 191-202.
- Brobst, R.W., et., al., "Ulthera: initial and six month results". *Facial Plast Surg Clin North Am*, 2012. 20(2): p. 163-176.
- Casabona, G., et. al., "Microfocused Ultrasound With Visualization and Fillers for Increased Neocollagenesis: Clinical and Histological Evaluation". *Dermatol Surg* 2014;40:S194-S198.
- Chan, N.P., et al., "Safety study of transcutaneous focused ultrasound for non-invasive skin tightening in Asians". *Lasers Surg Med*, 2011. 43(5): p. 366-375.
- Chapelon et al., "Effects of Cavitation in the High Intensity Therapeutic Ultrasound", *Ultrasonics Symposium—1357* (1991).
- Chapelon, et al., "Thresholds for Tissue Ablation by Focused Ultrasound" (1990).
- Dayan, S.H., et al., "Prospective, Multi-Center, Pivotal Trial Evaluating the Safety and Effectiveness of Micro-Focused Ultrasound with Visualization (MFU-V) for Improvement in Lines and Wrinkles of the Décolletage". *Plast Reconstr Surg*, Oct. 2014; 134(4 Suppl 1):123-4.
- Dobke, M.K., et al., "Tissue restructuring by energy-based surgical tools". *Clin Plast Surg*, 2012. 39(4): p. 399-408.
- Fabi, S.G., "Microfocused Ultrasound With Visualization for Skin Tightening and Lifting: My Experience and a Review of the Literature". *Dermatol Surg*. Dec. 2014; 40 Suppl 12:S164-7.
- Fabi, S.G., "Noninvasive skin tightening: focus on new ultrasound techniques". *Clin Cosmet Investig Dermatol*. Feb. 5, 2015; 8:47-52.
- Fabi, S.G., et. al., "A prospective multicenter pilot study of the safety and efficacy of microfocused ultrasound with visualization for improving lines and wrinkles of the décolleté". *Dermatol Surg*. Mar. 2015; 41(3):327-35.
- Fabi, S.G., et. al., "Evaluation of microfocused ultrasound with visualization for lifting, tightening, and wrinkle reduction of the décolletage". *J Am Acad Dermatol*, 2013. 69(6): p. 965-971.
- Fabi, S.G., et. al., "Future directions in cutaneous laser surgery". *Dermatol Clin*, 2014. 32(1): p. 61-69.
- Fabi, S.G., et. al., "Retrospective Evaluation of Micro-focused Ultrasound for Lifting and Tightening the Face and Neck". *Dermatol Surg*, 2014.
- Friedmann D.P., "Comments on evaluation of microfocused ultrasound system for improving skin laxity and tightening in the lower face". *Aesthet Surg J*. Mar. 2015;35(3):NP81-2.
- Friedmann, D.P., et. al., "Combination of intense pulsed light, Sculptra, and Ultherapy for treatment of the aging face". *J Cosmet Dermatol*, 2014. 13(2): p. 109-118.
- Fujimoto, et al., "A New Cavitation Suppression Technique for Local Ablation Using High-Intensity Focused Ultrasound" *Ultrasonics Symposium—1629* (1995).
- Gold, M.H., et. al., "Use of Micro-Focused Ultrasound with Visualization to Lift and Tighten Lax Knee Skin". *J Cosmet Laser Ther*, 2014: p. 1-15.
- Goldberg, D.J., et. al., "Safety and Efficacy of Microfocused Ultrasound to Lift, Tighten, and Smooth the Buttocks". *Dermatol Surg* 2014; 40:1113-1117.
- Greene, R.M., et al., "Skin tightening technologies". *Facial Plast Surg*. Feb. 2014; 30(1):62-7.

(56)

References Cited

OTHER PUBLICATIONS

- Harris, M.O., "Safety of Microfocused Ultrasound With Visualization in Patients With Fitzpatrick Skin Phototypes III to VI". *JAMA Facial Plast. Surg.*, 2015.
- Hart, et. al., "Current Concepts in the Use of PLLA: Clinical Synergy Noted with Combined Use of Microfocused Ultrasound and Poly-L-Lactic Acid on the Face, Neck, and Décolletage". *Amer. Soc. Plast. Surg.* 2015. 136; 180-187S.
- Hitchcock, T.M. et. al., "Review of the safety profile for microfocused ultrasound with Visualization". *Journal of Cosmetic Dermatology*, 13, 329-335. (2014).
- Hynynen et al., *Temperature Distributions During Local Ultrasound Induced Hyperthermia In Vivo*, *Ultrasonics Symposium—745* (1982).
- Jeong, K.H., et al., "Neurologic complication associated with intense focused ultrasound". *J Cosmet Laser Ther*, 2013.
- Kim, H.J. et al., "Coagulation and ablation patterns of high-intensity focused ultrasound on a tissue mimicking phantom and cadaveric skin". *Laser Med Sci.* Sep. 4, 2015.
- Kornstein, A.N., "Ulthera for silicone lip correction". *Plast Reconstr Surg*, 2012. 129(6): p. 1014e-1015e.
- Kornstein, A.N., "Ultherapy shrinks nasal skin after rhinoplasty following failure of conservative measures". *Plast Reconstr Surg*, 2013. 131(4): p. 664e-666e.
- Laubach, H.J., et. al., "Confined Thermal Damage with Intense Ultrasound (IUS)" [abstr.] *American Society for Laser Medicine and Surgery Abstracts*, p. 15 #43 (Apr. 2006).
- Laubach, H.J., et. al., "Intense focused ultrasound: evaluation of a new treatment modality for precise microcoagulation within the skin". *Dermatol Surg*, 2008. 34(5): p. 727-734.
- Lee, H.J., et. al. "The efficacy and safety of intense focused ultrasound in the treatment of enlarged facial pores in Asian skin". *J Dermatolog Treat*, 2014.
- Lee, H.S., et. al., "Multiple Pass Ultrasound Tightening of Skin Laxity of the Lower Face and Neck". *Dermatol Surg*, 2011.
- MacGregor J.L., et. al., "Microfocused Ultrasound for Skin Tightening". *Semin Cutan Med Surg* 32:18-25. (2013).
- Minkis, K., et. al., "Ultrasound skin tightening". *Dermatol Clin*, 2014. 32(1): p. 71-77.
- Nestor, M.S. et. al., "Safety and Efficacy of Micro-focused Ultrasound Plus Visualization for the Treatment of Axillary Hyperhidrosis". *J Clin Aesthet Dermatol*, 2014. 7(4): p. 14-21.
- Oni, G., et. al. "Response to 'comments on evaluation of microfocused ultrasound system for improving skin laxity and tightening in the lower face'". *Aesthet Surg J.* Mar. 2015;35(3):NP83-4.
- Oni, G., et. al., "Evaluation of a Microfocused Ultrasound System for Improving Skin Laxity and Tightening in the Lower Face". *Aesthet Surg* 3, 2014. 38:861-868.
- Pak, C.S. et. al., "Safety and Efficacy of Ulthera in the Rejuvenation of Aging Lower Eyelids: A Pivotal Clinical Trial". *Aesthetic Plast Surg*, 2014.
- Pritzker, R.N., et. al., "Updates in noninvasive and minimally invasive skin tightening". *Semin Cutan Med Surg.* Dec. 2014;33(4):182-7.
- Pritzker, R.N., et. al., "Comparison of different technologies for noninvasive skin tightening". *Journal of Cosmetic Dermatology*, 13, 315-323. (2014).
- Rokhsar, C., et. al., "Safety and efficacy of microfocused ultrasound in tightening of lax elbow skin". *Dermatol Surg*, 2015; 41(7):821-6.
- Sabef-Peyman, E.J. et. al., "Complications Using Intense Ultrasound Therapy to Treat Deep Dermal Facial Skin and Subcutaneous Tissues". *Dermatol Surg* 2014; 40:1108-1112.
- Sasaki, G.H. et. al., "Clinical Efficacy and Safety of Focused-Image Ultrasonography: A 2-Year Experience". *Aesthet Surg J*, 2012.
- Sasaki, G.H. et. al., "Microfocused Ultrasound for Nonablative Skin and Subdermal Tightening to the Periorbitum and Body Sites: Preliminary Report on Eighty-Two Patients". *Journal of Cosmetics, Dermatological Sciences and Applications*, 2012, 2, 108-116.
- Sklar, L.R., et. al., "Use of transcutaneous ultrasound for lipolysis and skin tightening: a review". *Aesthetic Plast Surg*, 2014. 38(2): p. 429-441.
- Suh, D.H., et. al., "A intense-focused ultrasound tightening for the treatment of infraorbital laxity". *J Cosmet Laser Ther*, 2012. 14(6): p. 290-295.
- Suh, D.H., et. al., "Comparative histometric analysis of the effects of high-intensity focused ultrasound and radiofrequency on skin". *J Cosmet Laser Ther.* Mar. 2015 24:1-7.
- Suh, D.H., et. al., "Intense focused ultrasound tightening in asian skin: clinical and pathologic results". *Dermatol Surg*, 2011. 37(11): p. 1595-1602.
- Weiss, M., "Commentary: noninvasive skin tightening: ultrasound and other technologies: where are we in 2011?" *Dermatol Surg*, 2012. 38(1): p. 28-30.
- White, W. M., et al., "Selective Transcutaneous Delivery of Energy to Facial Subdermal Tissues Using the Ultrasound Therapy System" [abstr]. *American Society for Laser Medicine and Surgery Abstracts*, p. 37 #113 (Apr. 2006).
- Woodward, J.A., et. al. "Safety and Efficacy of Combining Microfocused Ultrasound With Fractional CO2 Laser Resurfacing for Lifting and Tightening the Face and Neck". *Dermatol Surg*, Dec. 2014 40:S190-S193.
- Ulthera, Inc., *Petition for Inter Partes Review* filed Jul. 19, 2016 in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 63 pages.
- Ulthera Exhibit 1001, U.S. Pat. No. 6,113,559 to Klopotek, filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1002, Patent file history of U.S. Pat. No. 6,113,559 Klopotek.
- Ulthera Exhibit 1003, Declaration of Expert Witness Mark E. Schafer, Ph.D.
- Ulthera Exhibit 1004, Curriculum Vitae of Mark E. Schafer, Ph.D.
- Ulthera Exhibit 1005, International PCT Publication WO96/34568 Knowlton.
- Ulthera Exhibit 1006, French Patent No. 2,672,486, Technomed patent.
- Ulthera Exhibit 1007, English translation of French Patent No. 2,672,486, Technomed.
- Ulthera Exhibit 1008, International PCT Publication WO93/12742, Technomed PCT.
- Ulthera Exhibit 1009, English translation of International PCT Publication WO93/12742, Technomed PCT.
- Ulthera Exhibit 1010, U.S. Pat. No. 5,601,526, which claims priority to Technomed PCT.
- Ulthera Exhibit 1011, Patent file history for European Patent Application No. 98964890.2, Klopotek.
- Ulthera Exhibit 1012, Translator Declaration.
- Ulthera Exhibit 1013, U.S. Pat. No. 5,230,334 to Klopotek.
- Ulthera Exhibit 1014, U.S. Pat. No. 5,755,753 to Knowlton.
- Ulthera Exhibit 1015, Excerpts from the American Medical Association Encyclopedia of Medicine (1989).
- Ulthera Exhibit 1016, The Simultaneous Study of Light Emissions and Shock Waves Produced by Cavitation Bubbles, G. Gimenez, J. Acoust. Soc. Am. 71(4), Apr. 1982, pp. 839-847.
- Ulthera Exhibit 1017, Excerpts from Gray's Anatomy (1995).
- Ulthera Exhibit 1018, Anatomy of the Superficial Venous System, Comjen G.M., *Dermatol. Surg.*, 1995; 21:35-45.
- Ulthera Exhibit 1019, Section 2.6 from Ultrasonics Theory and Application, by G.L. Goberman (Hart Publishing Co., 1969).
- Ulthera Exhibit 1020, Deep Local Hyperthermia for Cancer Therapy: External Electromagnetic and Ultrasound Techniques, A.Y. Cheung and A. Neyzari, *Cancer Research (Suppl.)*, vol. 44, pp. 4736-4744 (1984).
- Agren, Magnus S. et al., 37 Collagenase in Wound Healing: Effect of Wound Age and Type. *The Journal of Investigative Dermatology*, vol. 99/No. 6, (Dec. 1992).
- Alster, Tinas S., Tanzi, Elizabeth L., "Cellulite Treatment using a Novel Combination Radiofrequency, Infrared Light, and Mechanical Tissue Manipulation Device," *Journal of Cosmetic & Laser Therapy*, Jun. 2005, vol. 7, Issue 2, pp. 81-85.
- Arthur et al., "Non-invasive estimation of hyperthermia temperatures with ultrasound," *Int. J. Hyperthermia*, Sep. 2005, 21(6), pp. 589-600.

(56)

References Cited

OTHER PUBLICATIONS

- Barthe et al., "Ultrasound therapy system and ablation results utilizing miniature imaging/therapy arrays," *Ultrasonics Symposium*, 2004 IEEE, Aug. 23, 2004, pp. 1792-1795, vol. 3.
- Bozec, Laurent et al., Thermal Denaturation Studies of Collagen by Microthermal Analysis and Atomic Force Microscopy, *Biophysical Journal*, vol. 101, pp. 228-236. (Jul. 2001).
- Calderhead et al., "One Mechanism Behind LED Photo-Therapy for Wound Healing and Skin Rejuvenation: Key Role of the Mast Cell" *Laser Therapy* 17.3: 141-148 (2008).
- Chen, L. et al., "Effect of Blood Perfusion on the ablation of liver parenchyma with high intensity focused ultrasound," *Phys. Med. Biol.* 38:1661-1673; 1993b.
- Coon, Joshua et al., "Protein identification using sequential ion/ion reactions and tandem mass spectrometry" *Proceedings of the National Academy of Sciences of the USA*, vol. 102, No. 27, Jul. 27, 2005, pp. 9463-9468.
- Corry, Peter M., et al., "Human Cancer Treatment with Ultrasound", *IEEE Transactions on Sonics and Ultrasonics*, vol. SU-31, No. 5, Sep. 1984, pp. 444, 456.
- Damianou et al., "Application of the Thermal Dose Concept for Predicting the Necrosed Tissue Volume During Ultrasound Surgery," 1993 IEEE Ultrasound Symposium, pp. 1199-1202.
- Daum et al., 37 Design and Evaluation of a Feedback Based Phased Array System for Ultrasound Surgery, *IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control*, vol. 45, No. 2, Mar. 1998, pp. 431-438.
- Davis, Brian J., et al., "An Acoustic Phase Shift Technique for the Non-Invasive Measurement of Temperature Changes in Tissues", 1985 *Ultrasonics Symposium*, pp. 921-924.
- Decision of the Korean Intellectual Property Tribunal dated Jun. 28, 2013 regarding Korean Patent No. 10-1142108, which is related to the pending application and/or an application identified in the Table on pp. 1-4 of the Information Disclosure Statement herein (English translation, English translation certification, and Korean decision included).
- Dierickx, Christine C., "The Role of Deep Heating for Noninvasive Skin Rejuvenation" *Lasers in Surgery and Medicine* 38:799-807 (2006).
- Dong, Yuan-Lin et al., "Effect of Ibuprofen on the Inflammatory Response to Surgical Wounds" *The Journal of Trauma*, vol. 35, No. 3. (1993).
- Dvivedi, Sanjay, et al. "Effect of Ibuprofen and diclofenac sodium on experimental wound healing" *Indian Journal of Experimental Biology*, vol. 35, pp. 1243-1245. (Nov. 1997).
- Fry, W.J. et al., "Production of Focal Destructive Lesions in the Central Nervous System with Ultrasound," *J. Neurosurg.*, 11:471-478; 1954.
- Gliklich et al., Clinical Pilot Study of Intense Ultrasound therapy to Deep Dermal Facial Skin and Subcutaneous Tissues, *Arch Facial Plastic Surgery*, Mar. 1, 2007, vol. 9, No. 1.
- Greenhalgh, David G., "Wound healing and diabetes mellitus" *Clinics in Plastic Surgery* 30; 37-45. (2003).
- Guo, S., et al., "Factors Affecting Wound Healing" *Critical Reviews in Oral Biology & Medicine*, *J Dent Res* 89(3), pp. 219-229. (2010).
- Haar, G.R. et al., "Tissue Destruction with Focused Ultrasound in Vivo," *Eur. Urol.* 23 (suppl. 1):8-11; 1993.
- Hantash, Basil M. et al., "Bipolar Fractional Radiofrequency Treatment Induces Neocollagenesis and Neocollagenesis" *Lasers in Surgery and Medicine* 41:1-9 (2009).
- Hantash, Basil M. et al., "In Vivo Histological Evaluation of a Novel Ablative Fractional Resurfacing Device" *Lasers in Surgery and Medicine* 39:96-107 (2007).
- Hassan et al., "Structure and Applications of Poly(vinyl alcohol) Hydrogels Produced by Conventional Crosslinking or by Freezing/Thawing Methods," *advanced in Polymer Science*, 2000, pp. 37-65, vol. 153.
- Hassan et al., "Structure and Morphology of Freeze/Thawed PVA Hydrogels," *Macromolecules*, Mar. 11, 2000, pp. 2472-2479, vol. 33, No. 7.
- Husseini et al., "The Role of Cavitation in Acoustically Activated Drug Delivery," *J. Control Release*, Oct. 3, 2005, pp. 253-261, vol. 107(2).
- Husseini et al. "Investigating the mechanism of acoustically activated uptake of drugs from Pluronic micelles," *BMD Cancer* 2002, 2:20k, Aug. 30, 2002, pp. 1-6.
- Jeffers et al., "Evaluation of the Effect of Cavitation Activity on Drug-Ultrasound Synergisms," 1993 *IEEE Ultrasonics Symposium*, pp. 925-928.
- Jenne, J., et al., "Temperature Mapping for High Energy US-Therapy", 1994 *Ultrasonics Symposium*, pp. 1879-1882.
- Johnson, S.A., et al., "Non-Intrusive Measurement of Microwave and Ultrasound-Induced Hyperthermia by Acoustic Temperature Tomography", *Ultrasonics Symposium Proceedings*, pp. 977-982. (1977).
- Krischak, G.D., et al., "The effects of non-steroidal anti-inflammatory drug application on incisional wound healing in rats" *Journal of Wound Care*, vol. 6, No. 2, (Feb. 2007).
- Lin, Sung-Jan, et al., "Monitoring the thermally induced structural transitions of collagen by use of second-harmonic generation microscopy" *Optics Letters*, vol. 30, No. 6, (Mar. 15, 2005).
- Madersbacher, S. et al., "Tissue Ablation in Benign Prostatic Hyperplasia with High Intensity Focused Ultrasound," *Dur. Urol.*, 23 (suppl. 1):39-43; 1993.
- Makin et al, "B-Scan Imaging and Thermal Lesion Monitoring Using Miniaturized Dual-Functionality Ultrasound Arrays," *Ultrasonics Symposium*, 2004 IEEE, Aug. 23, 2004, pp. 1788-1791, vol. 3.
- Makin et al, "Confirmed Bulk Ablation and Therapy Monitoring Using Intracorporeal Image-Treat Ultrasound Arrays," 4th International Symposium on Therapeutic Ultrasound, Sep. 19, 2004.
- Makin et al., "Miniaturized Ultrasound Arrays for Interstitial Ablation and Imaging," *UltraSound Med. Biol.* 2005, Nov. 1, 2005, pp. 1539-1550, vol. 31(11).
- Manohar et al, "Photoacoustic mammography laboratory prototype: imaging of breast tissue phantoms," *Journal of Biomedical Optics*, Nov./Dec. 2004, pp. 1172-1181, vol. 9, No. 6.
- Mast et al, "Bulk Ablation of Soft Tissue with Intense Ultrasound; Modeling and Experiments," *J. Acoust. Soc. Am.*, Oct. 1, 2005, pp. 2715-2724, vol. 118(4).
- Meshkinpour, Azin, et al., "Treatment of Hypertrophic Scars and Keloids With a Radiofrequency Device: A Study of Collagen Effects" *Lasers in Surgery and Medicine* 37:343-349 (2005).
- Mitragotri, S., "Healing sound: the use of ultrasound in drug delivery and other therapeutic applications," *Nature Reviews; Drug Delivery*, pp. 255-260, vol. 4 (Mar. 2005).
- Mosser, David M. et al., "Exploring the full spectrum of macrophage activation" *Nat Rev Immunol*; 8(12): 958-969. (Dec. 2008).
- Murota, Sei-Itsu, et al., "Stimulatory Effect of Prostaglandins on the Production of Hexosamine-Containing Substances by Cultured Fibroblasts (3) Induction of Hyaluronic Acid Synthetase by Prostaglandin" Department of Pharmacology, Tokyo Metropolitan Institute of Gerontology, Itabashiku, Tokyo-173, Japan. (Nov. 1977, vol. 14, No. 5).
- Murota, Sei-Itsu, et al., "The Stimulatory Effect of Prostaglandins on Production of Hexosamine-Containing Substances by Cultured Fibroblasts" Department of Pharmacology, Tokyo Metropolitan Institute of Gerontology, Itabashiku, Tokyo-173, Japan. (Aug. 1976, vol. 12, No. 2).
- Paradossi et al., "Poly(vinyl alcohol) as versatile biomaterial for potential biomedical applications," *Journal of Materials Science: Materials in Medicine*, 2003, pp. 687-691, vol. 14.
- Rappolee, Daniel A., et al., "Wound Macrophages Express TGF and Other Growth Factors in Vivo: Analysis by mRNA Phenotyping" *Science*, vol. 241, No. 4866 (Aug. 1988).
- Reid, Gavin, et al., "Tandem Mass spectrometry of ribonuclease A and B: N-linked glycosylation site analysis of whole protein ions," *Analytical Chemistry*. Feb. 1, 2002, vol. 74, No. 3, pp. 577-583.
- Righetti et al, "Elastographic Characterization of HIFU-Induced Lesions in Canine Livers," 1999, *Ultrasound in Med & Bio*, vol. 25, No. 7, pp. 1099-1113.

(56)

References Cited

OTHER PUBLICATIONS

- Rosenberg, Carol S. "Wound Healing in the Patient with Diabetes Mellitus" *Nursing Clinics of North America*, vol. 25, No. 1, (Mar. 1990).
- Saad et al., "Ultrasound-Enhanced Effects of Adriamycin Against Murine Tumors," *Ultrasound in Med. & Biol.* vol. 18, No. 8, pp. 715-723 (1992).
- Sandulache, Vlad C. et al., "Prostaglandin E2 inhibition of keloid fibroblast migration, contraction, and transforming growth factor (TGF)- β 1-induced collagen synthesis" *Wound Rep Reg* 15 122-133, 2007. (2007).
- Sanghvi, N.T., et al., "Transrectal Ablation of Prostate Tissue Using Focused Ultrasound," 1993 Ultrasonics Symposium, IEEE, pp. 1207-1210.
- Sassen, Sander, "ATI's R520 architecture, the new king of the hill?" <http://www.hardwareanalysis.com/content/article/1813>, Sep. 16, 2005, 2 pages.
- Seip, Ralf, et al., "Noninvasive Detection of Thermal Effects Due to Highly Focused Ultrasonic Fields," *IEEE Symposium*, pp. 1229-1232, vol. 2, Oct. 3-Nov. 1993.
- Seip, Ralf, et al., "Noninvasive Estimation of Tissue Temperature Response to Heating Fields Using Diagnostic Ultrasound," *IEEE Transactions on Biomedical Engineering*, vol. 42, No. 8, Aug. 1995, pp. 828-839.
- Simon et al., "Applications of Lipid-Coated Microbubble Ultrasonic Contrast to Tumor Therapy," *Ultrasound in Med. & Biol.* vol. 19, No. 2, pp. 123-125 (1993).
- Smith, Nadine Barrie, et al., "Non-invasive In Vivo Temperature Mapping of Ultrasound Heating Using Magnetic Resonance Techniques", 1994 Ultrasonics Symposium, pp. 1829-1832, vol. 3.
- Suh, D.H., et al., "Intense Focused Ultrasound Tightening in Asian Skin: Clinical and Pathologic Results" *American Society for Dermatologic Surgery, Inc.*; 37:1595-1602. (2011).
- Surry et al., "Poly(vinyl alcohol) cryogel phantoms for use in ultrasound and MR imaging," *Phys. Med. Biol.*, Dec. 6, 2004, pp. 5529-5546, vol. 49.
- Syka J. E. P. et al., "Peptide and Protein Sequence Analysis by Electron Transfer Dissociation Mass Spectrometry," *Proceedings of the National Academy of Sciences of USA, National Academy of Science*, Washington, DC, vol. 101, No. 26, Jun. 29, 2004, pp. 9528-9533.
- Talbert, D. G., "An Add-On Modification for Linear Array Real-Time Ultrasound Scanners to Produce 3D Displays," *UTS Int'l 1977 Brighton, England* (Jun. 28-30, 1977) pp. 57-67.
- Tata et al., "Interaction of Ultrasound and Model Membrane Systems: Analyses and Predictions," *American Chemical Society, Phys. Chem.* 1992, 96, pp. 3548-3555.
- Ueno, S., et al., "Ultrasound Thermometry in Hyperthermia", 1990 Ultrasonic Symposium, pp. 1645-1652.
- Verhofstad, Michiel H.J. et al., "Collagen Synthesis in rat skin and ileum fibroblasts is affected differently by diabetes-related factors" *Int. J. Exp. Path.* (1998), 79, 321-328.
- Wang, H., et al., "Limits on Focused Ultrasound for Deep Hyperthermia", 1994 Ultrasonic Symposium, Nov. 1-4, 1994, pp. 1869-1872, vol. 3.
- Wasson, Scott, "NVIDIA's GeForce 7800 GTX graphics processor Power MADD," <http://techreport.com/reviews/2005q2/geforce-7800gtx/index.x?pg=1>, Jun. 22, 2005, 4 pages.
- White et al "Selective Creating of Thermal Injury Zones in the Superficial Musculoaponeurotic System Using Intense Ultrasound Therapy," *Arch Facial Plastic Surgery*, Jan./Feb. 2007, vol. 9, No. 1 (pp. 22-29).
- White, W. Matthew, et al., "Selective Transcutaneous Delivery of Energy to Porcine Soft Tissues Using Intense Ultrasound (IUS) Lasers in Surgery and Medicine 40:67-75 (2008).
- Zelickson, Brian D. et al., "Histological and Ultrastructural Evaluation of the Effects of a Radiofrequency-Based Nonablative Dermal Remodeling Device, A Pilot Study" *Arch Dermatol*, vol. 140, (Feb. 2004).
- A Validated Photonumeric Cellulite Severity Scale; Hessel et al; *J Eur Acad Dermatol Venereol*. May 2009;23(5):523-8, 6 pages.
- Delon Martin, C., et al, "Venous Thrombosis Generation by Means of High-Intensity Focused Ultrasound" *Ultrasound in Med. & Biol.*, vol. 21, No. 1, pp. 113-119 (1995).
- Microfocused Ultrasound with Visualization and Calcium Hydroxylapatite for Improving Skin Laxity and Cellulite Appearance; Casabona et al.; *Plast Reconstr Surg Glob Open*. Jul. 25, 2017;5(7):e1388, 8 pages.
- Microfocused Ultrasound With Visualization and Fillers for Increased Neocollagenesis: Clinical and Histological Evaluation; Casabona et al.; *Dermatol Surg*. Dec. 2014; 40 Suppl 12:S194-8, 5 pages.
- Decision on Institution of Inter Partes Review in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 20 pages [011] (dated Jan. 23, 2017).
- DERMAFOCUS Response to Institution of Inter Partes Review in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 73 pages [018] (dated Apr. 26, 2017).
- DERMAFOCUS Exhibit List in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 5 pages [019] (dated Apr. 26, 2017).
- DERMAFOCUS Exhibit 2002, Declaration of Mark Palmeri, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 136 pages (Filed Apr. 26, 2017).
- DERMAFOCUS Exhibit 2003, Deposition of Dr. Mark Schafer, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 327 pages (Filed Apr. 26, 2017).
- DERMAFOCUS Exhibit 2004, Amendment No. 4 to Ulthera Form S-1, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 308 pages (Filed Apr. 26, 2017).
- DERMAFOCUS Exhibit 2005, Excerpt from Churchill Livingstone, *Gray's Anatomy* (38th ed. 1995), in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 7 pages (Filed Apr. 26, 2017).
- DERMAFOCUS Exhibit 2006, Bo Eklof et al., "Revision of the CEAP Classification for Chronic Venous Disorders: Consensus Statement," *ACTA FAC MED NAISS*, vol. 25, No. 1 (2008), 3-10 in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 7 pages (Filed Apr. 26, 2017).
- DERMAFOCUS Exhibit 2007, WebMD, "Varicose Veins and Spider Veins" downloaded from <http://www.webmd.com/skin-problems-and-treatments/guide/varicose-spider-veins#1> in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 3 pages (Filed Apr. 26, 2017).
- DERMAFOCUS Exhibit 2008, John M. Porter et al, "Reporting Standards in Venous Disease: An Update," *Journal of Vascular Surgery*, vol. 21, No. 4 (1995), 635-645 in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 11 pages (Filed Apr. 26, 2017).
- DERMAFOCUS Exhibit 2009, Kullervo Hynynen, "Review of Ultrasound Therapy," 1997 Ultrasonics Symposium (1997), 1305-1313, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 9 pages (Filed Apr. 26, 2017).
- DERMAFOCUS Exhibit 2010, A.G. Visioli et al, "Preliminary Results of a Phase I Dose Escalation Clinical Trial Using Focused Ultrasound in the Treatment of Localised Tumours," *European Journal of Ultrasound*, vol. 9 (1999), 11-18, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 8 pages (Filed Apr. 26, 2017).
- DERMAFOCUS Exhibit 2011, U.S. Pat. No. 5,143,063, dated Sep. 1, 1992, Fellner, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 6 pages (Filed Apr. 26, 2017).
- DERMAFOCUS Exhibit 2012, Hugh G. Beebe et al, "Consensus Statement: Classification and Grading of Chronic Venous Disease in the Lower Limbs," *European Journal of Vascular and Endovascular Surgery*, vol. 12 (1996), 487-492, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 6 pages (Filed Apr. 26, 2017).
- DERMAFOCUS Exhibit 2013, Excerpt from Mosby's Medical Dictionary (3rd ed. 1990), in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 4 pages (Filed Apr. 26, 2017).
- DERMAFOCUS Exhibit 2014, Excerpt from Miller-Keane Encyclopedia & Dictionary of Medicine, Nursing, & Allied Health (5th ed. 1992), in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 6 pages (Filed Apr. 26, 2017).
- DERMAFOCUS Exhibit 2015, David J. Tibbs et al, *Varicose Veins, Venous Disorders, and Lymphatic Problems in the Lower Limbs*

(56)

References Cited

OTHER PUBLICATIONS

(1997), Chapter 4: Clinical Patterns of Venous Disorder I, 47-67, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 24 pages (Filed Apr. 26, 2017).

DERMAFOCUS Exhibit 2016, Mitchel P. Goldman et al, *Varicose Veins and Telangiectasias* (2nd ed. 1999), Chapter 22: Treatment of Leg Telangiectasias with Laser and High-Intensity Pulsed Light, 470-497, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 31 pages (Filed Apr. 26, 2017).

DERMAFOCUS Exhibit 2017, Email from Anderson to Klopotek dated May 25, 2004, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 1 page (Filed Apr. 26, 2017).

DERMAFOCUS Exhibit 2018, List of Klopotek Patents, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 411 pages (Filed Apr. 26, 2017).

DERMAFOCUS Exhibit 2019, Declaration of Peter Klopotek Civil Action 15-cv-654-SLR, dated Nov. 2, 2016, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 1 page (Filed Apr. 26, 2017).

DERMAFOCUS Exhibit 2020, "Our Technology," downloaded from <http://job.ulthera.com/about> on Apr. 10, 2017, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 4 pages (Filed Apr. 26, 2017).

DERMAFOCUS Exhibit 2021, C. Damianou and K. Hynynen, "Focal Spacing and Near-Field Heating During Pulsed High Temperature Ultrasound Therapy," *Ultrasound in Medicine & Biology*, vol. 19, No. 9 (1993), 777-787, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 11 pages (Filed Apr. 26, 2017).

DERMAFOCUS Exhibit 2022, Excerpt from Mosby's Medical Dictionary (5th ed. 1997), in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 5 pages (Filed Apr. 26, 2017).

DERMAFOCUS Exhibit 2023, Excerpt from Miller-Keane Encyclopedia & Dictionary of Medicine, Nursing, & Allied Health (6th ed. 1997), in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 7 pages (Filed Apr. 26, 2017).

DERMAFOCUS Exhibit 2024, Excerpt from Stedman's Concise Medical Dictionary (3rd ed. 1997), in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 4 pages (Filed Apr. 26, 2017).

DERMAFOCUS Exhibit 2025, Excerpt from Taber's Cyclopedic Medical Dictionary (18th ed. 1997), in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 9 pages (Filed Apr. 26, 2017).

DERMAFOCUS Exhibit 2026, Bo Eklof et al, "Revision of the CEAP Classification for Chronic Venous Disorders: Consensus Statement," *Journal of Vascular Surgery*, vol. 40, No. 6 (2004), 1248-1252.e1, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 6 pages (Filed Apr. 26, 2017).

Ulthera, Inc., Reply in Support of Petition for Inter Partes Review in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 33 pages (Filed Aug. 2, 2017).

Ulthera Exhibit 1022, Use of the Argon and Carbon Dioxide Lasers for Treatment of Superficial Venous Varicosities of the Lower Extremity, D. Apfelberg et al., *Lasers in Surgery and Medicine*, vol. 4.3, pp. 221-231 (1984) (filed Aug 2, 2017 in re IPR2016-01459).

Ulthera Exhibit 1023, 532-Nanometer Green Laser Beam Treatment of Superficial Varicosities of the Lower Extremities, T. Smith et al., *Lasers in Surgery and Medicine*, vol. 8.2, pp. 130-134 (1988) (filed Aug. 2, 2017 in re IPR2016-01459).

Ulthera Exhibit 1024, Deposition Transcript of Dr. Mark Palmeri on Jul. 11, 2017 (filed Aug. 2, 2017 in re IPR2016-01459).

Ulthera Exhibit 1025, Ulthera Oral Proceeding Demonstrative Slides (filed Oct. 2, 2017 in re IPR2016-01459).

DERMAFOCUS Exhibit 2027, DermaFocus Oral Proceeding Demonstrative Slides (filed Oct. 2, 2017 in re IPR2016-01459).

* cited by examiner




FIG. 1




FIG. 2A

230




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 2E




FIG. 2F




FIG. 3A

300
↙




FIG. 3B




FIG. 4A

400
↙




FIG. 4B




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8A




FIG. 8B




FIG. 9




FIG. 10A




FIG. 10B




FIG. 10C




FIG. 10D




FIG. 10E




FIG. 10F




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16





FIG. 17

SYSTEM AND METHOD FOR NONINVASIVE SKIN TIGHTENING

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 13/964,820 entitled "Methods For Noninvasive Skin Tightening" filed on Aug. 12, 2013, and issue a U.S. Pat. No. 9,320,537 on Apr. 26, 2016, which is a continuation of U.S. application Ser. No. 12/028,636 entitled "Method and System for Noninvasive Face Lifts and Deep Tissue Tightening" filed on Feb. 8, 2008 and issued as U.S. Pat. No. 8,535,228 on Sep. 17, 2013, which is a continuation-in-part of U.S. application Ser. No. 11/163,151 entitled "Method and System for Noninvasive Face Lifts and Deep Tissue Tightening" filed on Oct. 6, 2005, now abandoned, which in turn claims priority to U.S. Provisional Application No. 60/616,755 entitled "Method and System for Noninvasive Face Lifts and Deep Tissue Tightening" filed on Oct. 6, 2004, now expired, each of which is incorporated by reference in its entirety. Further, U.S. application Ser. No. 12/028,636 is a continuation-in-part of U.S. application Ser. No. 11/163,148 entitled "Method and System for Controlled Thermal Injury of Human Superficial Tissue" filed on Oct. 6, 2005, now abandoned, which in turn claims priority to U.S. Provisional Application No. 60/616,754 entitled "Method and System for Controlled Thermal Injury of Human Superficial Tissue" filed on Oct. 6, 2004, now expired, each of which is incorporated by reference in its entirety. Any and all priority claims identified in the Application Data Sheet, or any correction thereto, are hereby incorporated by reference under 37 CFR 1.57.

BACKGROUND

Field of the Invention

The present invention relates to ultrasound therapy and imaging systems, and in particular to a method and system for noninvasive face lifts and deep tissue tightening.

Background of the Invention

Coarse sagging of the skin and facial musculature occurs gradually over time due to gravity and chronic changes in connective tissue generally associated with aging. Invasive surgical treatment to tighten such tissues is common, for example by facelift procedures. In these treatments for connective tissue sagging, a portion of the tissue is usually removed, and sutures or other fasteners are used to suspend the sagging tissue structures. On the face, the Superficial Muscular Aponeurosis System (SMAS) forms a continuous layer superficial to the muscles of facial expression and beneath the skin and subcutaneous fat. Conventional face lift operations involve suspension of the SMAS through such suture and fastener procedures.

No present procedures have been developed yet, which provide the combination of targeted, precise, local heating to a specified temperature region capable of inducing ablation (thermal injury) to underlying skin and subcutaneous fat. Attempts have included the use of radio frequency (RF) devices that have been used to produce heating and shrinkage of skin on the face with some limited success as a non-invasive alternative to surgical lifting procedures. However, RF is a dispersive form of energy deposition. RF energy is impossible to control precisely within the heated tissue volume and depth, because resistive heating of tissues by RF energy occurs along the entire path of electrical conduction through tissues. Another restriction of RF energy

for non-invasive tightening of the SMAS is unwanted destruction of the overlying fat and skin layers. The electric impedance to RF within fat, overlying the suspensory connective structures intended for shrinking, leads to higher temperatures in the fat than in the target suspensory structures. Similarly, mid-infrared lasers and other light sources have been used to non-invasively heat and shrink connective tissues of the dermis, again with limited success. However, light is not capable of non-invasive treatment of SMAS because light does not penetrate deeply enough to produce local heating there. Below a depth of approximately 1 mm, light energy is multiply scattered and cannot be focused to achieve precise local heating.

SUMMARY OF THE INVENTION

A method and system for noninvasive face lifts and deep tissue tightening are provided. An exemplary method and treatment system are configured for the imaging, monitoring, and thermal injury to treat the SMAS region. In accordance with an exemplary embodiment, the exemplary method and system are configured for treating the SMAS region by first, imaging of the region of interest for localization of the treatment area and surrounding structures, second, delivery of ultrasound energy at a depth, distribution, timing, and energy level to achieve the desired therapeutic effect, and third to monitor the treatment area before, during, and after therapy to plan and assess the results and/or provide feedback.

In accordance with an exemplary embodiment, an exemplary treatment system comprises an imaging/therapy probe, a control system and display system. The imaging/therapy probe can comprise various probe and/or transducer configurations. For example, the probe can be configured for a combined dual-mode imaging/therapy transducer, coupled or co-housed imaging/therapy transducers, or simply a therapy probe and an imaging probe. The control system and display system can also comprise various configurations for controlling probe and system functionality, including for example a microprocessor with software and a plurality of input/output devices, a system for controlling electronic and/or mechanical scanning and/or multiplexing of transducers, a system for power delivery, systems for monitoring, systems for sensing the spatial position of the probe and/or transducers, and systems for handling user input and recording treatment results, among others.

In accordance with an exemplary embodiment, ultrasound imaging can be utilized for safety purposes, such as to avoid injuring vital structures such as the facial nerve (motor nerve), parotid gland, facial artery, and trigeminal nerve (for sensory functions) among others. For example, ultrasound imaging can be used to identify SMAS as the superficial layer well defined by echoes overlying the facial muscles. Such muscles can be readily seen and better identified by moving them, and their image may be further enhanced via signal and image processing.

In accordance with an exemplary embodiment, ultrasound therapy via focused ultrasound, an array of foci, a locus of foci, a line focus, and/or diffraction patterns from single element, multiple elements, annular array, one-, two-, or three-dimensional arrays, broadband transducers, and/or combinations thereof, with or without lenses, acoustic components, mechanical and/or electronic focusing are utilized to treat the SMAS region at fixed and/or variable depth or dynamically controllable depths and positions.

In accordance with another exemplary embodiment, a therapeutic treatment method and system for controlled

thermal injury of human superficial tissue is based on the ability to controllably create thermal lesions of a variable shape, size, and depth through precise spatial and temporal control of acoustic energy deposition. This system and method for controlled thermal injury can be used to complete various procedures such as face lifts and deep tissue tightening described herein. In accordance with an exemplary embodiment, an exemplary therapeutic treatment system includes a control system and a probe system that can facilitate treatment planning, controlling and/or delivering of acoustic energy, and/or monitoring of treatment conditions to a region of interest. As a result, the ability to controllably produce conformal lesions of thermal injury in superficial human tissue can be realized.

In accordance with another exemplary embodiment, a treatment method can enable the regions of thermal injury to comprise controlled conformal shapes and sizes and allow the tissue to be destroyed (ablated) in a controlled spatial and temporal manner. For example, the thermal lesions may be suitably and selectively created with narrow or wide lateral extent, long or short axial length, and/or deep or shallow placement, including up to the tissue outer surface. Moreover, separate islands of destruction may also be created over part or whole of the tissue region-of-interest, and/or contiguous or overlapping structures may be produced out of discrete lesions.

In accordance with other exemplary embodiments of the present invention, exemplary methods can comprise scanning over part or whole of the region-of-interest to produce contiguous thermal injury. The conformal lesions can be achieved not only through the independent selection and control of transducer acoustic energy spatial distribution, such as selection of transducer configuration and placement, but also through temporal control, such as through drive amplitude levels, frequency/waveform selection, and timing sequences that can be adjusted and optimized to control thermal ablation of tissue. In addition, the temperature at the acoustic coupling interface can be controlled, thus further enabling another exemplary method of lesion formation control.

BRIEF DESCRIPTION OF THE DRAWINGS

The subject matter of the invention is particularly pointed out in the concluding portion of the specification. The invention, however, both as to organization and method of operation, may best be understood by reference to the following description taken in conjunction with the accompanying drawing figures, in which like parts may be referred to by like numerals:

FIG. 1 illustrates a block diagram of a treatment system in accordance with an exemplary embodiment of the present invention;

FIGS. 2A-2F illustrates schematic diagrams of an ultrasound imaging/therapy and monitoring system for treating the SMAS layer in accordance with various exemplary embodiments of the present invention;

FIGS. 3A and 3B illustrate block diagrams of an exemplary control system in accordance with exemplary embodiments of the present invention;

FIGS. 4A and 4B illustrate block diagrams of an exemplary probe system in accordance with exemplary embodiments of the present invention;

FIG. 5 illustrates a cross-sectional diagram of an exemplary transducer in accordance with an exemplary embodiment of the present invention;

FIGS. 6A and 6B illustrate cross-sectional diagrams of an exemplary transducer in accordance with exemplary embodiments of the present invention;

FIG. 7 illustrates exemplary transducer configurations for ultrasound treatment in accordance with various exemplary embodiments of the present invention;

FIGS. 8A and 8B illustrate cross-sectional diagrams of an exemplary transducer in accordance with another exemplary embodiment of the present invention;

FIG. 9 illustrates an exemplary transducer configured as a two-dimensional array for ultrasound treatment in accordance with an exemplary embodiment of the present invention;

FIGS. 10A-10F illustrate cross-sectional diagrams of exemplary transducers in accordance with other exemplary embodiments of the present invention;

FIG. 11 illustrates a schematic diagram of an acoustic coupling and cooling system in accordance with an exemplary embodiment of the present invention;

FIG. 12 illustrates a block diagram of a treatment system comprising an ultrasound treatment subsystem combined with additional subsystems and methods of treatment monitoring and/or treatment imaging as well as a secondary treatment subsystem in accordance with an exemplary embodiment of the present invention;

FIG. 13 illustrates a schematic diagram with imaging, therapy, or monitoring being provided with one or more active or passive oral inserts in accordance with an exemplary embodiment of the present invention;

FIG. 14 illustrates a cross sectional diagram of a human superficial tissue region of interest including a plurality of lesions of controlled thermal injury in accordance with an exemplary embodiment of the present invention;

FIG. 15 illustrates an exemplary diagram of simulation results for various spatially controlled configurations in accordance with exemplary embodiments of the present invention;

FIG. 16 illustrates an exemplary diagram of simulation results of a pair of lesioning and simulation results in accordance with the present invention; and

FIG. 17 illustrates another exemplary diagram of simulation results of a pair of lesioning results in accordance with the present invention.

DETAILED DESCRIPTION

The present invention may be described herein in terms of various functional components and processing steps. It should be appreciated that such components and steps may be realized by any number of hardware components configured to perform the specified functions. For example, the present invention may employ various medical treatment devices, visual imaging and display devices, input terminals and the like, which may carry out a variety of functions under the control of one or more control systems or other control devices. In addition, the present invention may be practiced in any number of medical contexts and that the exemplary embodiments relating to a method and system for noninvasive face lift and deep tissue tightening as described herein are merely indicative of exemplary applications for the invention. For example, the principles, features and methods discussed may be applied to any SMAS-like muscular fascia, such as platysma, temporal fascia, and/or occipital fascia, or any other medical application.

Further, various aspects of the present invention may be suitably applied to other applications. The system and method of the present invention may also be used for

controlled thermal injury of various tissue. Certain exemplary methods for controlled thermal injury to various tissues are disclosed in co-pending U.S. patent application Ser. No. 11/163,148 entitled "Method and System for Controlled Thermal Injury of Human Superficial Tissue" filed on Oct. 5, 2005 to which priority is claimed and which is incorporated herein by reference in its entirety as well as the provisional application to which that application claims priority to (U.S. Provisional Application No. 60/616,754 entitled "Method and System for Controlled Thermal Injury of Human Superficial Tissue").

In accordance with various aspects of the present invention, a method and system for noninvasive face lifts and deep tissue tightening are provided. For example, in accordance with an exemplary embodiment, with reference to FIG. 1, an exemplary treatment system **100** configured to treat a region of interest **106** comprises a control system **102**, an imaging/therapy probe with acoustic coupling **104**, and a display system **108**. Control system **102** and display system **108** can comprise various configurations for controlling probe **102** and overall system **100** functionality, such as, for example, a microprocessor with software and a plurality of input/output devices, system and devices for controlling electronic and/or mechanical scanning and/or multiplexing of transducers, a system for power delivery, systems for monitoring, systems for sensing the spatial position of the probe and/or transducers, and/or systems for handling user input and recording treatment results, among others. Imaging/therapy probe **104** can comprise various probe and/or transducer configurations. For example, probe **104** can be configured for a combined dual-mode imaging/therapy transducer, coupled or co-housed imaging/therapy transducers, or simply a separate therapy probe and an imaging probe.

In accordance with an exemplary embodiment, treatment system **100** is configured for treating the SMAS region by first, imaging of region of interest **106** for localization of the treatment area and surrounding structures, second, delivery of ultrasound energy at a depth, distribution, timing, and energy level to achieve the desired therapeutic effect, and third to monitor the treatment area before, during, and after therapy to plan and assess the results and/or provide feedback. According to another exemplary embodiment of the present invention, treatment system **100** is configured for controlled thermal injury of human superficial tissue based on treatment system **100**'s ability to controllably create thermal lesions of conformally variable shape, size, and depth through precise spatial and temporal control of acoustic energy deposition.

As to the treatment of the SMAS region, connective tissue can be permanently tightened by thermal treatment to temperatures about 60 degrees C. or higher. Upon ablating, collagen fibers shrink immediately by approximately 30% of their length. The shrunken fibers can produce tightening of the tissue, wherein the shrinkage should occur along the dominant direction of the collagen fibers. Throughout the body, collagen fibers are laid down in connective tissues along the lines of chronic stress (tension). On the aged face, the collagen fibers of the SMAS region are predominantly oriented along the lines of gravitational tension. Shrinkage of these fibers results in tightening of the SMAS in the direction desired for correction of laxity and sagging due to aging. The treatment comprises the ablation of specific regions of the SMAS region and similar suspensory connective tissues.

In addition, the SMAS region varies in depth and thickness at different locations, e.g., between 0.5 mm to 5 mm or

more. On the face, important structures such as nerves, parotid gland, arteries and veins are present over, under or near the SMAS region. Tightening of the SMAS in certain locations, such as the preauricular region associated with sagging of the cheek to create jowls, the frontal region to associated with sagging brows, mandibular region associated with sagging neck, can be conducted. Treating through localized heating of regions of the SMAS or other suspensory subcutaneous connective tissue structures to temperatures of about 60-90° C., without significant damage to overlying or distal/underlying tissue, i.e., proximal tissue, as well as the precise delivery of therapeutic energy to SMAS regions, and obtaining feedback from the region of interest before, during, and after treatment can be suitably accomplished through treatment system **100**.

To further illustrate an exemplary method and system **200**, with reference to FIG. 2, imaging of a region of interest **206**, such as by imaging a region **222** and displaying images **224** of the region of interest **206** on a display **208**, to facilitate localization of the treatment area and surrounding structures can initially be conducted. Next, delivery of ultrasound energy **220** at a suitably depth, distribution, timing, and energy level to achieve the desired therapeutic effect of thermal injury or ablation to treat SMAS region **216** can be suitably provided by probe **204** through control by control system **202**. Monitoring of the treatment area and surrounding structures before, during, and after therapy, i.e., before, during, and after the delivery of ultrasound energy to SMAS region **216**, can be provided to plan and assess the results and/or provide feedback to control system **202** and a system user.

Ultrasound imaging and providing of images **224** can facilitate safe targeting of the SMAS layer **216**. For example, with reference to FIG. 2B, specific targeting for the delivery of energy can be better facilitated to avoid heating vital structures such as the facial nerve (motor nerve) **234**, parotid gland (which makes saliva) **236**, facial artery **238**, and trigeminal nerve (for sensory functions) **232** among other regions. Further, use of imaging with targeted energy delivery to provide a limited and controlled depth of treatment can minimize the chance of damaging deep structures, such as for example, the facial nerve that lies below the parotid, which is typically 10 mm thick.

In accordance with an exemplary embodiment, with reference to FIG. 2C, ultrasound imaging of region **222** of the region of interest **206** can also be used to delineate SMAS layer **216** as the superficial, echo-dense layer overlying facial muscles **218**. Such muscles can be seen via imaging region **222** by moving muscles **218**, for example by extensional flexing of muscle layer **218** generally towards directions **250** and **252**. Such imaging of region **222** may be further enhanced via signal and image processing. Once SMAS layer **216** is localized and/or identified, SMAS layer **216** is ready for treatment.

The delivery of ultrasound energy **220** at a suitably depth, distribution, timing, and energy level is provided by probe **204** through controlled operation by control system **202** to achieve the desired therapeutic effect of thermal injury to treat SMAS region **216**. During operation, probe **204** can also be mechanically and/or electronically scanned within tissue surface region **226** to treat an extended area. In addition, spatial control of a treatment depth **220** can be suitably adjusted in various ranges, such as between a wide range of approximately 0 to 15 mm, suitably fixed to a few discrete depths, with an adjustment limited to a fine range, e.g. approximately between 3 mm to 9 mm, and/or dynamically adjusted during treatment, to treat SMAS layer **216** that

typically lies at a depth between approximately 5 mm to 7 mm. Before, during, and after the delivery of ultrasound energy to SMAS region **216**, monitoring of the treatment area and surrounding structures can be provided to plan and assess the results and/or provide feedback to control system **202** and a system user.

For example, in accordance with an exemplary embodiment, with additional reference to FIG. 2D, ultrasound imaging of region **222** can be used to monitor treatment by watching the amount of shrinkage of SMAS layer **216** in direction of areas **260** and **262**, such as in real time or quasi-real time, during and after energy delivery to region **220**. The onset of substantially immediate shrinkage of SMAS layer **216** is detectable by ultrasound imaging of region **222** and may be further enhanced via image and signal processing. The monitoring of such shrinkage can be ideal because it can confirm the intended therapeutic goal of noninvasive lifting and tissue tightening; in addition, such monitoring may be used for system feedback. In addition to image monitoring, additional treatment parameters that can be suitably monitored in accordance with various other exemplary embodiments may include temperature, video, profilometry, strain imaging and/or gauges or any other suitable spatial, temporal and/or other tissue parameters.

For example, in accordance with an exemplary embodiment of the present invention, with additional reference to FIG. 2E, an exemplary monitoring method and system **200** may suitably monitor the temperature profile or other tissue parameters of the region of interest **206**, such as attenuation or speed of sound of treatment region **222** and suitably adjust the spatial and/or temporal characteristics and energy levels of ultrasound therapy transducer probe **204**. The results of such monitoring techniques may be indicated on display **208** in various manners, such as, for example, by way of one-, two-, or three-dimensional images of monitoring results **270**, or may comprise an indicator **272**, such as a success, fail and/or completed/done type of indication, or combinations thereof.

In accordance with another exemplary embodiment, with reference to FIG. 2F, the targeting of particular region **220** within SMAS layer **216** can be suitably be expanded within region of interest **206** to include a combination of tissues, such as skin **210**, dermis **212**, fat/adipose tissue **214**, SMAS/muscular fascia/and/or other suspensory tissue **216**, and muscle **218**. Treatment of a combination of such tissues and/or fascia may be treated including at least one of SMAS layer **216** or other layers of muscular fascia in combination with at least one of muscle tissue, adipose tissue, SMAS and/or other muscular fascia, skin, and dermis, can be suitably achieved by treatment system **200**. For example, treatment of SMAS layer **216** may be performed in combination with treatment of dermis **280** by suitable adjustment of the spatial and temporal parameters of probe **204** within treatment system **200**.

In accordance with various aspects of the present invention, a therapeutic treatment method and system for controlled thermal injury of human superficial tissue to effectuate face lifts, deep tissue tightening, and other procedures is based on the ability to controllably create thermal lesions of conformally variable shape, size, and depth through precise spatial and temporal control of acoustic energy deposition. With reference to FIG. 1, in accordance with an exemplary embodiment, an exemplary therapeutic treatment system **200** includes a control system **102** and a probe system **104** that can facilitate treatment planning, controlling and/or delivering of acoustic energy, and/or monitoring of treatment conditions to a region of interest **106**. Region-of-

interest **106** is configured within the human superficial tissue comprising from just below the tissue outer surface to approximately 30 mm or more in depth.

Therapeutic treatment system **100** is configured with the ability to controllably produce conformal lesions of thermal injury in superficial human tissue within region of interest **106** through precise spatial and temporal control of acoustic energy deposition, i.e., control of probe **104** is confined within selected time and space parameters, with such control being independent of the tissue. In accordance with an exemplary embodiment, control system **102** and probe system **104** can be suitably configured for spatial control of the acoustic energy by controlling the manner of distribution of the acoustical energy. For example, spatial control may be realized through selection of the type of one or more transducer configurations insinuating region of interest **106**, selection of the placement and location of probe system **104** for delivery of acoustical energy relative to region-of-interest **106**, e.g., probe system **104** being configured for scanning over part or whole of region-of-interest **106** to produce contiguous thermal injury having a particular orientation or otherwise change in distance from region-of-interest **106**, and/or control of other environment parameters, e.g., the temperature at the acoustic coupling interface can be controlled, and/or the coupling of probe **104** to human tissue. In addition to the spatial control parameters, control system **102** and probe system **104** can also be configured for temporal control, such as through adjustment and optimization of drive amplitude levels, frequency/waveform selections, e.g., the types of pulses, bursts or continuous waveforms, and timing sequences and other energy drive characteristics to control thermal ablation of tissue. The spatial and/or temporal control can also be facilitated through open-loop and closed-loop feedback arrangements, such as through the monitoring of various spatial and temporal characteristics. As a result, control of acoustical energy within six degrees of freedom, e.g., spatially within the X, Y and Z domain, as well as the axis of rotation within the XY, YZ and XZ domains, can be suitably achieved to generate conformal lesions of variable shape, size and orientation.

For example, through such spatial and/or temporal control, an exemplary treatment system **100** can enable the regions of thermal injury to possess arbitrary shape and size and allow the tissue to be destroyed (ablated) in a controlled manner. With reference to FIG. 14, one or more thermal lesions may be created within a tissue region of interest **1400**, with such thermal lesions having a narrow or wide lateral extent, long or short axial length, and/or deep or shallow placement, including up to a tissue outer surface **1403**. For example, cigar shaped lesions may be produced in a vertical disposition **1404** and/or horizontal disposition **1406**. In addition, raindrop-shaped lesions **1408**, flat planar lesions **1410**, round lesions **1412** and/or other v-shaped/ellipsoidal lesions **1414** may be formed, among others. For example, mushroom-shaped lesion **1420** may be provided, such as through initial generation of an initial round or cigar-shaped lesion **1422**, with continued application of ablative ultrasound resulting in thermal expansion to further generate a growing lesion **1424**, such thermal expansion being continued until raindrop-shaped lesion **1420** is achieved. The plurality of shapes can also be configured in various sizes and orientations, e.g., lesions **1408** could be rotationally oriented clockwise or counterclockwise at any desired angle, or made larger or smaller as selected, all depending on spatial and/or temporal control. Moreover, separate islands of destruction, i.e., multiple lesions sepa-

rated throughout the tissue region, may also be created over part of or the whole portion within tissue region-of-interest **1400**. In addition, contiguous structures and/or overlapping structures **1416** may be provided from the controlled configuration of discrete lesions. For example, a series of one or more crossed-lesions **1418** can be generated along a tissue region to facilitate various types of treatment methods.

The specific configurations of controlled thermal injury are selected to achieve the desired tissue and therapeutic effect(s). For example, any tissue effect can be realized, including but not limited to thermal and non-thermal streaming, cavitational, hydrodynamic, ablative, hemostatic, diathermic, and/or resonance-induced tissue effects. Such effects can be suitably realized at treatment depths over a range of approximately 0-30000 μm within region of interest **200** to provide a high degree of utility.

An exemplary control system **202** and display system **208** may be configured in various manners for controlling probe and system functionality. With reference again to FIGS. **3A** and **3B**, in accordance with exemplary embodiments, an exemplary control system **300** can be configured for coordination and control of the entire therapeutic treatment process for noninvasive face lifts and deep tissue tightening. For example, control system **300** can suitably comprise power source components **302**, sensing and monitoring components **304**, cooling and coupling controls **306**, and/or processing and control logic components **308**. Control system **300** can be configured and optimized in a variety of ways with more or less subsystems and components to implement the therapeutic system for controlled thermal injury, and the embodiments in FIGS. **3A** and **3B** are merely for illustration purposes.

For example, for power sourcing components **302**, control system **300** can comprise one or more direct current (DC) power supplies **303** configured to provide electrical energy for entire control system **300**, including power required by a transducer electronic amplifier/driver **312**. A DC current sense device **305** can also be provided to confirm the level of power going into amplifiers/drivers **312** for safety and monitoring purposes.

Amplifiers/drivers **312** can comprise multi-channel or single channel power amplifiers and/or drivers. In accordance with an exemplary embodiment for transducer array configurations, amplifiers/drivers **312** can also be configured with a beamformer to facilitate array focusing. An exemplary beamformer can be electrically excited by an oscillator/digitally controlled waveform synthesizer **310** with related switching logic.

The power sourcing components can also include various filtering configurations **314**. For example, switchable harmonic filters and/or matching may be used at the output of amplifier/driver **312** to increase the drive efficiency and effectiveness. Power detection components **316** may also be included to confirm appropriate operation and calibration. For example, electric power and other energy detection components **316** may be used to monitor the amount of power going to an exemplary probe system.

Various sensing and monitoring components **304** may also be suitably implemented within control system **300**. For example, in accordance with an exemplary embodiment, monitoring, sensing and interface control components **324** may be configured to operate with various motion detection systems implemented within transducer probe **204** to receive and process information such as acoustic or other spatial and temporal information from a region of interest. Sensing and monitoring components can also include various controls, interfacing and switches **309** and/or power detectors **316**.

Such sensing and monitoring components **304** can facilitate open-loop and/or closed-loop feedback systems within treatment system **200**.

Still further, monitoring, sensing and interface control components **324** may comprise imaging systems configured for one-dimensional, two-dimensional and/or three dimensional imaging functions. Such imaging systems can comprise any imaging modality based on at least one of photography and other visual optical methods, magnetic resonance imaging (MRI), computed tomography (CT), optical coherence tomography (OCT), electromagnetic, microwave, or radio frequency (RF) methods, positron emission tomography (PET), infrared, ultrasound, acoustic, or any other suitable method of visualization, localization, or monitoring of a region-of-interest **106**. Still further, various other tissue parameter monitoring components, such as temperature measuring devices and components, can be configured within monitoring, sensing and interface control components **324**, such monitoring devices comprising any modality now known or hereinafter devised.

Cooling/coupling control systems **306** may be provided to remove waste heat from an exemplary probe **204**, provide a controlled temperature at the superficial tissue interface and deeper into tissue, and/or provide acoustic coupling from transducer probe **204** to region-of-interest **206**. Such cooling/coupling control systems **306** can also be configured to operate in both open-loop and/or closed-loop feedback arrangements with various coupling and feedback components.

Processing and control logic components **308** can comprise various system processors and digital control logic **307**, such as one or more of microcontrollers, microprocessors, field-programmable gate arrays (FPGAs), computer boards, and associated components, including firmware and control software **326**, which interfaces to user controls and interfacing circuits as well as input/output circuits and systems for communications, displays, interfacing, storage, documentation, and other useful functions. System software and firmware **326** controls all initialization, timing, level setting, monitoring, safety monitoring, and all other system functions required to accomplish user-defined treatment objectives. Further, various control switches **308** can also be suitably configured to control operation.

An exemplary transducer probe **204** can also be configured in various manners and comprise a number of reusable and/or disposable components and parts in various embodiments to facilitate its operation. For example, transducer probe **204** can be configured within any type of transducer probe housing or arrangement for facilitating the coupling of transducer to a tissue interface, with such housing comprising various shapes, contours and configurations. Transducer probe **204** can comprise any type of matching, such as for example, electric matching, which may be electrically switchable; multiplexer circuits and/or aperture/element selection circuits; and/or probe identification devices, to certify probe handle, electric matching, transducer usage history and calibration, such as one or more serial EEPROM (memories). Transducer probe **204** may also comprise cables and connectors; motion mechanisms, motion sensors and encoders; thermal monitoring sensors; and/or user control and status related switches, and indicators such as LEDs. For example, a motion mechanism in probe **204** may be used to controllably create multiple lesions, or sensing of probe motion itself may be used to controllably create multiple lesions and/or stop creation of lesions, e.g. for safety reasons if probe **204** is suddenly jerked or is dropped. In addition, an external motion encoder arm may be used to hold the probe

during use, whereby the spatial position and attitude of probe **104** is sent to the control system to help controllably create lesions. Furthermore, other sensing functionality such as profilometers or other imaging modalities may be integrated into the probe in accordance with various exemplary embodiments. Moreover, the therapy contemplated herein can also be produced, for example, by transducers disclosed in U.S. application Ser. No. 10/944,499, filed on Sep. 16, 2004, entitled METHOD AND SYSTEM FOR ULTRASOUND TREATMENT WITH A MULTI-DIRECTIONAL TRANSDUCER and U.S. application Ser. No. 10/944,500, filed on Sep. 16, 2004, and entitled SYSTEM AND METHOD FOR VARIABLE DEPTH ULTRASOUND TREATMENT, both hereby incorporated by reference.

With reference to FIGS. **4A** and **4B**, in accordance with an exemplary embodiment, a transducer probe **400** can comprise a control interface **402**, a transducer **404**, coupling components **406**, and monitoring/sensing components **408**, and/or motion mechanism **410**. However, transducer probe **400** can be configured and optimized in a variety of ways with more or less parts and components to provide ultrasound energy for controlled thermal injury, and the embodiment in FIGS. **4A** and **4B** are merely for illustration purposes. Transducer **404** can be any transducer configured to produce conformal lesions of thermal injury in superficial human tissue within a region of interest through precise spatial and temporal control of acoustic energy deposition.

Control interface **402** is configured for interfacing with control system **300** to facilitate control of transducer probe **400**. Control interface components **402** can comprise multiplexer/aperture select **424**, switchable electric matching networks **426**, serial EEPROMs and/or other processing components and matching and probe usage information **430** and interface connectors **432**.

Coupling components **406** can comprise various devices to facilitate coupling of transducer probe **400** to a region of interest. For example, coupling components **406** can comprise cooling and acoustic coupling system **420** configured for acoustic coupling of ultrasound energy and signals. Acoustic cooling/coupling system **420** with possible connections such as manifolds may be utilized to couple sound into the region-of-interest, control temperature at the interface and deeper into tissue, provide liquid-filled lens focusing, and/or to remove transducer waste heat. Coupling system **420** may facilitate such coupling through use of various coupling mediums, including air and other gases, water and other fluids, gels, solids, and/or any combination thereof, or any other medium that allows for signals to be transmitted between transducer active elements **412** and a region of interest. In addition to providing a coupling function, in accordance with an exemplary embodiment, coupling system **420** can also be configured for providing temperature control during the treatment application. For example, coupling system **420** can be configured for controlled cooling of an interface surface or region between transducer probe **400** and a region of interest and beyond by suitably controlling the temperature of the coupling medium. The suitable temperature for such coupling medium can be achieved in various manners, and utilize various feedback systems, such as thermocouples, thermistors or any other device or system configured for temperature measurement of a coupling medium. Such controlled cooling can be configured to further facilitate spatial and/or thermal energy control of transducer probe **400**.

In accordance with an exemplary embodiment, with additional reference to FIG. **11**, acoustic coupling and cooling **1140** can be provided to acoustically couple energy and

imaging signals from transducer probe **1104** to and from the region of interest **1106**, to provide thermal control at the probe to region-of-interest interface **1110** and deeper into tissue, and to remove potential waste heat from the transducer probe at region **1144**. Temperature monitoring can be provided at the coupling interface via a thermal sensor **1146** to provides a mechanism of temperature measurement **1148** and control via control system **1102** and a thermal control system **1142**. Thermal control may consist of passive cooling such as via heat sinks or natural conduction and convection or via active cooling such as with peltier thermoelectric coolers, refrigerants, or fluid-based systems comprised of pump, fluid reservoir, bubble detection, flow sensor, flow channels/tubing **1144** and thermal control **1142**.

With continued reference to FIG. **4**, monitoring and sensing components **408** can comprise various motion and/or position sensors **416**, temperature monitoring sensors **418**, user control and feedback switches **414** and other like components for facilitating control by control system **300**, e.g., to facilitate spatial and/or temporal control through open-loop and closed-loop feedback arrangements that monitor various spatial and temporal characteristics.

Motion mechanism **410** can comprise manual operation, mechanical arrangements, or some combination thereof. For example, a motion mechanism **422** can be suitably controlled by control system **300**, such as through the use of accelerometers, encoders or other position/orientation devices **416** to determine and enable movement and positions of transducer probe **400**. Linear, rotational or variable movement can be facilitated, e.g., those depending on the treatment application and tissue contour surface.

Transducer **404** can comprise one or more transducers configured for treating of SMAS layers and targeted regions. Transducer **404** can also comprise one or more transduction elements and/or lenses **412**. The transduction elements can comprise a piezoelectrically active material, such as lead zirconate titanate (PZT), or any other piezoelectrically active material, such as a piezoelectric ceramic, crystal, plastic, and/or composite materials, as well as lithium niobate, lead titanate, barium titanate, and/or lead metaniobate. In addition to, or instead of, a piezoelectrically active material, transducer **404** can comprise any other materials configured for generating radiation and/or acoustical energy. Transducer **404** can also comprise one or more matching layers configured along with the transduction element such as coupled to the piezoelectrically active material. Acoustic matching layers and/or damping may be employed as necessary to achieve the desired electroacoustic response.

In accordance with an exemplary embodiment, the thickness of the transduction element of transducer **404** can be configured to be uniform. That is, a transduction element **412** can be configured to have a thickness that is substantially the same throughout. In accordance with another exemplary embodiment, the thickness of a transduction element **412** can also be configured to be variable. For example, transduction element(s) **412** of transducer **404** can be configured to have a first thickness selected to provide a center operating frequency of approximately 2 kHz to 75 MHz, such as for imaging applications. Transduction element **412** can also be configured with a second thickness selected to provide a center operating frequency of approximately 2 to 400 MHz, and typically between 4 MHz and 15 MHz for therapy application. Transducer **404** can be configured as a single broadband transducer excited with at least two or more frequencies to provide an adequate output for generating a desired response. Transducer **404** can also be configured as two or more individual transducers, wherein

each transducer comprises one or more transduction element. The thickness of the transduction elements can be configured to provide center-operating frequencies in a desired treatment range. For example, transducer **404** can comprise a first transducer configured with a first transduction element having a thickness corresponding to a center frequency range of approximately 1 kHz to 3 MHz, and a second transducer configured with a second transduction element having a thickness corresponding to a center frequency of approximately 3 MHz to 100 MHz or more.

Transducer **404** may be composed of one or more individual transducers in any combination of focused, planar, or unfocused single-element, multi-element, or array transducers, including 1-D, 2-D, and annular arrays; linear, curvilinear, sector, or spherical arrays; spherically, cylindrically, and/or electronically focused, defocused, and/or lensed sources. For example, with reference to an exemplary embodiment depicted in FIG. **5**, transducer **500** can be configured as an acoustic array to facilitate phase focusing. That is, transducer **500** can be configured as an array of electronic apertures that may be operated by a variety of phases via variable electronic time delays. By the term “operated,” the electronic apertures of transducer **500** may be manipulated, driven, used, and/or configured to produce and/or deliver an energy beam corresponding to the phase variation caused by the electronic time delay. For example, these phase variations can be used to deliver defocused beams, planar beams, and/or focused beams, each of which may be used in combination to achieve different physiological effects in a region of interest **510**. Transducer **500** may additionally comprise any software and/or other hardware for generating, producing and or driving a phased aperture array with one or more electronic time delays.

Transducer **500** can also be configured to provide focused treatment to one or more regions of interest using various frequencies. In order to provide focused treatment, transducer **500** can be configured with one or more variable depth devices to facilitate treatment. For example, transducer **500** may be configured with variable depth devices disclosed in U.S. patent application Ser. No. 10/944,500, entitled “System and Method for Variable Depth Ultrasound”, filed on Sep. 16, 2004, having at least one common inventor and a common Assignee as the present application, and incorporated herein by reference. In addition, transducer **500** can also be configured to treat one or more additional ROI **510** through the enabling of sub-harmonics or pulse-echo imaging, as disclosed in U.S. patent application Ser. No. 10/944,499, entitled “Method and System for Ultrasound Treatment with a Multi-directional Transducer”, filed on Sep. 16, 2004, having at least one common inventor and a common Assignee as the present application, and also incorporated herein by reference.

Moreover, any variety of mechanical lenses or variable focus lenses, e.g. liquid-filled lenses, may also be used to focus and or defocus the sound field. For example, with reference to exemplary embodiments depicted in FIGS. **6A** and **6B**, transducer **600** may also be configured with an electronic focusing array **604** in combination with one or more transduction elements **606** to facilitate increased flexibility in treating ROI **610**. Array **604** may be configured in a manner similar to transducer **502**. That is, array **604** can be configured as an array of electronic apertures that may be operated by a variety of phases via variable electronic time delays, for example, $T_1, T_2 \dots T_j$. By the term “operated,” the electronic apertures of array **604** may be manipulated, driven, used, and/or configured to produce and/or deliver energy in a manner corresponding to the phase variation

caused by the electronic time delay. For example, these phase variations can be used to deliver defocused beams, planar beams, and/or focused beams, each of which may be used in combination to achieve different physiological effects in ROI **610**.

Transduction elements **606** may be configured to be concave, convex, and/or planar. For example, in an exemplary embodiment depicted in FIG. **6A**, transduction elements **606A** are configured to be concave in order to provide focused energy for treatment of ROI **610**. Additional embodiments are disclosed in U.S. patent application Ser. No. 10/944,500, entitled “Variable Depth Transducer System and Method”, and again incorporated herein by reference.

In another exemplary embodiment, depicted in FIG. **6B**, transduction elements **606B** can be configured to be substantially flat in order to provide substantially uniform energy to ROI **610**. While FIGS. **6A** and **6B** depict exemplary embodiments with transduction elements **604** configured as concave and substantially flat, respectively, transduction elements **604** can be configured to be concave, convex, and/or substantially flat. In addition, transduction elements **604** can be configured to be any combination of concave, convex, and/or substantially flat structures. For example, a first transduction element can be configured to be concave, while a second transduction element can be configured to be substantially flat.

With reference to FIGS. **8A** and **8B**, transducer **404** can be configured as single-element arrays, wherein a single-element **802**, e.g., a transduction element of various structures and materials, can be configured with a plurality of masks **804**, such masks comprising ceramic, metal or any other material or structure for masking or altering energy distribution from element **802**, creating an array of energy distributions **808**. Masks **804** can be coupled directly to element **802** or separated by a standoff **806**, such as any suitably solid or liquid material.

An exemplary transducer **404** can also be configured as an annular array to provide planar, focused and/or defocused acoustical energy. For example, with reference to FIGS. **10A** and **10B**, in accordance with an exemplary embodiment, an annular array **1000** can comprise a plurality of rings **1012**, **1014**, **1016** to N . Rings **1012**, **1014**, **1016** to N can be mechanically and electrically isolated into a set of individual elements, and can create planar, focused, or defocused waves. For example, such waves can be centered on-axis, such as by methods of adjusting corresponding transmit and/or receive delays, $\tau_1, \tau_2, \tau_3 \dots \tau_N$. An electronic focus can be suitably moved along various depth positions, and can enable variable strength or beam tightness, while an electronic defocus can have varying amounts of defocusing. In accordance with an exemplary embodiment, a lens and/or convex or concave shaped annular array **1000** can also be provided to aid focusing or defocusing such that any time differential delays can be reduced. Movement of annular array **800** in one, two or three-dimensions, or along any path, such as through use of probes and/or any conventional robotic arm mechanisms, may be implemented to scan and/or treat a volume or any corresponding space within a region of interest.

Transducer **404** can also be configured in other annular or non-array configurations for imaging/therapy functions. For example, with reference to FIGS. **10C-10F**, a transducer can comprise an imaging element **1012** configured with therapy element(s) **1014**. Elements **1012** and **1014** can comprise a single-transduction element, e.g., a combined imaging/transducer element, or separate elements, can be electrically

isolated **1022** within the same transduction element or between separate imaging and therapy elements, and/or can comprise standoff **1024** or other matching layers, or any combination thereof. For example, with particular reference to FIG. **10F**, a transducer can comprise an imaging element **1012** having a surface **1028** configured for focusing, defocusing or planar energy distribution, with therapy elements **1014** including a stepped-configuration lens configured for focusing, defocusing, or planar energy distribution.

With a better understanding of the various transducer structures, and with reference again to FIG. **14**, how the geometric configuration of the transducer or transducers that contributes to the wide range of lesioning effects can be better understood. For example, cigar-shaped lesions **1404** and **1406** may be produced from a spherically focused source, and/or planar lesions **1410** from a flat source. Concave planar sources and arrays can produce a "V-shaped" or ellipsoidal lesion **1414**. Electronic arrays, such as a linear array, can produce defocused, planar, or focused acoustic beams that may be employed to form a wide variety of additional lesion shapes at various depths. An array may be employed alone or in conjunction with one or more planar or focused transducers. Such transducers and arrays in combination produce a very wide range of acoustic fields and their associated benefits. A fixed focus and/or variable focus lens or lenses may be used to further increase treatment flexibility. A convex-shaped lens, with acoustic velocity less than that of superficial tissue, may be utilized, such as a liquid-filled lens, gel-filled or solid gel lens, rubber or composite lens, with adequate power handling capacity; or a concave-shaped, low profile, lens may be utilized and composed of any material or composite with velocity greater than that of tissue. While the structure of transducer source and configuration can facilitate a particular shaped lesion as suggested above, such structures are not limited to those particular shapes as the other spatial parameters, as well as the temporal parameters, can facilitate additional shapes within any transducer structure and source.

In accordance with various exemplary embodiments of the present invention, transducer **404** may be configured to provide one, two and/or three-dimensional treatment applications for focusing acoustic energy to one or more regions of interest. For example, as discussed above, transducer **404** can be suitably diced to form a one-dimensional array, e.g., transducer **602** comprising a single array of sub-transduction elements.

In accordance with another exemplary embodiment, transducer **404** may be suitably diced in two-dimensions to form a two-dimensional array. For example, with reference to FIG. **9**, an exemplary two-dimensional array **900** can be suitably diced into a plurality of two-dimensional portions **902**. Two-dimensional portions **902** can be suitably configured to focus on the treatment region at a certain depth, and thus provide respective slices **904** of the treatment region. As a result, the two-dimensional array **900** can provide a two-dimensional slicing of the image plane of a treatment region, thus providing two-dimensional treatment.

In accordance with another exemplary embodiment, transducer **404** may be suitably configured to provide three-dimensional treatment. For example, to provide three-dimensional treatment of a region of interest, with reference again to FIG. **1**, a three-dimensional system can comprise a transducer within probe **104** configured with an adaptive algorithm, such as, for example, one utilizing three-dimensional graphic software, contained in a control system, such as control system **102**. The adaptive algorithm is suitably configured to receive two-dimensional imaging, temperature

and/or treatment or other tissue parameter information relating to the region of interest, process the received information, and then provide corresponding three-dimensional imaging, temperature and/or treatment information.

In accordance with an exemplary embodiment, with reference again to FIG. **9**, an exemplary three-dimensional system can comprise a two-dimensional array **900** configured with an adaptive algorithm to suitably receive **904** slices from different image planes of the treatment region, process the received information, and then provide volumetric information **906**, e.g., three-dimensional imaging, temperature and/or treatment information. Moreover, after processing the received information with the adaptive algorithm, the two-dimensional array **900** may suitably provide therapeutic heating to the volumetric region **906** as desired.

In accordance with other exemplary embodiments, rather than utilizing an adaptive algorithm, such as three-dimensional software, to provide three-dimensional imaging and/or temperature information, an exemplary three-dimensional system can comprise a single transducer **404** configured within a probe arrangement to operate from various rotational and/or translational positions relative to a target region.

To further illustrate the various structures for transducer **404**, with reference to FIG. **7**, ultrasound therapy transducer **700** can be configured for a single focus, an array of foci, a locus of foci, a line focus, and/or diffraction patterns. Transducer **700** can also comprise single elements, multiple elements, annular arrays, one-, two-, or three-dimensional arrays, broadband transducers, and/or combinations thereof, with or without lenses, acoustic components, and mechanical and/or electronic focusing. Transducers configured as spherically focused single elements **702**, annular arrays **704**, annular arrays with damped regions **706**, line focused single elements **708**, 1-D linear arrays **710**, 1-D curvilinear arrays in concave or convex form, with or without elevation focusing, 2-D arrays, and 3-D spatial arrangements of transducers may be used to perform therapy and/or imaging and acoustic monitoring functions. For any transducer configuration, focusing and/or defocusing may be in one plane or two planes via mechanical focus **720**, convex lens **722**, concave lens **724**, compound or multiple lenses **726**, planar form **728**, or stepped form, such as illustrated in FIG. **10F**. Any transducer or combination of transducers may be utilized for treatment. For example, an annular transducer may be used with an outer portion dedicated to therapy and the inner disk dedicated to broadband imaging wherein such imaging transducer and therapy transducer have different acoustic lenses and design, such as illustrated in FIG. **10C-10F**.

Moreover, such transduction elements **700** may comprise a piezoelectrically active material, such as lead zirconate titanate (PZT), or any other piezoelectrically active material, such as a piezoelectric ceramic, crystal, plastic, and/or composite materials, as well as lithium niobate, lead titanate, barium titanate, and/or lead metaniobate. Transduction elements **700** may also comprise one or more matching layers configured along with the piezoelectrically active material. In addition to or instead of piezoelectrically active material, transduction elements **700** can comprise any other materials configured for generating radiation and/or acoustical energy. A means of transferring energy to and from the transducer to the region of interest is provided.

In accordance with another exemplary embodiment, with reference to FIG. **12**, an exemplary treatment system **200** can be configured with and/or combined with various auxiliary systems to provide additional functions. For example,

an exemplary treatment system **1200** for treating a region of interest **1206** can comprise a control system **1202**, a probe **1204**, and a display **1208**. Treatment system **1200** further comprises an auxiliary imaging modality **1274** and/or auxiliary monitoring modality **1272** may be based upon at least one of photography and other visual optical methods, magnetic resonance imaging (MRI), computed tomography (CT), optical coherence tomography (OCT), electromagnetic, microwave, or radio frequency (RF) methods, positron emission tomography (PET), infrared, ultrasound, acoustic, or any other suitable method of visualization, localization, or monitoring of SMAS layers within region-of-interest **1206**, including imaging/monitoring enhancements. Such imaging/monitoring enhancement for ultrasound imaging via probe **1204** and control system **1202** could comprise M-mode, persistence, filtering, color, Doppler, and harmonic imaging among others; furthermore an ultrasound treatment system **1270**, as a primary source of treatment, may be combined with a secondary source of treatment **1276**, including radio frequency (RF), intense pulsed light (IPL), laser, infrared laser, microwave, or any other suitable energy source.

In accordance with another exemplary embodiment, with reference to FIG. **13**, treatment composed of imaging, monitoring, and/or therapy to a region of interest may be further aided, augmented, and/or delivered with passive or active devices **1304** within the oral cavity. For example, if passive or active device **1304** is a second transducer or acoustic reflector acoustically coupled to the cheek lining it is possible to obtain through transmission, tomographic, or round-trip acoustic waves which are useful for treatment monitoring, such as in measuring acoustic speed of sound and attenuation, which are temperature dependent; furthermore such a transducer could be used to treat and/or image. In addition an active, passive, or active/passive object **1304** may be used to flatten the skin, and/or may be used as an imaging grid, marker, or beacon, to aid determination of position. A passive or active device **1304** may also be used to aid cooling or temperature control. Natural air in the oral cavity may also be used as passive device **1304** whereby it may be utilized to as an acoustic reflector to aid thickness measurement and monitoring function.

During operation of an exemplary treatment system, a lesion configuration of a selected size, shape, orientation is determined. Based on that lesion configuration, one or more spatial parameters are selected, along with suitable temporal parameters, the combination of which yields the desired conformal lesion. Operation of the transducer can then be initiated to provide the conformal lesion or lesions. Open and/or closed-loop feedback systems can also be implemented to monitor the spatial and/or temporal characteristics, and/or other tissue parameter monitoring, to further control the conformal lesions.

With reference to FIG. **13**, a collection of simulation results, illustrating thermal lesion growth over time are illustrated. Such lesion growth was generated with a spherically focused, cylindrically focused, and planar (unfocused) source at a nominal source acoustic power level, W_0 and twice that level, $2W_0$, but any configurations of transducer can be utilized as disclosed herein. The thermal contours indicate where the tissue reached 65°C . for different times. The contour for the cylindrically focused source is along the short axis, or so-called elevation plane. The figure highlights the different shapes of lesions possible with different power levels and source geometries. In addition, with reference to FIG. **14**, a pair of lesioning and simulation results is illustrated, showing chemically stained porcine tissue photomi-

crographs adjacent to their simulation results. In addition, with reference to FIG. **15**, another pair of lesioning results is illustrated, showing chemically stained porcine tissue photomicrographs, highlighting a tadpole shaped lesion and a wedge shaped lesion.

In summary, adjustment of the acoustic field spatial distribution via transducer type and distribution, such as size, element configuration, electronic or mechanical lenses, acoustic coupling and/or cooling, combined with adjustment of the temporal acoustic field, such as through control of transmit power level and timing, transmit frequency and/or drive waveform can facilitate the achieving of controlled thermal lesions of variable size, shape, and depths. Moreover, the restorative biological responses of the human body can further cause the desired effects to the superficial human tissue.

The present invention has been described above with reference to various exemplary embodiments. However, those skilled in the art will recognize that changes and modifications may be made to the exemplary embodiments without departing from the scope of the present invention. For example, the various operational steps, as well as the components for carrying out the operational steps, may be implemented in alternate ways depending upon the particular application or in consideration of any number of cost functions associated with the operation of the system, e.g., various of the steps may be deleted, modified, or combined with other steps. These and other changes or modifications are intended to be included within the scope of the present invention, as set forth in the following claims.

What is claimed is:

1. A method for tissue shrinkage, the method comprising: providing an ultrasound therapy transducer for treating a region of interest, wherein the region of interest comprises collagen below a skin surface; and transmitting ultrasound energy from the ultrasound therapy transducer into the region of interest at a frequency of 4 MHz to 15 MHz, thereby heating the collagen and a muscular fascia tissue in the region of interest to cause shrinkage of the collagen for tightening of the skin surface.
2. The method of claim 1, further comprising providing an ultrasound imaging transducer to image the region of interest.
3. The method of claim 2, wherein the imaging transducer is housed within a probe, wherein the probe also houses the therapy transducer.
4. The method of claim 1, further comprising heating a connective tissue in the region of interest.
5. The method of claim 1, further comprising heating a dermal tissue in the region of interest.
6. The method of claim 1, further comprising heating a muscle tissue in the region of interest.
7. The method of claim 1, further comprising heating a superficial muscular aponeurosis system (SMAS) in the region of interest.
8. The method of claim 1, wherein the heating of the collagen in the region of interest comprises heating the collagen to a temperature between 60°C . to 90°C .
9. The method of claim 1, further comprising monitoring the region of interest during or after therapy to provide feedback to a control system, wherein the control system controls the ultrasound therapy transducer.
10. The method of claim 1, further comprising monitoring the region of interest during or after therapy to provide feedback to an operator.

19

11. The method of claim 1, wherein the transmitting ultrasound energy from the ultrasound transducer into the region of interest comprises focusing the ultrasound energy at a depth of at most 5 mm below the skin surface.

12. A method for tissue shrinkage, the method comprising:

providing an ultrasound imaging transducer for imaging a region of interest under a skin surface;

wherein the region of interest comprises collagen;

providing an ultrasound therapy transducer for delivering therapeutic ultrasound energy to the region of interest to heat the collagen and a muscle tissue with the therapeutic ultrasound energy at a temperature sufficient to shrink the collagen, thereby tightening the skin surface; and

wherein the imaging transducer and the therapy transducer are co-housed within a single probe.

13. The method of claim 12, wherein the therapy transducer is configured to deliver energy at a frequency in the range of 4 MHz to 15 MHz.

14. The method of claim 12, wherein the probe is controlled by a control system.

15. The method of claim 14, wherein the control system is configured to receive feedback from the imaging transducer.

20

16. A method for tissue shrinkage, the method comprising:

providing an ultrasound therapy transducer for treating a region of interest,

wherein the region of interest comprises collagen below a skin surface; and

wherein ultrasound energy is transmitted from the ultrasound transducer into the region of interest, thereby heating the collagen in a superficial muscular aponeurosis system (SMAS) tissue in the region of interest to cause shrinkage of the collagen for tightening of the skin surface.

17. The method of claim 16, further comprising heating at least one of a connective tissue, a dermis tissue, a muscular fascia, and an adipose tissue.

18. The method of claim 16, further comprising providing an imaging transducer for imaging the region of interest.

19. The method of claim 18, wherein the imaging transducer and the therapy transducer are co-housed within a probe, and wherein the therapy transducer is configured to deliver energy at a frequency in the range of 4 MHz to 15 MHz.

20. The method of claim 19, wherein the therapy transducer is configured to deliver energy sufficient to heat the region of interest to a temperature between 60° C. to 90° C.

* * * * *

专利名称(译)	用于无创皮肤收紧的系统和方法		
公开(公告)号	US9974982	公开(公告)日	2018-05-22
申请号	US15/098139	申请日	2016-04-13
申请(专利权)人(译)	引导治疗系统公司		
当前申请(专利权)人(译)	引导治疗系统公司		
[标]发明人	SLAYTON MICHAEL H BARTHE PETER G MAKIN INDER RAJ S OCONNOR BRIAN D		
发明人	SLAYTON, MICHAEL H. BARTHE, PETER G. MAKIN, INDER RAJ S. O'CONNOR, BRIAN D.		
IPC分类号	A61B7/02 A61B17/32 G01S15/89 A61N7/00 A61H23/02 A61B8/12 A61B8/08 A61B5/00 A61N7/02 A61B8/00		
CPC分类号	A61N7/02 A61B5/6842 A61B8/08 A61B8/0858 A61B8/12 A61B8/4483 A61B8/483 A61B8/546 A61B17/320068 A61H23/0245 A61N7/00 G01S15/8909 A61B5/682 G01S15/899 A61B8/4281 A61B8/4455 A61H2201/5007 A61H2230/50 A61N2007/0008 A61N2007/0034 A61B2017/320069		
优先权	12/028636 2013-09-17 US 60/616755 2004-10-06 US 60/616754 2004-10-06 US		
其他公开文献	US20160228729A1		
外部链接	Espacenet USPTO		

摘要(译)

公开了用于无创脸部提升和深层组织收紧的方法和系统。示例性的方法和治疗系统被配置用于治疗SMAS区域的成像，监测和热损伤。根据示例性实施例，示例性方法和系统被配置用于通过首先对感兴趣区域进行成像以处理区域和周围结构的定位来处理SMAS区域，其次，在深度处输送超声能量，时间和能量水平，以达到理想的治疗效果；第三，在治疗之前，期间和之后监测治疗区域，以计划和评估结果和/或提供反馈。

