



US010126998B2

(12) **United States Patent**
Yuen et al.

(10) **Patent No.:** **US 10,126,998 B2**
(45) **Date of Patent:** **Nov. 13, 2018**

(54) **MOTION-ACTIVATED DISPLAY OF MESSAGES ON AN ACTIVITY MONITORING DEVICE**

(71) Applicant: **Fitbit, Inc.**, San Francisco, CA (US)

(72) Inventors: **Shelten Yuen**, Berkeley, CA (US);
Timothy Roberts, San Francisco, CA (US)

(73) Assignee: **Fitbit, Inc.**, San Francisco, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/583,959**

(22) Filed: **May 1, 2017**

(65) **Prior Publication Data**

US 2017/0249115 A1 Aug. 31, 2017

Related U.S. Application Data

(60) Continuation of application No. 15/156,103, filed on May 16, 2016, now Pat. No. 9,639,170, which is a (Continued)

(51) **Int. Cl.**
G06F 3/00 (2006.01)
A61B 5/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **G06F 3/14** (2013.01); **A61B 5/0022** (2013.01); **A61B 5/1118** (2013.01); **A61B 5/222** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC .. G01C 22/006; A61B 5/1118; A63B 24/0062
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,717,736 A 9/1955 Schlesinger
2,827,309 A 3/1958 Fred
(Continued)

FOREIGN PATENT DOCUMENTS

CN 101978374 2/2011
CN 102111434 6/2011
(Continued)

OTHER PUBLICATIONS

“Activator is One of the Best Cydia iPhone Hacks | Control your iPhone with Gestures,” *iphone-tips-and-advice.com*, [retrieved on Jul. 9, 2013 at <http://www.iphone-tips-and-advice.com/activator.html>], 10 pp.

(Continued)


Primary Examiner — Michael Dalbo

(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson & Bear, LLP

(57) **ABSTRACT**

Methods, systems and devices are provided for motion-activated display of messages on an activity monitoring device. In one embodiment, method for presenting a message on an activity monitoring device is provided, including the following method operations: storing a plurality of messages to the device; detecting a stationary state of the device; detecting a movement of the device from the stationary state; in response to detecting the movement from the stationary state, selecting one of a plurality of messages, and displaying the selected message on the device.

20 Claims, 16 Drawing Sheets



Related U.S. Application Data

(56)

References Cited

continuation of application No. 14/580,808, filed on Dec. 23, 2014, now Pat. No. 9,374,279, which is a continuation of application No. 14/271,389, filed on May 6, 2014, now Pat. No. 8,954,290, which is a continuation-in-part of application No. 13/959,714, filed on Aug. 5, 2013, now Pat. No. 8,762,101, which is a continuation-in-part of application No. 13/693,334, filed on Dec. 4, 2012, now Pat. No. 8,548,770, which is a division of application No. 13/667,229, filed on Nov. 2, 2012, now Pat. No. 8,437,980, which is a division of application No. 13/469,027, filed on May 10, 2012, now Pat. No. 8,311,769, which is a division of application No. 13/246,843, filed on Sep. 27, 2011, now Pat. No. 8,180,591, which is a division of application No. 13/156,304, filed on Jun. 8, 2011, now Pat. No. 9,167,991, said application No. 13/959,714 is a continuation-in-part of application No. 13/759,485, filed on Feb. 5, 2013, now Pat. No. 8,543,351, which is a division of application No. 13/667,229.

(60) Provisional application No. 61/388,595, filed on Sep. 30, 2010, provisional application No. 61/390,811, filed on Oct. 7, 2010.

(51) Int. Cl.

- G01C 22/00* (2006.01)
- A63B 23/00* (2006.01)
- G06F 3/14* (2006.01)
- G06F 3/01* (2006.01)
- G06F 17/21* (2006.01)
- H04L 29/08* (2006.01)
- A63B 24/00* (2006.01)
- H04W 4/21* (2018.01)
- A61B 5/22* (2006.01)
- G06F 19/00* (2018.01)
- H04L 12/24* (2006.01)
- G06F 1/16* (2006.01)
- H04L 29/06* (2006.01)
- H04W 4/02* (2018.01)
- G16H 40/63* (2018.01)
- A61B 5/0205* (2006.01)
- A61B 5/024* (2006.01)
- A61B 5/11* (2006.01)
- A61B 5/021* (2006.01)

(52) U.S. Cl.

- CPC *A61B 5/6838* (2013.01); *A61B 5/743* (2013.01); *A63B 24/0062* (2013.01); *G06F 1/163* (2013.01); *G06F 1/1694* (2013.01); *G06F 3/011* (2013.01); *G06F 3/017* (2013.01); *G06F 17/21* (2013.01); *G06F 19/00* (2013.01); *G06F 19/3481* (2013.01); *H04L 41/22* (2013.01); *H04L 67/1095* (2013.01); *H04L 67/22* (2013.01); *H04L 67/306* (2013.01); *H04L 67/42* (2013.01); *H04W 4/02* (2013.01); *H04W 4/21* (2018.02); *A61B 5/021* (2013.01); *A61B 5/024* (2013.01); *A61B 5/02055* (2013.01); *A61B 5/1112* (2013.01); *A61B 5/4809* (2013.01); *A61B 5/4812* (2013.01); *A61B 5/4815* (2013.01); *A61B 2560/0214* (2013.01); *A61B 2560/0242* (2013.01); *A61B 2562/0219* (2013.01); *G01C 22/006* (2013.01); *G16H 40/63* (2018.01)

U.S. PATENT DOCUMENTS

- 2,883,255 A 4/1959 Anderson
- 3,163,856 A 12/1964 Kirby
- 3,250,270 A 5/1966 Bloom
- 3,522,383 A 7/1970 Chang
- 3,918,658 A 11/1975 Beller
- 4,192,000 A 3/1980 Lipsey
- 4,244,020 A 1/1981 Ratcliff
- 4,281,663 A 8/1981 Pringle
- 4,284,849 A 8/1981 Anderson et al.
- 4,312,358 A 1/1982 Barney
- 4,367,752 A 1/1983 Jimenez et al.
- 4,390,922 A 6/1983 Pelliccia
- 4,407,295 A 10/1983 Steuer et al.
- 4,425,921 A 1/1984 Fujisaki et al.
- 4,466,204 A 8/1984 Wu
- 4,575,804 A 3/1986 Ratcliff
- 4,578,769 A 3/1986 Frederick
- 4,617,525 A 10/1986 Lloyd
- 4,887,249 A 12/1989 Thinesen
- 4,930,518 A 6/1990 Hrushesky
- 4,977,509 A 12/1990 Pitchford et al.
- 5,058,427 A 10/1991 Brandt
- 5,099,842 A 3/1992 Mannheimer
- 5,224,059 A 6/1993 Nita et al.
- 5,295,085 A 3/1994 Hoffacker
- 5,314,389 A 5/1994 Dotan
- 5,323,650 A 6/1994 Fullen et al.
- 5,365,930 A 11/1994 Takashima et al.
- 5,446,705 A 8/1995 Haas et al.
- 5,456,648 A 10/1995 Edinburg et al.
- 5,553,296 A 9/1996 Forrest et al.
- 5,583,776 A 12/1996 Levi et al.
- 5,645,509 A 7/1997 Brewer et al.
- 5,671,162 A 9/1997 Werbin
- 5,692,324 A 12/1997 Goldston et al.
- 5,704,350 A 1/1998 Williams, III
- 5,724,265 A 3/1998 Hutchings
- 5,817,008 A 10/1998 Rafert et al.
- 5,890,128 A 3/1999 Diaz et al.
- 5,891,042 A 4/1999 Sham et al.
- 5,894,454 A 4/1999 Kondo
- 5,899,963 A 5/1999 Hutchings
- 5,941,828 A 8/1999 Archibald et al.
- 5,947,868 A 9/1999 Dugan
- 5,955,667 A 9/1999 Fyfe
- 5,976,083 A 11/1999 Richardson et al.
- 6,018,705 A 1/2000 Gaudet et al.
- 6,077,193 A 6/2000 Buhler et al.
- 6,078,874 A 6/2000 Piety et al.
- 6,085,248 A 7/2000 Sambamurthy et al.
- 6,129,686 A 10/2000 Friedman
- 6,145,389 A 11/2000 Ebeling et al.
- 6,183,425 B1 2/2001 Whalen et al.
- 6,213,872 B1 4/2001 Harada et al.
- 6,241,684 B1 6/2001 Amino et al.
- 6,287,262 B1 9/2001 Amano et al.
- 6,301,964 B1 10/2001 Fyfe et al.
- 6,302,789 B2 10/2001 Harada et al.
- 6,305,221 B1 10/2001 Hutchings
- 6,309,360 B1 10/2001 Mault
- 6,454,708 B1 9/2002 Ferguson et al.
- 6,469,639 B2 10/2002 Tanenhaus et al.
- 6,478,736 B1 11/2002 Mault
- 6,513,381 B2 2/2003 Fyfe et al.
- 6,513,532 B2 2/2003 Mault et al.
- 6,527,711 B1 3/2003 Stivoric et al.
- 6,529,827 B1 3/2003 Beason et al.
- 6,558,335 B1 5/2003 Thede
- 6,561,951 B2 5/2003 Cannon et al.
- 6,571,200 B1 5/2003 Mault
- 6,583,369 B2 6/2003 Montagnino et al.
- 6,585,622 B1 7/2003 Shum et al.
- 6,607,493 B2 8/2003 Song
- 6,620,078 B2 9/2003 Pfeffer
- 6,678,629 B2 1/2004 Tsuji

(56)

References Cited

U.S. PATENT DOCUMENTS

6,699,188	B2	3/2004	Wessel	8,437,980	B2	5/2013	Yuen et al.
6,761,064	B2	7/2004	Tsuji	8,462,591	B1	6/2013	Marhaben
6,772,331	B1	8/2004	Hind et al.	8,463,576	B2	6/2013	Yuen et al.
6,788,200	B1	9/2004	Jamel et al.	8,463,577	B2	6/2013	Yuen et al.
6,790,178	B1	9/2004	Mault et al.	8,487,771	B2	7/2013	Hsieh et al.
6,808,473	B2	10/2004	Hisano et al.	8,533,269	B2	9/2013	Brown
6,811,516	B1	11/2004	Dugan	8,533,620	B2	9/2013	Hoffman et al.
6,813,582	B2	11/2004	Levi et al.	8,543,185	B2	9/2013	Yuen et al.
6,813,931	B2	11/2004	Yadav et al.	8,543,351	B2	9/2013	Yuen et al.
6,856,938	B2	2/2005	Kurtz	8,548,770	B2	10/2013	Yuen et al.
6,862,575	B1	3/2005	Anttila et al.	8,562,489	B2	10/2013	Burton et al.
6,984,207	B1	1/2006	Sullivan et al.	8,583,402	B2	11/2013	Yuen et al.
7,020,508	B2	3/2006	Stivoric et al.	8,597,093	B2	12/2013	Engelberg et al.
7,041,032	B1	5/2006	Calvano	8,634,796	B2	1/2014	Johnson
7,062,225	B2	6/2006	White	8,638,228	B2	1/2014	Amico et al.
7,099,237	B2	8/2006	Lall	8,670,953	B2	3/2014	Yuen et al.
7,133,690	B2	11/2006	Ranta-Aho et al.	8,684,900	B2	4/2014	Tran
7,162,368	B2	1/2007	Levi et al.	8,690,578	B1	4/2014	Nusbaum et al.
7,171,331	B2	1/2007	Vock et al.	8,738,321	B2	5/2014	Yuen et al.
7,200,517	B2	4/2007	Darley et al.	8,738,323	B2	5/2014	Yuen et al.
7,246,033	B1	7/2007	Kudo	8,744,803	B2	6/2014	Park et al.
7,261,690	B2	8/2007	Teller et al.	8,762,101	B2	6/2014	Yuen et al.
7,272,982	B2	9/2007	Neuhauser et al.	8,764,651	B2	7/2014	Tran
7,283,870	B2	10/2007	Kaiser et al.	8,825,445	B2	9/2014	Hoffman et al.
7,285,090	B2	10/2007	Stivoric et al.	8,847,988	B2	9/2014	Geisner et al.
7,373,820	B1	5/2008	James	8,868,377	B2	10/2014	Yuen et al.
7,443,292	B2	10/2008	Jensen et al.	8,892,401	B2	11/2014	Yuen et al.
7,457,724	B2	11/2008	Vock et al.	8,949,070	B1	2/2015	Kahn et al.
7,467,060	B2	12/2008	Kulach et al.	8,954,290	B2	2/2015	Yuen et al.
7,502,643	B2	3/2009	Farrinqdon et al.	8,961,414	B2	2/2015	Teller et al.
7,505,865	B2	3/2009	Ohkubo et al.	8,968,195	B2	3/2015	Tran
7,539,532	B2	5/2009	Tran	9,047,648	B1	6/2015	Lekutai et al.
7,558,622	B2	7/2009	Tran	9,081,534	B2	7/2015	Yuen et al.
7,559,877	B2	7/2009	Parks et al.	9,369,170	B2	6/2016	Sorrentino
7,608,050	B2	10/2009	Shugg	9,374,279	B2*	6/2016	Yuen G06F 3/011
7,653,508	B1	1/2010	Kahn et al.	9,426,769	B2	8/2016	Haro
7,690,556	B1	4/2010	Kahn et al.	9,639,170	B2*	5/2017	Yuen G06F 3/017
7,713,173	B2	5/2010	Shin et al.	2001/0049470	A1	12/2001	Mault et al.
7,762,952	B2	7/2010	Lee et al.	2001/0055242	A1	12/2001	Deshmuhk et al.
7,771,320	B2	8/2010	Riley et al.	2002/0013717	A1	1/2002	Ando et al.
7,774,156	B2	8/2010	Niva et al.	2002/0019585	A1	2/2002	Dickenson
7,789,802	B2	9/2010	Lee et al.	2002/0077219	A1	6/2002	Cohen et al.
7,827,000	B2	11/2010	Stirling et al.	2002/0082144	A1	6/2002	Pfeffer
7,865,140	B2	1/2011	Levien et al.	2002/0087264	A1	7/2002	Hills et al.
7,881,902	B1	2/2011	Kahn et al.	2002/0109600	A1	8/2002	Mault et al.
7,907,901	B1	3/2011	Kahn et al.	2002/0178060	A1	11/2002	Sheehan
7,925,022	B2	4/2011	Jung et al.	2002/0191797	A1	12/2002	Perlman
7,927,253	B2	4/2011	Vincent et al.	2002/0198776	A1	12/2002	Nara et al.
7,941,665	B2	5/2011	Berkema et al.	2003/0018523	A1	1/2003	Rappaport et al.
7,942,824	B1	5/2011	Kayyali et al.	2003/0050537	A1	3/2003	Wessel
7,953,549	B2	5/2011	Graham et al.	2003/0065561	A1	4/2003	Brown et al.
7,983,876	B2	7/2011	Vock et al.	2003/0107575	A1	6/2003	Cardno
8,005,922	B2	8/2011	Boudreau et al.	2003/0131059	A1	7/2003	Brown et al.
8,028,443	B2	10/2011	Case, Jr.	2003/0171189	A1	9/2003	Kaufman
8,036,850	B2	10/2011	Kulach et al.	2003/0208335	A1	11/2003	Unuma et al.
8,055,469	B2	11/2011	Kulach et al.	2003/0226695	A1	12/2003	Mault
8,059,573	B2	11/2011	Julian et al.	2004/0054497	A1	3/2004	Kurtz
8,060,337	B2	11/2011	Kulach et al.	2004/0061324	A1	4/2004	Howard
8,095,071	B2	1/2012	Sim et al.	2004/0117963	A1	6/2004	Schneider
8,099,318	B2	1/2012	Moukas et al.	2004/0122488	A1	6/2004	Mazar et al.
8,103,247	B2	1/2012	Ananthanarayanan et al.	2004/0152957	A1	8/2004	Stivoric et al.
8,132,037	B2	3/2012	Fehr et al.	2004/0239497	A1	12/2004	Schwartzman et al.
8,172,761	B1	5/2012	Rulkov et al.	2004/0249299	A1	12/2004	Cobb
8,177,260	B2	5/2012	Tropper et al.	2004/0257557	A1	12/2004	Block
8,180,591	B2	5/2012	Yuen et al.	2005/0037844	A1	2/2005	Shum et al.
8,180,592	B2	5/2012	Yuen et al.	2005/0038679	A1	2/2005	Short
8,190,651	B2	5/2012	Treu et al.	2005/0054938	A1	3/2005	Wehman et al.
8,213,613	B2	7/2012	Diehl et al.	2005/0102172	A1	5/2005	Sirmans, Jr.
8,260,261	B2	9/2012	Teague	2005/0107723	A1	5/2005	Wehman et al.
8,270,297	B2	9/2012	Akasaka et al.	2005/0163056	A1	7/2005	Ranta-Aho et al.
8,271,662	B1	9/2012	Gossweiler, III et al.	2005/0171410	A1	8/2005	Hielt et al.
8,289,162	B2	10/2012	Mooring et al.	2005/0186965	A1	8/2005	Pagonis et al.
8,311,769	B2	11/2012	Yuen et al.	2005/0187481	A1	8/2005	Hatib
8,311,770	B2	11/2012	Yuen et al.	2005/0195830	A1	9/2005	Chitrapu et al.
8,386,008	B2	2/2013	Yuen et al.	2005/0216724	A1	9/2005	Isozaki
				2005/0228244	A1	10/2005	Banet
				2005/0228692	A1	10/2005	Hodgdon
				2005/0234742	A1	10/2005	Hodgdon
				2005/0248718	A1	11/2005	Howell et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0272564	A1	12/2005	Pyles et al.	2008/0214360	A1	9/2008	Stirling et al.
2006/0004265	A1	1/2006	Pulkkinen et al.	2008/0275309	A1	11/2008	Stivoric et al.
2006/0020174	A1	1/2006	Matsumura	2008/0285805	A1	11/2008	Luinge et al.
2006/0020177	A1	1/2006	Seo et al.	2008/0287751	A1	11/2008	Stivoric et al.
2006/0025282	A1	2/2006	Redmann	2008/0300641	A1	12/2008	Brunekreeft
2006/0039348	A1	2/2006	Racz et al.	2009/0012418	A1	1/2009	Gerlach
2006/0047208	A1	3/2006	Yoon	2009/0018797	A1	1/2009	Kasama et al.
2006/0047447	A1	3/2006	Brady et al.	2009/0043531	A1	2/2009	Kahn et al.
2006/0064037	A1	3/2006	Shalon et al.	2009/0047645	A1	2/2009	Dibenedetto et al.
2006/0064276	A1*	3/2006	Ren G01C 22/006 702/160	2009/0048044	A1	2/2009	Oleson et al.
2006/0069619	A1	3/2006	Walker et al.	2009/0054737	A1	2/2009	Magar et al.
2006/0089542	A1	4/2006	Sands	2009/0054751	A1	2/2009	Babashan et al.
2006/0106535	A1	5/2006	Duncan	2009/0058635	A1	3/2009	Lalonde et al.
2006/0111944	A1	5/2006	Sirmans, Jr. et al.	2009/0063193	A1	3/2009	Barton et al.
2006/0129436	A1	6/2006	Short	2009/0063293	A1	3/2009	Barton et al.
2006/0136173	A1*	6/2006	Case, Jr. A63B 24/00 702/182	2009/0076765	A1	3/2009	Kulach et al.
2006/0143645	A1	6/2006	Vock et al.	2009/0088183	A1	4/2009	Piersol
2006/0166718	A1	7/2006	Seshadri et al.	2009/0093341	A1	4/2009	James et al.
2006/0189863	A1	8/2006	Peysner	2009/0098821	A1	4/2009	Shinya
2006/0217231	A1	9/2006	Parks et al.	2009/0144456	A1	6/2009	Gelf et al.
2006/0247952	A1	11/2006	Muraca	2009/0144639	A1*	6/2009	Nims A63B 24/0059 715/757
2006/0277474	A1	12/2006	Robarts et al.	2009/0150178	A1	6/2009	Sutton et al.
2006/0282021	A1	12/2006	DeVaul et al.	2009/0156172	A1*	6/2009	Chan H04M 1/72566 455/412.2
2006/0287883	A1	12/2006	Turgiss et al.	2009/0171788	A1	7/2009	Tropper et al.
2006/0288117	A1	12/2006	Raveendran et al.	2009/0195350	A1	8/2009	Tsern et al.
2007/0011028	A1	1/2007	Sweeney	2009/0262088	A1	10/2009	Moll-Carrillo et al.
2007/0049384	A1	3/2007	King et al.	2009/0264713	A1	10/2009	Van loenen et al.
2007/0050715	A1	3/2007	Behar	2009/0271147	A1	10/2009	Sugai
2007/0051369	A1	3/2007	Choi et al.	2009/0287921	A1	11/2009	Zhu et al.
2007/0061593	A1	3/2007	Celikkan et al.	2009/0307517	A1	12/2009	Fehr et al.
2007/0071643	A1	3/2007	Hall et al.	2009/0309742	A1	12/2009	Alexander et al.
2007/0072156	A1	3/2007	Kaufinan et al.	2009/0313857	A1	12/2009	Carnes et al.
2007/0083095	A1	4/2007	Rippo et al.	2010/0023348	A1	1/2010	Hardee et al.
2007/0083602	A1	4/2007	Heqqenhouqen et al.	2010/0043056	A1	2/2010	Ganapathy
2007/0123391	A1	5/2007	Shin et al.	2010/0058064	A1	3/2010	Kirovski et al.
2007/0135264	A1	6/2007	Hosenberc	2010/0059561	A1	3/2010	Ellis et al.
2007/0136093	A1	6/2007	Rankin et al.	2010/0069203	A1	3/2010	Kawaquchi et al.
2007/0146116	A1*	6/2007	Kimbrell A61B 5/681 340/5.52	2010/0079291	A1	4/2010	Kroll
2007/0155277	A1	7/2007	Amitai et al.	2010/0125729	A1	5/2010	Baentsch et al.
2007/0159926	A1	7/2007	Prstojevich et al.	2010/0130873	A1	5/2010	Yuen et al.
2007/0179356	A1	8/2007	Wessel	2010/0158494	A1	6/2010	Klnq
2007/0179761	A1	8/2007	Wren et al.	2010/0159709	A1	6/2010	Kotani et al.
2007/0194066	A1	8/2007	Ishihara et al.	2010/0167783	A1*	7/2010	Alameh H04M 1/0202 455/556.1
2007/0197920	A1	8/2007	Adams	2010/0179411	A1	7/2010	Holmstrom et al.
2007/0208544	A1	9/2007	Kulach et al.	2010/0185064	A1	7/2010	Bandic et al.
2007/0276271	A1	11/2007	Chan	2010/0191153	A1	7/2010	Sanders et al.
2007/0288265	A1	12/2007	Quinian et al.	2010/0205541	A1	8/2010	Rapaport et al.
2008/0001735	A1	1/2008	Tran	2010/0217099	A1	8/2010	LeBoeuf et al.
2008/0014947	A1	1/2008	Carnall	2010/0222179	A1	9/2010	Temple et al.
2008/0022089	A1	1/2008	Leedom	2010/0234181	A1*	9/2010	Cho A63B 24/0062 482/8
2008/0032864	A1	2/2008	Hakki	2010/0261987	A1	10/2010	Kamath et al.
2008/0044014	A1	2/2008	Corndorf	2010/0292050	A1	11/2010	DiBenedetto
2008/0054072	A1	3/2008	Katraqadda et al.	2010/0292600	A1	11/2010	DiBenedetto et al.
2008/0084823	A1	4/2008	Akasaka et al.	2010/0295684	A1	11/2010	Hsieh et al.
2008/0093838	A1	4/2008	Tropper et al.	2010/0298656	A1	11/2010	McCombie et al.
2008/0097550	A1	4/2008	Dicks et al.	2010/0298661	A1	11/2010	McCombie et al.
2008/0109158	A1	5/2008	Huhtala	2010/0304674	A1	12/2010	Kim et al.
2008/0114829	A1*	5/2008	Button H04L 67/327 709/203	2010/0311544	A1	12/2010	Robinette et al.
2008/0125288	A1	5/2008	Case	2010/0331145	A1	12/2010	Lakovic et al.
2008/0125959	A1	5/2008	Doherty	2011/0003665	A1	1/2011	Burton et al.
2008/0129457	A1	6/2008	Ritter et al.	2011/0009051	A1	1/2011	Khedouri et al.
2008/0134102	A1*	6/2008	Movold G06F 3/017 715/863	2011/0021143	A1	1/2011	Kapur et al.
2008/0139910	A1	6/2008	Mastrototaro et al.	2011/0022349	A1	1/2011	Stirling et al.
2008/0140163	A1	6/2008	Keacher et al.	2011/0029241	A1	2/2011	Miller et al.
2008/0140338	A1	6/2008	No et al.	2011/0032105	A1	2/2011	Hoffman et al.
2008/0146892	A1	6/2008	LeBoeuf et al.	2011/0051665	A1	3/2011	Huang
2008/0155077	A1	6/2008	James	2011/0080349	A1	4/2011	Holbein et al.
2008/0176655	A1	7/2008	James et al.	2011/0087076	A1	4/2011	Brynelsen et al.
2008/0190202	A1	8/2008	Kulach et al.	2011/0087431	A1*	4/2011	Gupta G01S 5/02 701/408
				2011/0106449	A1	5/2011	Chowdhary et al.
				2011/0109540	A1	5/2011	Milne et al.
				2011/0131005	A1	6/2011	Ueshima et al.
				2011/0145894	A1	6/2011	Garcia Morchon et al.
				2011/0153773	A1	6/2011	Vandwalle

(56) **References Cited**

FOREIGN PATENT DOCUMENTS

WO	WO 12/171032	12/2012
WO	WO 15/127067	8/2015
WO	WO 16/003269	1/2016

OTHER PUBLICATIONS

"Parts of Your Band," (Product Release Date Unknown, downloaded Jul. 22, 2013) Jawbone UP Band, 1 page.

Chandrasekar et al., Aug. 28-Sep. 1, 2012, Plug-and-Play, Single-Chip Photoplethysmography, 34th Annual International Conference of the IEEE EMBS, San Diego, California USA, 4 pages.

Chudnow, Alan (Dec. 3, 2012) "Basis Wristband Make Its Debut," The Wired Self, Living in a Wired World, published in Health [retrieved on Jul. 22, 2013 at <http://thewiredself.com/health/basis-wrist-band-make-its-debut/>], 3pp.

Clifford et al., Altimeter and Barometer System, Freescale Semiconductor Application Note AN1979, Rev. 3, Nov. 2006.

Definition of "Graphic" from Merriam-Webster Dictionary, downloaded from merriam-webster.com on Oct. 4, 2014, 3 pp.

Definition of "Graphical user interface" from Merriam-Webster Dictionary, downloaded from merriam-webster.com on Oct. 4, 2014, 2 pp.

DesMarais, Christina (posted on Sep. 3, 2013) "Which New Activity Tracker is Best for You?" Health and Home, Health & Fitness, Guides & Reviews, [Retrieved on Sep. 23, 2013 at <http://www.techlicious.com/guide/which-new-activity-tracker-is-right-for--you/>] 4 pp.

Empson, Rip, (Sep. 22, 2011) "Basis Reveals an Awesome New Affordable Heart and Health Tracker You Can Wear on Your Wrist," [retrieved on Sep. 23, 2013 at <http://techcrunch.com/2011/09/22/basis-reveals-an-awesome-new-...>], 3 pp.

Fang et al., Dec. 2005, Design of a Wireless Assisted Pedestrian Dead Reckoning System—The NavMote Experience, IEEE Transactions on Instrumentation and Measurement, 54(6):2342-2358.

Fitbit Inc., "Fitbit Automatically Tracks Your Fitness and Sleep" published online at web.archive.org/web/20080910224820/http://www.fitbit.com, copyright Sep. 10, 2008, 1 p.

Fitbit User's Manual, Last Updated Oct. 22, 2009, 15 pages.

Forerunner® 10 Owner's Manual (Aug. 2012), Garmin Ltd., 10 pp.

Forerunner® 110 Owner's Manual, (2010) "GPS-Enabled Sport Watch," Garmin Ltd., 16 pp.

Forerunner® 201 personal trainer owner's manual, (Feb. 2006) Garmin Ltd., 48 pp.

Forerunner® 205/305 Owner's Manual, GPS-enabled trainer for runners, (2006-2008), Garmin Ltd., 80 pp.

Forerunner® 210 Owner's Manual, (2010) "GPS-Enabled Sport Watch," Garmin Ltd., 28 pp.

Forerunner® 301 personal trainer owner's manual, (Feb. 2006) Garmin Ltd., 66 pp.

Forerunner® 310XT Owner's Manual, Multisport GPS Training Device, (2009-2013), Garmin Ltd., 56 pp.

Forerunner® 405 Owner's Manual, (Mar. 2011) "GPS-Enabled Sport Watch With Wireless Sync," Garmin Ltd., 56 pp.

Forerunner® 405CX Owner's Manual, "GPS-Enabled Sports Watch With Wireless Sync," (Mar. 2009), Garmin Ltd., 56 pp.

Forerunner® 410 Owner's Manual, (Jul. 2012) "GPS-Enabled Sport Watch With Wireless Sync," Garmin Ltd., 52 pp.

Forerunner® 50 with ANT+Sport.TM. wireless technology, Owner's Manual, (Nov. 2007) Garmin Ltd., 44 pp.

Forerunner® 910XT Owner's Manual, (Jan. 2013) Garmin Ltd., 56 pp.

Garmin Swim™ Owner's Manual (Jun. 2012), 12 pp.

Godfrey et al., 2008, Direct Measurement of Human Movement by Accelerometry, Medical Engineering & Physics, 30:1364-1386.

Godha et al., May 2008, Foot Mounted Inertia System for Pedestrian Navigation, Measurement Science and Technology, 19(7):1-9.

Intersema App., Using MS5534 for altimeters and barometers, Note AN501, Jan. 2006.

Ladetto et al. Sep. 2000, On Foot Navigation: When GPS alone is not Enough, Journal of Navigation, 53(2):279-285.

Lammel et al., Sep. 2009, Indoor Navigation with MEMS Sensors, Proceedings of the Eurosensors XIII conference, 1(1):532-535.

Lark/Larkpro, User Manual, (2012) "What's in the box," Lark Technologies, 7 pp.

Larklife, User Manual, (2012) Lark Technologies, 7 pp.

Lester et al., 2005, A Hybrid Discriminative/Generative Approach for Modeling Human Activities, Proc. of the Int'l Joint Conf. Artificial Intelligence, pp. 766-772.

Lester et al., 2009, Validated caloric expenditure estimation using a single body-worn sensor, Proc. of the Int'l Conf. on Ubiquitous Computing, pp. 225-234.

Minetti et al. Energy cost of walking and running at extreme uphill and downhill slopes. J Appl Physiol. 2002; 93:10-39-1046.

Nike+ FuelBand GPS Manual, User's Guide (Product Release Date Unknown, downloaded Jul. 22, 2013), 26 pages.

Nike+SportBand User's Guide, (Product Release Date Unknown, downloaded Jul. 22, 2013), 36 pages.

Nike+SportWatch GPS Manual, User's Guide, Powered by TOMTOM, (Product Release Date Unknown, downloaded Jul. 22, 2013), 42 pages.

O'Donovan et al., 2009, A context aware wireless body area network (BAN), Proc. 3rd Intl. Conf. Pervasive Computing Technologies for Healthcare, pp. 1-8.

Ohtaki et al., Aug. 2005, Automatic classification of ambulatory movements and evaluation of energy consumptions utilizing accelerometers and barometer, Microsystem Technologies, 11(8-10):1034-1040.

Parkka et al., Jan. 2006, Activity Classification Using Realistic Data From Wearable Sensors, IEEE Transactions on Information Technology in Biomedicine, 10(1):119-128.

Perrin et al., 2000, Improvement of Walking Speed Prediction by Accelerometry and Altimetry, Validated by Satellite Positioning, Medical & Biological Engineering & Computing, 38:164-168.

Polar WearLink® + Coded Transmitter 31 Coded Transmitter W.I.N.D. User Manual, POLAR® Listen to Your Body, Manufactured by Polar Electro Oy, 11 pages.

Rainmaker, (Jun. 25, 2012, updated Feb. 16, 2013) "Garmin Swim watch In-Depth Review," [retrieved on Sep. 9, 2013 at <http://www.dcrainmaker.com/2012/06/garmin-swim-in-depth-review.html>], 38 pp.

Retscher, 2006, An Intelligent Multi-Sensor system for Pedestrian Navigation, Journal of Global Positioning Systems, 5(1):110-118.

Sagawa et al., Aug.-Sep. 1998, Classification of Human Moving Patterns Using Air Pressure and Acceleration, Proceedings of the 24th Annual Conference of the IEEE Industrial Electronics Society, 2:1214-1219.

Sagawa et al., Oct. 2000, Non-restricted measurement of walking distance, IEEE Int'l Conf. on Systems, Man, and Cybernetics, 3:1847-1852.

SCP 1000-D01/D11 Pressure Sensor as Barometer and Altimeter, VTI Technologies Application, Jun. 2006, Note 33.

Specification of the Bluetooth® System, Core Package, version 4.1, Dec. 2013, vols. 0 & 1, 282 pages.

Stirling et al., 2005, Evaluation of a New Method of Heading Estimation of Pedestrian Dead Reckoning Using Shoe Mounted Sensors, Journal of Navigation, 58:31-45.

Suunto LUMI User Guide, Jun. and Sep. 1997.

Tanigawa et al., Mar. 2008, Drift-free dynamic height sensor using MEMS IMU aided by MEMS pressure sensor, Workshop on Positioning, Navigation and Communication, pp. 191-196.

Thompson et al., (Jan. 1996) "Predicted and measured resting metabolic rate of male and female endurance athletes," Journal of the American Dietetic Association 96(1):30-34.

International Search Report dated Aug. 15, 2008, in related application PCT/IB07/03617.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 4




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14

**MOTION-ACTIVATED DISPLAY OF
MESSAGES ON AN ACTIVITY
MONITORING DEVICE**

RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 15/156,103, filed May 16, 2016, titled "MOTION-ACTIVATED DISPLAY OF MESSAGES ON AN ACTIVITY MONITORING DEVICE," which is a continuation of U.S. patent application Ser. No. 14/580,808, filed Dec. 23, 2014, titled "MOTION-ACTIVATED DISPLAY OF MESSAGES ON AN ACTIVITY MONITORING DEVICE," which is a continuation of U.S. patent application Ser. No. 14/271,389, filed on May 6, 2014, titled "MOTION-ACTIVATED DISPLAY OF MESSAGES ON AN ACTIVITY MONITORING DEVICE," which is a continuation-in-part of U.S. patent application Ser. No. 13/959,714, filed on Aug. 5, 2013, titled "METHODS AND SYSTEMS FOR IDENTIFICATION OF EVENT DATA HAVING COMBINED ACTIVITY AND LOCATION INFORMATION OF PORTABLE MONITORING DEVICES," which is a continuation-in-part of U.S. patent application Ser. No. 13/693,334, filed on Dec. 4, 2012, titled "PORTABLE MONITORING DEVICES AND METHODS OF OPERATING SAME," and a continuation-in-part of U.S. patent application Ser. No. 13/759,485, filed on Feb. 5, 2013, titled "PORTABLE MONITORING DEVICES AND METHODS OF OPERATING SAME."

Each of U.S. patent application Ser. Nos. 13/693,334 and 13/759,485 is a divisional of U.S. patent application Ser. No. 13/667,229, filed on Nov. 2, 2012, titled "PORTABLE MONITORING DEVICES AND METHODS OF OPERATING SAME," which is a divisional of U.S. patent application Ser. No. 13/469,027, filed on May 10, 2012, titled "PORTABLE MONITORING DEVICES AND METHODS OF OPERATING SAME," which is a divisional of U.S. patent application Ser. No. 13/246,843, filed on Sep. 27, 2011, titled "PORTABLE MONITORING DEVICES AND METHODS OF OPERATING SAME," which is a divisional of U.S. patent application Ser. No. 13/156,304, filed on Jun. 8, 2011, titled "Portable Monitoring Devices and Methods of Operating Same," which claims the benefit of and priority to U.S. Provisional Patent Application No. 61/388,595, filed on Sep. 30, 2010, titled "Portable Monitoring Devices and Methods of Operating Same," and the benefit of and priority to U.S. Provisional Patent Application No. 61/390,811, filed on Oct. 7, 2010, titled "Portable Monitoring Devices and Methods of Operating Same." Each of the above-referenced applications is hereby incorporated by reference in its entirety.

FIELD

The present disclosure relates to systems and methods for motion-activated display of messages on an activity monitoring device.

BACKGROUND

In recent years, the need for health and fitness has grown tremendously. The growth has occurred due to a better understanding of the benefits of good fitness to overall health and wellness. Unfortunately, although today's modern culture has brought about many new technologies, such as the Internet, connected devices and computers, people have become less active. Additionally, many office jobs

require people to sit in front of computer screens for long periods of time, which further reduces a person's activity levels. Furthermore, much of today's entertainment options involve viewing multimedia content, computer social networking, and other types of computer involved interfacing. Although such computer activity can be very productive as well as entertaining, such activity tends to reduce a person's overall physical activity.

To provide users concerned with health and fitness a way of measuring or accounting for their activity or lack thereof, fitness activity trackers have recently grown in popularity. Fitness activity trackers are used to measure activity, such as walking, motion, running, sleeping, being inactive, bicycling, exercising on an elliptical trainer, and the like. Typically, the data collected by such devices can be transferred and viewed on a computing device. However, while fitness activity trackers enable many data-intensive features relating to fitness activity, interfacing with a fitness activity tracker can feel sterile and robotic to a user.

It is in this context that embodiments of the invention arise.

SUMMARY

Embodiments described in the present disclosure provide systems, apparatus, computer readable media, and methods for displaying motion-activated messages on a portable activity monitoring device.

In one embodiment, a method for presenting a message on an activity monitoring device is provided, including: storing a plurality of messages to the device; detecting a non-user interactive state of the device; detecting a change of the device from the non-user interactive state to a user-interactive state; in response to detecting the change from the non-user interactive state to the user-interactive state, selecting one of a plurality of messages, and displaying the selected message on the device; wherein selecting one of the plurality of messages is based on one or more of a length of time of the non-user interactive state, a current time of day, a current location of the device, or an activity history associated with a user of the device; wherein the method is executed by at least one processor.

In one embodiment, detecting the non-user interactive state includes detecting a stationary state that is defined by non-movement of the device for a predefined time period; and detecting the change of the device from the non-user interactive state to the user-interactive state includes detecting a movement of the device from the stationary state.

In one embodiment, detecting the change from the non-user interactive state to the user interactive state includes detecting a movement of the device from a first orientation to a second orientation.

In one embodiment, detecting the non-user interactive state includes detecting a charging state of the device; and detecting the change from the non-user interactive state to the user interactive state includes detecting a change of the device from the charging state to a non-charging state.

In one embodiment, detecting the change from the non-user interactive state to the user interactive state includes detecting one or more of a button press or a touchscreen input.

In one embodiment, the device is configured to detect one or more of the following activities by a user: steps taken, energy consumed, elevation gained, active minutes.

In one embodiment, storing the plurality of messages includes identifying the device to a server and downloading the plurality of messages from the server, the server being

configured to access a user account associated with the device, the plurality of messages being selected by the server based on the user account.

In one embodiment, at least one of the plurality of messages is defined based on one or more of a current date, a location of the device, a current season, or a current weather.

In one embodiment, at least one of the plurality of messages is defined based on an activity history of a user associated with the device.

In one embodiment, the activity history is defined by levels of activity associated to specific time periods.

In one embodiment, at least one of the plurality of messages is defined by input received from a secondary user, the secondary user being a member of a social graph of a primary user associated with the device.

In one embodiment, the operations of selecting and displaying are not performed during a time period for which an event is scheduled in a calendar of a user of the device.

In another embodiment, a method for presenting a message on an activity monitoring device is provided, comprising: storing a plurality of messages to the device; detecting a stationary state of the device; detecting a movement of the device from the stationary state; in response to detecting the movement from the stationary state, selecting one of a plurality of messages, and displaying the selected message on the device; wherein at least one of the plurality of messages is defined based on one or more of a current date, a location of the device, a current season, or a current weather; wherein the method is executed by at least one processor.

In one embodiment, detecting the stationary state includes detecting non-movement of the device for a predefined time period.

In one embodiment, storing the plurality of messages includes identifying the device to a server and downloading the plurality of messages from the server, the server being configured to access a user account associated with the device, the plurality of messages being selected by the server based on the user account.

In one embodiment, at least one of the plurality of messages is defined based on an activity history of a user associated with the device.

In one embodiment, the activity history is defined by levels of activity associated to specific time periods.

In one embodiment, at least one of the plurality of messages is defined by input received from a secondary user, the secondary user being a member of a social graph of a primary user associated with the device.

In one embodiment, the operations of selecting and displaying are not performed during a time period for which an event is scheduled in a calendar of a user of the device.

In another embodiment, an activity monitoring device is provided, comprising: a message storage device configured to store a plurality of messages; a motion sensor; a display; logic configured to detect, based on output of the motion sensor, a stationary state of the device and a subsequent movement of the device from the stationary state, and, in response to detecting the movement from the stationary state, select one of the plurality of messages, and display the selected message on the device; wherein at least one of the plurality of messages is defined based on an activity history of a user associated with the device; wherein the method is executed by at least one processor.

In one embodiment, detecting the stationary state includes detecting non-movement of the device for a predefined time period.

In one embodiment, selecting one of the plurality of messages is based on one or more of a length of time of the stationary state, a current time of day, a current location of the device, or an activity history associated with a user of the device.

In one embodiment, at least one of the plurality of messages is defined based on one or more of a current date, a location of the device, a current season, or a current weather.

In one embodiment, the activity history is defined by levels of activity associated to specific time periods.

In one embodiment, at least one of the plurality of messages is defined by input received from a secondary user, the secondary user being a member of a social graph of a primary user associated with the device.

In one embodiment, the activity monitoring device further comprises: logic configured to download the plurality of messages to the message storage, wherein the downloading includes identifying the device to a server, the server being configured to access a user account associated with the device, the plurality of messages being selected by the server based on the user account.

In another embodiment, an activity monitoring device is provided, comprising: a message storage device configured to store a plurality of messages; a motion sensor; a display; logic configured to detect, based on output of the motion sensor, a stationary state of the device and a subsequent movement of the device from the stationary state, and, in response to detecting the movement from the stationary state, select one of the plurality of messages, and display the selected message on the device; wherein at least one of the plurality of messages is defined by input received from a secondary user, the secondary user being a member of a social graph of a primary user associated with the device; wherein the method is executed by at least one processor.

In one embodiment, detecting the stationary state includes detecting non-movement of the device for a predefined time period.

In one embodiment, selecting one of the plurality of messages is based on one or more of a length of time of the stationary state, a current time of day, a current location of the device, or an activity history associated with a user of the device.

In one embodiment, at least one of the plurality of messages is defined based on one or more of a current date, a location of the device, a current season, or a current weather.

In one embodiment, at least one of the plurality of messages is defined based on an activity history of a user associated with the device.

In one embodiment, the activity history is defined by levels of activity associated to specific time periods.

In one embodiment, the activity monitoring device further comprises: logic configured to download the plurality of messages to the message storage, wherein the downloading includes identifying the device to a server, the server being configured to access a user account associated with the device, the plurality of messages being selected by the server based on the user account.

In another embodiment, a method for presenting a message on an activity monitoring device is provided, comprising: storing a plurality of messages to the device; detecting a stationary state of the device; detecting a movement of the device from the stationary state; in response to detecting the movement from the stationary state, selecting one of a plurality of messages, and displaying the selected message on the device; wherein the operations of selecting and

displaying are not performed during a time period for which an event is scheduled in a calendar of a user of the device; wherein the method is executed by at least one processor.

In another embodiment, a method for presenting messages on an activity monitoring device is provided, including the following method operations: receiving a request to synchronize the device with a user account to which the device is associated; retrieving profile data from the user account; selecting one or more messages from a message storage based on the profile data; sending the selected messages to the device, the device configured to display at least one of the selected messages in response to detecting movement of the device from a stationary state.

In one embodiment, the profile data defines one or more of an age, a gender, a location, or a historical activity profile.

In one embodiment, selecting one or more messages is based on one or more of a current date, a current day of the week, a current location of the device, an activity history associated with a user of the device, a current season, a current weather, and social network activity.

In one embodiment, one of the selected messages is defined by a secondary user, the secondary user being a member of a social graph of a primary user associated with the device.

Other aspects will become apparent from the following detailed description, taken in conjunction with the accompanying drawings, illustrating by way of example the principles of embodiments described in the present disclosure.

BRIEF DESCRIPTION OF THE DRAWINGS

Various embodiments described in the present disclosure may best be understood by reference to the following description taken in conjunction with the accompanying drawings.

FIG. 1A shows a block diagram of an activity tracking device, in accordance with one embodiment of the present invention.

FIG. 1B illustrates an example of an activity tracking device including example components utilized for tracking activity and motion of the device, and associated interfaces to a display screen, in accordance with one embodiment of the present invention.

FIG. 2 illustrates an example of activity tracking device in communication with a remote device, in accordance with one embodiment of the present invention.

FIG. 3A illustrates a perspective view of a portable activity monitoring device, in accordance with an embodiment of the invention.

FIG. 3B illustrates a top view of an activity monitoring device, in accordance with an embodiment of the invention.

FIG. 3C illustrates a top view of an activity monitoring device disposed in a carrying case, in accordance with an embodiment of the invention.

FIG. 3D illustrates a side view of an activity monitoring device disposed in a carrying case, in accordance with an embodiment of the invention.

FIG. 4 conceptually illustrates the display of a motion-activated message on a portable activity monitoring device, in accordance with an embodiment of the invention.

FIG. 5A illustrates a cross-section view of a portable activity monitoring device, in accordance with an embodiment of the invention.

FIG. 5B illustrates a cross-section view of a portable activity monitoring device, in accordance with an embodiment of the invention.

FIG. 5C illustrates an activity monitoring device placed upside-down on a substantially horizontal surface, in accordance with an embodiment of the invention.

FIG. 6 illustrates an activity monitoring device in the form of a wearable wrist attachable device, in accordance with an embodiment of the invention.

FIG. 7 conceptually illustrates a process for displaying a motion-activated message on an activity monitoring device, in accordance with an embodiment of the invention.

FIG. 8 conceptually illustrates components of an activity monitoring device, in accordance with an embodiment of the invention.

FIG. 9 conceptually illustrates selection of a motion activated message at an activity monitoring device based on a variety of factors, in accordance with an embodiment of the invention.

FIG. 10 conceptually illustrates a system for determining motion activated messages to be presented on an activity monitoring device, in accordance with an embodiment of the invention.

FIG. 11 conceptually illustrates various factors which may be considered for purposes of selecting one or more messages to be sent to an activity monitoring device for display in response to motion activation, in accordance with an embodiment of the invention.

FIG. 12 illustrates a system for enabling a first user to generate a message that will be displayed to a second user in response to motion of an activity monitoring device of the second user, in accordance with an embodiment of the invention.

FIG. 13 illustrates an interface for accessing activity data associated with the user of an activity monitoring device, in accordance with an embodiment of the invention.

FIG. 14 illustrates an example where various types of activities of users can be captured or collected by activity tracking devices, in accordance with various embodiments of the present invention.

DETAILED DESCRIPTION

Embodiments described in the present disclosure provide systems, apparatus, computer readable media, and methods for displaying motion-activated messages on a portable activity monitoring device.

It should be noted that there are many inventions described and illustrated herein. The present inventions are neither limited to any single aspect nor embodiment thereof, nor to any combinations and/or permutations of such aspects and/or embodiments. Moreover, each of the aspects of the present inventions, and/or embodiments thereof, may be employed alone or in combination with one or more of the other aspects of the present inventions and/or embodiments thereof. For the sake of brevity, many of those permutations and combinations will not be discussed separately herein.

Further, in the course of describing and illustrating the present inventions, various circuitry, architectures, structures, components, functions and/or elements, as well as combinations and/or permutations thereof, are set forth. It should be understood that circuitry, architectures, structures, components, functions and/or elements other than those specifically described and illustrated, are contemplated and are within the scope of the present inventions, as well as combinations and/or permutations thereof.

FIG. 1 shows a block diagram of an activity tracking device **100**, in accordance with one embodiment of the present invention. The activity tracking device **100** is contained in a housing, which may be worn or held by a user.

The housing may be in the form of a wristband, a clip on device, a wearable device, or may be held by the user either in the user's hand or in a pocket or attached to the user's body. The activity tracking device **100** includes device components **102**, which may be in the form of logic, storage, and glue logic, one or more processors, microelectronics, and interfacing circuitry. In one example, the components **102** will include a processor **106**, memory **108**, a wireless transceiver **110**, a user interface **114**, biometric sensors **116**, and environmental sensors **118**.

The environmental sensors **118** may be in the form of motion detecting sensors. In some embodiments, a motion sensor can be one or more of an accelerometer, or a gyroscope, or a rotary encoder, or a calorie measurement sensor, or a heat measurement sensor, or a moisture measurement sensor, or a displacement sensor, or an ultrasonic sensor, or a pedometer, or an altimeter, or a linear motion sensor, or an angular motion sensor, or a multi-axis motion sensor, or a combination thereof. The biometric sensors **116** can be defined to measure physiological characteristics of the user that is using the activity tracking device **100**. The user interface **114** provides a way for communicating with the activity tracking device **100**, in response to user interaction **104**. The user interaction **104** can be in the form of physical contact (e.g., without limitation, tapping, sliding, rubbing, multiple taps, gestures, etc.).

In some embodiments, the user interface **114** is configured to receive user interaction **104** by way of proximity sensors, button presses, touch sensitive screen inputs, graphical user interface inputs, voice inputs, sound inputs, etc. The activity tracking device **100** can communicate with a client and/or server **112** using the wireless transceiver **110**. The wireless transceiver **110** will allow the activity tracking device **100** to communicate using a wireless connection, which is enabled by wireless communication logic. The wireless communication logic can be in the form of a circuit having radio communication capabilities. The radio communication capabilities can be in the form of a Wi-Fi connection, a Bluetooth connection, a low-energy Bluetooth connection, or any other form of wireless tethering or near field communication. In still other embodiments, the activity tracking device **100** can communicate with other computing devices using a wired connection (not shown). As mentioned, the environmental sensors **118** can detect motion of the activity tracking device **100**.

The motion can be activity of the user, such as walking, running, stair climbing, etc. The motion can also be in the form of physical contact received on any surface of the activity tracking device **110**, so long as the environmental sensors **118** can detect such motion from the physical contact. Such physical contact may be in the form of a tap or multiple taps by a finger upon the housing of the activity tracking device **100**.

FIG. 1B illustrates an example of activity tracking device **100** of FIG. 1A, showing some additional example components utilized for tracking activity and motion of the device, and associated interfaces to display screen **122**. In one embodiment, examples of a display screen **122** can include, but are not limited to, liquid crystal display (LCD) screens, light emitting diode (LED) screens, organic light emitting diode (OLED) screens, plasma display screens, etc.

As shown in FIG. 1B, the activity tracking device **100** includes logic **158**. Logic **158** may include activity tracking logic **140**, motion-activated messaging logic **142**, display interface logic **144**, alarm management logic **146**, wireless communication logic **148**, processor **106**, and sensors **156**. Additionally, storage (e.g. memory) **108**, and a battery **154**

can be integrated within the activity tracking device **100**. The activity tracking logic **140** can include logic that is configured to process motion data produced by sensors **156**, so as to quantify the motion and produce identifiable metrics associated with the motion.

Some motions will produce and quantify various types of metrics, such as step count, stairs climbed, distance traveled, very active minutes, calories burned, etc. The physical contact logic **142** can include logic that calculates or determines when particular physical contact can qualify as an input. To qualify as an input, the physical contact detected by sensors **156** should have a particular pattern that is identifiable as input. For example, the input may be pre-defined to be a double tap input, and the physical contact logic **142** can analyze the motion to determine if a double tap indeed occurred in response to analyzing the sensor data produced by sensors **156**.

The display interface logic **144** is configured to interface with the processor and the motion-activated messaging logic to determine when specific messages will be displayed on the display screen **122** of the activity tracking device **100**. The display interface logic **144** can act to turn on the screen, display metric information, display characters or alphanumeric information, display graphical user interface graphics, or combinations thereof. Alarm management logic **146** can function to provide a user interface and settings for managing and receiving input from a user to set an alarm. The alarm management logic can interface with a timekeeping module (e.g., clock, calendar, time zone, etc.), and can trigger the activation of an alarm. The alarm can be in the form of an audible alarm or a non-audible alarm.

A non-audible alarm can provide such alarm by way of a vibration. The vibration can be produced by a motor integrated in the activity tracking device **100**. The vibration can be defined to include various vibration patterns, intensities, and custom set patterns. The vibration produced by the motor or motors of the activity tracking device **100** can be managed by the alarm management logic **146** in conjunction with processing by the processor **106**. The wireless communication logic **148** is configured for communication of the activity tracking device with another computing device by way of a wireless signal. The wireless signal can be in the form of a radio signal. As noted above, the radio signal can be in the form of a Wi-Fi signal, a Bluetooth signal, a low energy Bluetooth signal, or combinations thereof. The wireless communication logic can interface with the processor **106**, storage **108** and battery **154** of device **100**, for transferring activity data, which may be in the form of motion data or processed motion data, stored in the storage **108** to the computing device.

In one embodiment, processor **106** functions in conjunction with the various logic components **140**, **142**, **144**, **146**, and **148**. The processor **106** can, in one embodiment, provide the functionality of any one or all of the logic components. In other embodiments, multiple chips can be used to separate the processing performed by any one of the logic components and the processor **106**. Sensors **156** can communicate via a bus with the processor **106** and/or the logic components. The storage **108** is also in communication with the bus for providing storage of the motion data processed or tracked by the activity tracking device **100**. Battery **154** is provided for providing power to the activity tracking device **100**.

FIG. 2 illustrates an example of activity tracking device **100** in communication with a remote device **200**. Remote device **200** is a computing device that is capable of communicating wirelessly with activity tracking device **100** and

with the Internet 160. Remote device 200 can support installation and execution of applications. Such applications can include an activity tracking application 202. Activity tracking application 202 can be downloaded from a server. The server can be a specialized server or a server that provides applications to devices, such as an application store. Once the activity tracking application 202 is installed in the remote device 200, the remote device 200 can communicate or be set to communicate with activity tracking device 100 (Device A). The remote device 200 can be a smartphone, a handheld computer, a tablet computer, a laptop computer, a desktop computer, or any other computing device capable of wirelessly interfacing with Device A and the Internet.

In one embodiment, remote device 200 communicates with activity tracking device 100 over a Bluetooth connection. In one embodiment, the Bluetooth connection is a low energy Bluetooth connection (e.g., Bluetooth LE, BLE, or Bluetooth Smart). Low energy Bluetooth is configured for providing low power consumption relative to standard Bluetooth circuitry. Low energy Bluetooth uses, in one embodiment, a 2.4 GHz radio frequency, which allows for dual mode devices to share a single radio antenna. In one embodiment, low energy Bluetooth connections can function at distances up to 50 meters, with over the air data rates ranging between 1-3 megabits (Mb) per second. In one embodiment, a proximity distance for communication can be defined by the particular wireless link, and is not tied to any specific standard. It should be understood that the proximity distance limitation will change in accordance with changes to existing standards and in view of future standards and/or circuitry and capabilities.

Remote device 200 can also communicate with the Internet 160 using an Internet connection. The Internet connection of the remote device 200 can include cellular connections, wireless connections such as Wi-Fi, and combinations thereof (such as connections to switches between different types of connection links). The remote device, as mentioned above, can be a smartphone or tablet computer, or any other type of computing device having access to the Internet and with capabilities for communicating with the activity tracking device 100.

A server 220 is also provided, which is interfaced with the Internet 160. The server 220 can include a number of applications that service the activity tracking device 100, and the associated users of the activity tracking device 100 by way of user accounts. For example, the server 220 can include an activity management application 224. The activity management application 224 can include logic for providing access to various devices 100, which are associated with user accounts managed by server 220. Server 220 can include storage 226 that includes various user profiles associated with the various user accounts. The user account 228_a for user A and the user account 228_n for user N are shown to include various information.

The information can include, without limitation, data associated with motion-activated messaging 230, user data, etc. As will be described in greater detail below, the motion-activated messaging data 230 includes information regarding a user's preferences, settings, and configurations which are settable by the user or set by default at the server 220 when accessing a respective user account. The storage 226 will include any number of user profiles, depending on the number of registered users having user accounts for their respective activity tracking devices. It should also be noted that a single user account can have various or multiple devices associated therewith, and the multiple devices can

be individually customized, managed and accessed by a user. In one embodiment, the server 220 provides access to a user to view the user data 232 associated with activity tracking device.

The data viewable by the user includes the tracked motion data, which is processed to identify a plurality of metrics associated with the motion data. The metrics are shown in various graphical user interfaces of a website enabled by the server 220. The website can include various pages with graphical user interfaces for rendering and displaying the various metrics for view by the user associated with the user account. In one embodiment, the website can also include interfaces that allow for data entry and configuration by the user.

FIG. 3A illustrates a perspective view of a portable activity monitoring device, in accordance with an embodiment of the invention. The activity monitoring device 300 is shown to include a display 302 for displaying various data such as text or images. In one embodiment, the display 302 can be configured to display video. In the illustrated embodiment, the display 302 is currently displaying a step count, indicating the number of steps taken that have been detected by the activity monitoring device 300 over some defined time period (e.g. the current day or week). The activity monitoring device 300 is also shown to include a button 304. In one embodiment, the button 304 may be pressed to cycle the display of various fitness statistics which have been stored on the device 300. By way of example, these may include a number of steps taken, a number of floors climbed, distance traveled, a number of active minutes, a number of calories burned, an activity amount remaining in order to reach a particular goal, etc. Additionally, the button 304 may be pressed to turn on/off the display 302.

In some embodiments, additional information that may be of use to a user may be accessed by pressing the button 304, such as a current date or time, a battery charge level, a date/time of the device's last data sync (i.e. transfer of data from the activity monitoring device 300 to an external device), a pairing mode for pairing the activity monitoring device to an external device, an option to reset a fitness activity counter, an option to turn the device off, etc. Additionally, it should be appreciated that the button may be pressed in various ways to facilitate access to various features. By way of example, the button may be pressed once, pressed and held, pressed twice in rapid succession, etc. For example, pressing and holding the button 304 may turn the device 300 on or off.

FIG. 3B illustrates a top view of the activity monitoring device 300, in accordance with an embodiment of the invention. In the illustrated embodiment, a number of floors climbed is currently displayed on the display 302 of the activity monitoring device 300.

FIG. 3C illustrates a top view of the activity monitoring device 300 disposed in a carrying case 306, in accordance with an embodiment of the invention. The carrying case 306 defines a sheath 308 which extends around the sides and back of the activity monitoring device 300 so as to secure it in the carrying case 306, while leaving exposed the top surface of the activity monitoring device 300.

FIG. 3D illustrates a side view of the activity monitoring device 300 disposed in carrying case 306. As can be seen, the carrying case 306 includes an extension 310 which extends adjacent to the sheath 308, thus allowing the carrying case 306 to function as a clip, so that the device 300 and carrying case 306 can be attached to a user (e.g. attached to the user's clothing).

FIG. 4 conceptually illustrates the display of a motion-activated message on a portable activity monitoring device, in accordance with an embodiment of the invention. In one embodiment, a message can be displayed on the display 302 of the activity monitoring device 300 in response to detection of a movement of the device 300 from a stationary position.

The stationary position can be defined to require the device to be maintained in a non-moving or stationary state for a predefined length of time. For example, in one embodiment, the stationary position requires the device to be not moving for approximately two to three seconds. In other embodiments, the stationary position is defined to require the device to be not moving for any specified length of time.

Furthermore, it will be appreciated that the stationary state may be defined by the absence of movements exceeding a predefined threshold for a specified length of time. It should be appreciated that the specific types of movements and the predefined threshold can be defined in various ways. For example, in one embodiment, the movement is defined by the sensor output of motion-sensitive hardware included in the activity monitoring device, such as accelerometers, gravitometers, gyroscopes, etc., and the predefined threshold may be defined by a specific magnitude of a given sensor output (e.g. detected acceleration of the device exceeds an acceleration threshold). It will be appreciated that a combination of sensor outputs and corresponding thresholds can be considered. In one embodiment, a weighted combination (e.g., a weighted sum) of motion sensor outputs is defined and compared against a predefined threshold. In this manner, certain types of movements may be prioritized over others for purposes of identifying movement from a stationary state. For example, in one embodiment, translational movement of the device is prioritized over rotational movement, such that sensor outputs which are indicative of translational movement are more highly weighted than sensor outputs which are indicative of rotational movement.

In other embodiments, the detected movement and corresponding predefined threshold can be defined based on particular types of movements which are determined or derived from motion sensor output. For example, in one embodiment, a distance moved is determined for the device, and the device is defined to be in a stationary state so long as the distance moved by the device does not exceed a predefined distance threshold. In one embodiment, the detection of the distance moved is reset following a period of zero movement. In another embodiment, the detection of the distance moved is cumulative. By defining the stationary state based on the absence of movement exceeding a predefined threshold, false positive movements can be avoided, so that motion-activated messages are not displayed when the movements are of low significance or unlikely to be the result of intentional movement of the device warranting display of a motion-activated message.

Additionally, the stationary position can be defined to require not only a lack of movement of the activity monitoring device 300, but also a specific orientation of the activity monitoring device 300 in three-dimensional space. For example, in one embodiment, the device 300 is required to be in a substantially horizontal orientation, that is, the orientation that the device 300 has when it is laying on a substantially horizontal flat surface, with the top side of the device 300 (the side on which the display 302 may be viewed by a user) facing upward.

Thus, in accordance with the foregoing, a motion-activated message can be displayed when the following events are detected: non-movement of the device; orientation of the

activity monitoring device in a specified orientation; maintenance of the non-movement and specified orientation for a minimum specified length of time; and, following the maintenance of the non-movement and specified orientation, movement of the activity monitoring device (e.g. translational and/or rotational movement). The completion of the preceding events can be configured to trigger presentation of a motion-activated message on the display 302 of the activity monitoring device 300.

As shown with continued reference to FIG. 4, the activity monitoring device 300 is detected to be in a stationary position for at least a predefined length of time, following which the device 300 is picked up by a hand 400 of a user. The detection of this movement of the device 300 triggers the presentation of a motion-activated message (“Hi there!”) on the display 302. Upon pressing the button 304 of the activity monitoring device 300, the motion-activated message ceases to be displayed; and in one embodiment, a fitness activity statistic, such as the user’s step count, is presented on the display 302.

FIG. 5A illustrates a cross-section view of a portable activity monitoring device, in accordance with an embodiment of the invention. As shown, the activity monitoring device 500 is held in a case 502, which includes a sheath portion 504 for securing the device 500 and a clip extension 506 that abuts the sheath portion 504 to enable the case 502 to be clipped to an object, such as an article of clothing. The activity monitoring device and case may be similar to or the same as that described with reference to FIGS. 3A, 3B, 3C, and 3D. The activity monitoring device 500 includes a button 508, which is disposed on the top surface of the device 500. In the illustrated embodiment, the case 502 is shown resting on a substantially horizontal planar surface 510 in an orientation wherein the outward-facing side of the clip extension 506 faces downward and touches the surface 510. As such, the activity monitoring device 500 is therefore oriented with its top surface facing upward.

It should be appreciated that the orientation of the device 500 may be substantially horizontal, or may have a specific tilt depending upon the specific configuration of the case 502, which determines how the device 500 will be oriented when the case 502 is resting on the surface 510 as shown. For example, assuming that the activity monitoring device 500 has a shape that is elongated in a (lengthwise) direction that is substantially orthogonal to the cross-sectional plane shown in FIG. 5A, then the activity monitoring device 500 may be substantially horizontal along its lengthwise direction, or may have a specific lengthwise tilt, when the case is situated on the surface 510 as shown.

It will be appreciated that the configuration of the case 502 in combination with its particular orientation on the surface 510 will determine the orientation of the activity monitoring device 500. In one embodiment, the specific orientation of the activity monitoring device 500 when positioned as shown in FIG. 5A can be detected. That is, the device 500 can be configured to detect when it is positioned so as to have such an orientation, and upon maintenance of the orientation for some predefined time period, the device 500 can be configured to trigger display of a message when the device 500 is moved again.

FIG. 5B illustrates a cross-section view of a portable activity monitoring device, in accordance with an embodiment of the invention. In the illustrated embodiment, the case 502 is shown resting on its side on the surface 510, such that side portions of the sheath 504 and extension clip 506 contact the surface 510. In this configuration as shown, the activity monitoring device 500 is also tilted on its (length-

wise) side by an angle θ , measured relative to a direction substantially orthogonal to the top surface of the device 500. This tilted configuration of the device 500 resulting from the configuration of the case 502 represents a stable orientation of the case 502 and device 500. That is, it is possible for a user to place the case 502 and device 500 on a substantially horizontal surface in a tilted orientation that will be stable over time.

As such, the orientation of the device in the illustrated embodiment can be detected. When the orientation is detected for a minimum predefined time, subsequent movement of the device from such an orientation can be configured to trigger presentation of a motion-activated message on the display of the device 500.

FIG. 5C illustrates the activity monitoring device 500 placed upside-down on the substantially horizontal surface 510. In this orientation, the top surface of the activity monitoring device faces downward towards the surface 510. This orientation of the device 500 is another stable orientation, and can be detected by the device 500. As has been discussed, when the orientation is detected as being maintained for a predefined amount of time, subsequent movement of the device 500 from the detected orientation can be configured to trigger display of a message on the display of the device 500.

Though reference has been made to an activity monitoring device having a generally elongated shape, it should be appreciated that this form factor for an activity monitoring device is provided by way of example, and not by way of limitation. For example, FIG. 6 illustrates an activity monitoring device in the form of a wearable wrist attachable device, in accordance with an embodiment of the invention. The activity monitoring device 600 includes a display 602 for displaying various kinds of information, including motion-activated messages in accordance with various embodiments described herein.

In one embodiment, the device 600 can be configured to display a motion-activated message on the display 602 when the device 600 is moved from a stable stationary position in which the device 600 lays on its side on a substantially horizontal surface. In the stationary position, an outer edge of the band of the wrist attachable device 600 will contact the surface on which the device 600 rests, and the display 602 will have a sideways orientation. It will be appreciated that the device 600 has two such possible stable stationary positions, one in which the device rests on a right side of the display, and another in which the device rests on the left side of the display. Movement from these stable stationary positions may trigger presentation of a motion-activated message on the display 602.

In other embodiments, a recognizable motion can be detected and may be configured to trigger display of a motion-activated message. For example, with continued reference to the activity monitoring device 600, a detected movement of the device 600 indicating that a user wearing the device has raised their arm so as to view the display 602 may be configured to trigger display of a motion-activated message. Such a motion of the device 600 may be that resulting from simultaneous lifting and pronation of the user's forearm, by way of example. It should be appreciated that a similar concept can be extended to other types of motions and other form factors for the activity monitoring device, wherein an identifiable motion of the activity monitoring device triggers display of a motion-activated message.

FIG. 7 conceptually illustrates a process for displaying a motion-activated message on an activity monitoring device,

in accordance with an embodiment of the invention. In one embodiment, a plurality of motion-activated messages 700 are stored on the activity monitoring device 706. In the illustrated embodiment, the messages 700 include various Messages A, B, C, etc. Each message defines a portion of text for display on the display 708 of the activity monitoring device 706. By way of example, Message A is defined by the text "Hi there!"; Message B is defined by the text "Walk me"; etc.

To determine which one of the messages 700 to display, the messages 700 may be ranked (ref 702) based on various factors, including without limitation, time/date, prior display, activity/inactivity of the user as detected by the device 706, etc. Additional exemplary factors which may be utilized to rank, or otherwise determine selection from, a plurality of messages, are discussed in further detail below. As indicated at ref. 704, one of the messages is selected for display, based at least in part on the determined ranking. The selected message is displayed on the display 708 of the activity monitoring device 706. It will be appreciated that the presentation of the selected message may be scrolled across the display 708 if the length of the selected message is too long to permit the entirety of the selected message to be displayed simultaneously.

FIG. 8 conceptually illustrates components of an activity monitoring device, in accordance with an embodiment of the invention. As shown, the activity monitoring device 800 is defined to include motion sensors 806, which may include, without limitation, accelerometers, gyroscopes, magnetometers, motion sensitive contact switches, or other motion-sensing hardware. Additionally, the device 800 can include other environmental or biometric sensors 807, as discussed elsewhere herein. An activity processor 808 processes sensor output data generated by the sensors 806 and 807 to determine activity by the user, such as a number of steps taken, changes in altitude, periods of activity or inactivity, calories burned, etc. These activity data are stored in an activity data storage 810. It will be appreciated that raw sensor data can also be stored for later processing.

The device 800 further includes a motion activated message data storage 812 which contains message data defining various messages that can be presented based on motion of the device following a detected stationary state. Motion activated message display logic 814 is configured to determine when to display a motion activated message as well as the particular message that is displayed. The motion activated message display logic 814 includes activation logic 816. In one embodiment, the activation logic 816 is configured to identify, based on sensor data received from the motion sensors 806, when the device 800 is resting in a predefined orientation. As has been discussed, the predefined orientation may correspond to various possible resting orientations of the device 800 when it is placed on a substantially horizontal flat surface.

The activation logic 816 determines when the device 800 is continuously oriented in the predefined orientation for a specified minimum period of time. By way of example, the specified minimum period of time may be defined in the range of 2 to 5 seconds, 5 to 10 seconds, 10 seconds to 1 min, 1 to 10 min, or any other defined period of time. In one embodiment, the specified minimum period of time may be determined based on a user defined setting. In yet another embodiment, the specified minimum period of time may vary depending upon various factors, such as time of day, the amount of activity or inactivity recently associated with the device 800, etc.

When the activation logic **816** determines that the device **800** has continuously maintained the predefined orientation for the requisite minimum period of time, then the activation logic **816** is configured to detect a subsequent movement of the device **800** from the predefined orientation, based on sensor data from the motion sensors **806**. Upon such detection of movement, the activation logic is configured to trigger selection and display of a motion activated message on the device **800**.

In various embodiments, it will be appreciated that the activation logic **816** can be configured to consider other factors or purposes of determining when to trigger selection and display of a motion activated message. For example, a user interacting with the device **800** may place the device **800** on a flat surface while its display is still active. A timer can be configured to automatically turn off the display after a given amount of time in which interactivity with the display is not detected (e.g. a button on the device **800** which controls the operation of the display is not pressed). Thus in one embodiment, the activation logic **816** is configured to determine a current active or inactive state of the display **830**, and does not commence its procedure for determining when to trigger the motion activated message unless the display is currently inactive or turned off

In another embodiment, the activation logic **816** will not commence its activation procedure unless ambient light levels detected by the device **800** are above a predefined threshold. This may prevent the unnecessary display of a motion activated message when the device **800** is in a dark location, such as a pocket of a user, or a purse or bag, by way of example.

In another embodiment, the activation logic **816** will not trigger a motion-activated message during a time period for which an event is scheduled in a calendar of the user, such as a meeting or other type of event. This will prevent the display of motion-activated messages when the user is scheduled, and therefore expected, to be preoccupied with some activity. In one embodiment, this is facilitated via synchronization operations between the device **800** and another computing device which includes a calendar for the user, such as a smart phone or computer. During synchronization operations, the calendar of the user (on the additional device to which the device **800** syncs) is accessed to determine event scheduling information. This information defines time periods for events which have been scheduled on the calendar. At least the start and end times for the scheduled events can be transmitted to the device **800** and utilized to define time periods during which motion-activated messages will not be displayed.

In another embodiment, the activation logic **816** is configured to not trigger a motion-activated message when it is determined that the user is engaged in an activity during which it is expected that the user will be unavailable to view a motion-activated message. For example, in one embodiment, if it is determined that the device is currently moving in a motor vehicle such as a car (e.g. based on GPS data and/or motion data), the activation logic **816** may be configured to not trigger a motion-activated message.

When the activation logic **816** determines that a motion activated message is to be displayed, as discussed above, then selection logic **818** is engaged to select a message from the message data storage **812** for presentation. The selection logic **818** can be configured to select the message based on a variety of factors as discussed elsewhere herein. By way of example, the device **800** includes a clock **822**, which provides a current date and time, which may be utilized by the selection logic **818** to determine which message to

present. In one embodiment, the selection logic **818** determines a ranked order for a plurality of messages stored in the message data storage **812**, and identifies a specific message for presentation based on the ranked order. The motion activated message display logic **814** is configured to render the selected message on the display **830** of the device **800** via a display controller **828**.

The motion activated message display logic **814** further includes deactivation logic **820** which is configured to deactivate the operation of the display logic **814** under certain conditions. For example, when a user presses a button **824** to interact with the device **800**, this may trigger deactivation logic **822** to deactivate the message display logic **814**. As discussed herein, input received from the button **824** may trigger the display of various activity metrics by metrics display logic **826**. Thus, pressing the button **824** will cause any motion activated message that is currently displayed on the display **830** to be replaced by various metrics or other information, the display of which is triggered by a button press.

In other embodiments, the display of a motion activated message can be terminated in response to other types of interaction or the lack thereof. For example, a motion activated message may be configured to be displayed for a limited amount of time, whereupon if no additional interaction with the device **800** is detected, then rendering of the motion activated message is terminated, and the display is turned off. In such an embodiment, the deactivation logic **820** can be configured to include a timer that is activated when a motion activated message is rendered by the display logic **814**. Upon the expiration of the timer, then the display of the motion activated message is stopped. In a related embodiment, upon the expiration of a limited amount of time, the display of the motion activated message is ended and replaced with display of other information automatically, such as a current time, activity metric, or any other information which the device **800** may be configured to display.

In another embodiment, the display of a motion activated message is terminated upon the detection of a specific kind of physical interaction with the device **800**, e.g. shaking the device, tapping the device, touching or swiping a touchscreen on the device, etc. Additionally, these types of physical interactions with the device **800** can be configured to trigger display of other information replacing the previously displayed motion activated message on the display **830**.

The device **800** also includes synchronization logic **804** which is configured to handle synchronization of data with another device or with a remote server or cloud-based service. The activity monitoring device **800** is configured to wirelessly transmit and receive data, with wireless communications being handled by a wireless controller **802**. Synchronization logic **804** is configured to upload activity data from the activity data storage **810**. The synchronization logic **804** is also configured to download motion activated message data from a remote storage location to the motion activated message data storage **812**. In this manner, the synchronization logic **84** updates the messages which are stored in the message data storage **812**. It should be appreciated that the synchronization logic **804** may also be configured to effect deletion of messages from the motion activated message data storage **812**.

FIG. 9 conceptually illustrates selection of a motion activated message at an activity monitoring device based on a variety of factors, in accordance with an embodiment of the invention. In the illustrated embodiment, a device motion activated message selection engine **900** is shown.

The message selection engine **900** is configured to select a message for display on an activity monitoring device (ref. **902**) in response to detection of movement of the device from a predefined stationary orientation.

In one embodiment, a message may be selected based on a current time of day. For example, a message such as “good morning” may be selected when the current time is in the morning. A message may also be selected based on the current date or day of the week. For example, a message such as “TGIF” may be selected on a Friday. In another embodiment, a message may be selected based on a current location of the device. For example, if the user travels to a new location such as the city of San Francisco, then a message may be configured to welcome the user to the new location, such as “welcome to San Francisco.”

In one embodiment, a message may be selected based on the activity of a user as determined via the activity monitoring device. For example, if the user has recently been determined to have taken a certain number of steps, then a message may be selected congratulating the user on having taken that many steps. In message may also be selected based on the inactivity of the user is determined by the activity monitoring device. For example, if the device has been resting without movement for an extended period of time, then a message may be selected that is configured to encourage the user to engage in fitness activity or otherwise engage with the device, such as “walk me.”

In one embodiment, a message may be selected at random, or based on a random number. In another embodiment, a message may be selected based on prior message selection, so as to avoid displaying the same message to the user in a relatively short time span.

In some embodiments, a message may be selected for display based on various sensed conditions. For example, a message may be selected based on an environmental condition which the activity monitoring device is capable of detecting, such as ambient light, temperature, ambient pressure, altitude, humidity, ambient sound, orientation, etc.

FIG. 10 conceptually illustrates a system for determining motion activated messages to be presented on an activity monitoring device, in accordance with an embodiment of the invention. An activity monitoring device **1000** is shown to include synchronization logic **1002**. The synchronization logic **1002** includes a message update module **1004** that is configured to update motion activated message data that is stored in a motion activated message data storage **1008**. The synchronization logic **1002** further includes an activity data update module **1006** that is configured to manage activity data stored in the activity data storage **1010**, including uploading of activity data as well as deletion of activity data in accordance with the embodiments described herein.

The activity monitoring device **1000** communicates to a user device **1020**, that in turn communicates with a remote server **1050** via a network **1040**. The user device **1020** may be a mobile device or any other type of computing device capable of performing the functionality described herein. In the illustrated embodiment, the user device **1020** includes a calendar module **1022** that is configured to maintain a personal calendar of the user. The calendar may be synchronized to a cloud-based calendar service **1074**, which may be accessed via a calendar API **1076**. Additionally, the user device **1020** includes a GPS module **1024** that is configured to determine a geo-location of the user device **1020**.

The user device **1020** includes an application **1026**, which may be a browser or a dedicated application that is configured to interface with the activity monitoring device **1000** as well as the server **1050**. The application **1026** defines a

graphical user interface **1028** through which the user may control the operation of the application **1026**. The application **1026** further defines an activity analyzer **1030** which is configured to analyze activity data received from the activity monitoring device **1000**. A synchronization handler **1032** is configured to handle synchronization operations between the activity monitoring device, the user device **1020**, and cloud-based data storage accessed via the server **1050**. For example, the sync handler **1032** may communicate with the activity data update module **1006** defined by the sync logic **1002** of the activity monitoring device **1000** in order to facilitate uploading of activity data from the activity monitoring device **1000** to the user device **1020**. The uploaded activity data may be further processed by the activity analyzer **1030**, and/or may be transmitted via network **1040** to an activity data manager **1052** of the server **1050**, for storage in a cloud-based activity data storage **1054**. An activity analyzer **1056** of the cloud-based system is configured to analyze the activity data stored in the activity data **1054**, and may generate additional activity data that are also stored in the activity data storage **1054**.

The server includes a motion-activated message synchronization module that is configured to select messages and download them to the activity monitoring device. The downloading of selected messages is mediated by the sync handler **1032** of the user device **1020**, with which a message update module **1004** of the activity monitoring device **1000** communicates to receive message data for storage in the message data storage **1008**. In other words, the message data is transferred from the server **1050** to the user device **1020**, and the user device **1020** in turn transfers the message data to the activity monitoring device for storage. In this manner, the motion activated message data on the activity monitoring device is updated by the remote server **1050**. It should be appreciated that the transfers of the message data may occur in immediate succession when the user device **1020** is simultaneously connected to both the server **1050** and the activity monitoring device **1000**. However, when the user device **1020** is not connected to the activity monitoring device **1000**, then message data may be transferred by the server **1050** to the user device **1020** and temporarily stored at the user device **1020** until the activity monitoring device is connected to the user device **1020**, at which time the message data may then be transferred to the activity monitoring device **1000**.

In addition to transfers of message data defining specific motion activated messages to the activity monitoring device **1000**, the motion activated message synchronization module **1058** of the server **1050** may additionally be configured to effect other changes to the message data stored at the activity monitoring device **1000**. For example, commands or updates may be sent to the activity monitoring device **1002** to manage the message data stored in the message data storage **1008**. Examples of such commands or updates include, without limitation, deletion of messages, modification of messages, changes to metadata associated with messages, etc.

In the illustrated embodiment, the message synchronization module **1058** includes a message selection engine **1060** that is configured to select one or more messages to be transferred to the activity monitoring device **1000**. A plurality of messages that are available for selection are stored in a message data storage **1062**. A message manager **1064** is provided for managing the messages stored in the message data storage **1062**. In one embodiment, the message manager **1064** provides an interface whereby an editor may create new messages, or edit or delete existing messages.

The selection engine **1060** is configured to select messages based on a variety of factors. By way of example, selection engine **1060** can be configured to identify selected messages based on activity data that is associated with the activity monitoring device **1000**, as stored in the activity data storage **1054**. Such activity data can include various fitness metrics and other types of data which are determined based on the monitored activity of the activity monitoring device **1000**. The selection engine **1060** may also select messages based on the user profile associated with a user of the activity monitoring device **1000**. In the illustrated embodiment, the user profile may be defined in a profile data storage **1066**. By way of example and not limitation, a user profile may define various pieces of information about a given user, such as the user's age, gender, residence, height, weight, preferences, etc. The user profile can include a historical activity profile of the user based on the user's activity data and fitness metrics. In this manner, different messages may be selected based on, for example, whether the user is historically more sedentary or more active.

It will be appreciated that activity data may be defined by values, levels, metrics, etc. of particular activities which are associated to specific times or time periods. The activity data which are recorded over time can therefore define an activity history for a given user. It is noted that the granularity of such time associations may vary in accordance with the specific activity being tracked or other considerations such as a predefined goal or, a predefined threshold for defining or triggering a motion-activated message. As one example of an activity whose levels may be defined with varying time-associated granularity, consider that a user's step count might be determined on a per minute basis, per hour, per day, per week, per month, etc. Furthermore, a predefined threshold might be defined so that a motion-activated message is defined or triggered (i.e. selected or cued for motion-activated display) when the user achieves a given number of steps in a given time period (e.g. x number of steps in a day). As another example, a user's heart rate may be monitored over the course of a given time period, and a corresponding motion-activated message can be defined or triggered based on the user's heart rate data. It should be understood that similar concepts may be applied for any other activity discussed herein.

Thus in some embodiments, an activity history for a given user can define levels of activity that are associated to specific time periods, as determined from data recorded by a given activity tracking device to which the user is associated. Motion-activated messages can be defined and/or triggered based on the activity history of the user. In this manner, the motion-activated messages that are presented to the user are customized to the user's activity history, thereby providing a personalized experience the user.

In one embodiment, the message selection engine **1060** can be configured to select messages based on nutrition data which is stored in a nutrition data storage **1080**. The nutrition data for a given user can include information about the user's nutrition, such as meal information including foods/drinks that the user has consumed and the times they were ingested, diet plan information, etc.

In one embodiment, the selection engine **1060** is configured to identify selected messages for transfer to the activity monitoring device **1000** based on current or predicted weather information. The weather information can be obtained from a weather service **1068**, via an API **1070** according to which weather information is made available.

In one embodiment, the message selection engine **1060** is configured to identify selected messages based on social

network data that is associated with the user of the activity monitoring device **1000**. In the illustrated embodiment, the social network data can be obtained from a social network service provider **1072** via an API **1074**. By way of example, social network data can include activity of the user on the social network, such as posts or comments, as well as information relating to the social graph of the user on the social network, such as identified friends of the user from the user social graph and their activity on the social network.

In one embodiment, the selection engine **1060** is configured to select messages based on calendar events that are associated with the user of the activity monitoring device **1000**. In order to determine calendar events, a calendar service **1076** may be accessed via an API **1078**. The calendar service **1076** is configured to maintain a calendar associated with the user that defines various events and their dates/times.

Though in the foregoing description, the activity monitoring device **1000** is shown to communicate with a user device **1020**, which in turn communicates with the server **1050** over a network **1040**, in other embodiments, some or all of the functionality defined by the user device **1020** may be included in or otherwise performed by the activity monitoring device **1000**. Thus, in such embodiments, the activity monitoring device itself may communicate directly with the server **1050** over the network **1040** in order to perform data synchronization and other operations such as downloading selected messages to the activity monitoring device **1000**, as has been described.

FIG. **11** conceptually illustrates various factors which may be considered for purposes of selecting one or more messages to be sent to an activity monitoring device for display in response to motion activation, in accordance with an embodiment of the invention. In the illustrated embodiment, a server-side motion activated message selection engine **1100** is configured to select messages based on various factors or inputs. The selected messages are sent to an activity monitoring device (ref **1102**).

In one embodiment, the selection engine **1100** is configured to identify messages for selection based on demographic data associated with a user of the activity monitoring device, such as age, gender, ethnicity, height, weight, medical conditions, etc. For example, age-appropriate messages may be selected based on the user's age. In one embodiment, the selection engine **1100** is configured to select messages based on an identified location of the user. The location can be defined to varying degrees of specificity, such as by identifying a country, state, city, address, landmark, business, GPS coordinates, or other information which defines a location of the user. The location can be a current location of the user, or another location associated with the user, such as a residence or work address. By way of example, messages in the appropriate language may be provided based on location information. Or messages may reflect aspects of the locality of the user. For example, if the user is determined to be located near a park, then a message may be selected which encourage the user to go for a walk or run in the park.

In one embodiment, the selection engine **1100** is configured to select messages based on preferences or settings which are associated to the user. These may include, without limitation, fitness metric preferences such as which fitness metrics the user prefers, activity interests associated with the user, etc.

In one embodiment, the selection engine **1100** is configured to select messages based on fitness-related goals which may be user-defined goals or system-identified milestones. For example, a message may congratulate the user on

achieving a goal, or encourage a user to perform activity in furtherance of a goal/milestone. Examples of goals include, without limitation, walking a certain number of steps, burning a certain number of calories, accruing a certain number of active minutes, climbing a certain height (possibly represented by an equivalent number of stairs/floors), etc.

In one embodiment, the selection engine **1100** is configured to select messages based on events stored in a calendar associated with the user. For example, such a message may be configured to remind the user about an upcoming calendar event, ask the user about a current or prior event, etc.

In one embodiment, the selection engine **1100** is configured to select messages based on activity or inactivity of the user, as detected by the activity monitoring device. For example, if the user has been very active recently, then a selected message may congratulate the user on the activity, encourage the user to get rest/sleep, or encourage the user to eat appropriately. If the user has been rather inactive recently, then a selected message may encourage the user to engage in physical fitness activity.

In one embodiment, the selection engine **1100** is configured to select messages based on the current or predicted weather. For example, a message may recommend clothing or accessories which are appropriate for the day's weather (e.g. hat/sunglasses for sunshine, umbrella for rain, gloves/scarf for cold weather), recommend activities based on the weather (e.g. "it's a nice day for a walk"), etc.

In one embodiment, the selection engine **1100** is configured to select messages based on the current season. For example, during particular holidays or seasons, messages may be selected which are indicative of those holidays or seasons (e.g. "happy labor day"; "spring is in the air").

In one embodiment, the selection engine **1100** is configured to select messages based on events occurring. For example, a message may ask or inform a user about an upcoming fitness-related event (e.g. a 10K run), or other types of events (e.g. concerts, sporting events, festivals, shows, etc.).

In one embodiment, the selection engine **1100** is configured to select messages based on the current date or time, day of the week, month, or other indicator of time.

In one embodiment, the selection engine **1100** is configured to select messages based on previously selected messages which have been transferred to the activity monitoring device. For example, messages which have been recently transferred may not be selected so as to avoid duplication.

In one embodiment, the selection engine **1100** is configured to select messages based on nutrition data associated with the user.

In one embodiment, the selection engine **1100** is configured to select messages based on data or activity of the user on a social network, or that of members of the user's social graph. For example, social activity of the user may indicate an interest in basketball, and a message relating to basketball may be selected.

In one embodiment, a message may be generated by a secondary user, to be presented as a motion-activated message on the primary user's activity monitoring device, as discussed in further detail below. Such a message may be prioritized for transmission to the primary user's activity monitoring device.

It will be appreciated that the foregoing examples of factors according to which messages may be selected for transmission to an activity monitoring device, are provided by way of example and not by way of limitation. In other

embodiments, additional factors may be considered by a message selection engine in accordance with the principles described herein.

FIG. **12** illustrates a system for enabling a first user to generate a message that will be displayed to a second user in response to motion of an activity monitoring device of the second user, in accordance with an embodiment of the invention. In the illustrated embodiment, a user **1200** interacts with the user device **1202**. The user device **1202** can be any computing device, and as shown, includes an application or browser **1204** that is configured to access a user account which may define activity information as well as social network information associated with the user **1200**. For purposes of illustration, a web browser type implementation is described, though it should be appreciated that in other embodiments, a dedicated application can be configured to enable the functionality described herein.

The browser **1204** communicates over a network **1208** to a Web server **1210**. The Web server **1210** includes an authentication module **1212** that is configured to authenticate the user **1200** to their account. A request handler **1214** is provided for servicing requests from the browser **1204**. Activity module **1216** is provided for accessing and managing activity data associated with the user **1200** that is stored in the activity data storage **1220**. Additionally, a social module **1218** is provided for accessing and managing social data associated with the user **1200** that is stored in a social data storage **1222** it should be appreciated that the user **1200** may have access to activity data as well as social data associated with members of the user's social graph.

The browser **1204** communicates with the Web server **1210** to provide an interface on the user device **1202** whereby the user **1200** can access their activity data and social data, and perhaps view related activity of their friends on their social network. In one embodiment, the browser may access and present a message generation interface **1206** which may be utilized by the user **1200** generate a custom message to another user **1232**. The message generation interface **1206** can be configured to allow the user **1200** to enter text or other types of messaging data to define a custom user-generated message **1234**. The user-generated message **1234** is provided to an activity monitoring device **1230** associated with the user **1232** in accordance with embodiments previously described herein. For example, the activity monitoring device **1230** may communicate with a user device **1226** having a synchronization module **1228**, which in turn communicates with a synchronization server **1224** to effect downloading of the user generated message **1234** to the activity monitoring device **1230**. Then, when the activity monitoring device **1230** is placed in a predefined stationary state, the user generated message **1234** may be displayed when the activity monitoring device **1230** is subsequently moved from the stationary state.

FIG. **13** illustrates an interface for accessing activity data associated with the user of an activity monitoring device, in accordance with an embodiment of the invention. Broadly speaking, the illustrated interface is defined by various components or tiles which are configured to display activity related information. It should be appreciated that the illustrated components provided merely by way of example and not limitation, and that in other embodiments, additional components or types of information can be presented through an interface to the user.

A recent activity module **1300** provides a graph illustrating recent activity recorded by the activity monitoring device of the user. As shown, various selectable options enable the user to view the number of steps they have

recently taken, calories burned, or floors climbed. A steps module 1302 is configured to present a number of steps which have been taken by the user. It will be appreciated that the number of steps may be counted for a limited time period, such as the number of steps taken during the current day or current week. The steps module 1302 can also be configured to graphically illustrate the number of steps taken in relation to a goal or some predefined milestone or threshold, or a number of steps remaining to reach the goal or milestone.

A floors climbed module 1304 is configured to present a number of floors climbed within a given time period. It should be appreciated that the number of floors climbed is a conversion indicative of altitude changes that have been detected by the activity monitoring device. For example, if the activity monitoring device detects that the user has ascended a total of 100 feet and each floor is defined as the equivalent of 10 feet, then the 100 feet of ascension will be represented as a climb of 10 floors. The floors module 1304 can also be configured to indicate the relationship between the number of floors climbed and a goal, as well as the number of floors remaining to reach said goal.

A friends module 1306 is configured to display friends of the user from the user's social graph. Activity data associated with the user's friends can also be shown. In one embodiment, the user may access a message generation interface from the friends module 1306 to generate a custom user-defined message for display at the friend's activity monitoring device in response to movement from a stationary state, in accordance with the principles described herein. By way of example, clicking on or otherwise selecting a specific friend is presented in the friends module 1306 may provide access to options including an option to generate the custom motion activated message.

A weight module 1308 is configured to present a weight of the user, or a weight remaining to be lost by the user, or other weight related information. The distance module 1310 is configured to present a distance traveled by the user as measured based on data obtained from the user's activity monitoring device. The sleep module 1312 is configured to display an amount of sleep which the user has attained. A calories module 1314 is configured to display a number of calories burned by the user. A very active minutes module 1316 is configured to display the number of minutes of very active or vigorous activity by the user. A top badges module 1318 is configured to display badges or goals or milestones which the user has achieved. It will be appreciated that any of the foregoing modules may be configured to display specific metrics in relation to predefined goals, or amounts remaining to achieve such goals.

Though various embodiments have been described with reference to motion-activated messages which consist of text, it should be appreciated that the concepts relating to motion-activated messages may also apply to other forms of information which may be displayed or otherwise rendered in response to detected movement of an activity monitoring device from a stable stationary position. For example, a motion-activated "message" may be defined by an image, video, audio, animation, haptic event, or any other type of information or communicative event that may be presented through an activity monitoring device in accordance with embodiments of the invention.

In the foregoing embodiments, messages have been displayed on an activity monitoring device in response to detected movement of the device from a stationary position defined by a predefined orientation. However, in other embodiments, a message may be configured to be displayed

on the activity monitoring device in response to other types of changes which are detectable by the activity monitoring device.

Broadly speaking, the activity monitoring device can be configured to display a message in response to detecting a change from a non-user interactive state to a user interactive state. In embodiments presented above, the non-user interactive state can be defined by a stationary state in which non-movement of the device for a predefined period of time is detected. A change to a user-interactive state is detected when a movement of the device from the stationary state is detected.

In another embodiment, a change from a non-user interactive state to a user interactive state can include detecting a movement of the device from a first orientation to a second orientation, or detecting a predefined motion or movement of the device. For example, in an embodiment where the activity monitoring device is worn on a user's wrist, when the user maneuvers his/her arm to view the display on the activity monitoring device, such a movement or change in orientation can be detected, and in response, a message may be displayed. In another embodiment, the motion of the user flicking their wrist may be detected, and a message can be displayed in response.

The concept can be further extended to encompass different detected activity states, wherein the non-user interactive state might be defined by a particular detected physical activity state of the user (e.g. running, cycling, etc.). If the user moves or re-orientes the device so as to be able to view its display, then such a movement or re-orientation may be detected, and a message displayed in response.

In another embodiment, the non-user interactive state can include detecting a charging state of the device, wherein the device is connected to a charger. The change to the user-interactive state can be defined by detecting a change of the device from the charging state to a non-charging state, wherein the device is disconnected from the charger.

In still other embodiments, the change from the non-user interactive state to the user-interactive state can be defined by detected actions, such as a button press or an interaction with a touchscreen (e.g. touch, swipe, gesture, etc.).

In another embodiment, a message may be displayed in response to a change in temperature detected at the activity monitoring device. Such a message may be displayed in response to a change in the temperature having a magnitude greater than or equal to a predefined threshold, either an increase or a decrease in temperature. In a related embodiment, a message may be displayed in response to detection by the activity monitoring device of a specific ambient temperature. In this manner, message display is triggered by reaching specific ambient temperatures.

In another embodiment, a message can be configured to be displayed in response to changes in ambient light levels. For example, a sudden change from very low ambient light levels to comparatively high ambient light levels may indicate that the activity monitoring device has been removed from the user's pocket or otherwise taken out of a dark location for viewing by the user. Hence, the activity monitoring device may be configured to display a message in response to detection of such a change in ambient light.

In another embodiment, the activity monitoring device may be configured to display a message in response to changes in ambient sound levels.

The aforementioned methods and systems for displaying motion-activated messages on an activity monitoring device serve to improve the user experience of interacting with the activity monitoring device. By displaying messages in

response to motion from a stationary state, the activity monitoring device can react to the user's intent to interact with or otherwise utilize the device, as indicated by the motion. Furthermore, by intelligently selecting messages for display in a manner that is customized for the individual user, the experience can be highly personalized, and thus may appear to imbue the activity monitoring device with an apparent voice or persona.

FIG. 14 illustrates an example where various types of activities of users 1400A-1400I can be captured by activity tracking devices 100, in accordance with one embodiment of the present invention. As shown, the various types of activities can generate different types of data that can be captured by the activity tracking device 100. The data, which can be represented as motion data (or processed motion data) can be transferred 1420 to a network 176 for processing and saving by a server, as described above. In one embodiment, the activity tracking device 100 can communicate to a device using a wireless connection, and the device is capable of communicating and synchronizing the captured data with an application running on the server. In one embodiment, an application running on a local device, such as a smart phone or tablet or smart watch can capture or receive data from the activity tracking device 100 and represent the tract motion data in a number of metrics.

In one embodiment, the device collects one or more types of physiological and/or environmental data from embedded sensors and/or external devices and communicates or relays such metric information to other devices, including devices capable of serving as Internet-accessible data sources, thus permitting the collected data to be viewed, for example, using a web browser or network-based application. For example, while the user is wearing an activity tracking device, the device may calculate and store the user's step count using one or more sensors. The device then transmits data representative of the user's step count to an account on a web service, computer, mobile phone, or health station where the data may be stored, processed, and visualized by the user. Indeed, the device may measure or calculate a plurality of other physiological metrics in addition to, or in place of, the user's step count.

Some physiological metrics include, but are not limited to, energy expenditure (for example, calorie burn), floors climbed and/or descended, heart rate, heart rate variability, heart rate recovery, location and/or heading (for example, through GPS), elevation, ambulatory speed and/or distance traveled, swimming lap count, bicycle distance and/or speed, blood pressure, blood glucose, skin conduction, skin and/or body temperature, electromyography, electroencephalography, weight, body fat, caloric intake, nutritional intake from food, medication intake, sleep periods (i.e., clock time), sleep phases, sleep quality and/or duration, pH levels, hydration levels, and respiration rate. The device may also measure or calculate metrics related to the environment around the user such as barometric pressure, weather conditions (for example, temperature, humidity, pollen count, air quality, rain/snow conditions, wind speed), light exposure (for example, ambient light, UV light exposure, time and/or duration spent in darkness), noise exposure, radiation exposure, and magnetic field.

Still further, other metrics can include, without limitation, calories burned by a user (or energy expended), weight gained by a user, weight lost by a user, stairs ascended, e.g., climbed, etc., by a user, stairs descended by a user, steps taken by a user during walking or running, a number of rotations of a bicycle pedal rotated by a user, sedentary activity data, driving a vehicle, a number of golf swings

taken by a user, a number of forehands of a sport played by a user, a number of backhands of a sport played by a user, or a combination thereof. In some embodiments, sedentary activity data is referred to herein as inactive activity data or as passive activity data. In some embodiments, when a user is not sedentary and is not sleeping, the user is active. In some embodiments, a user may stand on a monitoring device that determines a physiological parameter of the user. For example, a user stands on a scale that measures a weight, a body fat percentage, a biomass index, or a combination thereof, of the user.

Furthermore, the device or the system collating the data streams may calculate metrics derived from this data. For example, the device or system may calculate the user's stress and/or relaxation levels through a combination of heart rate variability, skin conduction, noise pollution, and sleep quality. In another example, the device or system may determine the efficacy of a medical intervention (for example, medication) through the combination of medication intake, sleep and/or activity data. In yet another example, the device or system may determine the efficacy of an allergy medication through the combination of pollen data, medication intake, sleep and/or activity data. These examples are provided for illustration only and are not intended to be limiting or exhaustive.

This information can be associated to the users account, which can be managed by an activity management application on the server. The activity management application can provide access to the users account and data saved thereon. The activity manager application running on the server can be in the form of a web application. The web application can provide access to a number of websites screens and pages that illustrate information regarding the metrics in various formats. This information can be viewed by the user, and synchronized with a computing device of the user, such as a smart phone.

In one embodiment, the data captured by the activity tracking device 100 is received by the computing device, and the data is synchronized with the activity measured application on the server. In this example, data viewable on the computing device (e.g. smart phone) using an activity tracking application (app) can be synchronized with the data present on the server, and associated with the user's account. In this way, information entered into the activity tracking application on the computing device can be synchronized with application illustrated in the various screens of the activity management application provided by the server on the website.

The user can therefore access the data associated with the user account using any device having access to the Internet. Data received by the network 176 can then be synchronized with the user's various devices, and analytics on the server can provide data analysis to provide recommendations for additional activity, and or improvements in physical health. The process therefore continues where data is captured, analyzed, synchronized, and recommendations are produced. In some embodiments, the captured data can be itemized and partitioned based on the type of activity being performed, and such information can be provided to the user on the website via graphical user interfaces, or by way of the application executed on the users smart phone (by way of graphical user interfaces).

In an embodiment, the sensor or sensors of a device 100 can determine or capture data to determine an amount of movement of the monitoring device over a period of time. The sensors can include, for example, an accelerometer, a magnetometer, a gyroscope, or combinations thereof.

Broadly speaking, these sensors are inertial sensors, which capture some movement data, in response to the device 100 being moved. The amount of movement (e.g., motion sensed) may occur when the user is performing an activity of climbing stairs over the time period, walking, running, etc. The monitoring device may be worn on a wrist, carried by a user, worn on clothing (using a clip, or placed in a pocket), attached to a leg or foot, attached to the user's chest, waist, or integrated in an article of clothing such as a shirt, hat, pants, blouse, glasses, and the like. These examples are not limiting to all the possible ways the sensors of the device can be associated with a user or thing being monitored.

In other embodiments, a biological sensor can determine any number of physiological characteristics of a user. As another example, the biological sensor may determine heart rate, a hydration level, body fat, bone density, fingerprint data, sweat rate, and/or a bioimpedance of the user. Examples of the biological sensors include, without limitation, a biometric sensor, a physiological parameter sensor, a pedometer, or a combination thereof.

In some embodiments, data associated with the user's activity can be monitored by the applications on the server and the user's device, and activity associated with the user's friends, acquaintances, or social network peers can also be shared, based on the user's authorization. This provides for the ability for friends to compete regarding their fitness, achieve goals, receive badges for achieving goals, get reminders for achieving such goals, rewards or discounts for achieving certain goals, etc.

As noted, an activity tracking device 100 can communicate with a computing device (e.g., a smartphone, a tablet computer, a desktop computer, or computer device having wireless communication access and/or access to the Internet). The computing device, in turn, can communicate over a network, such as the Internet or an Intranet to provide data synchronization. The network may be a wide area network, a local area network, or a combination thereof. The network may be coupled to one or more servers, one or more virtual machines, or a combination thereof. A server, a virtual machine, a controller of a monitoring device, or a controller of a computing device is sometimes referred to herein as a computing resource. Examples of a controller include a processor and a memory device.

In one embodiment, the processor may be a general purpose processor. In another embodiment, the processor can be a customized processor configured to run specific algorithms or operations. Such processors can include digital signal processors (DSPs), which are designed to execute or interact with specific chips, signals, wires, and perform certain algorithms, processes, state diagrams, feedback, detection, execution, or the like. In some embodiments, a processor can include or be interfaced with an application specific integrated circuit (ASIC), a programmable logic device (PLD), a central processing unit (CPU), or a combination thereof, etc.

In some embodiments, one or more chips, modules, devices, or logic can be defined to execute instructions or logic, which collectively can be viewed or characterized to be a processor. Therefore, it should be understood that a processor does not necessarily have to be one single chip or module, but can be defined from a collection of electronic or connecting components, logic, firmware, code, and combinations thereof.

Examples of a memory device include a random access memory (RAM) and a read-only memory (ROM). A memory device may be a Flash memory, a redundant array of disks (RAID), a hard disk, or a combination thereof.

Embodiments described in the present disclosure may be practiced with various computer system configurations including hand-held devices, microprocessor systems, microprocessor-based or programmable consumer electronics, minicomputers, mainframe computers and the like. Several embodiments described in the present disclosure can also be practiced in distributed computing environments where tasks are performed by remote processing devices that are linked through a wire-based or wireless network.

With the above embodiments in mind, it should be understood that a number of embodiments described in the present disclosure can employ various computer-implemented operations involving data stored in computer systems. These operations are those requiring physical manipulation of physical quantities. Any of the operations described herein that form part of various embodiments described in the present disclosure are useful machine operations. Several embodiments described in the present disclosure also relate to a device or an apparatus for performing these operations. The apparatus can be specially constructed for a purpose, or the apparatus can be a computer selectively activated or configured by a computer program stored in the computer. In particular, various machines can be used with computer programs written in accordance with the teachings herein, or it may be more convenient to construct a more specialized apparatus to perform the required operations.

Various embodiments described in the present disclosure can also be embodied as computer-readable code on a non-transitory computer-readable medium. The computer-readable medium is any data storage device that can store data, which can thereafter be read by a computer system. Examples of the computer-readable medium include hard drives, network attached storage (NAS), ROM, RAM, compact disc-ROMs (CD-ROMs), CD-recordables (CD-Rs), CD-rewritables (RWs), magnetic tapes and other optical and non-optical data storage devices. The computer-readable medium can include computer-readable tangible medium distributed over a network-coupled computer system so that the computer-readable code is stored and executed in a distributed fashion.

Although the method operations were described in a specific order, it should be understood that other housekeeping operations may be performed in between operations, or operations may be performed in an order other than that shown, or operations may be adjusted so that they occur at slightly different times, or may be distributed in a system which allows the occurrence of the processing operations at various intervals associated with the processing.

Although the foregoing embodiments have been described in some detail for purposes of clarity of understanding, it will be apparent that certain changes and modifications can be practiced within the scope of the appended claims. Accordingly, the present embodiments are to be considered as illustrative and not restrictive, and the various embodiments described in the present disclosure are not to be limited to the details given herein, but may be modified within the scope and equivalents of the appended claims.

What is claimed is:

1. A wearable device, comprising:

- one or more first sensors configured to generate motion sensor data;
- one or more second sensors configured to generate environmental sensor data;
- a storage device configured to store a plurality of messages;
- a display configured to display the plurality of messages;
- and

one or more processors in communication with the storage device and configured to:

determine, based at least on the motion sensor data generated during a first time period, that the wearable device has been inactive for at least a threshold amount of time;

subsequent to the determination that the wearable device has been inactive for at least the threshold amount of time, cause the display to be turned off; subsequent to causing the display to be turned off, determine, based at least on the motion sensor data generated during a second time period subsequent to the first time period, that the wearable device is no longer inactive;

based at least on the determination that the wearable device is no longer inactive, select, based at least on one or both of the environmental sensor data or an orientation of the wearable device, a message from the plurality of messages stored in the storage device and cause the selected message to be displayed on the display;

wherein the environmental sensor data comprises at least one sensed environmental condition including one or more of ambient light, temperature, ambient pressure, altitude, humidity, or ambient sound; and wherein the message comprises information relating to one or more of the at least one sensed environmental condition, fitness activity, or social network activity.

2. The wearable device of claim 1, wherein the one or more processors are further configured to determine that the wearable device is no longer inactive based on a movement of the wearable device exceeding a predefined threshold.

3. The wearable device of claim 1, wherein the one or more processors are further configured to select the message further based on one or more of a current date, a current location of the wearable device, a current season, a length of inactivity, or an activity history.

4. The wearable device of claim 1, wherein the one or more processors are further configured to determine that the wearable device has been inactive for at least the threshold amount of time based on a determination that the wearable device has been in a predetermined orientation in 3-dimensional space for at least the threshold amount of time.

5. The wearable device of claim 1, wherein the one or more processors are further configured to determine that the wearable device is no longer inactive based on a determination that the wearable device is in a new position that is different by at least a threshold amount of movement from a previous position in which the determination that the wearable device has been inactive was made.

6. The wearable device of claim 5, wherein the threshold amount of movement comprises one or both of a threshold amount of translational movement and a threshold amount of rotational movement.

7. The wearable device of claim 5, wherein the display is disposed on the wearable device such that when the wearable device is resting on a planar surface in the previous position, the display would face a direction that is substantially parallel to the planar surface.

8. The wearable device of claim 5, wherein the display is disposed on the wearable device such that when the wearable device is resting on a planar surface in the previous position, the display would face a direction that is substantially perpendicular to the planar surface.

9. The wearable device of claim 1, wherein the one or more processors are further configured to:

determine that a current weather condition matches a first weather condition associated with one of the plurality of messages stored in the storage device; and cause the message corresponding to the first weather condition to be displayed on the display.

10. The wearable device of claim 1, wherein the one or more processors are further configured to:

identify an upcoming fitness-related event; and based at least on the determination that the wearable device is no longer inactive, cause the message including information about the upcoming fitness-related event to be displayed on the display.

11. The wearable device of claim 1, wherein the one or more processors are further configured to:

determine, based at least on an electronic calendar associated with the wearable device, that an event is not scheduled at a time the message is to be displayed on the display; and

based at least on the determination that the wearable device is no longer inactive and that an event is not scheduled at the time the message is to be displayed on the display, cause the message to be displayed on the display.

12. The wearable device of claim 1, wherein the one or more processors are further configured to:

detect, while the message is displayed on the display, an input for displaying a fitness metric on the display; and cause the message to be dismissed from the display and the fitness metric to be displayed on the display.

13. The wearable device of claim 1, wherein the one or more processors are further configured to:

determine, based at least on information available to the one or more processors, a ranked order of the plurality of messages stored in the storage device; and select the message from the plurality of messages according to the ranked order.

14. A method for presenting a message on a wearable device, comprising:

determining, based at least on motion sensor data generated during a first time period, that the wearable device has been inactive for at least a threshold amount of time;

subsequent to determining that the wearable device has been inactive for at least the threshold amount of time, causing the display to be turned off;

subsequent to causing the display to be turned off, determining, based at least on motion sensor data generated during a second time period subsequent to the first time period, that the wearable device is no longer inactive;

based at least on determining that the wearable device is no longer inactive, selecting, based at least on one or both of environmental sensor data or an orientation of the wearable device, a message from a plurality of messages stored in a storage device of the wearable device;

displaying the selected message on a display of the wearable device;

wherein the environmental sensor data comprises at least one sensed environmental condition including one or more of ambient light, temperature, ambient pressure, altitude, humidity, or ambient sound; and

wherein the message comprises information relating to one or more of the at least one sensed environmental condition, fitness activity, or social network activity.

31

15. The method of claim 14, further comprising determining that the wearable device is no longer inactive based on a movement of the wearable device exceeding a predefined threshold.

16. The method of claim 14, further comprising determining that the wearable device has been inactive for at least the threshold amount of time based on determining that the wearable device has been in a predetermined orientation in 3-dimensional space for at least the threshold amount of time.

17. The method of claim 14, further comprising determining that the wearable device is no longer inactive based on determining that the wearable device is in a new position that is at least a threshold amount of distance away from a previous position in which the determination that the wearable device has been inactive was made.

18. The method of claim 14, further comprising: determining that a current weather condition matches a first weather condition associated with one of the plurality of messages stored in the storage device; and

32

displaying the message corresponding to the first weather condition on the display.

19. The method of claim 14, further comprising: identifying an upcoming fitness-related event; and based at least on determining that the wearable device is no longer inactive, displaying the message including information about the upcoming fitness-related event on the display.

20. The method of claim 14, further comprising: determining, based at least on an electronic calendar associated with the wearable device, that an event is not scheduled at a time the message is to be displayed on the display; and

based at least on determining that the wearable device is no longer inactive and that an event is not scheduled at the time the message is to be displayed on the display, displaying the message on the display.

* * * * *

专利名称(译)	动态监视设备上的消息的动作激活显示		
公开(公告)号	US10126998	公开(公告)日	2018-11-13
申请号	US15/583959	申请日	2017-05-01
[标]申请(专利权)人(译)	飞比特公司		
申请(专利权)人(译)	FITBIT INC.		
当前申请(专利权)人(译)	FITBIT INC.		
[标]发明人	YUEN SHELLEN ROBERTS TIMOTHY		
发明人	YUEN, SHELLEN ROBERTS, TIMOTHY		
IPC分类号	G06F3/00 A61B5/00 G01C22/00 H04W4/02 H04L29/06 A63B24/00 H04L29/08 A63B23/00 G06F3/14 H04W4/21 A61B5/22 G06F19/00 H04L12/24 G06F1/16 G06F3/01 G06F17/21 A61B5/021 A61B5/11 G16H40/63 A61B5/0205 A61B5/024		
CPC分类号	G06F3/14 G16H20/30 A61B5/1118 A61B5/222 A61B5/6838 A61B5/743 A63B24/0062 G06F1/163 G06F1/1694 G06F3/011 G06F3/017 G06F17/21 G06F19/00 H04L41/22 H04L67/1095 H04L67/22 H04L67/306 H04L67/42 H04W4/02 H04W4/21 A61B5/0022 A61B5/021 A61B5/024 A61B5/02055 A61B5/1112 A61B5/4809 A61B5/4812 A61B5/4815 A61B2560/0214 A61B2560/0242 A61B2562/0219 G01C22/006 G16H40/63 G06F19/3481 G06F40/10 H04W4/029		
审查员(译)	DALBO , MICHAEL		
优先权	14/271389 2015-01-20 US 13/667229 2013-05-07 US 13/469027 2012-11-13 US 13/246843 2012-05-15 US 61/388595 2010-09-30 US 61/390811 2010-10-07 US		
其他公开文献	US20170249115A1		
外部链接	Espacenet		

摘要(译)

提供了用于在活动监视设备上动态激活消息显示的方法，系统和设备。在一个实施例中，提供了一种用于在活动监视设备上呈现消息的方法，包括以下方法操作：将多个消息存储到设备；检测设备的静止状态；检测设备从静止状态的移动；响应于检测到来自静止状态的移动，选择多个消息中的一个，并在设备上显示所选择的消息。

