



US010561458B2

(12) **United States Patent**
Danek et al.

(10) **Patent No.:** **US 10,561,458 B2**
(45) **Date of Patent:** **Feb. 18, 2020**

(54) **METHODS FOR TREATING AIRWAYS**

(71) Applicant: **Boston Scientific Scimed, Inc.**, Maple Grove, MN (US)

(72) Inventors: **Christopher J. Danek**, San Carlos, CA (US); **Michael Biggs**, Denver, CO (US); **Bryan E. Loomas**, Los Gatos, CA (US); **Michael D. Laufer**, Menlo Park, CA (US); **Gary S. Kaplan**, Mountain View, CA (US); **Kelly M. Shriner**, Arlington, MA (US); **William Wizeman**, Mountain View, CA (US)

(73) Assignee: **Boston Scientific Scimed, Inc.**, Maple Grove, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/364,614**

(22) Filed: **Mar. 26, 2019**

(65) **Prior Publication Data**

US 2019/0216529 A1 Jul. 18, 2019

Related U.S. Application Data

(63) Continuation of application No. 14/171,973, filed on Feb. 4, 2014, now Pat. No. 10,278,766, which is a (Continued)

(51) **Int. Cl.**

A61B 18/14 (2006.01)

A61B 1/00 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **A61B 18/14** (2013.01); **A61B 1/00085** (2013.01); **A61B 5/053** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC A61B 18/14; A61B 18/18; A61B 1/00085; A61B 5/085; A61B 5/0809;

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

612,724 A 10/1898 Jonathan
1,155,169 A 9/1915 Starkweather

(Continued)

FOREIGN PATENT DOCUMENTS

DE 19529634 A1 2/1997
EP 189329 A3 6/1987

(Continued)

OTHER PUBLICATIONS

An S.S., et al., "Airway Smooth Muscle Dynamics: A Common Pathway of Airway Obstruction in Asthma," *European Respiratory Journal*, 2007, 29 (5), 834-860.

(Continued)


Primary Examiner — William H Matthews

(74) *Attorney, Agent, or Firm* — Bookoff McAndrews, PLLC

(57) **ABSTRACT**

This relates to treating airways in a lung to decrease asthmatic symptoms. The also includes steps of measuring a parameter of an airway at a plurality of locations in a lung, identifying at least one treatment site from at least one of the plurality of locations based on the parameter, and applying energy to the treatment site to reduce the ability of the site to narrow.

20 Claims, 9 Drawing Sheets



Related U.S. Application Data

continuation of application No. 13/557,518, filed on Jul. 25, 2012, now abandoned, which is a continuation of application No. 11/398,353, filed on Apr. 4, 2006, now Pat. No. 8,251,070.

(51) **Int. Cl.**

- A61B 5/053* (2006.01)
- A61B 5/08* (2006.01)
- A61B 5/107* (2006.01)
- A61B 5/00* (2006.01)
- A61B 10/04* (2006.01)
- A61B 18/18* (2006.01)
- A61N 5/10* (2006.01)
- A61B 90/00* (2016.01)
- A61B 17/00* (2006.01)
- A61B 18/00* (2006.01)
- A61B 18/06* (2006.01)

(52) **U.S. Cl.**

- CPC *A61B 5/0538* (2013.01); *A61B 5/08* (2013.01); *A61B 5/0809* (2013.01); *A61B 5/1076* (2013.01); *A61B 5/6853* (2013.01); *A61B 5/6858* (2013.01); *A61B 10/04* (2013.01); *A61B 18/18* (2013.01); *A61N 5/1001* (2013.01); *A61B 5/411* (2013.01); *A61B 5/4519* (2013.01); *A61B 5/4836* (2013.01); *A61B 5/4878* (2013.01); *A61B 18/06* (2013.01); *A61B 18/1492* (2013.01); *A61B 2010/045* (2013.01); *A61B 2017/00106* (2013.01); *A61B 2017/00809* (2013.01); *A61B 2018/0022* (2013.01); *A61B 2018/00214* (2013.01); *A61B 2018/00244* (2013.01); *A61B 2018/00541* (2013.01); *A61B 2018/00773* (2013.01); *A61B 2018/00875* (2013.01); *A61B 2018/00898* (2013.01); *A61B 2018/1472* (2013.01); *A61B 2090/061* (2016.02); *A61B 2090/064* (2016.02)

(58) **Field of Classification Search**

- CPC .. *A61B 2018/0022*; *A61B 2018/00244*; *A61B 2018/00541*; *A61B 2018/00875*; *A61B 2018/1472*; *A61N 5/1002*
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,207,479 A 12/1916 Bisgaard
 1,216,183 A 2/1917 Charles
 2,072,346 A 3/1937 Smith
 3,320,957 A 5/1967 Sokolik
 3,568,659 A 3/1971 Karnegis
 3,667,476 A 6/1972 Muller
 3,692,029 A 9/1972 Adair
 3,995,617 A 12/1976 Watkins et al.
 4,095,602 A 6/1978 Leveen
 4,116,589 A 9/1978 Rishton
 4,129,129 A 12/1978 Amrine
 4,154,246 A 5/1979 Leveen
 4,461,283 A 7/1984 Doi
 4,502,490 A 3/1985 Evans et al.
 4,503,855 A 3/1985 Maslanka
 4,512,762 A 4/1985 Spears
 4,522,212 A 6/1985 Gelinas et al.
 4,557,272 A 12/1985 Carr
 4,565,200 A 1/1986 Cosman
 4,567,882 A 2/1986 Heller
 4,584,998 A 4/1986 McGrail
 4,612,934 A 9/1986 Borkan

4,621,642 A 11/1986 Chen
 4,621,882 A 11/1986 Krumme
 4,625,712 A 12/1986 Wampler
 4,643,186 A 2/1987 Rosen et al.
 4,646,737 A 3/1987 Hussein et al.
 4,674,497 A 6/1987 Ogasawara
 4,683,890 A 8/1987 Hewson
 4,704,121 A 11/1987 Moise
 4,706,688 A 11/1987 Don Michael et al.
 4,709,698 A 12/1987 Johnston et al.
 4,739,759 A 4/1988 Rexroth et al.
 4,754,065 A 6/1988 Levenson et al.
 4,754,752 A 7/1988 Ginsburg et al.
 4,765,959 A 8/1988 Fukasawa
 4,772,112 A 9/1988 Zider et al.
 4,773,899 A 9/1988 Spears
 4,779,614 A 10/1988 Moise
 4,784,135 A 11/1988 Blum et al.
 4,790,305 A 12/1988 Zoltan et al.
 4,799,479 A 1/1989 Spears
 4,802,492 A 2/1989 Grunstein
 4,817,586 A 4/1989 Wampler
 4,825,871 A 5/1989 Cansell
 4,827,935 A 5/1989 Geddes et al.
 4,846,152 A 7/1989 Wampler et al.
 4,862,886 A 9/1989 Clarke et al.
 4,895,557 A 1/1990 Moise et al.
 4,906,229 A 3/1990 Wampler
 4,907,589 A 3/1990 Cosman
 4,908,012 A 3/1990 Moise et al.
 4,920,978 A 5/1990 Colvin
 4,944,722 A 7/1990 Carriker et al.
 4,955,377 A 9/1990 Lennox et al.
 4,967,765 A 11/1990 Turner et al.
 4,969,865 A 11/1990 Hwang et al.
 4,976,709 A 12/1990 Sand
 4,985,014 A 1/1991 Orejola
 4,991,603 A 2/1991 Cohen et al.
 5,009,636 A 4/1991 Wortley et al.
 5,009,936 A 4/1991 Yamanaka et al.
 5,010,892 A 4/1991 Colvin et al.
 5,019,075 A 5/1991 Spears et al.
 5,027,829 A 7/1991 Larsen
 5,030,645 A 7/1991 Kollonitsch
 5,036,848 A 8/1991 Hewson
 5,053,033 A 10/1991 Clarke
 5,056,519 A 10/1991 Vince
 5,074,860 A 12/1991 Gregory et al.
 5,078,716 A 1/1992 Doll
 5,084,044 A 1/1992 Quint
 5,096,916 A 3/1992 Skupin
 5,100,388 A 3/1992 Behl et al.
 5,100,423 A 3/1992 Fearnot
 5,103,804 A 4/1992 Abele et al.
 5,105,826 A 4/1992 Smits et al.
 5,106,360 A 4/1992 Ishiware et al.
 5,107,830 A 4/1992 Younes
 5,114,423 A 5/1992 Kasprzyk et al.
 5,116,864 A 5/1992 March et al.
 5,117,828 A 6/1992 Metzger et al.
 5,135,517 A 8/1992 McCoy
 5,152,286 A 10/1992 Sitko et al.
 5,165,420 A 11/1992 Strickland
 5,167,223 A 12/1992 Koros et al.
 5,170,803 A 12/1992 Hewson et al.
 5,174,288 A 12/1992 Bardy et al.
 5,188,602 A 2/1993 Nichols
 5,191,883 A 3/1993 Lennox et al.
 5,213,576 A 5/1993 Abiuso et al.
 5,215,103 A 6/1993 Desai
 5,231,996 A 8/1993 Bardy et al.
 5,232,444 A 8/1993 Just et al.
 5,234,456 A 8/1993 Silvestrini
 5,254,088 A 10/1993 Lundquist et al.
 5,255,678 A 10/1993 Deslauriers et al.
 5,255,679 A 10/1993 Imran
 5,265,604 A 11/1993 Vince
 5,269,758 A 12/1993 Taheri
 5,281,218 A 1/1994 Imran

(56)

References Cited

U.S. PATENT DOCUMENTS

5,290,550 A	3/1994	Fisher et al.	5,607,462 A	3/1997	Imran
5,292,331 A	3/1994	Boneau	5,620,438 A	4/1997	Amplatz et al.
5,293,869 A	3/1994	Edwards et al.	5,623,940 A	4/1997	Daikuzono
5,309,910 A	5/1994	Edwards et al.	5,624,439 A	4/1997	Edwards et al.
5,313,943 A	5/1994	Houser et al.	5,626,618 A	5/1997	Ward et al.
5,324,284 A	6/1994	Imran	5,630,425 A	5/1997	Panescu et al.
5,343,936 A	9/1994	Beatenbough et al.	5,630,794 A	5/1997	Lax et al.
5,345,936 A	9/1994	Pomeranz et al.	5,634,471 A	6/1997	Fairfax et al.
5,366,443 A	11/1994	Eggers et al.	5,641,326 A	6/1997	Adams
5,368,591 A	11/1994	Lennox et al.	5,647,870 A	7/1997	Kordis et al.
5,370,644 A	12/1994	Langberg	5,660,175 A	8/1997	Dayal
5,370,679 A	12/1994	Atlee, III	5,674,483 A	10/1997	Tu et al.
5,374,287 A	12/1994	Rubin	5,678,535 A	10/1997	Dimarco
5,383,917 A	1/1995	Desai et al.	5,680,860 A	10/1997	Imran
5,393,207 A	2/1995	Maher et al.	5,681,280 A	10/1997	Rusk et al.
5,394,880 A	3/1995	Atlee, III	5,681,308 A	10/1997	Edwards et al.
5,396,887 A	3/1995	Imran	5,687,723 A	11/1997	Avitall
5,400,778 A	3/1995	Jonson et al.	5,688,267 A	11/1997	Panescu et al.
5,400,783 A	3/1995	Pomeranz et al.	5,693,078 A	12/1997	Desai et al.
5,411,025 A	5/1995	Webster	5,694,934 A	12/1997	Edelman
5,415,166 A	5/1995	Imran	5,695,471 A	12/1997	Wampler
5,415,656 A	5/1995	Tihon et al.	5,699,799 A	12/1997	Xu et al.
5,417,687 A	5/1995	Nardella et al.	5,702,386 A	12/1997	Stern et al.
5,422,362 A	6/1995	Vincent et al.	5,707,218 A	1/1998	Maher et al.
5,423,744 A	6/1995	Gencheff et al.	5,707,336 A	1/1998	Rubin
5,423,811 A	6/1995	Imran et al.	5,707,352 A	1/1998	Sekins et al.
5,425,023 A	6/1995	Haraguchi et al.	5,722,401 A	3/1998	Pietroski et al.
5,425,703 A	6/1995	Feiring	5,722,403 A	3/1998	McGee et al.
5,425,811 A	6/1995	Mashita	5,722,416 A	3/1998	Swanson et al.
5,431,696 A	7/1995	Atlee, III	5,725,525 A	3/1998	Kordis
5,433,730 A	7/1995	Alt	5,727,569 A	3/1998	Benetti et al.
5,437,665 A	8/1995	Munro	5,728,094 A	3/1998	Edwards
5,443,470 A	8/1995	Stern et al.	5,730,128 A	3/1998	Pomeranz et al.
5,454,782 A	10/1995	Perkins	5,730,704 A	3/1998	Avitall
5,456,667 A	10/1995	Ham et al.	5,730,726 A	3/1998	Klingenstein
5,458,596 A	10/1995	Lax et al.	5,730,741 A	3/1998	Horzewski et al.
5,465,717 A	11/1995	Imran et al.	5,735,846 A	4/1998	Panescu et al.
5,471,982 A	12/1995	Edwards et al.	5,740,808 A	4/1998	Panescu et al.
5,474,530 A	12/1995	Passafaro et al.	5,741,248 A	4/1998	Stern et al.
5,478,309 A	12/1995	Sweezer et al.	5,752,518 A	5/1998	McGee et al.
5,485,841 A	1/1996	Watkin et al.	5,755,714 A	5/1998	Murphy-Chutorian
5,496,271 A	3/1996	Burton et al.	5,755,753 A	5/1998	Knowlton
5,496,311 A	3/1996	Abele et al.	5,759,158 A	6/1998	Swanson
5,496,312 A	3/1996	Klicek	5,765,568 A	6/1998	Sweezer et al.
5,500,011 A	3/1996	Desai	5,769,846 A	6/1998	Edwards et al.
5,505,728 A	4/1996	Ellman et al.	5,772,590 A	6/1998	Webster
5,505,730 A	4/1996	Edwards	5,779,669 A	7/1998	Haissaguerre et al.
5,507,791 A	4/1996	Sit'ko	5,779,698 A	7/1998	Clayman et al.
5,509,419 A	4/1996	Edwards et al.	5,782,239 A	7/1998	Webster
5,522,862 A	6/1996	Testerman et al.	5,782,797 A	7/1998	Schweich et al.
5,531,779 A	7/1996	Dahl et al.	5,782,827 A	7/1998	Gough et al.
5,540,681 A	7/1996	Strul et al.	5,782,848 A	7/1998	Lennox
5,545,161 A	8/1996	Imran	5,782,899 A	7/1998	Imran
5,545,193 A	8/1996	Fleischman et al.	5,792,064 A	8/1998	Panescu et al.
5,547,469 A	8/1996	Rowland et al.	5,795,303 A	8/1998	Swanson et al.
5,549,559 A	8/1996	Eshel	5,800,375 A	9/1998	Sweezer et al.
5,549,655 A	8/1996	Erickson	5,807,306 A	9/1998	Shapland et al.
5,549,661 A	8/1996	Kordis et al.	5,810,757 A	9/1998	Sweezer et al.
RE35,330 E	9/1996	Malone et al.	5,810,807 A	9/1998	Ganz et al.
5,558,073 A	9/1996	Pomeranz et al.	5,817,028 A	10/1998	Anderson
5,562,608 A	10/1996	Sekins et al.	5,817,073 A	10/1998	Krespi
5,570,683 A	11/1996	Zapol	5,820,554 A	10/1998	Davis et al.
5,571,074 A	11/1996	Buckman et al.	5,823,189 A	10/1998	Kordis
5,571,088 A	11/1996	Lennox et al.	5,827,277 A	10/1998	Edwards
5,574,059 A	11/1996	Regunathan et al.	5,833,651 A	11/1998	Donovan et al.
5,578,072 A	11/1996	Barone et al.	5,836,905 A	11/1998	Lemelson et al.
5,582,609 A	12/1996	Swanson et al.	5,836,947 A	11/1998	Fleischman et al.
5,588,432 A	12/1996	Crowley	5,837,001 A	11/1998	Mackey
5,588,812 A	12/1996	Taylor et al.	5,843,075 A	12/1998	Taylor
5,595,183 A	1/1997	Swanson et al.	5,843,077 A	12/1998	Edwards
5,598,848 A	2/1997	Swanson et al.	5,846,238 A	12/1998	Jackson et al.
5,599,345 A	2/1997	Edwards et al.	5,848,969 A	12/1998	Panescu et al.
5,601,088 A	2/1997	Swanson et al.	5,848,972 A	12/1998	Triedman et al.
5,605,157 A	2/1997	Panescu et al.	5,849,026 A	12/1998	Zhou et al.
5,607,419 A	3/1997	Amplatz et al.	5,855,577 A	1/1999	Murphy-Chutorian et al.
			5,860,974 A	1/1999	Abele
			5,863,291 A	1/1999	Schaer
			5,865,791 A	2/1999	Whayne et al.
			5,868,740 A	2/1999	Leveen et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

5,871,443 A	2/1999	Edwards et al.	6,071,281 A	6/2000	Burnside et al.
5,871,523 A	2/1999	Fleischman et al.	6,071,282 A	6/2000	Fleischman
5,873,852 A	2/1999	Vigil et al.	6,083,255 A	7/2000	Laufer et al.
5,873,865 A	2/1999	Horzewski et al.	6,090,104 A	7/2000	Webster
5,876,340 A	3/1999	Tu et al.	6,092,528 A	7/2000	Edwards
5,876,399 A	3/1999	Chia et al.	6,102,886 A	8/2000	Lundquist et al.
5,881,727 A	3/1999	Edwards	6,106,524 A	8/2000	Eggers et al.
5,882,346 A	3/1999	Pomeranz et al.	6,123,702 A	9/2000	Swanson et al.
5,891,135 A	4/1999	Jackson et al.	6,123,703 A	9/2000	Tu et al.
5,891,136 A	4/1999	McGee et al.	6,139,527 A	10/2000	Laufer et al.
5,891,138 A	4/1999	Tu et al.	6,139,571 A	10/2000	Fuller et al.
5,893,847 A	4/1999	Kordis	6,142,993 A	11/2000	Wayne et al.
5,897,554 A	4/1999	Chia et al.	6,143,013 A	11/2000	Samson et al.
5,899,882 A	5/1999	Waksman et al.	6,149,647 A	11/2000	Tu et al.
5,904,651 A	5/1999	Swanson et al.	6,152,143 A	11/2000	Edwards
5,904,711 A	5/1999	Flom et al.	6,152,899 A	11/2000	Farley et al.
5,906,636 A	5/1999	Casscells, III et al.	6,159,194 A	12/2000	Eggers et al.
5,908,445 A	6/1999	Wayne et al.	6,179,833 B1	1/2001	Taylor
5,908,446 A	6/1999	Imran	6,183,468 B1	2/2001	Swanson et al.
5,908,839 A	6/1999	Levitt et al.	6,198,970 B1	3/2001	Freed et al.
5,911,218 A	6/1999	DiMarco	6,200,311 B1	3/2001	Danek et al.
5,916,235 A	6/1999	Guglielmi	6,200,332 B1	3/2001	Del Giglio
5,919,147 A	7/1999	Jain	6,200,333 B1	3/2001	Laufer
5,919,172 A	7/1999	Golba	6,210,367 B1	4/2001	Carr
5,924,424 A	7/1999	Stevens et al.	6,212,433 B1	4/2001	Behl
5,928,228 A	7/1999	Kordis et al.	6,214,002 B1	4/2001	Fleischman et al.
5,931,835 A	8/1999	Mackey	6,216,043 B1	4/2001	Swanson et al.
5,935,079 A	8/1999	Swanson et al.	6,216,044 B1	4/2001	Kordis
5,941,869 A	8/1999	Patterson et al.	6,217,576 B1	4/2001	Tu et al.
5,951,494 A	9/1999	Wang et al.	6,235,024 B1	5/2001	Tu
5,951,546 A	9/1999	Lorentzen	6,241,727 B1	6/2001	Tu et al.
5,954,661 A	9/1999	Greenspon et al.	6,245,065 B1	6/2001	Panescu et al.
5,954,662 A	9/1999	Swanson et al.	6,254,598 B1	7/2001	Edwards et al.
5,954,717 A	9/1999	Behl et al.	6,258,087 B1	7/2001	Edwards et al.
5,957,961 A	9/1999	Maguire et al.	6,264,653 B1	7/2001	Falwell
5,964,753 A	10/1999	Edwards	6,269,813 B1	8/2001	Fitzgerald et al.
5,964,796 A	10/1999	Imran	6,270,476 B1	8/2001	Santojanni et al.
5,971,983 A	10/1999	Lesh	6,273,907 B1	8/2001	Laufer
5,972,026 A	10/1999	Laufer et al.	6,283,988 B1	9/2001	Laufer et al.
5,976,175 A	11/1999	Hirano et al.	6,283,989 B1	9/2001	Laufer et al.
5,976,709 A	11/1999	Kageyama et al.	6,287,290 B1	9/2001	Perkins et al.
5,979,456 A	11/1999	Magovern	6,287,304 B1	9/2001	Eggers et al.
5,980,563 A	11/1999	Tu et al.	6,296,639 B1	10/2001	Truckai et al.
5,984,917 A	11/1999	Fleischman et al.	6,299,633 B1	10/2001	Laufer
5,984,971 A	11/1999	Faccioli et al.	6,322,559 B1	11/2001	Daulton et al.
5,991,650 A	11/1999	Swanson et al.	6,322,584 B2	11/2001	Ingle et al.
5,992,419 A	11/1999	Sterzer et al.	6,327,505 B1	12/2001	Medhkour et al.
5,993,462 A	11/1999	Pomeranz et al.	6,338,727 B1	1/2002	Noda et al.
5,997,534 A	12/1999	Tu et al.	6,338,836 B1	1/2002	Kuth et al.
5,999,855 A	12/1999	DiMarco	6,346,104 B2	2/2002	Daly et al.
6,001,054 A	12/1999	Regulla et al.	6,355,031 B1	3/2002	Edwards et al.
6,003,517 A	12/1999	Sheffield et al.	6,379,352 B1	4/2002	Reynolds et al.
6,004,269 A	12/1999	Crowley et al.	6,409,723 B1	6/2002	Edwards
6,006,755 A	12/1999	Edwards	6,411,852 B1	6/2002	Danek et al.
6,008,211 A	12/1999	Robinson et al.	6,416,511 B1	7/2002	Lesh et al.
6,009,877 A	1/2000	Edwards	6,416,740 B1	7/2002	Unger
6,010,500 A	1/2000	Sherman et al.	6,423,105 B1	7/2002	Iijima et al.
6,014,579 A	1/2000	Pomeranz et al.	6,425,895 B1	7/2002	Swanson et al.
6,016,437 A	1/2000	Tu et al.	6,433,040 B1	8/2002	Dellamary et al.
6,023,638 A	2/2000	Swanson	6,440,129 B1	8/2002	Simpson
6,024,740 A	2/2000	Lesh et al.	6,442,435 B2	8/2002	King et al.
6,029,091 A	2/2000	De La Rama et al.	6,458,121 B1	10/2002	Rosenstock et al.
6,033,397 A	3/2000	Laufer et al.	6,460,545 B2	10/2002	Kordis
6,036,687 A	3/2000	Laufer et al.	6,488,673 B1	12/2002	Laufer et al.
6,036,689 A	3/2000	Tu et al.	6,488,679 B1	12/2002	Swanson et al.
6,039,731 A	3/2000	Taylor et al.	6,493,589 B1	12/2002	Medhkour et al.
6,045,549 A	4/2000	Smethers et al.	6,494,880 B1	12/2002	Swanson et al.
6,045,550 A	4/2000	Simpson et al.	6,496,738 B2	12/2002	Carr
6,050,992 A	4/2000	Nichols	6,514,246 B1	2/2003	Swanson et al.
6,053,172 A	4/2000	Hovda et al.	6,526,320 B2	2/2003	Mitchell
6,053,909 A	4/2000	Shaddock	6,529,756 B1	3/2003	Phan et al.
6,056,744 A	5/2000	Edwards	6,544,226 B1	4/2003	Gaiser et al.
6,056,769 A	5/2000	Epstein et al.	6,544,262 B2	4/2003	Fleischman
6,063,078 A	5/2000	Wittkampf	6,547,788 B1	4/2003	Maguire et al.
6,071,280 A	6/2000	Edwards et al.	6,558,378 B2	5/2003	Sherman et al.
			6,572,612 B2	6/2003	Stewart et al.
			6,575,623 B2	6/2003	Werneth
			6,575,969 B1	6/2003	Rittman, III et al.
			6,582,427 B1	6/2003	Goble et al.

(56) **References Cited**

FOREIGN PATENT DOCUMENTS

WO	WO-9856234	A1	12/1998
WO	WO-1998056324	A1	12/1998
WO	WO-1999003413	A1	1/1999
WO	WO-1998058681	A3	3/1999
WO	WO-1999013779	A2	3/1999
WO	WO-9932040	A1	7/1999
WO	WO-1999034741	A1	7/1999
WO	WO-1999044506	A1	9/1999
WO	WO-1999045855	A1	9/1999
WO	WO-9964109	A1	12/1999
WO	WO-2000051510	A1	9/2000
WO	WO-0062699	A3	10/2000
WO	WO-2001003642	A1	1/2001
WO	WO-0232333	A1	4/2002
WO	WO-0232334	A1	4/2002
WO	WO-2009082433	A2	7/2009
WO	WO-2009137819	A1	11/2009

OTHER PUBLICATIONS

Bel E.H., "Hot stuff": Bronchial Thermoplasty for Asthma," *American Journal of Respiratory and Critical Care Medicine*, 2006, 173 (9), 941-943.

Brown R.H., et al., "Effect of Bronchial Thermoplasty on Airway Distensibility," *European Respiratory Journal*, 2005, 26 (2), 277-282.

Brown R.H., et al., "In Vivo evaluation of the Effectiveness of Bronchial Thermoplasty with Computed Tomography," *Journal of Applied Physiology*, 2005, 98 (5), 1603-1606.

Chhajed P.N., et al., "Will there be a Role for Bronchoscopic Radiofrequency Ablation", *Journal of Bronchology*, 2005, 12 (3), 184-186.

U.S. Appl. No. 09/095,323, filed Jun. 10, 1998.

U.S. Appl. No. 09/244,173, filed Feb. 4, 1999.

U.S. Appl. No. 12/640,644, filed Dec. 17, 2009.

U.S. Appl. No. 12/727,156, filed Mar. 18, 2018.

U.S. Appl. No. 12/765,704, filed Apr. 22, 2010.

Cox G., et al., "Asthma Control during the Year after Bronchial Thermoplasty," *New England journal of medicine*, 2007, 356 (13), 1327-1337.

Cox G., et al., "Asthma Intervention Research (AIR) Trial Evaluating Bronchial Thermoplasty: Early Results," *American Thoracic Society Annual Meeting*, 2002, 1 page.

Cox G., et al., "Bronchial Thermoplasty for Asthma," *American Journal of Respiratory and Critical Care Medicine*, 2006, 173 (9), 965-969.

Cox G., et al., "Bronchial Thermoplasty: Long-Term Follow-Up and Patient Satisfaction," *Chest*, 2004, 126 (4), 822s.

Cox G., et al., "Bronchial Thermoplasty: One-Year Update, American Thoracic Society Annual Meeting," *American Journal of Respiratory and Critical Care Medicine*, 2004, 169, A313.

Cox G., et al., "Clinical Experience with Bronchial Thermoplasty for the Treatment of Asthma," *Chest*, 2003, 124, 106S.

Cox G., et al., "Development of a Novel Bronchoscopic Therapy for Asthma," *Journal of Allergy and Clinical Immunology*, 2003, 113 (2), S33.

Cox G., et al., "Early Clinical Experience with Bronchial Thermoplasty for the Treatment of Asthma," *American Thoracic Society Annual Meeting*, 2002, 1068.

Cox G., et al., "Impact of Bronchial Thermoplasty on Asthma Status: Interim Results from the AIR Trial," 2006, 1 page.

Cox G., et al., "Radiofrequency Ablation of Airway Smooth Muscle for Sustained Treatment of Asthma: Preliminary Investigations," *European Respiratory Journal*, 2004, 24 (4), 659-663.

Danek C.J., et al., "Bronchial Thermoplasty Reduces Canine Airway Responsiveness to Local Methacholine Challenge," *American Thoracic Society Annual Meeting*, 2002, 1 page.

Danek C.J., et al., "Reduction in Airway Hyperresponsiveness to Methacholine by the Application of RF Energy in Dogs," *Journal of Applied Physiology*, 2004, 97 (5), 1946-1953.

Dierkesmann R., "Indication and Results of Endobronchial Laser Therapy," *Lung*, 1990, 168, 1095-1102.

Fazio F., et al., "Assessment of Regional Ventilation by Continuous Inhalation of Radioactive Krypton-81 m," *British Medical Journal*, 1975, vol. 3 (5985), pp. 673-676.

Global Strategy for Asthma Management and Prevention, National Institute of Health, National Heart, Lung and Blood Institute, 2002, 192 pages.

Hogg J. C., "The Pathology of Asthma," *APMIS*, 1997, 105 (10), 735-745.

International Search Report for Application No. PCT/US00/05412, dated Jun. 20, 2000, 2 pages.

International Search Report for Application No. PCT/US00/18197, dated Oct. 3, 2000, 1 page.

International Search Report for Application No. PCT/US00/28745, dated Mar. 28, 2001, 6 pages.

International Search Report for Application No. PCT/US01/32321, dated Jan. 18, 2002, 2 pages.

International Search Report for Application No. PCT/US98/03759, dated Jul. 30, 1998, 1 page.

International Search Report for Application No. PCT/US98/26227, dated Mar. 25, 1999, 1 page.

International Search Report for Application No. PCT/US99/00232, dated Mar. 4, 1999, 1 page.

International Search Report for Application No. PCT/US99/12986, dated Sep. 29, 1999, 1 page.

Ivanyuta O.M., et al., "Effect of Low-Power Laser Irradiation of Bronchial Mucosa on the State of Systemic and Local Immunity in Patients with Chronic Bronchitis," *Problemy Tuberkuleza*, 1991, 6, 26-29.

James A.L., et al., "The Mechanics of Airway Narrowing in Asthma," *American Review of Respiratory Diseases*, 1989, 139 (1), 242-246.

Janssen L.J., "Asthma Therapy: How Far have We Come, Why did We Fail and Where should We Go Next", *European Respiratory Journal*, 2009, 33 (1), 11-20.

Jeffery P.K., "Remodeling in Asthma and Chronic Obstructive Lung Disease," *American Journal of Respiratory and Critical Care Medicine*, 2001, 164 (10), S28-S38.

Johnson S. R., et al., "Synthetic Functions of Airway Smooth Muscle in Asthma," *Trends Pharmacol. Sci.*, 1997, 18 (8), 288-292.

Kitamura S., "Color Atlas of Clinical Application of Fiberoptic Bronchoscopy," 1990, Year Book Medical Publishers, 2 pages.

Kraft M., "The Distal Airways: Are they Important in Asthma", *European Respiratory Journal*, 1999, 14 (6), 1403-1417.

Laviolette M., et al., "Asthma Intervention Research (AIR) Trial: Early Safety Assessment of Bronchial Thermoplasty," *American Journal of Respiratory and Critical Care Medicine*, 2004, 169, A314.

Leff A., et al., "Bronchial Thermoplasty Alters Airway Smooth Muscle and Reduces Responsiveness in Dogs: A Possible Procedure for the Treatment of Asthma," *American Thoracic Society Annual Meeting*, 2002, 1 page.

Lim E.C., et al., "Botulinum Toxin: A Novel Therapeutic Option for Bronchial Asthma", *Medical Hypotheses*, 2006, 66 (5), 915-919.

Lombard C.M., et al., "Histologic Effects of Bronchial Thermoplasty of Canine and Human Airways," *American Thoracic Society Annual Meeting*, 2002, 1 page.

Macklem P. T., "Mechanical Factors Determining Maximum Bronchoconstriction," *European Respiratory Journal*, 1989, 6, 516s-519s.

Mayne M.L., et al., "Clinical Pearls for Bronchial Thermoplasty," *Journal of Bronchology*, 2007, 14 (2), 115-123.

Miller J.D., et al., "A Prospective Feasibility Study of Bronchial Thermoplasty in the Human Airway," *Chest*, 2005, 127 (6), 1999-2006.

Miller J.D., et al., "Bronchial Thermoplasty is Well Tolerated By Non-Asthmatic Patients Requiring Lobectomy," *American Thoracic Society Annual Meeting*, 2002, 1 page.

Mitzner W., "Airway Smooth Muscle The Appendix of the Lung," *American Journal of Respiratory and Critical Care Medicine*, 2004, 169 (7), 787-790.

(56)

References Cited

OTHER PUBLICATIONS

- Mitzner W., "Bronchial Thermoplasty in Asthma," *Allergy International*, 2006, 55 (3), 225-234.
- Netter F.H., "Respiratory System: A Compilation of Paintings Depicting Anatomy and Embryology, Physiology, Pathology, Pathophysiology, and Clinical Features and Treatment of Diseases, In The CIBA Collection of Medical Illustrations M.B. Divertie, ed., Summit: New Jersey," 1979, 7, 119-135.
- Non-Final Office Action for U.S. Appl. No. 11/361,564, dated Apr. 29, 2010. 12 pages.
- Non-Final Office Action for U.S. Appl. No. 11/361,564, dated Jan. 22, 2009. 8 pages.
- Notice of final Rejection, Japanese Patent Application No. 2000-553172, dated Sep. 2, 2008, 5 pages.
- Pitris C., et al., "High Resolution Imaging of the Upper Respiratory Tract with Optical Coherence Tomography: A Feasibility Study," *American Journal of Respiratory and Critical Care Medicine*, 1998, vol. 157 (5 Pt 1), pp. 1640-1644.
- Provotorov V.M., et al., "The Clinical Efficacy of Treating Patients with Nonspecific Lung Diseases Using Low-energy Laser Irradiation and Intrapulmonary Drug Administration," *Terapevticheskii Arkhiv*, 1991, 62 (12), 18-23.
- Rubin A., et al., "Bronchial Thermoplasty Improves Asthma Status of Moderate to Severe Persistent Asthmatics Over and Above Current Standard-of-Care," *American College of Chest Physicians*, 2006, 2 pages.
- Seow C.Y., et al., "Historical Perspective on Airway Smooth Muscle: The Saga of a Frustrated Cell," *Journal of Applied Physiology*, 2001, 91 (2), 938-952.
- Shesterina M.V., et al., "Effect of Laser Therapy on Immunity in Patients with Bronchial Asthma and Pulmonary Tuberculosis," *Problemy Tuberkuleza*, 1994, 5, 23-26.
- Shore S.A., "Airway Smooth Muscle in Asthma—Not Just More of the Same," *New England Journal of Medicine*, 2004, 351 (6), 531-532.
- Solway J., et al., "Airway Smooth Muscle as a Target for Asthma Therapy," *New England Journal of medicine*, 2007, 356 (13), 1367-1369.
- Sterk P.J., et al., "Heterogeneity of Airway Hyperresponsiveness: Time for Unconventional, But Traditional, Studies," *Journal of Applied Physiology*, 2004, 96 (6), 2017-2018.
- Toma T.P., et al., "Brave New World for Interventional Bronchoscopy," *Thorax*, 2005, 60 (3), 180-181.
- Trow T.K., "Clinical Year in Review I: Diagnostic Imaging, Asthma, Lung Transplantation, and Interventional Pulmonology," *Proceedings of the American Thoracic Society*, 2006, 3 (7), 553-556.
- UNSW Embryo—Respiratory System [online], *Embryology*, 2007, [retrieved on Dec. 10, 2007]. Retrieved from the internet: (URL:<http://embryology.med.unsw.edu.au/Refer/respire/slect.htm>).
- Vasilotta P.L., et al., "I-R Laser: A New Therapy in Rhino-Sino-Nasal Bronchial Syndrome with Asthmatic Component," *American Society for Laser Medicine and Surgery Abstracts*, 74, 1993.
- Vorotnev A.I., et al., "The Treatment of Patients with Chronic Obstructive Bronchitis by Using a Low-power Laser at a General Rehabilitation Center," *Terapevticheskii Arkhiv*, 1997, 69 (3), 17-19.
- Wiggs B.R., et al., "On the Mechanism of Mucosal Folding in Normal and Asthmatic Airways," *Journal of Applied Physiology*, 1997, 83 (6), 1814-1821.
- Wilson S.R., et al., "Global Assessment after Bronchial Thermoplasty: The Patients Perspective," *Journal of Outcomes Research*, 2006, 10, 37-46.
- Wizeman W., et al., "A Computer Model of Thermal Treatment of Airways by Radiofrequency (RF) Energy Delivery," *American Thoracic Society Annual Meeting*, 2007, 1 page.
- Mitchell et al., "Video-imaging of lumen narrowing; muscle shortening and flow responsiveness in isolated bronchial segments of the pig," *Eur Respir J. Jul.* 1994; 7(7), pp. 1317-1325.
- Templeton et al., "Effects of S-salbutamol on Human Isolated Bronchus". *Pulmonary Pharmacology & Therapeutics* Feb. 1998; 11(1), pp. 1-6.
- Douglas et al. "The Effect of Antispasmodic Drugs on the Endomural Bronchial (or "Squeeze") Pressures in Bronchitis and Asthma." *American Review of Respiratory Disease*, 1966; 93(5), pp. 703-715.
- Douglas et al. "The Measurement of Endomural Bronchial (or "Squeeze") Pressures in Bronchitis and Asthma." *American Review of Respiratory Disease*, 1966; 93(5), pp. 693-702.
- Crofton et al. "The Measurement of Bronchial Endomural or 'Squeeze' Pressure." *Thorax*. 1963;18(1):68-76.




FIG. 1




FIG. 2




FIG. 3




FIG. 4A





FIG. 4B








Fig 5







FIG 6C






FIG 6E 164




FIG 6F




FIG. 7




FIG. 8

METHODS FOR TREATING AIRWAYS**CROSS REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. patent application Ser. No. 14/171,973, filed Feb. 4, 2014, which is a continuation of U.S. patent application Ser. No. 13/557,518, filed Jul. 25, 2012, now, which is a continuation of U.S. patent application Ser. No. 11/398,353, filed Apr. 4, 2006, now U.S. Pat. No. 8,251,070, the entireties of each of which are incorporated herein by reference. This application is related to U.S. patent application Ser. No. 10/640,967, filed Aug. 13, 2003, and U.S. patent application Ser. No. 09/535,856, filed Mar. 27, 2000, the entireties of each of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

The invention relates to a method of treating a lung having at least one symptom of reversible obstructive pulmonary disease, and more particularly, methods of treating airways in a lung to decrease asthmatic symptoms of the lung, by measuring a parameter of an airway at a plurality of locations in a lung, identifying at least one treatment site from at least one of the plurality of locations based on the parameter; and applying energy to the treatment site to reduce the ability of the site to narrow.

Reversible obstructive pulmonary disease includes asthma and reversible aspects of chronic obstructive pulmonary disease (COPD). Asthma is a disease in which (i) bronchoconstriction, (ii) excessive mucus production, and (iii) inflammation and swelling of airways occur, causing widespread but variable airflow obstruction thereby making it difficult for the asthma sufferer to breathe. Asthma is further characterized by acute episodes of airway narrowing via contraction of hyper-responsive airway smooth muscle.

The reversible aspects of COPD include excessive mucus production and partial airway occlusion, airway narrowing secondary to smooth muscle contraction, and bronchial wall edema and inflation of the airways. Usually, there is a general increase in bulk (hypertrophy) of the large bronchi and chronic inflammatory changes in the small airways. Excessive amounts of mucus are found in the airways and semisolid plugs of mucus may occlude some small bronchi. Also, the small airways are narrowed and show inflammatory changes.

In asthma, chronic inflammatory processes in the airway play a central role in increasing the resistance to airflow within the lungs. Many cells and cellular elements are involved in the inflammatory process, particularly mast cells, eosinophils T lymphocytes, neutrophils, epithelial cells, and even airway smooth muscle itself. The reactions of these cells result in an associated increase in sensitivity and hyper-responsiveness of the airway smooth muscle cells lining the airways to particular stimuli.

The chronic nature of asthma can also lead to remodeling of the airway wall (i.e., structural changes such as airway wall thickening or chronic edema) that can further affect the function of the airway wall and influence airway hyper-responsiveness. Epithelial denudation exposes the underlying tissue to substances that would not normally otherwise contact the underlying tissue, further reinforcing the cycle of cellular damage and inflammatory response.

In susceptible individuals, asthma symptoms include recurrent episodes of shortness of breath (dyspnea), wheez-

ing, chest tightness, and cough. Currently, asthma is managed by a combination of stimulus avoidance and pharmacology.

Stimulus avoidance is accomplished via systematic identification and minimization of contact with each type of stimuli. It may, however, be impractical and not always helpful to avoid all potential stimuli.

Asthma is managed pharmacologically by: (1) long term control through use of anti-inflammatories and long-acting bronchodilators and (2) short term management of acute exacerbations through use of short-acting bronchodilators. Both of these approaches require repeated and regular use of the prescribed drugs. High doses of corticosteroid anti-inflammatory drugs can have serious side effects that require careful management. In addition, some patients are resistant to steroid treatment. The difficulty involved in patient compliance with pharmacologic management and the difficulty of avoiding stimulus that triggers asthma are common barriers to successful asthma management.

Asthma is a serious disease with growing numbers of sufferers. Current management techniques are neither completely successful nor free from side effects.

Accordingly, it would be desirable to provide an asthma treatment which improves airflow without the need for patient compliance.

In addition to the airways of the lungs, other body conduits such as the esophagus, ureter, urethra, and coronary arteries, are also subject to inflammation and periodic reversible spasms that produce obstruction to flow.

SUMMARY OF THE INVENTION

The present invention relates to methods for treating a lung, preferably having at least one symptom of reversible obstructive pulmonary disease, comprising the steps of advancing a treatment device into the lung and treating the lung with the device to at least reduce the ability of the lung to produce at least one symptom of reversible obstructive pulmonary disease and to decrease the resistance to the flow of air through the lung.

A variation of the invention includes the method described above further comprising the step of locating one or more treatment sites within an airway of the lung, selecting at least one of the treatment sites and treating at least one of the treatment sites selected in the selecting step. The invention may further include performing the steps while the lung is experiencing at least one symptom of either natural or artificially induced reversible obstructive pulmonary disease.

A further variation of the invention includes the method described above and further includes the steps of testing the lung for at least one pre-treatment pulmonary function value prior to the treating step, and re-testing the lung for at least one post-treatment pulmonary function value subsequent to the treating step.

A further variation of the invention includes the method described above further comprising identifying treatment sites within the airway being highly susceptible to either airway inflammation, airway constriction, excessive mucus secretion, or any other symptom of reversible obstructive pulmonary disease.

Another variation of the invention includes the method described above and the additional step of stimulating the lung to produce at least one artificially induced symptom of reversible obstructive pulmonary disease. The invention may further comprise the step of evaluating the results of the stimulating step.

Another variation of the invention includes the method described above where treating at least airway tissue within the lung further comprises the step of determining the effect of the treatment by visually observing the airway for blanching, or a change in appearance, of airway tissue.

Another variation of the invention includes the method described above where treating at least airway tissue at a treatment site within the lung further comprises the step of monitoring electrical impedance of tissue at one or more points.

Another variation of the invention includes the method described above where treating the lung includes sub-mucosal treatment of at least airway tissue in the lung.

Another variation of the invention includes the method described above where the treating step includes treating the lung by depositing a radioactive substance in at least one treatment site within the lung.

Another variation of the invention include the method described above further including the step of scraping tissue from a wall of an airway within the lung prior to the treating step. The invention may further comprise depositing a substance on the scraped wall of the airway.

Another variation of the invention includes the method described above where the treating step uses a modality selected from the group consisting of mechanical, chemical, radio frequency, radioactive energy, heat, and ultrasound.

Another variation of the invention includes the method described above further comprising pre-treating the lung to at least reduce the ability of the lung to produce at least one symptom of reversible obstructive pulmonary disease prior to the treating step, where at least one parameter of the pre-treating step is lesser than at least one parameter of the treating step.

Another variation of the invention comprises the method described above where the treating step includes separating the treating step into stages to reduce the healing load on the lung. The separating step may comprise treating different regions of the lung at different times or dividing the number of treatment sites into a plurality of groups of treatment sites and treating each group at a different time.

Another variation of the invention includes the method described above further comprising sensing movement of the lung and repositioning the treatment device in response to said sensing step.

Another variation of the invention includes the method described above further comprising reducing the temperature of lung tissue adjacent to a treatment site.

Another variation of the invention includes the method described above further comprising the step of providing drug therapy, exercise therapy, respiratory therapy, and/or education on disease management techniques to further reduce the effects of reversible obstructive pulmonary disease.

The invention further includes the method for reversing a treatment to reduce the ability of the lung to produce at least one symptom of reversible obstructive pulmonary disease comprising the step of stimulating re-growth of smooth muscle tissue in the lung.

The invention further includes the method of evaluating an individual having reversible obstructive pulmonary disease as a candidate for a procedure to reduce the ability of the individual's lung to produce at least one reversible obstructive pulmonary disease symptom by treating an airway within the lung of the individual, the method comprising the steps of assessing the pulmonary condition of the individual, comparing the pulmonary condition to a corresponding predetermined state; and evaluating the individual

based upon the comparing step. The method may additionally comprise the steps of performing pulmonary function tests on the individual to obtain at least one pulmonary function value, comparing the at least one pulmonary function value to a corresponding predetermined pulmonary function value, and evaluating the individual based upon the comparing step.

The invention further comprises a method of evaluating the effectiveness of a procedure to reduce the ability of lung to produce at least one symptom of reversible obstructive pulmonary disease previously performed on an individual having reversible obstructive pulmonary disease, the method comprising the steps of assessing the pulmonary condition of the individual, comparing the pulmonary condition to a corresponding predetermined state; and evaluating the effectiveness of the procedure based upon the comparing step. The method may additionally comprise the steps of performing pulmonary function tests on the individual to obtain at least one pulmonary function value, treating the lung to at least reduce the ability of the lung to produce at least one symptom of reversible obstructive pulmonary disease, performing post-procedure pulmonary function tests on the individual to obtain at least one post-procedure pulmonary function value; and comparing the pulmonary function value with the post-procedure pulmonary function value to determine the effect of the treating step.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will now be described in greater detail with reference to the various embodiments illustrated in the accompanying drawings:

FIG. 1 is a cross sectional view of an airway in a healthy lung.

FIG. 2 shows a section through a bronchiole having an airway diameter smaller than that shown in FIG. 1.

FIG. 3 illustrates the airway of FIG. 1 in which the smooth muscle 14 has hypertrophied and increased in thickness causing reduction of the airway diameter.

FIG. 4A is a schematic view of the lungs being treated with a treatment device as described herein.

FIG. 4B illustrates one example of a treatment system for use with the methods described herein.

FIG. 4C illustrates another variation of a treatment system that applies the treatment externally to the lungs.

FIG. 5 illustrates a map to aid in treatment of the airways.

FIG. 6A illustrates a device that stimulates the airway into contracting.

FIGS. 6B-6F illustrate various modes of measuring parameters within the lungs to identify treatment sites.

FIG. 7 is a side view of a device extending out of an endoscope/bronchoscope, where the device has an active distal end for treating tissue using energy delivery.

FIG. 8 shows various features of a device allowing for low force deployment of an energy element.

DETAILED DESCRIPTION

The invention relates to methods for improving airflow through the airways of a lung having reversible obstructive pulmonary disease. It is intended that the invention is applicable to any aspect of reversible obstructive pulmonary disease, including but not limited to asthma. One way of improving airflow is to decrease the resistance to airflow within the lungs. There are several approaches to reducing this resistance, including but not limited to reducing the ability of the airway to contract, increasing the airway

diameter, reducing the inflammation of airway tissues, and/or reducing the amount of mucus plugging of the airway. Another approach to reducing resistance is to increase the resting airway diameter of an airway such that any subsequent narrowing will not reduce the airway to a diameter such that obstruction to airflow is discernable by the patient. The present invention includes advancing a treatment device into the lung and treating the lung to at least reduce the ability of the lung to produce at least one symptom of reversible obstructive pulmonary disease. The following is a brief discussion of some causes of increased resistance to airflow within the lungs and the inventive treatment of the invention described herein. As such, the following discussion is not intended to limit the aspects or objective of the inventive method as the inventive method may cause physiological changes not described below but such changes still contributing to reducing or eliminating at least one of the symptoms of reversible obstructive pulmonary disease.

Reducing the Ability of the Airway to Contract

The inventive treatment reduces the ability of the airways to narrow or to reduce in diameter due to airway smooth muscle contraction. The inventive treatment uses a modality of treatments including, but not limited to the following: chemical, radio frequency, radioactivity, heat, ultrasound, radiant, laser, microwave, or mechanical energy (such as in the form of cutting, punching, abrading, rubbing, or dilating). This treatment reduces the ability of the smooth muscle to contract thereby lessening the severity of an asthma attack. The reduction in the ability of the smooth muscle to contract may be achieved by treating the smooth muscle itself or by treating other tissues which in turn influence smooth muscle contraction or the response of the airway to narrow or to constrict in response to a stimulus.

The amount of smooth muscle surrounding the airway can be reduced by exposing the smooth muscle to energy which either kills the muscle cells or prevents these cells from replicating. The reduction in smooth muscle reduces the ability of the smooth muscle to contract and to narrow the airway during a spasm. The reduction in smooth muscle and surrounding tissue has the added potential benefit of increasing the caliber or diameter of the airways, which further reduces the resistance to airflow through the airways. In addition to the use of debulking smooth muscle tissue to open up the airways, the device used in the present invention may also eliminate smooth muscle altogether by damaging or destroying the muscle. The elimination of the smooth muscle prevents the contraction or spasms of hyper-reactive airways of a patient having reversible obstructive pulmonary disease. By doing so, the elimination of the smooth muscle may reduce some symptoms of reversible obstructive pulmonary disease.

The ability of the airway to contract can also be altered by treatment of the smooth muscle in particular patterns. The smooth muscle is arranged around the airways in a generally helical pattern with pitch angles ranging from about -38 to about $+38$ degrees. Thus, the treatment of the smooth muscle in appropriate patterns interrupts or cuts through the helical pattern of the smooth muscle at a proper pitch and prevents the airway from constricting. This procedure of patterned treatment application eliminates contraction of the airways without completely eradicating smooth muscle and other airway tissue. A pattern for treatment may be chosen from a variety of patterns including longitudinal or axial stripes, circumferential bands, helical stripes, and the like as well as spot patterns having rectangular, elliptical, circular or other

shapes. The size, number, and spacing of the treatment bands, stripes, or spots are chosen to provide a desired clinical effect of reduced airway responsiveness while limiting insult to the airway to a clinically acceptable level.

The patterned treatment of the tissues surrounding the airways with energy provides various advantages. The careful selection of the portion of the airway to be treated allows desired results to be achieved while reducing the total healing load. Patterned treatment can also achieve desired results with decreased morbidity, preservation of epithelium, and preservation of a continuous or near continuous ciliated inner surface of the airway for mucociliary clearance. The pattern of treatment may also be chosen to achieve desired results while limiting total treatment area and/or the number of airways treated, thereby improving speed and ease of treatment.

Application of energy to the tissue surrounding the airways may also cause the DNA of the cells to become cross linked. The treated cells with cross linked DNA are incapable of replicating. Accordingly, over time, as the smooth muscle cells die, the total thickness of smooth muscle decreases because of the inability of the cells to replicate. The programmed cell death causing a reduction in the volume of tissue is called apoptosis. This treatment does not cause an immediate effect but causes shrinking of the smooth muscle and opening of the airway over time and substantially prevents re-growth. The application of energy to the walls of the airway may also be used to cause a cross linking of the DNA of the mucus gland cells thereby preventing them from replicating and reducing excess mucus plugging or production over time.

The ability of the airways to contract may also be reduced by altering mechanical properties of the airway wall, such as by increasing stiffness of the wall or by increasing parenchymal tethering of the airway wall. Both of these methods increase the strength of the airway wall and further oppose contraction and narrowing of the airway.

There are several ways to increase the stiffness of the airway wall. One way to increase stiffness is to induce fibrosis or a wound healing response by causing trauma to the airway wall. The trauma can be caused by delivery of therapeutic energy to the tissue in the airway wall, by mechanical insult to the tissue, or by chemically affecting the tissue. The energy is preferably delivered in such a way that it minimizes or limits the intra-luminal thickening that may occur.

Another way to increase the effective stiffness of the airway wall is to alter the submucosal folding of the airway upon narrowing. The mucosal layer includes the epithelium, its basement membrane, and the lamina propria, a subepithelial collagen layer. The submucosal layer may also play a role in airway folding. As an airway narrows, its perimeter remains relatively constant, with the mucosal layer folding upon itself. As the airway narrows further, the mucosal folds mechanically interfere with each other, effectively stiffening the airway. In asthmatic patients, the number of folds is fewer and the size of the folds is larger, and thus, the airway is free to narrow with less mechanical interference of mucosal folds than in a healthy patient. Thus, asthmatic patients have a decrease in airway stiffness and the airways have less resistance to narrowing.

The mucosal folding in asthmatic patients can be improved by treatment of the airway in a manner which encourages folding. Preferably, a treatment will increase the number of folds and/or decrease the size of the folds in the mucosal layer. For example, treatment of the airway wall in

a pattern such as longitudinal stripes can encourage greater number of smaller mucosal folds and increase airway stiffness.

The mucosal folding can also be increased by encouraging a greater number of smaller folds by reducing the thickness of the mucosa and/or submucosal layer. The decreased thickness of the mucosa or submucosa may be achieved by application of energy which either reduces the number of cells in the mucosa or submucosal layer or which prevents replication of the cells in the mucosa or submucosal layer. A thinner mucosa or submucosal layer will have an increased tendency to fold and increased mechanical stiffening caused by the folds.

Another way to reduce the ability of the airways to contract is to improve parenchymal tethering. The parenchyma surrounds airways and includes the alveolus and tissue connected to and surrounding the outer portion of the airway wall. The parenchyma includes the alveolus and tissue connected to and surrounding the cartilage that supports the larger airways. In a healthy patient, the parenchyma provides a tissue network which connects to and helps to support the airway. Edema or accumulation of fluid in lung tissue in patients with asthma or COPD is believed to decouple the airway from the parenchyma reducing the restraining force of the parenchyma which opposes airway constriction. Energy can be used to treat the parenchyma to reduce edema and/or improve parenchymal tethering.

In addition, the applied energy may be used to improve connection between the airway smooth muscle and submucosal layer to the surrounding cartilage, and to encourage wound healing, collagen deposition, and/or fibrosis in the tissue surrounding the airway to help support the airway and prevent airway contraction.

Increasing the Airway Diameter

Hypertrophy of smooth muscle, chronic inflammation of airway tissues, and general thickening of all parts of the airway wall can reduce the airway diameter in patients with reversible obstructive pulmonary disease. Increasing the overall airway diameter using a variety of techniques can improve the passage of air through the airways. Application of energy to the airway smooth muscle of an asthmatic patient can debulk or reduce the volume of smooth muscle. This reduced volume of smooth muscle increases the airway diameter for improved air exchange.

Reducing inflammation and edema of the tissue surrounding the airway can also increase the diameter of an airway. Inflammation and edema (accumulation of fluid) of the airway are chronic features of asthma. The inflammation and edema can be reduced by application of energy to stimulate wound healing and regenerate normal tissue. Healing of the epithelium or sections of the epithelium experiencing ongoing denudation and renewal allows regeneration of healthy epithelium with less associated airway inflammation. The less inflamed airway has an increased airway diameter both at a resting state and in constriction. The wound healing can also deposit collagen which improves parenchymal tethering.

Inflammatory mediators released by tissue in the airway wall may serve as a stimulus for airway smooth muscle contraction. Therapy that reduces the production and release of inflammatory mediator can reduce smooth muscle contraction, inflammation of the airways, and edema. Examples of inflammatory mediators are cytokines, chemokines, and histamine. The tissues which produce and release inflammatory mediators include airway smooth muscle, epithelium, and mast cells. Treatment of these structures with

produce or release inflammatory mediators. The reduction in released inflammatory mediators will reduce chronic inflammation, thereby increasing the airway inner diameter, and may also reduce hyper-responsiveness of the airway smooth muscle.

A further process for increasing the airway diameter is by denervation. A resting tone of smooth muscle is nerve regulated by release of catecholamines. Thus, by damaging or eliminating nerve tissue in the airways the resting tone of the smooth muscle is reduced, and the airway diameter is increased. Resting tone may also be reduced by directly affecting the ability of smooth muscle tissue to contract.

Reducing Plugging of the Airway

Excess mucus production and mucus plugging are common problems during both acute asthma exacerbation and in chronic asthma management. Excess mucus in the airways increases the resistance to airflow through the airways by physically blocking all or part of the airway. Excess mucus may also contribute to increased numbers of leukocytes found in airways of asthmatic patients by trapping leukocytes. Thus, excess mucus can increase chronic inflammation of the airways.

One type of asthma therapy involves treatment of the airways with energy to target and reduce the amount of mucus producing cells, ducts, and glands and to reduce the effectiveness of the remaining mucus producing cells and glands. The treatment can eliminate all or a portion of the mucus producing cells, ducts, and glands, can prevent the cells from replicating or can inhibit their ability to secrete mucus. This treatment will have both chronic benefits in increasing airflow through the airways and will lessen the severity of acute exacerbation of the symptoms of reversible obstructive pulmonary disease.

Application of Treatment

The following illustrations are examples of the invention described herein. It is contemplated that combinations of aspects of specific embodiments or combinations of the specific embodiments themselves are within the scope of this disclosure.

FIGS. 1 and 2 illustrate cross sections of two different airways in a healthy patient. The airway of FIG. 1 is a medium sized bronchus having an airway diameter D1 of about 3 mm. FIG. 2 shows a section through a bronchiole having an airway diameter D2 of about 1.5 mm. Each airway includes a folded inner surface or epithelium 10 surrounded by stroma 12 and smooth muscle tissue 14. The larger airways including the bronchus shown in FIG. 1 also have mucous glands 16 and cartilage 18 surrounding the smooth muscle tissue 14. Nerve fibers 20 and blood vessels 24 also surround the airway.

FIG. 3 illustrates the bronchus of FIG. 1 in which the smooth muscle 14 has hypertrophied and increased in thickness causing the airway diameter to be reduced from the diameter D1 to a diameter D3.

FIG. 4A is a schematic side view of the lungs being treated with a treatment device 38 according to the present invention. The treatment device 100 is an elongated member for treating tissue at a treatment site 34 within a lung. Although the invention discusses treatment of tissue at the airway wall surface it is also intended that the invention include treatment below an epithelial layer of the lung tissue. The invention may also rely on the use of an imaging device 36 to enable the identification of at least one treatments site from the plurality of possible treatment site locations. The imaging device may employ radiographic visualization such as fluoroscopy or other external visualization means such as computer aided tomography (CT), magnetic resonance

imaging (MRI), positron emission tomography (PET), optical coherence tomography, or ultrasonic imaging. The imaging device may be external as shown. Alternatively, the imaging device may have a component that is affixed to the treatment system **32** or otherwise is inserted in to the body.

FIG. **4B** represents one example of a treatment system **32** according to the present invention. In this variation, the system **32** delivers therapeutic energy to tissue of a patient via a device **100**. Variations of devices are described in U.S. application Ser. Nos. 11/255,796 and 11/256,295 both filed Oct. 21, 2005 and the entirety of each of which is incorporated by reference.

FIG. **4B** shows a schematic diagram of one example of a system **32** for delivering therapeutic energy to tissue of a patient for use with the device described herein. The illustrated variation shows, the system **32** having a power supply (e.g., consisting of an energy generator **112**, a controller **114** coupled to the energy generator, a user interface surface **116** in communication with the controller **114**). It is noted that the device may be used with a variety of systems (having the same or different components). For example, although variations of the device shall be described as RF energy delivery devices, variations of the device may include resistive heating systems, infrared heating elements, microwave energy systems, focused ultrasound, cryo-ablation, or any other energy deliver system. It is noted that the devices described should have sufficient length to access the tissue targeted for treatment. For example, it is presently believed necessary to treat airways as small as 3 mm in diameter to treat enough airways for the patient to benefit from the described treatment (however, it is noted that the invention is not limited to any particular size of airways and airways smaller than 3 mm may be treated). Accordingly, devices for treating the lungs must be sufficiently long to reach deep enough into the lungs to treat these airways. Accordingly, the length of the sheath/shaft of the device that is designed for use in the lungs should preferably be between 1.5-3 ft long in order to reach the targeted airways.

The particular system **32** depicted in FIG. **4B** is one having a user interface as well as safety algorithms that are useful for the asthma treatment discussed above. Additional information on such a system may be found in U.S. Provisional application Nos. 60/674,106, and 60/673,876 both filed Apr. 21, 2005 the entirety of each of which is incorporated by reference herein.

Referring again to FIG. **4B**, a variation of a device **100** described herein includes a flexible sheath **202**, an elongate shaft **204** (in this example, the shaft extends out from the distal end of the sheath **202**), and a handle or other operator interface **206** (optional) secured to a proximal end of the sheath **202**. The distal portion of the device **100** includes an energy transfer element **208** (e.g., an electrode, a basket electrode, a resistive heating element, cryoprobe, etc.). Additionally, the device includes a connector **210** common to such energy delivery devices. The connector **210** may be integral to the end of a cable **212** as shown, or the connector **210** may be fitted to receive a separate cable **212**. In any case, the device is configured for attachment to the power supply via some type connector **210**. The elongate portions of the device **202** and **204** may also be configured and sized to permit passage through the working lumen of a commercially available bronchoscope or endoscope. As discussed herein, the device is often used within an endoscope, bronchoscope or similar device. However, the device may also be advanced into the body with or without a steerable catheter,

in a minimally invasive procedure or in an open surgical procedure, and with or without the guidance of various vision or imaging systems.

FIG. **4B** also illustrates additional components used in variations of the system. Although the depicted systems are shown as RF type energy delivery systems, it is noted that the invention is not limited as such. Other energy delivery configurations contemplated may include or not require some of the elements described below. The power supply (usually the user interface portion **116**) shall have connections **120**, **128**, **130** for the device **100**, return electrode **124** (if the system **32** employs a monopolar RF configuration), and actuation pedal(s) **126** (optional). The power supply and controller may also be configured to deliver RF energy to an energy transfer element configured for bipolar RF energy delivery. The user interface **116** may also include visual prompts **132**, **160**, **168**, **174** for user feedback regarding setup or operation of the system. The user interface **116** may also employ graphical representations of components of the system, audio tone generators, as well as other features to assist the user with system use.

In many variations of the system, the controller **114** includes a processor **122** that is generally configured to accept information from the system and system components, and process the information according to various algorithms to produce control signals for controlling the energy generator **112**. The processor **122** may also accept information from the system **110** and system components, process the information according to various algorithms and produce information signals that may be directed to the visual indicators, digital display or audio tone generator of the user interface in order to inform the user of the system status, component status, procedure status or any other useful information that is being monitored by the system. The processor **122** of the controller **114** may be digital IC processor, analog processor or any other suitable logic or control system that carries out the control algorithms.

In one variation of the system shown in FIG. **4B**, the RF generator **112** generates RF energy at a frequency of about 400 kHz to about 500 kHz in with a wattage output sufficient to maintain a target tissue temperature of about 60 degrees C. to about 80 degrees C., specifically, about 60 degrees C. to about 70 degrees C. (when measuring at a surface of the electrode). The duration of the activation state for an embodiment of a single treatment cycle may be about 1 seconds to about 15 seconds, specifically, about 8 seconds to about 12 seconds. Alternatively, the duration of the activation state of the RF generator may also be set to not more than the duration required to deliver about 150 Joules of energy to the target tissue, specifically, not more than the duration required to deliver about 125 Joules of RF energy to target tissue.

Additional examples of devices for use with the methods of this invention are found in the following U.S. patent application Ser. Nos. 09/095,323 and 09/436,455; U.S. Pat. Nos. 6,488,673 and 6,411,852. The entirety of each of the aforementioned applications is incorporated by reference herein.

FIG. **4C** represents another schematic side view of lungs being treated with a treatment device **100** according to the present invention. In this variation, the treatment device **100** and system **32** are external to the lungs and/or body but still applies energy to within the lungs. For example, such a treatment may use a high frequency ultrasound (commonly referred to as HIFU). As discussed above, the invention may also rely on the use of an imaging device **36**.

The treatment of an airway with the treatment device may involve placing a visualization system such as an endoscope or bronchoscope into the airways. The treatment device is then inserted through or next to the bronchoscope or endoscope while visualizing the airways. Alternatively, the visualization system may be built directly into the treatment device using fiber optic imaging and lenses or a CCD and lens arranged at the distal portion of the treatment device. The treatment device may also be positioned using radiographic visualization such as fluoroscopy or other external visualization means. The treatment device which has been positioned with a distal end within an airway to be treated is energized so that energy is applied to the tissue of the airway walls in a desired pattern and intensity. The distal end of the treatment device may be moved through the airway in a uniform painting like motion to expose the entire length of an airway to be treated to the energy. The treatment device may be passed axially along the airway one or more times to achieve adequate treatment. The "painting-like" motion used to expose the entire length of an airway to the energy may be performed by moving the entire treatment device from the proximal end either manually or by motor. Alternatively, segments, stripes, rings or other treatment patterns may be used.

According to one variation of the invention, the energy is transferred to or from an airway wall in the opening region of the airway, preferably within a length of approximately two times the airway diameter or less, and to wall regions of airways distal to bifurcations and side branches, preferably within a distance of approximately twice the airway diameter or less. The invention may also be used to treat long segments of un-bifurcated airway.

The invention includes a method of advancing a treatment device into a lung and treating the lung with the device to, at least, reduce the ability of the lung to produce at least one symptom of reversible obstructive pulmonary disease. It is contemplated that the treatment may reduce all of the symptoms of reversible obstructive disease. Alternatively, the treatment may be selected to address specific symptoms of the disease. It is also intended that the treatment of the lung may sufficiently reduce the symptoms of reversible obstructive pulmonary disease such that the patient is able to function as those free from the disease. Alternatively, the treatment may be such that the symptoms are reduced to allow the patient to more easily manage the disease. It is also intended that the effects of the treatment may be either long term or short term with repeating treatment necessary to suppress the symptoms.

The methods of the invention described herein may be performed while the lung is experiencing natural symptoms of reversible obstructive pulmonary disease. One such example is where an individual, experiencing an asthma attack, or acute exacerbation of asthma or COPD, undergoes treatment to improve the individual's ability to breath. In such a case, the treatment, called 'rescue,' seeks to provide immediate relief for the patient.

The method may also include the steps of locating one or more treatment sites within an airway of the lung, selecting one of the treatment sites from the locating step and treating at least one of the selected treatment sites. As mentioned above, these steps may be, but are not necessarily, performed while the lung is experiencing symptoms of reversible obstructive pulmonary disease.

The invention may further comprise the step of stimulating the lung to produce at least one artificially induced symptom of reversible obstructive pulmonary disease. For example, stimulation of the lung would preferably increase

the resistance to airflow within the lung, constrict airways within the lung, inflame/irritate airway tissues, increase edema and/or increase the amount of mucus plugging of the airway. Stimulation of the lung may occur at any point during the procedure or before the procedure. For example, the lung may be stimulated either prior to or after, the step of locating a treatment site. If the lung is stimulated prior to the step of locating a treatment site, the reaction of the stimulated tissue within the lung may be useful in determining which locations are to be selected as treatment sites. The lung tissue or airway tissue within the lung may be stimulated by a variety of methods including but not limited to pharmacological stimulation, (e.g., histamine, methacholine, or other bronchoconstricting agents, etc.), electrical stimulation, mechanical stimulation, or any other stimuli causing obstructive pulmonary symptoms. For example, electrical stimulation may comprise exposing airway tissue to electrical field stimulation. An example of such parameters include 15 VDC, 0.5 ms pulses, 0.5-16 Hz, and 70 VDC, 2-3 ms pulses, 20 HZ.

The locating step described above may be performed using a non-invasive imaging technique, including but not limited to, a bronchogram, magnetic resonance imaging, computed tomography, radiography (e.g., x-ray), and ventilation perfusion scans.

The invention further includes the steps of testing the lung for at least one pre-treatment pulmonary function value prior to treating the lung with the device. After the lung is treated, the lung is re-tested for at least one post-treatment pulmonary function value. Naturally, the two pulmonary function values may be compared to estimate the effect of the treatment. The invention may also include treating additional sites in the lung after the re-testing step to at least reduce the effect of at least one symptom of reversible obstructive pulmonary disease. The invention may also include stimulating the lung to produce at least one artificially induced symptom of reversible obstructive pulmonary disease. As mentioned above, the stimulation of the lung may occur at any point during, or prior to, the procedure. For example, stimulation of the lung may occur prior to the step of testing the lung for pre-treatment pulmonary values. In this case, the values would be determinative of pulmonary function values of a lung experiencing symptoms of reversible obstructive pulmonary disease. Accordingly, the objective is to treat the lung until acceptable pulmonary function values are obtained. One benefit of such a procedure is that the effect of the treatment on the patient is more readily observed as compared to the situation where a patient, having previously been treated, must wait for an attack of reversible obstructive pulmonary disease to determine the efficacy of the treatment.

Pulmonary function values are well known in the art. The following is an example of pulmonary function values that may be used. Other pulmonary function values, or combinations thereof, are intended to be within the scope of this invention. The values include, but are not limited to, FEV (forced expiratory volume), FVC (forced vital capacity), FEF (forced expiratory flow), Vmax (maximum flow), PEFR (peak expiratory flow rate), FRC (functional residual capacity), RV (residual volume), TLC (total lung capacity).

FEV measures the volume of air exhaled over a predetermined period of time by a forced expiration immediately after a full inspiration. FVC measures the total volume of air exhaled immediately after a full inspiration. Forced expiratory flow measures the volume of air exhaled during a FVC divided by the time in seconds. Vmax is the maximum flow measured during FVC. PEFR measures the maxi-

mum flow rate during a forced exhale starting from full inspiration. RV is the volume of air remaining in the lungs after a full expiration.

The locating step described above may also comprise identifying treatment sites within the airway being susceptible to a symptom of reversible obstructive pulmonary disease. For example, symptoms may include, but are not limited to, airway inflammation, airway constriction, excessive mucous secretion, or any other asthmatic symptom. Stimulation of the lung to produce symptoms of reversible obstructive pulmonary disease may assist in identifying ideal treatment sites.

As noted above, the method of the present invention may include stimulating the lung to produce at least one artificially induced symptom of reversible obstructive pulmonary disease and further include the step of evaluating the result of stimulation of the lung. For example, the evaluating step may include visually evaluating the effect of the stimulating step on the airway using a bronchoscope with a visualization system or by non-invasive imaging techniques, such as those describe herein. The evaluating step may include measuring pressure changes in the airway before and after the stimulating step. Pressure may be measured globally (e.g., within the entire lung), or locally (e.g., within a specific section of the lung such as an airway or alveolar sac.) Also, the evaluating step may comprise measuring the electrical properties of the tissue before and after the stimulating step. The invention may also include evaluating the results of the stimulating step by combining any of the methods previously mentioned. Also, the invention may further comprise the step of selecting at least one treatment parameter based upon the results of the evaluating step. Such treatment parameters may include, but are not limited to, duration of treatment, intensity of treatment, temperature, amount of tissue treated, depth of treatment, etc.

The method may also include the step of determining the effect of the treatment by visually observing lung, airway or other such tissue for blanching of the tissue. The term "blanching" is intended to include any physical change in tissue that is usually, but not necessarily, accompanied by a change in the color of the tissue. One example of such blanching is where the tissue turns to a whitish color after the treatment of application of energy.

The invention may also include the step of monitoring impedance across a treated area of tissue within the lung. Measuring impedance may be performed in cases of monopolar or bipolar energy delivery devices. Additionally, impedance may be monitored at more than one site within the lungs. The measuring of impedance may be, but is not necessarily, performed by the same electrodes used to deliver the energy treatment to the tissue. Furthermore, the invention includes adjusting the treatment parameters based upon the monitoring of the change in impedance after the treatment step. For example, as the energy treatment affects the properties of the treated tissue, measuring changes in impedance may provide information useful in adjusting treatment parameters to obtain a desired result.

Another aspect of the invention includes advancing a treatment device into the lung and treating lung tissue to at least reduce the ability of the lung to produce at least one symptom of reversible obstructive pulmonary disease and further comprising the step of sub-mucosal sensing of the treatment to the lung tissue. The sub-mucosal sensing may be invasive such as when using a probe equipped to monitor temperature, impedance, and/or blood flow. Or, the sub-mucosal sensing may be non-invasive in such cases as infra-red sensing.

The invention may also include using the treatment device to deposit radioactive substances at select treatment sites within the lung. The radioactive substances, including, but not limited to Iridium (e.g. 192Ir.) either treat the lung tissue over time or provide treatment upon being deposited.

The invention also includes scraping epithelial tissue from the wall of an airway within the lung prior to advancing a treatment device into the lung to treat the lung tissue. The removal of the epithelial tissue allows the device to treat the walls of an airway more effectively. The invention further comprises the step of depositing a substance on the scraped wall of the airway after the device treats the airway wall. The substance may include epithelial tissue, collagen, growth factors, or any other bio-compatible tissue or substance, which promotes healing, prevents infection, and/or assists in the clearing of mucus. Alternatively, the treatment may comprise the act of scraping epithelial tissue to induce yield the desired response.

The invention includes using the treating device to pre-treat the lung to at least reduce the ability of the lung to produce at least one symptom of reversible obstructive pulmonary disease prior to the treating step. At least one of the parameters of the pre-treating step may differ than one of the parameters of the treating step. Such parameters may include time, temperature, amount of tissue over which treatment is applied, amount of energy applied, depth of treatment, etc.

The invention may also include advancing the treatment device into the lung and treating the lung tissue in separate stages. One of the benefits of dividing the treating step into separate stages is that the healing load of the patient is lessened. Dividing of the treating step may be accomplished by treating different regions of the lung at different times. Or, the total number of treatment sites may be divided into a plurality of groups of treatment sites, where each group of treatment sites is treated at a different time. The amount of time between treatments may be chosen such that the healing load placed on the lungs is minimized.

The invention may also include advancing a treatment device into the lung, treating the lung with the device and sensing movement of the lung to reposition the treatment device in response to the movement. This sensing step accounts for the tidal motion of the lung during breathing cycles or other movement. Taking into account the tidal motion allows improved accuracy in repositioning of the device at a desired target.

The invention may also include the additional step of reducing or stabilizing the temperature of lung tissue near to a treatment site. This may be accomplished for example, by injecting a cold fluid into lung parenchyma or into the airway being treated, where the airway is proximal, distal, or circumferentially adjacent to the treatment site. The fluid may be sterile normal saline, or any other bio-compatible fluid. The fluid may be injected into treatment regions within the lung while other regions of the lung normally ventilated by gas. Or, the fluid may be oxygenated to eliminate the need for alternate ventilation of the lung. Upon achieving the desired reduction or stabilization of temperature the fluid may be removed from the lungs. In the case where a gas is used to reduce temperature, the gas may be removed from the lung or allowed to be naturally exhaled. One benefit of reducing or stabilizing the temperature of the lung may be to prevent excessive destruction of the tissue, or to prevent destruction of certain types of tissue such as the epithelium, or to reduce the systemic healing load upon the patient's lung.

Also contemplated as within the scope of the invention is the additional step of providing therapy to further reduce the effects of reversible obstructive pulmonary disease or which aids the healing process after such treatment. Some examples of therapy include, drug therapy, exercise therapy, and respiratory therapy. The invention further includes providing education on reversible obstructive pulmonary disease management techniques to further reduce the effects of the disease. For example, such techniques may be instruction on lifestyle changes, self-monitoring techniques to assess the state of the disease, and/or medication compliance education.

There may be occurrences where it is necessary to reverse the effects of the treatment described herein. Accordingly, the invention further includes a method for reversing a treatment to reduce the ability of the lung to produce at least one symptom of reversible obstructive pulmonary disease comprising the step of stimulating re-growth of smooth muscle tissue. The re-stimulation of the muscle may be accomplished by the use of electro-stimulation, exercising of the muscle and/or drug therapy.

The invention further includes methods of evaluating individuals having reversible obstructive pulmonary disease, or a symptom thereof, as a candidate for a procedure to reduce the ability of the individual's lung to produce at least one symptom of reversible obstructive pulmonary disease. The method comprises the steps of assessing the pulmonary condition of the individual, comparing the pulmonary condition to a corresponding pre-determined state, and evaluating the individual as a candidate based upon the comparison.

In assessing the pulmonary condition, the method may comprise the steps of performing pulmonary function tests on the individual to obtain a pulmonary function value which is compared to a predetermined value. Examples of pre-determined values are found above.

The method of evaluating may further include the step of determining how the individual's tissue will react to treatment allowing the treatment to be tailored to the expected tissue response.

The method of evaluating may further comprises the step of pulmonary function testing using a gas, a mixture of gases, or a composition of several mixtures of gases to ventilate the lung. The difference in properties of the gases may aid in the pulmonary function testing. For example, comparison of one or more pulmonary function test values that are obtained with the patient breathing gas mixtures of varying densities may help to diagnose lung function. Examples of such mixtures include air, at standard atmospheric conditions, and a mixture of helium and oxygen. Additional examples of pulmonary testing include tests that measure capability and evenness of ventilation given diffusion of special gas mixtures. Other examples of gases used in the described tests, include but are not limited to, nitrogen, carbon monoxide, carbon dioxide, and a range of inert gases.

The invention may also comprise the step of stimulating the lung to produce at least one artificially induced symptom of reversible obstructive pulmonary disease. Stimulating the symptoms of the disease in an individual allows the individual to be evaluated as the individual experiences the symptoms thereby allowing appropriate adjustment of the treatment.

The method of evaluating may also comprise the step of obtaining clinical information from the individual and accounting for the clinical information for treatment.

The method may further comprise the selection of a patient for treatment based upon a classification of the subtype of the patient's disease. For example, in asthma there are a number of ways to classify the disease state. One such method is the assessment of the severity of the disease. An example of a classification scheme by severity is found in the NHLBI Expert Panel 2 Guidelines for the Diagnosis and Treatment of Asthma. Another selection method may include selecting a patient by the type of trigger that induces the exacerbation. Such triggers may be classified further by comparing allergic versus non-allergic triggers. For instance, an exercise induced bronchospasm (EIB) is an example of a non-allergenic trigger. The allergic sub-type may be further classified according to specific triggers (e.g., dust mites, animal dander, etc.). Another classification of the allergic sub-type may be according to characteristic features of the immune system response such as levels of IgE (a class of antibodies that function in allergic reactions, also called immunoglobulin). Yet another classification of allergic sub-types may be according to the expression of genes controlling certain interleukins (e.g., IL-4, IL-5, etc.) which have been shown to play a key role in certain types of asthma.

The invention further comprises methods to determine the completion of the procedure and the effectiveness of the reduction in the lung's ability to produce at least one symptom of reversible obstructive pulmonary disease. This variation of the invention comprises assessing the pulmonary condition of the individual, comparing the pulmonary condition to a corresponding predetermined state, and evaluating the effectiveness of the procedure based on the comparison. The invention may also comprise the steps of performing pulmonary function tests on the individual to obtain at least one pulmonary function value, treating the lung to at least reduce the ability of the lung to produce at least one symptom of reversible obstructive pulmonary disease, performing a post-procedure pulmonary function tests on the individual to obtain at least one post pulmonary function value and comparing the two values.

This variation of the invention comprises obtaining clinical information, evaluating the clinical information with the results of the test to determine the effectiveness of the procedure. Furthermore, the variation may include stimulating the lung to produce a symptom of reversible obstructive pulmonary disease, assessing the pulmonary condition of the patient, then repeating the stimulation before the post-procedure pulmonary therapy. These steps allow comparison of the lung function when it is experiencing symptoms of reversible obstructive pulmonary disease, before and after the treatment, thereby allowing for an assessment of the improved efficiency of the lung during an attack of the disease.

The medical practitioners performing the treatments described herein may wish to treat a limited number of sites in the lung to produce acceptable results in lessening the severity of asthmatic or reversible obstructive pulmonary disease symptoms. For example, if a patient requires an increasing amount of medication (e.g., sedatives or anesthesia) to remain under continued control for performance of the procedure, then a medical practitioner may limit the procedure time rather than risk overmedicating the patient. As a result, rather than treating the patient continuously to complete the procedure, the practitioner may plan to break the procedure in two or more sessions. Subsequently, increasing the number of sessions poses additional consequences on the part of the patient in cost, the residual effects of any medication, adverse effects of the non-therapeutic portion of the procedure, etc.

Accordingly, the invention includes methods of treating airways in a lung to decrease asthmatic symptoms. The methods include measuring a parameter of an airway at a plurality of locations in a lung, identifying at least one treatment site from at least one of the plurality of locations based on the parameter, and applying energy to the treatment site to reduce the ability of the site to narrow.

Identification of the treatment sites may comprise comparing the parameter to known or studied parameters and selecting those sites that meet or exceed specific criteria. Alternatively, or in combination, identification of treatment sites may comprise selecting the sites with the most significant parameters, or delivering a treatment specifically tailored to the parameters measured at each individual site. For example, if the parameter comprises measuring contractile force or the amount of contraction, then sites having the highest quantitative parameters may be selected as treatment sites. In another variation, the medical practitioner may simply rank the parameters in a desired order of value and treat those sites that are believed to provide the most benefit. For example, the medical practitioner may choose to treat the top 10% of sites having the most contraction, smooth muscle tissue, or other parameters as described herein. It is also contemplated that the diametrical size of the airway or the length of the airway segment may be correlated to the ability for that site to narrow. For example, when measuring a narrowed airway diameter relative to its natural diameter, the percentage change for a large diameter airway may be different than a percentage change for a smaller airway. In such a case, the medical practitioner may measure the airway diameter at each site for determining the course of treatment. In other words, the practitioner may deliver treatment to specific sites that meet certain criteria (e.g., sites having a certain diameter). Alternatively, or in combination, the practitioner may deliver treatment specifically tailored to each individual site based on a characteristic of the site (e.g., its diameter). For example, when delivering energy, the practitioner could deliver more energy to larger diameter airway, and less energy to smaller diameter airways (or vice versa).

In those cases where more than one treatment site is identified, the method may include the act of treating the new treatment site.

The method may also include correlating the treatment sites to a map **90**, as shown in FIG. **5**, the map may provide a graphical representation of a bronchial tree. As shown, the various bronchioles **92** decrease in size and have many branches **96** as they extend into the right and left bronchi **94**. Accordingly, an efficient treatment may require identification of potential treatment sites, treated sites, and other areas of the bronchial tree.

This mapping may be performed for a variety of reasons. For example, prior to treatment, the correlation may identify general areas for treatment by the medical practitioner. Once the area is treated, the map may then be marked to indicate a completed treatment. The treatment plan provided by the map should allow the medical practitioner a guide so that it is possible to treat less than all of the lungs. The treatment plan or map also may assist in avoiding double treatment of a particular treatment site. It is contemplated that the map **90** may be an actual chart, whether in tangible form or electronic form. Furthermore, the map may be incorporated into the treatment system **32** or the user interface **116** as discussed above. It is also contemplated that the map may be a three dimensional computer model, wherein the position of completed treatment sites are recorded by storing the spatial coordinates of these sites as each treatment is completed. As

subsequent treatments are made, the user may compare the current position of the catheter to the map, which will aid in determining which site to treat next.

The parameters to be measured in accordance with the methods described herein may be any parameter that is an indicator of or associated with symptoms of asthma. For example, the parameter may be a measure of pulmonary function values (see above), a measure of the contractile force at which the airway contracts, a thickness or amount of the airway smooth muscle at a particular location, eosinophil counts near or at the actual or potential treatment site, degree of airflow within the airway, degree of contraction of the airway during an asthma episode or after stimulation of the airway, metabolic rate to assess the presence of smooth muscle, electrical impedance to assess the nature of the airway tissue, and/or degree of wheezing at a particular location, etc. Other parameters indicative of asthma or a lack of airflow due to asthmatic symptoms are also intended to be within the scope of this disclosure.

Methods of the present invention include first stimulating the airway and then subsequently measuring the parameter. The stimulation may be performed electrically (such as by placing a device within the airway and stimulating using the settings described above). Alternatively, or in combination, the stimulation may be artificially induced using an agent, such as methacholine. For example, as shown in FIG. **6A**, a device **150** may deliver the agent **152** into the airway **2**.

Once the airway contracts, the contraction may be measured or assessed. Although not shown, the contraction may be measured or assessed without making contact with the airway wall (e.g., visually with a retical; or optically, via a camera). Alternatively, or in combination, as shown in FIG. **6B**, a contraction measurement device **154** may be placed against the airway (either prior or during contraction) and expanded to measure a natural state of the airway. The contraction measurement device **154** then transmits information regarding the contraction of the airway using, for example, strain gauges **156** placed on moveable arms of the device. The contraction measurement device **154** may also deliver an agent to cause contraction of the airways. In this manner, the device **154** will be in place while the airway contracts.

FIG. **6C** illustrates another variation where a balloon catheter **158** measures contraction of the airway. As the airway constricts, the balloon **160** increases in pressure. The pressure may then be characterized to determine the degree of contractile force of the airway. It should be noted that the balloon catheter **158** may also include fluid delivery ports to deliver an agent or have electrodes to induce the contraction. Other examples of devices that may be used to measure contraction of the airways are devices that measure the airway diameter mechanically or optically.

In another variation as shown in FIG. **6D**, a device **162** (e.g., an ultrasound balloon catheter, a non-balloon ultrasound catheter, a catheter (balloon or non-balloon) that is equipped to measure impedance, etc.), may be expanded within the airway to measure the thickness of the adjacent airway smooth muscle **14**. Alternatively, as described above, the measurement of the airway smooth muscle **14** may be achieved using the external imaging equipment **36** described above.

Another method of measuring parameters of an airway for identifying treatment sites comprises measuring eosinophil counts at the location. Eosinophils are white blood cells active in allergic diseases, parasitic infections, and other disorders. It is believed that eosinophils correlate to the amount of inflammation in an airway. FIG. **6E** shows one

way of obtaining an eosinophils count at a location in the lung. As shown, a device **164** advances a needle **166** within the airway to collect the eosinophils. Next, standard techniques are employed to measure the particular eosinophil count at the site.

FIG. 6F illustrates another variation of the invention where a device **168** measures airflow at a location or near to a location for treatment. The device **168** may be a hot-wire anemometer, where the airflow causes the heated wire **170** to cool and the rate of cooling of the wire provides information regarding the airflow.

In additional variations of the method, the medical practitioner may deliver hyperpolarized helium or a radioactive isotope to aid in the imaging of the airways. External imaging, as shown FIGS. 4A and 4C may be used to assess ventilation in the lung and select the areas that constrict at treatment sites.

Alternatively, the external imaging may take a first image of the airways. Next, an agent is applied (either locally, systemically, or limited to a particular lobe) to induce contraction of the airways. The medical practitioner may then obtain a second image of the airways for comparison with the first to determine contraction of the airways.

In another variation of the invention, the parameter comprises assessing a metabolic rate at the location. If the measurement of the metabolic rate indicates the presence of a significant amount of smooth muscle tissue, then the area may be designated as a treatment site. The metabolic rate may be measured over a treatment site or over an area of the airways (e.g., a particular lobe or a section thereof.) The measurement of the metabolic rate may be performed using standard measuring techniques. For example, the device may deliver cool air to the treatment site and then measure the rate at which the tissue temperature returns to the original baseline temperature, thereby providing a measurement of the calories used to bring the tissue back to the baseline temperature. This would, in turn, provide a measure of the responsiveness of the smooth muscle tissue because more reactive or responsive tissue may correlate to a higher metabolic rate.

FIG. 7 illustrates one example of an energy transfer element **208**. In this example the energy transfer element **208** is a "basket-type" configuration that requires actuation for expansion of the basket in diameter. Such a feature is useful when the device is operated intralumenally or in anatomy such as the lungs due to the varying size of the bronchial passageways that may require treatment. As illustrated, the basket contains a number of arms **220** which carry electrodes (not shown). In this variation the arms **220** are attached to the elongated shaft **204** at a proximal end while the distal end of the arms **220** are affixed to a distal tip **222**. To actuate the basket **208** a wire or tether **224** is affixed to the distal tip **222** to enable compression of the arms **220** between the distal tip **222** and elongate sheath **204**.

FIG. 7 also illustrates the device **100** as being advanced through a working channel **232** of a bronchoscope **318**. While a bronchoscope **318** may assist in the procedure, the device **100** may be used through direct insertion or other insertion means as well.

As noted above, some variations of the devices described herein have sufficient lengths to reach remote parts of the body (e.g., bronchial passageways around 3 mm in diameter). FIG. 8 illustrates a configuration that reduces the force required to actuate the device's basket or other energy transfer element.

FIG. 8 illustrates a cross section taken from the sheath **202** and elongate shaft **204**. As shown, the sheath **202** includes

an outer layer **226** and an inner lubricious layer **228**. The outer layer **226** may be any commonly known polymer such as Nylon, PTFE, etc. The lubricious layers **228** discussed herein may comprise a lubricious polymer (for example, HDPE, hydrogel, polytetrafluoroethylene). Typically, lubricious layer **228** will be selected for optimal pairing with the shaft **204**. One means to select a pairing of polymers is to maximize the difference in Gibbs surface energy between the two contact layers. Such polymers may also be chosen to give the lubricious layer **228** a different modulus of elasticity than the outer layer **226**. For example, the modulus of the lubricious layer **228** may be higher or lower than that of the outer layer **226**.

Alternatively, or in combination, the lubricious layers may comprise a fluid or liquid (e.g., silicone, petroleum based oils, food based oils, saline, etc.) that is either coated or sprayed on the interface of the shaft **204** and sheath **202**. The coating may be applied at the time of manufacture or at time of use. Moreover, the lubricious layers **228** may even include polymers that are treated such that the surface properties of the polymer changes while the bulk properties of the polymer are unaffected (e.g., via a process of plasma surface modification on polymer, fluoropolymer, and other materials). Another feature of the treatment is to treat the surfaces of the devices with substances that provide antibacterial/antimicrobial properties.

In one variation of the invention, the shaft **204** and/or sheath **202** will be selected from a material to provide sufficient column strength to advance the expandable energy transfer element within the anatomy. Furthermore, the materials and or design of the shaft/sheath will permit a flexibility that allows the energy transfer element to essentially self-align or self-center when expanded to contact the surface of the body passageway. For example, when advanced through tortuous anatomy, the flexibility of this variation should be sufficient that when the energy transfer element expands, the shaft and/or sheath deforms to permit self-centering of the energy transfer element. It is noted that the other material selection and/or designs described herein shall aid in providing this feature of the invention.

FIG. 8 also depicts a variation of a shaft **204** for use in the present device. In this variation the shaft **204** includes a corrugated surface **230**. It is envisioned that the corrugated surface **230** may include ribbed, textured, scalloped, striated, undercut, polygonal, or any similar geometry resulting in a reduced area of surface contact with any adjoining surface(s). The corrugated surface **230** may extend over a portion or the entire length of the shaft **204**. In addition, the shape of the corrugations may change at varying points along the shaft **204**.

The shaft **204** may also include one or more lumens **232**, **234**. Typically, one lumen will suffice to provide power to the energy transfer elements (as discussed below). However, in the variation shown, the shaft may also benefit from additional lumens (such as lumens **234**) to support additional features of the device (e.g., temperature sensing elements, other sensor elements such as pressure or fluid sensors, utilizing different lumens for different sensor leads, and fluid delivery or suctioning, etc.). In addition the lumens may be used to deliver fluids or suction fluid to assist in managing the moisture within the passageway. Such management may optimize the electrical coupling of the electrode to the tissue (by, for example, altering impedance). Since the device is suited for use in tortuous anatomy, a variation of the shaft **204** may have lumens **234** that are symmetrically formed about an axis of the shaft. As shown, the additional lumens **234** are symmetric about the shaft **204**. This construction

provides the shaft **204** with a cross sectional symmetry that aid in preventing the shaft **204** from being predisposed to flex or bend in any one particular direction.

The invention herein is described by examples and a desired way of practicing the invention is described. However, the invention as claimed herein is not limited to that specific description in any manner. Equivalence to the description as hereinafter claimed is considered to be within the scope of protection of this patent.

We claim:

1. A method of treating a lung, the method comprising: inserting a medical device into an airway of the lung, the medical device including a catheter and a balloon disposed at a distal end of the catheter, wherein a distalmost portion of the catheter extends distally of a distalmost portion of the balloon;

stimulating tissue surrounding an airway in the lung by introducing, via a port of the catheter, a pharmacological agent into the airway to constrict the airway;

after stimulating the tissue, measuring a constriction of the airway via the balloon;

delivering a fluid to the airway to electrically couple an electrode to the tissue surrounding the airway;

applying energy to the tissue, via the electrode and the fluid, to damage a portion of nerves disposed radially outward of the airway to reduce the ability of the lung to constrict in response to a stimulus, wherein the portion of the nerves is damaged to a greater extent than epithelium of the lung disposed radially inward of the portion of the nerves is damaged;

conveying the fluid from the airway; and

after applying energy, determining an effectiveness of applying energy by determining whether the lung has a reduced ability to produce at least one symptom of reversible obstructive pulmonary disease.

2. The method of claim 1, wherein delivering the fluid to the airway and applying energy to the tissue occur only if the measured constriction is greater than a threshold value.

3. The method of claim 1, further including monitoring electrical impedence of the tissue.

4. The method of claim 1, wherein applying energy to the tissue includes applying RF energy to the tissue.

5. The method of claim 1, wherein the pharmacological agent is methacholine.

6. The method of claim 1, wherein applying the energy to the tissue causes the tissue to reach a temperature from 60° C. to 80° C.

7. A method of treating a lung, the method comprising: inserting a medical device into an airway of the lung, the medical device including a catheter and a balloon disposed at a distal end of the catheter, wherein a distalmost portion of the catheter extends distally of a distalmost portion of the balloon;

stimulating tissue surrounding the airway in the lung; after stimulating the tissue, measuring a parameter of the airway via the balloon;

delivering a fluid to the airway to electrically couple an electrode to the tissue surrounding the airway; and applying energy to the tissue to damage a portion of nerves disposed radially outward of the airway to

reduce the ability of the lung to constrict in response to a stimulus, wherein the portion of the nerves is damaged to a greater extent than epithelium of the lung disposed radially inward of the portion of the nerves is damaged, wherein applying energy to the tissue occurs through the electrode and the fluid.

8. The method of claim 7, further including conveying the fluid from the airway.

9. The method of claim 7, wherein applying energy occurs only if the measured parameter is greater than a threshold value.

10. The method of claim 7, wherein the measured parameter is a contraction of the airway.

11. The method of claim 7, wherein, after applying energy, the method further includes determining an effectiveness of applying energy by determining whether the lung has a reduced ability to produce at least one symptom of reversible obstructive pulmonary disease.

12. The method of claim 7, wherein stimulating the tissue includes introducing a pharmacological agent into the airway.

13. A method of treating a lung, the method comprising: stimulating tissue surrounding an airway in the lung to constrict the airway;

after stimulating the tissue, measuring a parameter of the airway;

delivering a fluid to the airway to electrically couple an electrode to the tissue surrounding the airway; and

applying energy to the tissue, via the electrode and the fluid, to damage a portion of nerves disposed radially outward of the airway to reduce the ability of the lung to constrict in response to a stimulus, while minimizing damage to epithelium of the lung radially inward of the portion of the nerves.

14. The method of claim 13, further including conveying the fluid from the airway.

15. The method of claim 13, further including, before stimulating the tissue, inserting a medical device into the airway, the medical device including a catheter and a balloon disposed at a distal end of the catheter, wherein a distalmost portion of the catheter extends distally of a distalmost portion of the balloon.

16. The method of claim 13, wherein delivering the fluid and applying energy to the tissue occur only if the measured parameter is greater than a threshold value.

17. The method of claim 13, wherein the measured parameter is a contractile force of the airway.

18. The method of claim 13, wherein stimulating the tissue includes introducing a pharmacological agent into the airway.

19. The method of claim 18, wherein the pharmacological agent is methacholine.

20. The method of claim 13, further including after applying energy, determining an effectiveness of applying energy by determining whether the lung has a reduced ability to produce at least one symptom of reversible obstructive pulmonary disease.

* * * * *

专利名称(译)	治疗气道的方法		
公开(公告)号	US10561458	公开(公告)日	2020-02-18
申请号	US16/364614	申请日	2019-03-26
当前申请(专利权)人(译)	BOSTON SCIENTIFIC SCIMED , INC.		
[标]发明人	DANEK CHRISTOPHER J BIGGS MICHAEL LOOMAS BRYAN E LAUFER MICHAEL D KAPLAN GARY S SHRINER KELLY M WIZEMAN WILLIAM		
发明人	DANEK, CHRISTOPHER J. BIGGS, MICHAEL LOOMAS, BRYAN E. LAUFER, MICHAEL D. KAPLAN, GARY S. SHRINER, KELLY M. WIZEMAN, WILLIAM		
IPC分类号	A61B18/14 A61N5/10 A61B5/107 A61B5/00 A61B10/04 A61B18/18 A61B5/053 A61B1/00 A61B5/08 A61B18/06 A61B90/00 A61B17/00 A61B18/00		
CPC分类号	A61B18/18 A61N5/1001 A61B5/053 A61B5/1076 A61B10/04 A61B5/08 A61B5/6853 A61B18/14 A61B1/00085 A61B5/6858 A61B5/0538 A61B5/0809 A61B5/4519 A61B2018/1472 A61B2018/00541 A61B18/06 A61B2010/045 A61B5/4878 A61B5/411 A61B2018/00875 A61B2090/061 A61B2018/00214 A61B5/4836 A61B2018/00898 A61B2090/064 A61B2017/00106 A61B2018/0022 A61B2017/00809 A61B18/1492 A61B2018/00773 A61B2018/00244 A61B5/0036		
审查员(译)	马修斯, 威廉姆·H·		
其他公开文献	US20190216529A1		
外部链接	Espacenet		

摘要(译)

这涉及治疗肺中的气道以减轻哮喘症状。 还包括以下步骤：测量肺中多个位置处的气道参数；基于该参数从多个位置中的至少一个位置中识别至少一个治疗部位；以及向该治疗部位施加能量以减少肺动脉的压力。网站的缩小能力。

