




US 20160058342A1

(19) **United States**(12) **Patent Application Publication**
Maiz-Aguinaga et al.(10) **Pub. No.: US 2016/0058342 A1**(43) **Pub. Date: Mar. 3, 2016**(54) **APPARATUS AND METHODS FOR
TRANSDERMAL AND CELL INTERSTITIAL
BODY FLUID EXAMINATION, SENSING OF
ANALYTES, BIOMARKERS AND DRUG
CONCENTRATIONS AND ASSOCIATED DATA
TRANSMISSION SYSTEMS**(71) Applicants: **Jose Antonio Maiz-Aguinaga**,
Vancouver, WA (US); **Lennart Olsson**,
Los Altos Hills, CA (US)(72) Inventors: **Jose Antonio Maiz-Aguinaga**,
Vancouver, WA (US); **Lennart Olsson**,
Los Altos Hills, CA (US)(21) Appl. No.: **14/827,186**(22) Filed: **Aug. 14, 2015****Related U.S. Application Data**(60) Provisional application No. 62/070,182, filed on Aug.
18, 2014.**Publication Classification**(51) **Int. Cl.**
A61B 5/145 (2006.01)
A61B 5/00 (2006.01)
A61B 5/1473 (2006.01)(52) **U.S. Cl.**
CPC **A61B 5/14514** (2013.01); **A61B 5/14539**
(2013.01); **A61B 5/1473** (2013.01); **A61B**
5/14546 (2013.01); **A61B 5/14532** (2013.01);
A61B 5/685 (2013.01); **A61B 5/0002**
(2013.01); **A61B 5/4845** (2013.01); **A61B**
2505/07 (2013.01); **A61B 2560/063** (2013.01)(57) **ABSTRACT**

Embodiments of the invention enable sensing the presence and concentration of molecules such as electrolytes, biomarkers, chemically defined drugs and proteins in transdermal and cell interstitial body fluids. Today, these tests are generally performed by blood extraction in a clinic environment and a later analysis resulting in inconvenience to the patient, high cost, the need for specialized personnel and a delay in the results. The present invention enables performing those tests at a low cost, by non-specialized personnel or the patient him(her)self, in a home or clinic environment and provides near real time results that get communicated to the patient and authorized clinician. The invention achieves that by describing an innovative product architecture that integrating micro-needles with micro-sensors in a low cost disposable unit, a specially designed applicator for ease of use and automated wireless transmission and data analytics.






Fig 1




Fig. 2a




Fig. 2b




Fig. 2c




Fig. 2d

Fig. 2




Fig. 3a




Fig. 2a




Fig. 3b

Fig 3




Fig. 4a




Fig. 4b




Fig. 4c

Fig. 4




Fig 5




Fig 6




Fig. 7




Fig. 8

**APPARATUS AND METHODS FOR
TRANSDERMAL AND CELL INTERSTITIAL
BODY FLUID EXAMINATION, SENSING OF
ANALYTES, BIOMARKERS AND DRUG
CONCENTRATIONS AND ASSOCIATED DATA
TRANSMISSION SYSTEMS**

**CROSS-REFERENCE TO RELATED
APPLICATIONS**

[0001] A Provisional patent related to the invention was submitted:

TITLE OF PROVISIONAL PATENT

[0002] ‘Apparatus’ and methods for transdermal and interstitial body fluid examination, sensing and associated data transmission systems”

APPLICATION NUMBER

[0003] U.S. Provisional Patent Application 62/070,182

FILING OR 371(C) DATE filed on Aug. 18, 2014

**STATEMENT REGARDING FEDERALLY
SPONSORED RESEARCH OR DEVELOPMENT**

[0004] Not Applicable

**THE NAMES OF THE PARTIES TO A JOINT
RESEARCH AGREEMENT**

[0005] Not Applicable

**INCORPORATION-BY-REFERENCE OF
MATERIAL SUBMITTED ON A COMPACT DISK
OR AS TEXT FILE VIA THE OFFICE
ELECTRONIC FILING SYSTEM (EFS-WEB)**

[0006] Not Applicable

BACKGROUND OF THE INVENTION

[0007] 1. Field of the Invention

[0008] The present invention relates to the field of Bio-medical testing of body fluids, sensing device processing and fabrication, and more particularly to a method of fabricating a transdermal or interstitial fluid analyzer that integrates micro-needles with micro-sensors along with multiple integration layers and structures and uses a specially fabricated applicator, patch or carrier to communicate with a smart device, analyze the sensed data and communicate the results to both patient and medical personnel.

[0009] 2. Description of Related Art

[0010] Frequent testing for relevant biological materials such as K⁺, Na⁺, Cl⁻ ions, glucose, creatinine, cholesterol etc. and therapeutic agents such as drugs used in the treatment of cardiovascular, renal, neurological, oncological and other medical conditions is often required for the effective treatment and monitoring of patients. The standard of care involves blood extraction in a clinical setting with subsequent serum analysis for the concentrations of one or more electrolytes or other biological or therapeutic molecules of interest.

[0011] This testing process results in high costs related to the blood or fluid extraction being performed in a clinical setting, delays of hours to days related to the testing being frequently done by specialized personnel or laboratories, and inconvenience to the patient related to travelling to the medical facility and the significant time required. As a result, testing is often performed at suboptimal frequency and risks a delayed response to a medically significant event.

[0012] The use of micro-needles that can perforate the Stratum Corneum (the outer layer of the epidermis) and reach the transdermal fluid under the skin is part of the existing state of the art. When made hollow, the micro-needles provide access to the interstitial fluid among subcutaneous cells and permit the delivery of drugs or accessing the interstitial fluid for analysis. Micro-needles have been made from a large variety of materials from metals to ceramics to polymers to silicon with varying degrees of performance and process control. While these micro-needles can access the transdermal region, when manufactured to the correct dimensions, they are not deep enough to reach the blood capillaries or nerve endings and their application is therefore practically painless and does not produce bleeding. Research in the use of micro-needles has focused mostly on methods for delivering drugs into the subcutaneous region. Separately, sensors using especially formulated biochemical films to obtain electrical readings and transistors fabricated in semiconductors such as silicon and modified to make them sensitive and specific to ions such as K⁺ have also been sporadically described. Key difficulties with existing approaches are the lack of sufficient process control to achieve medical grade devices and complex integration methods that are not best suited for the high volume manufacturing that is necessary to achieve large volumes and low cost. As a result, practical devices that allow routine testing of transdermal fluid at low cost by non-specialized personnel are not available in the marketplace to the best knowledge of the inventors.

**CROSS-REFERENCE TO RELATED
APPLICATIONS**

Patent References

[0013]

Patent	Publication date	Applicant	Title
U.S. Pat. No. 8,920,359B2	Dec. 30, 2014	Wockhardt Res. Centre	A device and a system for delivery of biological material
US20140336487	Nov. 13, 2014	The Regents of the Univ. of Cal.	Microneedle arrays for biosensing and drug delivery
62/070,182	Provisional Aug. 18, 2014	Jose Maiz	Apparatus’ and methods for transdermal and interstitial body fluid examination, sensing and associated data transmission systems
WO2014120114	Aug. 7, 2014	Empire Tech. development	Microneedle-based natremia sensor and methods of use

-continued

Patent	Publication date	Applicant	Title
U.S. Pat. No. 8,560,059B2	Oct. 5, 2013	Covidien Hoarau	System and methods for optical sensing and drug delivery using microneedles
U.S. Pat. No. 6,591,124B2	Jul. 8, 2013	Procter & Gamble	Portable Interstitial Fluid Monitoring System
U.S. Pat. No. 8,303,518B2	Nov. 6, 2012	Intuity Medical	Autonomous, ambulatory analyte monitor or drug delivery device
US20120190950	Jul. 26, 2012	Medtronic Minimed Inc	Electrode compositions for use with analyte sensors
US20120186997	26 Jul. 2012	Medtronic Minimed Inc	Layered enzyme compositions for use in analyte sensors"
U.S. Pat. No. 7,941,201	May 10, 2011	Nat Chiao Tung Univ	Microprobe array structure and method for manufacturing the same
US20110105871	May 5, 2011	The Regents of the Univ. of Cal.	Monitoring method and/or apparatus
US20100025238	Feb. 4, 2010	Medtronic Minimed, Inc.	Analyte sensor apparatuses having improved electrode configurations and methods for making and using them
EP1841491B1	May 27, 2009	Janisys	Transdermal drug delivery device
US20090099427	Apr. 16, 2009	Arkal Medical, Inc.	Microneedle array with diverse needle configurations
US20090062752	Mar. 5, 2009	Gonnelli Robert R	Switchable microneedle arrays and systems and methods relating to same
EP1439871B1	Jan. 14, 2009	Massachusetts Inst Technology	Microneedle transport device
EP1448263B1	Jan. 7, 2009	Power Paper Ltd Mavor	Device and method for controlled delivery of active substance into the skin
U.S. Pat. No. 7,473,244B2	Jan. 6, 2009	Univ Utah	Active needle devices with integrated functionality
U.S. Pat. No. 7,416,541	Aug. 26, 2008	Corium International, Inc.	Intracutaneous microneedle array apparatus
U.S. Pat. No. 7,344,499B1	Mar. 18, 2008	Georgia Tech Research Corp.	Microneedle device for extraction and sensing of bodily fluids
EP1418977B1	Jan. 10, 2007	Hospira, Cho	Microneedles for minimally invasive drug delivery and method of manufacturing the same
U.S. Pat. No. 7,132,054B1	Nov. 7, 2006	Sandia Corporation	Method to fabricate hollow microneedle arrays
U.S. Pat. No. 6,908,453B2	Jun. 21, 2005	3M Innovative Properties Co	Microneedle devices and methods of manufacture
U.S. Pat. No. 6,471,903B2	Oct. 29, 2002	The Procter & Gamble Company	Apparatus and method for manufacturing an intracutaneous microneedle array
WO2001049346	Jul. 12, 2001	Redeon Inc	Stacked microneedle systems

BRIEF SUMMARY OF THE INVENTION

[0014] This invention provides processes and methods that enable and make practical the integration of micro-needles with biochemical micro-sensors and other associated or useful elements like reference electrodes, pH, and temperature sensors. The invention further allows for their miniaturization to achieve low cost and the enabling of high precision manufacturing methods required for a dependable and accurate medical grade device. It achieves this by implementing innovative process and integration architectures that leverage, adapt and take advantage of the state of the art in semiconductor wafer and thin film processing and materials with biochemical sensor devices and membranes that have been proposed for biochemical testing. It further describes a specialized applicator or carrier that allows its use by non-specialized medical personnel or by patients themselves along with built-in data analysis and communication capabilities so that the results can be communicated in real time to the patient and/or to medical staff (doctor, nurse etc.) without any specialized or skilled action by the user. The overall system

described by the invention achieves a low cost, medical grade, easy to use transdermal and cell interstitial sensor architecture that is suitable for use in both clinical and non-clinical environments by non-specialized personnel as well as by the patient him(her)self. To the best understanding of the inventors, this capability to simultaneously achieve low cost, ease of use, medical grade accuracy and suitability for high volume manufacturing has not been accomplished by integration architectures described in prior art and no equivalent capability devices have been offered or are in the process of being offered in the marketplace

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0015] While the specification concludes with claims particularly pointing out and distinctly claiming that which is regarded as the present invention, the advantages can be more readily be ascertained from the following description of the invention when read in conjunction with the accompanying drawings in which:

[0016] FIG. 1 represents the overall transdermal sensing system consisting of the integrated micro-needle/sensor element 200, an specially designed applicator 300 with a wired or wireless connection system to a smart device, an application for the smart device 400 to direct the sensing event and analyze results, a wired or wireless connection to a data server or the cloud and a software application in the server or cloud 500 for data analysis, storage and distribution while preserving the medically required protocols for privacy and data integrity.

[0017] FIG. 2a-2d in FIG. 2 represent cross-sections of structures used to form the integrated micro sensor unit. It integrates the operation of the micro-needles with the micro-sensors and a reference electrode in a monolithic block of silicon with a surrounding packaging structure that provides for the formation of a microfluidics chamber and electrical connections and may be formed when carrying out an embodiment of the method of the present invention.

[0018] FIG. 3a-3b in FIG. 3 represent cross-sections of structures that integrate the operation of the micro-needles with the micro-sensors and reference electrode as fabricated in separate blocks of silicon, a spacer enabling the formation of a microfluidics cavity and the surrounding packaging structure which may be formed when carrying out another embodiment of the method of the present invention.

[0019] FIG. 4a-4c in FIG. 4 represent cross sections of structures that integrate the operation of the micro-needles with the sensors and reference electrode as fabricated in separate blocks of silicon but where the etching in one of the silicon forming blocks provides for the microfluidics chamber and that may be formed when carrying out yet another embodiment of the method of the present invention.

[0020] FIG. 5 represent an applicator and handling pen-like device 300, or alternatively patch-like device 320, designed to facilitate securely picking and electrically contacting the micro-needle/sensor assembly and containing the power source and electronics circuit to direct and execute the sensing event and to communicate wirelessly or by wired connection the sensing results to a smart device such as a smart phone or smart watch.

[0021] FIG. 6 represents a smart device such as a computer, a smart phone or smartwatch 400 with a specially designed application to request and direct the sensing event by communicating wirelessly or by wired connection with the applicator device, to analyze the results, to communicate the results to a computer server or application in the cloud for storage and safekeeping and to communicate the results to the patient or appropriate clinician.

[0022] FIG. 7 represents a server computer or server in the cloud 500 with a database and a software application that receives the sensing data, performs further analysis, provides secure safekeeping of the results and communicates the results to those with the right to know by using secure protocols appropriate to handle medical data.

[0023] FIG. 8 represents a flow chart of the sensing event as directed by the server computer and the application in the smart device and executed by the applicator and the integrated micro-needle/sensor devices.

DETAILED DESCRIPTION OF THE INVENTION

[0024] In the following detailed description, reference is made to the accompanying drawings that show, by way of illustration and examples, some specific embodiments in which the invention may be practiced. These embodiments

are described in sufficient detail to enable those skilled in the art to practice the invention. Although the various embodiments of the invention are different, they are in no way mutually exclusive. For example, a particular feature, structure, or characteristic described herein, in connection with one embodiment, may be implemented within other embodiments without departing from the spirit and scope of the invention. In addition, it is to be understood that the location or arrangement of individual elements within each disclosed embodiment may be modified without departing from the spirit and scope of the invention. The following detailed description is, therefore, not to be taken in a limiting sense, but only as a mean to illustrate, and explain the scope of the present invention which is defined only by the appended claims, appropriately interpreted, along with the full range of equivalents to which the claims are entitled. In the drawings, like numerals refer to the same or similar functionality throughout the several views.

[0025] Methods of forming transdermal and cell interstitial body fluid sensing and data transmission systems (i.e. the integration of micro-needles, micro-sensors, reference electrodes, applicators, wireless communication and data processing capabilities) and associated structures are described. Those methods comprise forming a micro-needle unit that can pierce the Stratum Corneum portion of the skin, forming a micro-sensor unit for the ion or molecule species of interest (i.e. electrolytes, biomolecules and drugs whether therapeutic or otherwise) along with its associated control circuitry, forming a reference electrode, integrating all of them as a self-contained consumable unit in a way that can be greatly miniaturized to reduce cost, forming an applicator, patch, holder, or carrier that holds the consumable during the test, powers the sensors, acquires the data and transmits it to a smart device in a way that makes the device safe and easy to use by non-specialized personnel and an application for the smart device specifically developed to direct the sensing event, analyze the results and send them in real time to the patient and or appropriate medical personnel.

[0026] In an embodiment of the present invention, as illustrated in FIG. 1, an integrated system capable of transdermal and cell interstitial fluid examination, sensing of analytes, biomarkers and drug concentrations is described. An integrated disposable sensing unit 200 is fabricated by forming micro-needles, micro-sensors, a reference electrode, their supporting electronic circuitry and integrating them into a unit that is suitable for low cost manufacturing and easy to handle by non-specialized personnel. An applicator 300 such as a pen-like or a patch-like or carrier with a different form factor but same function and that is reusable is specially designed to handle the integrated disposable unit. This applicator 300 carries a battery unit to provide power, includes electronic circuits to power the sensors and read the resulting sensing data, and has additional electronic circuits for processing and preparing that data for transmission along with electronic circuits to transmit wirelessly or by wired connection that data to a smart device. A smart device 400 such as a smart phone, smart watch, smart bracelet or general computing device capable of sending data to and receiving data from the applicator and a software application that directs the sensing event, analyzes the sensing results, communicates it to a central or cloud based data repository system and communicates it to both the patient and authorized clinician or clinic. A computing device 500 with an especially designed software application whether local, at a dedicated server farm or in the

cloud to accept the data store it and provide secure access to only authorized personnel by following protocols generally accepted to handle sensitive medical information.

[0027] In an embodiment of the present invention, as illustrated in FIG. 2, a method of forming an integrated disposable sensing unit **200** is described by forming micro-needles, micro-sensors for one or multiple analytes or bio-chemical species of interest, a reference electrode and integrating them into a unit that is suitable for low cost manufacturing and easy to handle by non-specialized personnel. Referring to FIG. 2a, an array of micro-needles **106** are fabricated on a silicon block **102** by using photolithographic techniques, preferential crystal plane wet etch methods, isotropic and anisotropic dry etch techniques or a combination of all of them as it is well known to those skilled in the art. In this embodiment, the length of the micro-needles is between 25 micrometers and several millimeters as appropriate to the specific sensing function pursued. In the case of transdermal sensing lengths between 25 micrometers and 500 micrometers can be considered to ensure perforation of the Stratum Corneum and perform the testing without any significant pain or bleeding. Dimensions between 25 micrometers and several millimeters can be considered when probing for cell interstitial fluids in diseased body tissues. The micro-needles and supporting silicon block are formed with hollow perforations **104** which are formed commonly but not exclusively by Deep Reactive Ion Etching (DRIE) or alternative techniques as it is well known to those skilled in the art. FIG. 2b illustrates the formation of micro-sensors **108** designed to measure presence or concentration of the ion or biomolecule of interest, a reference electrode **107**, electronic circuitry **105** designed to power and control them with all of the being formed on the surface opposite from that used to form the micro-needles by using photolithography and commonly used thin and thick film processing techniques. These micro-sensors **108** can be formed in a manner that is optimized for the specific ion species, biomarker or drug and could be based on Ion Sensitive Field Effect Transistors, especially modified thin films whose conductivity is modulated by the concentration of the chemical species to be tested or optimized to use voltammetry or amperometry techniques as it is known to those skilled in the art. The micro-sensors **108** could be all similar so as to measure the concentration of a single species of analyte, biomarker/drug or may be formed to contain multiple sensor types so that multiple types of analytes, biomarkers and drugs can be measured simultaneously. The reference electrode **107** can be formed by adapting processing techniques commonly used in semiconductor technology and the use of different kinds of materials but preferably as a Ag/AgCl reference electrode as it is commonly used by those skilled in the art. The sensors **108** may be formed to include measurements of pH, temperature, ions such as K⁺, Na⁺, Cl⁻ and others, important biomolecules such as creatinine, glucose, lactic acid, lactates, cholesterol, nitrates etc., therapeutic drugs such as those used to treat cardiovascular, renal, neurological and oncological conditions and any other of biological interest. The same FIG. 2b illustrates the formation of specially designed electronic circuits **105** and metallic contacts **109** on the same surface than the micro-sensors **108** whose function is to power the micro-sensors, read the sensing results, and prepare the data for transmission to the electronic circuits in the applicator through the metallic contacts **109** and which are formed by standard processing techniques used to fabricate semiconductor devices. Referring to FIGS. 2c and 2d, a

specially formed casing **112** is used to assemble the micro-needle/micro-sensor(s) integrated block in a way that it creates a microfluidics chamber **114** and which allows the transdermal fluid to reach the sensor units. Making the dimensions of the hollow portion of the micro-needle **104** and the fluid chamber **114** small and their surfaces hydrophilic, along with the presence of a vent **120**, will allow the transdermal fluid to travel by capillary action and reach the micro-sensors. Preferred embodiments for the hollow portion of the micro-needles are below 150 micrometers although larger dimensions are possible. Preferred embodiments for the height of the microfluidics chamber are in the 10-500 micrometers although dimension of 1 millimeter and larger can be made work. The casing **112** may comprise materials such as metals, ceramics, polymers and plastics or others that provide similar structural function. Perforations **116** in the casing **112** are used to incorporate electrical conductors and provide electrical access to the sensors **108** and sensing circuitry **105**, to provide power, read the results and may be formed in sufficient quantity to tend the needs of the multiple sensors formed. A perforation formed in the casing **120** and identified as a vent allows air to be vented out of the chamber as the transdermal fluid fills the sensing chamber **114** by capillary action and can be formed anywhere that is convenient in the walls micro-fluidics chamber. Conductive pads **118** are formed on the casing to complete forming the consumable unit (FIG. 2d). In a preferred embodiment of this invention the integrated disposable unit **200** and described in more detail in FIG. 2d is between 0.5 millimeters and 10 millimeters wide with the dimension being dictated primarily by number of distinct sensor devices incorporated into the unit. In a preferred embodiment of this invention the integrated disposable unit **200** has a thickness between 500 micrometers and 5 millimeters.

[0028] In another embodiment of the invention and referring to the same FIGS. 2a-2d, the substrate **102** and micro-needles **106** are formed in a material different than silicon such as metal, ceramic, polymer, carbon or plastic and the micro-sensors **108**, controlling circuitry **105** and reference electrode **107** are fabricated separately either in silicon or in another suitable material such as a different semiconductor, carbon, metal or nanoparticle structure and are placed appropriately over the substrate **102** while allowing a similar method of integration of the consumable portion of the device.

[0029] In another embodiment of the invention, and as described in FIG. 3a-3b, the substrate **102** with the micro-needles **106** (FIG. 2a) are formed in a separate block than the micro-sensors **208**, control circuitry **205** and reference electrode **207** which are formed on a substrate **222** as is described in FIG. 3a. The micro-needles **106** and the micro-needle substrate **102** can be formed in a variety of materials including, but not limited to silicon, metals, ceramics, polymers, carbon or plastics. The substrate **222** can be formed in a variety of materials including, but not limited to silicon, metals, ceramics, polymers, carbon or plastics. The micro-sensors themselves **208** can be formed in silicon or in another material suitable for the fabrication of micro-sensors such as a different type of semiconductor, or a properly formulated carbon or polymer based paste and could be based on Ion Sensitive Field Effect Transistors, especially modified thin films whose conductivity is modulated by the concentration of the chemical species to be tested or optimized to use voltammetry or amperometry techniques as it is known to

those skilled in the art. The controlling circuitry 205 and reference electrode 207 can then be formed on substrate 222. In this embodiment (FIG. 3b), the electrical connections 216, electrical contacting pads 218 and the vent 220 are also formed in the substrate 222. During operation, and when the transdermal needles 106 pierce the stratum corneum, the interstitial fluid moves up the hollow portion of the needle 104 by capillary action reaching the cavity 214 and the micro-sensors 208 and generates an electrical sensing signal that can be read through the electrical pads 218.

[0030] In another embodiment of the invention and as illustrated in FIG. 4a-4c, the micro-fluidics chamber 230 is formed in the micro-needle block 102 by chemical etching, abrasion, stamping, laser processing or other suitable method. In the case where the micro-needle block 102 is made out of silicon, the micro-fluidics chamber 130 can be formed by anisotropic dry etching or by wet chemical etching of the silicon which preferentially etches or stops along certain crystalline planes or by other wet or dry etching methods as it is well known to those skilled in the art. An example is the case where Silicon <100> wafers are used and a KOH based etchant is used to preferentially stop etching when it reaches a <111> plane forming the desired cavity. However, multiple other options based in the same concept are possible as it is well known to those skilled in the art. Additionally, the venting perforation 220 is shown in block 222 for convenience but could also be easily formed laterally from the micro-fluidics chamber in the micro-needle block 102 and be equally effective.

[0031] In another embodiment of the invention and as it is illustrated in FIG. 5, a reusable applicator 300 is designed and formed to facilitate the handling of the sensing operation in a way that is easy to use by non-specialized personnel. The applicator can be formed by using metals, ceramics, plastics, polymers or a combination of them. As a method of illustration, the applicator 300 includes a grab and hold mechanism 302 that securely picks and holds the integrated sensing unit 200, a method of providing electrical connectivity 304, an electronic circuit unit 306 that provides power to the sensors by a battery or other means, has the capability to process the results, and transmits them wirelessly or by a wired connection to a smart device 400. The applicator 300 also contains a mechanical grab and hold actuator 310 which in one embodiment of the invention could be similar to the operation of a mechanical pencil, and an electrical switch 308 that initiates the sensing sequence under user control. The description of the mechanisms, actuators and switches illustrated in FIG. 5 are provided as examples and should not be interpreted as limiting the method of executing the inventions as many related options are available to those skilled in the art. The applicator 300 itself illustrated in FIG. 5 is a pen like device but many other options in the form of a patch or carrier device with alternative geometries are possible and this example should not be construed as limiting the application of the invention. The patch-like device 320 in FIG. 5 illustrates such an embodiment example of the reusable applicator with its grab and hold mechanism 302, an adhesive 322 to secure it to the skin and the electronics module 306 to confer it a substantially similar capability and function than that described for the pen-like applicator.

[0032] In another embodiment of the invention as illustrated in FIG. 6 a smart device 400 such as, but not limited to a smartphone, smart-watch, tablet or computer has been equipped with a specialized application or software program

that directs the sensing sequence, communicates by wire or wirelessly with the applicator 300, instructs the sensing to be done, collects and analyzes the results and communicates them by wire or wirelessly to devices 500 under the control of the patient and/or appropriate medical personnel as illustrated in FIG. 7. An example of the architecture of the integrated operation is described in FIG. 1 and an example of the operational flow is described in FIG. 8. It should be clear to those skilled in the art that the architecture of the integrated operation described in FIG. 1 and the operational flow described in FIG. 8, are examples and that variants in the sequence of events or modification in the flow that accomplish the same result are part of the claimed invention.

What is claimed is:

1. An apparatus and method of performing transdermal and or cell interstitial body fluid testing of analytes, bio-molecules, chemically defined drugs and proteins comprising a disposable integrated micro-sensing unit, a reusable applicator to enable the safe and easy handling of the test sequence and the automated test sequence execution, the analysis of results and data communication to authorized users.

2. The apparatus and method in claim 1, further comprising of a disposable micro-sensing unit that integrates hollow transdermal micro-needles with a single or multiple bio-analyte, bio-molecule, chemically defined drug or therapeutic molecule micro-sensor(s), a reference electrode, pH and temperature sensors and their appropriate electronic control circuitries formed in a monolithic block of silicon by the use of appropriate thick and thin film inorganic or organic materials processing techniques along with a formed casing, a spacer, a vent and electrical contacts that enable forming an integrated disposable sensing device.

3. The apparatus and method in claim 1, further comprising of a disposable micro-sensing unit that integrates micro-needles formed in one block of silicon while the micro-sensor(s), the reference electrode, the pH and temperature sensors and their electronic controlling circuitries are formed into a separate block(s) of silicon and integrated with a formed casing, a spacer, a vent and electrical contacts that enable forming an integrated disposable sensing device.

4. The apparatus and method in claim 1, further comprising of a disposable micro-sensing unit where the micro-needles, the micro-needle substrate, the micro-sensor substrate and the micro-sensor(s) themselves, whether formed as part of a single block or adjacent multiple blocks, are formed of a material other the silicon such as, but not limited to, a semiconductor other than silicon, metal, ceramic, polymer, carbon or plastic on any suitable substrate.

5. The apparatus and method in claim 1, further comprising of a disposable micro-sensing unit where the micro-sensor(s) have been formed by incorporating a sensing membrane that is of high sensitivity and specificity to the chemical species of interest into Ion Sensitive Field Effect Transistors, thin or thick films subject to conductivity modulation and any other device suitable for voltammetry or amperometric sensing techniques.

6. The apparatus and method in claim 1, further comprising of a disposable micro-sensing unit where the preferred dimensions for the micro-needle depth ranges from 25 micrometers to several millimeters depending of the specific application, where the preferred dimension for the hollow portion of the micro-needles is under 150 micrometers, where the preferred dimension of the formed microfluidics chamber ranges from 10 micrometers to 1 millimeter, where the pre-

ferred lateral dimension of the integrated disposable unit ranges from 0.5 millimeters to 10 millimeters and where the preferred thickness of the integrated disposable unit ranges from 0.5 millimeters to 5 millimeters.

7. The apparatus and method in claim 1, further comprising a reusable sensing applicator whether pen-like, patch-like or with other geometry that has been specially designed to enable the easy handling of the integrated disposable micro-sensing unit described in claims 2 through 6

8. The apparatus and method in claim 1, further comprising a reusable sensing applicator incorporating a battery to provide power to the integrated disposable micro-sensing unit, electronic circuitry to power and direct the sensing event and electronic circuitry to receive the measured sensing data from the integrated micro-sensing unit and transmit it wirelessly of by wire to a computing or smart device.

9. The apparatus and method in claim 1, further comprising a reusable sensing applicator that incorporates a mechanical, magnetic or electromagnetic grab and hold mechanism with a controlling button that makes it easy to use to non-specialized personnel.

10. The apparatus and method in claim 1, further comprising a reusable sensing applicator that incorporates a button switch that makes it easy for the user to initiate the sensing event when ready and which executes the sensing event and data transmission under the full automatic control of the electronics without any further intervention of the user.

11. The apparatus and method in claim 1, further comprising an application resident in a smart device such as a smart phone, smart watch, tablet, wearable or computing devices specially designed to communicate either wirelessly or by wire with the disposable micro-sensing unit applicator to direct the sensing event, collect the sensing data, analyze the results and communicate them to authorized persons and devices.

12. The apparatus and method in claim 1, further comprising a smart device application specially designed to communicate wirelessly or by wired connection with a server computer, whether local or in the cloud for permanent data repository and distribution according to established protocols of data security and privacy.

* * * * *

专利名称(译)	用于透皮和细胞间质体液检查，分析物，生物标记物和药物浓度的传感以及相关数据传输系统的装置和方法		
公开(公告)号	US20160058342A1	公开(公告)日	2016-03-03
申请号	US14/827186	申请日	2015-08-14
[标]申请(专利权)人(译)	马伊斯阿吉纳加何塞·安东尼奥 OLSSON 伦纳特		
申请(专利权)人(译)	马伊斯-阿吉纳加，何塞·安东尼奥 OLSSON，伦纳特		
当前申请(专利权)人(译)	马伊斯-阿吉纳加，何塞·安东尼奥 OLSSON，伦纳特		
[标]发明人	MAIZ AGUINAGA JOSE ANTONIO OLSSON LENNART		
发明人	MAIZ-AGUINAGA, JOSE, ANTONIO OLSSON, LENNART		
IPC分类号	A61B5/145 A61B5/00 A61B5/1473		
CPC分类号	A61B5/14514 A61B5/14539 A61B5/1473 A61B5/14546 A61B2560/063 A61B5/685 A61B5/0002 A61B5/4845 A61B2505/07 A61B5/14532 A61B5/0004		
优先权	62/070182 2014-08-18 US		
其他公开文献	US10321858		
外部链接	Espacenet USPTO		

摘要(译)

本发明的实施方案使得能够在透皮和细胞间质体液中感测分子（例如电解质，生物标志物，化学上确定的药物和蛋白质）的存在和浓度。今天，这些测试通常通过临床环境中的血液提取和随后的分析来执行，导致对患者的不便，高成本，对专业人员的需求和结果的延迟。本发明使得能够以低成本，由非专业人员或患者（她）自己在家庭或诊所环境中执行那些测试，并且提供接近实时的结果，该结果被传达给患者和授权的临床医生。本发明通过描述将微针与微传感器集成在低成本一次性单元中的创新产品架构，专门设计的易于使用的应用器以及自动化无线传输和数据分析来实现。

