



US010226216B2

(12) **United States Patent**  
**Das et al.**

(10) **Patent No.:** **US 10,226,216 B2**  
(45) **Date of Patent:** **\*Mar. 12, 2019**

(54) **WEARABLE PATCH COMPRISING  
MULTIPLE SEPARABLE ADHESIVE LAYERS**

(71) Applicant: **Zansors LLC**, Tysons, VA (US)

(72) Inventors: **Ranjit Das**, Gaithersburg, MD (US);  
**Mark Travaglini**, Northville, MO (US)

(73) Assignee: **Zansors LLC**, Tysons, VA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/456,051**

(22) Filed: **Mar. 10, 2017**

(65) **Prior Publication Data**

US 2017/0181705 A1 Jun. 29, 2017

**Related U.S. Application Data**

(63) Continuation of application No. 14/023,560, filed on Sep. 11, 2013, now Pat. No. 9,629,585.

(Continued)

(51) **Int. Cl.**

**A61B 5/00** (2006.01)

**A61B 5/08** (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC ..... **A61B 5/6833** (2013.01); **A61B 5/0022** (2013.01); **A61B 5/08** (2013.01); **A61B 5/11** (2013.01); **A61B 5/1118** (2013.01); **A61B 5/145** (2013.01); **A61B 5/14517** (2013.01); **A61B 5/4806** (2013.01); **A61B 5/4818** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC ..... A61B 5/6833; A61B 5/0022; A61B 5/08; A61B 5/11; A61B 5/145; A61B 5/6801; A61B 5/113; A61B 5/1118; A61B 5/4806; A61B 5/4818; A61F 13/00051; A61F 13/02; A61F 13/025; A61F 13/0246; A61K 9/703

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,426,884 A 1/1984 Poichaninoff  
4,641,643 A 2/1987 Greer

(Continued)

**OTHER PUBLICATIONS**

“Wireless Sensor Systems for the Medical Ward of the 21st Century” (<http://www.enel.ucalgary.ca/People/Haslett/WCLM/CHE/WebPage/AdHoc.html>).

(Continued)

*Primary Examiner* — Eric Winakur


*Assistant Examiner* — Chu Chuan (JJ) Liu

(74) *Attorney, Agent, or Firm* — DLA Piper LLP US

(57) **ABSTRACT**

Wearable patches comprising multiple separable adhesive layers. One or more of the layers can comprise electronics, mechanical components, gauze, medicine and/or other types of hardware suitable for the intended use of the patch. In use, a first layer of the patch is adhered to a user. When it is time to change layers, the patch is removed from the user, the first layer is removed from the patch to expose a second adhesive layer, and the second layer is applied to the user. The process may be repeated until the remaining layers of the patch have been used.

**19 Claims, 1 Drawing Sheet**



<b>Related U.S. Application Data</b>					
		8,560,046	B2	10/2013	Kumar et al.
		8,734,341	B2	5/2014	Howell et al.
(60)	Provisional application No. 61/699,790, filed on Sep. 11, 2012.	8,738,112	B2	5/2014	Choe et al.
		8,852,114	B2 *	10/2014	Buxi ..... A61B 5/02438 600/500
(51)	<b>Int. Cl.</b>	2002/0109600	A1	8/2002	Mault et al.
	<i>A61B 5/11</i> (2006.01)	2002/0180605	A1	12/2002	Ozguz et al.
	<i>A61B 5/145</i> (2006.01)	2004/0208916	A1	10/2004	Abbott et al.
	<i>A61F 13/02</i> (2006.01)	2005/0096513	A1	5/2005	Ozguz et al.
	<i>A61M 35/00</i> (2006.01)	2006/0276700	A1	12/2006	O'Neil et al.
	<i>A61K 9/70</i> (2006.01)	2007/0206655	A1 *	9/2007	Haslett ..... A61B 5/01 374/141
	<i>G06F 19/00</i> (2018.01)	2008/0091090	A1	4/2008	Guillory et al.
	<i>G16H 40/67</i> (2018.01)	2008/0275327	A1	11/2008	Faarbaek et al.
	<i>A61B 5/113</i> (2006.01)	2009/0022941	A1 *	1/2009	Fischer ..... A61B 5/00 428/116
	<i>A61F 13/00</i> (2006.01)	2009/0054742	A1	2/2009	Kaminska et al.
(52)	<b>U.S. Cl.</b>	2009/0076346	A1	3/2009	James et al.
	CPC ..... <i>A61B 5/6801</i> (2013.01); <i>A61F 13/00051</i> (2013.01); <i>A61F 13/02</i> (2013.01); <i>A61F 13/025</i> (2013.01); <i>A61F 13/0246</i> (2013.01); <i>A61K 9/703</i> (2013.01); <i>A61M 35/00</i> (2013.01); <i>G06F 19/00</i> (2013.01); <i>G16H 40/67</i> (2018.01); <i>A61B 5/113</i> (2013.01); <i>A61B 2503/04</i> (2013.01); <i>A61B 2560/0412</i> (2013.01); <i>A61F 2013/0094</i> (2013.01)	2010/0274099	A1	10/2010	Telfort et al.
		2010/0286607	A1	11/2010	Saltzstein
		2010/0298895	A1	11/2010	Ghaffari et al.
		2010/0317958	A1	12/2010	Beck et al.
		2011/0213272	A1	9/2011	Telfort et al.
		2011/0213274	A1	9/2011	Telfort et al.
		2011/0279963	A1	11/2011	Kumar et al.
		2012/0071742	A1	3/2012	Medina et al.
		2012/0130330	A1 *	5/2012	Wilson ..... A61F 13/42 604/361
(56)	<b>References Cited</b>	2012/0277549	A1	11/2012	Libbus et al.
		2013/0053669	A1 *	2/2013	Yoo ..... A61B 5/04 600/372
	<b>U.S. PATENT DOCUMENTS</b>	2013/0079605	A1	3/2013	Bandaru et al.
	5,061,258 A	10/1991	Martz		
	5,763,943 A *	6/1998	Baker ..... H01L 25/065 257/686		
	5,797,867 A	8/1998	Guerrera et al.		
	6,113,539 A	9/2000	Ridenour		
	6,160,196 A	12/2000	Knieler et al.		
	7,113,815 B2	9/2006	O'Neil et al.		
	7,206,630 B1	4/2007	Tarler		
	7,219,627 B1	5/2007	Egloff		
	7,499,739 B2	3/2009	Sweitzer et al.		
	7,894,869 B2	2/2011	Hoarau		
	8,433,383 B2	4/2013	O'Neil et al.		
					<b>OTHER PUBLICATIONS</b>
					U.S. Appl. No. 14/023,553, filed Sep. 11, 2013.
					International Search Report and Written Opinion from corresponding PCT Application No. PCT/US2013/059125 dated Jan. 22, 2014.
					International Preliminary Report on Patentability from PCT/US2013/059125 dated Mar. 17, 2015.
					* cited by examiner




FIG. 1




FIG. 2

## WEARABLE PATCH COMPRISING MULTIPLE SEPARABLE ADHESIVE LAYERS

### CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. Non-Provisional application Ser. No. 14/023,560 filed Sep. 11, 2013, which claims priority from U.S. Provisional Application Ser. No. 61/699,790 filed Sep. 11, 2012, the entireties of which are incorporated herein by reference.

### FIELD OF THE INVENTION

Embodiments of the invention relate to wearable patches comprising multiple separable adhesive layers.

### BACKGROUND

Patches that adhere to a person's body are being used for several purposes in today's society. The configuration and use of the patch often depends upon its intended purpose. For example, a patch comprising gauze or other material can be applied to a person to cover a wound and prevent infection (i.e., it is being used as an adhesive bandage). A patch that contains medicine or other substances can be applied to a person to treat a wound or an addiction (e.g., a nicotine patch), or to counteract e.g., sea sickness. Other patches can include electronics such as sensors or integrated circuits to monitor e.g., a person's health or response to physical activity. These patches can also include communication circuitry for communicating data from the patch to an external source.

All of these patches, however, have their shortcomings. For example, single wearable adhesive bandages must be changed frequently, especially if they get wet. In addition, these bandages are contained within individual packaging that must be opened and discarded before the bandage can even be used. Thus, these patches produce packaging waste and are inconvenient for the user because he/she must carry or have access to multiple bandages if they want to properly cover a wound, etc.

Patches that include electronics have additional problems. For example, a single wearable adhesive patch having electronics or other hardware would be used once and discarded, causing all of its electronics/hardware to be discarded even if they are still functional. As can be appreciated, this can be wasteful and expensive, raising the cost of the patches (for both the manufacturer and consumer). To avoid wasting expensive components, and to reduce costs, these patches will sometimes use inferior components that could malfunction, provide low power for its circuitry, and/or low memory storage capacity—all of which are undesirable. Moreover, with single disposable patches, the equipment loses the ability to record/use data from, or share data with, other patches used on the same user, which is also desirable.

Accordingly, there is a need and desire for a better wearable adhesive patch.

### SUMMARY

Embodiments disclosed herein provide a wearable patch comprising multiple separable adhesive layers. By stacking multiple layers on top of each other, the same patch can be used, removed (e.g., when the user takes a shower or goes

swimming) and reapplied without affecting its adhesion to the user (i.e., another adhesive layer can be applied to the user when needed).

One or more of the layers can comprise electronics, mechanical components, gauze, medicine and/or other types of hardware or other substances suitable for the intended use of the patch. In use, a first adhesive layer of the patch is adhered to a user. When it is time to change layers, the patch is removed from the user, the first adhesive layer is removed from the patch to expose a second adhesive layer, and the second adhesive layer is applied to the user. The process may be repeated until the remaining adhesive layers of the patch have been used.

If the adhesive layers contain electronics, data can be passed through the layers to a main processing circuit and memory contained in e.g., a top adhesive layer. This way, the patch has the ability to record/use data from, or share data with, other layers throughout the use of the patch. In addition, the layers can be powered by a single power source in the top adhesive layer or by individual power sources in each layer. Moreover, more expensive and better quality components can be used in the top layer, while disposable components can be used in the lower layers; providing better functionality of the patch circuitry while also reducing its cost because the relatively expensive hardware (that would have been disposed of with each use of a single use patch) is preserved until the lifetime of the multi-layer patch has expired (i.e., all of the layers are used).

### BRIEF DESCRIPTION OF THE DRAWING

FIG. 1 illustrates an example wearable patch comprising multiple separable adhesive layers in accordance with an embodiment disclosed herein.

FIG. 2 illustrates another example of a wearable patch comprising multiple separable adhesive layers in accordance with another embodiment disclosed herein.

### DETAILED DESCRIPTION

In the following detailed description, a plurality of specific details, such as types of materials and dimensions, are set forth in order to provide a thorough understanding of the preferred embodiments discussed below. The details discussed in connection with the preferred embodiments should not be understood to limit the claimed invention. Furthermore, for ease of understanding, certain method steps are delineated as separate steps; however, these steps should not be construed as necessarily distinct nor order dependent in their performance.

FIG. 1 illustrates an example wearable patch 10 comprising multiple separable adhesive lower layers 12a, 12b, 12c and a top layer 14 in accordance with an embodiment disclosed herein. In the illustrated embodiment, there are three lower layers 12a, 12b, 12c and a top layer 14. It should be appreciated that any number of layers can be used and that the disclosed embodiment should not be limited to the number of layers illustrated in FIG. 1. The patch 10 can include as many layers that are practical for the application (e.g., three-day, seven-day, thirty-day patch, etc.). For example, a three-day patch could comprise three separate lower layers 12a, 12b, 12c, one for each day, and a top layer 14 to e.g., protect the adhesiveness of the lower layers 12a, 12b, 12c. If the top layer 14 is constructed the same as the lower layers, then the three-day patch could comprise only two lower layers 12a, 12b for days one and two and the top layer 14 for day three.

Each lower layer **12a**, **12b**, **12c** comprises a substrate **22** having an adhesive **20** formed on one surface. The top layer **14** also comprises a substrate **26** having an adhesive **24** formed on one surface. In one embodiment, when the patch **10** will be applied to a person's body, the substrates **22**, **26** comprise white polyethylene foam such as e.g.,  $\frac{1}{16}$ " 4# cross linked polyethylene foam. Similarly, when the patch **10** will be applied to a person's body, the substrates **22**, **26** are coated with an adhesive **20**, **24** such as e.g., an aggressive medical grade pressure-sensitive adhesive (e.g., MA-46 acrylic medical grade adhesive). Although not shown, the adhesive side of one or more layers in the patch **10** may be protected by a liner or release paper such as e.g., a siliconized polycoated release paper (e.g., 84# siliconized polycoated Kraft release paper). The adhesive side of one or more layers in the patch **10** may include the liner, release paper or some other substance that provides quick/easy release/removability of the layer from the patch **10**. It should be appreciated that less than all layers may have a liner, release paper, etc. It should be appreciated that the embodiments are not limited to the type of substrate, adhesive or liner (if used) discussed herein and that any suitable substrate, adhesive or liner may be used to form the patch **10**.

Although not shown, the substrates **22**, **26** can comprise gauze (e.g., the patch **10** is intended to be used as a bandage), medicine (e.g., the patch **10** is intended to be used to apply medicine to treat a wound, infection or a patient's addiction) and/or another substance. An embodiment of a patch **110** that includes electronics or other hardware is discussed below with reference to FIG. 2. In one embodiment, the top layer **14** can comprise a durable coating to provide more protection (e.g., water-proofing) for the other layers **12a**, **12b**, **12c**. It should be appreciated, however, that lower layers **12a**, **12b**, **12c** are protected by the layers above them in the stack of layers **12a**, **12b**, **12c**, **14** and that the durable coating (or other coating) would be providing additional protection. Additionally or alternatively, the top layer **14** can contain a design and/or colors rendering the patch **10** esthetically pleasing to the user and others. For example, the patch **10** can be viewed as a tattoo or other form of body art. Additionally or alternatively, the top layer **14** can comprise padding or another suitable substance to provide protection/comfort to the user in case contact is made to the outside of the patch **10**. In addition, although not shown, the substrates **22**, **26** can include a tab or other component to help the user separate the layers **12a**, **12b**, **12c**, **14** from each other when it is time to remove a layer and/or the patch **10**.

In use, the patch **10** (e.g., a 7-day patch) is removed from its packaging and adhered to the user at the desired location. If the lower layer **12a** includes a liner, the liner would be removed before the patch **10** is adhered to the user. After the first intended use of the layer **12a** (e.g., after day one, before a shower, etc.), the entire patch **10** is removed, the bottom layer **12a** is peeled off and disposed of. The remaining layers **12b**, **12c**, **14** of the patch **10** should still have fresh adhesive because they are protected by each other and the substrate **26** of the top layer **14**. The patch **10** can then be re-adhered to the desired location on the user using the next available adhesive layer (e.g., **12b**). This process is repeated for each intended use of the patch. When last usable layer is used, it can be peeled off and disposed of.

As can be appreciated, stacking multiple adhesive layers in one patch **10** creates more convenient user experience and less packaging in comparison to today's wearable patches. In the illustrated embodiment, the patch **10** comprises three lower layers **12a**, **12b**, **12c** and a top layer **14**. Existing patches would require four separate packages, creating

packaging waste and placing the burden on the user to carry or have access to multiple individual packages.

Although the patch **10** is advantageously used as a bandage or other type of patch applied to a person's body, the patch **10** illustrated in FIG. 1 can be used in many other ways. As such, the illustrated patch **10** is not limited solely to medical use (e.g., bandages, etc.) and/or application to a person's body. For example, the patch **10** can be used as a multiple layer adhesive tape to cover something or hold two or more items together. This would be useful for situations in which the adhesive wears off and a new adhesive tape of the same/similar size is needed.

FIG. 2 illustrates an example wearable patch comprising multiple separable adhesive lower layers **112a**, **112b**, **112c** and a top layer **114** in accordance with an embodiment disclosed herein. In the illustrated embodiment, there are three lower layers **112a**, **112b**, **112c** and a top layer **114**. It should be appreciated that, like the patch **10** illustrated in FIG. 1, any number of layers can be used in patch **110** and that the disclosed embodiment should not be limited to the number of layers illustrated in FIG. 2.

Each lower layer **112a**, **112b**, **112c** comprises a substrate **122** having an adhesive **120** formed on one surface. The top layer **114** also comprises a substrate **126** having an adhesive **124** formed on one surface. Although not shown, the adhesive side of one or more layers in the patch **110** is preferably protected by a liner or release paper. The adhesive side of one or more layers in the patch **110** may include the liner, release paper or some other substance that provides quick/easy release/removability of the layer from the patch **110**. It should be appreciated that less than all layers may have a liner, release paper, etc. It should be appreciated that the materials used for the substrates **122**, **126**, adhesives **120**, **124** and release paper can be the same as the materials used for the patch **10** illustrated in FIG. 1. It should also be appreciated that the disclosed embodiments are not limited to the type of substrate, adhesive or liner (if used) discussed herein and that any suitable substrate, adhesive or liner may be used to form the patch **110**.

In one embodiment, the top layer **114** can comprise a durable coating to provide more protection (e.g., water-proofing) for the other layers **112a**, **112b**, **112c**. Additionally or alternatively, the top layer **114** can contain a design and/or colors rendering the patch **110** esthetically pleasing to the user and others. Additionally or alternatively, the top layer **114** can comprise padding or another suitable substance to provide protection/comfort to the user in case contact is made to the outside of the patch **110**. In addition, although not shown, the substrates **122**, **126** can include a tab or other component to help the user separate the layers **112a**, **112b**, **112c**, **114** from each other when it is time to remove a layer and/or the patch **10**.

As can be seen in FIG. 2, the various layers of the patch **110** include electrical devices (e.g., sensors, microphones, accelerometers) that interface with and/or monitor activity of the person the patch **110** is being applied to; as such, the patch **110** is suitable for use in monitoring e.g., a person's health, sleep patterns or response to physical activity (example uses of the patch **110** and its electronics are discussed below). In addition, the patch **110** could include electronics and components so that it can be used for recreational, fashion or other purposes such as e.g., a watch, smartphone, GPS, skin activated fashion 'mood' device. Furthermore, the patch **110** could include components to measure biological fluids (e.g., blood, hormones); for example, a person can wear a patch **110** to measure insulin or cardiac markers for heart attack (troponin). This allows the user to wear patches

to measure biological fluids sub-cutaneous or trans-dermal. With no external wiring, the patch 110 can be worn while the user showers. According to the illustrated embodiment, each lower layer 112a, 112b, 112c comprises a power component 130 (e.g., a battery or a connection to a power component 150 in the top layer 114), one or more sensors 132, 134, 136, 138, an integrated circuit (IC) chip (or circuit) 140 and a data bus portion 142. The sensors 132, 134, 136, 138 could be microphones, accelerometers, pressure sensors for sensing the wearer's pulse, humidity sensors for measuring sweat, temperature sensors for measuring heat, altimeters for measuring incline, and electrical sensors for measuring electrical heartbeats. In addition, the sensors 132, 134, 136, 138 can comprise more complex (higher order) sensors based on micro-electro-mechanical systems (MEMS) sensors or even microfluidic sensors. The illustrated top layer 114 comprises a power component 150 (e.g., a battery), a main IC chip 160 a memory device 170 and a bus portion 180.

Although not shown, the components in each layer 112a, 112b, 112c, 114 are interconnected by interconnects formed in or attached to the substrates 122, 126. Examples of suitable interconnects include e.g., embedded fine copper wire, etched silver plating, conductive polymers or flexible circuit boards; all of these interconnections are very flexible and readably available. Although not shown, other components can be included on each layer such as e.g., resistors; Bluetooth circuitry/chip, etc. depending upon the intended use of the patch 110. In addition, an on/off button/switch and/or other buttons/switches can also be present so that the user can e.g., activate/deactivate the electronics, cause the patch 110 to transmit or receive data, etc.

The top layer 114 comprises a main IC chip (or circuit) 160, which may be a programmed processor or a microcontroller and may include at least one low power communication mechanism (e.g., Bluetooth, wireless RF communications, RS-232/RS-432 serial port, USB connector, etc.) for communicating data collected by the patch's electronics to the outside world (discussed below). It should be appreciated that the layers 112a, 112b, 112c, 114 can communicate with each other via wireless communications as well. This would allow the top layer 114 to talk to the lower layers 112a, 112b, 112c to e.g., check stickiness, power levels, or malfunctions of any layer 112a, 112b, 112c. The top layer 114 would have the more expensive wireless technology while the lower layers 112a, 112b, 112c will have "low level" wireless technology to communicate upwards to the top of the stack. Alternatively, the lower layers 112a, 112b, 112c could require the more advanced wireless technology to provide for more robust sensing electronics in those layers.

It should be appreciated that the illustrated main IC chip 160 could comprise one or more chips and/or circuits connected to perform and control the intended function of the patch 110 and to communicate with an external source to input/output any needed data.

The IC chips 140 on the lower layers 112a, 112b, 112c can be programmed processor or microcontrollers that control the activity of the individual layer. These IC chips 140 are connected to the sensors 132, 134, 136, 138 and will collect data from the sensor and pass the data through the bus portion 142 where it can be used by another lower layer or the top layer 114. The IC chip 160 of the top layer 114 can process the data, have it stored in the memory device 170 and/or transmitted externally from the patch 110 using the communication mechanism in or connected to the chip 160. If desired, the main IC chip 160 could be connected to the IC chips 140 in the other layers 112a, 112b, 112c via a

suitable interconnect 162. Addressing, data and/or control data can be passed between the thus connected IC chips 140, 160 as desired. In addition, data can be passed between layers 112a, 112b, 112c, 114 using the data bus portions 142, 180. This data can be stored in the memory device 170, which in one embodiment is a flash memory or other type of non-volatile memory device.

In one embodiment, the power component 150 of the main layer 114 powers all of the layers 112a, 112b, 112c, 114. As such, the power components of the lower layers 112a, 112b, 112c merely need to be connections (e.g., a bus) to the power component 150. In another embodiment, each power component 130, 150 is a separate source of power for its layer. The power components 130, 150 in each layer are illustrated as being connected to each other (e.g., in a manner in which multiple batteries may be connected to each other). It should be appreciated, however, that the power components 130, 150 do not have to be connected to each other if they have enough power to power the electronics (i.e., sensors, IC chips, memory, data bus portion, etc.) on their respective layer. As can be appreciated, depending upon its intended duration of use for each layer (e.g., a few hours to one or more days), each patch 110 will have its own unique power requirements that dictate the type of power components 130, 150 used therein. It should be appreciated that the top layer 114 may need a more robust power component because it is the last layer disposed of. Similarly, lower layers 112a, 112b, 112c that are in an upper portion of the stack of lower layers may need a more robust power source than layers that are in the lower portion of the stack.

It should be appreciated that other types of power components besides batteries can be used. For example, the power components could be one or more of solar cells, hydraulic, hybrid, gas, chemical, mechanical, or other power components. It should also be appreciated that a layer, power component, or other electronics in the patch 110 can be activated e.g., by skin contact, adhesive sticking, adhesive heating and/or removal of the liner that had components (electrical or non-electrical) and which lost contact with the adhesive/stick-to-skin layer, thus turning on that layer in whole or solely parts/portions of that layer. In addition, a layer above another layer may have its power component in the off state because it has not yet been applied to e.g., the user's skin.

As can be appreciated, by stacking multiple adhesive layers on top of each other, more expensive electronic/hardware components can be used on the top layer 114 while less expensive (and more easily disposable) electronic/hardware components can be placed in lower layers 112a, 112b, 112c, which are used and disposed of at regular intervals. This reduces costs because the necessary expensive hardware is not being disposed of after each use of a layer. This also means that more durable electronic/hardware components can be used in the top layer 114 since the top layer 114 is not discarded until the intended usefulness/lifetime of the patch 110 has expired. Likewise, the top layer 114 can comprise more robust power, memory storage and/or communication electronic/hardware components for the same reason. Thus, there will be less chance that the patch 110 will malfunction; in addition, the patch 110 can process, store and transmit more data than existing patches.

Although not intended to be limiting, the following are examples of the electronic/hardware components that could be used in the patch 110. Example sensors 132, 134, 136, 138 include off-the-shelf microphones made e.g., by Panasonic (part number WM-64K) and/or accelerometers made

e.g., by Analog Devices (part number ADXL362BCCZ). These are inexpensive devices that are suitable for use in the regularly disposable lower layers **112a**, **112b**, **112c**. An example of the power component **150** used in the top layer **114** can include a lithium battery such as e.g., the CR2032 battery by Panasonic. An example of the IC chip **160** used in the top layer **114** can include an MSP430F5528IYFF micro controller by Texas Instrument.

As mentioned above, the patch **110** can collect data (via the sensors **132**, **134**, **136**, **138**), process the data and/or store it in the memory device **170** in the top layer **114**. The data can be passed between layers **112a**, **112b**, **112c** and to the top layer **114** (via bus portions **142**, **180**). Thus, with the preservation of IC chip **160** and memory **170** of the top layer **114**, data from the disposable lower layers **112a**, **112b**, **112c** is recorded allowing the data to be integrated and more robust data analysis to be performed on the patch **110**, if desired. In addition, it is desirable to output the raw or processed data to the “outside” world. Thus, the firmware and embedded software provided in the top layer **114** communicates desired data to an external device (e.g., computer, tablet, smart phone, etc.) or a network/Internet “cloud” using one or more of Bluetooth or other wireless communication or with a hardwired communication mechanism such as e.g., a USB, RS-232 or RS-432 port on the patch **110**.

As can be appreciated, there are numerous uses for the patches **10**, **110** disclosed herein. As mentioned above, patch **10** can be used as a bandage (e.g., when gauze or other suitable material is contained on/within the layers **12a**, **12b**, **12c**, **14**), can be used to apply medicine to treat a wound, infection or a patient’s addiction (e.g., when medicine or another substance is contained on/within the layers **12a**, **12b**, **12c**, **14**), or can be used as a multi-layer adhesive tape. Patch **110**, because it contains electronics/hardware, can be used for at least the following applications: monitoring sleep apnea or other sleeping disorders/problems; monitoring a discharged patient; self-monitoring a person’s response to physical activity; and monitoring how a child/baby is breathing. In addition, the patch **110** can be adapted to be used with medical equipment such as e.g., cardio-rhythm devices (e.g., EKG and Holter monitors) and diabetes devices (e.g., artificial pancreas). Moreover, the patch **110** can be used as a digital bandage, providing both a healing function and a health monitoring function at the same time. The patch **110** could be used as a point-of-care fluid reading device where the lower layer is “dirty” thus, protecting top layer from contamination. The patch **110** could be used as point of care devices/analyzers that monitor CBC, minerals, chemical levels. (related to POC type device), etc. The patch **110** could use Bluetooth ‘pairing’ such that e.g., if children in one family are wearing the patch **110**, a parent can monitor their proximity to each other and an alarm can be sounded if one or more of the children stray too far (e.g. this would be useful at a large event). Once again, it should be appreciated that the disclosed patches **10**, **110** should not be limited to a particular use and/or construction and that the following examples are merely for illustration purposes.

When used to monitor sleep apnea, or other sleeping disorders, a user could apply a e.g., a 3-day patch **110** having a lower layer **112a**, **112b**, **112c** for each day/night being monitored. The user opens the package, hits the on switch, peels off the liner (if provided) from the lowest layer **112a**, and sticks the patch **110** on his/her neck. Real-time sleep data (e.g., breathing and body motion) is sent wirelessly to a remote device provided by a doctor or e.g., a smart phone, tablet, or computer using e.g., Bluetooth communications.

When the user wakes up, he/she peels off the patch **110** and disposes the lowermost layer **112a**. The user goes about his/her daily activities and when it is time to go back to sleep, he/she reapplies the patch **110** using the next lower layer (e.g., **112b**). This process is repeated until the lower layers **112a**, **112b**, **112c**, etc. are used up. In addition to, or alternatively, the monitored data can be stored in the memory device **170** and the top layer **114** can be attached, via a wireless or wired connection, to a device that can download the data from the memory device **170**.

The disclosed patch **110** can be used by a hospital to reduce its readmission rate by monitoring a discharged patient for an extended period of time (e.g., 60 days). When used in this type of application, a user is provided with a one or two month patch **110** that is worn continuously for approximately twenty-four hours a day (i.e., the patch **110** is only removed to peel off a lower layer and then reapplied). Real-time results are recorded during the day and sent e.g., to real-time Internet/network cloud associated with the hospital or patient’s doctor. The patch **110** is beneficial to the patient because the patient can take a shower without wearing bulky devices (e.g., Halter Monitor) as is presently required. It should be appreciated that long-use patches can be implemented in many ways. For example, a 60-day patch could be implemented as one big patch containing 60/61 layers; alternatively, the patch **110** could be divided into “intervals” (e.g., monthly, weekly, pack of five layers, etc.). It should be appreciated that the uniqueness of the top layer **114** (and its relatively expensive components) may also determine the stack size of the patch **110**. Moreover, the patch **110** can be packaged with other patches **110** in the same package/box (e.g., 6 ten-day patches in one package); a digital time stamp could be used to show when one patch **110** can be or was used and then the next patch **110**, etc. (i.e., the patches **110** are automatically dated). When multiple patches **110** are to be used, one patch **110** can contain a master top layer **114** while the other patches **110** can contain solely lower layers **112a**, **112b**, **112c** or modified top layers **114** with less electronics than the main top layer **114**.

The disclosed patch **110** can be used for self-monitoring of a person’s health during physical activity such as jogging or yoga. The user will wear the patch **110** during the activity and then may look at results e.g., real-time on a smart phone/tablet application or a later time on any suitable device. As another example, people showing up for a yoga class can buy the disclosed low-cost patch **110** while also paying for a towel or mat. People use the patch as a way to start new conversations with their coach who can then review data from the patch **110**.

As can be appreciated, the patches **110** can be made small enough for a parent to apply them to a baby or small child. This way, the parent can monitor a baby/child’s breathing, sleep pattern, and/or asthma. The disclosed patch **110** is also easy to use, even a child could use it on his/her own. It should also be appreciated that the patches **10/110** could include mechanical supports or other material to conform the patch **10/110** to a particular shape such as e.g., a curved shape. For example, the top layer **14/114** could mold or hold the rest of the layers in the stack in the desired shape.

The foregoing examples are provided merely for the purpose of explanation and are in no way to be construed as limiting. While reference to various embodiments is made, the words used herein are words of description and illustration, rather than words of limitation. Further, although reference to particular means, materials, and embodiments are shown, there is no limitation to the particulars disclosed herein. Rather, the embodiments extend to all functionally

equivalent structures, methods, and uses, such as are within the scope of the appended claims.

Additionally, the purpose of the Abstract is to enable the patent office and the public generally, and especially the scientists, engineers and practitioners in the art who are not familiar with patent or legal terms or phraseology, to determine quickly from a cursory inspection the nature of the technical disclosure of the application. The Abstract is not intended to be limiting as to the scope of the present inventions in any way.

What is claimed is:

1. A re-usable patch comprising:

a plurality of removable lower layers, each lower layer having a substrate with a first surface and a second surface, the removable lower layers being configured into a stack, each lower layer comprising a same lower layer electronics as other lower layers in the stack; and a top layer provided over a second surface of a topmost lower layer in the stack, the top layer comprising top layer electronics in communication with the electronics of the lower layers,

wherein the electronics on the lower layers comprise one or more sensors configured to monitor a same characteristic or activity of a wearer of the patch,

wherein each of said lower layers is configured to be removable such that removal of a lower layer removes the electronics of that lower layer and exposes the first surface of a next lower layer in the stack such that the one or more sensors of a lowest one of said lower layers monitor the characteristic or activity of the wearer and the one or more sensors of all other lower layers are inactive, and

wherein each of said lower layers is configured so that upon removal of a lowest of said lower layers, the one or more sensors of the next lower layer in the stack monitors the characteristic or activity of the wearer.

2. The patch of claim 1, further comprising a liner attached to the adhesive of a bottommost layer in the stack.

3. The patch of claim 2, wherein the liner comprises release paper.

4. The patch of claim 1, wherein the one or more sensors are configured to monitor one or more of movement, breathing, and biological fluids of the wearer.

5. The patch of claim 1, wherein the lower layer and top layer electronics comprise one or more of microphones, accelerometers, pressure sensors, humidity sensors, temperature sensors, altimeters, electrical sensors, microcontrollers, power source components, data bus components, memory storage devices and communication devices.

6. The patch of claim 5, wherein the power source components comprise solar cells.

7. The patch of claim 5, wherein the communication devices comprise wired or wireless communication devices.

8. The patch of claim 1, wherein at least one of the lower layers comprises a tab configured to assist with removal of the at least one of the lower layers from the patch.

9. The patch of claim 1, wherein each first surface comprises an adhesive formed thereon.

10. A patch comprising:

a plurality of first layers formed into a stack; and

a second layer provided over a topmost first layer of the stack,

wherein each first layer and the second layer comprises a first surface and a second surface, and a second surface of a lower first layer in the stack is removably adhered to a first surface of an upper first layer in the stack,

wherein each first layer comprises at least one sensor and an integrated circuit configured to perform a monitoring function,

wherein the at least one sensor and the integrated circuit of a lowest one first layer is configured to perform the monitoring function until the lowest one first layer is removed from the stack, and

wherein, when the lowest one first layer is removed, the at least one sensor and the integrated circuit of a next first layer perform the same monitoring function that the lowest one first layer performed prior to removal.

11. The patch of claim 10, wherein the second layer comprises electronics.

12. The patch of claim 10, wherein the electronics of each first layer are configured to pass data to the electronics on another first layer and the second layer using a data bus formed across each first layer and the second layer.

13. The patch of claim 10, wherein the electronics of each first layer are configured to pass data to the electronics on another first layer and the second layer using wireless communications.

14. The patch of claim 10, wherein the electronics of a first layer are powered by a power source on that first layer and the electronics of the second layer are powered by a power source on the second layer.

15. The patch of claim 10, wherein the electronics of a first layer are powered by a power source on the second layer.

16. The patch of claim 10, wherein each first surface comprises an adhesive and each second surface comprises a non-adhesive substrate.

17. A method comprising:

performing, with at least one sensor and an integrated circuit of a lowest one of a plurality of first layers formed into a stack, a monitoring function, wherein each first layer comprises a first surface and a second surface, and a second surface of a lower first layer in the stack is removably adhered to a first surface of an upper first layer in the stack; and

upon removal of the lowest one of the plurality of the first layers from the stack, performing, with at least one sensor and an integrated circuit of a next first layer, the same monitoring function that the lowest one first layer performed prior to removal, where each first layer comprises a same at least one sensor and integrated circuit as each other first layer in the stack.

18. The method of claim 17, wherein the monitoring function comprises monitoring one or more of movement, breathing, and biological fluids of a wearer.

19. The method of claim 17, further comprising passing, from the lowest one of the first layers or the next first layer, data generated by performing the monitoring function to electronics on the second layer.

专利名称(译)	可穿戴贴片包括多个可分离的粘合剂层		
公开(公告)号	<a href="#">US10226216</a>	公开(公告)日	2019-03-12
申请号	US15/456051	申请日	2017-03-10
[标]申请(专利权)人(译)	赞索斯有限责任公司		
申请(专利权)人(译)	ZANSORS LLC		
当前申请(专利权)人(译)	ZANSORS, LLC		
[标]发明人	DAS RANJIT TRAVAGLINI MARK		
发明人	DAS, RANJIT TRAVAGLINI, MARK		
IPC分类号	A61B5/00 A61B5/145 A61B5/11 A61B5/08 A61F13/02 A61M35/00 A61K9/70 G16H40/67 A61F13/00 A61B5/113		
CPC分类号	A61B5/6833 A61B5/08 A61B5/11 A61B5/1118 A61B5/145 A61B5/14517 A61B5/4806 A61B5/4818 A61B5/6801 A61F13/00051 A61F13/02 A61F13/025 A61F13/0246 A61K9/703 A61M35/00 G16H40/67 A61B5/0022 A61F2013/0094 A61B5/113 A61B2503/04 A61B2560/0412 G06F19/00		
优先权	61/699790 2012-09-11 US		
其他公开文献	US20170181705A1		
外部链接	<a href="#">Espacenet</a>		

摘要(译)

可穿戴贴片包括多个可分离的粘合剂层。一个或多个层可包括电子器件，机械部件，纱布，药品和/或适合于贴片的预期用途的其他类型的硬件。在使用中，贴片的第一层粘附到用户。当需要更换层时，从用户移除贴片，从贴片移除第一层以暴露第二粘合剂层，并将第二层施加到用户。可以重复该过程，直到已经使用了补丁的剩余层。

