




US 20150250423A1


(19) **United States**(12) **Patent Application Publication**  
**Hacker et al.**(10) **Pub. No.: US 2015/0250423 A1**(43) **Pub. Date: Sep. 10, 2015**(54) **ENDOTRACHEAL TUBE APPARATUS**(71) Applicant: **MEDTRONIC XOMED, INC.**,  
Jacksonville, FL (US)(72) Inventors: **David C. Hacker**, Jacksonville, FL  
(US); **Maria Charles Vijay Stanislaus**,  
Irvine, CA (US); **Wenjeng Li**, Saint  
Johns, FL (US); **Dwayne S. Yamasaki**,  
St. Augustine, FL (US); **William C.**  
**Brunnett**, Mission Viejo, CA (US);  
**Kevin L. McFarlin**, St. Johns, FL (US);  
**James Britton Hissong**, Jacksonville,  
FL (US); **Robert K. Vaccaro**, Ponte  
Vedra Beach, FL (US); **John M.**  
**Murphy**, Jacksonville, FL (US); **Carla**  
**A. Pagotto**, Ponte Vedra Beach, FL  
(US); **Tino Schuler**, Jacksonville, FL  
(US)(21) Appl. No.: **14/716,351**(22) Filed: **May 19, 2015****Related U.S. Application Data**(63) Continuation of application No. 12/896,578, filed on  
Oct. 1, 2010, now Pat. No. 9,037,226.(60) Provisional application No. 61/248,294, filed on Oct.  
2, 2009.**Publication Classification**(51) **Int. Cl.****A61B 5/00** (2006.01)**A61B 5/0492** (2006.01)**A61B 5/07** (2006.01)**A61B 5/0488** (2006.01)**A61B 5/11** (2006.01)**A61B 5/01** (2006.01)**A61B 1/07** (2006.01)**A61B 1/04** (2006.01)**A61B 1/267** (2006.01)**A61M 16/04** (2006.01)**A61B 5/04** (2006.01)(52) **U.S. Cl.**CPC ..... **A61B 5/6853** (2013.01); **A61M 16/0434**  
(2013.01); **A61B 5/0492** (2013.01); **A61B 5/07**  
(2013.01); **A61B 5/04886** (2013.01); **A61B**  
**5/04012** (2013.01); **A61B 5/01** (2013.01);  
**A61B 1/07** (2013.01); **A61B 1/04** (2013.01);  
**A61B 1/267** (2013.01); **A61B 5/11** (2013.01);  
**A61M 2230/08** (2013.01); **A61M 2205/3546**  
(2013.01); **A61B 2562/0209** (2013.01); **A61B**  
**2562/046** (2013.01); **A61B 2562/0219**  
(2013.01); **A61B 2562/0261** (2013.01); **A61M**  
**2205/0294** (2013.01)

(57)


**ABSTRACT**

An apparatus for monitoring EMG signals of a patient's laryngeal muscles includes an endotracheal tube having an exterior surface. Conductive electrodes are formed on the endotracheal tube. The conductive electrodes are configured to receive the EMG signals from the laryngeal muscles when the endotracheal tube is placed in a trachea of the patient. At least wireless sensor is formed on the endotracheal tube, and is configured to wirelessly transmit information to a processing apparatus.





**Fig. 1**



**Fig. 2**




Fig. 3












Fig. 4









**Fig. 11**




**Fig. 12A**






**Fig. 12B**




**Fig. 13**




**Fig. 14**









**Fig. 18**



**Fig. 19**



**Fig. 20**



**Fig. 21**




Fig. 22




Fig. 23




Fig. 25




Fig. 24





Fig. 26



**Fig. 27**




Fig. 28A




Fig. 28B




Fig. 28C







Fig. 28D

**Fig. 29**




**Fig. 30**




**Fig. 31**






**Fig. 32**



**Fig. 33**



**Fig. 34**




Fig. 35A







Fig. 35B



**Fig. 36C**



**Fig. 36A**



**Fig. 36B**




Fig. 37A




Fig. 37B




Fig. 38




Fig. 39A




Fig. 39B




Fig. 39C





Fig. 39D



**Fig. 39E**

## ENDOTRACHEAL TUBE APPARATUS

### CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation of U.S. patent application Ser. No. 12/896,578, filed Oct. 1, 2010, entitled "Endotracheal Tube Apparatus", and bearing Attorney Docket No. M190.350.102/P0035756.02, which claims priority under 35 U.S.C. §119(e)(1) to U.S. Provisional Patent Application Ser. No. 61/248,294, filed Oct. 2, 2009, entitled "Endotracheal Tube Apparatus", and bearing Attorney Docket No. M190.350.101/P0035756.00; and the entire teachings of which are incorporated herein by reference.

### BACKGROUND

[0002] Endotracheal tubes include electrodes that are designed to make contact with a patient's vocal cords to facilitate electromyographic (EMG) monitoring of the vocal cords during surgery when connected to an EMG monitoring device. Endotracheal tubes provide an open airway for patient ventilation, and provide for monitoring of EMG activity of the intrinsic laryngeal musculature when connected to an appropriate EMG monitor. Endotracheal tubes can provide continuous monitoring of the nerves supplying the laryngeal musculature during surgical procedures.

### SUMMARY

[0003] One embodiment is directed to an apparatus for monitoring EMG signals of a patient's laryngeal muscles. The apparatus includes an endotracheal tube having an exterior surface. Conductive ink electrodes are formed on the exterior surface of the endotracheal tube. The conductive ink electrodes are configured to receive the EMG signals from the laryngeal muscles when the endotracheal tube is placed in a trachea of the patient. At least one conductor is coupled to the conductive ink electrodes and is configured to carry the EMG signals received by the conductive ink electrodes to a processing apparatus.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0004] FIG. 1 shows an EMG endotracheal tube made from extruded polymer according to one embodiment.

[0005] FIG. 2 shows a close-up view of a portion of the endotracheal tube shown in FIG. 1 according to one embodiment.

[0006] FIG. 3 shows an EMG endotracheal tube made from PVC according to one embodiment.

[0007] FIG. 4 shows a close-up view of a portion of the endotracheal tube shown in FIG. 3 according to one embodiment.

[0008] FIG. 5 shows an EMG endotracheal tube with conductive ink electrodes printed on the tube according to one embodiment.

[0009] FIG. 6 shows a close-up view of a portion of the endotracheal tube shown in FIG. 5 according to one embodiment.

[0010] FIG. 7 is a diagram illustrating a cross-sectional view of the endotracheal tube shown in FIG. 5 according to one embodiment.

[0011] FIG. 8 shows an EMG endotracheal tube with multiple pairs of conductive ink electrodes printed around the circumference of the tube according to one embodiment.

[0012] FIG. 9 shows a close-up view of a portion of the endotracheal tube shown in FIG. 8 according to one embodiment.

[0013] FIG. 10 is a diagram illustrating a cross-sectional view of the endotracheal tube shown in FIG. 8 according to one embodiment.

[0014] FIG. 11 shows an EMG endotracheal tube with a primary cuff and a secondary cuff according to one embodiment.

[0015] FIG. 12A shows the secondary cuff of the endotracheal tube shown in FIG. 11 with conductive ink electrodes printed on the secondary cuff according to one embodiment.

[0016] FIG. 12B shows the secondary cuff of the endotracheal tube shown in FIG. 11 according to another embodiment.

[0017] FIG. 13 shows an EMG endotracheal tube with a visual indicator for tracking and verifying electrode location according to one embodiment.

[0018] FIG. 14 shows a close-up view of a portion of the endotracheal tube shown in FIG. 13 according to one embodiment.

[0019] FIG. 15 shows an EMG endotracheal tube with a magnet indicator for tracking and verifying electrode location according to one embodiment.

[0020] FIGS. 16 and 17 show close-up views of a portion of the endotracheal tube shown in FIG. 15 according to one embodiment.

[0021] FIG. 18 shows an EMG endotracheal tube with a coupling adapter to provide rotational freedom according to one embodiment.

[0022] FIG. 19 shows a close-up view of a portion of the endotracheal tube shown in FIG. 18 according to one embodiment.

[0023] FIG. 20 shows an EMG endotracheal tube with ribs on the top and bottom of the EMG electrodes according to one embodiment.

[0024] FIG. 21 shows a close-up view of a portion of the endotracheal tube shown in FIG. 20 according to one embodiment.

[0025] FIG. 22 shows an EMG endotracheal tube with conductive tape on the surface of the tube for recording EMG signals according to one embodiment.

[0026] FIG. 23 shows a close-up view of a portion of the endotracheal tube shown in FIG. 22 according to one embodiment.

[0027] FIG. 24 shows an EMG endotracheal tube with a custom extruded PVC tube according to one embodiment.

[0028] FIGS. 25 and 26 show close-up views of a portion of the endotracheal tube shown in FIG. 24 according to one embodiment.

[0029] FIG. 27 shows an EMG endotracheal tube positioned within a patient's throat according to one embodiment.

[0030] FIGS. 28A-28D show an EMG endotracheal tube with electrodes having an increased surface area according to various embodiments.

[0031] FIG. 29 shows an EMG endotracheal tube with an overall shape that is curved to match the shape of a human throat according to one embodiment.

[0032] FIG. 30 shows a cross-sectional view of an EMG endotracheal tube with electrodes configured to reduce or eliminate rotational sensitivity according to one embodiment.

[0033] FIG. 31 shows an EMG endotracheal tube with electrodes configured to reduce or eliminate rotational sensitivity according to another embodiment.



[0034] FIG. 32 shows a cuff for an EMG endotracheal tube according to one embodiment.

[0035] FIG. 33 shows an electrical schematic diagram of an electrode array configured to be used in an EMG endotracheal tube according to one embodiment.

[0036] FIG. 34 shows flexible, expanding electrodes configured to be used in an EMG endotracheal tube according to one embodiment.

[0037] FIG. 35A shows a first side view (posterior side) of an EMG endotracheal tube with three electrodes according to one embodiment.

[0038] FIG. 35B shows a second side view (rotated 90 degrees from the view shown in FIG. 35A) of the EMG endotracheal tube shown in FIG. 35A according to one embodiment.

[0039] FIG. 35C is a diagram illustrating a cross-sectional view of the endotracheal tube shown in FIGS. 35A and 35B according to one embodiment.

[0040] FIG. 36A shows a first side view (posterior side) of an EMG endotracheal tube with four electrodes according to one embodiment.

[0041] FIG. 36B shows a second side view (rotated 90 degrees from the view shown in FIG. 36A) of the EMG endotracheal tube shown in FIG. 36A according to one embodiment.

[0042] FIG. 36C is a diagram illustrating a cross-sectional view of the endotracheal tube shown in FIGS. 36A and 36B according to one embodiment.

[0043] FIG. 37A shows a first side view (posterior side) of an EMG endotracheal tube with four electrodes according to another embodiment.

[0044] FIG. 37B shows a second side view (rotated 90 degrees from the view shown in FIG. 37A) of the EMG endotracheal tube shown in FIG. 37A according to one embodiment.

[0045] FIG. 38 shows a side view of an EMG endotracheal tube with a plurality of ring electrodes according to one embodiment.

[0046] FIGS. 39A-39E show EMG endotracheal tubes with tube placement markings according to various embodiments.

#### DETAILED DESCRIPTION

[0047] FIG. 1 shows an EMG endotracheal tube 100 made from extruded polymer. FIG. 2 shows a close-up view of a portion of the endotracheal tube 100 shown in FIG. 1. Endotracheal tube 100 includes solid wires 102, fitting 104, cuff inflating conduit 106, extruded polymer tube 110, wire electrodes 112, and primary cuff 114. Solid wires 102 are connected to wire electrodes 112 at interconnection 108. Tube 110 transports gases to and from the lungs. Fitting 104 is configured to be connected to a respirating machine (not shown) for injecting air into the lungs and withdrawing air from the lungs. Cuff inflating conduit 106 is configured to be connected to a source of compressed air (not shown) for inflating cuff 114. Cuff inflating conduit 106 communicates with a lumen located in the wall of tube 110, and the lumen communicates with primary cuff 114. After endotracheal tube 100 is inserted into the trachea of a patient, electrode wires 112 sense EMG signals, which are output to an EMG processing machine, such as nerve integrity monitor (NIM) device 120, via solid wires 102. Die cut tape may be used to tape tube 110 to a patient's mouth to secure the tube and keep it appropriately positioned.

[0048] In one embodiment, the NIM 120 is configured to determine when the electrodes 112 are in contact with the vocal folds, and is configured to provide an alert to the surgeon when such contact is lost. In one embodiment, the NIM 120 is also configured to determine whether the electrodes 112 are in contact with muscle or tissue based on the received signals. In one embodiment, EMG tube 100 is configured to wirelessly communicate with the NIM 120, and the NIM 120 is configured to wirelessly monitor the electrodes 112. In form of this embodiment, the NIM 120 wirelessly transmits energy to the electrodes 112, and the electrodes 112 wirelessly transmit EMG signals to the NIM 120.

[0049] Some existing endotracheal tubes can rotate, which causes the electrodes to move away from the vocal folds. In contrast, tube 110 includes a flexible tube segment 113 that is configured to make contact with the vocal folds, and exposed electrodes 112 are formed over the flexible tube segment 113. The flexible tube segment 113 is more flexible or softer (e.g., made from a low durometer material) than the remainder of the tube 110, which allows the electrodes 112 to maintain better opposition with the vocal folds and reduce or eliminate translational and rotational movement of the tube 110. In one embodiment, primary cuff 114 is formed from a tacky, low-durometer material to contour against the tracheal rings, which helps to reduce or eliminate translational and rotational movement of the tube 110. In one embodiment, electrodes 112 are about 1.3 inches long. In another embodiment, electrodes 112 are about 1.9 inches long. Extending the length of electrodes 112 helps the tube 110 to become less sensitive to neck extension.

[0050] In one embodiment, tube 110 is a braided tube that is more flexible than conventional solid polymer tubes, and that reduces kinking. Tube 110 according to one embodiment is formed from a braided polymer or nitinol within a thin-walled tube, and reduces or eliminates rotation of the tube at the vocal folds, while allowing a proximal portion of the tube to rotate.

[0051] FIG. 3 shows an EMG endotracheal tube 300 made from PVC. FIG. 4 shows a close-up view of a portion of the endotracheal tube 300 shown in FIG. 3. Endotracheal tube 300 includes solid wires 302, fitting 304, cuff inflating conduit 306, PVC tube 310, taped-on electrodes 312, primary cuff 314, and electrode wires 316. Solid wires 302 are connected to electrode wires 316 at interconnection 308, and electrode wires 316 are connected to taped-on electrodes 312. Tube 310 transports gases to and from the lungs. Fitting 304 is configured to be connected to a respirating machine (not shown) for injecting air into the lungs and withdrawing air from the lungs. Cuff inflating conduit 306 is configured to be connected to a source of compressed air (not shown) for inflating cuff 314. Cuff inflating conduit 306 communicates with a lumen located in the wall of tube 310, and the lumen communicates with primary cuff 314. After endotracheal tube 300 is inserted into the trachea of a patient, taped-on electrodes 312 sense EMG signals, which are output to an EMG processing machine (e.g., NIM device 120) via solid wires 302.

[0052] FIG. 5 shows an EMG endotracheal tube 500 with conductive ink electrodes printed on the tube according to one embodiment. FIG. 6 shows a close-up view of a portion of the endotracheal tube 500 shown in FIG. 5 according to one embodiment. Endotracheal tube 500 includes solid wires 502, fitting 504, cuff inflating conduit 506, PVC tube 510, conductive ink electrodes 512, and primary cuff 514. Solid wires 502

are connected to conductive ink electrodes **512** at interconnection **508**. Tube **510** transports gases to and from the lungs. Fitting **504** is configured to be connected to a respirating machine (not shown) for injecting air into the lungs and withdrawing air from the lungs. Cuff inflating conduit **506** is configured to be connected to a source of compressed air (not shown) for inflating cuff **514**. Cuff inflating conduit **506** communicates with a lumen **522** (FIG. 7) located in the wall **520** of tube **510**, and the lumen **522** communicates with primary cuff **514**. After endotracheal tube **500** is inserted into the trachea of a patient, conductive ink electrodes **512** sense EMG signals, which are output to an EMG processing machine (e.g., NIM device **120**) via solid wires **502**.

[0053] FIG. 7 is a diagram illustrating a cross-sectional view of the endotracheal tube **500** shown in FIG. 5 according to one embodiment. As shown in FIG. 7, lumen **522** is located in the wall **520** of tube **510** for inflating the cuff **514**. Conductive ink electrodes **512** are formed on the outer surface of wall **520**. In one embodiment, conductive ink electrodes **512** are formed by tracing or printing a silver filled polymer conductive ink or a carbon conductive ink on tube **510**. Conductive inks are available in variety of flowable material choices such as Silver, Carbon, Gold, Platinum, Palladium, Silver-Tungsten, and Silver-Titanium. Conductive inks can be deposited on the substrate using various known technologies such as PAD printing, Screen printing, Ink jet dispensing, digital printing, Micropen dispensing, painting, vapor deposition, and plasma sputtering. Conductive inks can be used both for stimulation and recording purposes in nerve monitoring applications.

[0054] FIG. 8 shows an EMG endotracheal tube **800** with multiple pairs of conductive ink electrodes printed around the circumference of the tube according to one embodiment. FIG. 9 shows a close-up view of a portion of the endotracheal tube **800** shown in FIG. 8 according to one embodiment. Endotracheal tube **800** includes fitting **804**, cuff inflating conduit **806**, PVC tube **810**, conductive ink electrodes **812**, and primary cuff **814**. Tube **810** transports gases to and from the lungs. Fitting **804** is configured to be connected to a respirating machine (not shown) for injecting air into the lungs and withdrawing air from the lungs. Cuff inflating conduit **806** is configured to be connected to a source of compressed air (not shown) for inflating cuff **814**. Cuff inflating conduit **806** communicates with a lumen **822** (FIG. 10) located in the wall **820** of tube **810**, and the lumen **822** communicates with primary cuff **814**. After endotracheal tube **800** is inserted into the trachea of a patient, conductive ink electrodes **812** sense EMG signals, which are output to an EMG processing machine (e.g., NIM device **120**) via solid wires connected to the electrodes **812** (e.g., solid wires **502** shown in FIG. 5).

[0055] FIG. 10 is a diagram illustrating a cross-sectional view of the endotracheal tube **800** shown in FIG. 8 according to one embodiment. As shown in FIG. 10, lumen **822** is located in the wall **820** of tube **810** for inflating the cuff **814**. Multiple pairs of conductive ink electrodes **812** are formed around the circumference of the tube **810** to achieve uninterrupted EMG recording even when the tube **810** is shifted rotationally. In one embodiment, conductive ink electrodes **812** are formed by tracing or printing a silver filled polymer conductive ink on tube **810**.

[0056] FIG. 11 shows an EMG endotracheal tube **1100** with a primary cuff **1114** and a secondary cuff **1130** according to one embodiment. FIG. 12A shows a close-up view of the secondary cuff **1130** of the endotracheal tube shown in FIG.

**11** with conductive ink electrodes **1132** printed on the secondary cuff **1130** according to one embodiment. FIG. 12B shows a close-up view of the secondary cuff **1130** of the endotracheal tube shown in FIG. 11 according to another embodiment. The embodiment of the secondary cuff **1130** shown in FIG. 12A is identified by reference number **1130-1**, and the embodiment shown in FIG. 12B is identified by reference number **1130-2**. Endotracheal tube **1100** includes PVC tube **1110**, primary cuff **1114**, and secondary cuff **1130** with conductive ink electrodes **1132** formed thereon. Tube **1110** transports gases to and from the lungs. At least one cuff inflating conduit (not shown) is configured to be connected to a source of compressed air (not shown) for inflating cuffs **1114** and **1130**. After endotracheal tube **1100** is inserted into the trachea of a patient, the secondary cuff **1130** is inflated and the conductive ink electrodes **1132** come in contact with the vocal folds and sense EMG signals from the vocal folds. The sensed signals are output to an EMG processing machine (e.g., NIM device **120**) via wires connected to the electrodes **1132**. In one embodiment, the secondary cuff **1130** is made of a compliant or semi-compliant material, and conductive ink electrodes **1132** are formed by tracing or printing a silver filled polymer conductive ink on secondary cuff **1130**. The secondary cuff **1130** with the silver ink printed thereon helps establish a better electrode contact when inflated over the vocal folds. Electrodes **1132** may be sprayed on secondary cuff **1130** or tube **1110**, and may cover substantially the entire surface of secondary cuff **1130**. Electrodes **1132** may take a variety of shapes or forms other than that shown in FIG. 12A, such as any of the shapes or forms shown in any of the other Figures of the present disclosure, or other shapes. In other embodiments, EMG tube **1100** may include three or more cuffs.

[0057] Secondary cuff **1130** may also have a different shape than that shown in FIG. 12A, such as that shown in FIG. 12B. As shown in FIG. 12B, secondary cuff **1130-2** has a flattened peanut shape with two rounded ends **1133** and **1137** that taper to a mid portion **1135**. The flattened peanut shape of the cuff **1130-2** according to one embodiment fits or contours to the shape of the vocal folds, and helps to reduce or eliminate translational and rotational movement of the tube **1110**. In another embodiment, the secondary cuff **1130** is formed from an elastomer or foam pillow with two rounded ends that taper to a mid portion like that shown in FIG. 12B. In one form of this embodiment, the ends of the pillow have a substantially triangular cross-section. In one embodiment, the secondary cuff **1130** includes one or more position sensors to monitor the position or location of the tube **1110**.

[0058] FIG. 13 shows an EMG endotracheal tube **1300** with a visual indicator **1320** for tracking and verifying electrode location according to one embodiment. FIG. 14 shows a close-up view of a portion of the endotracheal tube **1300** shown in FIG. 13 according to one embodiment. Endotracheal tube **1300** includes solid wires **1302**, fitting **1304**, cuff inflating conduit **1306**, PVC tube **1310**, electrodes **1312**, primary cuff **1314**, and visual indicator **1320**. Solid wires **1302** are connected to electrodes **1312**. Tube **1310** transports gases to and from the lungs. Fitting **1304** is configured to be connected to a respirating machine (not shown) for injecting air into the lungs and withdrawing air from the lungs. Cuff inflating conduit **1306** is configured to be connected to a source of compressed air (not shown) for inflating cuff **1314**. Cuff inflating conduit **1306** communicates with a lumen located in the wall of tube **1310**, and the lumen communicates with

primary cuff **1314**. After endotracheal tube **1300** is inserted into the trachea of a patient, electrodes **1312** sense EMG signals, which are output to an EMG processing machine (e.g., NIM device **120**) via solid wires **1302**.

**[0059]** In one embodiment, visual indicator **1320** is a bright lit light emitting diode (LED) or fiber optic light source that is used to track and verify the location of the electrodes **1312**. The visual indicator **1320** is placed on the surface of the tube **1310** near the electrodes **1312** to identify the electrode position with respect to the vocal fold after tube intubation. A user can see the light spot facing anterior and mark the spot on the patient's skin. In another embodiment, visual indicator **1320** is an LED band that surrounds a portion or the entire circumference of tube **1310**.

**[0060]** FIG. **15** shows an EMG endotracheal tube **1500** with a magnet indicator **1520** for tracking and verifying electrode location according to one embodiment. FIGS. **16** and **17** show close-up views of a portion of the endotracheal tube **1500** shown in FIG. **15** according to one embodiment. Endotracheal tube **1500** includes solid wires **1502**, cuff inflating conduit **1506**, tube **1510**, electrodes **1512**, primary cuff **1514**, and magnetic indicator **1520**. Solid wires **1502** are connected to electrodes **1512**. Tube **1510** transports gases to and from the lungs. A fitting of the tube **1500** is configured to be connected to a respirating machine (not shown) for injecting air into the lungs and withdrawing air from the lungs. Cuff inflating conduit **1506** is configured to be connected to a source of compressed air (not shown) for inflating cuff **1514**. Cuff inflating conduit **1506** communicates with a lumen located in the wall of tube **1510**, and the lumen communicates with primary cuff **1514**. After endotracheal tube **1500** is inserted into the trachea of a patient, electrodes **1512** sense EMG signals, which are output to an EMG processing machine (e.g., NIM device **120**) via solid wires **1502**.

**[0061]** In one embodiment, magnetic indicator **1520** is a tiny magnet that is used to track and verify the location of the electrodes **1512**. The magnetic indicator **1520** is placed on the surface of the tube **1510** near the electrodes **1512** to identify the electrode position with respect to the vocal fold after tube intubation. A user can track and locate the magnet inside the patient with a device **1530** (FIG. **17**) that includes a magnet pick-up sensor.

**[0062]** In addition to the LED-based and magnet-based techniques described above with respect to FIGS. **13-17**, other embodiments may use other techniques for determining electrode location within a patient, such as the following: (1) locating an anatomy landmark; (2) Automatic Periodic Stimulation (APS) electrode tracking; (3) sonar/ultra sound (similar to a wall stud finder); (4) surgical navigation using a coil; (5) use of stimulator combined with locating device, and synchronizing the lighting of LED with the stimulator pulse of the wand; (6) use of an accelerometer (e.g., positioned on the cuff) to monitor movement; (7) use of a vibration sensor and air inlets and outlets so that air flow past the vocal folds causes vibration that is sensed by the vibration sensor; (8) use of an ultrasonic transducer in or on the tube, and a sensing circuit external to the body; (9) use of a resonant circuit for positional and rotational sensing (could use stimulator channel to provide pulses); use resonant vibration near vocal fold tissue resonance; mechanical impedance of the vocal fold is detected by impedance match and energy transfer to surrounding tissue; use surface acoustic wave or other mechanical resonator; (10) use of a pressure sensor or pressure sensor array near the electrode sites to detect engagement with the

vocal folds (e.g., a pressure sensitive surface with capacitive sensor on each side of the tube); (11) wireless sensors linked to a wireless interface (e.g., the tube may include a wireless video chip to send signals to an external monitor (e.g., picture-in-picture on the NIM or miniscreen) to view placement in real time); (12) temperature sensors (temperature will be higher when in contact with the vocal folds); (13) embedded fiber optic viewer with light source at proximal end and viewing window near electrodes (software in NIM to identify position); (14) one or more RF ID tags incorporated in or on the tube with signals sent to an external device or the NIM for reading and evaluation; (15) flexible piezo strips for monitoring the movement of one or more portions of the tube, such as the flexible tube segment **113** (FIGS. **1** and **2**)—monitoring movement of the flexible tube segment **113** indirectly results in monitoring of the movement of the vocal folds; (16) impedance monitors placed around one or more portions of the tube, such as around tube segment **113** (FIGS. **1** and **2**), to detect changes in the diameter of the tube at the vocal folds (such impedance monitoring allows the vocal fold movement to be monitored without recording EMG potentials); and (17) use electrodes with the ability to differentiate between muscle contact and non-muscle contact, which helps the NIM to ensure proper position and contact.

**[0063]** FIG. **18** shows an EMG endotracheal tube **1800** with a coupling adapter **1820** to provide rotational freedom according to one embodiment. FIG. **19** shows a close-up view of a portion of the endotracheal tube **1800** shown in FIG. **18** according to one embodiment. Endotracheal tube **1800** includes solid wires **1802**, fitting **1804**, cuff inflating conduit **1806**, PVC tube **1810**, electrodes **1812**, primary cuff **1814**, and plastic coupling adapter **1820**. Solid wires **1802** are connected to electrodes **1812**. Tube **1810** transports gases to and from the lungs. Fitting **1804** is configured to be connected to a respirating machine (not shown) for injecting air into the lungs and withdrawing air from the lungs. Cuff inflating conduit **1806** is configured to be connected to a source of compressed air (not shown) for inflating cuff **1814**. Cuff inflating conduit **1806** communicates with a lumen located in the wall of tube **1810**, and the lumen communicates with primary cuff **1814**. After endotracheal tube **1800** is inserted into the trachea of a patient, electrodes **1812** sense EMG signals, which are output to an EMG processing machine (e.g., NIM device **120**) via solid wires **1802**.

**[0064]** In one embodiment, after insertion of the endotracheal tube **1800** into a patient, the tube is taped to the patient's mouth. The coupling adapter **1820** is positioned at the proximal end (away from the patient's mouth), and allows the proximal end of the tube **1810** to swivel around as indicated by arrow **1830** in FIG. **19**, which minimizes rotational movement of the distal portion of the tube **1810** in the patient. In one embodiment, the coupling adapter **1820** allows thirty degrees of rotation in either direction. In another embodiment, endotracheal tube **1800** includes a tube within a tube configuration that allows a proximal portion of the tube to rotate while preventing rotation of the distal portion of the tube. In one embodiment, primary cuff **1814** is formed from a sticky or tacky material (e.g., a tacky balloon) to help prevent the distal portion of the tube from rotating.

**[0065]** FIG. **20** shows an EMG endotracheal tube **2000** with ribs **2020** on the top and bottom of the EMG electrodes **2012** according to one embodiment. FIG. **21** shows a close-up view of a portion of the endotracheal tube **2000** shown in FIG. **20** according to one embodiment. Endotracheal tube **2000**

includes solid wires **2002**, fitting **2004**, cuff inflating conduit **2006**, tube **2010**, electrodes **2012**, primary cuff **2014**, and ribs **2020**. Solid wires **2002** are connected to electrodes **2012**. Tube **2010** transports gases to and from the lungs. Fitting **2004** is configured to be connected to a respirating machine (not shown) for injecting air into the lungs and withdrawing air from the lungs. Cuff inflating conduit **2006** is configured to be connected to a source of compressed air (not shown) for inflating cuff **2014**. Cuff inflating conduit **2006** communicates with a lumen located in the wall of tube **2010**, and the lumen communicates with primary cuff **2014**. After endotracheal tube **2000** is inserted into the trachea of a patient, electrodes **2012** sense EMG signals, which are output to an EMG processing machine (e.g., NIM device **120**) via solid wires **2002**.

[0066] The ribs **2020** according to one embodiment provide a positive feel when passing the vocal fold during intubation, and the ribs **2020** on top and bottom of the vocal fold will not allow the tube **2010** to move out of position. In one embodiment, the ribs **2020** are shaped to match the contour of the opening, and are made with compliant or semi-compliant material. In another embodiment, ribs **2020** are implemented with inflatable balloons.

[0067] FIG. 22 shows an EMG endotracheal tube **2200** with conductive tape on the surface of the tube for recording EMG signals according to one embodiment. FIG. 23 shows a close-up view of a portion of the endotracheal tube **2200** shown in FIG. 22 according to one embodiment. Endotracheal tube **2200** includes fitting **2204**, cuff inflating conduit **2206**, tube **2210**, electrodes **2212**, and primary cuff **2214**. Solid wires are connected to electrodes **2212**. Tube **2210** transports gases to and from the lungs. Fitting **2204** is configured to be connected to a respirating machine (not shown) for injecting air into the lungs and withdrawing air from the lungs. Cuff inflating conduit **2206** is configured to be connected to a source of compressed air (not shown) for inflating cuff **2214**. Cuff inflating conduit **2206** communicates with a lumen located in the wall of tube **2210**, and the lumen communicates with primary cuff **2214**. After endotracheal tube **2200** is inserted into the trachea of a patient, electrodes **2212** sense EMG signals, which are output to an EMG processing machine (e.g., NIM device **120**) via solid wires attached to the electrodes **2212**.

[0068] In the embodiment illustrated in FIGS. 22 and 23, electrodes **2212** are strips of conducting tape that stick to the surface of the tube **2210**. In one embodiment, the conducting tape is a woven material, and replaces the solid wire electrodes found in some conventional tubes (2 channel or multiple pairs). In one embodiment, one or more of the strips **2212** shown in FIGS. 22 and 23 comprise a piezo strip for monitoring movement of the tube **2210**. In another embodiment, electrodes **2212** are covered with an expandable, conductive foam that expands when it absorbs moisture, thereby providing improved contact with the vocal folds.

[0069] FIG. 24 shows an EMG endotracheal tube **2400** with a custom extruded PVC tube according to one embodiment. FIGS. 25 and 26 show close-up views of a portion of the endotracheal tube **2400** shown in FIG. 24 according to one embodiment. Endotracheal tube **2400** includes solid wires **2402**, fitting **2404**, cuff inflating conduit **2406**, tube **2410**, electrodes **2412**, and primary cuff **2414**. Solid wires **2402** are connected to electrodes **2412**. Tube **2410** transports gases to and from the lungs. Fitting **2404** is configured to be connected to a respirating machine (not shown) for injecting air into the

lungs and withdrawing air from the lungs. Cuff inflating conduit **2406** is configured to be connected to a source of compressed air (not shown) for inflating cuff **2414**. Cuff inflating conduit **2406** communicates with a lumen located in the wall of tube **2410**, and the lumen communicates with primary cuff **2414**. After endotracheal tube **2400** is inserted into the trachea of a patient, electrodes **2412** sense EMG signals, which are output to an EMG processing machine (e.g., NIM device **120**) via solid wires **2402**.

[0070] In one embodiment, tube **2410** comprises a custom extruded PVC tube (rigid or reinforced), and the PVC cuff is not sticky like a silicone cuff. The size of the custom extruded PVC tube **2410** according to one embodiment is close to standard off-the-shelf endotracheal tubes.

[0071] Features of embodiments of the EMG endotracheal tubes described herein include: (1) more placement tolerant than conventional tubes; (2) NIM is used to help place the tube; (3) the electrode is periodically checked to assure constant contact; (4) intentional bend in correct direction for proper tube insertion; (5) include high brightness LED in tube to observe placement through the skin; (6) use external Hall sensors with magnets in the tube to sense correct tube placement; (7) kit-pack tapes for stabilizing the tube; (8) improved means to detect EMG generators and shunt tissue; (9) use muscle “artifact” as an indicator of proper placement (artifact can be minimized by adjusting tube position); (10) fiber optic bundle connected to light source or camera; (11) a “fixture” molded at the proximal end of the tube to register on the patient anatomy for proper orientation; (12) improved way and connector for plugging into the patient box; (13) creation of 4-channels from 2-channels via added connectors (not added wires) or cross-point switch within the NIM; (14) providing a signal from the NIM to measure resistance and phase angle of tissue contacting the electrodes to decide if there is enough EMG generator tissue vs. shunt tissue; (15) EMG tube with reduced overall outer diameter; and (16) reduced cost and quality associated issues with custom extruded silicone tubing by utilizing standard off the shelf endotracheal tube. Additional features and information are set forth below.

[0072] The EMG tube electrodes according to one embodiment may contact both EMG generators (striated muscle) and shunt tissue (conductive tissue that does not generate EMG signals but which does conduct current, thus shunting (reducing) the EMG signal available for the amplifier). A “high quality tube placement” has a high ratio of EMG generator tissue to shunt tissue.

[0073] Embodiments of the EMG endotracheal tubes described herein may include a conducting hydro gel coating on the electrodes, such as electrodes **112** (FIG. 1). Coating the electrodes with a conducting hydro gel increases the contact surface of the electrodes, allows for more rotation of the EMG tube without a loss of contact with the vocal folds, and results in an improved recorded signal. Some embodiments may use paddle electrodes for posterior and anterior monitoring, including monitoring arytenoids and posterior cricoarytenoid (PCA).

[0074] There are some problems with existing EMG endotracheal, such as: (1) ridges on the outside of the tube can cause tissue irritation; (2) the tube can shift rotationally during surgery; and (3) the tube wall is too thick. These problems are addressed in one embodiment in the following ways: (1) use of a non-silicone material such as pebax with Teflon for the tube, which allows the tube to slide easily (a high friction

material may be used for the cuff to help prevent translational shift); (2) placing bumps for wires on the inner diameter (ID) of the tube; (3) splicing together different pieces of tubing along the length (each with potentially a different cross-sectional shape) to get a more optimal cross-sectional geometry that more closely matches a patient's anatomy, such as using a first tube portion near the proximal end with a circular cross-section to allow rotation and a second tube portion near the vocal folds with a triangular cross-section (e.g., with a circular or triangular inner diameter); (4) just above the electrodes, adding a region of lower wall thickness to de-couple upper sections from lower section; and (5) decoupling the proximal end of the tube from the distal end by switching to a braided tube from a spring coil reinforced tube.

[0075] FIG. 27 shows an EMG endotracheal tube 2700 positioned within a patient's throat according to one embodiment. Endotracheal tube 2700 includes fitting 2704, tube 2710, electrodes 2712, primary cuff 2714, esophageal extension 2720, and esophageal electrodes 2722. The portions of the patient's anatomy shown in FIG. 27 include tongue 2730, trachea 2732, and esophagus 2734. Tube 2710 transports gases to and from the lungs. Fitting 2704 is configured to be connected to a respirating machine (not shown) for injecting air into the lungs and withdrawing air from the lungs. A cuff inflating conduit is configured to be connected to a source of compressed air for inflating cuff 2714. After endotracheal tube 2700 is inserted into the trachea 2732 of the patient, electrodes 2712 sense EMG signals, which are output to an EMG processing machine (e.g., NIM device 120) via solid wires connected to electrodes 2712.

[0076] As shown in FIG. 27, esophageal extension 2720 extends away from the tube 2710 and into the patient's esophagus 2734. The esophageal electrodes 2722 formed on the extension 2720 sense signals from the backside muscles of the vocal folds from the esophagus 2734. The electrodes 2722 according to one embodiment are used to record EMG signals of laryngeal muscles behind the larynx. In one embodiment, the electrodes 2722 are positioned behind the cricoid cartilage during surgery. Most of the muscles innervated by the recurrent laryngeal nerve (RLN) are behind and posterolateral to the larynx (e.g., arytenoids, posterior cricoarytenoid (PCA), and lateral cricoarytenoid (LCA)). Positioning the electrodes 2722 behind the cricoid cartilage provides superior EMG signals. In one embodiment, esophageal extension 2720 is also used to set both the depth of insertion of the tube 2710 and the angular placement.

[0077] FIG. 28A shows an EMG endotracheal tube 2800A with electrodes having an increased surface area according to one embodiment. Tube 2800A includes electrode 2802A, which has a sinusoidal wave shape that extends around the circumference of the tube 2800A with peaks and valleys that extend in a longitudinal direction of the tube 2800A.

[0078] FIG. 28B shows an EMG endotracheal tube 2800B with electrodes having an increased surface area according to another embodiment. Tube 2800B includes electrodes 2802B, which are formed around a circumference of the tube 2800B and extend in a longitudinal direction of the tube 2800B. Electrodes 2802B include a first set of electrodes 2802B-1 that are interleaved with and longitudinally displaced from a second set of electrodes 2802B-2. The electrodes 2802B-1 are positioned closer to a proximal end of the tube 2800B than electrodes 2802B-2, and the electrodes 2802B-2 are positioned closer to a distal end of the tube 2800B than electrodes 2802B-1.

[0079] FIG. 28C shows an EMG endotracheal tube 2800C with electrodes having an increased surface area according to another embodiment. Tube 2800C includes electrodes 2802C-1 and 2802C-2, which each have a sinusoidal wave shape that extends along a portion of the length of the tube 2800C, with peaks and valleys that extend in a lateral direction of the tube 2800C.

[0080] FIG. 28D shows an EMG endotracheal tube 2800D with electrodes having an increased surface area according to another embodiment. Tube 2800D includes electrode array 2802D, which includes a plurality of horizontal electrodes 2802D-1 and 2802D-2 and a plurality of vertical electrodes 2802D-3 and 2802D-4 that form a grid pattern. Horizontal electrodes 2802D-1 and 2802D-2 extend laterally around a circumference of the tube 2800D, and vertical electrodes 2802D-3 and 2802D-4 extend longitudinally along a portion of the length of the tube 2800D.

[0081] The electrode configurations shown in FIGS. 28A-28D help to reduce or eliminate rotational sensitivity of the tube. In one embodiment, the shape of the electrodes conforms to the vocal folds to avoid shunting problems.

[0082] FIG. 29 shows an EMG endotracheal tube 2900 with an overall shape that is curved to match the shape of a human throat according to one embodiment. Endotracheal tube 2900 includes fitting 2904, tube 2910, electrodes 2912, and primary cuff 2914. Tube 2910 transports gases to and from the lungs. Fitting 2904 is configured to be connected to a respirating machine (not shown) for injecting air into the lungs and withdrawing air from the lungs. A cuff inflating conduit is configured to be connected to a source of compressed air for inflating cuff 2914. After endotracheal tube 2900 is inserted into the trachea of the patient, electrodes 2912 sense EMG signals, which are output to an EMG processing machine (e.g., NIM device 120) via solid wires connected to electrodes 2912.

[0083] As shown in FIG. 29, tube 2910 is not a straight tube, but rather is bent or curved in at least one location along the length of the tube 2910, such that the tube 2910 has a natural shape that matches or substantially matches the shape of a human throat. The curved shape of the tube 2910 provides tactual feel for proper placement in a patient.

[0084] FIG. 30 shows a cross-sectional view of an EMG endotracheal tube 3000 with electrodes configured to reduce or eliminate rotational sensitivity according to one embodiment. Four electrodes 3002A-3002D are positioned on tube 3004 and extend longitudinally along a portion of the length of the tube 3004 (i.e., into and out of the paper in FIG. 30). In the illustrated embodiment, the four electrodes 3002A-3002D are spaced equally apart along the circumference of the tube 3004. Electrode 3002A corresponds to channel 1+ and channel 3+. Electrode 3002B corresponds to channel 2+ and channel 4-. Electrode 3002C corresponds to channel 1- and channel 4+. Electrode 3002D corresponds to channel 2- and channel 3-.

[0085] As shown in FIG. 30, a four-electrode tube can be used to create four channels by using the diagonal pairs of electrodes for channels 3 and 4. This electrode configuration helps ensure that the tube will always have two good monitoring channels regardless of rotation, and thereby helps reduce or eliminate rotational sensitivity of the tube. A four-electrode tube can also be used to create six channels (e.g., by using the top two electrodes for channel 5 and the bottom two electrodes for channel 6). In one embodiment, the NIM 120 (FIG. 1) is configured to display all four or six channels. In

another embodiment, the NIM 120 is configured to determine which of the four or six channels are providing the best signal, and display only the best channel or channels. In one embodiment, tube 3004 includes an identification component (e.g., resistor, RF, magnet, digital) that causes the NIM 120 to switch into a multi-channel mode. The tube may also include one or more LEDs to verify the depth of insertion of the tube. Rotational sensitivity may also be reduced or eliminated by multiplexing a large number of electrode pairs.

[0086] FIG. 31 shows an EMG endotracheal tube 3100 with electrodes configured to reduce or eliminate rotational sensitivity according to another embodiment. EMG endotracheal tube 3100 includes tube 3110, primary cuff 3114, and electrode carriers 3120A and 3120B. Each of the electrode carriers 3120A and 3120B is donut-shaped, and surrounds the circumference of the tube 3110. The electrode carriers 3120A and 3120B are spaced apart from each other along the length of the tube 3110. Electrode 3112A is formed on electrode carrier 3120A, and electrode 3112B is formed on electrode carrier 3120B. Each of the electrodes 3112A and 3112B has a sinusoidal wave shape that extends around the circumference of the respective carrier 3120A and 3120B, with peaks and valleys that extend in a longitudinal direction of the tube 3110. In one embodiment, electrode 3112A is a negative electrode and electrode 3112B is a positive electrode. The electrode configuration shown in FIG. 31 helps to reduce or eliminate rotational sensitivity of EMG endotracheal tube 3100.

[0087] In another embodiment, EMG endotracheal tube 3100 includes only a single donut-shaped electrode carrier 3120A, and the carrier 3120A is slidably coupled to the tube 3110 to allow the carrier 3120A to longitudinally slide up and down along the length of the tube 3110. In one form of this embodiment, a control member may be attached to the carrier 3120A to selectively cause the carrier 3120A to expand and allow sliding, or to contract and prevent sliding. For example, the control member may cause the carrier 3120A to expand when the carrier 3120A is positioned at the vocal folds such that the carrier 3120A stays at that location while the tube 3110 is allowed to slide through the carrier 3120A. In one embodiment, one or both of the carriers 3120A and 3120B may have a circular cross-sectional shape, or a non-circular cross-sectional shape (e.g., triangular shape).

[0088] FIG. 32 shows a cuff 3200 for an EMG endotracheal tube according to one embodiment. Cuff 3200 includes an expandable cuff portion 3202 and tension members 3204. Cuff 3200 also includes a cylindrically-shaped opening 3206 that extends through the cuff 3200, and allows the cuff 3200 to be slid onto an endotracheal tube. Tension members 3204 allow expansion of the cuff portion 3202, but resist torsion and help to minimize rotation of cuff 3200 and the endotracheal tube. In one embodiment, tension members 3204 are self-expanding and are formed from a shape memory material, such as nitinol. In one embodiment, tension members 3204 are a nitinol framework or basket, and the cuff 3200 includes electrodes formed thereon. In one form of this embodiment, the cuff 3200 is configured to atraumatically conform to the shape of the vocal folds.

[0089] FIG. 33 shows an electrical schematic diagram of an electrode array configured to be used in an EMG endotracheal tube according to one embodiment. The electrode array includes five electrodes 3302 in a star configuration, with the electrodes 3302 sharing a common node 3304. Positive terminal 3306 is connected to the common node 3304. The array

also includes terminal 3308. In one embodiment, terminal 3306 and electrodes 3302 are located on the tube, and terminal 3308 is located on a primary or secondary cuff of the tube. The electrode configuration shown in FIG. 33 helps to reduce or eliminate rotational sensitivity of the EMG endotracheal tube. Rotational sensitivity may also be reduced or eliminated by using two ring electrodes that surround the circumference of the tube at two locations (e.g., one ring electrode at the vocal folds and a second ring electrode on a primary or secondary cuff of the tube).

[0090] FIG. 34 shows flexible, expanding electrodes configured to be used in an EMG endotracheal tube according to one embodiment. As shown in FIG. 34, a pair of spaced-apart retaining rings 3422 and 3424 each surround the circumference of tube 3410. The rings 3422 and 3424 hold flexible electrodes 3412 in place between the rings. The electrodes 3412 extend longitudinally along a portion of the length of tube 3410. The closer that rings 3422 and 3424 are positioned toward each other along tube 3410, the farther that the electrodes 3412 extend away from tube 3410. The farther that rings 3422 are positioned away from each other along tube 3410, the closer that the electrodes 3412 are to the tube 3410. The electrodes 3412 may be used to mechanically stimulate the vocal chords. The vocal folds will push the flexible electrodes 3412 inward toward tube 3410.

[0091] In the event of movement of an EMG endotracheal tube during surgery, the EMG electrodes on the tube may lose contact with the target muscle and may fail to provide the optimal EMG response. One embodiment provides an EMG endotracheal tube that is insensitive or substantially insensitive to tube movement (rotational and vertical), and provides uninterrupted EMG recording even if the tube moves rotationally or vertically inside the patient during surgery. One form of this embodiment is a tube with three electrodes, with two electrodes configured to be positioned above the vocal folds and one electrode configured to be positioned below the vocal folds. Another form of this embodiment is a tube with four electrodes, with two electrodes configured to be positioned above the vocal folds and two electrodes configured to be positioned below the vocal folds, with the electrodes arranged equally angularly. The electrode configuration for these embodiments differs above and below the level of the vocal folds, which maximizes the signal difference between the activated muscle group and the inactive region. The electrodes above and below the level of the vocal folds improve monitoring of electromyographic (EMG) signals from the muscles of the larynx innervated by the recurrent laryngeal nerves (or the non-recurrent laryngeal nerves) and external branch of the superior laryngeal nerves. The electrodes above and below the level of the vocal folds provide posterior, lateral, and anterior monitoring of the larynx, for example; monitoring left and the right Vocalis muscle, Arytenoids, Thyroarytenoids, Posterior Cricoarytenoids, Lateral Cricoarytenoid, and Cricothyroid muscles. Embodiments that are substantially insensitive to tube position are described in further detail below with reference to FIGS. 35-37.

[0092] FIG. 35A shows a first side view (posterior side) of an EMG endotracheal tube 3500 with three electrodes according to one embodiment. FIG. 35B shows a second side view (rotated 90 degrees from the view shown in FIG. 35A) of the EMG endotracheal tube 3500 shown in FIG. 35A according to one embodiment. FIG. 35C is a diagram illustrating a cross-sectional view of the endotracheal tube 3500 shown in FIGS. 35A and 35B according to one embodiment. As shown

in FIGS. 35A-35C, endotracheal tube 3500 includes tube 3510, electrodes 3512, and primary cuff 3514. Tube 3510 transports gases to and from the lungs. A proximal end (left end in FIG. 35A) of tube 3510 is configured to be connected to a respirating machine (not shown) for injecting air into the lungs and withdrawing air from the lungs. A cuff inflating conduit (not shown) is configured to be connected to a source of compressed air (not shown) for inflating cuff 3514. After endotracheal tube 3500 is inserted into the trachea of a patient, electrodes 3512 sense EMG signals, which are output to an EMG processing machine (e.g., NIM device 120).

[0093] Electrodes 3512 include three electrodes 3512A-3512C, which are formed around a circumference of the tube 3510 and extend in a longitudinal direction of the tube 3510 and extend in a longitudinal direction of the tube 3510. Electrode 3512B is positioned entirely on the posterior side of the tube 3510 and is also referred to herein as posterior electrode 3512B. Electrodes 3512A and 3512C are positioned primarily on the anterior side of the tube 3510 and are also referred to as anterior electrodes 3512A and 3512C. The anterior side of the tube 3510 is the bottom half of the tube 3510 shown in FIG. 35C, and the posterior side of the tube 3510 is the top half of the tube 3510 shown in FIG. 35C. Each of the electrodes 3512A-3512C is coupled to a respective trace 3524A-3524C (trace 3524A is not visible in the Figures). Traces 3524A-3524C are positioned in a protected (masked) region 3528 of tube 3510. Posterior electrode 3512B is positioned in an exposed (unmasked) region 3526A of tube 3510. Anterior electrodes 3512A and 3512C are positioned in an exposed (unmasked) region 3526B of tube 3510.

[0094] In one embodiment, each of the electrodes 3512A-3512C has a length of about one inch, and extends laterally around a circumference of the tube for a distance corresponding to an angle 3522 of about 90 degrees (i.e., each of the electrodes 3512A-3512C has a width of about 25 percent of the total circumference of the tube). The electrodes 3512A-3512C are laterally spaced apart around the circumference of the tube by a distance corresponding to an angle 3520 of about 30 degrees (i.e., the lateral spacing between each of the electrodes 3512A-3512C is about 8.333 percent of the total circumference of the tube). In another embodiment, each of the electrodes 3512A-3512C extends laterally around a circumference of the tube for a distance corresponding to an angle 3522 of about 60 degrees, and the electrodes 3512A-3512C are laterally spaced apart around the circumference of the tube by a distance corresponding to an angle 3520 of about 60 degrees. In yet another embodiment, the electrodes 3512A-3512C are laterally spaced apart around the circumference of the tube by a distance corresponding to an angle 3520 of greater than about 15 degrees. In one embodiment, the distance around the circumference of the tube from the center of one of the electrodes 3512A-3512C to the center of an adjacent electrode is about 110 degrees to 220 degrees. The posterior electrode 3512B is laterally positioned between the two anterior electrodes 3512A and 3512C, and is longitudinally offset or displaced from the anterior electrodes 3512A and 3512B. The posterior electrode 3512B is positioned closer to the distal end (right side in FIGS. 35A and 35B) of the tube 3510 than the anterior electrodes 3512A and 3512C, and the anterior electrodes 3512A and 3512C are positioned closer to the proximal end (left side in FIGS. 35A and 35B) of the tube 3510 than the posterior electrode 3512B.

[0095] Tube 3510 includes an overlap region 3530 where a proximal portion of the posterior electrode 3512B longitudinally overlaps with a distal portion of the anterior electrodes

3512A and 3512C. The electrodes 3512 do not physically overlap each other since they are laterally offset from each other. In one embodiment, the overlap region 3530 is about 0.1 inches long, and the overall length from a proximal end of the anterior electrodes 3512A and 3512C to a distal end of the posterior electrode 3512B is about 1.9 inches. In another embodiment, the overlap region 3530 is about 0.2 inches long, and the overall length from a proximal end of the anterior electrodes 3512A and 3512C to a distal end of the posterior electrode 3512B is about 1.8 inches. Tube 3510 is configured to be positioned such that the vocal folds of a patient are positioned in the overlap region 3530. Thus, the configuration of the electrodes 3512 above the vocal folds is different than the configuration below the vocal folds. The single posterior electrode 3512B is configured to be positioned primarily below the vocal folds, and the two anterior electrodes 3512A and 3512C are configured to be positioned primarily above the vocal folds. It has been determined that the largest response is provided on the anterior side at about 0.5 inches above the vocal folds. In one embodiment, electrodes 3512A and 3512B are used for a first EMG channel, and electrodes 3512C and 3512B are used for a second EMG channel.

[0096] FIG. 36A shows a first side view (posterior side) of an EMG endotracheal tube 3600 with four electrodes according to one embodiment. FIG. 36B shows a second side view (rotated 90 degrees from the view shown in FIG. 36A) of the EMG endotracheal tube 3600 shown in FIG. 36A according to one embodiment. FIG. 36C is a diagram illustrating a cross-sectional view of the endotracheal tube 3600 shown in FIGS. 36A and 36B according to one embodiment. As shown in FIGS. 36A-36C, endotracheal tube 3600 includes tube 3610, electrodes 3612, and primary cuff 3614. Tube 3610 transports gases to and from the lungs. A proximal end (left end in FIG. 36A) of tube 3610 is configured to be connected to a respirating machine (not shown) for injecting air into the lungs and withdrawing air from the lungs. A cuff inflating conduit (not shown) is configured to be connected to a source of compressed air (not shown) for inflating cuff 3614. After endotracheal tube 3600 is inserted into the trachea of a patient, electrodes 3612 sense EMG signals, which are output to an EMG processing machine (e.g., NIM device 120).

[0097] Electrodes 3612 include four electrodes 3612A-3612D, which are formed around a circumference of the tube 3610 and extend in a longitudinal direction of the tube 3610. Electrodes 3612A and 3612B are positioned entirely on the posterior side of the tube 3610 and are also referred to herein as posterior electrodes 3612A and 3612B. Electrodes 3612C and 3612D are positioned entirely on the anterior side of the tube 3610 and are also referred to as anterior electrodes 3612C and 3612D. The anterior side of the tube 3610 is the bottom half of the tube 3610 shown in FIG. 36C, and the posterior side of the tube 3610 is the top half of the tube 3610 shown in FIG. 36C. Each of the electrodes 3612A-3612D is coupled to a respective trace 3624A-3624D (trace 3624D is not visible in the Figures). Traces 3624A-3624D are positioned in a protected (masked) region 3628 of tube 3610. Posterior electrodes 3612A and 3612B are positioned in an exposed (unmasked) region 3626A of tube 3610. Anterior electrodes 3612C and 3612D are positioned in an exposed (unmasked) region 3626B of tube 3610.

[0098] In one embodiment, each of the electrodes 3612A-3612D has a length of about one inch, and extends laterally around a circumference of the tube for a distance correspond-



ing to an angle 3622 of about 60 degrees (i.e., each of the electrodes 3612A-3612D has a width of about 16.666 percent of the total circumference of the tube). The electrodes are laterally spaced apart around the circumference of the tube by a distance corresponding to an angle 3620 of about 30 degrees (i.e., the lateral spacing between each of the electrodes 3612A-3612D is about 8.333 percent of the total circumference of the tube). The posterior electrodes 3612A and 3612B are longitudinally offset or displaced from the anterior electrodes 3612C and 3612D. The posterior electrodes 3612A and 3612B are positioned closer to the distal end (right side in FIGS. 36A and 36B) of the tube 3610 than the anterior electrodes 3612C and 3612D, and the anterior electrodes 3612C and 3612D are positioned closer to the proximal end (left side in FIGS. 36A and 36B) of the tube 3610 than the posterior electrodes 3612A and 3612B.

[0099] Tube 3610 includes an overlap region 3630 where a proximal portion of the posterior electrodes 3612A and 3612B longitudinally overlap with a distal portion of the anterior electrodes 3612C and 3612D. The electrodes 3612 do not physically overlap each other since they are laterally offset from each other. In one embodiment, the overlap region 3630 is about 0.1 inches long, and the overall length from a proximal end of the anterior electrodes 3612C and 3612D to a distal end of the posterior electrodes 3612A and 3612B is about 1.9 inches. In another embodiment, the overlap region 3630 is about 0.2 inches long, and the overall length from a proximal end of the anterior electrodes 3612C and 3612D to a distal end of the posterior electrodes 3612A and 3612B is about 1.8 inches. Tube 3610 is configured to be positioned such that the vocal folds of a patient are positioned in the overlap region 3630. Thus, the configuration of the electrodes 3612 above the vocal folds is different than the configuration below the vocal folds. The posterior electrodes 3612A and 3612B are configured to be positioned primarily below the vocal folds, and the anterior electrodes 3612C and 3612D are configured to be positioned primarily above the vocal folds. In one embodiment, electrodes 3612A and 3612C are used for a first EMG channel, and electrodes 3612B and 3612D are used for a second EMG channel. In another embodiment, electrodes 3612A and 3612D are used for a first EMG channel, and electrodes 3612B and 3612C are used for a second EMG channel.

[0100] FIG. 37A shows a first side view (posterior side) of an EMG endotracheal tube 3700 with four electrodes according to another embodiment. FIG. 37B shows a second side view (rotated 90 degrees from the view shown in FIG. 37A) of the EMG endotracheal tube 3700 shown in FIG. 37A according to one embodiment. As shown in FIGS. 37A and 37B, endotracheal tube 3700 includes tube 3710, electrodes 3712, and primary cuff 3714. Tube 3710 transports gases to and from the lungs. A proximal end (left end in FIG. 37A) of tube 3710 is configured to be connected to a respiring machine (not shown) for injecting air into the lungs and withdrawing air from the lungs. A cuff inflating conduit (not shown) is configured to be connected to a source of compressed air (not shown) for inflating cuff 3714. After endotracheal tube 3700 is inserted into the trachea of a patient, electrodes 3712 sense EMG signals, which are output to an EMG processing machine (e.g., NIM device 120).

[0101] Electrodes 3712 include four electrodes 3712A-3712D, which are formed around a circumference of the tube 3710 and extend in a longitudinal direction of the tube 3710. Each of the electrodes 3712A-3712D is coupled to a respec-

tive trace 3724A-3724D (traces 3724A and 3724D are not visible in the Figures). Traces 3724A-3724D are positioned in a protected (masked) region 3728 of tube 3710. Electrodes 3712C and 3712D are positioned in an exposed (unmasked) region 3726A of tube 3710. Electrodes 3712A and 3712B are positioned in an exposed (unmasked) region 3726B of tube 3710.

[0102] In one embodiment, each of the electrodes 3712A-3712D has a length of about one inch. In one embodiment, each of the electrodes 3712A and 3712B extends laterally around a circumference of the tube for a distance corresponding to an angle of about 140 degrees (i.e., each of the electrodes 3712A and 3712B has a width of about 38.888 percent of the total circumference of the tube). In one embodiment, each of the electrodes 3712C and 3712D extends laterally around a circumference of the tube for a distance corresponding to an angle of about 110 degrees (i.e., each of the electrodes 3712C and 3712D has a width of about 30.555 percent of the total circumference of the tube). Electrodes 3712A and 3712B are laterally spaced apart from each other around the circumference of the tube by a distance corresponding to an angle of about 40 degrees (i.e., the lateral spacing between the electrodes 3712A and 3712B is about 11.111 percent of the total circumference of the tube). Electrodes 3712C and 3712D are laterally spaced apart from each other around the circumference of the tube by a distance corresponding to an angle of about 70 degrees (i.e., the lateral spacing between the electrodes 3712C and 3712D is about 19.444 percent of the total circumference of the tube). The electrodes 3712A and 3712B are longitudinally offset or displaced from the electrodes 3712C and 3712D. The electrodes 3712C and 3712D are positioned closer to the distal end (right side in FIGS. 37A and 37B) of the tube 3710 than the electrodes 3712A and 3712B, and the electrodes 3712A and 3712B are positioned closer to the proximal end (left side in FIGS. 37A and 37B) of the tube 3710 than the electrodes 3712C and 3712D.

[0103] Tube 3710 includes a separation region 3730 where a proximal end of the electrodes 3712C and 3712D is longitudinally separated from a distal end of the electrodes 3712A and 3712B. In one embodiment, the separation region 3730 is about 0.1 inches long, and the overall length from a proximal end of the electrodes 3712A and 3712B to a distal end of the electrodes 3712C and 3712D is about 2.1 inches. In another embodiment, the separation region 3730 is about 0.2 inches long, and the overall length from a proximal end of the electrodes 3712A and 3712B to a distal end of the electrodes 3712C and 3712D is about 2.2 inches. Tube 3710 is configured to be positioned such that the vocal folds of a patient are positioned in the separation region 3730. Thus, the configuration of the electrodes 3712 above the vocal folds is different than the configuration below the vocal folds. The electrodes 3712C and 3712D are configured to be positioned primarily below the vocal folds, and the electrodes 3712A and 3712B are configured to be positioned primarily above the vocal folds.

[0104] FIG. 38 shows a side view of an EMG endotracheal tube 3800 with a plurality of ring electrodes according to one embodiment. As shown in FIG. 38, endotracheal tube 3800 includes tube 3810, electrodes 3812, and primary cuff 3814. Tube 3810 transports gases to and from the lungs. A proximal end (left end in FIG. 38) of tube 3810 is configured to be connected to a respiring machine (not shown) for injecting air into the lungs and withdrawing air from the lungs. A cuff inflating conduit (not shown) is configured to be connected to



a source of compressed air (not shown) for inflating cuff **3814**. After endotracheal tube **3800** is inserted into the trachea of a patient, electrodes **3812** sense EMG signals, which are output to an EMG processing machine (e.g., NIM device **120**).

[**0105**] Electrodes **3812** include a plurality of ring electrodes **3812A**. In one embodiment, each of the ring electrodes **3812A** completely surrounds a circumference of the tube **3810**. In one embodiment, electrodes **3812** include sixteen ring electrodes **3812A** that are longitudinally separated from each other along the length of the tube by a distance of about 0.05 inches, and have an overall length in the longitudinal direction of the tube of about 1.55 inches.

[**0106**] FIGS. **39A-39E** show EMG endotracheal tubes with tube placement markings according to various embodiments. In one embodiment, the tube markings shown in FIGS. **39A-39E** are formed from a radio opaque material.

[**0107**] As shown in FIG. **39A**, EMG endotracheal tube **3900A** includes three bands **3902**, **3904**, and **3906**, and a vertical line segment **3908**. The bands **3902**, **3904**, and **3906**, and the vertical line segment **3908**, are positioned on an electrode region of the tube **3900A**, and facilitate proper longitudinal and rotational positioning of the electrodes of tube **3900A** with respect to a patient's anatomy. Bands **3902**, **3904**, and **3906** are positioned adjacent to each other, with band **3904** positioned between band **3902** and **3906**. In one embodiment, each of the bands **3902**, **3904**, and **3906** surrounds a circumference of the tube **3900A** or a portion of the circumference of the tube **3900A**, and the bands **3902**, **3904**, and **3906** have an overall length along a longitudinal axis of the tube **3900A** that is the same or substantially the same as the length of the electrodes of tube **3900A**. In one embodiment, bands **3902** and **3906** have substantially the same length, which is about twice as long as the length of band **3904**. Bands **3902**, **3904**, and **3906** are solid color bands in one embodiment, and at least two different colors are used for the three bands. In one embodiment, bands **3902**, **3904**, and **3906** are each a solid color band with a different color than the other bands (i.e., 3 different solid colors are used for the three bands). In one form of this embodiment, band **3902** is a green band, band **3904** is a white band, and band **3906** is a blue band. The colors are selected in one embodiment to differentiate the bands from blood and surrounding tissue. Vertical line segment **3908** extends in a longitudinal direction along tube **3900A**, and has a length that is the same or substantially the same as the overall length of the bands **3902**, **3904**, and **3906**.

[**0108**] As shown in FIG. **39B**, EMG endotracheal tube **3900B** includes band **3910**, vertical line segment **3914**, and horizontal line segments **3916**, **3918**, and **3920**. The band **3910** and the line segments **3914**, **3916**, **3918**, and **3920** are positioned on an electrode region of the tube **3900B**, and facilitate proper longitudinal and rotational positioning of the electrodes of tube **3900B** with respect to a patient's anatomy. In one embodiment, band **3910** surrounds a circumference of the tube **3900B**, and has a length along a longitudinal axis of the tube **3900B** that is the same or substantially the same as the length of the electrodes of tube **3900B**. Band **3910** is a solid color band in one embodiment. In one embodiment, band **3910** is a white band. In another embodiment, band **3910** is a blue band. The color is selected in one embodiment to differentiate the band from blood and surrounding tissue.

[**0109**] Vertical line segment **3914** extends in a longitudinal direction along tube **3900B**, and has a length that is the same

or substantially the same as the length of the band **3910**. Each of the horizontal line segments **3916**, **3918**, and **3920** intersects the vertical line segment **3914** and extends in a lateral direction around a portion of the circumference of the tube **3900B**. The horizontal line segments **3916**, **3918**, and **3920** are each centered on the vertical line segment **3914**, and are spaced apart from each other along a longitudinal axis of the tube **3900B**. Horizontal line segment **3918** is positioned between segments **3916** and **3920**. Horizontal line segments **3916** and **3920** have the same length in one embodiment, which is less than the length of segment **3918**. In one embodiment, segment **3918** has a length that is at least about twice as long as the length of each of the segments **3916** and **3920**.

[**0110**] As shown in FIG. **39C**, EMG endotracheal tube **3900C** includes band **3922**, vertical line segment **3926**, horizontal line segment **3928**, and diagonal line segments **3930** and **3932**. The band **3922** and the line segments **3926**, **3928**, **3930**, and **3932** are positioned on an electrode region of the tube **3900C**, and facilitate proper longitudinal and rotational positioning of the electrodes of tube **3900C** with respect to a patient's anatomy. In one embodiment, band **3922** surrounds a circumference of the tube **3900C**, and has a length along a longitudinal axis of the tube **3900C** that is the same or substantially the same as the length of the electrodes of tube **3900C**. Band **3922** is a solid color band in one embodiment. In one embodiment, band **3922** is a white band. In another embodiment, band **3922** is a blue band. The color is selected in one embodiment to differentiate the band from blood and surrounding tissue.

[**0111**] The line segments **3926**, **3928**, **3930**, and **3932** all intersect at a common point **3924**. Vertical line segment **3926** extends in a longitudinal direction along tube **3900C**, and has a length that is the same or substantially the same as the length of the band **3922**. The horizontal line segment **3928** is centered on the vertical line segment **3926** and extends in a lateral direction around a portion of the circumference of the tube **3900C**. Diagonal line segments **3930** and **3932** extend longitudinally and laterally along tube **3900C** and intersect each other at common point **3924** to form an x-type marking.

[**0112**] As shown in FIG. **39D**, EMG endotracheal tube **3900D** includes band **3934**, triangular markings **3936** and **3940**, and vertical line segment **3942**, which are positioned on an electrode region of the tube **3900D**, and facilitate proper longitudinal and rotational positioning of the electrodes of tube **3900D** with respect to a patient's anatomy. In one embodiment, band **3934** surrounds a circumference of the tube **3900D**, and has a length along a longitudinal axis of the tube **3900D** that is the same or substantially the same as the length of the electrodes of tube **3900D**. Band **3934** is a solid color band in one embodiment. In one embodiment, band **3934** is a white band.

[**0113**] Each of the triangular markings **3936** and **3940** according to one embodiment has substantially the shape of an isosceles triangle. Each of the triangular markings **3936** and **3940** has a base segment that extends laterally around a portion of the circumference of the tube **3900D**, and two equal sides that extend away from the base portion and meet at an apex of the triangle. The apexes of the triangular markings **3936** and **3940** share a common point **3938**. Each of the triangular markings **3936** and **3940** is a solid color marking in one embodiment. In one embodiment, the color of marking **3936** is different than the color of marking **3940**. In one form of this embodiment, marking **3936** is a green marking, and

marking **3940** is a blue marking. The colors are selected in one embodiment to differentiate the markings from blood and surrounding tissue.

[0114] Vertical line segment **3942** extends in a longitudinal direction along tube **3900D** from the middle of the base segment of the triangular marking **3936** to the middle of the base segment of the triangular marking **3936**, and intersects the common point **3938**. Vertical line segment **3942** has a length that is the same or substantially the same as the length of the band **3934**.

[0115] As shown in FIG. **39E**, EMG endotracheal tube **3900E** includes band **3950**, vertical line or strip **3952**, and horizontal line or strip **3954**, which are positioned on an electrode region of the tube **3900E**, and facilitate proper longitudinal and rotational positioning of the electrodes of tube **3900E** with respect to a patient's anatomy. In one embodiment, band **3950** surrounds a circumference of the tube **3900E**. Band **3950** is a solid color band in one embodiment.

[0116] Vertical strip **3952** extends in a longitudinal direction along tube **3900E**, and has a length that is the same or substantially the same as the length of the electrodes of tube **3900E**. Vertical strip **3952** includes two end portions **3952A** and **3952C** separated by a middle portion **3952B**. In one embodiment, the end portions **3952A** and **3952C** have a substantially equal length, which is about four times longer than the length of the middle portion **3952B**. Band **3950** extends from a bottom end of vertical strip end portion **3952A** to a top end of vertical strip middle portion **3952B**.

[0117] Horizontal strip **3954** intersects the vertical strip **3952** at the middle portion **3952B**, and extends in a lateral direction around at least a portion of the circumference of the tube **3900E**. In one embodiment, band **3950** is a solid color band (e.g., gray), and horizontal strip **3954** is a solid color strip (e.g., white). In one embodiment, vertical strip portions **3952A** and **3952C** are formed from the same solid color (e.g., blue), which is different than the solid color of vertical strip portion **3952B** (e.g., white). The colors are selected in one embodiment to differentiate the bands from blood and surrounding tissue.

[0118] One embodiment is directed to an apparatus for monitoring EMG signals of a patient's laryngeal muscles. The apparatus includes an endotracheal tube having an exterior surface and conductive ink electrodes formed on the exterior surface. The conductive ink electrodes are configured to receive the EMG signals from the laryngeal muscles when the endotracheal tube is placed in a trachea of the patient. At least one conductor is coupled to the conductive ink electrodes and is configured to carry the EMG signals received by the conductive ink electrodes to a processing apparatus.

[0119] The conductive ink electrodes according to one embodiment comprise a silver filled polymer conductive ink or a carbon conductive ink. In one embodiment, the conductive ink electrodes include at least six conductive ink electrodes that extend longitudinally along a length of the tube and that are spaced apart to surround a circumference of the endotracheal tube. The apparatus according to one embodiment includes an inflatable cuff connected to the endotracheal tube, and at least one conductive ink electrode formed on the inflatable cuff and configured to sense EMG signals from vocal folds of the patient. In one embodiment, at least one of a light source and a magnet is positioned on the endotracheal tube near the conductive ink electrodes.

[0120] One embodiment of the apparatus includes a coupling adapter configured to allow a proximal end of the endotracheal tube to rotate with respect to a distal end of the endotracheal tube.

In one embodiment, the apparatus includes a first rib surrounding the endotracheal tube and positioned above the conductive ink electrodes on the endotracheal tube, and a second rib surround the endotracheal tube and positioned below the conductive ink electrodes on the endotracheal tube. At least one automatic periodic stimulation (APS) electrode is formed on the endotracheal tube in one embodiment, and the processing apparatus is configured to determine a position of the endotracheal tube based on signals generated by the at least one APS electrode. In one embodiment, at least one of a conducting hydro gel and an expandable, conductive foam is formed on the electrodes.

[0121] The endotracheal tube comprises a braided endotracheal tube in one embodiment. In one embodiment, the electrodes include four electrodes and the at least one conductor includes at least four pairs of conductors, and each pair of conductors is coupled to a different pair of the four electrodes to provide at least four channels of EMG signals from the four electrodes. In one form of this embodiment, the processing apparatus is configured to analyze the four channels of EMG signals and identify a subset of the four channels to display based on the analysis. At least one wireless sensor is provided on the endotracheal tube in one embodiment, with the at least one wireless sensor configured to wirelessly transmit information to the processing apparatus. In one embodiment, each of the electrodes is at least about 1.9 inches in length. The electrodes form an electrode grid with at least two horizontal electrodes and at least two vertical electrodes. In one embodiment the apparatus includes at least one of a temperature sensing element, fiber optic element, and video element. In one embodiment, the apparatus includes at least one of a strain measurement element, an acceleration measurement element, and a piezoelectric element.

[0122] Another embodiment is directed to a method of monitoring EMG signals of a patient's laryngeal muscles. The method includes providing an endotracheal tube having an exterior surface and conductive ink electrodes formed on the exterior surface. The EMG signals from the laryngeal muscles are sensed with the conductive ink electrodes when the endotracheal tube is placed in a trachea of the patient. The EMG signals sensed by the conductive ink electrodes are output to a processing apparatus.

[0123] Another embodiment is directed to an apparatus for monitoring EMG signals of a patient's laryngeal muscles. The apparatus includes an endotracheal tube having an exterior surface. Four electrodes are formed on the exterior surface of the endotracheal tube. The four electrodes are configured to receive the EMG signals from the laryngeal muscles when the endotracheal tube is placed in a trachea of the patient. At least four pairs of conductors are coupled to the four electrodes and configured to carry the EMG signals received by the electrodes to a processing apparatus. Each pair of the conductors is coupled to a different pair of the four electrodes to provide at least four channels of EMG signals from the four electrodes.

[0124] Although embodiments set forth herein have been described in the context of an EMG endotracheal tube, it will be understood that the techniques are also applicable to other types of devices, such as a tube for monitoring a patient's anal sphincter or urethral sphincter.

[0125] Although the present disclosure has been described with reference to preferred embodiments, workers skilled in

the art will recognize that changes can be made in form and detail without departing from the spirit and scope of the present disclosure.

What is claimed is:

1. An apparatus for monitoring EMG signals of a patient's laryngeal muscles, comprising:

an endotracheal tube having an exterior surface;  
conductive electrodes formed on the endotracheal tube, the conductive electrodes configured to receive the EMG signals from the laryngeal muscles when the endotracheal tube is placed in a trachea of the patient; and  
at least one wireless sensor formed on the endotracheal tube, the at least one wireless sensor configured to wirelessly transmit information to a processing apparatus.

2. The apparatus of claim 1, wherein the conductive electrodes comprise a silver filled polymer conductive ink.

3. The apparatus of claim 1, wherein the conductive electrodes comprise a carbon conductive ink.

4. The apparatus of claim 1, wherein the conductive electrodes include at least six conductive electrodes that extend longitudinally along a length of the tube and that are spaced apart to surround a circumference of the endotracheal tube.

5. The apparatus of claim 1, and further comprising:  
an inflatable cuff connected to the endotracheal tube; and  
at least one conductive electrode formed on the inflatable cuff.

6. The apparatus of claim 5, wherein the at least one conductive electrode formed on the inflatable cuff is configured to sense EMG signals from vocal folds of the patient.

7. The apparatus of claim 1, and further comprising:  
at least one of a light source and a magnet positioned on the endotracheal tube near the conductive electrodes.

8. The apparatus of claim 1, and further comprising:  
a coupling adapter configured to allow a proximal end of the endotracheal tube to rotate with respect to a distal end of the endotracheal tube.

9. The apparatus of claim 1, and further comprising:  
a first rib surrounding the endotracheal tube and positioned above the conductive electrodes on the endotracheal tube; and  
a second rib surround the endotracheal tube and positioned below the conductive electrodes on the endotracheal tube.

10. The apparatus of claim 1, and further comprising:  
at least one automatic periodic stimulation (APS) electrode formed on the endotracheal tube, wherein the processing apparatus is configured to determine a position of the endotracheal tube based on signals generated by the at least one APS electrode.

11. The apparatus of claim 1, and further comprising:  
at least one of a conducting hydro gel and an expandable, conductive foam formed on the electrodes.

12. The apparatus of claim 1, wherein the endotracheal tube comprises a braided endotracheal tube.

13. The apparatus of claim 1, wherein the electrodes include four electrodes and the at least one conductor includes at least four pairs of conductors, and wherein each pair of conductors is coupled to a different pair of the four electrodes to provide at least four channels of EMG signals from the four electrodes.

14. The apparatus of claim 13, wherein the processing apparatus is configured to analyze the four channels of EMG signals and identify a subset of the four channels to display based on the analysis.

15. The apparatus of claim 1, wherein the at least one wireless sensor is configured to wirelessly transmit the EMG signals received by the conductive electrodes to the processing apparatus.

16. The apparatus of claim 1, wherein each of the electrodes is at least about 1.9 inches in length.

17. The apparatus of claim 1, wherein the electrodes form an electrode grid with at least two horizontal electrodes and at least two vertical electrodes.

18. The apparatus of claim 1, and further comprising at least one of a temperature sensing element, fiber optic element, and video element.

19. The apparatus of claim 1, and further comprising at least one of a strain measurement element, an acceleration measurement element, and a piezoelectric element.

20. A method of monitoring EMG signals of a patient's laryngeal muscles, comprising:

providing an endotracheal tube having an inflatable cuff with at least one conductive electrode formed on the inflatable cuff;

sensing the EMG signals from the laryngeal muscles with the at least one conductive electrode when the endotracheal tube is placed in a trachea of the patient; and  
outputting the EMG signals sensed by the conductive electrodes to a processing apparatus.

21. An apparatus for monitoring EMG signals of a patient's laryngeal muscles, comprising:

an endotracheal tube having an exterior surface;  
four electrodes formed on the exterior surface of the endotracheal tube, the four electrodes configured to receive the EMG signals from the laryngeal muscles when the endotracheal tube is placed in a trachea of the patient; and  
at least four pairs of conductors coupled to the four electrodes and configured to carry the EMG signals received by the electrodes to a processing apparatus, wherein each pair of the conductors is coupled to a different pair of the four electrodes to provide at least four channels of EMG signals from the four electrodes.

\* \* \* \* \*

专利名称(译)	气管内导管装置		
公开(公告)号	<a href="#">US20150250423A1</a>	公开(公告)日	2015-09-10
申请号	US14/716351	申请日	2015-05-19
[标]申请(专利权)人(译)	美敦力公司		
申请(专利权)人(译)	美敦力公司XOMED , INC.		
当前申请(专利权)人(译)	美敦力公司XOMED , INC.		
[标]发明人	HACKER DAVID C STANISLAUS MARIA CHARLES VIJAY LI WENJENG YAMASAKI DWAYNE S BRUNETT WILLIAM C MCFARLIN KEVIN L HISSONG JAMES BRITTON VACCARO ROBERT K MURPHY JOHN M PAGOTTO CARLA A SCHULER TINO		
发明人	HACKER, DAVID C. STANISLAUS, MARIA CHARLES VIJAY LI, WENJENG YAMASAKI, DWAYNE S. BRUNETT, WILLIAM C. MCFARLIN, KEVIN L. HISSONG, JAMES BRITTON VACCARO, ROBERT K. MURPHY, JOHN M. PAGOTTO, CARLA A. SCHULER, TINO		
IPC分类号	A61B5/00 A61B5/0492 A61B5/07 A61B5/0488 A61B5/11 A61B5/01 A61B1/07 A61B1/04 A61B1/267 A61M16/04 A61B5/04		
CPC分类号	A61B5/6853 A61M2205/0294 A61B5/0492 A61B5/07 A61B5/04886 A61B5/04012 A61B5/01 A61B1/07 A61B1/04 A61B1/267 A61B5/11 A61M2230/08 A61M2205/3546 A61B2562/0209 A61B2562/046 A61B2562/0219 A61B2562/0261 A61M16/0434 A61B1/00082 A61B1/00147 A61B1/005 A61B1/015 A61B1/018 A61B1/2673 A61B5/0488 A61B5/064 A61B2562/0215 A61B2562/0217 A61M16/04 A61M16 /0411 A61M16/0443 A61M16/0445 A61M16/0459 A61M16/0825 A61M2205/0233 A61M2205/3306 A61M2205/332 A61M2205/3344 A61M2205/3368 A61M2205/3569 A61M2205/3592 A61M2205/6054 A61M2210/065 A61N1/0517 A61N1/0519 A61B5/0496 A61B5/0533 A61B5/746 A61B5/0421 A61B5 /062 A61B5/065 A61M16/0463 A61M16/0488		
优先权	61/248294 2009-10-02 US		
其他公开文献	US9918675		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		
摘要(译)			

一种用于监测患者喉部肌肉的EMG信号的装置包括具有外表面的气管内导管。在气管内导管上形成导电电极。导电电极配置成当气管内管放置在患者的气管中时接收来自喉部肌肉的EMG信号。至少无线传感器形成在气管内管上，并且被配置为将信息无线传输到处理设备。

