



(11)

EP 1 929 956 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:

29.06.2016 Bulletin 2016/26

(51) Int Cl.:

A61B 8/13 (2006.01)

A61B 6/08 (2006.01)

A61B 5/055 (2006.01)

A61B 8/12 (2006.01)

A61B 5/044 (2006.01)

(21) Application number: **07254746.6**

(22) Date of filing: **07.12.2007**

(54) **Coloring electroanatomical maps to indicate ultrasound data acquisiton**

Färbung elektroanatomischer Karten zur Anzeige einer Ultraschalldatenerfassung

Coloration de cartes électroanatomiques pour indiquer l'acquisition de données ultrasoniques

(84) Designated Contracting States:

**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE
SI SK TR**

(30) Priority: **08.12.2006 US 608506**

(43) Date of publication of application:

11.06.2008 Bulletin 2008/24

(60) Divisional application:

11157122.0 / 2 359 749

(73) Proprietor: **Biosense Webster, Inc.**

Diamond Bar, CA 91765 (US)

(72) Inventors:

- **Altmann, Andres Claudio**
Haifa 34614 (IL)
- **Govari, Assaf**
Haifa 34400 (IL)

- **Kirshenbaum, Dina**
Nesher 36721 (IL)

(74) Representative: **Small, Gary James**

Carpmaels & Ransford LLP

One Southampton Row

London WC1B 5HA (GB)

(56) References cited:

EP-A- 1 720 038

WO-A-99/60921

JP-A- 2001 070 269

US-A1- 2003 231 789

US-A1- 2006 239 527

- **SERMESANT ET AL: "Simulation of cardiac
pathologies using an electromechanical
biventricular model and XMR interventional
imaging" MEDICAL IMAGE ANALYSIS, OXFORD
UNIVERSITY PRESS, OXOFRD, GB, vol. 9, no. 5,
October 2005 (2005-10), pages 467-480,
XP005040723 ISSN: 1361-8415**

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

BACKGROUND OF THE INVENTION

Field of the Invention

[0001] This invention relates generally to mapping and reconstruction of body organs. More particularly, this invention relates to imaging internal body organs, such as the heart.

Description of the Related Art

[0002] Ultrasound imaging is now well established as a modality for imaging the heart. For example, U.S. Patent No. 6,066,096, whose disclosure is incorporated herein by reference, describes an imaging probe for volumetric intraluminal ultrasound imaging. The probe, configured to be placed inside a patient's body, includes an elongated body having proximal and distal ends. An ultrasonic transducer phased array is connected to and positioned on the distal end of the elongated body. The ultrasonic transducer phased array is positioned to emit and receive ultrasonic energy for volumetric forward scanning from the distal end of the elongated body. The ultrasonic transducer phased array includes a plurality of sites occupied by ultrasonic transducer elements.

[0003] However, many physicians find it difficult to interpret ultrasound images, which typically appear as a two-dimensional fan-shaped pattern. Although the physician knows what anatomical features should appear in a display produced by an ultrasound catheter, he may not be able to match these features with the bright and dark areas of the fan.

[0004] It has been proposed to improve medical image interpretation by superimposing images acquired by different modalities in registration. For example, U.S. Patent No. 6,556,695, issued to Packer et al., suggests that a magnetic resonance image can be acquired, and then registered with a subsequently acquired electrical activation map or ultrasound image.

[0005] EP-A-1 720 038 discloses a system and method for imaging a target in a patient's body that uses a pre-acquired image of the target and a catheter having a position sensor and an ultrasonic imaging sensor. The catheter is placed in the patient's body and positional information of a portion of the catheter in the patient's body is determined using the position sensor. The catheter is used to generate an ultrasonic image of the target using the ultrasonic imaging sensor. An image processor is used for determining positional information for any pixel of the ultrasonic image of the target and registering the pre-acquired image with the ultrasonic image; and a display is used for displaying the registered pre-acquired image and ultrasonic image.

[0006] WO 99/60921 A discloses a method and apparatus for three-dimensional imaging and treatment of a patient's body. The method and apparatus utilize a sys-

tem for developing a therapy plan for treatment of an organ of the patient, a device for generating ultrasound image data from a treatment region, a device for providing a translucent volume image of a portion of a patient's body and a separate translucent image of the patient organ, and a three-dimensional viewing device to superimpose a translucent article image to enable viewing of the article image simultaneously with the patient organ and a portion of the patient's body.

[0007] US2003231789 A1 discloses an apparatus for producing images of a living subject comprising: a display; a memory for storing a three-dimensional topological map of a structure in a body of said subject; a two-dimensional imaging module operative for acquiring a sequence of two-dimensional anatomic images of at least a portion of said structure, said two-dimensional anatomic images having respective image planes; and a processor linked to said memory and to said two-dimensional imaging module, said processor operative for marking said three-dimensional topological map on said display to show an intersection of said image plane with said topological map.

SUMMARY OF THE INVENTION AND DISCLOSURE

[0008] In order to assist the physician in performing a realtime cardiac imaging procedure, a three-dimensional image of the heart may be rendered during acquisition. However, this blocks the user's view of the heart chamber by other tissue reflection, e.g., from other chambers or organs. Therefore, it is difficult for the user to determine when adequate image data have been acquired or whether details are still missing.

[0009] According to disclosed embodiments of the invention, a three-dimensional representation of the structure, such as a functional map, e.g., an electroanatomical map, is displayed and marked, typically by application of pseudocolor, during acquisition of ultrasound data in order to show the progress of data acquisition. For example, the planes of intersection of successive ultrasound two-dimensional fans that are acquired may be marked on an electroanatomical map as lines or colored regions on the map surface. This display enables the operator to determine regions where sufficient ultrasound data have been captured, and guides the operator to areas of the heart chamber where additional data collection is still needed. Various color schemes are used to indicate the relative sufficiency of data collection.

[0010] An example of the disclosure provides a computer-assisted method for producing images of a living subject, which is carried out by displaying a three-dimensional model of a surface of a structure in a body of the subject, acquiring a sequence of two-dimensional anatomic images of at least a portion of the structure, and while acquiring the sequence, marking the three-dimensional model to show respective intersections of the image planes with the surface.

[0011] In an aspect of the method, the three-dimen-

sional model may be a computed tomographic image or a magnetic resonance image, which is automatically registered with the image planes.

[0012] Another aspect of the method includes displaying the three-dimensional model and the respective intersections of the image planes with the surface on the three-dimensional model.

[0013] According to an additional aspect of the method, a pseudocolor is displayed on the respective intersections of the image planes with the surface.

[0014] Yet another aspect of the method includes interpolating areas of the three-dimensional model between the respective intersections, marking the interpolated areas, and displaying the interpolated areas.

[0015] Another aspect of the method includes reconstructing a three-dimensional anatomic image of the structure from the two-dimensional anatomic images, and displaying at least a portion of the three-dimensional anatomic image with the three-dimensional model.

[0016] According to still another aspect of the method, the displayed portion of the three-dimensional anatomic image does not extend beyond a predefined distance from a surface of the three-dimensional model.

[0017] According to one aspect of the method, the structure is a heart and the three-dimensional model is an anatomical map.

[0018] In other aspects of the method, the two-dimensional anatomic images can be acquired by realtime three-dimensional ultrasound imaging, realtime computed tomographic imaging, or realtime magnetic resonance imaging.

[0019] The invention provides an apparatus for carrying out the above-described method.

BRIEF DESCRIPTION OF THE DRAWINGS

[0020] For a better understanding of the present invention, reference is made to the detailed description of the invention, by way of example, which is to be read in conjunction with the following drawings, wherein like elements are given like reference numerals, and wherein:

Fig. 1 illustrates a system for imaging and mapping a heart of a patient in accordance with a disclosed embodiment of the invention;

Fig. 2 is a block diagram illustrating further details of the system shown in Fig. 1 in accordance with a disclosed embodiment of the invention;

Fig. 3 is a flow chart of a general method of marking a three-dimensional model of an internal structure of the body to indicate progress in acquiring a plurality of two-dimensional images of the structure in accordance with a disclosed embodiment of the invention;

Fig. 4 is a detailed flow chart of a method of coloring a functional map to indicate ultrasound data acquisition in accordance with an alternate embodiment of the invention;

Fig. 5 is a display of multimodal images of the heart in accordance with a disclosed embodiment of the invention;

Fig. 6 shows a skeleton model of the right ventricle of a heart, which is prepared in accordance with a disclosed embodiment of the invention; and

Fig. 7 is a composite image, in which a skeleton model representing of a three-dimensional ultrasound cardiac image of the heart is superimposed on an electro-anatomical map of the right ventricle, in accordance with a disclosed embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

[0021] In the following description, numerous specific details are set forth in order to provide a thorough understanding of the present invention. It will be apparent to one skilled in the art, however, that the present invention may be practiced without these specific details. In other instances, well-known circuits, control logic, and the details of computer program instructions for conventional algorithms and processes have not been shown in detail in order not to obscure the present invention unnecessarily.

System Overview

[0022] Turning now to the drawings, reference is initially made to Fig. 1, which is an illustration of a system 20 for imaging and generating electrical activation maps of a heart 24 of a patient, and which is suitable for performing diagnostic or therapeutic procedures involving the heart 24, in accordance with an embodiment of the present invention.

[0023] While the principles of the invention are disclosed with reference to cardiac imaging, the techniques described may be adapted for use for imaging other organs using a manually or automatically controlled probe, particularly hollow organs, such as the bladder, which may be imaged using an ultrasound catheter.

[0024] The system 20 comprises a catheter 28, which is percutaneously inserted by a physician into a chamber or vascular structure of the heart. The catheter 28 typically comprises a handle 29 for operation of the catheter by the physician. Suitable controls on the handle 29 enable the physician to steer, position and orient the distal end of the catheter as desired.

[0025] The system 20 enables the physician to perform a variety of mapping and imaging procedures. These procedures comprise, for example, the following techniques, which are described in further detail in copending, commonly assigned Application Nos. 11/115,002 and 11/262,217, the disclosures of which are herein incorporated by reference:

[0026] display real-time or near real-time two-dimensional images, e.g. ultrasound images;

[0027] reconstruct three-dimensional models of a tar-

get structure in the patient's body, based on two-dimensional ultrasound images;

[0028] register, overlay and display a parametric map, such as an electrophysiological information map or an electro-anatomical map on the reconstructed three-dimensional model;

[0029] register, overlay and display a three-dimensional image acquired from an external system on the reconstructed three-dimensional model; and

[0030] register and display two-dimensional ultrasound images on a three-dimensional image acquired from an external system.

[0031] The system 20 comprises a positioning subsystem that measures three-dimensional location information and orientation coordinates of the catheter 28 with up to six degrees of freedom. The positioning subsystem may comprise a magnetic position tracking system that determines the position and orientation of the catheter 28. The positioning subsystem generates magnetic fields in a predefined working volume its vicinity and senses these fields at the catheter. The positioning subsystem typically comprises a set of external radiators, such as field generating coils 30, which are located in fixed, known positions external to the patient. The coils 30 generate fields, typically electromagnetic fields, in the vicinity of the heart 24.

[0032] In an alternative embodiment, a radiator in the catheter, such as a coil, generates electromagnetic fields, which are received by sensors (not shown) outside the patient's body.

[0033] The position sensor transmits, in response to the sensed fields, position-related electrical signals over cables 33 running through the catheter to a console 34. Alternatively, the position sensor may transmit signals to the console 34 over a wireless link. The console 34 comprises a positioning processor 36 that calculates the location and orientation of the catheter 28 based on the signals sent by a location sensor 46. The positioning processor 36 typically receives, amplifies, filters, digitizes, and otherwise processes signals from the catheter 28. Images produced by the system 20 are displayed on a monitor 44.

[0034] Some position tracking systems that may be used for this purpose are described, for example, in U.S. Patents 6,690,963, 6,618,612 and 6,332,089, and U.S. Patent Application Publications 2004/0147920, and 2004/0068178, whose disclosures are incorporated herein by reference. Although the positioning subsystem shown in Fig. 1 uses magnetic fields, the methods described below may be implemented using any other suitable positioning subsystem, such as systems based on acoustic or ultrasonic measurements.

[0035] For ultrasound image generation, the system 20 may employ the catheters disclosed in U.S. Patent Nos. 6,716,166 and 6,773,402, whose disclosures are herein incorporated by reference, in order to acquire ultrasound images for display in near realtime ultrasound images concurrently with an image or representation of

the position of a deployment catheter in the same or different sessions, and in many different combinations. Such catheters have acoustic transducers that are adapted for emitting sound waves, and receiving reflections from echogenic interfaces in the heart. The reflections are then analyzed to construct two-dimensional and three-dimensional images of the heart.

[0036] The system 20 comprises an ultrasound driver 39 that drives the ultrasound transducers of the catheter 28 when it functions as an ultrasound imaging catheter. One example of a suitable ultrasound driver that can be used for this purpose is an AN2300™ ultrasound system produced by Analogic Corporation, 8 Centennial Drive, Peabody, MA 01960. The ultrasound driver 39 may support different imaging modes such as B-mode, M-mode, CW Doppler and color flow Doppler, as are known in the art.

[0037] Optionally, the catheter 28 and another catheter 48 are both incorporated in the system 20 and inserted concurrently into the heart via different vascular approaches. In this example, the catheter 28 functions as a mapping catheter, and the catheter 48 functions as an ultrasound imaging catheter, using an array of acoustic transducers 50. Each has an instance of the location sensor 46 that is used to determine the position and orientation of the catheter within the body.

[0038] The system 20 contains electronic circuitry for generation of an electrical activation map, and can be used in conjunction with many specialized mapping catheters. A suitable mapping catheter for use as the catheter 28 is described in commonly assigned U.S. Patent No. 6,892,091, whose disclosure is herein incorporated by reference. Briefly, the distal end of the mapping catheter includes a distally placed mapping electrode 52 for measuring the electrical properties of the heart tissue. The distal end of the mapping catheter further also includes an array of non-contact electrodes 54 for measuring far field electrical signals in the heart chamber.

[0039] Typically, the mapping catheter is introduced first, and an electrical activation map generated from its data. Afterward, an ultrasound imaging catheter is introduced. The two catheters may be introduced via the same or different vascular approaches.

[0040] In yet another alternative, a hybrid catheter, capable of both data acquisition suitable for electrical activation map generation, and also having ultrasound imaging functions can be used. Such catheters are described, for example, in U.S. Patents Nos. 6,773,402, 6,788,967, and 6,645,145. Use of such catheters may permit the medical procedure to be shortened. In this alternative, only one catheter need be inserted. In all the alternatives, as explained in further detail below, the electrical activation map is usually acquired first, and then applied to the ultrasound images to assist in the interpretation of the latter. Suitable image registration techniques for coordinating the two modalities are disclosed in U.S. Patent No. 6,650,927 and in co-pending Application No. 11/215,435, both of common assignee herewith, and

herein incorporated by reference.

[0041] Reference is now made to Fig. 2, which is a block diagram illustrating further details of the system 20 (Fig. 1). As noted above, many elements of the system 20 can be realized as a general purpose or specialized computer that includes a processor and a memory that contains objects corresponding to the functional blocks depicted in Fig. 2. The positioning processor 36 is linked to location sensors that are placed near the distal tip of the cardiac catheter and performs location tracking.

[0042] The ultrasound driver 39, which drives the transducers 50 (Fig. 1) is cooperative with ultrasound circuitry 56, and produces two-dimensional ultrasound images.

[0043] An image processor 60 is linked to the mapping circuitry 58, the positioning processor 36, and the ultrasound circuitry 56. The image processor 60 can perform three-dimensional ultrasound image reconstruction, and is specialized for the automatic identification of cardiac topological features on the ultrasound images. In some embodiments, the image processor 60 may augment automatic identification of topologic features on the electrical activation map by the mapping circuitry 58, without operator assistance. The image processor 60 also performs image registration functions. Its operation is mediated via a user input 62. Its output is sent to a display 64.

[0044] A commercial unit suitable for use in the system 20, which is capable of generating an electrical activation map, is the CARTO XP EP Navigation and Ablation System, available from Biosense Webster, Inc., 3333 Diamond Canyon Road, Diamond Bar, CA 91765. Images acquired using different modalities can be registered for display using the CartoMerge™ image integration module, which is adapted for operation with the CARTO XP EP Navigation and Ablation System. In particular, it is possible to register a three-dimensional anatomical map or electroanatomical map with a three-dimensional ultrasound image with this module. Furthermore, the ultrasound fan image produced by two-dimensional ultrasound imaging shares the coordinate system of the anatomical or electroanatomical map. The system is able to automatically compute the intersection of the fan image and the three-dimensional image, as well as interpolate between adjacent intersections of different fan images.

Operation

[0045] Reference is now made to Fig. 3, which is a flow chart of a general method of marking a three-dimensional model of an internal structure of the body to indicate progress in acquiring a plurality of two-dimensional images of the structure in accordance with a disclosed embodiment of the invention.

[0046] At initial step 80, a three-dimensional model of the structure is acquired and displayed. This can be an image of the heart, obtained with a system such as the above-noted CARTO XP EP Navigation and Ablation System. However any three-dimensional model can be

used, for example a tomographic image. It is important to display the topography of the heart or other structure, and the functional data, for example electrical potentials that may be shown on the model are incidental.

[0047] Next, at step 82 a two-dimensional image of a portion of the structure is acquired. This may be an ultrasound image. Alternatively, the two-dimensional image could be a two-dimensional functional image, obtained by techniques such as magnetic resonance imaging or computed tomographic imaging.

[0048] Next, at step 84, the two-dimensional image acquired in step 82 is automatically registered or otherwise coordinated with the three-dimensional model produced in initial step 80. This step allows topographic features of the three-dimensional model to be related to the structures imaged in step 82.

[0049] Next, at step 86, the intersection of the plane of the two-dimensional image with the three-dimensional model is marked on the display. This step can be performed by applying a pseudocolor to the display. Alternatively, many other graphical techniques can be used to indicate the intersection, e.g., flashing effects, bolding emphasis. Additionally, as explained below, pseudocolor may be applied in order to display areas on the three-dimensional model located between adjacent intersections of different fan images. Such areas are identified by interpolation. In any case, the operator can identify topographical features of the structure that were obtained on the current two-dimensional image by reference to the display and the markings on the three-dimensional model. Optionally, the operator may annotate the display by textual descriptive information relating to the current two-dimensional image.

[0050] Control now proceeds to decision step 88, where it is determined if more images are required to complete the imaging study. If the determination at decision step 88 is affirmative, then control returns to step 82 for another iteration.

[0051] If the determination at decision step 88 is negative, then control proceeds to final step 90, and the procedure ends.

Alternate Embodiment 1

[0052] Reference is now made to Fig. 4, which is a detailed flow chart of a method of coloring an electroanatomical map or other functional map to indicate ultrasound data acquisition in accordance with an alternate embodiment. It will be understood that "coloring", also referred to herein as the application of pseudocolor, denotes a computing task and involves modifications to memory in which image data is stored. The results of the operation may be visualized on a computer monitor as a colored display. The method is discussed with reference to an electroanatomical map by way of example. However, the method is applicable to other functional images of the heart, so long as the topology of the heart is shown and can be related to the location of the ultrasound data.

In initial step 66, using instrumentation described above with reference to Fig. 1 and Fig. 2, a mapping catheter is introduced into a subject using well-known techniques. An ultrasound imaging catheter is also introduced into the heart.

[0053] Next, at step 68, the mapping catheter is navigated within the heart, and electrical data obtained. A functional image is generated. In one embodiment, an electroanatomical map is generated, for example, using the above-mentioned CARTO XP EP Navigation and Ablation System. The image is generated using the mapping catheter by determining spatial coordinates of different locations in the heart to define a three-dimensional space. Then a functional model is prepared, which is a three-dimensional map of the heart in the three-dimensional space, in which the map displays functional information, i.e., electrical potentials at multiple points of the heart.

[0054] Concurrently with step 68, at step 70, at least one two-dimensional ultrasound image is acquired. Generally, this is a gated image. Position information provided by location sensors on the ultrasound imaging catheter are processed by the positioning subsystem to establish coordinates of different points on the ultrasound image. Typically, the electroanatomical map and the two-dimensional ultrasound image are obtained during the same session. However, this is not necessary, and alternatively, the electroanatomical map may be pre-acquired and registered with the two-dimensional ultrasound image.

[0055] Next, at step 69, the area of the electro-anatomical map or other functional image corresponding to the ultrasound image acquired in the last iteration of step 70 is identified by application of pseudocolor. One pseudocolor may be used, at different intensities as the sufficiency of the image improves. Alternatively, multiple pseudocolors can be used and combined in order to indicate current image quality in many different schemes. Additionally or alternatively, other graphical indications of image quality may be displayed in this step, for example flashing effects. In one embodiment, the relevant portion of the electroanatomical map is determined by computing the plane of intersection of the ultrasound fan image on the electro-anatomical map.

[0056] Reference is now made to Fig. 5, which is a display of multimodal images of the heart in accordance with a disclosed embodiment. An image 92, at the left side of Fig. 5, is a topological map of a heart chamber generated by the above-noted CARTO XP EP Navigation and Ablation System.

[0057] In a central image 94, the map is partly colored to show an area 96 of the chamber wall where ultrasound data have been collected. For example, the plane of intersection of each successive ultrasound two-dimensional fan that is acquired may be marked on the image 94 as a colored region on the map surface. Alternatively, the plane of intersection may be marked as a colored line. Further alternatively, the image 94 may be colored

to mark every data voxel where the ultrasound beam plane intersected the electroanatomical map. In any case, the display enables the operator to see where sufficient ultrasound data have been captured and is useful to guide the operator to areas of the heart chamber where additional data collection is still needed.

[0058] An image 98 on the right of Fig. 5 shows a reconstruction of a three-dimensional ultrasound image 100 superimposed on the image 98, which is here referenced as an area 102. The image 98 and the area 102 are based on the collected ultrasound data.

[0059] In one embodiment, two-dimensional ultrasound images are projected without reconstructing a solid three-dimensional model. This technique is described in the above-noted Application Nos. 11/115,002 and 11/262,217. For example, successive two-dimensional ultrasound images can be acquired in iterations of step 70 (Fig. 4), and contours-of-interest tagged. The images can then be oriented and projected in three-dimensional space.

[0060] Reference is now made to Fig. 6, which shows a skeleton model 88 of the right ventricle of a heart, in accordance with a disclosed embodiment. The system 20 (Fig. 1) can automatically trace and reconstruct contours 90, 92 from untagged ultrasound images and can automatically reconstruct contours 94 from two-dimensional physician-labeled counterparts.

[0061] Reference is now made to Fig. 7, which is an exemplary composite image 96 in which a skeleton model of a three-dimensional ultrasound image 98 of the heart is superimposed on an electro-anatomical map 100 of the right ventricle, in accordance with a disclosed embodiment. The skeleton model is similar to the skeleton model 88 (Fig. 6), having a plurality of contours 102, 104 outlining the right ventricle and left ventricle, respectively. The contours 102 are overlaid on the electro-anatomical map. Different electrical potential values are indicated by different shading patterns. Superimposing the skeletal model on the electroanatomical map in step 72 (Fig. 4) results in less interference on the display than using a fully reproduced three-dimensional model, as can be appreciated by a comparison of Fig. 7 with the image 98 (Fig. 5). As in Fig. 5, portions of the map 100 may be automatically marked using pseudocolor to indicate adequate ultrasound data collection. For example, pseudocolor has been applied to an area 105, represented by a diagonally hatched pattern in Fig. 7.

[0062] Referring again to Fig. 4, as the data are acquired in successive iterations of step 70, the electroanatomical map, and optionally vessels, which may be shown diagrammatically on the electroanatomical map as contours or cylindrical structures, are progressively colored to indicate the areas that were imaged, as shown on the image 94 (Fig. 5). For example, the map may start with a gray color, as on the image 92 (Fig. 5), and the color may then change from gray to red at every point on the map that corresponds to points where ultrasound image data were acquired. In this manner, the operator re-

ceives a clear indication of the current data coverage.

[0063] Next, at step 72, the ultrasound images acquired in iterations of step 70 are superimposed on the electroanatomical map, such that the two are seen in registration on a display. This is carried out automatically, using methods of synchronization, and registration of the reconstructed image with the electroanatomical map, as noted above. Briefly, the ultrasound catheter includes both a location sensor and an ultrasound transducer in one unit. The system, after appropriate calibration, can automatically correlate any point seen on the ultrasound image with its corresponding point in three-dimensional space of the electroanatomic map. The image registration is typically established by correlating the coordinates during the generation of the electroanatomic map with position information and coordinates on the ultrasound image that were obtained in step 70. External anatomic markers may be used to provide a common frame of reference in order to couple the data from the two modalities. In some embodiments, the ultrasound image is a three-dimensional ultrasound image that is reconstructed from multiple two-dimensional ultrasound images. Alternatively, two-dimensional fan images are superimposed as lines on the electroanatomical map.

[0064] Optionally, as shown in step 75, the ultrasound images and the electroanatomical map are displayed separately. This option has the advantages that multimodal image registration issues are avoided in the display. Furthermore, one image is not obscured by the other. In a variation of step 75, at least a portion of the three-dimensional image is displayed inside the three-dimensional model, and the three-dimensional image does not extend more than a predefined distance from the surface of the three-dimensional model. The result is that a three-dimensional space is segmented according to the proportion of the three-dimensional image that is displayed. Segmentation techniques suitable for this operation are disclosed in the above-noted Application No. 11/215,435.

[0065] In either of steps 72, 75 synchronization between the two modalities required, of course. Referring again to Fig. 7, the ultrasound image 98 and the electroanatomical map 100 can be acquired using different equipment. When one or both of the images are being tracked in near-real time, and particularly when different equipment is used for the two modalities, propagation delays between the source equipment and the processor 36 (Fig. 1) necessitate careful attention to synchronization of the two components of the composite image 96. Indeed, synchronization issues occur generally, in different embodiments of the system 20 (Fig. 1). Solutions for this problem are taught in the above-noted Application No. 11/262,217. Briefly, when near real-time electroanatomic data are acquired and superimposed upon previously acquired anatomic images or models, a constant pre-defined offset, which can be a temporal offset, is established between the electroanatomical data and the anatomic image gating. This offset compensates for sys-

tem delays caused by image processing and image transfer from the source of the anatomic images to the image processor, which as noted above, generates an electroanatomical map from the electroanatomical data.

[0066] After performing either of steps 72, 75, the operator may identify anatomical features and mark them on the display, using a graphical user interface.

[0067] Control next proceeds to decision step 79, where it is determined if more two-dimensional ultrasound images are necessary to complete the examination. This decision is normally made by the operator, but he may be prompted by the system, which can automatically determine if the examination is complete. If the determination at decision step 79 is affirmative, then control returns to step 70. When imaging the heart, the operator may start the imaging procedure with contour mapping of the left and right atria, marking relevant structures, such as the pulmonary veins, aorta and fossa ovalis. The pulmonary veins and aorta can be shown as vessels with adjustable radii defined by the ultrasound contours.

[0068] If the determination at decision step 79 is negative, then control proceeds to final step 81. The catheters are withdrawn, and the procedure ends.

25 Alternate Embodiment 2

[0069] This embodiment is similar to alternate embodiment 1, except that an inverse display mode can be used for displaying a three-dimensional image, e.g., the image 100 (Fig. 5) in steps 72, 75 (Fig. 4). The data acquisition for the ultrasound images is essentially the same, but instead of showing high gray scale levels for tissue, the three-dimensional ultrasound image indicates the blood in the chamber or vessel, and is an indicator of the chamber or vessel blood volume.

Alternate Embodiment 3

[0070] Other physiological data that may be mapped for co-display in steps 72, 75 (Fig. 4) with ultrasound images and pseudocolor applied colored to indicate sufficiency of ultrasound data collection as described above. Volumetric intraluminal ultrasound imaging as described by the above-noted U.S. Patent No. 6,066,096 can be used. Other physiological parameters that can be mapped include temperature, blood flow rate, chemical properties and mechanical activity, e.g., regional wall motion. For example, areas of high-speed flow detected by an ultrasound catheters, as disclosed, e.g., in the above-noted U.S. Patent Nos. 6,716,166 and 6,773,402, may be identified in a Doppler image and registered with stenoses in blood vessels observed in a three-dimensional ultrasound image. As another example, a chemical sensor may be used to identify areas of the heart with low NADPH levels, indicative of ischemia. Such areas may be registered with corresponding areas observed on ultrasound images. The technique described in the article Quantitative Measurements of Cardiac Phosphorus Me-

tabolites in Coronary Artery Disease by 31P Magnetic Resonance Spectroscopy, Takahiro Yabe et al., Circulation. 1995;92:15-23 is suitable for displaying such areas.

Alternate Embodiment 4

[0071] In this embodiment, step 70 (Fig. 4) is performed using a modality other than two-dimensional ultrasound imaging to acquire realtime data as a series of image "slices" through the target structure. Step 70 can be performed using a realtime three-dimensional ultrasound imaging probe, realtime computed tomographic imaging, realtime magnetic resonance imaging or other realtime imaging modality from which three-dimensional images can be generated and co-displayed with a functional image to which pseudocolor is applied to indicate sufficiency of data imaging in particular areas.

Alternate Embodiment 5

[0072] This variation can be employed additionally to any of the preceding embodiments. In steps 72, 75 (Fig. 4), additional indications are shown on the map display to guide the operator during data acquisition. For example, the fill ratio, the ratio of colored area to total target area on the electroanatomical map or other functional map, can be displayed to quantitatively indicate the extent of completion of the session.

[0073] In additional application of pseudocolor itself can be modified according to the gray scale level of each voxel using a corresponding lookup table. This enables the user to see if the acquired data corresponds to a wall tissue or to a vessel or valve opening in the chamber.

[0074] It will be appreciated by persons skilled in the art that the present invention is not limited to what has been particularly shown and described hereinabove.

Claims

1. An apparatus (20) for producing images of a living subject comprising:

- a display (44);
- a memory for storing a three-dimensional topological map of a structure in a body of said subject;
- a two-dimensional imaging module operative for acquiring a sequence of two-dimensional anatomic images of at least a portion of said structure, said two-dimensional anatomic images having respective image planes; and
- a processor (60) linked to said memory and to said two-dimensional imaging module, said processor (60) operative for marking said three-dimensional topological map on said display to show successive respective intersections of

said image planes with said topological map where imaging data have been collected, wherein the topological map is an electroanatomical map or other functional map.

2. The apparatus (20) according to claim 1, wherein said two-dimensional anatomic images are selected from the group consisting of a computed tomographic image and a magnetic resonance image, and said processor (60) is operative for automatically registering said image planes with said three-dimensional topological map.

3. The apparatus (20) according to claim 1, wherein said processor (60) is operative for:

- reconstructing a three-dimensional anatomic image (100) of said structure from said two-dimensional anatomic images; and
- displaying said three-dimensional anatomic image (100) with said three-dimensional topological map.

4. The apparatus (20) according to claim 1, wherein said two-dimensional imaging module generates two-dimensional anatomic images selected from the group consisting of ultrasound images, computed tomographic images and magnetic resonance images, said structure is a heart and said three-dimensional topological map is an electroanatomical map.

Patentansprüche

1. Vorrichtung (20) zum Herstellen von Bildern eines lebenden Objekts, umfassend:

- ein Display (44);
- einen Speicher zum Speichern einer dreidimensionalen topologischen Karte einer Struktur in einem Körper des Objekts;
- ein zweidimensionales Bildgebungsmodul, das operativ ist zum Erfassen einer Sequenz zweidimensionaler anatomischer Bilder von mindestens einem Abschnitt der Struktur, wobei die zweidimensionalen anatomischen Bilder jeweilige Bildebenen aufweisen; und
- einen Prozessor (60), der mit dem Speicher und mit dem zweidimensionalen Bildgebungsmodul verknüpft ist, wobei der Prozessor (60) operativ ist zum Markieren der dreidimensionalen topologischen Karte auf dem Display, um aufeinanderfolgende jeweilige Kreuzungen der Bildebenen mit der topologischen Karte zu zeigen, wo Bildgebungsdaten gesammelt worden sind, wobei die topologische Karte eine elektroanatomische Karte oder eine andere Funktionskarte ist.

2. Vorrichtung (20) nach Anspruch 1, wobei die zweidimensionalen anatomischen Bilder ausgewählt sind aus der Gruppe bestehend aus einem berechneten Tomographiebild und einem Magnetresonanzbild und der Prozessor (60) operativ ist zum automatischen Registrieren der Bildebenen mit der dreidimensionalen topologischen Karte.
3. Vorrichtung (20) nach Anspruch 1, wobei der Prozessor (60) operativ ist zum:
- Rekonstruieren eines dreidimensionalen anatomischen Bilds (100) der Struktur aus den zweidimensionalen anatomischen Bildern; und
- Anzeigen des dreidimensionalen anatomischen Bilds (100) mit der dreidimensionalen topologischen Karte.
4. Vorrichtung (20) nach Anspruch 1, wobei das zweidimensionale Bildgebungsmodul zweidimensionale anatomische Bilder generiert ausgewählt aus der Gruppe bestehend aus Ultraschallbildern, Computertomographiebildern und Magnetresonanzbildern, die Struktur ein Herz ist und die dreidimensionale topologische Karte eine elektroanatomische Karte ist.

Revendications

1. Appareil (20) destiné à produire des images d'un sujet vivant comprenant :
- un écran (44) ;
- une mémoire servant à stocker une carte topologique tridimensionnelle d'une structure dans le corps dudit sujet ;
- un module d'imagerie bidimensionnelle opérationnel pour acquérir une séquence d'images anatomiques bidimensionnelles d'au moins une partie de ladite structure, lesdites images anatomiques bidimensionnelles ayant des plans images respectifs ; et
- un processeur (60) associé à ladite mémoire et audit module d'imagerie bidimensionnelle, ledit processeur (60) étant opérationnel pour marquer ladite carte topologique tridimensionnelle sur ledit écran pour montrer des intersections respectives successives desdits plans images avec ladite carte topologique où des données d'imagerie ont été collectées, la carte topologique étant une carte électro-anatomique ou une autre carte fonctionnelle.
2. Appareil (20) selon la revendication 1, dans lequel lesdites images anatomiques bidimensionnelles sont choisies dans le groupe constitué par une image tomodensitométrie et une image de résonance

magnétique, et ledit processeur (60) est opérationnel pour aligner automatiquement lesdits plans images avec ladite carte topologique tridimensionnelle.

3. Appareil (20) selon la revendication 1, dans lequel ledit processeur (60) est opérationnel pour :
- reconstruire une image anatomique tridimensionnelle (100) de ladite structure à partir desdites images anatomiques bidimensionnelles ; et
- afficher ladite image anatomique tridimensionnelle (100) avec ladite carte topologique tridimensionnelle.
4. Appareil (20) selon la revendication 1, dans lequel ledit module d'imagerie bidimensionnelle génère des images anatomiques bidimensionnelles choisies dans le groupe constitué par des images ultrasonores, des images tomodensitométries et des images de résonance magnétique, ladite structure est un cœur et ladite carte topologique tridimensionnelle est une carte électro-anatomique.




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6





FIG. 7



REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 6066096 A [0002] [0070]
- US 6556695 B, Packer [0004]
- EP 1720038 A [0005]
- WO 9960921 A [0006]
- US 2003231789 A1 [0007]
- WO 11115002 A [0025] [0059]
- WO 11262217 A [0025] [0059] [0065]
- US 6690963 B [0034]
- US 6618612 B [0034]
- US 6332089 B [0034]
- US 20040147920 A [0034]
- US 20040068178 A [0034]
- US 6716166 B [0035] [0070]
- US 6773402 B [0035] [0040] [0070]
- US 6892091 B [0038]
- US 6788967 B [0040]
- US 6645145 B [0040]
- US 6650927 B [0040]
- US 11215435 B [0040]
- WO 11215435 A [0064]

Non-patent literature cited in the description

- TAKAHIRO YABE et al. *Circulation*, 1995, vol. 92, 15-23 [0070]

专利名称(译)	着色电解剖图以指示超声数据采集		
公开(公告)号	EP1929956B1	公开(公告)日	2016-06-29
申请号	EP2007254746	申请日	2007-12-07
[标]申请(专利权)人(译)	韦伯斯特生物官能公司		
申请(专利权)人(译)	生物传感韦伯斯特，INC.		
当前申请(专利权)人(译)	生物传感韦伯斯特，INC.		
[标]发明人	ALTMANN ANDRES CLAUDIO GOVARI ASSAF KIRSHENBAUM DINA		
发明人	ALTMANN, ANDRES CLAUDIO GOVARI, ASSAF KIRSHENBAUM, DINA		
IPC分类号	A61B8/13 A61B8/12 A61B6/08 A61B5/044 A61B5/055		
CPC分类号	A61B5/044 A61B5/7285 A61B5/743 A61B6/08 A61B6/463 A61B6/5229 A61B6/5241 A61B8/12 A61B8/13 A61B8/4488 A61B8/463 A61B8/483 A61B8/5238 A61B8/543 A61B34/20 A61B90/36 A61B2034/105 A61B2034/2051 A61B2090/364 A61B2090/365 A61B2090/367 A61B2090/378		
优先权	11/608506 2006-12-08 US		
其他公开文献	EP1929956A3 EP1929956A2		
外部链接	Espacenet		

摘要(译)

在医学成像过程中获取超声数据期间，被成像的结构三维模型（例如，电解剖图）被共同显示并可视地标记，以指示数据获取的进展。交叉平面连续的二维图像在三维模型上标记为线或彩色区域。该显示使操作员能够确定捕获了足够数据的区域，并指导操作员到仍需要额外数据收集的区域。各种颜色方案用于指示数据收集的相对充分性。

