(19)





# (11) **EP 1 633 266 B1**

(12)

## **EUROPEAN PATENT SPECIFICATION**

- (45) Date of publication and mention of the grant of the patent: 18.05.2016 Bulletin 2016/20
- (21) Application number: 04754905.0
- (22) Date of filing: 09.06.2004

(51) Int Cl.: **A61N 7/02** <sup>(2006.01)</sup> A61B 90/00 <sup>(2016.01)</sup>

A61B 8/12 (2006.01)

- (86) International application number: PCT/US2004/018452
- (87) International publication number: WO 2005/000097 (06.01.2005 Gazette 2005/01)

# (54) APPARATUS FOR TREATING ATRIAL FIBRILLATION USING HIGH INTENSITY FOCUSED ULTRASOUND

GERÄT FÜR DIE BEHANDLUNG VON VORHOFFLIMMERN MIT HOCHINTENSIVEN ULTRASCHALL

APPAREIL DE TRAITEMENT DE LA FIBRILLATION AURICULAIRE PAR DES ULTRASONS FOCALISES A HAUTE INTENSITE

| (84)  <br> <br> <br>(30) | Designated Contracting States:<br>AT BE BG CH CY CZ DE DK EE ES FI FR GB GR<br>HU IE IT LI LU MC NL PL PT RO SE SI SK TR<br>Priority: 10.06.2003 US 477532 P | (74) | Representative: Shanks<br>Marks & Clerk LLP<br>Aurora<br>120 Bothwell Street<br>Glasgow G2 7JS (GB) | , Andrew et al                   |
|--------------------------|--|------|---|----------------------------------|
| (43)                     | Date of publication of application:<br>15.03.2006 Bulletin 2006/11   | (56) | References cited:<br>WO-A-01/82778<br>FR-A- 2 827 149   | WO-A-89/07909<br>GB-A- 2 267 035 |
| (73)  <br>               | Proprietor: The Foundry, LLC<br>Menlo Park, CA 94025 (US)  |      | US-A- 5 391 140<br>US-A1- 2003 014 093  | US-A- 5 817 021                  |
| (72)                     | Inventor: GIFFORD, Hanson, S.<br>Woodside, CA 94062 (US)   |      |   |                                  |

EP 1 633 266 B1

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

#### Description

#### Field of the Invention

**[0001]** The present invention relates to an apparatus for treatment of atrial fibrillation, and more particularly, to an apparatus using high intensity focused ultrasound non-invasively to disrupt abnormal cardiac electrical pathways contributing to atrial fibrillation.

### Background of the Invention

**[0002]** US 5 391 140 relates to therapy apparatus configured for rectal insertion for prostate treatment. The apparatus has focused, therapeutic ultrasound waves having a first frequency, which includes an ultrasound locating system that emits diagnostic ultrasound that has a second frequency. The ultrasound locating system also receives parts of the diagnostic ultrasound reflected in the body of the subject and converts them into electrical signals which are used to form an image of the zone to be treated.

[0003] FR 2 827 149 relates to a treatment probe for focussed ultrasound comprising: a probe body which is mounted in rotation around an axis; an elongated treatment transducer with a focussed ultrasound emission acoustic axis which is more or less the same as the rotation axis of the probe body; and an imaging transducer, the imaging plane of which contains the acoustic axis of the treatment transducer. The inventive probe can be used to provide a simple treatment. The probe body can be rotated around the axis in order to vary the direction of the imaging plane without moving the focus which always remains in the imaging plane. The treatment transducer can be extended in order to provide safer treatment in relation to the organs to be treated and without risk of damaging the fragile surrounding organs. The focused ultrasound probe has a casing which rotates around an axis. The image transducer has a bar shape giving a linear sweep, its axis is parallel to the longitudinal direction of the treatment transducer.

**[0004]** US 5 817 021 relates to a therapy apparatus and method for treating conditions of the heart and, particularly, of heart-proximate vessels with therapeutic ultrasound waves having a therapeutically effective region. The therapy apparatus generates therapeutic ultrasound waves with such intensity that tissue modifications, particularly necrotization, are produced in the tissue located in the region of influence. The therapy apparatus preferably contains an ultrasound source that can be transesophageally applied.

**[0005]** WO 01/82778 relates to a method of treating tissue that includes providing orienting the transducers adjacent the treatment region, exciting the transducers to treat the tissue, and flushing fluid over the transducers. The apparatus for treating tissue includes a catheter, a device for monitoring the temperature adjacent the transducers, at least one transducer driver for exciting the

transducers to treat the tissue, and a source providing a flow of fluid through the lumen and over the transducers. **[0006]** GB 2 267 035 relates to a catheter comprising an ultrasonic transducer at its distal end and an electrode mounted in proximity thereto for receiving electrical cardiac signals to enable positioning of the transducer. Wires traverse the length of the catheter to connect the electrode with external monitoring equipment such as an electrocardiograph. The transducer, which may be of sin-

<sup>10</sup> gle crystal or phased array crystal type, delivers ultrasonic energy to myocardial tissue at frequencies sufficient to destroy tissue implicated in arrhythmia.

**[0007]** WO 89/07909 relates to a transducer assembly for visualization and treatment of transcutaneous and intraoperative sites. The assembly includes a visualization transducer and a treatment transducer, each of which

are movable with both linear and rotary degrees of freedom. Movement of each transducer is by various motor and geared drive arrangements wherein certain degrees

20 of freedom for one transducer are separate and independent from the degrees of freedom for the other transducer. At least one degree of freedom for each transducer is common and the transducers are moved concurrently. One arrangement of the transducer combination is for

<sup>25</sup> prostate treatment and includes a specific shape and configuration for anatomical considerations and a control unit which is operable external to the patient to control both transducers and a reflective scanner which are inserted into the patient as part of the ultrasound probe.

30 [0008] Up until the 1980s, there was dramatic growth in the creation of new surgical methods for treating a wide variety of previously untreated conditions. Over the past twenty years there has been a clear trend towards the invention of devices and methods that enable less-inva-

<sup>35</sup> sive treatment of such diseases, moving from invasive surgery, and then to less-invasive surgery, and to interventional techniques. Ultimately, it is desirable to move to totally non-invasive therapies.

[0009] The history of treatment of atrial fibrillation has followed this progression. First, Dr. James Cox invented a new open-heart surgical procedure that interrupted depolarization waves using surgical incisions in the walls of the atrium. More recently, a number of devices have been developed to allow surgeons to make such lesions

<sup>45</sup> during surgery on the beating heart, and without making incisions in the walls of the atrium. More recently, interventional electrophysiologists have worked with companies to develop catheter-based systems to create similar lesions. Although only partial success has been achieved
 <sup>50</sup> to date, there is optimism for further progress within the

next few years. [0010] It would be still more desirable to develop meth-

ods of treating atrial fibrillation which were still less invasive, eliminating even the need for catheters.

<sup>55</sup> [0011] A wide variety of energy modes have been used to create lesions using epicardial or intracardiac probes. Radio-frequency electrical energy, microwaves, cryothermia probes, alcohol injection, laser light, and ultrasound energy are just a few of the technologies that have been pursued.

**[0012]** Separately, several groups have developed focused ultrasound devices with both imaging and therapeutic capabilities. These efforts began perhaps with lithotripsy, in which a high power focused ultrasound system developed by Dornier Medizintechnik, Germany, is used to break up kidney stones in the body. The kidney stones are located within the body at a significant depth from the skin. One ultrasound imaging system is used to aim the system at the kidney stones, and then a second, high energy ultrasound system delivers energy that breaks up the stones so they can be passed.

**[0013]** More recently, Therus Corp of Seattle has developed a system to seal blood vessels after the vessels have been punctured to insert sheaths and catheters. The Therus system shrinks and seals femoral artery punctures at a depth of approximately 5 cm.

**[0014]** In addition, Timi-3 Systems, Inc. has developed and is testing a trans-thoracic ultrasound energy delivery system to accelerate the thrombolysis process for patients suffering an acute myocardial infarction. This system delivers energy at a frequency intended to accelerate thrombolysis without damaging the myocardium or vasculature of the heart.

**[0015]** Epicor Medical, Inc. of Sunnyvale, CA, has developed a localized high intensity focused ultrasound ("HIFU") device to create lesions in the atrial walls. The Epicor device is a hand-held intraoperative surgical device, and is configured to be held directly against the epicardium or outside wall of the heart. When energized, the device creates full-thickness lesions through the atrial wall of the heart, and has demonstrated that ultrasound energy may be safely and effectively used to create atrial lesions, despite presence of blood flow past the interior wall of the atrium.

**[0016]** In addition, Transurgical, Inc., Setauket, NY has been actively developing HIFU devices. However, while the Epicor Medical devices are placed in close approximation against the outside of the heart, the Transurgical devices are directed to intravascular catheters for ablating tissue in the heart by bringing the catheter into close approximation with the targeted tissue.

**[0017]** In view of the aforementioned limitations, it would be desirable to provide methods and apparatus for treating atrial fibrillation and other conduction defects by ablating tissue at a distance from that tissue, so that the procedure may be performed non-invasively.

**[0018]** It also would be desirable to provide methods and apparatus for treating atrial fibrillation by applying energy from outside the body or from organs, such as the esophagus, that are easily accessible via natural body openings.

#### Summary of the Invention

**[0019]** In view of the foregoing, it is an object of a disclosed example to provide methods and apparatus for

treating atrial fibrillation and other conduction defects by ablating tissue at a distance from that tissue, so that the procedure may be performed noninvasively.

**[0020]** It is another object of a disclosed example to <sup>5</sup> provide methods and apparatus for treating cardiac dysfunction by applying energy from outside the body or from neighboring organs, such as the esophagus, that are easily accessible.

**[0021]** These and other objects of the disclosed example(s) are accomplished by providing methods and apparatus that enable a physician to image tissue within the body that is to be ablated, and then to ablate that tissue using a completely or relatively non-invasive procedure, and with little or no anesthesia.

<sup>15</sup> [0022] According to an aspect of the present invention there is provided an apparatus for intraluminally treating atrial fibrillation according to the appended claims.
 [0023] Advantageously, the apparatus of the present

invention is expected to be cost-effective and to perform
 time efficient compared to the previously-known surgical

#### Brief Description of the Drawings

and interventional procedures.

<sup>25</sup> [0024] The above and other objects and advantages of the present invention will be apparent upon consideration of the following detailed description, taken in conjunction with the accompanying drawings, in which like reference characters refer to like parts throughout, and
 <sup>30</sup> in which:

FIG. 1 is a schematic view of an illustrative imaging and treatment ultrasound sound system according to a disclosed example;

FIG. 2 is a schematic view of an illustrative display of the imaging and treatment ultrasound sound system;

FIG. 3 is a schematic view showing the imaging and treatment ultrasound sound system of FIG. 1 disposed adjacent to a cross-section of a patient's thorax; and

FIG. 4 is a schematic view of the distal region of a catheter-based high intensity focused ultrasound array according to the invention.

#### Detailed Description of the Invention

the heart wall from a greater distance.

**[0025]** The present disclosure is directed to methods and apparatus for creating lesions in the walls of the heart in a completely non-invasive manner using high intensity focused ultrasound (HIFU). Previously-known HIFU systems, such as those being developed by Epicor Medical or Transurgical, require close approximation of the HIFU device to the target tissue. The methods and apparatus of the present disclosure overcome this drawback by providing a system that enables the creation of lesions in

[0026] Referring to FIG. 1, an apparatus constructed

35

40

45

50

in accordance with a disclosed example is described. System 10 comprises head 11 housing ultrasound imaging system 12 and high intensity focused ultrasound energy ("HIFU") system 14. Ultrasound imaging system 12 and HIFU system 14 may have in common all or just a subset of the transducers and related components, operating in different modes to image or ablate. Head 11 is mounted on arm 13 that permits the head to be positioned in contact with a patient (not shown) lying on table 15. Head 11 may also be a handheld unit, not needing an arm 13 to support or position it. System 10 includes controller 16 that controls operation of imaging system 12 and HIFU system 14. Monitor 18 displays images output by imaging system 12 that allows the clinician to identify the desired locations on the walls of the heart to be treated.

**[0027]** Controller 16 and monitor 18 also are programmed to indicate the focus of the HIFU energy relative to the image of the tissue cross-section. FIG. 2 is illustrative screen display 19 of monitor 18 showing the outline T of the tissue, as imaged by imaging system 12, and a marker corresponding to the location of focal point F of HIFU system 14.

**[0028]** When activated, the HIFU system delivers ablative energy to the specific location shown on monitor 18 (focal point F in FIG. 2), thus enabling safe creation of transmural lesions. Because the HIFU system is configured to deliver energy from a number of sources focused towards the target tissue area, intervening tissue is subjected to only a fraction of the energy deposited in the target tissue receives, and thus the intervening tissue is not significantly heated or ablated.

**[0029]** Still referring to FIG. 1, ultrasound imaging system 12 may be similar in design to previously-known trans-thoracic ultrasound imaging systems, and are per se known. High intensity focused ultrasound system 14 may comprise one or more HIFU generators 20 constructed as described in U. S. Patent Application No. US20010031922A1.

As mentioned before, imaging system 12 and HIFU system 14 may also use the same elements. Preferably, each HIFU generator 20 is the same as or is disposed approximately in the same plane as the imaging elements of ultrasound imaging system 12, so that the focus of HIFU system 14 occurs in the plane of the target tissue imaged by ultrasound imaging system 12. In addition, this arrangement advantageously ensures that the HIFU energy will reach the target.

**[0030]** In a preferred disclosed example, HIFU generators 20 deliver energy at a frequency optimized for creating lesions in myocardium, to thereby interrupt conduction pathways through the tissue without reducing the strength of the tissue. Once the lesions are created, a gradual healing process is begun in which the lesions fibrose, but do not fall apart or regain the ability to conduct electrical impulses.

**[0031]** While it may be possible to image and ablate simultaneously, it is possible that the output of HIFU sys-

tem 14 may block the ability to image the tissue using ultrasound imaging system 12. Accordingly, controller 16 may be programmed to time-gate operation of imaging system 12 and HIFU system 14, so that the tissue is alternately imaged and ablated at a frequency of several

times per second. [0032] In order to create linear lesions in the wall of the atria of the heart, it may be desirable to slowly move the focus of the HIFU system along the wall of the atrium

<sup>10</sup> during the ablation process. While this may be accomplished by manually moving the HIFU system, for example, for treating relatively short lesions that encircle each or all of the pulmonary veins. Controller 16 may include suitable programming and joystick 22, or other input de-

vice, for refocusing the focal point of HIFU system 14 along a desired trajectory.Referring now to FIG. 3, a further alternative for using

HIFU system to create linear lesions is described. In the system shown in FIG. 3 the focus of the HIFU system is
fixed at a certain point within the field of the ultrasound image. For example, the ultrasound image might show a picture of rectangular planar cross-section of tissue approximately 80 mm wide and 160 mm deep, with a fixed focus of the HIFU energy at a depth of 130 mm in the center of the field.

[0033] In operation, the clinician manually moves the probe until the desired tissue is in the target area, and then fires the HIFU system to ablate the tissue. With such a system the depth of maximal ablation is 130 mm below
<sup>30</sup> the skin. In order to ablate tissue located less than 130 mm below the skin and still retain a continuous fluid path from the probe to the target, the HIFU system includes fluid-filled balloon 24 that covers the face of the probe. Balloon 24 preferably is filled with water and enables the
<sup>35</sup> clinician to reposition the probe at a variable distance from the skin. Balloon 24 also permits the clinician to position the probe at any desired angle to target tissue

not aligned directly under the focal point of HIFU system 14. Alternatively, the patient could sit in a tub of water, so the patient's chest and the probe were both underwater, again ensuring a continuous fluid path. [0034] As a further alternative, controller 16 may be

programmed so that the depth of the focal point of the HIFU system is depth-adjustable relative to the imaged

<sup>45</sup> tissue. Advantageously, the depth of the targeted tissue could then be adjusted relative to the imaged field, so a smaller fluid-filled balloon, or no balloon, is used to maintain fluid contact while adjusting the angle of the imaged section or make minor changes in the depth of the tar-

50 geted tissue. WIPO Patent Publication No. WO/0145550A2 to Therus describes several ways to adjust the depth of the focused energy by changing the radius of curvature of one or more of the ultrasound generators.

<sup>55</sup> Alternatively, the direction of several focused energy generators of relatively fixed focal length could be shifted relative to one another to move the focal point.

[0035] In accordance with a disclosed example, fo-

cused energy is applied from outside the patient's body. Because ultrasound energy does not travel coherently through non-fluid filled tissue, such as the lungs, positioning of the ultrasound imaging system and HIFU system at certain angles may be more advantageous for treatment of specific areas of the heart. For example, the posterior wall of the left atrium is a particularly important treatment area for treating atrial fibrillation; it is also a peculiarly difficult area to image with trans-thoracic ultrasound.

**[0036]** Accordingly, it may be desirable to locate the imaging system and HIFU system on a movable arm or to position it by hand so as to permit other external approaches, such as from below the diaphragm on the left anterior side of the body, so the ultrasound has a coherent path through the diaphragm and apex and ventricles of the heart to the atria. Application of the probe to a patient's back also may provide a coherent path to the posterior wall of the patient's left atrium.

**[0037]** It is expected that the system and methods of the disclosed example also may be useful for treating a number of cardiac dysfunctions. Apart from treatment of atrial fibrillation, the methods and apparatus also may be used to treat other electrophysiologic defects of the heart, or to create lesions for other purposes. For example, if transmyocardial revascularization (TMR) is believed to have a positive effect on damaged ventricles by causing focal areas of damage and healing, such lesions may be created non-invasively using the methods and system of the disclosed example.

**[0038]** As another example, localized tissue damage and the consequent healing process may cause the septum primum and septum secundum of a patent foramen ovale (PFO) to heal together, closing the PFO. If the system and methods are effective in closing PFO even a small percentage of the time, the non-invasive nature of the procedure might have it the first choice for use an initial therapy in most cases.

**[0039]** In addition, the HIFU system described hereinabove also may be used to repair diseased heart valves, by shrinking tissue in certain areas. For example, specific areas of elongated chordae of a mitral valve leaflet may be shortened by heating using the external HIFU.

**[0040]** While in the preferred disclosed example described hereinabove energy is delivered from outside the body, situations may arise where it is difficult to deliver the energy to locations deep inside the body or locations adjacent to the lungs or other non-ultrasound-conductive tissue.

**[0041]** Referring now to FIG. 4, methods and apparatus are provided for positioning a probe inside the body and closer to the targeted tissue, but still not necessarily adjacent to it. Intraluminal probe 30 is configured to deliver HIFU energy to the heart from the esophagus, from the aorta, or from the great veins of the heart such as the inferior vena cava, superior vena cava, or the right atrium itself.

[0042] This approach is fundamentally different from

previously-known methods of performing ablation during surgical procedures using epicardial probes or during interventional procedures using intracardiac ablation catheters. These previously-known devices are designed to

- <sup>5</sup> be in direct contact or at least very close proximity (e.g., within 5 mm) of the target tissue, and are not designed to avoid ablation of intervening tissue between the probe and the target tissue.
- **[0043]** In addition, previously-known devices are capable of making only a single lesion from a given position, rather than forming a number of lesions at a distance from a device from a single location. Making multiple lesions from a single catheter position advantageously may save time and reduce the cost of the procedure. For ex-

<sup>15</sup> ample, approximating a surgical maze procedure using previously-known intracardiac catheters typically takes from four to eight hours, and subject both the patient and physician to high levels of radiation from the fluoroscope. By contrast, a device constructed in accordance with the

20 principles of the present invention, under ultrasound imaging guidance, could create multiple lesions while disposed at a single position in the esophagus, aorta, or great veins or right atrium.

[0044] Still referring to FIG. 4, intraluminal catheter 30
is designed to image and deliver HIFU energy from body lumens such as the esophagus, aorta, and great veins. Catheter 30 preferably has a diameter in a range of 5 to 10 mm for vascular devices, and a diameter in a range of 5 to 20 mm for an esophageal device. Imaging elements 32 and HIFU elements 34 are arranged linearly along the longitudinal axis of the catheter.

**[0045]** The linear nature of the imaging element and HIFU element array may impose limitations on the ability to reposition the device. While translation and rotation of the catheter may be relatively easy, it is contemplated that it may be difficult to move the device very far to one side or another within a relatively small-diameter body

lumen.
[0046] Accordingly, intraluminal catheter 30 preferably
is configured to adjust the focal point of the HIFU system with respect to both longitudinal position and depth. This may be accomplished by programming the controller used with intraluminal catheter 30 to adjust the focal point of the HIFU system, as described above.

 <sup>45</sup> Alternatively, refocusing of the array of HIFU elements may be achieved by locating individual HIFU elements on independently steerable actuators 36. Actuators 36 are controlled by the system controller and permit the clinician to move the focal point of the HIFU array to any
 <sup>50</sup> desired point in the field of view of the imaging system.

[0047] Methods of using intraluminal catheter 30 to perform ablation from the esophagus to treat atrial fibrillation are described. The esophagus is separated from the center of the posterior left atrial wall only by the oblique pericardial sinus, so a linear vertical lesion may be easily made in the center of the posterior left atrial wall using a probe capable of delivering energy at a distance of approximately 5-10 mm.

**[0048]** Such methods are believed to offer substantial advantages with respect to ease of use, and may be effective in treating a high percentage of atrial fibrillation patients. These methods also may obviate the need to contract significant areas of the posterior wall of the left atrium, as typically happens when broad encircling lesions are made around the pulmonary veins.

**[0049]** In accordance with this aspect, one or more vertical ablation lines are formed in the posterior wall of the left atrium using intraluminal catheter 30 disposed within the esophagus. It is expected that formation of straight ablation lines vertically in the posterior wall of the atrium, under ultrasound imaging guidance from the esophagus, may also be easier than making encircling ablation lines around the pulmonary veins.

**[0050]** The foregoing methods of creating lesions are consistent with the underlying concept of the maze procedure as invented by Dr. James Cox in the early 1990s. His research in mapping the depolarization waves in patients with atrial fibrillation showed that dysfunction arose from waves recirculating around the atria. This recirculation is enabled by slightly damaged tissue, which slows the progress of the depolarization wave, and enlargement of the atria due to damage, valve dysfunction, or congestive heart failure.

**[0051]** The maze concept relies on the creation of numerous dead-end pathways in the atria, so the depolarization wave reaches all of the atrial walls, but cannot recirculate. A series of vertical ablation lines in the posterior wall of the left atrium, extending from the atrioventricular groove up to above the superior pulmonary veins would accomplish exactly this goal.

**[0052]** Preferably, the ablation lines extend all the way down to the atrioventricular groove. This allows the depolarization wave to reach that tissue from the dome of the left atrium (the more cranial and anterior surface) but not to progress back to the rest of the atrial wall along the atrioventricular groove.

**[0053]** As described above, intraluminal catheter 30 preferably is configured, either mechanically or by suitable software algorithms, to move its focal point longitudinally to enable a continuous linear ablation without moving the device. Alternatively, the HIFU array of the catheter may be configured to create a linear ablation, or have a fixed-focus so that a linear ablation may be created by translating the HIFU array within the esophagus.

[0054] Further, additional lesions may be made closer to the left and right pulmonary veins. More preferably, lesions could be made on the opposite sides of the left and right pulmonary veins, i.e., to the left of the left pulmonary veins and to the right of the right pulmonary veins. Alternatively, and depending on the geometry of the HIFU probe, it may be more desirable to make encircling lesions in the left and right pulmonary veins using the same vertical motion.

**[0055]** In addition, it may be beneficial to cool tissue surrounding the HIFU array of intraluminal catheter 30,

to further reduce the risk of damage to the esophagus. Intraluminal catheter 30 may therefore include a water jacket that circulates fluid around the HIFU array to prevent any heat generated by the array or ultrasound energy absorbed by the esophagus from causing any tissue damage.

**[0056]** The methods and apparatus also may be beneficially applied to other applications besides cardiac dysfunction. For example, the apparatus of the present in-

10 vention may be used, disposed in small body lumens, nearly anywhere a radiofrequency ablation probe is currently being used to ablate or shrink tissue. Such treatments include treating the prostate from the urethra, tightening up the bladder neck from inside the vagina, ablating

<sup>15</sup> fibroid masses from inside the uterus, tightening up the tissue in the area of the gastroesophageal junction, and so on.

Likewise, the external device described with respect to FIG. 1 may be beneficially used to ablate tumors almost

<sup>20</sup> anywhere in the body that is accessible to focused ultrasound.

**[0057]** Although preferred illustrative embodiments of the present invention are described above, it will be evident to one skilled in the art that various changes and modifications may be made without departing from the invention.

#### Claims

25

30

**1.** Apparatus for intraluminally treating atrial fibrillation, the apparatus comprising:

a catheter (30) configured to deliver high intensity focused ultrasound (HIFU) energy to the heart from a position in the esophagus, from the aorta, or from the great veins of the heart such as the inferior vena cava, superior cava or the right atrium itself;

an ultrasound imaging system (12) disposed at a distal portion within the catheter (30);

a high intensity focused ultrasound (HIFU) system (14) disposed within the catheter (30) in alignment with the ultrasound imaging system (12), said high intensity focused ultrasound (HI-FU) system (14) including a linear array of high intensity focused ultrasound (HIFU) elements (34) located on independently steerable actuators (36) configured to create multiple lesions from a single said position, wherein the linear array of high intensity focused ultrasound (HI-FU) elements (34) is arranged along a longitudinal axis of the catheter; and

a controller (16) operably connected to the ultrasound imaging system (12) and high intensity focused ultrasound (HIFU) system (14) to control said steerable actuators (36), with said controller (16) programmable to adjust the focal

10

15

20

25

30

point of the high intensity focused ultrasound (HIFU) system (14) to any point in the field of view of said imaging system (12) to create said lesions in a target tissue by delivering energy from a number of high intensity focused ultrasound (HIFU) elements (34) without significantly heating or ablating intervening tissue.

- **2.** The apparatus of claim 1, wherein the catheter (30) is suitable for location in the esophagus and has a diameter in the range of 5 mm to 20 mm.
- **3.** The apparatus of claim 1, wherein the catheter (30) is configured for intraluminal vascular positioning and has a diameter in the range of 5 mm to 10 mm.
- **4.** The apparatus of claim 1, 2, or 3, wherein the ultrasound imaging system (12) and the high intensity focused ultrasound (HIFU) system (14) comprise common components or common transducers.
- **5.** The apparatus of claim 1, 2, 3, or 4, wherein the controller (16) is programmed to display a marker corresponding to a focal point of the high intensity focused ultrasound (HIFU) system (14).
- 6. The apparatus of claim 5, wherein the controller (16) is programmed to adjust a location of the focal point of the high intensity focused ultrasound (HIFU) system (14) within a two-dimensional plane orthogonal to an axis of the high intensity focused ultrasound (HIFU) system (14).
- The apparatus of claim 5, wherein the controller (16) is programmed to adjust a location of a depth of the <sup>35</sup> focal point of the high intensity focused ultrasound (HIFU) system (14).
- The apparatus of any of claims 1 to 7, wherein the high intensity focused ultrasound (HIFU) system (14) <sup>40</sup> is configured to focus along a linear ablation target in the atrial wall.
- The apparatus of claim 8, wherein the controller (16) is programmed to adjust the focal point of the high <sup>45</sup> intensity focused ultrasound (HIFU) system (14) with respect to both longitudinal position and depth.
- 10. The apparatus of claim 9, wherein the controller (16) is further programmed to control the high intensity focused ultrasound (HIFU) system (14) to make a linear vertical lesion in the center of the posterior left atrial wall from a position in the esophagus.
- The apparatus of claim 10, wherein the controller 55 (16) is programmed to control the high intensity fo-cused ultrasound (HIFU) system (14) to form plural vertical ablation lines in the posterior wall of the left

atrium.

- **12.** The apparatus of any of claims 1 to 8, further comprising a water jacket circulating fluid around the high intensity focused ultrasound (HIFU) array to prevent any heat generated by the high intensity focused ultrasound (HIFU) array from causing any tissue damage.
- **13.** The apparatus of claim 12, wherein the circulated fluid prevents ultrasound energy absorbed by the esophagus, the aorta, or the great veins of the heart such as the inferior vena cava, superior cava or the right atrium itself from causing any tissue damage.
- 14. The apparatus of any preceding claim, wherein the high intensity focused ultrasound (HIFU) system (14) is adapted to deliver ablative energy to a specific location to create transmural lesions.

#### Patentansprüche

1. Gerät für die intraluminale Behandlung von Vorhofflimmern, wobei das Gerät aufweist:

> einen Katheter (30), der ausgebildet ist, um dem Herzen eine hochintensive, fokussierte Ultraschallenergie (HIFU-Energie) von einer Position in der Speiseröhre, von der Aorta oder von den großen Venen des Herzens aus zuzuführen, wie beispielsweise der inferioren Vena cava, der Cava superior oder der rechten Herzvorkammer selbst;

ein Ultraschallabbildungssystem (12), das in einem distalen Abschnitt innerhalb des Katheters (30) angeordnet ist;

ein hochintensives, fokussiertes Ultraschallsystem (HIFU-System) (14), das innerhalb des Katheters (30) in Ausrichtung mit dem Ultraschallabbildungssystem (12) angeordnet ist, wobei das hochintensive, fokussierte Ultraschallsystem (HIFU-System) (14) eine lineare Anordnung von hochintensiven, fokussierten Ultraschallelementen (HIFU-Elementen) (34) umfasst, die an unabhängig steuerbaren Betätigungselementen (36) angeordnet sind, die ausgebildet sind, um mehrfache Verletzungen von einer einzelnen Position aus zu bewirken, wobei die lineare Anordnung der hochintensiven, fokussierten Ultraschallelemente (HIFU-Elemente) (34) entlang einer Längsachse des Katheters angeordnet ist; und

einen Regler (16), der funktionell mit dem Ultraschallabbildungssystem (12) und dem hochintensiven, fokussierten Ultraschallsystem (HIFU-System) (14) verbunden ist, um die steuerbaren Betätigungselemente (36) zu steuern, wobei der

10

15

25

30

35

40

45

Regler (16) programmierbar ist, um den Fokus des hochintensiven, fokussierten Ultraschallsystems (HIFU-Systems) (14) auf einen beliebigen Punkt im Sichtfeld des Abbildungssystems (12) einzustellen, um die Verletzungen in einem Zielgewebe zu bewirken, indem Energie von einer Anzahl von hochintensiven, fokussierten Ultraschallelementen (HIFU-Elementen) (34) ohne bedeutende Erwärmung oder operative Entfernung von dazwischenliegendem Gewebe zugeführt wird.

- 2. Gerät nach Anspruch 1, bei dem der Katheter (30) für eine Anordnung in der Speiseröhre geeignet ist und einen Durchmesser im Bereich von 5 mm bis 20 mm aufweist.
- Gerät nach Anspruch 1, bei dem der Katheter (30) für eine intraluminale vaskuläre Positionierung ausgebildet ist und einen Durchmesser im Bereich von 20 5 mm bis 10 mm aufweist.
- Gerät nach Anspruch 1, 2 oder 3, bei dem das Ultraschallabbildungssystem (12) und das hochintensive, fokussierte Ultraschallsystem (HIFU-System) (14) gemeinsame Bauteile oder gemeinsame Wandler aufweisen.
- Gerät nach Anspruch 1, 2, 3 oder 4, bei dem der Regler (16) programmiert ist, um eine Markierung entsprechend einem Fokus des hochintensiven, fokussierten Ultraschallsystems (HIFU-Systems) (14) anzuzeigen.
- Gerät nach Anspruch 5, bei dem Regler (16) programmiert ist, um eine Stelle des Fokus des hochintensiven, fokussierten Ultraschallsystems (HIFU-Systems) (14) innerhalb einer zweidimensionalen Ebene einzustellen, die orthogonal zu einer Achse des hochintensiven, fokussierten Ultraschallsystems (HIFU-Systems) (14) ist.
- Gerät nach Anspruch 5, bei dem der Regler (16) programmiert ist, um eine Stelle einer Tiefe des Fokus des hochintensiven, fokussierten Ultraschallsystems (HIFU-Systems) (14) einzustellen.
- Gerät nach einem der Ansprüche 1 bis 7, bei dem das hochintensive, fokussierte Ultraschallsystem (HIFU-System) (14) ausgebildet ist, um längs eines linearen Ablationsziels in der Vorhofwand zu fokussieren.
- Gerät nach Anspruch 8, bei dem der Regler (16) programmiert ist, um den Fokus des hochintensiven, <sup>55</sup> fokussierten Ultraschallsystems (HIFU-Systems) (14) mit Bezugnahme auf sowohl die Längsposition als auch die Tiefe einzustellen.

- 10. Gerät nach Anspruch 9, bei dem der Regler (16) außerdem programmiert ist, um das hochintensive, fokussierte Ultraschallsystem (HIFU-System) (14) zu steuern, um eine lineare vertikale Verletzung in der Mitte der posterioren linken Vorhofwand von einer Position in der Speiseröhre aus zu bewirken.
- **11.** Gerät nach Anspruch 10, bei dem der Regler (16) programmiert ist, um das hochintensive, fokussierte Ultraschallsystem (HIFU-System) (14) zu steuern, um mehrere vertikale Ablationslinien in der posterioren Wand der linken Herzvorkammer zu bilden.
- 12. Gerät nach einem der Ansprüche 1 bis 8, das außerdem einen Wassermantel aufweist, der Fluid um die hochintensive, fokussierte Ultraschallanordnung (HIFU-Anordnung) zirkulieren lässt, um zu verhindern, dass jegliche Wärme, die durch die hochintensive, fokussierte Ultraschallanordnung (HIFU-Anordnung) erzeugt wird, eine Gewebebeschädigung hervorruft.
- 13. Gerät nach Anspruch 12, bei dem das zirkulierende Fluid verhindert, dass Ultraschallenergie, die von der Speiseröhre, der Aorta oder den großen Venen des Herzens absorbiert wird, wie beispielsweise der inferioren Vena cava, der Cava superior oder der rechten Herzvorkammer selbst, eine Gewebebeschädigung hervorruft.
- 14. Gerät nach einem der vorhergehenden Ansprüche, bei dem das hochintensive, fokussierte Ultraschallsystem (HIFU-System) (14) ausgebildet ist, um eine ablative Energie einer spezifischen Stelle zuzuführen, um transmurale Verletzungen zu bewirken.

#### Revendications

1. Appareil permettant de traiter de manière intraluminale une fibrillation auriculaire, l'appareil comprenant :

> un cathéter (30) configuré pour fournir une énergie d'ultrasons focalisés de haute intensité (HI-FU) au coeur à partir d'un emplacement situé dans l'oesophage, à partir de l'aorte, ou à partir des grandes veines du coeur telles que la veine cave inférieure, la veine cave supérieure ou de oreillette droite proprement dite ;

un système d'imagerie par ultrasons (12) agencé au niveau d'une partie distale au sein du cathéter (30) ;

un système (14) à ultrasons focalisés de haute intensité (HIFU) agencé au sein du cathéter (30) en alignement avec le système d'imagerie par ultrasons (12), ledit système (14) à ultrasons focalisés de haute intensité (HIFU) comprenant

10

15

20

30

35

40

45

50

un réseau linéaire d'éléments (34) à ultrasons focalisés de haute intensité (HIFU) situés sur des actionneurs (36), orientables de manière indépendante, configurés pour créer des lésions multiples à partir d'un emplacement unique, dans lequel le réseau linéaire d'éléments (34) à ultrasons focalisés de haute intensité (HIFU) est agencé le long d'un axe longitudinal du cathéter ; et

un dispositif de commande (16) raccordé de manière fonctionnelle au système d'imagerie par ultrasons (12) et au système (14) à ultrasons focalisés de haute intensité (HIFU) afin de commander lesdits actionneurs (36) orientables, ledit dispositif de commande (16) pouvant être programmé pour ajuster le point focal du système (14) à ultrasons focalisés de haute intensité (HIFU) sur un point quelconque du champ de vision dudit système d'imagerie (12) afin de créer lesdites lésions dans un tissu cible en fournissant de l'énergie à partir d'un certain nombre d'éléments (34) à ultrasons focalisés de haute intensité (HIFU) sans chauffage ou ablation significative de tissus interposés.

- Appareil selon la revendication 1, dans lequel le cathéter (30) convient pour un emplacement situé dans l'oesophage et présente un diamètre dans la plage de 5 mm à 20 mm.
- Appareil selon la revendication 1, dans lequel le cathéter (30) est configuré pour un positionnement vasculaire intraluminal et présente un diamètre dans la plage de 5 mm à 10mm.
- 4. Appareil selon la revendication 1, 2 ou 3, dans lequel le système d'imagerie par ultrasons (12) et le système (14) à ultrasons focalisés de haute intensité (HI-FU) comprennent des composants communs ou des transducteurs communs.
- Appareil selon la revendication 1, 2, 3, ou 4, dans lequel le dispositif de commande (16) est programmé pour afficher un repère correspondant à un point focal du système (14) à ultrasons focalisés de haute intensité (HIFU).
- 6. Appareil selon la revendication 5, dans lequel le dispositif de commande (16) est programmé pour ajuster un emplacement du point focal du système (14) à ultrasons focalisés de haute intensité (HIFU) au sein d'un plan bidimensionnel orthogonal par rapport à un axe du système (14) à ultrasons focalisés de haute intensité (HIFU).
- Appareil selon la revendication 5, dans lequel le dispositif de commande (16) est programmé pour ajuster un emplacement d'une profondeur du point focal

du système (14) à ultrasons focalisés de haute intensité (HIFU).

- Appareil selon l'une quelconque des revendications 1 à 7, dans lequel le système (14) à ultrasons focalisés de haute intensité (HIFU) est configuré pour se focaliser le long d'une cible d'ablation linéaire dans la paroi auriculaire.
- 9. Appareil selon la revendication 8, dans lequel le dispositif de commande (16) est programmé pour ajuster le point focal du système (14) à ultrasons focalisés de haute intensité (HIFU) par rapport à la fois à la position longitudinale et à la profondeur.
- 10. Appareil selon la revendication 9, dans lequel le dispositif de commande (16) est en outre programmé pour commander le système (14) à ultrasons focalisés de haute intensité (HIFU) afin de créer une lésion verticale linéaire au centre de la paroi auriculaire postérieure gauche à partir d'un emplacement situé dans l'oesophage.
- 11. Appareil selon la revendication 10, dans lequel le dispositif de commande (16) est programmé pour commander le système (14) à ultrasons focalisés de haute intensité (HIFU) afin de former plusieurs lignes d'ablation verticales dans la paroi postérieure de l'oreillette gauche.
  - 12. Appareil selon l'une quelconque des revendications 1 à 8, comprenant en outre une chemise d'eau faisant circuler un fluide autour du réseau d'ultrasons focalisés de haute intensité (HIFU) afin d'empêcher toute chaleur générée par le réseau d'ultrasons focalisés de haute intensité (HIFU) de provoquer un quelconque dommage tissulaire.
  - **13.** Appareil selon la revendication 12, dans lequel le fluide en circulation empêche l'énergie ultrasonore absorbée par l'oesophage, l'aorte, ou les grandes veines du coeur telles que la veine cave inférieure, la veine cave supérieure ou l'oreillette droite proprement dite de provoquer un quelconque dommage tissulaire.
  - 14. Appareil selon l'une quelconque des revendications précédentes, dans lequel le système (14) à ultrasons focalisés de haute intensité (HIFU) est conçu pour fournir une énergie d'ablation vers un emplacement spécifique afin de créer des lésions transmurales.



FIG. I





FIG. 2





### **REFERENCES CITED IN THE DESCRIPTION**

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

#### Patent documents cited in the description

- US 5391140 A [0002]
- FR 2827149 [0003]
- US 5817021 A [0004]
- WO 0182778 A [0005]

- GB 2267035 A [0006]
- WO 8907909 A [0007]
- US 20010031922 A1 [0029]
- WO 0145550 A2 [0034]

# patsnap

| 专利名称(译)        | 使用高强度聚焦超声治疗心房颤动的装置   |         |            |  |  |
|----------------|--|---------|------------|--|--|
| 公开(公告)号        | EP1633266B1  | 公开(公告)日 | 2016-05-18 |  |  |
| 申请号            | EP2004754905   | 申请日     | 2004-06-09 |  |  |
| [标]申请(专利权)人(译) | 铸造公司   |         |            |  |  |
| 申请(专利权)人(译)    | 代工,INC.  |         |            |  |  |
| 当前申请(专利权)人(译)  | ▲) 铸造有限责任公司  |         |            |  |  |
| [标]发明人         | GIFFORD HANSON S   |         |            |  |  |
| 发明人            | GIFFORD, HANSON, S.  |         |            |  |  |
| IPC分类号         | A61N7/02 A61B8/12 A61B90/00 A61B A61B17/00 A61B18/04 A61B18/18 A61N7/00                              |         |            |  |  |
| CPC分类号         | A61N7/02 A61B8/0883 A61B8/12 A61B8/4488 A61B2017/00243 A61B2018/00351 A61B2090/3782<br>A61N2007/0078 |         |            |  |  |
| 代理机构(译)        | SHANKS , ANDREW  |         |            |  |  |
| 优先权            | 60/477532 2003-06-10 US  |         |            |  |  |
| 其他公开文献         | 术 EP1633266A4<br>EP1633266A2   |         |            |  |  |
| 外部链接           | Espacenet  |         |            |  |  |

摘要(译)

提供了使医生能够对要消融的身体内的组织进行成像,然后使用具有超 声成像系统和对准的高强度聚焦超声系统的设备对组织进行消融的方法 和装置。

