

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
13 October 2005 (13.10.2005)

PCT

(10) International Publication Number
WO 2005/094689 A1

(51) International Patent Classification⁷: A61B 8/12

(21) International Application Number:

PCT/IB2005/050984

(22) International Filing Date: 22 March 2005 (22.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/559,321 2 April 2004 (02.04.2004) US

(71) Applicant (for all designated States except US): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): BECKER, David [US/US]; P.O. Box 3003, Bothell, WA 98041-3003 (US). WRAY, Terry [US/US]; P.O. Box 3003, Bothell, WA 98041-3003 (US). HART, Jeffrey [US/US]; P.O. Box 3003, Bothell, WA 98041-3003 (US).


(74) Common Representative: KONINKLIJKE PHILIPS ELECTRONICS N.V.; c/o W. Brinton Yorks, Jr., P.O. Box 3003, Bothell, WA 98041-3003 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: ULTRASONIC INTRACAVITY PROBE FOR 3D IMAGING



WO 2005/094689 A1

(57) Abstract: An intracavity ultrasound probe includes a pivotally mounted array transducer which is oscillated to scan a volumetric region from within the body. The transducer is oscillated by a motor located in the probe handle. The array transducer is immersed in a liquid which acoustically couples ultrasonic energy between the elements of the transducer and the body. The acoustic coupling liquid is located in the distal tip of the probe shaft, where only 6 cc of liquid is required. The small amount of liquid reduces the weight of the shaft of the probe so that the center of gravity of the probe is in the handle, making the probe comfortable and easy to manipulate. The majority of parts in the probe shaft are made of aluminum or other low density materials, keeping the overall weight of the probe to about 250 grams.

**Declaration under Rule 4.17:**

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM,

AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Published:

- with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

ULTRASONIC INTRACAVITY PROBE FOR 3D IMAGING

5 This invention relates to medical diagnostic imaging systems and, in particular, to intracavity probes for three dimensional imaging for ultrasonic diagnostic imaging systems.

10 Intracavity ultrasound probes have been in use for many years for imaging the body from within the body. By imaging from within the body internal organs can be imaged more directly without the need to transmit ultrasound waves through intervening tissue and body structure. For example, transesophageal probes can image the heart and abdominal organs from the esophagus or stomach and 15 avoid the need to send and receive ultrasound through or around the ribs. The present invention relates to intracavity probes inserted in the vagina (IVT probes) or rectum (ICT probes) to image the cervix, uterus, or prostate.

20 In the past, IVT and ICT probes have scanned a two dimensional image region from within the body. This could be done with an array transducer or oscillating single crystal transducer which would scan a sector-shaped area of the body. By curving 25 the elements of an array transducer completely around the distal tip region of the probe, sectors approximating 180° could be scanned. A typical IVT intracavity probe 10 is shown in FIGURE 1. This probe includes a shaft portion 12 of about 6.6 inches 30 (16.7 cm) in length and one inch in diameter which is inserted into a body cavity. The ultrasound transducer is located in the distal tip 14 of the shaft. The probe is grasped and manipulated by a handle 16 during use. At the end of the handle is a 35 strain relief 18 for a cable 20 which extend about 3-

7 feet and terminates at a connector 22 which couples the probe to an ultrasound system. A typical IVT probe may have a shaft and handle which is 12 inches in length and weigh about 48 ounces (150 grams) including the cable 20 and the connector 22.

5 In recent years ultrasound systems have been introduced with three dimensional (3D) imaging capability and intracavity probes have been designed to perform 3D imaging. Generally this is done by
10 replacing the array transducer which is statically affixed in the distal tip with an array transducer which can be oscillated rapidly in the elevation direction. This oscillation will sweep the image plane being scanned through a volumetric region,
15 acquiring multiple adjacent planar images which can be rendered into a three dimensional image. However, as was the case with earlier oscillating single crystal or annular array transducers, the oscillating array transducer of the 3D probe must be contained
20 within a fluid through which it can oscillate and which is highly transmissive of ultrasound.
Generally this fluid will be a water or oil-based solution such as a mineral oil. The fluid is
25 preferably biocompatible so as not to injure or irritate the tissues of the patient in the event of leakage.

30 These mechanically oscillating 3D array probes will generally house the motor for the oscillation drive within the handle of the probe, thereby keeping it outside the body of the patient. This motor location then mandates a fluid compartment for the oscillating mechanism and transducer which extends through most of or all of the shaft and distal tip of the probe. The fluid will comprise a large portion
35 of the weight of the probe which is located in the

shaft of the probe, causing the center of gravity of the probe to be forward of the handle and in the shaft of the probe. This imbalance makes the intracavity probe unwieldy and difficult to 5 manipulate easily. It would be desirable to reduce the forward weight and balance of the probe so that the 3D intracavity probe is easier to manipulate during a diagnostic procedure.

10 In accordance with the principles of the present invention a 3D intracavity probe includes an array transducer in the distal tip which is swept to scan a volumetric region. The array transducer is swept by motor which is located in the handle of the probe. The array transducer is contained within a fluid 15 chamber located at the distal tip of the probe and requiring less than 10 cc of fluid. As a result, the center of gravity of the shaft and handle is located in the handle and not the shaft, making the probe easier and more comfortable to hold and manipulate 20 during use.

25 In accordance with further aspects of the present invention, the array transducer is mounted on an array mount made of a low mass material and displacing space within the chamber which otherwise would be filled with fluid, thereby reducing the fluid volume of the chamber. The shaft and shaft components, except for critical wear surfaces of the array drive mechanism, are also made of low mass materials such as plastics and aluminum. 30 Accordingly, the weight of the probe is less than two-thirds of the weight of prior art 3D intracavity probes.

35 In the drawings:

FIGURE 1 illustrates a typical intracavity ultrasound probe of the prior art.

FIGURE 2 illustrates a side view of an intracavity probe for three dimensional imaging of the present invention.

5 FIGURE 3 is a side cross-sectional view of a 3D intracavity probe of the present invention.

FIGURE 4 is a perspective view of the tip assembly of a 3D intracavity probe of the present invention.

Referring now to FIGURE 2, an intracavity ultrasound probe 30 of the present invention is shown. The probe 30 includes a handle section 36 by which the user holds the handle for manipulation during use. At the rear of the handle is a strain relief 18 for the probe cable (not shown). Extending from the forward end of the handle 36 is the shaft 32 of the probe which terminates in a dome-shaped acoustic window 34 at the distal end through which ultrasound is transmitted and received during imaging. Contained within the distal end of the shaft is a transducer mount assembly 40 which is also shown in the cross-sectional view of the shaft of FIGURE 3 and in the uncovered view of FIGURE 4. A convex curved array transducer 46 is attached to a transducer cradle 48 at the distal end of the assembly 40. The transducer cradle 48 is pivotally mounted by its pivot axis 49 to be rocked back and forth in the distal end of the probe and thereby sweep an image plane through a volumetric region in front of the probe. The transducer cradle 48 is rocked by an oscillating drive shaft 50 which extends from a motor and position sensor 60 in the handle 36 to the transducer mount assembly 40. The drive shaft 50 extends through an isolation tube 52 in the shaft which serves to isolate the moving drive shaft from the electrical conductors and volume compensation

balloon 44 located in the shaft proximal the transducer mount assembly 40. The drive shaft 50 rocks the cradle by means of two mating bevel gears 54, one at the end of the drive shaft 50 and another 5 on the transducer cradle 48. The motor alternately drives the drive shaft 50 in one direction of rotation and then the other, which alternately rocks the transducer cradle 48 in one direction and then the other, which sweeps the image plane of the 10 transducer array 46 back and forth through the volumetric region in front of the distal end of the probe. The echo signals acquired by the transducer array 46 are beamformed, detected, and rendered by the ultrasound system to form a three dimensional 15 image of the volumetric region scanned by the probe.

Because ultrasonic energy does not efficiently pass through air, the array transducer 46 is surrounded by a liquid which is transmissive of ultrasound and closely matches the acoustic impedance 20 of the body which is approximately that of water. Water-based, oil-based, and synthetic polymeric liquids may be used. In a constructed embodiment silicone oil is used. In accordance with the principles of the present invention, only a small 25 amount of liquid is required in the shaft 32 because the weight of the liquid can contribute significantly to the overall weight of the shaft. In some prior art probes the entire shaft is filled with liquid, adding substantial weight to the shaft and causing 30 the center of gravity of the handle and shaft to be located in the shaft. Other prior art probes have used sizeable elastomeric bags of liquid for the liquid bath of the transducer array. These 35 embodiments also locate the center of gravity of the probe in the shaft, which makes the probe ungainly

and difficult to maneuver easily. The liquid used in such embodiments can approach 50 cc, for instance, adding its weight to the probe shaft at the distal end.

5 In accordance with the principles of the present invention the majority of the liquid bath for the transducer array is contained within the transducer mount assembly 40. The only liquid located to the rear of the back surface 42 of the transducer mount assembly 40 (see FIGURE 2) is the small amount of the volume compensation balloon 44. In a constructed embodiment the total amount of liquid in the shaft of the probe is 6.3 cc, of which 95% is contained within the transducer mount assembly 40. Only 0.3 cc of
10 liquid is contained within the volume compensation balloon 44, which can be kept to a small volume of liquid due to the low overall volume of liquid. In the constructed embodiment the length of the shaft 32 was 7.5 inches from the handle to the distal tip
15 (dimension A in FIGURE 2). The transducer mount assembly 40 is contained within the distal 1.5 inches of that length (dimension B in FIGURE 2). Thus, there is only 6 cc of liquid in the forward half of the probe shaft 32, and only 6.3 cc of liquid in the
20 entire shaft. Ninety-five percent of the liquid is in close proximity to the transducer array, located as it is in the distal 20% of the probe shaft. With so little liquid in the shaft and so little liquid in the forward half of the probe shaft, and the motor located in the handle, the center of gravity 62 of
25 the probe handle and shaft is located in the handle, a full inch behind the handle/shaft interface (dimension C in FIGURE 2). With the center of gravity located in the handle the probe is much
30 easier and more comfortable to manipulate during use.
35

In addition to the small amount of fluid needed in the forward section of the shaft, the embodiment of FIGURES 3 and 4 employ additional measures to reduce the amount of liquid and the weight of the probe shaft 32. Only critical wear surfaces within the shaft 32, such as the drive shaft 50, the gears 54, and pivot points for the transducer cradle are made of stainless steel. Selected fasteners and fittings are also made of stainless steel. Other components within the shaft are made of lighter materials with a density lighter than that of stainless steel. The transducer cradle 48 is made of three pieces of aluminum and is tapered on the sides which are the leading edges as the cradle travels through the liquid. The tapering on either side causes the cradle to move more easily through the liquid with less resistance. The space behind the transducer array and backing is not hollow but is filled so as to displace volume that would otherwise be occupied by liquid, further reducing the liquid needed in the distal end of the probe. The main body of the transducer mount assembly 40 is also made of aluminum, as is the isolation tube 52. The volume compensation balloon 44 is made of a thin plastic. The transducer array and its backing are made of material customarily used for those purposes such as piezoelectric ceramic and epoxy. This use of lightweight materials enables a constructed embodiment of the present invention including the probe shaft and handle to weigh only 250 grams, compared to the 400 gram weights of prior art probes.

WHAT IS CLAIMED IS:

1. 1. An ultrasonic intracavity probe for scanning a volumetric region from within the body comprising:

5 a handle section to be held during use of the probe; and

10 a shaft section having a distal end which is to be inserted into a body cavity during use of the probe;

a pivotally mounted array transducer located in the distal end of the shaft section;

a motor located in the handle section;

15 a drive mechanism coupled to the motor and the array transducer which acts to move the array transducer during scanning; and

20 a liquid bath located in the distal end of the shaft, a portion of which is located between the array transducer and the distal end of the shaft during scanning,

wherein the center of gravity of the probe is located in the handle section.

2. The ultrasonic intracavity probe of Claim 1, further comprising a transducer mount assembly located in the distal end of the shaft section, the array transducer being pivotally mounted to the transducer mount assembly,

25 30 wherein the liquid bath is located within the transducer mount assembly.

3. The ultrasonic intracavity probe of Claim 2, wherein the transducer mount assembly has a proximal termination within three inches of the distal end of the shaft section,

wherein 75% of the liquid bath is contained within the transducer mount assembly.

4. The ultrasonic intracavity probe of Claim 5, wherein the transducer mount assembly has a proximal termination within one and one-half inches of the distal end of the shaft section.

5. The ultrasonic intracavity probe of Claim 10, wherein 90% of the liquid bath is contained within the transducer mount assembly.

6. The ultrasonic intracavity probe of Claim 15, wherein the liquid bath has a volume of less than 25 cc of liquid.

7. The ultrasonic intracavity probe of Claim 20, wherein the liquid bath has a volume of less than 10 cc of liquid.

8. The ultrasonic intracavity probe of Claim 7, wherein the liquid bath has a volume of approximately 6 cc of liquid.

25 9. The ultrasonic intracavity probe of Claim 1, wherein 90% of the liquid bath is located in the most distal 25% of the length of the shaft section.

30 10. The ultrasonic intracavity probe of Claim 9, wherein the liquid bath has a volume of less than 10 cc of liquid.

35 11. The ultrasonic intracavity probe of Claim 1, further comprising a transducer mount assembly having a main body and located in the distal end of

the shaft section, the array transducer being pivotally mounted to the transducer mount assembly, the main body of the transducer mount assembly being formed of a material which is lighter than stainless steel.

12. The ultrasonic intracavity probe of Claim 11, wherein the array transducer is pivotally mounted to the transducer mount assembly by a transducer cradle,

wherein the transducer cradle is made of a material which is lighter than stainless steel.

13. The ultrasonic intracavity probe of Claim 12, wherein the transducer cradle includes a solid body located behind the array transducer which displaces volume in the transducer mount assembly that would otherwise be occupied by liquid.

14. The ultrasonic intracavity probe of Claim 12, wherein the transducer cradle is tapered so as to pass more easily through the liquid bath.

15. The ultrasonic intracavity probe of Claim 11, wherein the transducer mount assembly includes wear surfaces which made of stainless steel.

16. The ultrasonic intracavity probe of Claim 15, wherein the wear surfaces are part of the drive mechanism.

17. The ultrasonic intracavity probe of Claim 11, wherein the weight of the probe is less than 400 grams.

18. The ultrasonic intracavity probe of Claim 17, wherein the weight of the probe is less than 300 grams.

5 19. The ultrasonic intracavity probe of Claim 18, wherein the weight of the probe is approximately 250 grams.

10 20. The ultrasonic intracavity probe of Claim 18, wherein the only components of the shaft which are made of a material at least equal to the density of stainless steel are components of the drive mechanism.

1/3




FIG. 1




FIG. 2




FIG. 3

3/3




FIG. 4

INTERNATIONAL SEARCH REPORT

PCT/IB2005/050984

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61B8/12

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category ^o	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6 592 520 B1 (PESZYNSKI MICHAEL ET AL) 15 July 2003 (2003-07-15) column 7, line 55 - column 12, line 24; figures 1,2,2A,4A -----	1
A	PATENT ABSTRACTS OF JAPAN vol. 2003, no. 12, 5 December 2003 (2003-12-05) -& JP 2003 230568 A (OLYMPUS OPTICAL CO LTD), 19 August 2003 (2003-08-19) abstract -----	1
A	US 5 090 414 A (TAKANO ET AL) 25 February 1992 (1992-02-25) column 3, line 66 - column 6, line 8; figures 1,2 ----- -/-	1

 Further documents are listed in the continuation of box C. Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

28 June 2005

Date of mailing of the international search report

06/07/2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl
Fax: (+31-70) 340-3016

Authorized officer

Artikis, T

INTERNATIONAL SEARCH REPORT

PCT/IB2005/050984

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 740 804 A (CEROFOLINI ET AL) 21 April 1998 (1998-04-21) column 5, line 18 - column 7, line 56; figures 1,3,6 -----	1
A	DE 44 20 220 A1 (SCHNORRENBERG, ARNO, 13086 BERLIN, DE) 21 December 1995 (1995-12-21) column 2, line 9 - column 4, line 29; figure 1 -----	1

INTERNATIONAL SEARCH REPORT

PCT/IB2005/050984

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
US 6592520	B1	15-07-2003	NONE	
JP 2003230568	A	19-08-2003	NONE	
US 5090414	A	25-02-1992	JP 1867291 C JP 2055050 A JP 5078344 B	26-08-1994 23-02-1990 28-10-1993
US 5740804	A	21-04-1998	NONE	
DE 4420220	A1	21-12-1995	NONE	

专利名称(译)	超声腔内探头用于三维成像		
公开(公告)号	EP1742580A1	公开(公告)日	2007-01-17
申请号	EP2005718545	申请日	2005-03-22
[标]申请(专利权)人(译)	皇家飞利浦电子股份有限公司		
申请(专利权)人(译)	皇家飞利浦电子N.V.		
当前申请(专利权)人(译)	皇家飞利浦N.V.		
[标]发明人	BECKER DAVID WRAY TERRY HART JEFFREY		
发明人	BECKER, DAVID WRAY, TERRY HART, JEFFREY		
IPC分类号	A61B8/12		
CPC分类号	A61B8/4461 A61B8/12 A61B8/4281 A61B8/445 A61B8/483		
优先权	60/559321 2004-04-02 US		
其他公开文献	EP1742580B1		
外部链接	Espacenet		

摘要(译)

腔内超声探头包括枢转安装的阵列换能器，其被振荡以从身体内扫描体积区域。换能器由位于探头手柄中的电机振荡。阵列换能器浸没在液体中，该液体在换能器的元件和主体之间声学地耦合超声能量。声耦合液体位于探针轴的远端尖端，其中仅需要6cc的液体。少量液体减少了探头轴的重量，使得探头的重心位于手柄中，使探头舒适且易于操作。探头轴中的大部分部件由铝或其他低密度材料制成，使探头的总重量保持在约250克。