



(11) **EP 2 444 002 B1**

(12) **EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention of the grant of the patent:
13.06.2018 Bulletin 2018/24

(51) Int Cl.:
A61B 8/08 (2006.01) G06F 19/00 (2018.01)

(21) Application number: **11182839.8**

(22) Date of filing: **27.09.2011**

(54) **3D ultrasound system for intuitive displaying an abnormality of a fetus and method for operating 3D ultrasound system**

3D-Ultraschallsystem zur intuitiven Anzeige von Abnormalitäten eines Fötus und Betriebsverfahren für das 3D-Ultraschallsystem

Systèmes à ultrasons 3D pour l'affichage intuitif visant les anomalies d'un foetus et procédé d'exploitation du système à ultrasons 3D

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

(30) Priority: **22.10.2010 KR 20100103448**

(43) Date of publication of application:
25.04.2012 Bulletin 2012/17

(73) Proprietor: **Samsung Medison Co., Ltd.**
Nam-myun
Hongchun-gun
Kangwon do 250-875 (KR)

(72) Inventor: **Hyun, Dong Gyu**
Gyeonggi-do (KR)

(74) Representative: **Markfort, Iris-Anne Lucie**
Lorenz & Kollegen
Patentanwälte Partnerschaftsgesellschaft mbB
Alte Ulmer Straße 2
89522 Heidenheim (DE)

(56) References cited:
WO-A2-2009/136332 KR-A- 20080 004 775
US-A1- 2007 073 147

- **PANDYA ET AL: "Screening for fetal trisomies by maternal age and fetal nuchal translucency thickness at 10 to 14 weeks of gestation.", BRITISH JOURNAL OF OBSTETRICS AND GYNAECOLOGY, vol. 102, no. 12, 1 December 1995 (1995-12-01), pages 957-962, XP55015665, ISSN: 0306-5456**
- **"First-Trimester Risk Assessment", , 1 January 2006 (2006-01-01), XP55015666, Retrieved from the Internet:
URL:http://www.gehealthcare.com/usen/ultrasound/education/docs/TRImester_CSpages.pdf [retrieved on 2012-01-04]**
- **Jeffrey M Braithwaite ET AL: "Nuchal translucency measurements: frequency distribution and changes with gestation in a general population", British Journal of Obstetrics and Gynaecology, 1 December 1996 (1996-12-01), pages 1201-1204, XP55015667, Retrieved from the Internet:
URL:<http://onlinelibrary.wiley.com/store/10.1111/j.1471-0528.1996.tb09629.x/asset/j.1471-0528.1996.tb09629.x.pdf?v=1&t=gwyxvf7j&s=4ae18c3f6b20dfa834d6c60bfe4ecc057cd61406> [retrieved on 2012-01-04]**
- **J. MORATALLA ET AL: "Semi-automated system for measurement of nuchal translucency thickness", ULTRASOUND IN OBSTETRICS AND GYNECOLOGY, vol. 36, no. 4, 1 October 2010 (2010-10-01), pages 412-416, XP55015669, ISSN: 0960-7692, DOI: 10.1002/uog.7737**

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 2 444 002 B1

Description

CROSS-REFERENCE TO RELATED PATENT APPLICATION

[0001] This application claims the benefit of Korean Patent Application No. 10-2010-0103448, filed on October 22, 2010, in the Korean Intellectual Property Office, the disclosure of which is incorporated herein in its entirety by reference.

BACKGROUND

[0002] The present invention relates to a method for intuitively checking the abnormality of an object.

[0003] Ultrasound systems transmit ultrasound signals from a surface of a human body or an animal body towards a predetermined part within the body (i.e., an object such as a fetus or internal organ) and use information about ultrasound signals reflected from a tissue within the body to obtain images related to a cross-section of a soft tissue or blood flow. Due to its compact and cheap design, real-time display, and high stability with no risk of exposure to X-rays or other radiations, such an ultrasound system has been widely used together with other image diagnostic devices such as an X-ray diagnostic device, a Computerized Tomography (CT) scanner, a Magnetic Resonance Image (MRI) device, and a nuclear medicine diagnostic device,

[0004] A common method for detecting a fetus with Down syndrome is to measure the thickness of a nuchal translucency (NT) in the fetus using an ultrasound system. According to this method that was devised by Nicolaides in 1992, if it is determined that a fetus has any abnormality, an NT thickness has increased due to subcutaneous accumulation of fluid at the back of a fetal neck.

[0005] In particular, a fetus with Down syndrome or other chromosomal abnormalities, or heart defects may usually have an increased NT. Thus, when a doctor measures the thickness of a translucent space behind a fetal neck using an ultrasound system and finds that the thickness of the translucent space exceeds 2.5 mm, a more accurate test, such as chorionic villus sampling or amniocentesis, is performed to see whether a fetus has an abnormality.

[0006] However, this approach has a problem that it is difficult to accurately measure the thickness of an NT because it may vary depending on an angle or measurement method. Thus, a doctor is inconvenienced in having to check whether an actual NT thickness is greater than 2.5 mm for each test before making conclusions about the abnormality of a fetus.

SUMMARY

[0007] The invention is defined by the appended claims. All other embodiments are merely exemplary.

The present invention provides a three-dimensional (3D) ultrasound system and a method for operating the 3D ultrasound system, which are capable of intuitively displaying the abnormality of an object by generating measurement data using ultrasound data relating to the object, comparing the measurement data with reference data, and controlling a color of the measurement data according to the comparison result.

[0008] The present invention also provides a 3D ultrasound system and a method for operating the 3D ultrasound system, which allow a more intuitive display of the degree of severity of an abnormality in an object by displaying measurement data in different colors that are allocated depending on whether a Nuchal Translucency (NT) thickness measured on the object is in an abnormal, warning, or normal range.

[0009] According to an aspect of the present invention, there is provided a 3D ultrasound system with the features of claim 1, including: a scanning unit configured to scan an object and generate ultrasound data; a measuring unit configured to receive an input of a measurement point in the ultrasound data and generate measurement data associated with the measurement point; and a display controller configured to compare the measurement data with reference data, determine one of an abnormal grade, a warning grade and a normal grade, and display the measurement data based on the determined grade, wherein if the object is a fetus and the measurement point is an input around a Nuchal Translucency (NT) of the fetus, the measuring unit is configured to generate two measurement lines corresponding to the NT of the fetus, measure the distance between the two measurement lines as the measured length of the NT and generate measurement data including the measured length, wherein the reference data include a measurement statistical distribution for each of ages based on number of fetuses according to NT lengths, wherein the display controller is configured to analyze an age of the fetus based on the ultrasound data, extract from a plurality of standard length ranges in the reference data a first standard length range corresponding to the age that is obtained from the analysis, compare the first standard length range with the measured length in the measurement data and determine the grade. According to the invention, if the determined grade is the 'warning grade', the display controller is configured to display the measurement data by adjusting a luminance of a color allocated to the warning grade based on a distance between the point and one of abnormal and normal intervals within the measurement statistical distribution data for the measurement point.

[0010] The display controller may be configured to display the measurement data in a color allocated to the determined grade.

[0011] Furthermore, the measuring unit may be configured to generate two measurement lines corresponding to the NT of the fetus, measure the distance between the two measurement lines as the measured length of the NT and generate measurement data including the

measured length.

[0012] The 3D ultrasound system may further include an alarm output unit configured to output an alarm if the point is in one of abnormal and warning intervals within the measurement statistical distribution and determined to correspond to one of the abnormal and warning grades.

[0013] According to another aspect of the present invention, there is provided a method for operating a 3D ultrasound system with the features of claim 4, including: scanning an object and generating ultrasound data; receiving an input of a measurement point from the ultrasound data and generating measurement data associated with the measurement point; comparing the measurement data with selected reference data and determining one of an abnormal grade, a warning grade and a normal grade; and displaying the measurement data based on the determined grade, wherein if the object is a fetus and the measurement point is an input around a Nuchal Translucency (NT) of the fetus, the generating of the measurement data associated with the measurement point comprises generating two measurement lines corresponding to the NT of the fetus, measuring the distance between the two measurement lines as the measured length of the NT and generating measurement data including the measured length, wherein the reference data include a measurement statistical distribution for each of ages based on number of fetuses according to NT lengths, and wherein the displaying of the measurement data based on the determined grade comprises: analyzing an age of the fetus based on the ultrasound data; extracting from a plurality of standard length ranges in the reference data a first standard length range corresponding to the age that is obtained from the analysis; comparing the first standard length range with the measured length in the measurement data and, if the determined grade is the 'warning grade', displaying the measurement data by adjusting a luminance of a color allocated to the warning grade based on a distance between the point and one of abnormal and normal intervals within the measurement statistical distribution data for the measurement point.

[0014] The 3D ultrasound system and the method for operating the 3D ultrasound system are capable of intuitively displaying the abnormality of an object by generating measurement data using ultrasound data relating to the object, comparing the measurement data with reference data, and controlling a color of the measurement data based on the comparison result.

[0015] According to an embodiment of the present invention, measurement data is displayed in different colors that are allocated depending on whether an NT thickness measured with respect to the object is in an abnormal, warning, or normal range, thereby allowing more intuitive display of the degree of severity according to the presence of abnormality in the object.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] The above and other features and advantages of the present invention will become more apparent by describing in detail exemplary embodiments thereof with reference to the attached drawings in which:

FIG. 1 illustrates an internal configuration of a three-dimensional (3D) ultrasound system according to an embodiment of the present invention;

FIG. 2 illustrates an example of an ROI when an object is a fetus;

FIG. 3 illustrates an example of displaying measurement data obtained from an object;

FIG. 4 illustrates an example of reference data including a measurement statistical distribution; and
FIG. 5 is a flowchart illustrating a method for operating a 3D ultrasound system of FIG. 1, according to an embodiment of the present invention.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0017] Hereinafter, embodiments of the present invention will be described in detail with reference to the attached drawings. In the drawings, like reference numerals refer to like elements.

[0018] FIG. 1 illustrates an internal configuration of a three-dimensional (3D) ultrasound system 100 according to an embodiment of the present invention.

[0019] Referring to FIG. 1, the 3D ultrasound system 100 includes a scanning unit, a measuring unit 120, a display controller 130, an alarm output unit 140, and a database 150.

[0020] The scanning unit 110 scans an object to generate ultrasound data. More specifically, the scanning unit 110 generates ultrasound data including image data obtained by scanning the object within a human body or an animal body. The object within the human body or the animal body may be a fetus and its internal organs. In other words, the scanning unit 110 generates ultrasound data by scanning the fetus and its internal organs.

[0021] In order to generate ultrasound data for an object, the scanning unit 110 may set a region of interest (ROI) on the object and locates a seed in the ROI. The seed may be set by an observer. Otherwise, the seed may be automatically set based on the ROI.

[0022] When the object is a fetus, the seed may be located near a Nuchal Translucency (NT) of the fetus. Thereafter, the scanning unit 110 performs a 3D ultrasound scan on the object to generate image data such that the ultrasound data may be generated. The image data corresponds to a region in the ultrasound data occupied by the object.

[0023] The measuring unit 120 receives an input of a measurement point from the ultrasound data and generates measurement data associated with the measurement point. In this case, the measurement point may be interpreted as a 'seed'.

[0024] FIG. 2 illustrates an example of an ROI when an object is a fetus.

[0025] Referring to FIGS. 1 and 2, when the object is a 'fetus', the measuring unit 120 may receive as an input a measurement point + around an NT of the fetus. The measuring unit 120 may generate two measurement lines 10, 20 corresponding to the NT of the fetus around the measurement point +. The measuring unit 120 may measure a distance between the two measurement lines 10, 20 as a measured length ML of the NT.

[0026] The two measurement lines 10, 20 may be generated by various methods. For one example, the measuring unit 120 may recognize the NT of the fetus around the measurement point + based on the characteristics of the fetal NT, and generate the two measurement lines 10, 20 corresponding to the fetal NT. In this case, the measuring unit 120 can recognize the fetal NT based on brightness difference of pixels around the measurement point +.

[0027] For another example, an observer, e.g., a doctor, may input positions of the two measurement lines 10, 20 to generate the two measurement lines 10, 20.

[0028] However, a method for obtaining the measured length ML according to FIG. 2 is an example, and the measured length ML of the NT may be measured by various methods.

[0029] In this case, the measuring unit 120 generates measurement data including the measured length ML.

[0030] A common method for detecting a fetus with Down syndrome is to measure the thickness of an NT of a fetus. A fetus having Down syndrome or other chromosomal abnormalities, or heart defects may usually have a thick NT. Thus, when a doctor measures the thickness of a translucent space behind a fetal neck using an ultrasound system and finds that the thickness of the translucent space is greater than 2.5 mm, a more accurate test such as chorionic villus sampling or amniocentesis is performed to check whether a fetus has an abnormality.

[0031] However, because an NT thickness used in detecting a fetus with Down syndrome varies depending on the age of a fetus, it is necessary to set a standard length range for future use so as to determine whether a fetus has an abnormality by comparing a measured length obtained by measuring an actual object with a standard length range.

[0032] The display controller 130 compares the measurement data with reference data to determine a grade and displays the measurement data based on the determined grade. For example, the reference data may contain a standard NT length range for each fetal age. In other words, the reference data may include a plurality of standard length ranges one to one corresponding to the fetal ages.

[0033] The display controller 130 analyzes an age of the fetus, extracts from the reference data a standard length range corresponding to the age which is obtained from the analysis, and compares the standard length range with the measured length ML in the measurement

data. The display controller 130 then determines a grade depending on whether the measured length ML is less or greater than the standard length range, and displays the measurement data in a color that is allocated to the determined grade.

[0034] FIG. 3 illustrates an example of displaying measurement data obtained from an object.

[0035] Referring to FIGS. 1 through 3, when a measured length ML in measurement data is included in a standard length range extracted from reference data for the age of an object, e.g., a fetus, the display controller 130 displays the measurement data (MaxNT 0.18 cm) around a measurement point + in a green color image 210. The measured length ML that is included in the standard length range may indicate that the fetus corresponds to a 'normal grade'.

[0036] When the measured length ML is greater than the standard length range extracted from reference data, the display controller 130 displays the measurement data (MaxNT 0.25 cm) around the measurement point + in a red color image 220. The measured length ML that is greater than the standard length range may indicate that the fetus has Down syndrome and corresponds to an 'abnormal grade'. Thus, the display controller 130 may display the measurement data (MaxNT 0.25 cm) in the red color image 220 so that a doctor may intuitively check for the abnormality of the fetus, thereby allowing a doctor to easily recognize the severity of the abnormality of the fetus.

[0037] Conversely, when the measured length ML is less than the standard length range extracted from reference data, the display controller 130 displays the measurement data (MaxNT 0.08 cm) around the measurement point + in a yellow color image 230. The measured length ML that is less than the standard length range may indicate that the fetus corresponds to a 'warning grade'.

[0038] When the fetus is determined to correspond to the 'abnormal grade' or the 'warning grade', the alarm output unit 140 outputs an alarm.

[0039] In order to facilitate the detection of a fetus having Down syndrome, the 3D ultrasound system 100 needs to have reference data to compare with measurement data for future use. The reference data may contain a measurement statistical distribution for the measurement point. A doctor uses statistical data created from many years of experience and experimental values to obtain standard NT length ranges for each age level.

[0040] For example, the doctor may create statistical data using ultrasound data obtained from fetuses for each age level and compare ultrasound data obtained from a fetus with statistical data in order to determine the age of the fetus. The statistical data and the reference data may be stored in the database 150.

[0041] For example, the database 150 may contain reference data and statistical data for each age level.

[0042] FIG. 4 illustrates an example of reference data including a measurement statistical distribution.

[0043] Referring to FIGS. 1, 2 and 4, the reference data includes the measurement statistical distributions for each of ages where an x-axis represents an NT length and a y-axis represents the number of objects (fetuses). The measurement statistical distributions may vary depending on ages 310 and 320. In other words, although numeric values are not described in detail in FIG. 4, an NT length may vary depending on ages.

[0044] Thus, the display controller 130 analyzes the age of the fetus based on the ultrasound data, extracts reference data corresponding to the determined age from the database 150, and compares a standard length range in the extracted reference data with a measured length ML in the measurement data.

[0045] In one embodiment, the display controller 130 checks a point in the measurement statistical distribution at which the measurement data, e.g., the measured length ML, is located and determines one of an abnormal grade, a warning grade, and a normal grade. When the point is in a normal interval (including the largest number of objects) within the measurement statistical distribution and the fetus is determined to correspond to a normal grade, the display controller 130 may display the measurement data in 'green'.

[0046] When the point is in a warning interval (including an increasing or decreasing number of objects) within the measurement statistical distribution and the fetus is determined to correspond to a warning grade, the display controller 130 may display the measurement data in 'yellow'.

[0047] When the point is in an abnormal interval (with the smallest number of objects) within the measurement statistical distribution and the fetus is determined to correspond to an abnormal grade, the display controller 130 may display the measurement data in 'red'.

[0048] Furthermore, when the point is in the warning interval and the fetus is determined to correspond to the 'warning grade', the display controller 130 may display the measurement data by adjusting the luminance of the color allocated to the warning grade based on a distance between the point and one of abnormal and normal intervals within the measurement statistical distribution. In other words, when the point is located at a position in the warning interval that is closer to one of the normal and abnormal intervals, the display controller 130 may display the measurement data in different colors such as dark or light yellow.

[0049] When the point is in an abnormal or warning interval within the measurement statistical distribution and determined to correspond to the abnormal or warning grade, the alarm output unit 140 outputs an alarm.

[0050] FIG. 5 is a flowchart illustrating a method for operating the 3D ultrasound system 100 of FIG. 1, according to an embodiment of the present invention.

[0051] Referring to FIGS. 1, 2 and 5, in operation 410, the 3D ultrasound system 100 scans an object to generate ultrasound data. More specifically, the 3D ultrasound system 100 scans a fetus and its internal organs as an

object to obtain image data and generates ultrasound data including the obtained image data.

[0052] In operation 420, the 3D ultrasound system 100 receives an input of a measurement point + in the ultrasound data and generates measurement data associated with the measurement point +. For example, if the object is a fetus and the measurement point + is input with respect to an NT of the fetus, the 3D ultrasound system 100 measures a measured length ML of the NT based on the measurement point + and generates measurement data including the measured length ML.

[0053] In operation 430, the 3D ultrasound system 100 compares the measurement data with reference data to determine a grade and displays the measurement data based on the determined grade. In other words, the 3D ultrasound system 100 may display the measurement data in a color allocated for the determined grade.

[0054] In one embodiment, the reference data may contain standard NT lengths for each of ages. The 3D ultrasound system 100 analyzes the age of the fetus based on the ultrasound data, extracts from the reference data a standard length range corresponding to the age which is obtained from the analysis, and compares the standard length range with the a measured length ML in the measurement data. The age of the fetus may be analyzed by comparing statistical data stored in the database 150 with the ultrasound data. The 3D ultrasound system 100 determines a grade depending on whether the measured length ML is less or greater than the standard length range and displays the measurement data in a color that is allocated to the determined grade.

[0055] Alternatively, if the reference data contains a measurement statistical distribution for the measurement point +, the 3D ultrasound system 100 may check a point in the measurement statistical distribution at which the measurement data is located and determine one of an abnormal grade, a warning grade, and a normal grade. The 3D ultrasound system 100 may then display the measurement data in one of red, yellow and green colors that is allocated for the determined grade.

[0056] For example, if the point is in the warning interval within the measurement statistical distribution and is determined to correspond to the 'warning grade', the 3D ultrasound system 100 may display the measurement data by adjusting the luminance of the color allocated to the warning grade based on a distance between the point and one of the abnormal and normal intervals within the measurement statistical distribution.

[0057] Alternatively, if the point is in the abnormal or warning interval within the measurement statistical distribution and is determined to correspond to the abnormal or warning grade, the 3D ultrasound system 100 may output an alarm.

[0058] Embodiments can include a computer readable medium including program commands for executing operations implemented through various computers. The computer readable medium can store program commands, data files, data structures or combinations there-

of. The program commands recorded in the medium may be specially designed and configured for the present invention or be known to those skilled in the field of computer software. Examples of a computer readable recording medium include magnetic media such as hard disks, floppy disks and magnetic tapes, optical media such as CD-ROMs and DVDs, magneto-optical media such as floptical disks, or hardware devices such as ROMs, RAMs and flash memories, which are specially configured to store and execute program commands. Examples of the program commands include a machine language code created by a compiler and a high-level language code executable by a computer using an interpreter and the like.

Claims

1. A three-dimensional (3D) ultrasound system comprising:

a scanning unit configured to scan an object and generate ultrasound data;

a measuring unit configured to receive an input of a measurement point in the ultrasound data and generate measurement data associated with the measurement point; and

a display controller configured to compare the measurement data with reference data, determine one of an abnormal grade, a warning grade, and a normal grade, and display the measurement data based on the determined grade,

wherein if the object is a fetus and the measurement point is an input around to a Nuchal Translucency (NT) of the fetus, the measuring unit is configured to generate two measurement lines corresponding to the NT of the fetus, measure the distance between the two measurement lines as the measured length of the NT and generate measurement data including the measured length,

wherein the reference data include a measurement statistical distribution for each of ages based on number of fetuses and NT lengths,

wherein the display controller is configured to analyze an age of the fetus based on the ultrasound data, extract from a plurality of standard length ranges in the reference data a first standard length range corresponding to the age that is obtained from the analysis, compare the first standard length range with the measured length in the measurement data and determine the grade,

wherein if the determined grade is the 'warning grade', the display controller is configured to display the measurement data by adjusting a luminance of a color allocated to the warning grade

based on a distance between the measurement point and one of abnormal and normal intervals within a measurement statistical distribution data for the measurement point.

2. The system of claim 1, wherein the display controller is configured to display the measurement data in a color allocated to the determined grade.

3. The system of claim 1, further comprising an alarm output unit configured to output an alarm if the measurement point is in one of abnormal and warning intervals within the measurement statistical distribution data and determined to correspond to one of the abnormal and warning grades.

4. A method for operating a three-dimensional (3D) ultrasound system, the method comprising:

scanning an object and generating ultrasound data;

receiving an input of a measurement point from the ultrasound data and generating measurement data associated with the measurement point;

comparing the measurement data with reference data and determining one of an abnormal grade, a warning grade, and a normal grade; and displaying the measurement data based on the determined grade,

wherein if the object is a fetus and the measurement point is an input around to a Nuchal Translucency (NT) of the fetus,

the generating of the measurement data associated with the measurement point comprises generating two measurement lines corresponding to the NT of the fetus, measuring the distance between the two measurement lines as the measured length of the NT and generating measurement data including the measured length

wherein the reference data include a measurement statistical distribution for each of ages based on number of fetuses and NT lengths, and wherein the displaying of the measurement data based on the determined grade comprises:

analyzing an age of the fetus based on the ultrasound data,;

extracting from a plurality of standard length ranges in the reference data a first standard length range corresponding to the age that is obtained from the analysis; and

comparing the first standard length range with the measured length in the measurement data,

wherein if the determined grade is the 'warning grade',

displaying the measurement data by adjusting a luminance of a color allocated to the warning grade based on a distance between the measurement point and one of abnormal and normal intervals within a measurement statistical distribution data for the measurement point.

5. The method of claim 4, wherein the displaying of the measurement data based on the determined grade comprises displaying the measurement data in a color allocated to the determined grade.

6. The method of claim 4, further comprising outputting an alarm if the measurement point is in one of abnormal and warning intervals within the measurement statistical distribution data and determined to correspond to one of the abnormal and warning grades.

Patentansprüche

1. Dreidimensionale (3D)-Ultraschallanordnung, aufweisend:

eine Scaneinheit, die dazu ausgebildet ist, ein Objekt zu scannen und Ultraschalldaten zu erzeugen;

eine Messeinheit, die dazu ausgebildet ist, einen Input eines Messpunktes in den Ultraschalldaten zu erhalten und Messdaten zu erzeugen, die mit dem Messpunkt in Verbindung stehen; und

eine Anzeigesteuerung, die dazu ausgebildet ist, die Messdaten mit Referenzdaten zu vergleichen, einen abnormalen Grad, einen Warngrad oder einen normalen Grad zu bestimmen, und die Messdaten basierend auf dem bestimmten Grad anzuzeigen,

wobei dann, wenn das Objekt ein Fötus ist und der Messpunkt ein Input um eine Nackentransparenz (NT) des Fötus ist, die Messeinheit dazu ausgebildet ist, zwei Messlinien zu erzeugen, die der NT des Fötus entsprechen, den Abstand zwischen den zwei Messlinien als die gemessene Länge der NT zu messen und Messdaten zu erzeugen, die die gemessene Länge umfassen, wobei die Referenzdaten eine statistische Verteilung bezüglich einer Messung für jedes Alter basierend auf einer Anzahl von Fetten und NT-Längen umfassen, wobei die Anzeigesteuerung dazu ausgebildet ist, ein Alter des Fötus basierend auf den Ultraschalldaten zu analysieren, aus einer Vielzahl von standardisierten Längenbereichen in den Referenzdaten einen ersten Standardlängenbereich zu extrahieren, der dem Alter entspricht, das von der Analyse erhalten

wurde, den ersten Standardlängenbereich mit der gemessenen Länge in den Messdaten zu vergleichen und den Grad zu bestimmen, wobei dann, wenn der bestimmte Grad der "Warngrad" ist, die Anzeigesteuerung dazu ausgebildet ist, die Messdaten durch Anpassung einer Helligkeit einer Farbe anzuzeigen, die dem Warngrad basierend auf einem Abstand zwischen dem Messpunkt und einem abnormalen oder normalen Intervall innerhalb einer statistischen Messdatenverteilung für den Messpunkt zugeordnet ist.

2. Anordnung nach Anspruch 1, wobei die Anzeigesteuerung dazu ausgebildet ist, die Messdaten in einer Farbe anzuzeigen, die dem bestimmten Grad zugeordnet ist.

3. Anordnung nach Anspruch 1, ferner umfassend eine Alarmausgabeeinheit, die dazu ausgebildet ist, einen Alarm auszugeben, wenn der Messpunkt in dem abnormalen oder Warnintervall innerhalb der statistischen Messdatenverteilung ist und wenn bestimmt wurde, dass er dem abnormalen oder Warngrad entspricht.

4. Verfahren zum Betreiben einer dreidimensionalen (3D)-Ultraschallanordnung, wobei das Verfahren aufweist:

Scannen eines Objekts und Erzeugen von Ultraschalldaten;

Erhalten eines Inputs eines Messpunkts von den Ultraschalldaten und Erzeugen von Messdaten, die mit dem Messpunkt in Verbindung stehen;

Vergleichen der Messdaten mit Referenzdaten und Bestimmen eines abnormalen Grades, eines Warngrades oder eines normalen Grades; und

Anzeigen der Messdaten basierend auf dem bestimmten Grad,

wobei dann, wenn das Objekt ein Fötus ist und der Messpunkt ein Input um eine Nackentransparenz (NT) des Fötus ist,

der Schritt des Erzeugens von Messdaten, die mit dem Messpunkt in Verbindung stehen, umfasst: Erzeugen zweier Messlinien, die der NT des Fötus entsprechen, Messen des Abstandes zwischen den zwei Messlinien als die gemessene Länge der NT und Erzeugen von Messdaten, die die gemessene Länge umfassen, wobei die Referenzdaten eine statistische Verteilung bezüglich einer Messung für jedes Alter basierend auf einer Anzahl von Fetten und NT-Längen umfassen, und

wobei der Schritt des Anzeigens der Messdaten basierend auf dem bestimmten Grad aufweist:

Analysieren eines Alters des Fötus basierend auf den Ultraschalldaten;
 Extrahieren aus einer Vielzahl von standardisierten Längenbereichen in den Referenzdaten eines ersten Standardlängenbereichs, der dem Alter entspricht, das von der Analyse erhalten wurde; und
 Vergleichen des ersten Standardlängenbereichs mit der gemessenen Länge in den Messdaten,
 wobei dann, wenn der bestimmte Grad der "Warngrad" ist,
 das Anzeigen der Messdaten durch Anpassung einer Helligkeit einer Farbe erfolgt, die dem Warngrad basierend auf einem Abstand zwischen dem Messpunkt und einem abnormalen oder normalen Intervall innerhalb einer statistischen Messdatenverteilung für den Messpunkt zugeordnet ist.

5. Verfahren nach Anspruch 4, wobei das Anzeigen der Messdaten basierend auf dem bestimmten Grad das Anzeigen der Messdaten in einer Farbe umfasst, die dem bestimmten Grad zugeordnet ist.
6. Verfahren nach Anspruch 4, ferner umfassend: Ausgeben eines Alarms, wenn der Messpunkt in dem abnormalen oder Warnintervall innerhalb der statistischen Messdatenverteilung ist und bestimmt wurde, dass er dem abnormalen oder Warngrad entspricht.

Revendications

1. Système ultrasonique tridimensionnel (3D) comprenant :

une unité de balayage configurée pour scanner un objet et générer des données ultrasoniques ;
 une unité de mesure configurée pour recevoir une donnée d'entrée d'un point de mesure dans les données ultrasoniques et générer des données de mesure associées avec le point de mesure ; et
 un contrôleur d'affichage configuré pour comparer les données de mesure avec des données de référence, déterminer un des degrés anormal, un degré d'alerte, et un degré normal, et afficher les données de mesure basées sur le degré déterminé ;
 dans lequel, si l'objet est un fœtus et le point de mesure est une entrée concernant une Translucidité Nucléique (NT) du fœtus, l'unité de mesure est configurée pour générer deux lignes de mesure correspondant à la NT du fœtus, mesure la distance entre les deux lignes de mesure en tant que longueur mesurée de la NT et génère

des données de mesure incluant la longueur mesurée,
 dans lequel la donnée de référence inclut une mesure de distribution statistique pour chacun des âges basé sur le nombre de fœtus et les longueurs de NT,
 dans lequel le contrôleur d'affichage est configuré pour analyser un âge du fœtus basé sur les données ultrasoniques, extrait d'une pluralité de gammes de longueurs standard dans les données de référence, une première gamme de longueurs standard correspondant à l'âge qui est obtenu par l'analyse, pour comparer la première gamme de longueurs standard avec la longueur mesurée dans les données de mesure et déterminer le degré,
 dans lequel, si le degré déterminé est le degré d'alerte, le contrôleur d'affichage est configuré pour afficher les données de mesure en ajustant une luminosité d'une couleur attribuée au degré d'alerte basé sur une distance entre le point de mesure et un des intervalles anormal et normal dans une distribution de données statistique de mesure pour le point de mesure.

2. Système selon la revendication 1, dans lequel le contrôleur d'affichage est configuré pour afficher la donnée de mesure dans une couleur associée au degré déterminé.
3. Système selon la revendication 1, comprenant en outre une unité de sortie d'alarme configurée pour émettre une alarme si le point de mesure est un des intervalles anormal et d'alerte dans les données de mesures de distribution statistiques et déterminées pour correspondre à un des degrés anormal et d'alerte.
4. Procédé pour utiliser un système ultrasonique tridimensionnel (3D), le procédé comportant :

le balayage d'un objet et la génération de données ultrasoniques ;
 la réception d'une entrée d'un point de mesure des données ultrasoniques et la génération de données de mesure associées avec le point de mesure ;
 la comparaison des données de mesure avec des données de référence et la détermination d'un des degrés anormal, d'un degré d'alerte, et d'un degré normal, et
 l'affichage des données de mesure basées sur le degré déterminé,
 dans lequel, si l'objet est un fœtus et le point de mesure est une entrée concernant une Translucidité Nucléique (NT) du fœtus, la génération des données de mesure associées avec le point de mesure comprend la génération

de deux lignes de mesures correspondant à la (NT) du fœtus, la mesure de la distance entre les deux lignes de mesure en tant que longueur mesurée de la NT et la génération des données de mesure incluant la longueur mesurée dans lequel la donnée de référence inclut une mesure de distribution statistique pour chacun des âges basé sur le nombre de fœtus et de longueurs de NT, et dans lequel l'affichage des données de mesures basées sur degré déterminé comprend :

- l'analyse d'un âge du fœtus basé sur les données ultrasoniques ;
 l'extraction d'une pluralité de gammes de longueurs standard dans les données de référence d'une première gamme de longueurs standard à l'âge qui est obtenu par l'analyse ; et la comparaison la première gamme de longueurs standard avec la longueur mesurée dans les données de mesure, dans lequel, si le degré déterminé est le degré d'alerte, l'affichage des données de mesures en ajustant une luminance d'une couleur attribué au degré d'alerte basé sur une distance entre le point de mesure et l'un des intervalles anormal et normal dans une distribution de données statistiques de mesures pour le point de mesure.
- 5
- 10
- 15
- 20
- 25
- 30
5. Procédé selon la revendication 4, dans lequel l'affichage de la donnée de mesure basée sur le degré déterminé comprend l'affichage de la donnée de mesure dans une couleur attribuée au degré déterminé.
- 35
6. Procédé selon la revendication 4, comprenant en outre l'émission d'une alarme si le point de mesure est un des intervalles anormal et d'alerte dans les données de mesure de distribution statistique et déterminées pour correspondre à un des degrés anormal ou d'alerte.
- 40

45

50

55

FIG. 1




FIG. 2




FIG. 3






FIG. 4






FIG. 5



REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- KR 1020100103448 [0001]

专利名称(译)	用于直观显示胎儿异常的3D超声系统和用于操作3D超声系统的方法		
公开(公告)号	EP2444002B1	公开(公告)日	2018-06-13
申请号	EP2011182839	申请日	2011-09-27
[标]申请(专利权)人(译)	三星麦迪森株式会社		
申请(专利权)人(译)	三星MEDISON CO. , LTD.		
当前申请(专利权)人(译)	三星MEDISON CO. , LTD.		
[标]发明人	HYUN DONG GYU		
发明人	HYUN, DONG GYU		
IPC分类号	A61B8/08 G06F19/00		
CPC分类号	A61B5/1072 A61B8/0866 A61B8/466 A61B8/483 A61B8/5223 A61B2503/02 G01S7/52071 G06F19/321 G06T7/0012 G06T2207/10136 G06T2207/30044 G16H30/20 G16H50/20 G16H50/30 A61B8/461		
优先权	1020100103448 2010-10-22 KR		
其他公开文献	EP2444002A1		
外部链接	Espacenet		

摘要(译)

提供了一种三维 (3D) 超声系统和用于操作3D超声系统的方法，其通过比较通过测量与所述超声数据相关的超声数据获得的测量数据，通过确定等级，能够直观地显示对象的异常。根据确定的等级以不同的方式对象和显示测量数据。在当前的应用中，对象是胎儿，测量数据是NT。

FIG. 1




FIG. 2

