



(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(43) Date of publication:
31.08.2016 Bulletin 2016/35

(51) Int Cl.:
A61B 8/08 (2006.01) A61B 8/12 (2006.01)

(21) Application number: **15833184.3**

(86) International application number:
PCT/JP2015/061632

(22) Date of filing: **15.04.2015**

(87) International publication number:
WO 2016/027508 (25.02.2016 Gazette 2016/08)

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME
Designated Validation States:
MA

(71) Applicant: **Olympus Corporation**
Hachioji-shi
Tokyo 192-8507 (JP)
(72) Inventor: **TSURUTA, Teppei**
Tokyo 192-8507 (JP)
(74) Representative: **Gunzelmann, Rainer**
Wuesthoff & Wuesthoff
Patentanwälte PartG mbB
Schweigerstraße 2
81541 München (DE)


(30) Priority: **22.08.2014 JP 2014169442**

(54) **ULTRASONIC ENDOSCOPE, LIQUID FEEDING DEVICE FOR ULTRASONIC ENDOSCOPE, AND ULTRASONIC ENDOSCOPE SYSTEM**

(57) An ultrasound endoscope capable of obtaining a favorable elastography image by a simple configuration without upsizing a distal end portion is provided. For this purpose, an ultrasound endoscope 2 is configured having an ultrasound probe 17 arranged at a distal end rigid portion 10, an auxiliary water feeding channel opening 24 through which fluid is ejected from a vicinity of the

ultrasound probe 17 in a projecting direction of the ultrasound probe 17, an auxiliary water feeding channel 47 communicating with the auxiliary water feeding channel opening 24, and an adjustment valve 48 for variably adjusting a flow rate of the fluid flowing through the auxiliary water feeding channel 47 among two or more states.

FIG. 3



Description

Technical Field

[0001] The present invention relates to an ultrasound endoscope provided with an ultrasound probe at a distal end of an insertion portion, a liquid feeding apparatus for ultrasound endoscope suitable for the ultrasound endoscope, and an ultrasound endoscope system.

Background Art

[0002] In recent years, elastography for displaying hardness of living tissue has been put to practical use in ultrasound observation using an ultrasound diagnostic apparatus (see, for example, Japanese Patent Application Laid-Open Publication No. 2012-81295 (Patent Literature 1)). In the elastography technique, it is possible to measure change (displacement) of a deformed state of living tissue, for example, by causing a pressing state of an ultrasound probe against an organ, which can be detected by ultrasound, to switch among two or more states, and construct an elastography image from strain obtained by spatially differentiating the displacement.

[0003] Application of such an elastography technique to various ultrasound observation apparatuses is expected. For example, if the elastography technique is applied to an ultrasound endoscope having an ultrasound probe at a distal end of an insertion portion, it is possible to cause a rate of detecting a lesion in a deep organ to be improved.

[0004] In order to detect a lesion by an elastography function, however, it is necessary to perform periodical pressing of the ultrasound probe against tissue in a body cavity, and the like.

[0005] Here, as a method for periodically pressing the ultrasound probe in the body cavity, for example, a method of utilizing beats of a heart is conceivable. However, since change in the pressing state in observation utilizing beats is slight, there is a possibility that it is difficult to acquire a stable and favorable elastography image.

[0006] Further, as the method for periodically pressing the ultrasound probe in the body cavity, for example, a method of a surgeon or the like manually causing the insertion portion to move back and forth is conceivable. However, the insertion portion of an endoscope is generally long, and, furthermore, it has flexibility. Therefore, even if the insertion portion is caused to move back and forth, much of an amount of the movement is absorbed by the flexibility and the like midway. Thus, in this case also, there is a possibility that it is difficult to acquire a stable and favorable elastography image.

[0007] To cope with this, it is conceivable to provide a pressing mechanism for mechanically pressing the body cavity at a distal end portion of the endoscope. However, there is a possibility that providing such a mechanism at the distal end portion brings about upsizing, structure complication and the like of the distal end portion.

[0008] The present invention has been made in view of the above situation, and an object is to provide an ultrasound endoscope making it possible to obtain a favorable elastography image by a simple configuration without causing a distal end portion to be upsized, a liquid feeding apparatus for ultrasound endoscope, and an ultrasound endoscope system.

Disclosure of Invention

Means for Solving the Problem

[0009] An ultrasound endoscope according to an aspect of the present invention includes: an insertion portion configured to be inserted into a subject; a distal end portion arranged at a distal end of the insertion portion; an ultrasound observation portion arranged at the distal end portion; an opening portion enabling fluid to be ejected from a vicinity of the ultrasound observation portion in a projecting direction of the ultrasound observation portion; a fluid conduit communicating with the opening portion; and a first flow rate adjusting portion configured to variably adjust a flow rate of the fluid flowing through the fluid conduit among two or more states.

[0010] A liquid feeding apparatus for ultrasound endoscope according to an aspect of the present invention is a liquid feeding apparatus for ultrasound endoscope suitable for an ultrasound endoscope, the ultrasound endoscope including: an insertion portion configured to be inserted into a subject; a distal end portion arranged at a distal end of the insertion portion; an ultrasound observation portion arranged at the distal end portion; an opening portion enabling fluid to be ejected from a vicinity of the ultrasound observation portion in a projecting direction of the ultrasound observation portion; and a fluid conduit communicating with the opening portion; and the liquid feeding apparatus for ultrasound endoscope includes: a fluid guiding-out portion configured to guide the fluid into the fluid conduit; and a second flow rate adjusting portion configured to variably adjust a flow rate of the fluid guided out from the fluid guiding-out portion among two or more states.

[0011] Further, an ultrasound endoscope system according to an aspect of the present invention is provided with: an ultrasound endoscope including: an insertion portion configured to be inserted into a subject; a distal end portion arranged at a distal end of the insertion portion; an ultrasound observation portion arranged at the distal end portion; an opening portion enabling fluid to be ejected from a vicinity of the ultrasound observation portion in a projecting direction of the ultrasound observation portion; a fluid conduit communicating with the opening portion; and a first flow rate adjusting portion configured to variably adjust a flow rate of the fluid flowing through the fluid conduit among two or more states; a pressing control portion configured to control a pressing state of the ultrasound probe pressing the subject, by controlling a flow rate of the fluid ejected from the opening portion

by flow rate adjustment through the first flow rate adjusting portion; a probe control portion configured to drive-control the ultrasound probe in two or more pressing states controlled by the pressing control portion to acquire an ultrasound signal of the subject; and an elastographic image generating portion configured to measure an amount of displacement of the subject based on the ultrasound signal and generate an elastographic image showing distribution of moduli of elasticity for respective coordinates of the subject based on the amount of displacement.

[0012] Further, an ultrasound endoscope system according to another aspect of the present invention is provided with: an ultrasound endoscope including: an insertion portion configured to be inserted into a subject; a distal end portion arranged at a distal end of the insertion portion; an ultrasound observation portion arranged at the distal end portion; an opening portion enabling fluid to be ejected from a vicinity of the ultrasound observation portion in a projecting direction of the ultrasound observation portion; and a fluid conduit communicating with the opening portion; a liquid feeding apparatus for ultrasound endoscope including: a fluid guiding-out portion configured to guide the fluid into the fluid conduit; and a second flow rate adjusting portion configured to variably adjust a flow rate of the fluid guided out from the fluid guiding-out portion among two or more states; a pressing control portion configured to control a pressing state of the ultrasound probe pressing the subject, by controlling a flow rate of the fluid ejected from the opening portion by flow rate adjustment through the second flow rate adjusting portion; a probe control portion configured to drive-control the ultrasound probe in two or more pressing states controlled by the pressing control portion to acquire an ultrasound signal of the subject; and an elastographic image generating portion configured to measure an amount of displacement of the subject based on the ultrasound signal and generate an elastographic image showing distribution of moduli of elasticity for respective coordinates of the subject based on the amount of displacement.

Brief Description of the Drawings

[0013]

Fig. 1 relates to a first embodiment of the present invention and is a configuration diagram of an ultrasound endoscope system;

Fig. 2 relates to the first embodiment of the present invention and is an explanatory diagram schematically showing a relationship between an ultrasound probe and a stomach wall when water is not fed;

Fig. 3 relates to the first embodiment of the present invention and is an explanatory diagram schematically showing a relationship between the ultrasound probe and the stomach wall when water is fed;

Fig. 4 relates to the first embodiment of the present

invention and is a perspective view showing a distal end portion;

Fig. 5 relates to the first embodiment of the present invention and is an end face view showing the distal end portion;

Fig. 6 relates to a second embodiment of the present invention and is a schematic configuration diagram of a liquid feeding apparatus for ultrasound endoscope;

Fig. 7 relates to a first modification of the second embodiment of the present invention and is a schematic configuration diagram of a liquid feeding apparatus for ultrasound endoscope;

Fig. 8 relates to a second modification of the second embodiment of the present invention and is a schematic configuration diagram of a liquid feeding apparatus for ultrasound endoscope;

Fig. 9 relates to the second modification of the second embodiment of the present invention and is a time chart showing pump generated pressure;

Fig. 10 relates to a third modification of the second embodiment of the present invention and is a schematic configuration diagram of a liquid feeding apparatus for ultrasound endoscope;

Fig. 11 relates to a fourth modification of the second embodiment of the present invention and is a schematic configuration diagram of a liquid feeding apparatus for ultrasound endoscope;

Fig. 12 relates to a fifth modification of the second embodiment of the present invention and is a schematic configuration diagram of a liquid feeding apparatus for ultrasound endoscope;

Fig. 13 relates to a third embodiment of the present invention and is an exploded perspective view showing a distal end portion and an adapter;

Fig. 14 relates to the third embodiment of the present invention and is a cross-sectional view showing main portions of the distal end portion equipped with the adapter;

Fig. 15 relates to a first modification of the third embodiment of the present invention and is an exploded perspective view showing a distal end portion and an adapter;

Fig. 16 relates to the first modification of the third embodiment of the present invention and is a cross-sectional view showing main portions of the distal end portion equipped with the adapter;

Fig. 17 relates to a second modification of the third embodiment of the present invention and is an exploded perspective view showing a distal end portion and an adapter;

Fig. 18 relates to the second modification of the third embodiment of the present invention and is a cross-sectional view showing main portions of the distal end portion equipped with the adapter;

Fig. 19 relates to a fourth embodiment of the present invention and is a block diagram showing a configuration of an ultrasound endoscope system;

Fig. 20 relates to the fourth embodiment of the present invention and is a flowchart showing an elastographic image generation process routine; and Fig. 21 relates to a first modification of the fourth embodiment of the present invention and is a block diagram showing a configuration of an ultrasound endoscope system.

Best Mode for Carrying Out the Invention

[0014] Embodiments of the present invention will be described below with reference to drawings. Figs. 1 to 5 relate to a first embodiment of the present invention. Fig. 1 is a configuration diagram of an ultrasound endoscope system; Fig. 2 is an explanatory diagram schematically showing a relationship between an ultrasound probe and a stomach wall when water is not fed; Fig. 3 is an explanatory diagram schematically showing a relationship between the ultrasound probe and the stomach wall when water is fed; Fig. 4 is a perspective view showing a distal end portion; and Fig. 5 is an end face view showing the distal end portion.

[0015] An ultrasound endoscope system 1 of the present embodiment shown in Fig. 1 has an ultrasound endoscope (hereinafter also referred to simply as an endoscope) 2, for example, for a stomach and a duodenum. The endoscope 2 is configured, being provided with an elongated insertion portion 5 to be inserted into a body cavity, an operation portion 6 provided at a proximal end of the insertion portion 5, and a universal cord 7 extending from the operation portion 6.

[0016] The insertion portion 5 is provided with a distal end rigid portion 10, a bending portion 11 located at a proximal end of the distal end rigid portion 10, and a long and flexible tube portion 12 with a small diameter which is located at a proximal end of the bending portion 11 and leads to the operation portion 6, and these are connectedly arranged in that order from a distal end side to constitute main portions.

[0017] As shown in Figs. 2 to 5, the distal end rigid portion 10 is provided with an ultrasound unit 15 for obtaining acoustic image information by ultrasound. The ultrasound unit 15 of the present embodiment is a convex-shaped ultrasound unit, and the ultrasound unit 15 is configured having a nose piece 16, which is a case, and an ultrasound probe 17 as an ultrasound observation portion.

[0018] The nose piece 16 has, for example, a tissue abutting face 16a forming a convex-shaped partial arc, and the tissue abutting face 16a projects further forward than a distal end face 10a of the distal end rigid portion 10 (see Figs. 4 and 5).

[0019] The ultrasound probe 17 is configured having a plurality of ultrasound transducers 17a arrayed in a convex-shaped partial arc and an acoustic lens 17b covering a front of the ultrasound transducers 17a (see Figs. 2 and 3). The ultrasound probe 17 is arranged at a substantial center of the tissue abutting face 16a of the nose

piece 16 (see Figs. 4 and 5). Further, the acoustic lens 17b of the ultrasound probe 17 projects further forward than the distal end face 10a of the distal end rigid portion 10 together with the tissue abutting face 16a of the nose piece 16. Thereby, the ultrasound probe 17 can scan mainly living tissue and the like existing forward of in an endoscope insertion direction.

[0020] Further, for example, as shown in Figs. 4 and 5, an observation window 20 constituting an observation optical system, a pair of illuminating windows 21a and 21b constituting an illumination optical system, a suction/forceps opening 22 from which a treatment instrument such as a puncture needle is guided out, an air/water feeding nozzle 23 from which fluid such as air and water is ejected toward the observation window 20, and an auxiliary water feeding channel opening 24 as an opening portion from which fluid such as water is ejected forward of the distal end rigid portion 10 (that is, in a projecting direction of the ultrasound probe 17) are provided on the distal end face of the distal end rigid portion 10.

[0021] Here, in order to arrange the treatment instrument guided out from the suction/forceps opening 22 in a scanning area As of the ultrasound probe 17, the suction/forceps opening 22 is arranged so that its central axis 01 is located on an extension line of a scanning direction (a center line L1) of the ultrasound probe 17 on the distal end face of the distal end rigid portion 10 (see Fig. 5). Further, on the distal end face 10a of the distal end rigid portion 10, the observation window 20, the illuminating window 21a and the air/water feeding nozzle 23 are collectively arranged on one side of the suction/forceps opening 22, and the illuminating window 21b and the auxiliary water feeding channel opening 24 are collectively arranged on the other side of the suction/forceps opening 22. Thereby, the auxiliary water feeding channel opening 24 is arranged at a position offset relative to the scanning area As of the ultrasound probe 17 (see Fig. 4).

[0022] As shown in Fig. 1, an angle knob 30 for performing a bending operation of the bending portion 11 in a desired direction, an air/water feeding button 31 for performing an air feeding and water feeding operations, a suction button 32 for performing a suction operation, a plurality of buttons/switches 33 to which arbitrary functions among various functions related to the endoscope 2 can be allocated, and a treatment instrument insertion port 34 to be an entrance of a treatment instrument to be guided into a body are arranged on the operation portion 6. Here, in the present embodiment, any of the buttons/switches 33 can be set, for example, as a switch for giving an instruction to start and end elastography observation using the ultrasound unit 15. Further, the treatment instrument insertion port 34 communicates with the suction/forceps opening 22 via a treatment instrument insertion channel (not shown) provided inside the insertion portion 5.

[0023] One end side of the universal cord 7 is arranged being connected to a side portion of the operation portion

6 via a bend preventing portion 40. On the other hand, a scope connector portion 41 is provided on an extension end, which is the other end side of the universal cord 7. At an end portion of the scope connector portion 41, a light source side connector 42 is provided which is attachable to and detachable from a light source apparatus not shown. On the light source side connector 42, proximal end portions of a light guide 42a and an air feeding tube 42b which extend from an insertion portion 5 side are projectingly provided, and an electrical contact not shown is arranged. Further, on one side portion of the scope connector portion 41, an ultrasound connector 43 attachable to and detachable from an ultrasound observation apparatus 50, an electrical connector 44 attachable to and detachable from a video processor not shown are provided side by side. Furthermore, on the other side portion of the scope connector portion 41, proximal end portions of a pressurized tube 45a and a water feeding tube 45b are projectingly provided, and an auxiliary water feeding pipe sleeve 46 attachable to and detachable from a liquid feeding apparatus for ultrasound endoscope 55 is also provided.

[0024] Here, as shown in Figs. 2 and 3, the auxiliary water feeding pipe sleeve 46 communicates with the auxiliary water feeding channel opening 24 via an auxiliary water feeding channel 47 as a fluid conduit. Further, for example, in the scope connector portion 41, an adjustment valve 48 as a first flow rate adjusting portion is interposed in a middle of the auxiliary water feeding channel 47. The adjustment valve 48 is configured, for example, with a normally closed electromagnetic solenoid valve. The adjustment valve 48 can control a flow rate of fluid flowing through the auxiliary water feeding channel 47 so that the flow rate is in an arbitrary state, by a valve opening time period being controlled by an arbitrary duty ratio. More specifically, for example, by the valve opening time period being periodically duty-controlled by an arbitrary duty ratio, it is possible for the adjustment valve 48 to cause the flow rate of the fluid flowing through the auxiliary water feeding channel 47 to switch among two or more arbitrary states (for example, it is possible to cause the flow rate to periodically switch between arbitrary two states). Note that the adjustment valve 48 can be provided inside the operation portion 6 or the like instead of being provided inside the scope connector portion 41. The flow rate stated here includes a state that the flow rate is zero.

[0025] As shown in Figs. 1 to 3, the liquid feeding apparatus for ultrasound endoscope 55 of the present embodiment is, for example, a pneumatic liquid feeding apparatus. The liquid feeding apparatus for ultrasound endoscope 55 is configured having a pump unit 56 which generates air pressure and a liquid feeding tank 57 which stores liquid (fluid) such as sterile water and degassed water. The pump unit 56 has a peristaltic pump 60, and the peristaltic pump 60 communicates with an upper part of the liquid feeding tank 57 via a pressurized tube 61. Further, one end of an auxiliary water feeding tube 62 is

caused to face a bottom portion of the liquid feeding tank 57, and the other end of the auxiliary water feeding tube 62 is connected to the auxiliary water feeding channel 47 via the auxiliary water feeding pipe sleeve 46. In the liquid feeding apparatus for ultrasound endoscope 55, when the peristaltic pump 60 of the pump unit 56 is driven, air pressure which occurs in the peristaltic pump 60 is supplied to an upper part in the liquid feeding tank 57 via the pressurized tube 61. Internal pressure of the liquid feeding tank 57 is increased by the supply of the air pressure, and liquid such as degassed water stored in the liquid feeding tank 57 is guided out into the auxiliary water feeding channel 47 via the auxiliary water feeding tube 62 by the increase in the internal pressure. That is, in the present embodiment, the peristaltic pump 60 realizes a function as a fluid guiding-out portion.

[0026] As shown in Fig. 1, the ultrasound observation apparatus 50 is connected to the ultrasound connector 43 via an ultrasound connection cable 51. The ultrasound observation apparatus 50 drive-controls the ultrasound probe 17, and generates various kinds of ultrasound images based on an ultrasound echo signal (an ultrasound signal) received at the ultrasound probe 17 by the drive control. For example, the ultrasound observation apparatus 50 is capable of performing generation of a B-mode image in which amplification of the received ultrasound echo signal is associated with luminance, and the like.

[0027] Further, for example, an instruction to the effect that elastography observation is to be started is made through an operation of the buttons/switches 33 by a user or the like, the ultrasound observation apparatus 50 causes the peristaltic pump 60 to be driven, and adjusts a flow rate of fluid (for example, liquid such as degassed water) which flows through the auxiliary water feeding channel 47 through the control of the adjustment valve 48. Thereby, the flow rate of the fluid ejected from the auxiliary water feeding channel opening 24 changes, and pressing force living tissue receives by the ejection of the fluid changes. Since the ejection of the fluid presses the living tissue in the projecting direction of the ultrasound probe 17 in a vicinity of the ultrasound probe 17, the pressing force of the ultrasound probe 17 pressing the living tissue indirectly changes by the ejection of the fluid without causing the ultrasound probe 17 to move. As a result, it becomes possible for the ultrasound probe 17 to obtain an ultrasound signal in a different pressing state. Then, the ultrasound observation apparatus 50 measures change (displacement) of a deformed state of the living tissue based on the ultrasound signal in the different pressing state and generates an elastography image based on a displacement measurement result.

[0028] To describe a case of performing elastography observation of a pancreas 101 via a stomach wall 100 in order to perform examination of a tumor/lymph node metastasis of the pancreas 101 and the like as a specific example, referring to Fig. 2 and 3, the distal end rigid portion 10 of the endoscope 2 inserted in a body cavity is arranged at a position of pressing the stomach wall

100 and the pancreas 101 with predetermined pressing force via the ultrasound probe 17 first prior to observation. Further, the peristaltic pump 60 is driven by the ultrasound observation apparatus 50, and the adjustment valve 48 is duty-controlled. Thereby, for example, a state in which degassed water or the like is not ejected from the auxiliary water feeding channel opening 24 (see Fig. 2) and a state in which the degassed water or the like is ejected from the auxiliary water feeding channel opening 24 at a predetermined hydraulic pressure (see Fig. 3) are periodically repeated. Here, in the state in which the degassed water or the like is ejected from the auxiliary water feeding channel opening 24, living tissue in the vicinity of the ultrasound probe 17 is pressed by the hydraulic pressure. As a result, pressing force against the stomach wall 100 and the like by the ultrasound probe 17 is reduced without moving the ultrasound probe 17 relative to the stomach wall 100 and the like. That is, the pressing force against the stomach wall 100 and the like by the ultrasound probe 17 periodically switches between pressing force at the time when the degassed water or the like is not ejected from the auxiliary water feeding channel opening 24 (first pressing force) and pressing force at the time when the degassed water or the like is ejected from the auxiliary water feeding channel opening 24 (second pressing force weaker than the first pressing force). Then, by drive-controlling the ultrasound probe 17 (the ultrasound transducers 17a) each time the pressing force against the stomach wall 100 and the like by the ultrasound probe 17 switches between the first pressing force and the second pressing force, the ultrasound observation apparatus 50 acquires an ultrasound signal in each pressing state.

[0029] According to such an embodiment, by providing the ultrasound probe 17 arranged at the distal end rigid portion 10, the auxiliary water feeding channel opening 24 through which fluid is ejected from the vicinity of the ultrasound probe 17 in the projecting direction of the ultrasound probe 17, the auxiliary water feeding channel 47 communicating with the auxiliary water feeding channel opening 24, and the adjustment valve 48 for variably adjusting the flow rate of the fluid flowing through the auxiliary water feeding channel 47 among two or more states, it is possible to obtain a favorable elastography image by a simple configuration without upsizing the distal end portion.

[0030] That is, by adopting the configuration in which living tissue in the vicinity of the ultrasound probe 17 is pressed by the hydraulic pressure of the fluid ejected from the auxiliary water feeding channel opening 24, it is possible to obtain a favorable elastography image by the simple configuration without providing a pressing mechanism or the like for mechanically pressing a body cavity at the distal end rigid portion 10 of the endoscope 2.

[0031] In this case, by using the auxiliary water feeding channel opening 24 arranged at the position offset from the scanning area As of the ultrasound probe 17 as a fluid ejection nozzle, it is possible to reduce influence of

the ejected fluid such as degassed water on an ultrasound signal.

[0032] Next, Fig. 6 relates to a second embodiment of the present invention, and Fig. 6 is a schematic configuration diagram of a liquid feeding apparatus for ultrasound endoscope. Note that the present embodiment is different from the first embodiment described above mainly in a point that an adjustment valve 70 as a second flow rate adjusting portion is arranged on a liquid feeding apparatus for ultrasound endoscope 55 side, instead of the adjustment valve 48 as the first flow rate adjusting portion arranged on an endoscope 2 side. As for components and the like similar to those of the first embodiment described above, same reference numerals will be given, and description will be appropriately omitted.

[0033] As shown in Fig. 6, the adjustment valve 70 of the present embodiment is interposed, for example, in a middle of the auxiliary water feeding tube 62 in the pump unit 56.

[0034] The adjustment valve 70 is configured, for example, with a normally closed electromagnetic solenoid valve. The adjustment valve 70 can control the flow rate of the fluid flowing through the auxiliary water feeding channel 47 so that the flow rate is in an arbitrary state by the ultrasound observation apparatus 50 controlling a valve opening time period by an arbitrary duty ratio. More specifically, for example, by the valve opening time period being periodically duty-controlled by an arbitrary duty ratio, it is possible for the adjustment valve 70 to cause the flow rate of the fluid flowing through the auxiliary water feeding channel 47 to switch among a plurality of arbitrary states (for example, it is possible to cause the flow rate to periodically switch between arbitrary two states).

[0035] According to such an embodiment, it is possible to obtain operations and/or effects which are substantially similar to those of the first embodiment described above. In addition, in the present embodiment, by providing the adjustment valve 70 inside the liquid feeding apparatus for ultrasound endoscope 55, it is possible to obtain a favorable elastography image without making any change in design or the like in the endoscope 2 which is provided with the auxiliary water feeding channel opening 24 and the like.

[0036] Here, in the present embodiment, various modifications are possible as a configuration for performing flow rate adjustment by the liquid feeding apparatus for ultrasound endoscope 55.

[0037] For example, instead of the configuration in which the adjustment valve 70 is interposed in the auxiliary water feeding tube 62, it is also possible to interpose the adjustment valve 70 as the second flow rate adjusting portion in a middle of the pressurized tube 61 as shown in Fig. 7.

[0038] Further, for example, it is also possible to, instead of the pneumatic liquid feeding apparatus for ultrasound endoscope 55 which guides out liquid in the liquid feeding tank 57 utilizing air pressure generated by the pump unit 56, adopt a liquid feeding apparatus for ultra-

sound endoscope 55 of a type which directly pumps up the liquid in the liquid feeding tank 57 by a positive displacement pump 72 interposed in the middle of the auxiliary water feeding tube 62 in the pump unit 56, as shown in Fig. 8. In this case, for example, as shown in Fig. 9, since the positive displacement pump 72 constituting the pump unit 56 is originally such that generates predetermined pulsation at time of pumping up liquid, it is possible to periodically change the flow rate of the fluid flowing through the auxiliary water feeding channel 47 without using an adjustment valve. That is, in a modification shown in Fig. 8, the positive displacement pump 72 itself realizes functions as the fluid guiding-out portion and the second flow rate adjusting portion.

[0039] Otherwise, by adopting a DC pump 73 as a pump constituting the pump unit 56 instead of the positive displacement pump 72 and using an AC power source 74 as means for supplying power to the DC pump 73, for example, as shown in Fig. 10, it is possible to periodically change output power and periodically change the flow rate of the fluid flowing through the auxiliary water feeding channel 47 without using an adjustment valve. Furthermore, a power source control portion may be interposed between the DC pump 73 and the AC power source 74 to change a voltage period of the AC power source.

[0040] Further, it is also possible to interpose a relief valve 75 as the second flow rate adjusting portion in the middle of the auxiliary water feeding tube 62 on a downstream side of the DC pump 73, for example, as shown in Fig. 11 and cause a flow rate of degassed water or the like pressure-fed from the DC pump 73 to change by mechanical operation of the relief valve 75. That is, in such a configuration, the DC pump 73 is driven, for example, to pressure-feed fluid at a predetermined high pressure. Then, internal pressure of the auxiliary water feeding tube 62 between the DC pump 73 and a drain passage 75a increases and becomes a predetermined high pressure or higher, the relief valve 75 mechanically opens the drain passage 75a, and, thereby, hydraulic pressure in the auxiliary water feeding tube 62 between the DC pump 73 and the drain passage 75a decreases. On the other hand, when the internal pressure of the auxiliary water feeding tube 62 between the DC pump 73 and the drain passage 75a decreases and becomes lower than a predetermined low pressure by the drain passage 75a being opened, the relief valve 75 mechanically blocks the drain passage 75a, and, thereby, the internal pressure of the auxiliary water feeding tube 62 increases again. By the relief valve 75 repeating such operation, the flow rate of the fluid flowing through the auxiliary water feeding channel 47 is periodically changed.

[0041] Further, it is also possible to interpose a three-way valve 76 as the second flow rate adjusting portion in the middle of the auxiliary water feeding tube 62 on the downstream side of the DC pump 73, for example, as shown in Fig. 12 and cause the flow rate of the degassed water or the like pressure-fed from the DC pump 73 to change by controlling the three-way valve 76 by

the ultrasound observation apparatus 50 or the like. That is, in such a configuration, the ultrasound observation apparatus 50 periodically connects the DC pump 73 to a downstream side of the auxiliary water feeding tube 62 and to a drain passage 76a alternately through control of the three-way valve 76. Thereby, the flow rate of the fluid flowing through the auxiliary water feeding channel 47 is periodically changed.

[0042] Next, Figs. 13 and 14 relate to a third embodiment of the present invention. Fig. 13 is an exploded perspective view showing a distal end portion and an adapter; and Fig. 14 is a cross-sectional view showing main portions of the distal end portion equipped with the adapter. Note that the present embodiment is different from the first and second embodiments described above mainly in a point that the distal end rigid portion 10 of the endoscope 2 is equipped with an adapter 80 to optimize an ejection direction of fluid. As for components and the like similar to those of the first and second embodiments described above, same reference numerals will be given, and description will be appropriately omitted.

[0043] As shown in Figs. 13 and 14, the distal end rigid portion 10 is equipped with a ring-shaped adapter 80 on a distal-end side outer circumference of the distal end rigid portion 10 by fitting or the like. At a position corresponding to the auxiliary water feeding channel opening 24 on an inner circumferential side of the adapter 80, a guiding projection 80a is provided, and a guide hole 80b communicating with the auxiliary water feeding channel opening 24 is made in the guiding projection 80a. For example, as shown in Fig. 14, the guide hole 80b functions as an opening portion for ejecting fluid and is inclined at a predetermined angle relative to an insertion axis direction of the distal end rigid portion 10. More specifically, the guide hole 80b has a component in the projecting direction of the ultrasound probe 17 and is inclined at the predetermined angle in a direction away from the ultrasound probe 17.

[0044] According to such a configuration, it is possible to adjust the ejection direction of the fluid such as degassed water supplied via the auxiliary water feeding channel opening 24 by fitting the adapter 80 having the guide hole 80b to an arbitrary direction. By setting the ejection direction of the fluid from the guide hole 80b to a direction having a component in the projecting direction of the ultrasound probe 17 and being away from the ultrasound probe 17, it is possible to cause a state of pressing living tissue to change while avoiding degassed water or the like from flowing in between the ultrasound probe 17 and the living tissue, and it becomes possible to acquire a more favorable ultrasound signal.

[0045] Here, by adopting the configuration in which the ejection direction of fluid is arbitrarily adjusted by the guide hole of the adapter 80 fitted to the distal end rigid portion 10, it is possible to use even the suction/forceps opening 22 or the like which is not offset from the operating area As of the ultrasound probe 17 as an opening portion for ejection of fluid, for example, as shown in Figs.

15 and 16. In this case, the treatment instrument insertion channel communicating with the suction/forceps opening 22 functions as a fluid conduit. For example, as shown in Fig. 16, ejection of fluid via the suction/forceps opening 22 becomes possible by a water feeding tube 58 or the like of the liquid feeding apparatus for ultrasound endoscope 55 being inserted into the treatment instrument insertion port 34. Further, at a position corresponding to the suction/forceps opening 22 on the inner circumferential side of the adapter 80, a guiding projection 80c is provided, and a guide hole 80d communicating with the suction/forceps opening 22 is made in the guiding projection 80c. The guide hole 80d functions as an opening portion for ejecting fluid and is inclined at a predetermined angle relative to the insertion axis direction of the distal end rigid portion 10. More specifically, the guide hole 80d has a component in the projecting direction of the ultrasound probe 17 and is inclined at the predetermined angle in a direction away from the ultrasound probe 17. Note that, though detailed description for other matters will be omitted, it is possible to adopt a similar configuration, for example, for the air/water feeding nozzle 23.

[0046] Furthermore, for example, as shown in Figs. 17 and 18, it is also possible to adopt a configuration in which an independent conduit 59 which is additionally provided for the insertion portion 5 of the endoscope 2 appropriately is used as a fluid conduit, and the independent conduit 59 is caused to communicate with a guide hole 80e of the adapter 80 fitted to the distal end rigid portion 10.

[0047] Next, Figs. 19 and 20 relate to a fourth embodiment of the present invention. Fig. 19 is a block diagram showing a configuration of an ultrasound endoscope system; and Fig. 20 is a flowchart showing an elastographic image generation process routine. Note that the present embodiment is such that describes a specific control example at a time of performing the elastography observation performed in the first embodiment described above, in detail. Therefore, as for components similar to those of the first embodiment described above, same reference numerals will be given, and the components will be appropriately omitted. Note that, though specific description will be omitted, similar control is, of course, applicable to the second and third embodiment described above.

[0048] The ultrasound observation apparatus 50 is provided with a transmission circuit 121, a transmission/reception switching circuit 124, a reception circuit 125, a phasing addition circuit 126, a signal processing circuit 127, a displacement-for-generation-of-elastographic-image measuring circuit 128, a modulus-of-elasticity calculating circuit 129 and a pressurization mechanism control circuit 132.

[0049] The transmission circuit 121 includes a transmission waveform generating circuit 122 and a transmission delay circuit 123.

[0050] The transmission waveform generating circuit 122 generates a signal waveform for driving each of the transducers 17a constituting the ultrasound probe 17 and outputs the signal waveform.

[0051] The transmission delay circuit 123 adjusts timing for driving each of the transducers 17a constituting the ultrasound probe 17. Thereby, a focus and direction of an ultrasound beam transmitted from the ultrasound probe 17 are controlled, and it is possible to cause ultrasound to converge to a desired position (depth).

[0052] The transmission/reception switching circuit 124 includes, for example, a multiplexer which sequentially selects a plurality of transducers for transmitting and receiving ultrasound; and the transmission/reception switching circuit 124 transmits a driving signal from the transmission circuit 121 to the ultrasound probe 17 and transmits an ultrasound signal (an echo signal) from the ultrasound probe 17 to the reception circuit 125.

[0053] The reception circuit 125 receives the ultrasound signal from the transmission/reception switching circuit 124 and performs, for example, processing such as amplification and conversion to a digital signal.

[0054] Thus, in the present embodiment, the transmission circuit 121 (the transmission waveform generating circuit 122 and the transmission delay circuit 123), the transmission/reception switching circuit 124 and the reception circuit 125 realize a function as a probe control portion.

[0055] The phasing addition circuit 126 delays an ultrasound signal to adjust a phase and then performs addition.

[0056] In an ultrasound diagnostic mode, the signal processing circuit 127 performs coordinate transformation or interpolation processing for an ultrasound signal from the phasing addition circuit 126 to create an ultrasound image as an image for display. Furthermore, in an elastographic image observation mode (an elastography image observation mode), the signal processing circuit 127 creates an image for display as for an elastographic image from the modulus-of-elasticity calculating circuit 29 or creates an image for display by superposing the elastographic image on an ultrasound image.

[0057] The displacement-for-generation-of-elastographic-image measuring circuit 128 is a displacement-for-elastographic-image measuring portion which measures an amount of displacement for an image of a subject (an amount of displacement for generating an elastographic image of the subject) based on an ultrasound signal.

[0058] The modulus-of-elasticity calculating circuit 129 is a modulus-of-elasticity calculating portion which calculates a modulus of elasticity of the subject based on the amount of displacement for image measured by the displacement-for-generation-of-elastographic-image measuring circuit 128. Since the modulus-of-elasticity calculating circuit 129 calculates a modulus of elasticity for each coordinate of the subject, a calculation result is an elastographic image on which moduli of elasticity are distributed on two-dimensional coordinates.

[0059] Thus, in the present embodiment, the phasing addition circuit 126, the signal processing circuit 127, the displacement-for-generation-of elastographic-image

measuring circuit 128 and the modulus-of-elasticity calculating circuit 129 realize a function as an elastographic image generating portion.

[0060] For example, when an instruction to the effect that elastography observation is to be started is made through an operation of the buttons/switches 33 by the user or the like (that is, when the elastographic image observation mode is selected), the pressurization mechanism control circuit 132 performs an automatic pressurization (pressure reduction) control process for the subject. That is, by performing valve opening control of the control valve 48 at a predetermined duty ratio for each predetermined period and controlling an amount of ejection of fluid ejected from the auxiliary water feeding channel opening 24, through the valve opening control, the pressurization mechanism control circuit 132 indirectly causes a pressing state of the ultrasound probe 17 pressing the subject to change. It is desirable to perform such control performed for the control valve 48 in synchronization of spontaneous displacement such as beats of the subject. For example, in the present embodiment in which pressing force against the subject by the ultrasound probe 17 is reduced by ejection of fluid, it is desirable that the control valve 48 is controlled so that the amount of ejection of the fluid is smallest at timing when the spontaneous displacement of the subject is the largest (otherwise, so that the amount of ejection of the fluid becomes zero).

[0061] Thus, in the present embodiment, the pressurization mechanism control circuit 132 realizes a function as a pressing control portion.

[0062] A monitor 140 displays an image for display from the signal processing circuit 27.

[0063] Next, Fig. 20 is a flowchart showing an elastographic image generation process routine.

[0064] When the ultrasound observation system 1 is set to the elastographic image observation mode, the process shown in Fig. 20 is started.

[0065] Then, first, an automatic pressurization control process in the pressurization mechanism control circuit 132 is activated (step S1).

[0066] Then, transmission/reception of ultrasound to and from the ultrasound probe 17 is performed (step S2), and an amount of displacement (an amount of displacement for image) of a subject to be a diagnosis target is measured by the displacement-for-generation-of-elastographic-image measuring circuit 128 (step S3).

[0067] Next, the modulus-of-elasticity calculating circuit 129 calculates a modulus of elasticity of the subject for each coordinate of the subject, based on the amount of displacement for image measured at step S3 (step S4).

[0068] The calculated moduli of elasticity is transmitted to the signal processing circuit 127 together with coordinates and configured as an elastographic image for display (step S5). The elastographic image is further superposed on an ultrasound image as necessary to create an image for display, and the image for display is displayed on the monitor 140.

[0069] After that, it is judged whether the process is to be ended or not (step S6). If the process is not to be ended, the process returns to step S2 to generate an elastographic image for a next frame, and the process as described above is repeated.

[0070] On the other hand, if it is judged that the process is to be ended, the automatic pressurization control process by the pressurization mechanism control circuit 132 is caused to end (step S7), and then the elastographic image generation process is ended.

[0071] Here, though detailed description is omitted, the present embodiment can be, of course, applied to the configuration shown in the second embodiment, for example, as shown in Fig. 21. Note that the present invention is not limited to each of the embodiments described above, and various modifications and changes are possible. The modifications and changes are also within a technical scope of the present invention. For example, though description has been made on an example of the case of performing elastography observation by the ultrasound endoscope system 1 to perform examination of a tumor/lymph node metastasis of the pancreas 101 and the like in the embodiments described above, the elastography observation using the present invention can be applied to various examinations for chronic pancreatitis, a tumor/lymph node metastasis of a liver, hepatic cirrhosis, a tumor/lymph node metastasis of a mediastinum (an esophagus), a tumor/lymph node metastasis of a prostate, and the like.

[0072] Further it is, of course, possible to appropriately combine components of the respective embodiments and respective modifications described above.

[0073] This application is filed, claiming priority based on Japanese Patent Application No. 2014-169442 filed to Japan on August 22, 2014, the content of which is incorporated in the specification, the claims and the drawings of this application.

Claims

1. An ultrasound endoscope comprising:

- an insertion portion configured to be inserted into a subject;
- a distal end portion arranged at a distal end of the insertion portion;
- an ultrasound observation portion arranged at the distal end portion;
- an opening portion enabling fluid to be ejected from a vicinity of the ultrasound observation portion in a projecting direction of the ultrasound observation portion;
- a fluid conduit communicating with the opening portion; and
- a first flow rate adjusting portion configured to variably adjust a flow rate of the fluid flowing through the fluid conduit among two or more

states.

2. The ultrasound endoscope according to claim 1, wherein the opening portion is made being oriented in the projecting direction of the ultrasound observation portion and in a direction of ejecting the fluid in a direction away from the ultrasound observation portion. 5
3. The ultrasound endoscope according to claim 1, wherein the opening portion is provided at a position offset relative to a scanning area of the ultrasound observation portion. 10
4. The ultrasound endoscope according to claim 1, wherein the opening portion is formed in an adapter fitted to the distal end portion. 15
5. The ultrasound endoscope according to claim 1, wherein the first flow rate adjusting portion causes the flow rate of the fluid flowing through the fluid conduit to periodically switch between two states. 20
6. A liquid feeding apparatus for ultrasound endoscope suitable for an ultrasound endoscope, the ultrasound endoscope comprising: an insertion portion configured to be inserted into a subject; a distal end portion arranged at a distal end of the insertion portion; an ultrasound observation portion arranged at the distal end portion; an opening portion enabling fluid to be ejected from a vicinity of the ultrasound observation portion in a projecting direction of the ultrasound observation portion; and a fluid conduit communicating with the opening portion; the liquid feeding apparatus for ultrasound endoscope comprising: 25
 - a fluid guiding-out portion configured to guide the fluid into the fluid conduit;
 - and
 - a second flow rate adjusting portion configured to variably adjust a flow rate of the fluid guided out from the fluid guiding-out portion among two or more states. 40
7. The liquid feeding apparatus for ultrasound endoscope according to claim 6, wherein the second flow rate adjusting portion causes the flow rate of the fluid guided out from the fluid guiding-out portion to periodically switch between two states. 45
8. An ultrasound endoscope system comprising: 50
 - an ultrasound endoscope comprising: an insertion portion configured to be inserted into a subject; a distal end portion arranged at a distal end of the insertion portion; an ultrasound observation portion arranged at the distal end portion; an opening portion enabling fluid to be ejected

from a vicinity of the ultrasound observation portion in a projecting direction of the ultrasound observation portion; a fluid conduit communicating with the opening portion; and a first flow rate adjusting portion configured to variably adjust a flow rate of the fluid flowing through the fluid conduit among two or more states;

a pressing control portion configured to control a pressing state of the ultrasound probe pressing the subject, by controlling a flow rate of the fluid ejected from the opening portion by flow rate adjustment through the first flow rate adjusting portion;

a probe control portion configured to drive-control the ultrasound probe in two or more pressing states controlled by the pressing control portion to acquire an ultrasound signal of the subject; and

an elastographic image generating portion configured to measure an amount of displacement of the subject based on the ultrasound signal and generate an elastographic image showing distribution of moduli of elasticity for respective coordinates of the subject based on the amount of displacement.

9. An ultrasound endoscope system comprising:

an ultrasound endoscope comprising: an insertion portion configured to be inserted into a subject; a distal end portion arranged at a distal end of the insertion portion; an ultrasound observation portion arranged at the distal end portion; an opening portion enabling fluid to be ejected from a vicinity of the ultrasound observation portion in a projecting direction of the ultrasound observation portion; and a fluid conduit communicating with the opening portion;

a liquid feeding apparatus for ultrasound endoscope comprising: a fluid guiding-out portion configured to guide the fluid into the fluid conduit; and a second flow rate adjusting portion configured to variably adjust a flow rate of the fluid guided out from the fluid guiding-out portion among two or more states;

a pressing control portion configured to control a pressing state of the ultrasound probe pressing the subject, by controlling a flow rate of the fluid ejected from the opening portion by flow rate adjustment through the second flow rate adjusting portion;

a probe control portion configured to drive-control the ultrasound probe in two or more pressing states controlled by the pressing control portion to acquire an ultrasound signal of the subject; and

an elastographic image generating portion configured to measure an amount of displacement

of the subject based on the ultrasound signal and generate an elastographic image showing distribution of moduli of elasticity for respective coordinates of the subject based on the amount of displacement.

5

10

15

20

25

30

35

40

45

50

55




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19






FIG. 20

FIG. 21



INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP2015/061632

A. CLASSIFICATION OF SUBJECT MATTER

A61B8/08(2006.01)i, A61B8/12(2006.01)i

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

A61B8/00-8/15, A61B1/00-1/32

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Jitsuyo Shinan Koho 1922-1996 Jitsuyo Shinan Toroku Koho 1996-2015

Kokai Jitsuyo Shinan Koho 1971-2015 Toroku Jitsuyo Shinan Koho 1994-2015

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	JP 2001-224594 A (Olympus Optical Co., Ltd.),	1-3, 6, 8, 9
Y	21 August 2001 (21.08.2001),	4
A	paragraphs [0014] to [0022], [0033], [0041], [0042], [0067]; fig. 3 (Family: none)	5, 7
Y	JP 2009-254468 A (Olympus Medical Systems Corp.),	4
	05 November 2009 (05.11.2009), paragraph [0034]; fig. 10 (Family: none)	

☐ Further documents are listed in the continuation of Box C.☐ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

07 July 2015 (07.07.15)

Date of mailing of the international search report

14 July 2015 (14.07.15)

Name and mailing address of the ISA/

Japan Patent Office

3-4-3, Kasumigaseki, Chiyoda-ku,

Tokyo 100-8915, Japan

Authorized officer

Telephone No.

Form PCT/ISA/210 (second sheet) (July 2009)

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- JP 2012081295 A [0002]
- JP 2014169442 A [0073]

专利名称(译)	超声波内窥镜，超声波内窥镜用液体输送装置，超声波内窥镜系统		
公开(公告)号	EP3061400A1	公开(公告)日	2016-08-31
申请号	EP2015833184	申请日	2015-04-15
[标]申请(专利权)人(译)	奥林巴斯株式会社		
申请(专利权)人(译)	OLYMPUS CORPORATION		
当前申请(专利权)人(译)	OLYMPUS CORPORATION		
[标]发明人	TSURUTA TEPPEI		
发明人	TSURUTA, TEPPEI		
IPC分类号	A61B8/08 A61B8/12		
CPC分类号	A61B1/015 A61B1/00091 A61B1/005 A61B1/018 A61B8/08 A61B8/12 A61B8/429 A61B8/485 A61B8/5207		
优先权	2014169442 2014-08-22 JP		
其他公开文献	EP3061400B1 EP3061400A4		
外部链接	Espacenet		

摘要(译)

本发明提供一种超声波内窥镜，其能够通过简单的结构获得良好的弹性成像图像而不增大远端部分的尺寸。为此目的，超声内窥镜2被配置为具有布置在远端刚性部分10处的超声探头17，辅助供水通道开口24，流体通过该辅助供水通道开口24在超声探头17的突出方向上从超声探头17的附近射出。超声波探头17，与辅助供水通道开口24连通的辅助供水通道47，以及调节阀48，用于在两个或多个状态中可变地调节流过辅助供水通道47的流体的流量。

FIG. 3

