



(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(43) Date of publication:
02.10.2013 Bulletin 2013/40

(51) Int Cl.:
A61B 8/12 (2006.01)

(21) Application number: **12851965.9**

(86) International application number:
PCT/JP2012/076272

(22) Date of filing: **11.10.2012**

(87) International publication number:
WO 2013/077101 (30.05.2013 Gazette 2013/22)

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

(72) Inventor: **IRIE, Kei**
Shibuya-ku
Tokyo 151-0072 (JP)

(30) Priority: **24.11.2011 JP 2011256430**

(74) Representative: **Gunzelmann, Rainer**
Wuesthoff & Wuesthoff
Patent- und Rechtsanwälte
Schweigerstraße 2
D-81541 München (DE)


(71) Applicant: **Olympus Medical Systems Corp.**
Tokyo 151-0072 (JP)

(54) **ULTRASONIC PROBE**

(57) An ultrasound probe including: an ultrasound transmission/reception portion; a cable 41; a housing 34; a hole portion 34h of the housing 34; an insulation pipe 36 having a proximal end side exposed outside the housing 34; an insulation tube 42 covering an outer circumference of an exposed region 36r of the insulation pipe

36 and an out circumference of the cable 41; an adhesive 52 configured to adhere the outer circumference of the exposed region 36r and a distal end side region 42s of the insulation tube 42; and a sticky member 61 disposed between the exposed region 36r and the distal end side region 42s together with the adhesive 52.

FIG.3



Description

Technical Field

[0001] The present invention relates to an ultrasound probe provided with an ultrasound transmission/reception portion having an ultrasound transmitting/receiving surface configured to transmit and receive ultrasound and a cable having a distal end electrically connected to the ultrasound transmission/reception portion.

Background Art

[0002] An ultrasound probe used for obtaining an ultrasound image by transmitting and receiving ultrasound to and from a region to be examined is configured such that an ultrasound transmission/reception portion, which is located at a distal end of the ultrasound probe and which is configured to transmit and receive ultrasound, is connected, through a cable, to a connector which is located at a proximal end of the ultrasound probe and which connects the ultrasound probe to an ultrasound observation apparatus.

[0003] In addition, the ultrasound probe has a configuration in which the outer circumference of the cable is covered with an insulation tube, or the like, which is a reinforced insulation member, in order to ensure electrical safety of the cable.

[0004] Japanese Patent Application Laid-Open Publication No. 2009-28109 discloses a configuration in which an ultrasound transmission/reception portion to which a distal end of a cable is electrically connected is provided in a housing having an insulation property on a distal end side of an ultrasound probe, an insulation pipe through which the cable is inserted is fixed in a hole portion which is formed on the housing and from which the cable is extended outside the housing, and a distal end side region of an insulation tube is adhered and fixed with adhesive to an outer circumference of an exposed region of the insulation pipe which is exposed outside the housing.

[0005] However, in the configuration disclosed in the Japanese Patent Application Laid-Open Publication No. 2009-28109, when the ultrasound probe is used for an ultrasound endoscope, for example, there is a possibility that the adhesive before being cured flows out from the proximal end of the insulation pipe into the insulation tube and adheres to the cable in the insulation tube, and after the adhesive is cured, the part of the cable, where the adhesive is adhered, is hardened, which results in difficulty of bending the bending portion of the insertion portion of the ultrasound endoscope at which the hardened part is located.

[0006] Note that the flowing-out of the adhesive can be prevented by increasing a length of the exposed region of the insulation pipe. However, if the length of the exposed region of the insulation pipe is increased, there is a problem that also a length of the distal end rigid por-

tion of the insertion portion of the ultrasound endoscope, at which the exposed region is located, is increased.

[0007] The present invention has been achieved in view of the above-described problem, and an object of the present invention is to provide an ultrasound probe configured to be capable of preventing flowing-out of an adhesive for fixing a distal end side region of an insulation tube onto an outer circumference of an exposed region of an insulation pipe exposed from a housing, without increasing a length of the exposed region, while surely ensuring electric safety of a cable by using the insulation pipe and the insulation tube.

Disclosure of Invention

Means for Solving the Problem

[0008] An ultrasound probe according to one aspect of the present invention includes: an ultrasound transmission/reception portion having an ultrasound transmitting/reception surface for transmitting and receiving ultrasound; a cable having a distal end electrically connected to the ultrasound transmission/reception portion; a housing configured to hold the ultrasound transmission/reception portion such that the ultrasound transmission/reception surface is exposed; a hole portion provided to the housing and configured to lead out the cable from inside of the housing; an insulation pipe through which the cable is inserted, the insulation pipe having a distal end side fixed to the hole portion in a state of contacting an inner circumference of the hole portion, and a proximal end side exposed outside the housing; insulation tube configured to cover an outer circumference of an exposed region of the insulation pipe which is exposed from the hole portion and an outer circumference of the cable led out from a proximal end of the insulation pipe; an adhesive configured to adhere the outer circumference of the exposed region of the insulation pipe and a distal end side region of the insulation tube covering the outer circumference of the exposed region; and a liquid dripping prevention portion disposed between the exposed region of the insulation pipe and the distal end side region of the insulation tube, together with the adhesive, the liquid dripping prevention portion being configured to prevent the adhesive from flowing out from the proximal end of the insulation pipe and contacting the cable.

Brief Description of the Drawings

[0009]

FIG. 1 is a perspective view showing ultrasound probe according to a first embodiment.

FIG. 2 is a cross-sectional view of the ultrasound probe along the II-II line in FIG. 1.

FIG. 3 is an enlarged cross-sectional view of the region of the ultrasound probe enclosed by the line III

in FIG. 2.

FIG. 4 is a partial cross-sectional view showing, in an enlarged manner, a vicinity of a proximal end side of an insulation pipe of an ultrasound probe according to a second embodiment.

FIG. 5 is a partial cross-sectional view showing, in an enlarged manner, a vicinity of a proximal end side of an insulation pipe of an ultrasound probe according to a third embodiment.

FIG. 6 is a partial cross-sectional view showing, in an enlarged manner, a vicinity of a proximal end side of an insulation pipe of an ultrasound probe according to a fourth embodiment.

FIG. 7 is a view showing an ultrasound endoscope apparatus provided with an ultrasound endoscope including an ultrasound probe.

Best Mode for Carrying Out the Invention

[0010] Hereinafter, embodiments of the present invention will be described with reference to drawings. Note that each of the drawings is a pattern diagram, and care should be taken to the fact that the relationship between the thicknesses and widths of the respective members, a ratio of the thickness of a certain member to that of another member, and the like are different from those of the members in actual sizes. It is needless to say that each of the drawings includes a relationship and a ratio of the dimensions which are different from those in other drawings.

(First Embodiment)

[0011] FIG 1 is a perspective view showing an ultrasound probe according to the present embodiment, FIG. 2 is a cross-sectional view of the ultrasound probe along the II-II line in FIG 1, and FIG. 3 is an enlarged cross-sectional view of the region of the ultrasound probe enclosed by the line III in FIG. 2.

[0012] As shown in FIG 1, an ultrasound probe 50 includes an ultrasound transducer cable 40. The ultrasound transducer cable 40 has a main part configured by a cable 41 including a plurality of signal lines, and an insulation tube 42 which covers an outer circumference of the cable 41. In addition, the cable 41 including a plurality of signal lines is bundled into one with the insulation tube 42.

[0013] Note that the insulation tube 42 is made of a heat-shrinkable tube, for example, which is formed by a thin and flexible rubber or the like having voltage endurance, so as to ensure specified voltage endurance of the cable 41, and so as not to impede the flexibility of an insertion portion 2 when an ultrasound probe 50 is provided in an ultrasound endoscope 1 (Regarding these components, see FIG 7).

[0014] Further, the insulation tube 42 has a function for preventing the cable 41 from contacting metal members such as a light guide, a balloon conduit, and a for-

ceps channel and the like, not shown, provided in the insertion portion 2, when the ultrasound probe 50 is provided in the ultrasound endoscope 1, to be described later, for example. That is, the insulation tube 42 has a function for insulating the cable 41 from other metal members.

[0015] In addition, since the outer circumference of the cable 41 is not covered with the insulation tube 42 on the proximal end side of the ultrasound transducer cable 40, the cable 41 is exposed. Furthermore, a plurality of connectors 45, which electrically connect the cable 41 to a substrate, not shown, of an ultrasound connector 8 provided in an endoscope connector 5 to be described later, are provided to the exposed region of the cable 41 (regarding these components, see FIG. 7).

[0016] Furthermore, the distal end of the ultrasound transducer cable 40 is connected with an ultrasound transducer unit 30.

[0017] As shown in FIG. 2, the ultrasound transducer unit 30 has a main part configured by including an ultrasound transmission/reception portion 35 having an ultrasound transmission/reception surface 35f configured to transmit and receive ultrasound, and a housing 34 configured to hold the ultrasound transmission/reception portion 35 such that the ultrasound transmission/reception surface 35f is exposed.

[0018] Note that, similarly as the insulation tube 42, the housing 34 is made of a member having voltage endurance, for example, a resin such as polysulphone, polyimide, or PET, in order to ensure specified voltage endurance of the cable 41.

[0019] The ultrasound transmission/reception portion 35 includes an ultrasound transducer 32, an acoustic lens 31, and a substrate 33, and is disposed in a space 34i located on a distal end side in the housing 34.

[0020] The ultrasound transducer 32 emits ultrasound to a region to be examined through the acoustic lens 31, and after the emission, receives ultrasound reflected back from the region to be examined through the acoustic lens 31 to convert the ultrasound into an electric signal.

[0021] The acoustic lens 31 has a function for collecting the ultrasound emitted from the ultrasound transducer 32 to the region to be examined so as not to diffuse, and emitting the ultrasound. Note that the surface of the acoustic lens 31 configures the ultrasound transmission/reception surface 35f.

[0022] The substrate 33 is electrically connected to the ultrasound transducer 32, and is connected with a distal end 41s of the cable 41, which is not covered with the insulation tube 42, on the distal end side of the ultrasound transducer cable 40.

[0023] According to such a configuration, the electric signal converted from the ultrasound by the ultrasound transducer 32 is transmitted to the ultrasound transducer cable 40 through the substrate 33.

[0024] In addition, as shown in FIGS. 2 and 3, a hole portion 34h for leading out the cable 41 having the distal end electrically connected to the substrate 33, from inside

of the housing 34 to the outside of the housing 34, is formed on the proximal end side of the housing 34, and the hole portion 34h is formed such that the space 34i inside the housing 34, in which the ultrasound transmission/reception portion 35 is provided, communicates with the proximal end surface 34e of the housing 34.

[0025] A distal end side of the insulation pipe 36 through which the cable 41 is inserted is fixed to the hole portion 34h so as to contact the inner circumference of the hole portion 34h. Note that the proximal end side of the insulation pipe 36 is located so as to be exposed outside the housing 34.

[0026] In addition, similarly as the insulation tube 42 and the housing 34, the insulation pipe 36 is made of a member having voltage endurance, for example, a resin such as polysulphone, polyimide, or PET, and has a function for preventing other metal members from contacting the cable 41, in order to ensure specified voltage endurance of the cable 41.

[0027] Note that, since other configurations of the ultrasound transducer unit 30 are the same as those of a well-known ultrasound transducer unit, the description thereof will be omitted.

[0028] The distal end side region of the cable 41, more specifically, as shown in FIG. 2, a region of the cable 41 which is more distal end side than the region inserted into the insulation pipe 36 is not covered with the insulation tube 42. That is, the insulation tube 42 covers the outer circumference of the part of the cable 41 led out rearward from a proximal end 36k of the insulation pipe 36, except for the connectors 45 provided on the proximal end side.

[0029] In addition, a distal end side region 42s of the insulation tube 42 covers the outer circumference of an exposed region 36r of the insulation pipe 36, which is exposed from the hole portion 34h, and as shown in FIG. 3, the distal end side region 42s is adhered and fixed to the outer circumference of the exposed region 36r with an adhesive 52 applied to a distal end side area between the outer circumference of the exposed region 36r and the distal end side region 42s.

[0030] Note that, in order to improve the adherence property of the distal end side region 42s with respect to the exposed region 36r, the area where the adhesive 52 is applied on the outer circumference of the exposed region 36r may be so formed as to have a rough surface.

[0031] In addition, as shown in FIG. 3, a sticky member 61, which is a liquid dripping prevention portion that prevents the adhesive 52 from flowing into the insulation tube 42 from the proximal end 36k of the insulation pipe 36 and contacting the cable 41, is provided between the outer circumference of the exposed region 36r and the distal end side region 42s so as to be located at an area which is more proximal end side than the area where the adhesive 52 is applied.

[0032] The sticky member 61 clings to the outer circumference of the exposed region 36r and the distal end side region 42s, and is made of a member having a higher

viscosity than the adhesive 52, for example, a member having a viscosity of 2 to 30 N, such as a double-stick tape made of silicone.

[0033] Note that the sticky member 61 just clings to the distal end side region 42s. Therefore, the distal end side region 42s is not damaged by the clinging of the sticky member 61.

[0034] Since other configurations of the ultrasound probe 50 are the same as those of a known ultrasound probe, the description thereof will be omitted.

[0035] Thus, in the present embodiment, the distal end side region 42s of the insulation tube 42 is adhered and fixed to the outer circumference of the exposed region 36r of the insulation pipe 36 with the adhesive 52, and the sticky member 61 is provided between the outer circumference of the exposed region 36r and the distal end side region 42s so as to be located at the area which is more proximal end side than the area where the adhesive 52 is applied.

[0036] According to such a configuration, since the sticky member 61 clings to the outer circumference of the exposed region 36r and the distal end side region 42s, there is no gap in a proximal end side area between the outer circumference of the exposed region 36r and the distal end side region 42s. Therefore, it is possible to surely prevent the adhesive 52 from flowing into the insulation tube 42 from the proximal end 36k of the insulation pipe 36 by the sticky member 61.

[0037] In addition, the insulation tube 42 and the insulation pipe 36 which cover the outer circumference of the cable 41 are made of the members having voltage endurance, thereby capable of sufficiently ensuring specified voltage endurance of the cable 41.

[0038] As described above, it is possible to provide the ultrasound probe 50 having a configuration capable of preventing the adhesive 52, which fixes the distal end side region 42s of the insulation tube 42 to the outer circumference of the exposed region 36r of the insulation pipe 36, from flowing out without increasing the length of the exposed region 36r while surely ensuring the electric safety of the cable 41 using the insulation pipe 36 and the insulation tube 42.

(Second Embodiment)

[0039] FIG. 4 is a partial cross-sectional view showing, in an enlarged manner, the vicinity of the proximal end side of the insulation pipe of the ultrasound probe according to the present embodiment.

[0040] The configuration of the ultrasound probe according to the second embodiment is different from that of the ultrasound probe according to the first embodiment shown in the above-described FIGS. 1 to 3 in that, instead of the sticky member, a projection portion, which is provided along the outer circumference of the proximal end of the insulation pipe, is used for the liquid dripping prevention portion. Accordingly, the same components as those in the first embodiment are attached with the same

reference numerals and the description thereof will be omitted.

[0041] As shown in FIG. 4, in the present embodiment, an outward flange-shaped projection portion 36t as a liquid dripping prevention portion is formed in a circumferential shape along the outer circumference of the proximal end of the exposed region 36r of the insulation pipe 36.

[0042] The projection portion 36t is provided between the outer circumference of the exposed region 36r and the distal end side region 42s so as to be located in the area which is more proximal end side than the area where the adhesive 52 is applied, and contacts the distal end side region 42s of the insulation tube 42.

[0043] Note that the projection portion 36t may be formed as a body separated from the insulation pipe 36, or may be formed integrally with the insulation pipe 36 by causing the outer circumference of the proximal end of the insulation pipe 36 to be bulged.

[0044] In addition, also in the present embodiment, the distal end side region 42s of the insulation tube 42 covers the outer circumference of the exposed region 36r of the insulation pipe 36 and is adhered and fixed to the outer circumference of the exposed region 36r with the adhesive 52 applied between the outer circumference of the area, which is more distal end side than the projection portion 36t, of the exposed region 36r and the distal end side region 42s.

[0045] The projection portion 36t is provided between the outer circumference of the exposed region 36r and the distal end side region 42s so as to be located on the more distal end side than the area where the adhesive 52 is applied, and blocks the adhesive 52 which attempts to flow out toward the proximal end side, thereby preventing the adhesive 52 from flowing into the insulation tube 42 from the proximal end 36k of the insulation pipe 36 and contacting the cable 41.

[0046] Note that a tapered surface 36v, which inclines toward the cable 41 side from the outer circumference to the inner circumference of the insulation pipe 36, is formed at the proximal end 36k of the insulation pipe 36.

[0047] The tapered surface 36v is formed by cutting off an edge portion of the end face of the outer circumference of the proximal end 36k of the insulation pipe 36, in order to prevent damage on the insulation tube 42 by the edge portion of the end face.

[0048] Note that other configurations of the ultrasound probe 50 are the same as those in the above-described first embodiment.

[0049] Thus, in the present embodiment, the distal end side region 42s of the insulation tube 42 is adhered and fixed to the outer circumference of the exposed region 36r of the insulation pipe 36 with the adhesive 52. In addition, the projection portion 36t formed in a circumferential shape along the outer circumference of the proximal end of the insulation pipe 36 is provided between the outer circumference of the exposed region 36r and the distal end side region 42s so as to be located in the

area which is more proximal end side than the area where the adhesive 52 is applied.

[0050] According to such a configuration, the projection portion 36t blocks the adhesive 52 flowing out toward the proximal end side on the outer circumference of the exposed region 36r, thereby capable of surely preventing the adhesive 52 from flowing into the insulation tube 42 from the proximal end 36k of the insulation pipe 36.

[0051] Note that other effects are the same as those in the above-described first embodiment.

(Third Embodiment)

[0052] FIG 5 is a partial cross-sectional view showing, in an enlarged manner, the vicinity of the proximal end side of the insulation pipe of the ultrasound probe according to the present embodiment.

[0053] The configuration of the ultrasound probe according to the third embodiment is different from the ultrasound probe according to the first embodiment shown in the above-described FIGS. 1 to 3, in that an absorbing member is used for the liquid dripping prevention portion, instead of the sticky member. Accordingly, the components as those in the first embodiment are attached with the same reference numerals, and the description thereof will be omitted.

[0054] As shown in FIG. 5, in the present embodiment, an absorbing member 62 as the liquid dripping prevention portion is provided between the outer circumference of the exposed region 36r and the distal end side region 42s so as to be located in the area which is more proximal end side than the region where the adhesive 52 is applied.

[0055] The absorbing member 62 has a function for absorbing the adhesive 52 flown out toward the proximal end side between the outer circumference of the exposed region 36r and the distal end side region 42s, and is made of an adhesive absorbing sheet.

[0056] Note that the adhesive absorbing sheet is a sheet-like porous member which can absorb fluid, and more specifically, a sponge such as polyurethane or polystyrene, or superabsorbent polymer such as sodium polyacrylate is used.

[0057] In addition, also in the present embodiment, the distal end side region 42s of the insulation tube 42 covers the outer circumference of the exposed region 36r of the insulation pipe 36, and is adhered and fixed to the outer circumference of the exposed region 36r with the adhesive 52 applied between the outer circumference of the area, which is more distal end side than the absorbing member 62, of the exposed region 36r and the distal end side region 42s.

[0058] The absorbing member 62 is provided between the outer circumference of the exposed region 36r and the distal end side region 42s so as to be located on the more proximal end side than the area where the adhesive 52 is applied. The absorbing member absorbs the adhesive 52 which attempts to flow out toward the proximal

end side on the outer circumference of the insulation pipe 36, thereby preventing the adhesive 52 from flowing into the insulation tube 42 from the proximal end 36k of the insulation pipe 36 and contacting the cable 41.

[0059] Since the absorbing member 62 is made of a flexible porous member, as described above, the absorbing member does not cause damage on the insulation tube 42 contacting the absorbing member.

[0060] Other configurations of the ultrasound probe 50 are the same as those in the above-described first embodiment.

[0061] Thus, in the present embodiment, the distal end side region 42s of the insulation tube 42 is adhered and fixed to the outer circumference of the exposed region 36r of the insulation pipe 36 with the adhesive 52, and the absorbing member 62 is provided between the outer circumference of the exposed region 36r and the distal end side region 42s so as to be located in the area which is more proximal end side than the area where the adhesive 52 is applied.

[0062] According to such a configuration, the absorbing member 62 absorbs the adhesive 52 flown out toward the proximal end side on the outer circumference of the exposed region 36r, thereby surely preventing the adhesive 52 from flowing into the insulation tube 42 from the proximal end 36k of the insulation pipe 36.

[0063] Note that other effects are the same as those in the first embodiment.

(Fourth Embodiment)

[0064] FIG. 6 is a partial cross-sectional view showing, in an enlarged manner, the vicinity of the proximal end side of the insulation pipe of the ultrasound probe according to the present embodiment.

[0065] The configuration of the ultrasound probe according to the fourth embodiment is different from the ultrasound probe according to the first embodiment shown in the above-described FIGS. 1 to 3 in that a groove formed at the exposed region of the insulation pipe is used as the liquid dripping prevention portion, instead of the sticky member. Therefore, the same components as those in the first embodiment are attached with the same reference numerals and the description thereof will be omitted.

[0066] As shown in FIG. 6, in the present embodiment, a groove portion 36m as a liquid dripping prevention portion in which the adhesive 52 is injected is formed on the outer circumference of the exposed region 36r by causing the outer circumference to be dented.

[0067] Note that the groove portion 36m may be formed in a circumferential shape along the outer circumference of the exposed region 36r, or may be partially formed along the outer circumference. In addition, in FIG. 6, the groove portion 36m is formed on the exposed region 36r so as to be located in the vicinity of the proximal end surface 34e of the housing 34. However, the groove portion 36m may be formed at any position as along as

the position is located on the exposed region 36r. Further, the groove portion 36m may be formed in plural numbers on the exposed region 36r so as to be located at positions separated from one another.

[0068] Furthermore, in the present embodiment, the distal end side region 42s of the insulation tube 42 directly covers the outer circumference of the exposed region 36r of the insulation pipe 36, and is adhered and fixed to the outer circumference of the exposed region 36r with the adhesive 52 injected in the groove portion 36m on the exposed region 36r.

[0069] The groove portion 36m prevents the adhesive 52 from flowing out toward the proximal end side on the outer circumference of the exposed region 36r by the adhesive 52 being injected in the groove portion between the outer circumference of the exposed region 36r and the distal end side region 42s, thereby preventing the adhesive 52 from flowing into the insulation tube 42 from the proximal end 36k of the insulation pipe 36 and contacting the cable 41.

[0070] Note that other configurations of the ultrasound probe 50 are the same as those in the above-described first embodiment.

[0071] Thus, in the present embodiment, the distal end side region 42s of the insulation tube 42 is adhered and fixed to the outer circumference of the exposed region 36r of the insulation pipe 36 with the adhesive 52, and the adhesive 52 is injected in the groove portion 36m formed on the outer circumference of the exposed region 36r.

[0072] According to such a configuration, extra adhesive 52 which is not used for adhering remains in the groove portion 36m. Therefore, it is possible to surely prevent the adhesive 52 from flowing into the insulation tube 42 from the proximal end 36k of the insulation pipe 36. Note that other effects are the same as those in the first embodiment.

[0073] The ultrasound probe 50 described above in the first to fourth embodiments are used in an ultrasound endoscope, for example.

[0074] FIG. 7 is a view showing an ultrasound endoscope apparatus provided with an ultrasound endoscope including ultrasound probe.

[0075] As shown in FIG. 7, an ultrasound endoscope apparatus 100 includes a main part configured by an ultrasound endoscope 1, a light source device 11, a video processor 12, an ultrasound observation apparatus 14, a suctioning pump 15, and a water-feeding tank 16.

[0076] The ultrasound endoscope 1 includes a main part configured by an elongated insertion portion 2 configured to be inserted into a body, an operation portion 3 provided at a proximal end of the insertion portion 2 and serving also as a grasping portion, a flexible universal cord 4 extended from the operation portion 3, and an endoscope connector 5 provided at an extension end of the universal cord 4.

[0077] The endoscope connector 5 is provided with a light source connector 6, an electric connector 7, an ul-

trasound connector 8, a suction cap 9, and an air/water feeding mouthpiece 10.

[0078] The light source device 11 that supplies illumination light is configured to be attachable to and detachable from the light source connector 6. In addition, the video processor 12 that performs various signal processings is configured to be attachable to and detachable from the electric connector 7 through a signal cable, not shown.

[0079] Furthermore, as described above, the ultrasound observation apparatus 14 is configured to be attachable to and detachable from the ultrasound connector 8, through an ultrasound cable 13, the ultrasound connector 8 being electrically connected with the connectors 45 provided on the proximal end side of the cable 41 of the ultrasound transducer cable 40 (regarding these components, see FIG 1).

[0080] In addition, the suctioning pump 15 is configured to be attachable to and detachable from the suction cap 9 through a suction tube, not shown. Furthermore, the water-feeding tank 16 is attachable to and detachable from the air/water feeding mouthpiece 10 through an air/water feeding tube, not shown.

[0081] The ultrasound observation apparatus 14 controls various operations of the ultrasound endoscope 1, for example, controls driving of the ultrasound transducer 32 and performs operation for generating a video signal by performing signal processing on an electric signal obtained by driving control of the ultrasound transducer 32.

[0082] Note that the video signal generated in the ultrasound observation apparatus 14 is outputted to a display device, not shown. As a result, an ultrasound image is displayed on the screen of the display device which receives the video signal.

[0083] The insertion portion 2 of the ultrasound endoscope 1 includes, in a linked manner, in the following order from the distal end side: a distal end rigid portion 21; a bending portion 22 configured to be bendable in up/down direction and left/right direction, for example; and a flexible tube portion 23 which is long and has flexibility. Note that the above-described ultrasound transducer unit 30 is located on the more distal end side than the distal end rigid portion 21 and fixed to the distal end rigid portion 21.

[0084] The operation portion 3 is provided with bending operation knobs 25, 26 that perform bending operation of the bending portion 22. In addition, a treatment instrument insertion port 27, which introduces the treatment instrument into a body through a treatment instrument insertion conduit, not shown, provided in the insertion portion 2 and the operation portion 3, is provided to the operation portion 3 so as to be located at a position closer to the insertion portion 2.

[0085] The video processor 12 performs signal processing on the electric signal transmitted from an image pickup unit, not shown, provided in the distal end rigid portion 21, to thereby generate a standard video signal, and output the video signal to the display device,

not shown, to display an endoscopic observation image on the screen of the display device.

[0086] If the ultrasound probe 50 according to the above-described first to fourth embodiments is applied to the ultrasound endoscope 1 thus configured, there is no need for increasing the length of the insulation pipe 36 in order to prevent the adhesive 52 from flowing out. Therefore, it is possible to form the distal end rigid portion 21, the length of which is short, which improves the operability.

[0087] In addition, since the adhesive 52 is prevented from flowing out, it is possible to surely prevent the bending of the bending portion 22 from being interfered with as a result that the adhesive 52 adheres to the region of the cable 41 located in the bending portion 22 and the adhered adhesive 52 is cured.

[0088] Note that description has been made above by taking the cases in which the ultrasound probe 50 is applied to the ultrasound endoscope 1 as examples. However, the ultrasound probe 50 may be provided in an instrument other than the ultrasound endoscope 1, and also in such a case, it is needless to say that it is possible to obtain the same effects as those in the case where the ultrasound probe 50 is applied to the ultrasound endoscope 1.

[0089] The present application is filed claiming the priority of Japanese Patent Application No. 2011-256430 filed in Japan on November 24, 2011, and the above described disclosure is incorporated by reference in the present description, claims and drawings.

Claims

1. An ultrasound probe comprising:

- an ultrasound transmission/reception portion having an ultrasound transmission/reception surface for transmitting and receiving ultrasound;
- a cable having a distal end electrically connected to the ultrasound transmission/reception portion;
- a housing configured to hold the ultrasound transmission/reception portion such that the ultrasound transmission/reception surface is exposed;
- a hole portion provided to the housing and configured to lead out the cable from inside of the housing;
- an insulation pipe through which the cable is inserted, the insulation pipe having a distal end side fixed to the hole portion in a state of contacting an inner circumference of the hole portion, and a proximal end side exposed outside the housing;
- an insulation tube configured to cover an outer circumference of an exposed region of the insu-

- lation pipe which is exposed from the hole portion and an outer circumference of the cable led out from a proximal end of the insulation pipe; an adhesive configured to adhere the outer circumference of the exposed region of the insulation pipe and a distal end side region of the insulation tube covering the outer circumference of the exposed region; and
a liquid dripping prevention portion disposed between the exposed region of the insulation pipe and the distal end side region of the insulation tube, together with the adhesive, the liquid dripping prevention portion being configured to prevent the adhesive from flowing out from the proximal end of the insulation pipe and contacting the cable.
2. The ultrasound probe according to claim 1, wherein the liquid dripping prevention portion is a sticky member having a higher viscosity than the adhesive, the sticky member being configured to cling to the distal end side region of the insulation tube together with the adhesive, and located on a more proximal end side than the adhesive between the exposed region of the insulation pipe and the distal end side region of the insulation tube.
3. The ultrasound probe according to claim 1, wherein the liquid dripping prevention portion is a projection portion provided along an outer circumference of the proximal end of the insulation pipe and configured to block the adhesive flown out toward the proximal end side, the projection portion being located on a more proximal end side than the adhesive between the exposed region of the insulation pipe and the distal end side region of the insulation tube.
4. The ultrasound probe according to claim 3, wherein the projection portion is formed integrally with the insulation pipe by causing the outer circumference of the proximal end of the insulation pipe to be bulged.
5. The ultrasound probe according to claim 1, wherein the liquid dripping prevention portion is an absorbing member for absorbing the adhesive flown out toward the proximal end side, the absorbing member being located on a more proximal end side than the adhesive between the exposed region of the insulation pipe and the distal end side region of the insulation tube.
6. The ultrasound probe according to claim 1, wherein the liquid dripping prevention portion is a groove portion in which the adhesive is injected, the groove portion being formed on the outer circumference of the exposed region of the insulation pipe by causing the outer circumference to be dented.
7. The ultrasound probe according to claim 6, wherein the groove portion is formed in a circumferential shape on the outer circumference of the insulation pipe.

FIG.1




FIG.2




FIG.3




FIG.4




FIG.5




FIG.6





FIG.7



INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP2012/076272

A. CLASSIFICATION OF SUBJECT MATTER A61B8/12(2006.01) i		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols) A61B8/12		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Jitsuyo Shinan Koho 1922-1996 Jitsuyo Shinan Toroku Koho 1996-2012 Kokai Jitsuyo Shinan Koho 1971-2012 Toroku Jitsuyo Shinan Koho 1994-2012		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	JP 2009-28109 A (Olympus Medical Systems Corp.), 12 February 2009 (12.02.2009), paragraphs [0038], [0041] to [0042]; fig. 3 (Family: none)	1-7
A	JP 2005-237611 A (Pentax Corp.), 08 September 2005 (08.09.2005), paragraphs [0002], [0018] to [0020]; fig. 1, 4 (Family: none)	1-7
☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "I" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search 20 December, 2012 (20.12.12)		Date of mailing of the international search report 08 January, 2013 (08.01.13)
Name and mailing address of the ISA/ Japanese Patent Office		Authorized officer
Facsimile No.		Telephone No.

Form PCT/ISA/210 (second sheet) (July 2009)

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- JP 2009028109 A [0004] [0005]
- JP 2011256430 A [0089]

专利名称(译)	超声波探头		
公开(公告)号	EP2644103A4	公开(公告)日	2013-11-27
申请号	EP2012851965	申请日	2012-10-11
[标]申请(专利权)人(译)	奥林巴斯医疗株式会社		
申请(专利权)人(译)	奥林巴斯医疗系统股份有限公司.		
当前申请(专利权)人(译)	奥林巴斯医疗系统股份有限公司.		
[标]发明人	IRIE KEI		
发明人	IRIE, KEI		
IPC分类号	A61B8/12 A61B1/00 A61B8/00		
CPC分类号	A61B8/4444 A61B1/0011 A61B1/00114 A61B8/12 A61B8/445		
优先权	2011256430 2011-11-24 JP		
其他公开文献	EP2644103A1 EP2644103B1		
外部链接	Espacenet		

摘要(译)

一种超声波探头，包括：超声波发射/接收部分；电缆41；住房34；壳体34的孔部分34h；绝缘管36，其近端侧暴露在壳体34的外部；绝缘管42覆盖绝缘管36的暴露区域36r的外周和电缆41的外周；粘合剂52，其构造为粘合暴露区域36r的外周和绝缘管42的远端侧区域42s；粘合构件61与粘合剂52一起设置在暴露区域36r和远端侧区域42s之间。