



(19) **United States**

(12) **Patent Application Publication**
Pagoulatos et al.

(10) **Pub. No.: US 2019/0105019 A1**
(43) **Pub. Date: Apr. 11, 2019**

(54) **SYSTEM AND METHOD FOR FUSING
ULTRASOUND WITH ADDITIONAL
SIGNALS**

A61B 5/044 (2006.01)
A61B 5/0404 (2006.01)
A61B 5/04 (2006.01)
A61B 5/0408 (2006.01)
A61B 5/0432 (2006.01)

(71) Applicant: **EchoNous, Inc.**, Redmond, WA (US)

(72) Inventors: **Nikolaos Pagoulatos**, Kirkland, WA (US); **Ramachandra Pailoor**, Woodinville, WA (US); **Greg Nieminen**, Bothell, WA (US); **Terry Doherty**, Snohomish, WA (US); **Ron Broad**, Arlington, WA (US); **Shelby Brunke**, Sammamish, WA (US)

(52) **U.S. Cl.**
CPC *A61B 8/5284* (2013.01); *A61B 7/04* (2013.01); *A61B 5/0006* (2013.01); *A61B 5/14551* (2013.01); *A61B 8/4472* (2013.01); *A61B 8/4427* (2013.01); *A61B 5/0432* (2013.01); *A61B 5/044* (2013.01); *A61B 5/0404* (2013.01); *A61B 8/4416* (2013.01); *A61B 8/463* (2013.01); *A61B 5/04012* (2013.01); *A61B 5/04085* (2013.01); *A61B 5/0205* (2013.01)

(21) Appl. No.: **15/969,632**

(22) Filed: **May 2, 2018**

Related U.S. Application Data


(60) Provisional application No. 62/568,709, filed on Oct. 5, 2017.

Publication Classification

(51) **Int. Cl.**
A61B 8/08 (2006.01)
A61B 7/04 (2006.01)
A61B 5/00 (2006.01)
A61B 5/1455 (2006.01)
A61B 8/00 (2006.01)
A61B 5/0205 (2006.01)

(57) **ABSTRACT**

Systems, methods and devices for providing combined ultrasound, electrocardiography, and auscultation data are provided. One such system includes an ultrasound sensor, an electrocardiogram (EKG) sensor, an auscultation sensor, and a computing device. The computing device includes memory and a processor, and the processor receives signals from the ultrasound sensor, the EKG sensor, and the auscultation sensor. Artificial intelligence techniques may be employed for automatically analyzing the data obtained from the ultrasound sensor, the EKG sensor, and the auscultation sensor and producing a clinically-relevant determination based on a combined analysis of the data.






FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4




FIG. 5




FIG. 6




FIG. 7

SYSTEM AND METHOD FOR FUSING ULTRASOUND WITH ADDITIONAL SIGNALS

BACKGROUND

Technical Field

[0001] The present application pertains to physiological sensing systems and methods, and more particularly to such systems and methods for acquiring and displaying ultrasound, electrocardiography, and auscultation data.

Description of the Related Art

[0002] Ultrasound imaging is typically performed in a clinical setting, by trained ultrasound experts, utilizing ultrasound systems that are specifically designed to acquire ultrasound data. Similarly, electrocardiography (EKG) is typically performed in a clinical setting by trained experts and utilizing equipment that is specifically designed for acquiring electrocardiography data. Auscultation data is typically acquired by a physician or other clinician utilizing a stethoscope.

[0003] Acquisition of these different types of clinical data, i.e., ultrasound data, EKG data, and auscultation data, is thus conventionally performed utilizing separate pieces of equipment, and often in separate patient visits or separate environments.

BRIEF SUMMARY

[0004] The present disclosure provides systems, methods and devices for acquiring or providing combined ultrasound, electrocardiography, and auscultation data. All three or any combination of two signals may be concurrently obtained by a single computing device connected to an ultrasound sensor, an electrocardiogram (EKG) sensor, and an auscultation sensor. The obtained signals may be synchronized with one another, such that the data obtained from the various sensors may be stored in a time-aligned manner. Alternatively or additionally, the obtained signals may be displayed in synchronization. Alternatively or additionally, the computing device may be configured such that each signal is obtained and displayed separately. Artificial intelligence techniques may be utilized to analyze the signals received from the ultrasound sensor, EKG sensor, and auscultation sensor to determine whether the signals, individually or in combination with one another, indicate one or more pathologies.

[0005] In at least one embodiment, a system is provided that includes an ultrasound sensor, an EKG sensor, an auscultation sensor, and a computing device. The computing device includes memory and a processor, and the processor is configured to receive and process signals from the ultrasound sensor, the EKG sensor, and the auscultation sensor.

[0006] In another embodiment, a handheld device is provided that includes a processor, a memory coupled to the processor, an ultrasound sensor, an EKG sensor, and an auscultation sensor. The ultrasound sensor, EKG sensor, and auscultation sensor are positioned on a sensing surface of the handheld device. Each of the ultrasound sensor, the EKG sensor, and the auscultation sensor are communicatively coupled to the processor.

[0007] In another embodiment, a method is provided that includes receiving by a computing device, ultrasound data, EKG data, and auscultation data; synchronizing at least two

of the received ultrasound data, EKG data, and auscultation data; and storing the ultrasound data, EKG data, and auscultation data in memory.

[0008] In yet another embodiment, a system is provided that includes a computing device and an artificial intelligence (AI) data recognition module. The computing device is configured to acquire ultrasound data, EKG data, and auscultation data. The AI data recognition module is configured to receive the acquired ultrasound data, EKG data, and auscultation data and to automatically assess the data to produce a clinically-relevant determination based on a combined analysis of the data (e.g., automatically determine whether the received data indicates one or more pathologies).

[0009] In another embodiment, a handheld probe is provided that includes an ultrasound sensor positioned on a sensing surface of the probe, and an electrocardiogram (EKG) sensor positioned on the sensing surface of the probe.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0010] FIG. 1 is a block diagram illustrating a system for acquiring, synchronizing, and displaying a combination of ultrasound, electrocardiography, and auscultation signals, in accordance with one or more embodiments of the present disclosure.

[0011] FIG. 2 is a block diagram illustrating a system for acquiring, synchronizing, and displaying a combination of ultrasound, electrocardiography, and auscultation signals, in accordance with one or more embodiments of the present disclosure.

[0012] FIG. 3A is a perspective view of a probe that may be used in the system shown in FIG. 2, in accordance with one or more embodiments of the present disclosure.

[0013] FIG. 3B is a front view of the probe shown in FIG. 3A, in accordance with one or more embodiments of the present disclosure.

[0014] FIG. 4 is a block diagram illustrating a synchronization module that synchronizes data acquired from an auscultation sensor, an EKG sensor, and an ultrasound sensor, in accordance with one or more embodiments of the present disclosure.

[0015] FIG. 5 is a pictorial diagram illustrating synchronous display of acquired ultrasound data, EKG data, and auscultation data, in accordance with one or more embodiments of the present disclosure.

[0016] FIG. 6 is a block diagram illustrating a system for acquiring ultrasound, EKG, and auscultation signals that includes an artificial intelligence (AI) data recognition module, in accordance with one or more embodiments of the present disclosure.

[0017] FIG. 7 is a block diagram illustrating training of the AI data recognition module shown in FIG. 6, in accordance with one or more embodiments.

DETAILED DESCRIPTION

[0018] Three primary techniques used extensively in medicine for physiological assessment, e.g., of the cardiothoracic cavity, include sonography, auscultation, and electrocardiography. Each technique provides different kinds of information usable to assess the anatomy and physiology of the organs present in a region of interest, e.g., the cardiothoracic cavity.

[0019] Medical ultrasound imaging (sonography) has been one of the most effective methods for examining both the heart and the lungs. Ultrasound imaging provides anatomical information of the heart as well as qualitative and quantitative information on blood flow through valves and main arteries such as the aorta and pulmonary artery. One significant advantage of ultrasound imaging is that, with its high frame rate, it can provide dynamic anatomical and blood flow information which is vital for assessing the condition of the heart which is always in motion. Combined with providing blood flow information, ultrasound imaging provides one of the best available tools for assessing the structure and function of heart chambers, valves, and arteries/veins. Similarly, ultrasound imaging can assess fluid status in the body and is the best tool in assessing pericardial effusion (fluid around the heart).

[0020] In the case of lungs, ultrasound imaging provides information on the anatomical structure of the lungs with the ability to show specific imaging patterns associated with various lung diseases and with an ability to assess fluid status around the lung and within individual compartments of the lung including the assessment of pericardial effusion.

[0021] Auscultation allows for assessing the physiological condition and function of organs such as the heart and lungs by capturing audible sounds that are produced by or otherwise associated with these organs. The condition and function of these organs, or other organs as the case may be, can be evaluated based on clinical information indicating how different sounds are associated with various physiological phenomena and how the sounds change for each pathological condition.

[0022] Electrocardiography (EKG or ECG) is focused on the heart by capturing the electrical activity of the heart as it is related to the various phases of the cardiac cycle. The condition and function of the heart may be evaluated based on clinical knowledge indicating how the electrical activity of the heart changes based on various pathological conditions.

[0023] The present disclosure provides systems, devices, and methods in which these three types of signals (i.e., auscultation, EKG, and ultrasound signals) are acquired and displayed (possibly in a synchronous manner) via one or more audiovisual outputs. Providing a combination of auscultation, EKG, and ultrasound data significantly enhances the ability of doctors and others to accurately and efficiently assess the physiological condition of a patient, especially of the patient's heart and lungs. Furthermore, by digitizing all three signals, analysis of such signals using digital signal processing is enabled, thereby allowing for implementation of various signal and image processing algorithms that can assess the signal data in combination. Such algorithms may include algorithms that are based on machine learning and pattern recognition to detect patterns in each of the three signals that are known to be associated with certain disease conditions. When combined and jointly evaluated, the three signals may provide more insight into the physiological condition of a patient than would otherwise be provided by separate, individual assessment of each of the signals. That is, the combined acquisition and display of these signals provides additional information, particularly if the signals are synchronized, which ultimately results in significantly better sensitivity and specificity than would be obtained using any one signal alone. By combining these three signals in a synchronous manner, as described herein, analysis of the

signals using machine learning is facilitated, including advanced methods such as deep learning, which provides a clear path for capturing expert physician knowledge associated with all three signals into the systems and devices. This results in the ability of non-expert physicians and others to assess the physiological condition of a patient quickly with high sensitivity and specificity.

[0024] The systems and devices provided by the present disclosure allow for ultrasound, EKG, and auscultation sensors to be connected to a single computing device, digitized, stored in memory, and visualized through a user interface or display showing all three signals to the user, possibly in real-time as they are acquired. Furthermore, modules and methods are provided for synchronizing all three signals as they are acquired such that dynamic phenomena in the patient are properly captured and are time aligned for all three signals. The synchronization of the three signals has clinical importance in that, when physiological phenomena are properly represented by all three different signals and shown in a time-aligned manner, the information revealed in the ultrasound, audible sound, and electrical signals reflects conditions associated with the physiology at the same moment of time.

[0025] FIG. 1 is a block diagram illustrating a system 10 for acquiring ultrasound, electrocardiographic, and auscultation signals. The system 10 includes a computing device 12 (also referred to as a "medical device"), at least one auscultation sensor 14, at least one electrocardiogram (EKG) sensor 16, and at least one ultrasound sensor 18. One or more additional sensors 26 may further be included, for example a pulse oximeter sensor, although embodiments provided herein are not limited thereto. For example, the additional sensors 26 may include one or more of a gyroscope, a pressure sensor, a motion sensor, a temperature sensor, an EEG sensor, or any other type of sensor for sensing a physiological state, condition, or response of a patient, an environment around the patient, or a state or condition of the system 10.

[0026] The auscultation sensor 14, EKG sensor 16, and ultrasound sensor 18 are each communicatively coupled to the computing device 12 by a wired or wireless communication channel. The computing device 12 acquires, preferably digitizes, and processes the three types of signals, e.g., auscultation, EKG, and ultrasound signals.

[0027] The auscultation sensor 14 may be any sensor that detects internal body sounds of a patient, including, for example, body sounds associated with the circulatory, respiratory, and gastrointestinal systems. The auscultation sensor 14 has a sensor surface that may be placed in contact with a patient's skin in order to detect sound signals through the skin surface. The auscultation sensor 14 may be an electronic or digital stethoscope, and may include amplification and signal processing circuitry for amplifying and processing sensed signals, as may be known in the relevant field.

[0028] The EKG sensor 16 may be any sensor that detects electrical activity of a patient's heart, as may be known in the relevant field. For example, the EKG sensor 16 may include any number of electrodes, which in operation are placed on a patient's skin and used to detect electrical changes in the patient that are due to the heart muscle's pattern of depolarizing and repolarizing during each heart-beat.

[0029] The ultrasound sensor 18 includes a transducer configured to transmit an ultrasound signal toward a target

structure in a region of interest in the patient. The transducer is further configured to receive echo signals returning from the target structure in response to transmission of the ultrasound signal. To that end, the transducer may include transducer elements that are capable of transmitting an ultrasound signal and receiving subsequent echo signals. In various embodiments, the transducer elements may be arranged as elements of a phased array. Suitable phased array transducers are known in the art.

[0030] The transducer array of the ultrasound sensor **18** may be a one-dimensional (1D) array or a two-dimensional (2D) array of transducer elements. The transducer array may include piezoelectric ceramics, such as lead zirconate titanate (PZT), or may be based on microelectromechanical systems (MEMS). For example, in various embodiments, the ultrasound sensor **18** may include piezoelectric micro-machined ultrasonic transducers (PMUT), which are micro-electromechanical systems (MEMS)-based piezoelectric ultrasonic transducers, or the ultrasound sensor **18** may include capacitive micromachined ultrasound transducers (CMUT) in which the energy transduction is provided due to a change in capacitance.

[0031] As shown in FIG. 1, the auscultation sensor **14**, the EKG sensor **16**, and the ultrasound sensor **18** may each be separately coupled to the computing device **12** via respective wired or wireless channels. For example, each of the auscultation sensor **14**, the EKG sensor **16**, and the ultrasound sensor **18** may be electrically and communicatively coupled to the computing device **12** by respective cables. In the case of the EKG sensor **16**, which may include any number of electrodes, the electrodes may be coupled to the computing device **12** by leads. For example, the EKG sensor **16** may be a 10-electrode, 12-lead EKG sensor, although any EKG sensing configuration may be utilized as the EKG sensor **16** in accordance with the present disclosure. For example, the probe **140** shown in FIGS. 3A and 3B, described in greater detail below, includes an EKG sensor **116** with three electrodes.

[0032] In operation, a user of the system **10** may place each of the sensors **14**, **16**, **18** in a desired location in order to acquire signals, preferably simultaneously or during overlapping time intervals, from each of the sensors. For example, the EKG sensor **16** may include multiple electrodes, which may be placed in a suitable configuration on a patient's body, with the electrodes coupled to the computing device **12** by one or more leads. The user may place the auscultation sensor **14** at any desired location on the patient's skin, and similarly, may position the ultrasound sensor **18** as desired in order to obtain signals of interest. Accordingly, in operation, the computing device **12** may receive signals from each of the auscultation sensor **14**, the EKG sensor **16**, and the ultrasound sensor **18**, preferably as the signals are each obtained.

[0033] The computing device **12** includes various electronics and a processor (referred to herein, collectively, as "electronics and processor **20**" or in some cases simply "processor **20**"). The electronics and processor **20** may include processing circuitry and driving circuitry. In part, the processing circuitry, or processor, controls the acquisition of signals from the auscultation sensor **14**, the EKG sensor **16**, and the ultrasound sensor **18**.

[0034] For example, the electronics and processor **20** may include processing circuitry that controls the transmission of an ultrasound signal from the transducer elements of the

ultrasound sensor **18**, and driving circuitry that is operatively coupled to the transducer elements for driving the transmission of the ultrasound signal. The driving circuitry may drive the transmission of the ultrasound signal in response to a control signal received from the processing circuitry. The computing device **12** may further include a power supply that provides power to the electronics and processor **20**, for example, to power the driving circuitry for transmission of the ultrasound signal. The electronics and processor **20** may similarly include processing circuitry that controls the acquisition of auscultation signals from the auscultation sensor **14**, and controls the acquisition of EKG signals from the EKG sensor **16**.

[0035] Additionally, the electronics and processor **20** may include signal processing circuitry, such as filters, amplifiers, preconditioning and digitization circuitry, and the like, which process the signals received from the auscultation sensor **14**, the EKG sensor **16**, and the ultrasound sensor **18**. In particular, the electronics and processor **20** may include or otherwise implement a synchronization module for synchronizing the received signals, as will be discussed in further detail with respect to FIG. 4.

[0036] The electronics and processor **20** may include one or more application specific integrated circuits (ASICs) for providing or implementing the operations of the computing device **12** as described herein.

[0037] The computing device **12** shown in FIG. 1 further includes a memory **22** and a display **24**. The memory **22** may be or include any computer-readable storage medium, including, for example, read-only memory (ROM), random access memory (RAM), flash memory, hard disk drive, optical storage device, magnetic storage device, electrically erasable programmable read-only memory (EEPROM), organic storage media, or the like. The memory **22** is coupled to the electronics and processor **20**, which may execute programmed instructions that are stored in the memory **22** to perform the functions of the computing device **12** as described herein. Moreover, the memory **22** may store the signals acquired by the computing device **12**. The signals may be stored in the memory **22** in a synchronized manner, or with associated information for synchronizing the signals, as will be discussed in further detail below with respect to FIG. 4.

[0038] The display **24** is an output interface that provides visual and/or audible information to a user of the computing device **12**. The display **24** and/or the computing device **12** may include or be coupled to one or more speakers to provide audible information to the user. The display **24** may use, for example, any type of display technology including, but not limited to, an LED display technology. The display **24** may display signals acquired from the auscultation sensor **14**, the EKG sensor **16**, and the ultrasound sensor **18**. More particularly, the display **24** may be used to display the signals and/or images acquired from the auscultation sensor **14**, the EKG sensor **16**, and the ultrasound sensor **18** in a synchronized manner, as will be discussed in further detail below with respect to FIGS. 4 and 5. In some embodiments, the display **24** may provide an input interface, such as a touch screen capable of receiving input from a user that touches the screen. In some embodiments, the computing device **12** may include one or more buttons, knobs, switches, and the like, capable of receiving input from a user of the computing device **12**.

[0039] FIG. 2 is a block diagram illustrating a system 100 for acquiring ultrasound, electrocardiographic, and auscultation signals. The system 100 is similar to the system 10 in many respects; however, a main difference between the system 100 of FIG. 2 and the system 10 of FIG. 1 is that, in the system 100, the auscultation sensor 114, the EKG sensor 116, and the ultrasound sensor 118 are all included in a probe 140, which is communicatively coupled to a computing device 112, e.g., by any wired or wireless communication channel. For example, the probe 140 may be coupled to the computing device 112 by one or more electrical cables.

[0040] Additionally, the probe 140 may itself include electronics and processor 130, which may be substantially the same as the electronics and processor 20 of the computing device 12 of FIG. 1. For example, the electronics and processor 130 in the probe 140 may include processing circuitry and driving circuitry that controls the acquisition of signals from the auscultation sensor 114, the EKG sensor 116, and the ultrasound sensor 118. In implementations where the probe 140 includes a power source, the probe may be operated separate from the computing device 112 to acquire ultrasound, electrocardiographic, and auscultation signal data from a patient, and later if desired, be communicatively coupled to the computing device 112 to upload the acquired signal data for further processing.

[0041] In some implementations, the probe 140 may be configured to use the electronics and processor 130 when the probe is operating separate from the computing device 112, but when the probe 140 is coupled (or “docked”) to the computing device 112, the probe 140 may use some or all of the electronics and processor 120 in the computing device 112 in place of its own electronics and processor 130. This may be advantageous in cases where the electronics and processor 120 in the computing device 112 employs higher-quality components, such as a quieter power supply, more precise oscillator, and/or improved heat dissipation elements, or provides greater computational resources for generating, receiving, and/or processing the acquired signals or signal data.

[0042] For example, U.S. patent application Ser. No. 15/446,290, assigned to the assignee of the present disclosure and incorporated by reference herein, describes an ultrasound system that comprises an ultrasound probe and a docking station. The ultrasound probe is preferably a portable ultrasound probe, such as the handheld probe, that includes one or more first transducer elements that transmit an ultrasound signal toward a target structure in a region of interest. The ultrasound probe also includes processing circuitry that controls transmission of the ultrasound signal from the one or more first transducer elements and driving circuitry operatively coupled to the one or more first transducer elements and the processing circuitry. The driving circuitry drives the transmission of the ultrasound signal by the one or more first transducer elements in response to a control signal received from the processing circuitry. The ultrasound probe further includes one or more second transducer elements that receive echo signals returning from the target structure in response to transmission of the ultrasound signal, and a power supply that provides power to the driving circuitry for transmission of the ultrasound signal in at least a pulsed wave mode of operation.

[0043] The docking station includes an interface that allows coupling to the ultrasound probe. The docking station also includes circuitry that electrically couples to the ultra-

sound probe via the interface and enhances the ultrasound functionality of the ultrasound probe. In at least one embodiment, the docking station is provided separate from the ultrasound probe. In various embodiments, the circuitry in the docking station enhances the ultrasound functionality of the ultrasound probe by employing higher-quality components, such as a quieter power supply, oscillator, and/or heat dissipation elements or by providing greater computational resources for generating, receiving, and/or processing ultrasound signals or data.

[0044] The system described in U.S. patent application Ser. No. 15/446,290 may be adapted to further include auscultation and EKG signal acquisition as described herein, and provide a combined probe 140 according to the principles of the present disclosure. The auscultation and EKG signal acquisition of the combined probe 140 may similarly be enhanced when the combined probe 140 is electrically coupled or docked to the computing device 112.

[0045] Further, the probe 140 may include memory 132 that is coupled to the electronics and processor 130. The memory 132 may store the signals acquired by, and possibly digitized by, the electronics and processor 130. The auscultation, EKG, and ultrasound signal data may be stored in a synchronized manner, or with associated information for synchronizing the signals, as described herein.

[0046] The auscultation sensor 114, EKG sensor 116, and ultrasound sensor 118 may be similar to the auscultation sensor 14, EKG sensor 16, and ultrasound sensor 18 described above with respect to the system 10 of FIG. 1.

[0047] However, some implementations may include certain differences as described herein with reference to FIG. 2 and FIGS. 3A and 3B.

[0048] FIG. 3A is a perspective view of at least one embodiment of the probe 140, and FIG. 3B is a front view of the embodiment shown in FIG. 3A, which illustrates a sensing surface 160 of the probe 140.

[0049] As shown in FIG. 3B, the auscultation sensor 114, EKG sensor 116, and ultrasound sensor 118 may be disposed on the sensing surface 160 of the probe. For example, the ultrasound sensor 118 (which may include an array of ultrasound transducers) may form a central portion of the sensing surface 160, while the EKG sensor 116 and the auscultation sensor 114 may be positioned on portions of the sensing surface 160 that extend outwardly from the central portion on which the ultrasound sensor 118 is positioned.

[0050] The auscultation sensor 114 may otherwise be substantially the same as the auscultation sensor 14 shown in FIG. 1, and may be any sensor for detecting internal body sounds of a patient, including, for example, body sounds associated with the circulatory, respiratory, and gastrointestinal systems. A plurality of auscultation sensors 114 may be provided on the sensing surface 160 of the probe 140. In such a case, one or more auscultation sensors 114 may be positioned on either or both sides of the ultrasound sensor 118. Any number of auscultation sensors 114 may be included in the probe 140 and positioned, for example, on the sensing surface 160.

[0051] The EKG sensor 116 may be any sensor for detecting the electrical activity of a patient’s heart, as may be known in the relevant field. As shown in FIG. 3B, the EKG sensor 116 may include a plurality of electrodes arranged on the sensing surface 160 of the probe 140. In such a case, one or more EKG sensors 116 may be positioned on either or both sides of the ultrasound sensor 118. The EKG sensors

116 may preferably be positioned such that at least one EKG sensor **116** is positioned on each side of the ultrasound sensor **118**, which provides a greater distance between the EKG electrodes.

[0052] The ultrasound sensor **118** includes a transducer, which may include transducer elements that are capable of transmitting an ultrasound signal and receiving subsequent echo signals as described above with respect to the ultrasound sensor **18** of FIG. 1.

[0053] In use, the sensing surface **160** of the probe **140** may be placed on a patient's skin, and auscultation, EKG, and ultrasound signals may be received, preferably simultaneously, by the probe **140**. The acquisition of signals may be controlled by the electronics and processor **130** and stored in the memory **132** in the probe **140**, in a manner that is the same or similar to that described above with respect to the electronics and processor **20** and memory **22** of FIG. 1.

[0054] In some embodiments, only the ultrasound sensor **118** and the EKG sensor **116** may be positioned on the sensing surface **160** of the probe **140**, while in other embodiments, the auscultation sensor **114** may further be positioned on the sensing surface **160** of the probe **140**.

[0055] Returning to FIG. 2, the computing device **112** shown in FIG. 2 includes electronics and processor **120** and memory **122**. The electronics and processor **120** and memory **122** of the computing device **112** may control the acquisition of signals by the probe **140**, in addition to or as an alternative to the acquisition of signals performed by the electronics and processor **130** and memory **132** of the probe. The electronics and processor **120** and memory **122** of the computing device **112** may also control operations of the computing device **112**. For example, the electronics and processor **120** and memory **122** may receive signals from the probe **140**, and cause the computing device **112** to display the signals and/or images associated with the signals on the display **124**.

[0056] The computing device **112** may be, for example, a tablet computer, a PC or workstation computer, a mobile computing device such as a smartphone, or the like. The computing device **112** may communicate with the probe **140** over any wired or wireless communications channel, and may thus receive the signals acquired, processed and/or stored by the probe **140**, and may display such signals or images associated with or derived from such signals.

[0057] In one or more embodiments, the probe **140** may include a display for displaying the acquired signals, images or clinical parameters associated with or derived from the acquired signals. In such a case, the computing device **112** may not be needed in order to acquire, process and display signals from the auscultation sensor **114**, EKG sensor **116**, and ultrasound sensor **118**, as this may all be performed by the probe **140** itself.

[0058] FIG. 4 is a block diagram illustrating a synchronization module **400** that synchronizes signals or data that are simultaneously acquired from any two or more of an auscultation sensor, an EKG sensor, and an ultrasound sensor. In one or more embodiments, the synchronization module **400** may synchronize signals or data that is acquired from all three of the auscultation sensor, EKG sensor, and ultrasound sensor, as will be described herein. However, it will be readily appreciated that the embodiments provided herein are not limited to synchronization of signals from all three sensors, as the synchronization module may synchronize signals from any two or more of such sensors. With regard

to the system **10** of FIG. 1, the synchronization module **400** may be included in or otherwise be accessible by the electronics and processor **20** and memory **22**. In the system **100** of FIG. 2, the synchronization module **400** may be included in or otherwise accessible by the electronics and processor **130** and memory **132** in the probe **140** and/or may be included in or accessible by the electronics and processor **120** and memory **122** in the computing device **112**.

[0059] As shown in FIG. 4, auscultation data, EKG data, and ultrasound data, which are derived from signals received by the auscultation sensor, EKG sensor, and ultrasound sensor, respectively, are provided to the synchronization module **400**. In one embodiment, the synchronization module **400** synchronizes the auscultation data, EKG data, and ultrasound data by appending or associating time stamp information to each of these data. For example, the synchronization module **400** may include a clock (or otherwise have access to a clock) and may time stamp the data with time stamp information that indicates a time of receiving the data. The time stamp information may indicate a time with respect to a reference time, such as UTC time.

[0060] The synchronization module **400** may be coupled to memory (e.g., memory **22** of FIG. 1, or memory **122** or **132** of FIG. 2), such that the output data may be stored in the memory in a synchronized manner. For example, the data may be stored in the memory along with the associated time stamp information provided by the synchronization module **400**. Alternatively or additionally, the synchronization module **400** may provide the auscultation data, EKG data, and ultrasound data to a remotely-located memory for storage in a synchronized manner.

[0061] In another embodiment, the synchronization module **400** does not append a time stamp to the received data, but instead associates the auscultation data, EKG data, and ultrasound data that are acquired at the same time and jointly stores the data in a combined manner in memory locations that are ordered or that may be retrieved based on the sequence in which the data is received. For example, auscultation data, EKG data, and ultrasound data that are acquired at a same point in time (e.g., time t_1) may be associated with one another by the synchronization module **400**, and then stored in an ordered memory location. At a next point in time (e.g., at time t_2), the auscultation data, EKG data, and ultrasound data at that time may be associated with one another and stored in an ordered memory location that sequentially follows the memory location of the data acquired at time t_1 . That is, the acquired data may be ordered based on a relative time that it was received by the synchronization module **400**.

[0062] FIG. 5 is a pictorial diagram illustrating synchronous display of the auscultation data, EKG data, and ultrasound data, which may be acquired by the separate auscultation sensor **14**, EKG sensor **16**, and ultrasound sensor **18** in the system **10**, or which may be acquired by the combination auscultation sensor **114**, EKG sensor **116**, and ultrasound sensor **118** that are provided on a same sensing surface **160** of the probe **140** in the system **100**. Synchronous display of the data may be provided on the display **24** of the computing device **12** of the system **10**, on the display **124** of the computing device **112** of the system **100**, or may be displayed on the probe **140** in embodiments where the probe includes a display.

[0063] As shown in FIG. 5, the ultrasound image **502** is shown for a particular point in time, t . The EKG waveform

504 at the time, *t*, is depicted by the dashed line. Similarly, the auscultation waveform **506** for the time, *t*, is depicted by the dashed line, which corresponds to the dashed line for the EKG waveform **504**. As the signals in this embodiment are acquired in real-time, the ultrasound image **502** is sequentially updated (e.g., to reflect the current ultrasound image), and the EKG and auscultation waveforms **504**, **506** grow from left to right with the dashed bar always indicating the time, *t*, that corresponds to the displayed ultrasound image **502**.

[0064] The three auscultation, EKG, and ultrasound signals may be displayed in real-time, i.e., as they are acquired, or may be stored in memory in a synchronous manner, and later retrieved from memory and displayed in a synchronized display as shown in FIG. 5. Additionally, audio information may be provided in synchronization with the display of one or more of the auscultation data, EKG data, and ultrasound data. The audio information may be provided through one or more speakers. For example, the auscultation data may be output as audible information through one or more speakers in synchronization with the display of video information associated with the auscultation data.

[0065] The ultrasound data may be any ultrasound data associated with any ultrasound mode, including but not limited to, A-mode, B-mode, C-mode, M-mode, Doppler mode including continuous wave (CW) and pulsed wave (PW), and the like. The ultrasound data may be acquired in any ultrasound mode and may be displayed and/or provided as audible information in any ultrasound mode.

[0066] In one or more embodiments, artificial intelligence techniques may be employed in an artificial intelligence (“AI”) data recognition module to analyze the auscultation, EKG, and ultrasound signals acquired by any of the devices or systems described herein. The analysis by the AI data recognition module may be based on any of the auscultation, EKG, and ultrasound signals individually, or may be based on any combination of these signals.

[0067] For example, U.S. patent application Ser. No. 15/454,678, assigned to the assignee of the present disclosure and incorporated by reference herein, describes various embodiments of artificial intelligence network systems and methods for ultrasound imaging, which utilize an ultrasound image recognition module to make determinations regarding acquired ultrasound images, such as determining whether (i) acquired ultrasound images accurately or substantially accurately depict or represent, or do not accurately or substantially accurately depict or represent, a desired view of a structure and/or anatomy including, for example, a patient’s organ or other tissue, feature or region of interest in a patient, and (ii) whether acquired images representing clinically desired views of anatomy indicate normal function or a particular pathology.

[0068] The artificial intelligence techniques described in U.S. patent application Ser. No. 15/454,678 may be modified and implemented in embodiments of the present disclosure for similarly analyzing the acquired auscultation, EKG, and ultrasound signals and determining whether the signals indicate one or more pathologies. In at least one embodiment, AI parameters that are used to implement the artificial intelligence techniques are learned by processing training data obtained from auscultation, EKG, and ultrasound signals that are known to indicate one or more pathologies.

[0069] FIG. 6 is a block diagram illustrating a system **200** for acquiring ultrasound, EKG, and auscultation signals, in accordance with embodiments of the present disclosure. The system **200** shown in FIG. 6 is similar to the system **100** shown in FIG. 2; however, one difference is that the system **200** further includes an AI data recognition module **228** for analyzing acquired auscultation, EKG, and ultrasound signals.

[0070] As shown in FIG. 6, the system **200** includes the computing device **112** and the probe **140**, which may be the same as shown and described with respect to FIG. 2. In one or more embodiments, the system **200** may instead utilize the computing device **12** separately coupled to one or more of the auscultation sensor **14**, the EKG sensor **16**, the ultrasound sensor **18**, and the additional sensors **26**, as shown and described with respect to FIG. 1. In one or more embodiments, the system **200** may instead utilize probe **140** without the use of computing device **112**.

[0071] The system **200** may further include a communications network **202**, an AI data recognition module **228**, and an AI knowledge database **226**. One or both of the AI data recognition module **228** and AI knowledge database **226** may be incorporated into the computing device **112** or probe **140**, or they may constitute multiple devices operatively and/or communicatively linked or linkable to one another.

[0072] As described with respect to FIG. 2, the probe **140** may be used to acquire auscultation data, EKG data, and ultrasound data. The acquired data may be provided to the AI data recognition module **228** via the communications network **202**. Communications network **202** may utilize one or more protocols to communicate via one or more physical networks, including local area networks, wireless networks, dedicated lines, intranets, the Internet, and the like.

[0073] In one or more embodiments, the AI data recognition module **228** may be provided within the computing device **112**, or a local implementation of the AI data recognition module **228** and/or knowledge stored in the AI knowledge database **226** may be contained within the computing device **112**, with the computing device **112** having access to a remotely located (e.g., stored on one or more server computers, or in the “cloud”) AI data recognition module **228**, e.g., for receiving updated data recognition algorithms and/or knowledge.

[0074] The AI data recognition module **228** receives the auscultation, EKG, and ultrasound data acquired by the computing device **112**, and makes determinations based on the acquired data. For example, the AI data recognition module **228** may determine whether the acquired data indicates normal function or a particular pathology. Such determinations may be made by the AI data recognition module **228** based on individual data signals (e.g., any one of the auscultation data, EKG data, or ultrasound data), or based on any combination of the acquired data signals.

[0075] The AI data recognition module **228** may be implemented by any computationally intelligent system that employs artificial intelligence, drawing from an AI knowledge database **226**, to determine whether the acquired data indicates a particular pathology. Such determination may be performed automatically by the AI data recognition module **228**, for example, in response to receiving the acquired auscultation, EKG, and ultrasound data.

[0076] “Artificial intelligence” is used herein to broadly describe any computationally intelligent systems and meth-

ods that can learn knowledge (e.g., based on training data), and use such learned knowledge to adapt its approaches for solving one or more problems. Artificially intelligent machines may employ, for example, neural network, deep learning, convolutional neural network, and Bayesian program learning techniques to solve problems such as image recognition. Further, artificial intelligence may include any one or combination of the following computational techniques: constraint program, fuzzy logic, classification, conventional artificial intelligence, symbolic manipulation, fuzzy set theory, evolutionary computation, cybernetics, data mining, approximate reasoning, derivative-free optimization, decision trees, and/or soft computing. Employing one or more computationally intelligent techniques, the AI data recognition module 228 may learn to adapt to an unknown and/or changing environment for better assessment of the auscultation, EKG, and ultrasound signal data.

[0077] The AI knowledge database 226 may include a variety of information facilitating data analysis, with respect to received auscultation, EKG, and/or ultrasound data, by the AI data recognition module 228. In particular, the AI knowledge database 226 may contain information correlating particular auscultation, EKG, and/or ultrasound data to various pathologies. The AI knowledge database 226 may be stored in any computer-readable storage medium accessible by the AI data recognition module 228.

[0078] FIG. 7 is a block diagram illustrating training of the AI data recognition module 228, in accordance with one or more embodiments. The AI data recognition module 228 may be trained based on training data 210. Training data 210 may include any auscultation, EKG, or ultrasound information. For example, the training data 210 may include a variety of auscultation data (e.g., audio waveforms) that are associated with particular pathologies, such as abnormal heart sounds that may be associated with heart murmurs or the like, abnormal lung sounds such as wheezes, crepitations or the like, or any other body sounds that may be associated with one or more pathologies. Similarly, the training data 210 may include a variety of EKG data (e.g., electrical waveforms) that are associated with particular pathologies, such as arrhythmia, myocardial infarction, pulmonary embolism or the like. The training data 210 may further include a variety of ultrasound data (e.g., ultrasound image data) associated with known views of an organ, such as the heart, as well as ultrasound data associated with particular pathologies.

[0079] Other training input 220 may further be provided to the AI data recognition module 228 for training. The other training input 220 may include, for example, manually-entered input to adjust or otherwise manage the data recognition model developed in the AI data recognition module 228 through the training process.

[0080] Using training data 210, the AI data recognition module 228 may implement an iterative training process. Training may be based on a wide variety of learning rules or training algorithms. For example, the learning rules may include one or more of the following: back-propagation, real-time recurrent learning, pattern-by-pattern learning, supervised learning, interpolation, weighted sum, reinforced learning, temporal difference learning, unsupervised learning, and/or recording learning.

[0081] As a result of the training, the AI data recognition module 228 may learn to modify its behavior in response to the training data 210, and obtain or generate AI knowledge

230. The AI knowledge 230 may represent any information upon which the AI data recognition module 228 may determine an appropriate response to new data or situations. In particular, the AI knowledge 230 represents relationships between auscultation, EKG, and ultrasound data and one or more pathologies. The AI knowledge 230 may be stored in the AI knowledge database 226.

[0082] Based on the training data 210, the AI recognition module 228 may learn to modify its behavior, and may apply knowledge contained in the AI knowledge database 226 to alter the manner in which it makes determinations with respect to new input, such as, for example, auscultation, EKG, and ultrasound data received by the computing device 112. The AI data recognition module 228 may apply the acquired knowledge to incoming auscultation, EKG, and ultrasound data, and automatically assess the data to produce one or more clinically-relevant determinations based on a combined analysis of the data. For example, the AI recognition module 228 may automatically determine whether the received data indicates one or more specific pathologies.

[0083] In one or more embodiments, the present disclosure provides a system that includes: a computing device configured to acquire ultrasound data, electrocardiogram (EKG) data, and auscultation data; and an artificial intelligence (AI) data recognition module configured to receive the acquired ultrasound data, EKG data, and auscultation data and to automatically determine whether the received data, in any combination, indicates one or more pathologies.

[0084] The system may further include a synchronization module communicatively coupled to the computing device, and the synchronization module may be configured to synchronize two or more of the acquired ultrasound data, EKG data, and auscultation data.

[0085] The AI data recognition module may be configured to determine whether the synchronized two or more of the acquired ultrasound data, EKG data, and auscultation data indicates one or more pathologies.

[0086] In one or more embodiments, the present disclosure provides a handheld probe that includes: an ultrasound sensor positioned on a sensing surface of the probe; and an electrocardiogram (EKG) sensor positioned on the sensing surface of the probe.

[0087] The handheld probe may further include: a processor; and a memory coupled to the processor, wherein the ultrasound sensor and the EKG sensor are communicatively coupled to the processor. The EKG sensor may include a plurality of electrodes positioned on the sensing surface of the probe.

[0088] The various embodiments described above can be combined to provide further embodiments. All of the U.S. patent applications referred to in this specification and/or listed in the Application Data Sheet are incorporated herein by reference, in their entirety. Aspects of the embodiments can be modified, if necessary to employ concepts of the various patents, applications and publications to provide yet further embodiments.

[0089] These and other changes can be made to the embodiments in light of the above-detailed description. In general, in the following claims, the terms used should not be construed to limit the claims to the specific embodiments disclosed in the specification and the claims, but should be construed to include all possible embodiments along with

the full scope of equivalents to which such claims are entitled. Accordingly, the claims are not limited by the disclosure.

1. A system, comprising:
 - a handheld device including:
 - an ultrasound sensor;
 - an electrocardiogram (EKG) sensor; and
 - an auscultation sensor; and
 - a computing device including memory and a processor, wherein the ultrasound sensor, the EKG sensor, and the auscultation sensor are configured to simultaneously acquire respective signals of a patient, and the processor is configured to receive and process the signals from the ultrasound sensor, the EKG sensor, and the auscultation sensor.
2. The system of claim 1, further comprising a display coupled to the computing device and configured to display information associated with the signals from the ultrasound sensor, the EKG sensor, and the auscultation sensor.
3. The system of claim 1, further comprising synchronization circuitry configured to synchronize the signals received from two or more of the ultrasound sensor, the EKG sensor, and the auscultation sensor.
4. The system of claim 3 wherein the synchronization circuitry associates time stamp information with the signals received from the two or more of the ultrasound sensor, the EKG sensor, and the auscultation sensor.
5. The system of claim 3 wherein the synchronization circuitry is configured to store the signals received from the two or more of the ultrasound sensor, the EKG sensor, and the auscultation sensor in a memory in a synchronized manner.
6. The system of claim 3, further comprising a display coupled to the computing device, wherein the display is configured to display information derived from the signals received from the ultrasound sensor, the EKG sensor, and the auscultation sensor in a synchronized manner.
7. The system of claim 1 wherein the handheld device includes a probe having a sensing surface, the ultrasound sensor and the auscultation sensor being positioned on the sensing surface of the probe.
8. The system of claim 7 wherein the EKG sensor is electrically coupled to the probe.
9. The system of claim 7 wherein the probe communicates with the computing device wirelessly.
10. The system of claim 1, further comprising a pulse oximetry sensor, wherein the processor is further configured to receive and process signals from the pulse oximetry sensor.
11. A handheld device, comprising:
 - a processor;
 - a memory coupled to the processor;
 - an ultrasound sensor;
 - an electrocardiogram (EKG) sensor; and
 - an auscultation sensor,
 wherein the ultrasound sensor, EKG sensor, and auscultation sensor are positioned on a same sensing surface of the handheld device, and wherein each of the ultrasound sensor, the EKG sensor, and the auscultation sensor is communicatively coupled to the processor.
12. The handheld device of claim 11, further comprising a display coupled to the processor, the display being con-

figured to display information derived from respective signals acquired by the ultrasound sensor, the EKG sensor, and the auscultation sensor.

13. The handheld device of claim 11, wherein the ultrasound sensor, EKG sensor, and auscultation sensor are configured to simultaneously acquire respective signals of a patient, the handheld device further comprising synchronization circuitry configured to synchronize the signals acquired by two or more of the ultrasound sensor, the EKG sensor, and the auscultation sensor.
14. The handheld device of claim 13 wherein the synchronization circuitry associates time stamp information with each of the signals being synchronized.
15. The handheld device of claim 13 wherein the synchronization circuitry is configured to store the signals acquired by the two or more of the ultrasound sensor, the EKG sensor, and the auscultation sensor in the memory in a synchronized manner.
16. A method, comprising:
 - simultaneously acquiring, by sensors in a handheld device, ultrasound data, electrocardiogram (EKG) data, and auscultation data;
 - receiving, by a computing device, the ultrasound data, the EKG data, and the auscultation data;
 - synchronizing at least two of the received ultrasound data, EKG data, and auscultation data; and
 - storing the ultrasound data, EKG data, and auscultation data in a memory.
17. The method of claim 16, further comprising:
 - displaying the ultrasound data, EKG data, and auscultation data on a combined display in a synchronized manner.
18. The method of claim 16 wherein synchronizing the at least two of the received ultrasound data, EKG data, and auscultation data includes associating time stamp information with each of the at least two of the ultrasound data, EKG data, and auscultation data.
19. The method of claim 16 wherein the ultrasound data, EKG data, and auscultation data are stored in the memory in a synchronized manner.
20. The method of claim 16, further comprising:
 - analyzing the received ultrasound data, EKG data, and auscultation data by an artificial intelligence (AI) data recognition system to determine whether the received data indicates one or more pathologies.
21. A handheld probe, comprising:
 - an ultrasound sensor positioned on a sensing surface of the handheld probe; and
 - an electrocardiogram (EKG) sensor positioned on the sensing surface of the handheld probe,
 wherein, in use, the ultrasound sensor and the EKG sensor simultaneously acquire respective signals of a patient.
22. The handheld probe of claim 21, further comprising:
 - a processor; and
 - a memory coupled to the processor,
 wherein the ultrasound sensor and the EKG sensor are communicatively coupled to the processor.
23. The handheld probe of claim 21 wherein the EKG sensor includes a plurality of electrodes positioned on the sensing surface of the handheld probe.

专利名称(译)	用于将超声与附加信号融合的系统和方法		
公开(公告)号	US20190105019A1	公开(公告)日	2019-04-11
申请号	US15/969632	申请日	2018-05-02
[标]发明人	PAGOULATOS NIKOLAOS PAILOOR RAMACHANDRA NIEMINEN GREG BROAD RON BRUNKE SHELBY		
发明人	PAGOULATOS, NIKOLAOS PAILOOR, RAMACHANDRA NIEMINEN, GREG DOHERTY, TERRY BROAD, RON BRUNKE, SHELBY		
IPC分类号	A61B8/08 A61B7/04 A61B5/00 A61B5/1455 A61B8/00 A61B5/0205 A61B5/044 A61B5/0404 A61B5/04 A61B5/0408 A61B5/0432		
CPC分类号	A61B8/5284 A61B7/04 A61B5/0006 A61B5/14551 A61B8/4472 A61B8/4427 A61B5/0205 A61B5/044 A61B5/0404 A61B8/4416 A61B8/463 A61B5/04012 A61B5/04085 A61B5/0432 A61B5/7264 A61B8/0883 A61B8/543 A61B8/565 A61B2562/0219 A61B2562/0247 G16H50/20		
优先权	62/568709 2017-10-05 US		
其他公开文献	US10507009		
外部链接	Espacenet USPTO		

摘要(译)

提供了用于提供组合超声，心电图和听诊数据的系统，方法和设备。一种这样的系统包括超声传感器，心电图（EKG）传感器，听诊传感器和计算设备。计算设备包括存储器和处理器，并且处理器从超声传感器，EKG传感器和听诊传感器接收信号。可以采用人工智能技术来自动分析从超声传感器，EKG传感器和听诊传感器获得的数据，并基于数据的组合分析产生临床相关的确定。

