



(19) **United States**

(12) **Patent Application Publication**
Tsujita

(10) **Pub. No.: US 2012/0259223 A1**

(43) **Pub. Date: Oct. 11, 2012**

(54) **ULTRASONIC DIAGNOSTIC APPARATUS
AND ULTRASONIC IMAGE DISPLAY
METHOD**

(30) **Foreign Application Priority Data**

Jan. 18, 2010 (JP) 2010-007699

Publication Classification

(51) **Int. Cl.**
A61B 8/08 (2006.01)
A61B 8/13 (2006.01)
(52) **U.S. Cl.** **600/442**

(57) **ABSTRACT**

Provided is an ultrasonic diagnostic apparatus configured to appropriately display a region of interest that is intended to be observed in a 3-dimensional elastic image, and also provided is an ultrasonic image display method. The ultrasonic diagnostic apparatus includes an elastic opacity table creating section for creating, on the basis of the elasticity values, an elastic opacity table used for setting an opacity in the volume rendering of the elastic volume data.

(75) Inventor: **Takehiro Tsujita, Tokyo (JP)**

(73) Assignee: **HITACHI MEDICAL CORPORATION, Tokyo (JP)**

(21) Appl. No.: **13/513,371**

(22) PCT Filed: **Nov. 25, 2010**

(86) PCT No.: **PCT/JP2010/070965**

§ 371 (c)(1),
(2), (4) Date:

Jun. 18, 2012





FIG. 1







FIG. 3







FIG. 5



111

FIG. 6




FIG. 7






FIG. 8

(a)



(b)






FIG. 9





FIG. 10



ULTRASONIC DIAGNOSTIC APPARATUS AND ULTRASONIC IMAGE DISPLAY METHOD

FIELD OF THE INVENTION

[0001] The present invention relates to an ultrasonic diagnostic apparatus and an ultrasonic image display method capable of displaying a 3-dimensional elastic image showing the hardness or softness of biological tissue in an object using ultrasonic waves.

DESCRIPTION OF RELATED ART

[0002] An ultrasonic diagnostic apparatus transmits ultrasonic waves to the inside of an object to be examined by an ultrasonic probe, and is capable of obtaining and displaying a 3-dimensional tomographic image and a 3-dimensional elastic image on the basis of the reception signals received from the biological tissue in the object.

[0003] At the time of superimposing and displaying a 3-dimensional elastic image over a 3-dimensional tomographic image, the opacity of the 3-dimensional tomographic image is set so that the profile or volume of the hard region or soft region in the 3-dimensional elastic image can be recognized (for example, Patent Document 1).

PRIOR ART DOCUMENTS

Patent Documents

[0004] Patent Document 1: JP-A-2008-259605

[0005] Though the technique disclosed in Patent Document 1 performs volume rendering of a 3-dimensional tomographic image based on an opacity table in which the opacity is defined in accordance with the feature quantity of an elasticity value, the setting of opacity in the volume rendering process of the 3-dimensional elastic image is not disclosed therein.

[0006] Therefore, there is a possibility, at the time of constructing a 3-dimensional elastic image by performing volume rendering in the line of sight, in the case that a thick region which is not a region of interest that exists in front of the region of interest in the line of sight, that the region of interest is hidden behind the region other than the region of interest. For example, in the setting of opacity that changes linearly from the hard region which is the region of interest to the soft region, there is a possibility that the hard region is hidden behind the region having the average hardness which is the region other than the region of interest.

[0007] The objective of the present invention is to provide the ultrasonic diagnostic apparatus and the ultrasonic image display method capable of appropriately displaying a desired region of interest in a 3-dimensional elastic image.

BRIEF SUMMARY OF THE INVENTION

[0008] In order to achieve the above-described objective, the ultrasonic diagnostic apparatus of the present invention comprises:

[0009] an ultrasonic probe provided with transducers configured to transmit and receive ultrasonic waves;

[0010] a transmission unit configured to transmit ultrasonic waves to an object to be examined via an ultrasonic probe;

[0011] a reception unit configured to receive the reflected echo signals from the objective;

[0012] a 3-dimensional elastic image constructing unit configured to construct a 3-dimensional elastic image by performing volume rendering on the elastic volume data formed by the elasticity values based on reflected echo signals; and

[0013] a display unit configured to display an 3-dimensional elastic image,

[0014] wherein the 3-dimensional elastic image constructing unit constructs a 3-dimensional elastic image by setting the opacity in the volume rendering of the elastic volume data on the basis of elasticity values.

[0015] In accordance with the present invention, it is possible to appropriately display a desired region of interest in a 3-dimensional elastic image.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] FIG. 1 is a block diagram showing the general configuration of the present invention.

[0017] FIG. 2 is a view showing a 3-dimensional tomographic image constructing unit 117 and a 3-dimensional elastic image constructing unit 118 of the present invention.

[0018] FIG. 3 shows an example of an elastic opacity table in a first embodiment of the present invention.

[0019] FIG. 4 shows an example of the elastic opacity table in the first embodiment of the present invention.

[0020] FIG. 5 shows a display pattern of a display unit 111 related to the present invention.

[0021] FIG. 6 shows an example of the elastic opacity table in a second embodiment of the present invention.

[0022] FIG. 7 is a view showing the 3-dimensional elastic image constructing unit 118 in a third embodiment of the present invention.

[0023] FIG. 8 shows an example of the elastic opacity table in the third embodiment of the present invention.

[0024] FIG. 9 is a view showing the 3-dimensional elastic image constructing unit 118 in a fourth embodiment of the present invention.

[0025] FIG. 10 shows an example of the elastic opacity table in the fourth embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[0026] An ultrasonic diagnostic apparatus 100 to which the present invention is applied will be described referring to FIG. 1.

[0027] As shown in FIG. 1, the ultrasonic diagnostic apparatus 100 comprises an ultrasonic probe 102 configured to be used by applying to an object 101, a transmission unit 105 configured to repeatedly transmit ultrasonic waves to the object 101 via the ultrasonic probe 102 at predetermined time intervals, a reception unit 106 configured to receive the reflected echo signals reflected from the object 101, a transmission/reception control unit 107 configured to control the transmission unit 105 and the reception unit 106, and a phasing and adding unit 108 configured to perform phasing and adding on the reflected echoes received by the reception unit 106.

[0028] The ultrasonic probe 102 is formed by a plurality of transducers arrayed therein, and has a function to transmit/receive ultrasonic waves to the object via the transducers. The ultrasonic probe 102 is formed by a plurality of rectangle or fan-shaped transducers, capable of transmitting/receiving ultrasonic waves 3-dimensionally by mechanically vibrating the transducers in the direction orthogonal to the array direc-

tion of the plurality of transducers. The ultrasonic probe 102 may also be provided with a plurality of transducers being 2-dimensionally arrayed therein and a function capable of electronically controlling transmission and reception of ultrasonic waves.

[0029] The transmission unit 105 generates a transmission pulse for generating an ultrasonic wave by activating transducers of the ultrasonic probe 102. The transmission unit 105 has a function to set the convergent point of a transmitted ultrasonic wave at a certain depth. Also, the reception unit 106 generates an RF signal, i.e. a reception signal by amplifying the reflected echo signal received by the ultrasonic probe 102 at a predetermined gain. The ultrasonic transmission/reception control unit 107 controls the transmission unit 105 and the reception unit 106.

[0030] The phasing and adding unit 108 controls the phase of the RF signal which is amplified in the reception unit 106 and generates RF signal frame data (equivalent to RAW data) by forming an ultrasonic beam with respect to one or plural convergent points.

[0031] Further, the ultrasonic diagnostic apparatus 100 comprises a data storage unit 109 configured to store the RF signal frame data generated in the phasing and adding unit 108, a 2-dimensional tomographic image constructing unit 113 configured to construct a 2-dimensional tomographic image on the basis of the RF signal frame data stored in the data storage unit 109, a tomographic volume data generating unit 115 configured to generate tomographic volume data by performing 3-dimensional coordinate conversion on the 2-dimensional tomographic image constructed by the 2-dimensional tomographic image constructing unit 113 on the basis of the position where the 2-dimensional tomographic image is obtained, a 3-dimensional tomographic image constructing unit 117 configured to construct a 3-dimensional tomographic image from tomographic volume data, a 2-dimensional elastic image constructing unit 114 configured to construct a 2-dimensional elastic image on the basis of the plural sets of RF signal frame data stored in the data storage unit 109, an elastic volume data generating unit 116 configured to generate elastic volume data by performing 3-dimensional coordinate conversion on the 2-dimensional elastic image constructed in the 2-dimensional elastic image constructing unit 114 on the basis of the position where the 2-dimensional elastic image is obtained, a 3-dimensional elastic image constructing unit 118 configured to construct a 3-dimensional elastic image from the elastic volume data on which the coordinate conversion is performed, a synthesis processing unit 110 configured to synthesize a 2-dimensional tomographic image and a 2-dimensional elastic image or a 3-dimensional tomographic image and a 3-dimensional elastic image, and a display unit 111 configured to display images such as a synthetic image which is synthesized by the synthesis processing unit 110, a 2-dimensional tomographic image or a 2-dimensional tomographic image.

[0032] Also, the ultrasonic diagnostic apparatus 100 comprises a control unit 103 configured to control the above-described components and an operation unit 104 configured to perform various input to the control unit 103. The operation unit 104 comprises devices such as a keyboard or a trackball.

[0033] The 2-dimensional tomographic image constructing unit 113 executes signal processing such as gain compensation, log compression, detection, edge enhancement or filtering by inputting the RF signal frame data output from the data

storage unit 109 on the basis of the setting condition in the control unit 103, and constructs a 2-dimensional tomographic image.

[0034] The ultrasonic probe 2 is capable of measuring the transmission/reception directions (θ, ϕ) at the time of transmitting and receiving ultrasonic waves, and the tomographic volume data generating unit 115 generates the tomographic volume data by executing 3-dimensional conversion on plural 2-dimensional tomographic images on the basis of the transmission/reception directions (θ, ϕ) which are equivalent to the positions where the 2-dimensional images are obtained.

[0035] The 3-dimensional tomographic image constructing unit 117 performs volume rendering on the basis of the luminance and the opacity of the tomographic volume data. In concrete terms, the 3-dimensional tomographic image constructing unit 117 is configured by a tomographic opacity table creating section 200 and a tomographic rendering calculation section 202 as shown in FIG. 2(a).

[0036] The tomographic opacity table creating section 200 creates a tomographic opacity table in which the luminance of a tomographic image represented by voxel values is set as the lateral axis and the opacity is set as the vertical axis. The tomographic rendering calculation section 202 performs volume rendering on the basis of the created tomographic opacity table using the following equation for constructing a 3-dimensional tomographic image from the tomographic volume data.

[Equation 1]

$$Cout(i)=Cout(i-1)+(a-Aout(i-1))\cdot A(i)\cdot C(i)\cdot S(i) \quad (1)$$

$$Aout(i)=Aout(i-1)+(1-Aout(i-1))\cdot A(i) \quad (2)$$

$$A(i)=Opacity[C(i)] \quad (3)$$

[0037] $C(i)$ is the luminance value of the i -th voxel that exists on the line of sight when a 3-dimensional tomographic image is viewed from a certain point on the created 2-dimensional projected plane. $Cout(i)$ is the output pixel value. For example, when luminance values of N -number of voxels are lined up on the line of sight, the luminance value $Cout(N-1)$ obtained by integration from $i=0$ to $N-1$ is the pixel value to be ultimately output. $Cout(i-1)$ represents the integrated value up to the $(i-1)$ -th voxel.

[0038] Also, $A(i)$ is the opacity of the i -th luminance value that exists on the line of sight, and is the tomographic opacity table which takes the values of 0-1.0 as indicated in the above equation (3). The tomographic opacity table is generated in the tomographic opacity table creating section 200, and determines the contribution ratio on the output 2-dimensional projected plane (3-dimensional tomographic image) by referring to the opacity based on the luminance value.

[0039] $S(i)$ is the weighting component for shading to be computed by the slope which is acquired by luminance $C(i)$ and the surrounding pixel values thereof. For example, when the light source coincides with the normal line of the plane which is centered on voxel " i ", 1.0 is given for the maximum reflection, and when the light source and the normal line are orthogonal to each other, 0.0 is given which indicates accentuation effect.

[0040] Both $Cout(i)$ and $Aout(i)$ have 0 as the initial value. As shown in the above equation (2), $Aout(i)$ is integrated each time it passes through a voxel and converged to 1.0. Thus as shown in the above equation (1), when integrated value $Aout$

(i-1) of up to the (i-1)-th opacity is about 1.0, the i-th and sequence luminance values C(i) will not be reflected on the output image.

[0041] The tomographic opacity table creating section 200 is capable of imaging the tomographic volume data with high luminance without imaging the tomographic volume data with low luminance by, for example, setting the opacity of the low luminance value in the tomographic opacity table as zero. The tomographic rendering calculation section 202 perform volume rendering on the basis of the created tomographic opacity table, and outputs the constructed 3-dimensional tomographic image to the synthesis processing unit 110.

[0042] In the present embodiment, it is possible to make changes in a tomographic opacity table. By the control of the control unit 103 based on the operation of the operation unit 104, the tomographic opacity table creating section 200 can make changes in the tomographic opacity table, thereby the tomographic volume data in which the changes are made in accordance with the changed tomographic opacity table can be imaged.

[0043] The 2-dimensional elastic image constructing unit 114 measures the displacement from the plural sets of RF signal frame data stored in the data storage unit 109. Then the 2-dimensional elastic image constructing unit 114 calculates the elasticity value on the basis of the measured displacement, and constructs a 2-dimensional elastic image. The elasticity value includes elasticity information such as the strain, elasticity modulus, displacement, viscosity or strain ratio.

[0044] The elastic volume data generating unit 116 executes 3-dimensional conversion on plural 2-dimensional elastic images on the basis of the transmission/reception directions (θ , ϕ) equivalent to the positions where the 2-dimensional elastic images are obtained, and generates the elastic volume data. On the elastic volume data, color values (blue, light blue, green, yellow, red, etc.) are allotted in accordance with the elasticity values. For example, a hard region is colored in blue and a soft region is colored in red.

[0045] The 3-dimensional elastic image constructing unit 118 constructs a 3-dimensional elastic image by setting the opacity in volume rendering of the elastic volume data on the basis of the elasticity values. The opacity is set by the elastic opacity table in which the relationship between the opacity and the elasticity value is set. In concrete terms, the 3-dimensional elastic image constructing unit 118 is configured by an elastic opacity table creating section 204 and an elastic rendering calculation section 206 as shown in FIG. 2(b).

[0046] The elastic opacity table creating section 204 creates the elastic opacity table in which the relationship between the opacity and the elasticity value is set. The elastic opacity table is created for setting the opacity in the volume rendering on the basis of the elasticity value. FIG. 3 and FIG. 4 show the elastic opacity table to be created by the elastic opacity table creating section 204. The relationship between the elasticity value and the opacity is determined by the elastic opacity table, and the contribution ratio of the elastic volume data is set on the 2-dimensional projected plane in the display unit 111.

[0047] The elastic opacity table is formed by an opacity line 300 for setting the opacity on the basis of the elasticity value and a guideline 302 for guiding the setting of the opacity line 300. Also, a color bar 304 which corresponds to the elasticity value of the opacity table is displayed on FIG. 3 and FIG. 4.

[0048] As shown in FIG. 3, the elastic opacity table is set by the opacity line 300 to emphasize and display the region of

interest (hard region) to which blue color is given based on the elasticity value. The opacity is set by the opacity line 300 so that the opacity of the region of interest (hard region) determined by the elasticity value becomes higher compared to the opacity of the region other than the region of interest (standard region, soft region) to which green color or red color is given. The standard region to be the region other than the region of interest has the average hardness in the elastic volume data, to which mainly green color is given. The region other than the region of interest mainly includes the standard region.

[0049] In the elastic opacity table, when the opacity in the opacity line 300 of the region of interest (hard region) to which blue color is given is set as T1, T1 is set at a value which is close to 1.0 (for example, $0.7 \leq T1 < 1.0$). Also, when the opacity in the opacity line 300 of the region other than the region of interest (standard region, soft region) to which green or red is given is set as T2, T2 is set at a value which is close to 0 (for example, $0 < T2 \leq 0.5$). The opacity of the opacity line 300 is set so that opacity T2 of the region other than the region of interest will not be zero. The purpose of this setting is to display the region of interest (hard region) to which blue color is given relatively. Also, when the opacity in the opacity line 300 of the region between the region of interest to which light blue is given and the region other than the region of interest is set as T3, it is set at a value between T2 and T1 (for example, $T2 \leq T3 \leq T1$).

[0050] In the present embodiment, further changes can be made in the opacity of the elastic opacity table. The opacity of the elastic opacity table can be changed by the elastic opacity table creating section 204 under the control of the control unit 104 based on the operation in the operation unit 104.

[0051] The elastic opacity table creating section 204 makes changes in the opacity of the opacity line 300 which is equivalent to the region (the region including the standard region) other than the region of interest to which green color, etc. is given.

[0052] In concrete terms, when an operator moves the opacity line 300 set in the region other than the region of interest shown in the left view of FIG. 3 in the upward direction, the elastic opacity table creating section 204 sets the opacity of the elastic opacity table so that the opacity of the region other than the region of interest is at the higher level as shown in the right view of FIG. 3. Conversely, when the operator moves the opacity line 300 set in the region other than the region of interest in the downward direction, the elastic opacity table creating section 204 sets the opacity of the elastic opacity table so that the opacity of the region other than the region of interest is at the lower level. The guideline 302 for guiding the setting of the opacity line 300 indicates the movable range of the opacity line 300 (for example, $0 < T2 \leq 0.5$). In this manner, the operator can set the opacity in the opacity line 300 to be set at the region other than the region of interest (hard region).

[0053] While the opacity line 300 is represented by a straight line in the present embodiment, it may also be represented by a curved line. In the case that the opacity line 300 is represented by a curved line, the elastic opacity table creating section 204 sets the opacity corresponding to the curved line in the region (the region which includes the standard region) other than the region of interest.

[0054] The elastic rendering calculation section 206 performs volume rendering using the elastic opacity table based

on the opacity line **300** created in the elastic opacity table creating section **204** and the following equation.

[Equation 2]

$$Eout(i)=Eout(i-1)+(1-Aout(i-1))\cdot A(i)\cdot E(i)\cdot S(i) \quad (4)$$

$$Aout(i)=Aout(i-1)+(1-Aout(i-1))\cdot A(i) \quad (5)$$

$$A(i)=Opacity[E(i)] \quad (6)$$

[0055] $E(i)$ is the i -th elasticity value that exists on the line of sight in the case that a 3-dimensional elastic image is viewed from a certain point on the created 2-dimensional projected plane. $Eout(i)$ is the output pixel value. For example, when elasticity values of N -voxels are lined up in the line of sight, integrated value $Eout(N-1)$ in which the elasticity values of $i=0-N-1$ are integrated is the pixel value to be ultimately output. $Eout(i-1)$ represents the integrated value up to the $(i-1)$ -th voxel. Also, $A(i)$ is the opacity of the i -th elasticity value which exists in the line of sight, and is the elastic opacity table which is created in the elastic opacity table creating section **204** as shown in the equation (6).

[0056] $S(i)$ is the weighting component for shading to be computed by the slope which is acquired based on elasticity value $E(i)$ and the surrounding elasticity values thereof. For example, when the light source coincides with the normal line of the plane which is centered on voxel “ i ”, 1.0 is given for the maximum reflection, and when the light source and the normal line are orthogonal to each other, 0.0 is given which indicates accentuation effect.

[0057] Both $Eout(i)$ and $Aout(i)$ have 0 as the initial value. As shown in the equation (5), $Aout(1)$ is integrated each time it passes through a voxel and converged to 1.0. Thus as shown in the equation (4), when integrated value $Aout(i-1)$ of the opacity of up to the $(i-1)$ -th voxel is about 1.0, the i -th and subsequent voxel values $E(i)$ will not be reflected on the output image.

[0058] The synthesis processing unit **110** respectively reads out the 3-dimensional tomographic image which is constructed as above and a 3-dimensional elastic image, performs cumulative addition by multiplying the transmission factor which is set in the operation unit **104** on a 2-dimensional projected plane, and creates a 3-dimensional synthetic image. The display unit **111** displays the 3-dimensional synthetic image created in the synthesis processing unit **110**.

[0059] Also, the elastic opacity table creating section **204** is capable of setting the opacity by the opacity line **300** of the elastic opacity table so that the region of interest (soft region) to which red color is given based on the elasticity value is emphasized and displayed as shown in FIG. 4(a). The elastic opacity table is set such that the opacity of the region of interest determined by the elasticity value becomes higher compared to the opacity of the region other than the region of interest. In concrete terms, the opacity is set by the opacity line **300** so that the region of interest (soft region) determined on the basis of the elasticity value becomes higher compared to the opacity of the region other than the region of interest (standard region, hard region) to which green color or blue color, etc. is given.

[0060] The elastic opacity table creating section **204** is capable of setting the opacity of an opacity line **400** which is equivalent to the region other than the region of interest (standard region, hard region) to which green color or red color, etc. is given under the control of the control unit **103** based on the operation of the operation unit **104**. When the

opacity line **400** set at the region other than the region of interest is moved in the upward direction as shown in the left view of FIG. 4(a), the opacity of the region other than the region of interest is set at the higher level as shown in the right view of FIG. 4(a). Conversely, when the opacity line **400** set at the region other than the region of interest is moved in the downward direction, the opacity of the region other than the region of interest is set at the lower level. A guideline **402** for guiding the setting of the opacity line **400** indicates the movable range of the opacity line **400** (for example, $0 < T2 \leq 0.5$)

[0061] Also, the elastic opacity table creating section **204** is capable of setting the opacity by an opacity line **404** of the elastic opacity table such that the region of interest (hard region, soft region) to which blue color or red color is given on the basis of the elasticity value is emphasized and displayed as shown in FIG. 4(b). The opacity is set by the opacity line **404** so that the opacity of the region of interest (hard region, soft region) determined by the elasticity value becomes higher compared to the opacity of the region other than the region of interest (standard region) to which green color, etc. is given.

[0062] The elastic opacity table creating section **204** is capable of setting the opacity of the opacity line **404** which is equivalent to the region other than the region of interest (standard region) to which green color, etc. is given, under control of the control unit **103** based on the operation of the operation unit **104**. When the opacity line **404** set at the region other than the region of interest shown in the left view of FIG. 4(b) is moved in the upward direction, the opacity of the region other than the region of interest is set at the higher level as shown in the right view of FIG. 4(b). Conversely, when the opacity line **404** set at the region other than the region of interest is moved in the downward direction, the opacity of the region other than the region of interest is set at the lower level. A guideline **406** for guiding the setting of the opacity line **404** indicates the movable range of the opacity line **404** (for example, $0 < T2 \leq 0.5$).

[0063] FIG. 5 shows a display pattern of the display unit **111**. An image **500**, an opacity table selecting area **502**, an opacity setting area **504** and an elastic opacity table **506** are displayed on the same screen.

[0064] The image **500** is, for example a 3-dimensional synthetic image in which a 3-dimensional tomographic image and a 3-dimensional elastic image are synthesized, or a 3-dimensional elastic image.

[0065] The opacity table selecting area **502** is for selecting the elastic opacity table from among a plurality of opacity tables which are stored in advance. It comprises a storage area (not shown in the diagram) that stores a plurality of elastic opacity tables in FIG. 3, FIGS. 4(a) and (b) that are described above. A plurality of opacity tables are displayed on the display unit **111**, and an elastic opacity table can be selected under control of the control unit **103** based on the operation of the operation unit **104**. The elastic opacity table **506** which is selected by the operation unit **104** is displayed. Here, the concaved elastic opacity table in FIG. 4(b) is selected, and is displayed as shown in **506**.

[0066] The opacity setting area **504** is capable of setting the opacity of the opacity line **404** which is equivalent to the region other than the region of interest (standard region) by a numeric setting unit or a slide bar which is equivalent to the operation unit **104**. Here, the opacity of the opacity line **404** is set at “0.5”. The numeric or the slide bar can also indicate the settable range of the opacity of the opacity line **400**.

[0067] Since the image 500, the opacity table selecting area 502, the opacity setting area 504 and the opacity table are displayed on the same screen, the operator can select the pattern of the opacity table or set the opacity of the elastic opacity table while observing the image 500, for constructing an optimum image.

[0068] As described above, in accordance with the first embodiment, at the time of constructing a 3-dimensional elastic image by performing volume rendering in the line of sight direction, even when a thick region (the region including the standard region) other than the region of interest exists in front of the region of interest which is the observation target in the line of sight of the 3-dimensional elastic image, the region of interest can be displayed without being hidden by the region (the region including the standard region) other than the region of interest by setting the opacity of an elastic opacity table in accordance with the elasticity value.

[0069] For example, in the case that the region of interest is at the deep portion in the line of sight, the region of interest can be observed by lowering the opacity of the region (the region including the standard region) other than the region of interest to make the region (the region including the standard region) other than the region of interest which is on the near side of the region of interest transparent.

[0070] In this manner, a region of interest which is the observation target in a 3-dimensional elastic image can be appropriately displayed.

[0071] Here, the second embodiment will be described referring to FIG. 1~FIG. 6. The difference from the first embodiment is that the opacity of the region excluding the standard region is set by the elastic opacity table creating section 204. The configuration other than the elastic opacity table creating section 204 will be omitted since it is the same as the first embodiment.

[0072] The elastic opacity table creating section 204 sets the opacity by an opacity line 600 of an elastic opacity table so that the region of interest (hard region, soft region) to which blue color or red color is given on the basis of the elasticity value is emphasized and displayed, as shown in the left view of FIG. 6.

[0073] Given this factor, for example in the case that the region of interest (hard region) to which blue color is given is to be further emphasized, the elastic opacity table creating section 204 sets the opacity of the opacity line 600 which is equivalent to the region excluding the standard region to which red color is given. In concrete terms, when the opacity line 600 which is set at the opacity of the region excluding the standard region shown in the left view of FIG. 6 is moved in downward direction, the opacity of the region excluding the standard region is set lower as shown in the right view of FIG. 6.

[0074] In the present embodiment in the case that the region of interest (soft region) to which red color is given is to be further emphasized, the elastic opacity table creating section 204 can also set the opacity of the opacity line 600 which is equivalent to the region excluding the standard region to which blue color is given.

[0075] As described above, in accordance with the present embodiment at the time of constructing a 3-dimensional elastic image by performing volume rendering in the line of sight direction, it is possible to further emphasize and display the region of interest which requires specific attention.

[0076] The third embodiment will be described referring to FIG. 1~FIG. 8. The difference from the first embodiment and

the second embodiment is that the opacity of the elastic opacity table is set for every line of sight (direction) on the basis of the number of voxels in the elastic volume data on which volume rendering is performed. In other words, the opacity in the elastic opacity table is set on the basis of the number of voxels in the elastic volume data on which volume rendering is performed.

[0077] As shown in FIG. 7, the 3-dimensional elastic image constructing unit 118 is formed by a visual-line setting section 700 configured to set the line of sight (direction) with respect to the elastic volume data, a voxel counting section 702 configured to count the number of voxels in the line of sight (direction) set in the elastic volume data, an elastic opacity table creating section 704 configured to create the elastic opacity table based on the counted number of voxels, and an elastic rendering calculation section 706 configured to perform volume rendering on the elastic volume data using the created elastic opacity table.

[0078] The 3-dimensional elastic image constructing unit 118 in the present embodiment will be described in concrete terms referring to FIG. 8. In the pattern of FIG. 8(a), the visual-line setting section 700 sets a line of sight 802 on the diagonal line of elastic volume data 800 under control of the control unit 103 based on the operation of the operation unit 104. The display unit 111 can display the elasticity volume data 800 and the line of sight 802. The voxel counting section 702 counts the number of voxels in the line of sight 802 which is set in the elastic volume data 800. The counted number of voxels is indicated by the length of a line 806. The voxel counting section 702 may also execute the processing for searching a structural object that positions at the shallowest or deepest portion in the line of sight and calculate the number of voxels up to the target structural object.

[0079] As shown in the first embodiment, the elastic opacity table creating section 704 first sets the opacity of the elastic opacity table by an opacity line 808 so that the opacity of the region of interest (hard region, soft region) to which blue color or red color that are determined by the elasticity value is given becomes higher compared to the opacity of the region other than the region of interest (standard region) to which green color, etc. is given.

[0080] In the pattern of FIG. 8(a), since the line of sight 802 is set on the diagonal line of the elastic volume data 800, it has the maximum number of voxels for performing volume rendering. Given this factor, the elastic opacity creating section 704 sets the opacity of the elastic opacity table in accordance with the number of voxels, so that the region of interest (hard region, soft region) will not be hidden by the region other than the region of interest (standard region) due to having higher number of voxels for performing volume rendering.

[0081] In concrete terms, the elastic opacity table creating section 704, when the opacity in the opacity line 808 of the region other than the region of interest (standard region) to which green color is given is set as T2, sets the opacity line 808 so that an opacity T2 of the region other than the region of interest becomes low (for example, $0 < T2 \leq 0.1$). A guideline 810 is for indicating the movable range of the opacity line 808 (for example, $0 < T2 \leq 0.5$).

[0082] The elastic rendering calculation section 706 performs volume rendering using the elastic opacity table based on the opacity line 808 created in the elastic opacity table creating section 704 and the above equation (equation 2).

[0083] On the other hand, in the pattern of FIG. 8(b), the visual-line setting section 700 sets the line of sight 802 so that

the line of sight **802** will not cross orthogonally with respect to a side of the elastic volume data **800**, under control of the control unit **103** based on the operation of the operation unit **104**. The voxel counting section **702** counts the number of voxels in the line of sight **802** which is set in the elastic volume data **800**. The counted number of voxels is indicated by the length of a line **814**.

[**0084**] As in the first embodiment, the elastic opacity table creating section **704** first sets the opacity of the elastic opacity table by the opacity line **808** so that the opacity of the region of interest (hard region, soft region) to which blue color or red color determined by the elasticity is given becomes higher compared to the opacity of the region other than the region of interest (standard region) to which green color, etc. is given.

[**0085**] In the pattern of FIG. **8(b)**, since the line of sight **802** is set so that the line of sight **802** will not cross a side of the elastic volume data **800** orthogonally, the number of voxels for performing volume rendering is smaller than the pattern in FIG. **8(a)**. The elastic opacity creating section **704** sets the opacity of the elastic opacity table in accordance with the number of voxels, so that the region of interest (hard region, soft region) will not be hidden by the region other than the region of interest (standard region).

[**0086**] In concrete terms, the elastic opacity table creating section **704**, when the opacity in the opacity line **808** of the region other than the region of interest (standard region) to which green color is given is set as T_2 , sets the opacity line **808** so that an opacity T_2 of the region other than the region of interest becomes high (for example, $0.1 < T_2 \leq 0.3$).

[**0087**] The elastic rendering calculation section **706** performs volume rendering using the elastic opacity table based on the opacity line **808** created in the elastic opacity table creating section **704** and the above equation (equation 2).

[**0088**] In the third embodiment, when the number of voxels for performing volume rendering is high, the elastic opacity table creating section **704** sets the opacity line **808** so that the opacity of the region other than the region of interest becomes low. On the other hand, when the number of voxels for performing volume rendering is low, the elastic opacity table creating section **704** sets the opacity line **808** so that the opacity of the region other than the region of interest becomes low. In this manner, even when a 3-dimensional elastic image is constructed by changing the line of sight (direction), since the elastic opacity table creating section **704** counts the number of voxels for each line of sight and arbitrarily sets the opacity in accordance with the number of voxels for each line of sight (direction), it is possible to display a 3-dimensional elastic image evenly from any line of sight (direction).

[**0089**] The fourth embodiment will be described referring to FIGS. **1-10**. The difference between the present embodiment and the first - third embodiments is that the cumulative opacity of the elastic volume data in the line of sight (direction) is analyzed and the opacity of the elastic opacity table is set on the basis of the analyzed cumulative opacity.

[**0090**] As shown in FIG. **9**, the 3-dimensional elastic image constructing unit **118** is formed by a visual-line setting section **900** configured to set the line of sight (direction) with respect to the elastic volume data, a cumulative opacity analyzing section **902** configured to analyze the cumulative opacity with respect to the distance of the line of sight (number of voxels) in the set line of sight (direction), an elastic opacity table creating section **904** configured to create an elastic opacity table on the basis of the analyzed cumulative opacity, and an elastic rendering calculation section **906** configured to

perform volume rendering of the elastic volume data using the created elastic opacity table.

[**0091**] The 3-dimensional elastic image constructing unit **118** in the present embodiment will be described in concrete terms referring to FIG. **10**. FIG. **10** shows the cumulative opacity with respect to the distance of the line of sight (number of voxels) in the line of sight (direction) set in the visual-line setting section **900**. In the present embodiment, a cumulative opacity graph **1004** is set as optimal cumulative opacity graph, since the setting of the opacity thereof is generally well-balanced.

[**0092**] The cumulative opacity analyzing section **902** analyzes the cumulative opacity with respect to the visual-line distance (number of voxels) in the set line of sight (direction).

[**0093**] Here, it is assumed that a cumulative opacity graph **1002** is acquired as a result of analyzing the cumulative opacity in the line of sight (direction) in the cumulative opacity analyzing section **902**. The cumulative opacity graph **1002** has a high cumulative opacity with respect to the visual-line distance (number of voxels), and the cumulative opacity reaches 1.0 at the point where the visual-line distance (number of voxels) reaches P1.

[**0094**] Given this factor, the elastic opacity table creating section **904** sets the opacity in the elastic opacity table so that the cumulative opacity graph **1002** in the line of sight (direction) becomes the optimal cumulative opacity graph **1004**. In concrete terms, elastic opacity table creating section **904**, for example moves the opacity line **404** which is set in the region other than the region of interest to which green color, etc. is given in the downward direction, and lowers the opacity of the region other than the region of interest as shown in FIG. **4(b)**.

[**0095**] Also, it is assumed that a cumulative opacity graph **1006** is acquired as a result of analyzing the cumulative opacity in the line of sight (direction) by the cumulative opacity analyzing section **902**. The cumulative opacity of the cumulative opacity graph **1006** with respect to the visual-line distance (number of voxels) is low, and the cumulative opacity reaches 1.0 at the point where the visual-line distance (number of voxels) reaches P2. Also, the cumulative opacity of the cumulative opacity graph **1006** reaches 0.5 at the position of a visual-line distance (number of voxels) P1. In this case, the output elasticity value becomes half the elasticity value of the elastic volume data, and the value can be diagnosed as harder than the actual hardness.

[**0096**] Given this factor, the elasticity opacity table creating section **904** sets the opacity in the elasticity opacity table so that the cumulative opacity graph **1006** in the line of sight (direction) becomes the optimal cumulative opacity graph **1004**. In concrete terms, for example the elastic opacity table creating section **904** moves the opacity line **404** which is set at the region other than the region of interest to which green color, etc. is given toward upward direction, and sets the opacity at a higher value than the opacity in the region other than the region of interest, as shown in FIG. **4(b)**.

[**0097**] The elastic rendering calculation unit **906** performs volume rendering using the elasticity opacity table created in the elastic opacity table creating section **904** the above equation (equation 2).

[**0098**] In the fourth embodiment, a 3-dimensional elastic image can be displayed evenly from any line of sight (direction), by analyzing the cumulative opacity in the line of sight

(direction) and setting the opacity of the elastic opacity table on the basis of the analyzed cumulative opacity.

DESCRIPTION OF REFERENCE NUMERALS

[0099]	100	ultrasonic diagnostic apparatus
[0100]	102	ultrasonic probe
[0101]	103	control unit
[0102]	104	operation unit
[0103]	105	transmission unit
[0104]	106	reception unit
[0105]	107	transmission/reception control unit
[0106]	108	phasing and adding unit
[0107]	109	data storage unit
[0108]	110	synthesis processing unit
[0109]	111	display unit
[0110]	113	2-dimensional tomographic image constructing unit
[0111]	115	elastic image 3-dimensional coordinate converting unit
[0112]	117	3-dimensional tomographic image constructing unit
[0113]	114	2-dimensional elastic image constructing unit
[0114]	116	elastic image 3-dimensional coordinate converting unit
[0115]	118	3-dimensional elastic image constructing unit

1. An ultrasonic diagnostic apparatus comprising:
 an ultrasonic probe provided with transducers for transmitting/receiving ultrasonic waves;
 a transmission unit configured to transmit ultrasonic waves to an object to be examined via the ultrasonic probe;
 a reception unit configured to receive the reflected echo signal from the object;
 a 3-dimensional elastic image constructing unit configured to construct a 3-dimensional elastic image by performing volume rendering on the elastic volume data formed by the elasticity values based on the reflected echo signals; and
 a display unit configured to display the 3-dimensional elastic image,
 wherein the 3-dimensional elastic image constructing unit constructs a 3-dimensional elastic image by setting the opacity in the volume rendering of the elastic volume data on the basis of the elasticity values.

2. The ultrasonic diagnostic apparatus according to claim 1, wherein the opacity is set using an elastic opacity table in which the relationship between the opacity and the elasticity value is set.

3. The ultrasonic diagnostic apparatus according to claim 2, wherein the elastic opacity table is set so that the opacity of the region of interest which is determined by the elasticity value becomes higher compared to the opacity of the region other than the region of interest.

4. The ultrasonic diagnostic apparatus according to claim 2, wherein the elastic opacity table is formed by an opacity line for setting the opacity in accordance with the elasticity values.

5. The ultrasonic diagnostic apparatus according to claim 2, comprising an elastic opacity table creating section configured to create the elastic opacity table in which the relationship between the opacity and the elasticity values is set.

6. The ultrasonic diagnostic apparatus according to claim 5, wherein the elastic opacity table creating section sets the opacity of the elastic opacity table which is equivalent to the region other than the region of interest.

7. The ultrasonic diagnostic apparatus according to claim 2, comprising an opacity table selecting area configured to select the elastic opacity table from among the plurality of elastic opacity tables that are stored in advance.

8. The ultrasonic diagnostic apparatus according to claim 2, wherein the display unit displays the 3-dimensional elastic image and the elastic opacity table.

9. The ultrasonic diagnostic apparatus according to claim 8, wherein the display unit displays an opacity setting area for setting the opacity.

10. The ultrasonic diagnostic apparatus according to claim 7, wherein the display unit displays an opacity table selecting area for selecting the elastic opacity table from among the plurality of elastic opacity tables.

11. The ultrasonic diagnostic apparatus according to claim 1, comprising a 3-dimensional tomographic image constructing unit configured to generate tomographic volume data on the basis of the reflected echo signals and perform volume rendering based on the luminance and opacity of the tomographic volume data, wherein the display unit displays a 3-dimensional tomographic image.

12. The ultrasonic diagnostic apparatus according to claim 2, wherein the opacity in the elastic opacity table is set based on the number of voxels of the elastic volume data on which the volume rendering is performed.

13. The ultrasonic diagnostic apparatus according to claim 12, comprising a voxel counting section configured to execute the processing for searching a structural object positioned at the shallowest or deepest portion in the line of sight, and computes the number of voxels up to the searched structural object.

14. The ultrasonic diagnostic apparatus according to claim 2, wherein the opacity of the elastic opacity table is set on the basis of the cumulative opacity of the elastic volume data in the line of sight.

15. An ultrasonic image display method which performs volume rendering on elastic volume data formed by elasticity values based on the reflected echo signals of ultrasonic waves and displays a 3-dimensional elastic image, wherein the opacity in volume rendering of the elastic volume data is set on the basis of the elasticity values.

* * * * *

专利名称(译)	超声诊断设备和超声图像显示方法		
公开(公告)号	US20120259223A1	公开(公告)日	2012-10-11
申请号	US13/513371	申请日	2010-11-25
[标]申请(专利权)人(译)	株式会社日立医药		
申请(专利权)人(译)	日立医疗器械股份有限公司		
当前申请(专利权)人(译)	日立医疗器械股份有限公司		
[标]发明人	TSUJITA TAKEHIRO		
发明人	TSUJITA, TAKEHIRO		
IPC分类号	A61B8/08 A61B8/13		
CPC分类号	A61B8/08 A61B8/461 A61B8/463 A61B8/466 A61B8/485 A61B8/483 G01S7/52071 G01S7/52073 G01S15/8993 G06T15/08 A61B8/5223 G16H50/30		
优先权	2010007699 2010-01-18 JP		
其他公开文献	US9247922		
外部链接	Espacenet USPTO		

摘要(译)

本发明提供一种超声波诊断装置，其被配置为适当地显示要在三维弹性图像中观察的关注区域，并且还提供超声波图像显示方法。超声诊断设备包括弹性不透明度表创建部分，用于基于弹性值创建弹性不透明度表，该弹性不透明度表用于设置弹性体数据的体绘制中的不透明度。

