



US010575821B2

(12) **United States Patent**
Halmann et al.

(10) **Patent No.:** **US 10,575,821 B2**
(45) **Date of Patent:** ***Mar. 3, 2020**

(54) **METHOD AND SYSTEM FOR PDA-BASED
ULTRASOUND**

(71) Applicant: **GE Medical Systems Global
Technology Company, LLC,**
Waukesha, WI (US)

(72) Inventors: **Menachem Halmann,** Milwaukee, WI
(US); **Shinichi Amemiya,** Tokyo (JP)

(73) Assignee: **GE MEDICAL SYSTEMS GLOBAL
TECHNOLOGY COMPANY, LLC,**
Waukesha, WI (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **15/910,724**

(22) Filed: **Mar. 2, 2018**

(65) **Prior Publication Data**

US 2018/0185009 A1 Jul. 5, 2018

Related U.S. Application Data

(60) Continuation of application No. 14/274,122, filed on
May 9, 2014, now Pat. No. 9,936,936, which is a
(Continued)

(51) **Int. Cl.**
A61B 5/00 (2006.01)
A61B 8/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61B 8/462** (2013.01); **A61B 8/14**
(2013.01); **A61B 8/145** (2013.01); **A61B**
8/4411 (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC .. A61B 8/14; A61B 8/04; A61B 8/145; A61B
8/4411

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,043,181 A 8/1977 Nigam
4,428,237 A 1/1984 Zeger et al.
(Continued)

FOREIGN PATENT DOCUMENTS

JP 11508461 7/1999
JP 2003506172 A 2/2003
(Continued)

OTHER PUBLICATIONS

US 5,751,608 A, 05/1998, Koch et al. (withdrawn)
(Continued)


Primary Examiner — Joel F Brutus

(74) *Attorney, Agent, or Firm* — McAndrews, Held &
Malloy, Ltd.; Jacob Groethe; David Bates

(57) **ABSTRACT**

A method and system are disclosed for a compact, inexpensive ultrasound system using an off-the-shelf personal digital assistant (PDA) device interfacing to a hand-held probe assembly through a standard digital interface. The hand-held probe assembly comprises a detachable transducer head attached to a beamforming module that performs digital beamforming. The PDA runs Windows applications and displays menus and images to a user. The PDA also runs ultrasound data processing software to support a plurality of imaging modes. An internal battery is provided in the PDA to power the system. The transducer head is detachable from the beamforming module.

35 Claims, 6 Drawing Sheets



Related U.S. Application Data

continuation of application No. 14/015,252, filed on Aug. 30, 2013, which is a continuation of application No. 11/044,401, filed on Jan. 27, 2005, now Pat. No. 8,535,227, which is a division of application No. 10/063,342, filed on Apr. 12, 2002, now Pat. No. 7,115,093.

- (60) Provisional application No. 60/332,023, filed on Nov. 21, 2001.

(51) **Int. Cl.**

A61B 8/14 (2006.01)

G01S 7/52 (2006.01)

G01S 15/89 (2006.01)

A61B 8/08 (2006.01)

(52) **U.S. Cl.**

CPC **A61B 8/4427** (2013.01); **A61B 8/4472** (2013.01); **A61B 8/4488** (2013.01); **A61B 8/463** (2013.01); **A61B 8/465** (2013.01); **A61B 8/469** (2013.01); **A61B 8/5207** (2013.01); **A61B 8/56** (2013.01); **G01S 7/5208** (2013.01); **G01S 7/52082** (2013.01); **G01S 7/52085** (2013.01); **G01S 15/8909** (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,777,416 A 10/1988 George et al.
 5,343,869 A 9/1994 Pross et al.
 5,817,024 A * 10/1998 Ogle A61B 8/00
 600/447
 5,893,363 A * 4/1999 Little A61B 8/00
 600/447
 5,930,744 A 7/1999 Koch et al.
 6,063,030 A 5/2000 Vara et al.
 6,106,472 A * 8/2000 Chiang A61B 8/4236
 600/447

6,251,073 B1 6/2001 Imran et al.
 6,416,475 B1 7/2002 Hwang et al.
 6,440,072 B1 * 8/2002 Schuman A61B 5/0017
 600/437

6,464,636 B1 10/2002 Kinicki et al.
 6,475,146 B1 11/2002 Frelburger et al.
 6,482,158 B2 11/2002 Mault
 6,491,634 B1 * 12/2002 Leavitt G01N 29/06
 600/447

6,497,661 B1 12/2002 Brock-Fisher
 6,530,887 B1 3/2003 Gilbert et al.
 6,540,685 B1 4/2003 Rhoads et al.
 6,569,097 B1 5/2003 McMorrow et al.
 6,569,101 B2 5/2003 Quistgaard et al.
 6,575,908 B2 6/2003 Barnes et al.
 6,610,012 B2 8/2003 Mault
 6,635,019 B2 10/2003 Davidsen
 6,716,171 B1 4/2004 Brock-Fisher
 6,969,352 B2 11/2005 Chiang et al.
 6,997,876 B2 2/2006 Mo et al.
 7,022,075 B2 4/2006 Grunwald et al.
 7,238,157 B2 7/2007 McLaughlin et al.
 2003/0164820 A1 * 9/2003 Kent G06F 3/0418
 345/177

FOREIGN PATENT DOCUMENTS

JP 20030033350 A 2/2003
 WO 0701768 A2 1/1997
 WO 9828631 A2 7/1998
 WO 0019905 A1 4/2000
 WO 0031634 A1 6/2000
 WO 0079300 A1 12/2000
 WO 0113796 A1 3/2001

OTHER PUBLICATIONS

Unofficial translation of German Official Letter for German Patent Application No. 10254191.4 dated Feb. 21, 2014.
 Office Actions from Japanese Office for Application No. 2002-337732, dated Dec. 2, 2008 and May 12, 2009, 2 pages.

* cited by examiner

FIG. 1




FIG. 1B




FIG. 2




FIG. 3




FIG. 4





FIG. 5



METHOD AND SYSTEM FOR PDA-BASED ULTRASOUND

CROSS-REFERENCE TO RELATED APPLICATIONS/INCORPORATION BY REFERENCE

The present application is a continuation of U.S. patent application Ser. No. 14/274,122, filed May 9, 2014, which is a continuation of U.S. patent application Ser. No. 14/015,252, filed Aug. 30, 2013, which is a continuation of U.S. patent application Ser. No. 11/044,401, now U.S. Pat. No. 8,535,227, filed Jan. 27, 2005, which is a divisional of U.S. patent application Ser. No. 10/063,342, now U.S. Pat. No. 7,115,093, filed Apr. 12, 2002, which claims the benefit of U.S. Provisional Application Ser. No. 60/332,023, filed Nov. 21, 2001. Each of the above-identified applications is hereby incorporated herein by reference in its entirety.

FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

[Not Applicable]

BACKGROUND OF THE INVENTION

Certain embodiments of the present invention relate to a medical diagnostic ultrasound scanner. More particularly, certain embodiments relate to a method and system for configuring a personal digital assistant (PDA) device as an integral part of a portable, hand-held ultrasound system.

Traditional ultrasound systems are often large and bulky and do not lend themselves for ease of portability and tend to be expensive. Therefore, traditional ultrasound systems are not practical for certain market segments such as emergency medical personnel in ambulances, medical school students in training, and physicians and nurses at remote locations.

For example, today, emergency medical personnel (EMP) may use a stethoscope to listen to a patient's chest for lung rattles, or abdominal sounds such as bowel noise, or heart murmurs, etc. If equipped with ultrasound, the EMP could see fluid in the lungs, movement of the bowel, or blood flow in the heart. A more portable type of ultrasound system is required for such an application.

Smaller systems exist but are often still too expensive and/or do not provide desired features. For example, in U.S. Pat. No. 6,106,472 to Chiang et al., a portable ultrasound imaging system is described that uses charge coupled device (CCD) technology and performs beamforming in the analog domain. Such an implementation is limited by the specialized CCD technology and by performing beamforming in the analog domain.

It is more desirable to perform beamforming in the digital domain by first converting ultrasound data from the analog domain to the digital domain by, for example, using a simple analog-to-digital converter (ADC). Beamforming in the digital domain provides more flexibility and potentially better accuracy than beamforming in the analog domain.

A need exists for a small, inexpensive, highly portable ultrasound system employing existing technology that may be used quickly and easily for basic diagnosis in emergency situations at remote locations and for training purposes. A need also exists to perform digital beamforming in a highly portable ultrasound system in order increase beamforming flexibility and remove the need for specialized hardware.

BRIEF SUMMARY OF THE INVENTION

An embodiment of the present invention provides for a compact, inexpensive ultrasound system using an off-the-shelf, commercially available personal digital assistant (PDA) device interfacing to a signal beamforming module through a standard digital interface. A detachable ultrasound transducer head also interfaces to the beamforming module to form a hand-held probe assembly. The PDA runs Windows applications and displays menus and images to a user. The PDA is also modified to include ultrasound data processing and application software to support a plurality of ultrasound imaging modes. An internal battery is provided in the PDA to power the system. Digital beamforming is performed within the beamforming module by a beamforming ASIC.

A method is provided for attaching a detachable transducer head to a beamforming module to form a hand-held probe assembly that includes the beamforming module and the detachable transducer head. Ultrasound signals are received with the hand-held probe assembly from a region of interest to generate a plurality of received digital signals within the hand-held probe assembly. The plurality of received digital signals are digitally beamformed within the hand-held probe assembly to generate beams of digital data corresponding to the region of interest. The beams of digital data are transmitted to a commercially available personal digital assistant (PDA) over a standard digital interface to be further processed and displayed to a user as a displayed image representing the region of interest.

Certain embodiments of the present invention afford an approach to interface a standard, off-the-shelf, inexpensive PDA device to a hand-held ultrasound probe assembly to provide ultrasound scanning capability that is highly portable and affordable.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic block diagram of a portable diagnostic ultrasound system formed in accordance with an embodiment of the present invention such that digital beamforming is performed within a hand-held probe assembly.

FIG. 1B shows a realistic illustration of the portable diagnostic ultrasound system of FIG. 1.

FIG. 2 illustrates the formation of ultrasound beams in a scan plane originating at certain locations with respect to transducer elements in accordance with an embodiment of the present invention.

FIG. 3 illustrates an image frame made up of multiple received beams in accordance with an embodiment of the present invention.

FIG. 4 is a schematic block diagram of a diagnostic ultrasound system formed in accordance with another embodiment of the present invention such that digital beamforming is performed in a PDA device.

FIG. 5 is a schematic block diagram of a diagnostic ultrasound system formed in accordance with a third embodiment of the present invention.

The foregoing summary, as well as the following detailed description of certain embodiments of the present invention, will be better understood when read in conjunction with the appended drawings. It should be understood, however, that the present invention is not limited to the arrangements and instrumentality shown in the attached drawings.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 is a schematic block diagram of a portable ultrasound system 5 in accordance with an embodiment of the

present invention. Certain illustrated elements of the ultrasound system **5** include a detachable transducer module **10**, a beamforming module **40**, a PDA device **120**, and, optionally, an external battery/power source **110**. The transducer module **10** attaches to the beamforming module **40** to form a hand-held probe assembly **2**. In an embodiment of the present invention, the PDA **120** includes an internal battery to power the PDA **120** and the hand-held probe assembly **2**. A battery power interface **140** connects between the PDA **120** and the hand-held probe assembly **2**. FIG. 1B shows a more realistic illustration of the ultrasound system **5**.

The transducer module **10** comprises a 64-element transducer array **20** and a 64 channel to 16 channel multiplexer **30**. The beamforming module **40** comprises a pulser **60**, a TX/RX switching module **35**, a folder module **50**, a voltage controlled amplifier (VCA) **70**, an analog-to-digital converter (ADC) **80**, a beamforming ASIC **90**, and a PDA interface controller **100**. The PDA device **120** is a standard, off-the-shelf device such as a Palm Pilot running Windows applications such as Windows-CE applications and having a touch-screen display **125**. The PDA **120** is also modified to include ultrasound data processing and application software to support a plurality of ultrasound imaging modes.

In the transducer module **10**, the transducer array **20** is connected to the multiplexer **30**. When the transducer module **10** is connected to the beamforming module **40**, the multiplexer **30** is then connected to an input of TX/RX switching module **35**.

In the beamforming module **40**, the output of the TX/RX switching module **35** connects to the input of the folder module **50** and the output of the folder module **50** connects to the input of the VCA **70**. The output of the VCA **70** connects to the input of the ADC **80**. The output of the ADC **80** connects to the input of the beamforming ASIC **90**. The output of the beamforming ASIC **90** connects to the input of the PDA interface controller **100**. The output of the 16-channel pulser **60** connects to an input of TX/RX switching module **35**. Optionally, an external battery/power source **110** connects to beamforming module **40**.

The PDA interface controller **100** connects to the pulser **60**, and to the PDA device **120** through a standard digital interface **150**. In an embodiment of the present invention, the standard digital interface **150** is a Universal Serial Bus (USB) interface and the PDA interface controller **100** is a USB controller. Optionally, the standard digital interface **150** may be a parallel interface where the PDA interface controller **100** is a PC card. As a further alternative, the standard digital interface may be a wireless interface such as Bluetooth providing RF communication between the PDA interface controller **100** and the PDA **120**.

The various elements of the portable ultrasound system **5** may be combined or separated according to various embodiments of the present invention. For example, the folder **50** and VCA **70** may be combined into a single processing element. Also, the external battery **110** may be integrated into the beamforming module **40**, becoming an internal battery.

A function of the PDA-based ultrasound scanner **5** is to transmit ultrasound energy into a subject to be imaged, and receive and process backscattered ultrasound signals from the subject to create and display an image on the display **125** of the PDA device **120**. A user selects a transducer head **10** to connect to the beamforming module **40** to form a hand-held probe assembly **2** to be used for a particular scanning application. The transducer head is selected from a group of transducers including linear arrays, curved arrays, and

phased arrays. An imaging mode may be selected from a menu on the display **125** of the PDA device **120** using a touch-screen stylus.

To generate a transmitted beam of ultrasound energy, the PDA device **120** sends digital control signals to the PDA interface controller **100** within the beamforming module **40** through the standard digital interface **150**. The digital control signals instruct the beamforming module **40** to generate transmit parameters to create a beam of a certain shape that originates from a certain point at the surface of the transducer array **20**. The transmit parameters are selected in the pulser **60** in response to the digital control signals from the PDA device **120**. The pulser **60** uses the transmit parameters to properly encode transmit signals to be sent to the transducer array **20** through the TX/RX switching module **35** and the multiplexer **30**. The transmit signals are set at certain levels and phases with respect to each other and are provided to individual transducer elements of the transducer array **20**. The transmit signals excite the transducer elements of the transducer array **20** to emit ultrasound waves with the same phase and level relationships as the transmit signals. As a result, a transmitted beam of ultrasound energy is formed in a subject within a scan plane **200** (see FIG. 2) along a scan line **210** when the transducer array **20** is acoustically coupled to the subject by using, for example, ultrasound gel.

In an embodiment of the present invention, a single ultrasound beam is formed along a particular scan line (e.g. **210**) using 16 transducer elements. For example, elements **301** through **316** may be used to form a first ultrasound beam along a scan line **210** and elements **302** through **317** may be used to form a second adjacent ultrasound beam along a scan line **212** and so on. As a result, 64 ultrasound beams may be formed to create an image if the transducer array **20** has 64 transducer elements. Alternatively, elements **301** to **316** may be used to form a first ultrasound beam along a scan line **210** and elements **302** through **316** may be used to form a second adjacent ultrasound beam along a scan line **211** and elements **302** through **317** may be used to form a third ultrasound beam along a scan line **212** adjacent to the second ultrasound beam and so on. As a result, 128 ultrasound beams may be formed to create an image if the transducer array **20** has 64 transducer elements. In any event, the pulser **60** sends 16 transmit signals at a time through multiplexer **30** to form a given transmit ultrasound beam along a given scan line. The multiplexer **30** routes the transmit signals to the correct subset of transducer elements in the transducer array **20** to form a particular transmit beam along a particular scan line.

The transducer elements form a two-way transducer array **20**. Once ultrasound waves are transmitted into a subject, the ultrasound waves are backscattered off of tissue and blood samples within the structure. The backscattered waves arrive at the transducer array **20** at different times, depending on the distance into the subject they return from and the angle with respect to the surface of the transducer array **20** at which they return. The transducer elements are responsive to the backscattered waves and convert the ultrasound energy from the backscattered waves into received electrical signals.

The received electrical signals are routed through the multiplexer **30**, 16 signals at a time, to the folder module **50** by way of the TX/RX switching module **35** in beamforming module **40**. The folder module **50** uses the symmetry of the ultrasound beam to process the signals from the 8 right-most transducer elements in the same manner as the signals from the 8 left-most transducer elements since the ultrasound beam originates from the center of 16 transducer elements. The folder module **50** amplifies and weights the received

signals and collapses the original 16 received signals into 8 received signals due to the symmetry of the transducer elements about the received beam to be formed.

Next, the received signals are passed to the VCA 70. The VCA 70 provides the function of gain compensation as a function of time (distance into the image). Next, the ADC 80 digitizes the received signals. The beamforming ASIC 90 then takes the digitized received signals and creates a received beam of data along a scan line (e.g. 210). The beamforming ASIC 90 operates on the digitized received signals by performing time delaying and summing to create the received beam of data corresponding to sample volumes along a scan line (e.g. 210) in the scan plane 200 within the subject. The beamforming ASIC 90 is a digital ASIC performing beamforming in the digital domain and providing beamforming flexibility. For example, the beamforming ASIC 90 may be digitally loaded with various beamforming coefficients and instructions from the PDA 120 to perform different types of digital beamforming.

The received beam of digital data is sent to the PDA device 120 by the PDA interface controller 100 over the standard digital interface 150. The process is repeated for the next receive beam to be formed and so on to generate all of the received beams 260 that make up the image frame 250 for the region of interest (see FIG. 3).

The PDA device 120 collects and processes the received beam data for the entire set of received beams 260 that make up an image frame 250 and displays the resultant image to the user on the display 125 of the PDA device 120. The PDA device 120 performs ultrasound data processing including the ultrasound functions of demodulation, parameter estimation, scan conversion, and display processing. A plurality of ultrasound modes may be supported including Doppler processing modes and non-Doppler processing modes.

Frame rates on the order of 10 frames per second may be achieved and the system may consume less than 5 watts of power, allowing for operation over approximately a 2-hour period of time.

As an alternative, the function of the beamforming ASIC 90 may be performed by software in the PDA device 120 as shown in FIG. 4. Instead of the transducer head attaching to a beamforming module 40, it attaches to a signal processing module 45 that does not include the beamforming ASIC 90. The data out of the ADC 80 is sent to the PDA interface controller 100 and the pre-beamformed data is sent to the PDA 120. Digital beamforming is performed by software within the PDA 120 along with the other subsequent data processing functions.

As a further alternative, the hand-held-probe assembly may include an internal battery to provide power. A docking station may also be provided for the hand-held probe assembly to provide the function of battery recharging.

As still a further alternative, the transducer module 10 may be a sterile probe for use in an operating room (OR), such as in a sterile wireless probe assembly.

As yet another alternative, the beamforming module (or signal processing module) may be designed to perform 16 bit processing. For example, the folder module 50 may be eliminated and the VCA 70 and the ADC 80 may be designed to handle 16 bits instead of just 8 bits as shown in FIG. 5.

The various configurations and interfaces within the system 5 may be combined or separated according to various embodiments of the present invention. For example, the beamforming module 40 may comprise custom hardware

elements such as a small circuit board with digital signal processors or may comprise readily available off-the-shelf components.

In summary, the advantages and features include, among others, a light-weight, portable ultrasound system based on inexpensive, off-the-shelf PDA technology to provide high portability and ease of use for certain users. Digital beamforming provides maximum beamforming flexibility, and a transducer head may be selected from a set of detachable transducer heads to connect to a beamforming or signal processing module to form a hand-held probe assembly. A user may easily change applications by attaching a different transducer head to the beamforming module or signal processing module and/or by selecting a new imaging application on the touch-screen display of the PDA.

While the invention has been described with reference to certain embodiments, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted without departing from the scope of the invention. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the invention without departing from its scope. Therefore, it is intended that the invention not be limited to the particular embodiment disclosed, but that the invention will include all embodiments falling within the scope of the appended claims.

The invention claimed is:

1. A system for performing ultrasound imaging, the system comprising:
 - a hand-held probe assembly comprising:
 - a transducer head configured to receive ultrasound signals; and
 - a beamforming module comprising at least one probe processor disposed in a hand-held probe assembly housing, the at least one probe processor configured to:
 - generate a plurality of received digital signals from the ultrasound signals; and
 - digitally beamform the plurality of received digital signals to generate at least one beam of digital data;
 - a hand-held display assembly comprising:
 - at least one display processor disposed in a hand-held display assembly housing, the at least one display processor configured to execute ultrasound application software to create an ultrasound image from the at least one beam of digital data, wherein the ultrasound application software is configured to perform scan conversion; and
 - a display configured to present the ultrasound image; and
 - a digital interface configured to communicatively couple the hand-held probe assembly with the hand-held display assembly, wherein the at least one beam of digital data is transmitted over the digital interface.
2. The system of claim 1, wherein the digital interface is a standard digital interface.
3. The system of claim 2, wherein the standard digital interface is wireless.
4. The system of claim 2, wherein the standard digital interface is a Universal Serial Bus (USB) interface.
5. The system of claim 1, wherein the at least one display processor is configured to receive an imaging mode selection from a plurality of imaging modes via a user interface at the hand-held display assembly.
6. The system of claim 5, wherein the ultrasound application software is configured to create the ultrasound image based at least in part on the imaging mode selection.

7. The system of claim 5, wherein the at least one display processor is configured to send a digital control signal via the digital interface to the beamforming module, the digital control signal comprising instructions for generating transmit parameters to acquire the ultrasound signals.

8. The system of claim 1, wherein the ultrasound application software is configured to perform one or both demodulation and parameter estimation.

9. The system of 1, wherein the transducer head is one of a plurality of detachable transducer heads, each of the plurality of detachable transducer heads of a different type corresponding to one of a plurality of imaging applications of the ultrasound application software, and wherein each of the plurality of detachable transducer heads is configured to detachably couple with the beamforming module.

10. The system of claim 1, wherein the display is a touch-screen display.

11. The system of claim 1, wherein the touch-screen display is configured to display menus generated by the ultrasound application software.

12. The system of claim 1, wherein the hand-held probe assembly includes an internal battery to power the hand-held probe assembly.

13. The system of claim 1, comprising a docking station to plug the hand-held probe assembly into for charging a battery of the hand-held probe assembly.

14. The system of claim 1, wherein each of the hand-held probe assembly and the hand-held display assembly comprises an internal battery.

15. The system of claim 1, comprising a cable with a detachable connector configured to detachably couple the hand-held probe assembly and the hand-held display assembly.

16. The system of claim 1, wherein the transducer head comprises:

- a set of transducer elements; and
- a multiplexer connecting to the set of transducer elements to select and route a first set of received analog signals from a subset of the set of transducer elements to the beamforming module.

17. The system of claim 1, wherein the beamforming module comprises:

- an analog-to-digital converter (ADC) configured to convert a third set of received analog signals to a first set of received digital signals; and
- a pulser module configured to generate a set of analog transmit signals in response to digital control data received from the hand-held display assembly and send the set of analog transmit signals to the transducer head.

18. The system of claim 17, wherein the beamforming module comprises:

- a TX/RX switching module configured to switch between passing the set of analog transmit signals and a first set of received analog signals;
- a folder module configured to generate a second set of received analog signals from the first set of received analog signals received from the transducer head via the TX/RX switching module;
- a voltage controlled amplifier (VCA) connecting to the folder module and configured to generate the third set of received analog signals from the second set of received analog signals; and
- a digital interface controller connecting to the ADC and configured to transmit the first set of received digital signals to the hand-held display assembly and receive the digital control data from the hand-held display assembly over the digital interface.

19. A method of ultrasound imaging, the method comprising:

receiving ultrasound signals at a transducer head of a hand-held probe assembly;

generating, by at least one probe processor disposed in a hand-held probe assembly housing of a beamforming module of the hand-held probe assembly, a plurality of received digital signals from the ultrasound signals; digitally beamforming, by the at least one probe processor, the plurality of received digital signals to generate at least one beam of digital data;

transmitting the at least one beam of digital data to a hand-held display assembly over a digital interface communicatively coupling the hand-held probe assembly with the hand-held display assembly;

executing, by at least one display processor disposed in a hand-held display assembly housing of the hand-held display assembly, ultrasound application software to create an ultrasound image from the at least one beam of digital data, wherein the ultrasound application software is configured to perform scan conversion; and presenting, at a display of the hand-held display assembly, the ultrasound image.

20. The method of claim 19, wherein the digital interface is a standard digital interface.

21. The method of claim 20, wherein the standard digital interface is wireless.

22. The method of claim 20, wherein the standard digital interface is a Universal Serial Bus (USB) interface.

23. The method of claim 19, comprising receiving, by the at least one display processor, an imaging mode selection from a plurality of image modes via a user interface at the hand-held display assembly.

24. The method of claim 23, wherein the executing the ultrasound application software to create the ultrasound image is based at least in part on the imaging mode selection.

25. The method of claim 23, comprising transmitting, by the at least one display processor, a digital control signal via the digital interface to the beamforming module, the digital control signal comprising instructions for generating transmit parameters to acquire the ultrasound signals.

26. The method of claim 19, comprising performing by the at least one display processor executing the ultrasound application software, one or both of demodulation and parameter estimation.

27. The method of 19, comprising automatically changing to one of a plurality of imaging applications based on the transducer head detachably coupled to the beamforming module, wherein the transducer head is one of a plurality of detachable transducer heads configured to detachably couple with a beamforming module of the hand-held probe assembly, each of the plurality of detachable transducer heads of a different type corresponding to one of the plurality of imaging applications of the ultrasound application software.

28. The method of claim 19, wherein the display is a touch-screen display.

29. The method of claim 28, comprising displaying menus generated by the ultrasound application software at touch-screen display.

30. The method of claim 19, comprising detachably coupling the hand-held probe assembly and the hand-held display assembly by a cable with a detachable connector.

31. The method of claim 19, wherein the transducer head is one of a plurality of detachable transducer heads selected from a group comprising a linear array transducer, a curved array transducer, and a phased array transducer.

32. The method of claim **19**, wherein the executing, by the at least one display processor, the ultrasound application software to create the ultrasound image from the at least one beam of digital data comprises:

demodulating the at least one beam of digital data to 5
generate demodulated data;
parameter estimating the demodulated data to generate
parameter estimate data;
scan converting the parameter estimate data to generate
scan converted data; and 10
display processing the scan converted data to create the
ultrasound image for presentation on the display of the
hand-held display assembly.

33. The method of claim **32**, wherein the parameter
estimating comprises performing Doppler processing. 15

34. The method of claim **19**, wherein the digitally beam-
forming includes time delaying and summing the plurality of
received digital signals.

35. The method of claim **19**, comprising recharging an
internal battery in the hand-held probe assembly. 20

* * * * *

专利名称(译)	PDA超声的方法和系统		
公开(公告)号	US10575821	公开(公告)日	2020-03-03
申请号	US15/910724	申请日	2018-03-02
申请(专利权)人(译)	通用电气医疗系统全球性技术公司，有限责任公司		
当前申请(专利权)人(译)	通用电气医疗系统全球性技术公司，有限责任公司		
[标]发明人	HALMANN MENACHEM AMEMIYA SHINICHI		
发明人	HALMANN, MENACHEM AMEMIYA, SHINICHI		
IPC分类号	A61B5/00 A61B8/00 A61B8/14 A61B8/08 G01S15/89 G01S7/52		
CPC分类号	A61B8/5207 G01S7/5208 A61B8/463 G01S7/52085 A61B8/4411 A61B8/145 G01S15/8909 A61B8/4488 A61B8/14 A61B8/462 G01S7/52082 A61B8/469 A61B8/4427 A61B8/4472 A61B8/465 A61B8/56		
代理人(译)	贝茨DAVID		
优先权	60/332023 2001-11-21 US		
其他公开文献	US20180185009A1		
外部链接	Espacenet		

摘要(译)

公开了一种用于紧凑，便宜的超声系统的方法和系统，该超声系统使用通过标准数字接口与手持式探针组件接口的现成的个人数字助理（PDA）设备。手持式探针组件包括可拆卸的换能器头，该换能器头连接到执行数字波束形成的波束形成模块。PDA运行Windows应用程序，并向用户显示菜单和图像。PDA还运行超声数据处理软件以支持多种成像模式。PDA中提供了一个内部电池来为系统供电。换能器头可从波束形成模块上卸下。

