



US009504446B2

(12) **United States Patent**
Jaeger et al.

(10) **Patent No.:** **US 9,504,446 B2**
(45) **Date of Patent:** **Nov. 29, 2016**

(54) **SYSTEMS AND METHODS FOR COUPLING
AN ULTRASOUND SOURCE TO TISSUE**

(75) Inventors: **Paul Jaeger**, Mesa, AZ (US); **Peter G.
Barthe**, Phoenix, AZ (US); **Michael H.
Slayton**, Tempe, AZ (US)

(73) Assignee: **GUIDED THERAPY SYSTEMS,
LLC**, Mesa, AZ (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 600 days.

(21) Appl. No.: **13/547,023**

(22) Filed: **Jul. 11, 2012**

(65) **Prior Publication Data**

US 2013/0012838 A1 Jan. 10, 2013

Related U.S. Application Data

(63) Continuation-in-part of application No. 13/136,544,
filed on Aug. 2, 2011.

(60) Provisional application No. 61/506,609, filed on Jul.
11, 2011, provisional application No. 61/506,610,

(Continued)

(51) **Int. Cl.**
A61B 8/00 (2006.01)
A61N 7/02 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **A61B 8/429** (2013.01); **A61B 8/56**
(2013.01); **A61N 7/02** (2013.01); **A61B**
2018/00642 (2013.01); **A61B 2018/00898**
(2013.01); **A61B 2090/378** (2016.02); **A61N**
2007/006 (2013.01);

(Continued)

(58) **Field of Classification Search**
CPC A61B 8/429; A61B 8/56; A61B

2018/00642; A61B 2018/00898; A61B
2090/378; A61N 7/02; A61N 2007/0034;
A61N 2007/006; A61N 2007/0095; A61N
2007/0091; A61N 2007/027
USPC 600/437-480; 601/2-4
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,427,348 A 9/1947 Bond et al.
3,913,386 A 10/1975 Saglio

(Continued)

FOREIGN PATENT DOCUMENTS

DE 4029175 3/1992
DE 10140064 3/2003

(Continued)

OTHER PUBLICATIONS

Alster, Tinas S., Tanzi, Elizabeth L., "Cellulite Treatment using a
Novel Combination Radiofrequency, Infrared Light, and Mechanical
Tissue Manipulation Device," Journal of Cosmetic & Laser
Therapy, Jun. 2005, vol. 7, Issue 2, pp. 81-85.

(Continued)

Primary Examiner — Long V Le


Assistant Examiner — Angela M Hoffa

(74) *Attorney, Agent, or Firm* — Quarles & Brady, LLP

(57) **ABSTRACT**

This disclosure provides systems and methods for sensing
coupling of an ultrasound source to a target and for provid-
ing a constant average output of power from an ultrasound
source. The systems and methods can include a frequency
sweep function. The systems and methods can also include
receiving reflected energy from an acoustic window and
determining a feedback using the reflected energy. The
systems and methods can also include comparing the feed-
back with a threshold level and using the comparison to
determine if the ultrasound source is coupled with a target.

14 Claims, 6 Drawing Sheets



Related U.S. Application Data

filed on Jul. 11, 2011, provisional application No. 61/369,782, filed on Aug. 2, 2010, provisional application No. 61/369,793, filed on Aug. 2, 2010, provisional application No. 61/369,806, filed on Aug. 2, 2010, provisional application No. 61/370,095, filed on Aug. 2, 2010.

(51) Int. Cl.

A61B 18/00 (2006.01)

A61N 7/00 (2006.01)

(52) U.S. Cl.

CPC *A61N 2007/0034* (2013.01); *A61N 2007/0091* (2013.01); *A61N 2007/0095* (2013.01); *A61N 2007/027* (2013.01)

(56) References Cited

U.S. PATENT DOCUMENTS

3,965,455 A	6/1976	Hurwitz	4,874,562 A	10/1989	Hyon
3,992,925 A	11/1976	Perillhou	4,875,487 A	10/1989	Seppi
4,039,312 A	8/1977	Patru	4,891,043 A	1/1990	Zeimer et al.
4,059,098 A	11/1977	Murdock	4,893,624 A	1/1990	Lele
4,101,795 A	7/1978	Fukumoto	4,896,673 A	1/1990	Rose
4,166,967 A	9/1979	Benes et al.	4,900,540 A	2/1990	Ryan et al.
4,211,948 A	7/1980	Brisken et al.	4,901,729 A	2/1990	Saitoh et al.
4,211,949 A	7/1980	Brisken et al.	4,917,096 A	4/1990	Englehart
4,213,344 A	7/1980	Rose	4,932,414 A	6/1990	Coleman et al.
4,276,491 A	6/1981	Daniel	4,938,216 A	7/1990	Lele
4,315,514 A	2/1982	Drewes et al.	4,938,217 A	7/1990	Lele
4,325,381 A	4/1982	Glenn	4,947,046 A	8/1990	Kawabata et al.
4,343,301 A	8/1982	Indech	4,951,653 A	8/1990	Fry
4,372,296 A	2/1983	Fahim	4,955,365 A	9/1990	Fry
4,379,145 A	4/1983	Masuhio et al.	4,958,626 A	9/1990	Nambu
4,381,007 A	4/1983	Doss	4,976,709 A	12/1990	Sand
4,381,787 A	5/1983	Hottinger	4,979,501 A	12/1990	Valchanov
4,397,314 A	8/1983	Vaguine	4,992,989 A	2/1991	Watanabe et al.
4,409,839 A	10/1983	Taenzer	5,012,797 A	5/1991	Liang
4,431,008 A	2/1984	Wanner et al.	5,018,508 A	5/1991	Fry et al.
4,441,486 A	4/1984	Pounds	5,030,874 A	7/1991	Saito et al.
4,452,084 A	6/1984	Taenzer	5,036,855 A	8/1991	Fry
4,484,569 A	11/1984	Driller	5,040,537 A	8/1991	Katakura
4,507,582 A	3/1985	Glenn	5,054,310 A	10/1991	Flynn
4,513,749 A	4/1985	Kino	5,054,470 A	10/1991	Fry
4,513,750 A	4/1985	Heyman et al.	5,070,879 A	12/1991	Herres
4,527,550 A	7/1985	Ruggera et al.	5,088,495 A	2/1992	Miyagawa
4,528,979 A	7/1985	Marchenko	5,115,814 A	5/1992	Griffith
4,534,221 A	8/1985	Fife et al.	5,117,832 A	6/1992	Sanghvi
4,566,459 A	1/1986	Umemura et al.	5,123,418 A	6/1992	Saurel
4,567,895 A	2/1986	Putzke	5,143,063 A	9/1992	Fellner
4,586,512 A	5/1986	Do-huu	5,143,074 A	9/1992	Dory
4,601,296 A	7/1986	Yerushalmi	5,149,319 A	9/1992	Unger
4,603,702 A *	8/1986	Hwang et al. 600/437	5,150,711 A	9/1992	Dory
4,620,546 A	11/1986	Aida et al.	5,150,714 A	9/1992	Green
4,637,256 A	1/1987	Sugiyama et al.	5,152,294 A	10/1992	Mochizuki et al.
4,646,756 A	3/1987	Watmough	5,156,144 A	10/1992	Iwasaki et al.
4,663,358 A	5/1987	Hyon	5,158,536 A	10/1992	Sekins
4,668,516 A	5/1987	Duraffourd	5,159,931 A	11/1992	Pini
4,672,591 A	6/1987	Breimesser et al.	5,163,421 A	11/1992	Bernstein et al.
4,680,499 A	7/1987	Umemura et al.	5,163,436 A	11/1992	Saitoh et al.
4,697,588 A	10/1987	Reichenberger	5,178,135 A	1/1993	Uchiyama et al.
4,708,127 A *	11/1987	Abdelghani 601/2	5,190,518 A	3/1993	Takasu
4,754,760 A	7/1988	Fukukita et al.	5,190,766 A	3/1993	Ishihara
4,757,820 A	7/1988	Itoh	5,191,880 A	3/1993	McLeod
4,771,205 A	9/1988	Mequio	5,205,287 A	4/1993	Erbel et al.
4,801,459 A	1/1989	Liburdy	5,209,720 A	5/1993	Unger
4,803,625 A	2/1989	Fu et al.	5,212,671 A	5/1993	Fujii et al.
4,807,633 A	2/1989	Fry	5,215,680 A	6/1993	D Arrigo
4,817,615 A	4/1989	Fukukita et al.	5,224,467 A	7/1993	Oku
4,858,613 A	8/1989	Fry	5,230,334 A	7/1993	Klopotek
4,860,732 A	8/1989	Hasegawa et al.	5,230,338 A	7/1993	Allen et al.
4,865,041 A	9/1989	Hassler	5,247,924 A	9/1993	Suzuki et al.
4,865,042 A	9/1989	Umemura	5,255,681 A	10/1993	Ishimura et al.
4,867,169 A	9/1989	Machida	5,257,970 A	11/1993	Dougherty
			5,265,614 A	11/1993	Hayakawa
			5,267,985 A	12/1993	Shimada et al.
			5,269,297 A	12/1993	Weng
			5,282,797 A	2/1994	Chess
			5,295,484 A	3/1994	Marcus
			5,295,486 A	3/1994	Wollschlager et al.
			5,304,169 A	4/1994	Sand
			5,305,756 A	4/1994	Entrekin et al.
			5,321,520 A	6/1994	Inga et al.
			5,323,779 A	6/1994	Hardy et al.
			5,327,895 A	7/1994	Hashimoto et al.
			5,348,016 A	9/1994	Unger et al.
			5,360,268 A	11/1994	Hayashi
			5,370,121 A	12/1994	Reichenberger
			5,371,483 A	12/1994	Bhardwaj
			5,375,602 A	12/1994	Lancee et al.
			5,379,773 A	1/1995	Hornsby
			5,380,280 A	1/1995	Peterson
			5,380,519 A	1/1995	Schneider et al.
			5,383,917 A	1/1995	Desai et al.
			5,391,140 A	2/1995	Schaetzle
			5,391,197 A	2/1995	Burdette et al.
			5,392,259 A	2/1995	Bolorforosh
			5,396,143 A	3/1995	Seyed-Bolorforosh et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

5,398,689 A	3/1995	Connor et al.	5,727,554 A	3/1998	Kalend et al.
5,406,503 A	4/1995	Williams, Jr. et al.	5,735,280 A	4/1998	Sherman et al.
5,417,216 A	5/1995	Tanaka	5,743,863 A	4/1998	Chapelon
5,419,327 A	5/1995	Rohwedder	5,746,005 A	5/1998	Steinberg
5,423,220 A	6/1995	Finsterwald et al.	5,746,762 A	5/1998	Bass
5,435,311 A	7/1995	Umemura	5,748,767 A	5/1998	Raab
5,438,998 A	8/1995	Hanafy	5,749,364 A	5/1998	Sliwa et al.
5,458,596 A	10/1995	Lax	5,755,228 A	5/1998	Wilson et al.
5,460,179 A	10/1995	Okunuki et al.	5,755,753 A	5/1998	Knowlton
5,460,595 A	10/1995	Hall et al.	5,762,066 A	6/1998	Law
5,469,854 A	11/1995	Unger et al.	5,763,886 A	6/1998	Schulte
5,471,988 A	12/1995	Fujio	5,769,790 A	6/1998	Watkins
5,487,388 A	1/1996	Rello et al.	5,779,644 A	7/1998	Eberle et al.
5,492,126 A	2/1996	Hennige	5,792,058 A	8/1998	Lee et al.
5,496,256 A	3/1996	Bock	5,795,297 A	8/1998	Daigle
5,501,655 A	3/1996	Rolt	5,795,311 A	8/1998	Wess
5,503,152 A	4/1996	Oakley et al.	5,810,009 A	9/1998	Mine et al.
5,503,320 A	4/1996	Webster et al.	5,810,888 A	9/1998	Fenn
5,507,790 A	4/1996	Weiss	5,814,599 A	9/1998	Mitragotri et al.
5,520,188 A	5/1996	Hennige	5,817,013 A	10/1998	Ginn et al.
5,522,869 A	6/1996	Burdette	5,817,021 A	10/1998	Reichenberger
5,523,058 A	6/1996	Umemura et al.	5,820,564 A	10/1998	Slayton
5,524,620 A	6/1996	Rosenschein	5,823,962 A	10/1998	Schaetzle
5,524,624 A	6/1996	Tepper	5,827,204 A	10/1998	Grandia et al.
5,524,625 A	6/1996	Okazaki et al.	5,840,032 A	11/1998	Hatfield et al.
5,526,624 A	6/1996	Berg	5,844,140 A	12/1998	Seale
5,526,812 A	6/1996	Dumoulin et al.	5,853,367 A	12/1998	Chalek et al.
5,526,814 A	6/1996	Cline et al.	5,869,751 A	2/1999	Bonin
5,526,815 A	6/1996	Granz	5,871,524 A	2/1999	Knowlton
5,529,070 A	6/1996	Augustine et al.	5,873,902 A	2/1999	Sanghvi
5,540,235 A	7/1996	Wilson	5,876,431 A	3/1999	Spehr et al.
5,558,092 A	9/1996	Unger	5,879,303 A	3/1999	Averkiou et al.
5,560,362 A	10/1996	Sliwa et al.	5,882,557 A	3/1999	Hayakawa
5,575,291 A	11/1996	Hayakawa	5,891,034 A	4/1999	Bucholz
5,575,807 A	11/1996	Faller	5,899,861 A	5/1999	Friemel et al.
5,577,502 A	11/1996	Darrow et al.	5,904,659 A	5/1999	Duarte
5,577,507 A	11/1996	Snyder et al.	5,919,219 A	7/1999	Knowlton
5,577,991 A	11/1996	Akui et al.	5,923,099 A	7/1999	Bilir
5,580,575 A	12/1996	Unger et al.	5,924,989 A	7/1999	Polz
5,601,526 A	2/1997	Chapelon	5,928,169 A	7/1999	Schatzle et al.
5,603,323 A	2/1997	Pflugrath et al.	5,931,805 A	8/1999	Brisken
5,609,562 A	3/1997	Kaali	5,938,606 A	8/1999	Bonnefous
5,615,091 A	3/1997	Palatnik	5,938,612 A	8/1999	Kline-Schoder et al.
5,617,858 A	4/1997	Taverna et al.	5,948,011 A	9/1999	Knowlton
5,618,275 A	4/1997	Bock	5,957,844 A	9/1999	Dekel
5,620,479 A	4/1997	Diederich	5,957,882 A	9/1999	Nita et al.
5,622,175 A	4/1997	Sudol et al.	5,957,941 A	9/1999	Ream
5,638,819 A	6/1997	Manwaring et al.	5,967,980 A	10/1999	Ferre et al.
5,643,179 A	7/1997	Fujimoto	5,968,034 A	10/1999	Fullmer
5,644,085 A	7/1997	Lorraine et al.	5,971,949 A	10/1999	Levin
5,647,373 A	7/1997	Paltiel	5,977,538 A	11/1999	Unger et al.
5,654,509 A *	8/1997	Miele et al. 73/602	5,984,882 A	11/1999	Rosenschein
5,655,535 A	8/1997	Friemel et al.	5,990,598 A	11/1999	Sudol et al.
5,655,538 A	8/1997	Lorraine	5,997,471 A	12/1999	Gumb et al.
5,657,760 A	8/1997	Ying	5,997,497 A	12/1999	Nita et al.
5,658,328 A	8/1997	Johnson	5,999,843 A	12/1999	Anbar
5,660,836 A	8/1997	Knowlton	6,004,262 A	12/1999	Putz et al.
5,662,116 A	9/1997	Kondo et al.	6,007,499 A	12/1999	Martin et al.
5,665,053 A	9/1997	Jacobs	6,013,032 A	1/2000	Savord
5,665,141 A	9/1997	Vago	6,016,255 A	1/2000	Bolan et al.
5,671,746 A	9/1997	Dreschel et al.	6,019,724 A	2/2000	Gronningsaeter et al.
5,673,699 A	10/1997	Trahey et al.	6,022,308 A	2/2000	Williams
5,676,692 A	10/1997	Sanghvi	6,022,327 A	2/2000	Chang
5,685,820 A	11/1997	Riek et al.	6,036,646 A	3/2000	Barthe
5,687,737 A	11/1997	Branham et al.	6,039,048 A	3/2000	Silberg
5,690,608 A	11/1997	Watanabe	6,039,689 A	3/2000	Lizzi
5,694,936 A	12/1997	Fujimoto	6,042,556 A	3/2000	Beach et al.
5,697,897 A	12/1997	Buchholtz	6,049,159 A	4/2000	Barthe
5,701,900 A	12/1997	Shehada et al.	6,050,943 A	4/2000	Slayton
5,704,361 A	1/1998	Seward et al.	6,059,727 A	5/2000	Fowlkes
5,706,252 A	1/1998	Le Verrier et al.	6,071,239 A	6/2000	Cribbs
5,706,564 A	1/1998	Rhyne	6,080,108 A	6/2000	Dunham
5,715,823 A	2/1998	Wood et al.	6,083,148 A	7/2000	Williams
5,720,287 A	2/1998	Chapelon et al.	6,086,535 A	7/2000	Ishibashi
5,722,411 A	3/1998	Suzuki	6,086,580 A	7/2000	Mordon et al.
			6,090,054 A	7/2000	Tagishi
			6,093,883 A	7/2000	Sanghvi
			6,101,407 A	8/2000	Groezienger
			6,106,469 A	8/2000	Suzuki et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,113,558 A	9/2000	Rosenschein	6,461,378 B1	10/2002	Knowlton
6,113,559 A	9/2000	Klopotek	6,470,216 B1	10/2002	Knowlton
6,120,452 A	9/2000	Barthe	6,488,626 B1	12/2002	Lizzi et al.
6,123,081 A	9/2000	Durette	6,491,657 B2	12/2002	Rowe
6,126,619 A	10/2000	Peterson et al.	6,500,121 B1	12/2002	Slayton
6,135,971 A	10/2000	Hutchinson et al.	6,500,141 B1	12/2002	Irion
6,139,499 A	10/2000	Wilk	6,508,774 B1	1/2003	Acker
6,159,150 A	12/2000	Yale et al.	6,511,427 B1	1/2003	Sliwa, Jr. et al.
6,171,244 B1	1/2001	Finger et al.	6,511,428 B1	1/2003	Azuma
6,176,840 B1	1/2001	Nishimura	6,514,244 B2	2/2003	Pope
6,183,426 B1	2/2001	Akisada	6,517,484 B1	2/2003	Wilk et al.
6,183,502 B1	2/2001	Takeuchi	6,524,250 B1	2/2003	Weber
6,183,773 B1	2/2001	Anderson	6,540,679 B2	4/2003	Slayton
6,190,323 B1	2/2001	Digs et al.	6,540,685 B1	4/2003	Rhoads et al.
6,190,336 B1	2/2001	Duarte	6,540,700 B1	4/2003	Fujimoto et al.
6,193,658 B1	2/2001	Wendelken et al.	6,554,771 B1	4/2003	Buil et al.
6,210,327 B1	4/2001	Brackett et al.	6,569,099 B1	5/2003	Babaev
6,213,948 B1	4/2001	Barthe	6,569,108 B2	5/2003	Sarvazyan et al.
6,216,029 B1	4/2001	Paltieli	6,572,552 B2	6/2003	Fukukita
6,233,476 B1	5/2001	Strommer et al.	6,575,956 B1	6/2003	Briskin et al.
6,234,990 B1	5/2001	Rowe et al.	6,595,934 B1	7/2003	Hissong
6,241,753 B1	6/2001	Knowlton	6,599,256 B1	7/2003	Acker
6,246,898 B1	6/2001	Vesely et al.	6,607,498 B2	8/2003	Eshel
6,251,074 B1	6/2001	Averkiou et al.	6,610,011 B2 *	8/2003	Emery 600/437
6,251,088 B1	6/2001	Kaufman et al.	6,618,620 B1	9/2003	Freundlich et al.
6,268,405 B1	7/2001	Yao	6,623,430 B1	9/2003	Slayton
6,273,864 B1	8/2001	Duarte	6,626,854 B2	9/2003	Friedman
6,273,884 B1 *	8/2001	Altshuler et al. 606/9	6,626,855 B1	9/2003	Weng
6,280,402 B1	8/2001	Ishibashi et al.	6,638,226 B2	10/2003	He et al.
6,287,257 B1	9/2001	Matichuk	6,645,162 B2	11/2003	Friedman
6,296,619 B1	10/2001	Briskin	6,662,054 B2	12/2003	Kreindel
6,301,989 B1	10/2001	Brown et al.	6,663,627 B2	12/2003	Francischelli
6,309,355 B1	10/2001	Cain et al.	6,665,806 B1	12/2003	Shimizu
6,311,090 B1	10/2001	Knowlton	6,666,835 B2	12/2003	Martin
6,315,741 B1	11/2001	Martin	6,669,638 B1	12/2003	Miller et al.
6,322,509 B1	11/2001	Pan et al.	6,685,640 B1	2/2004	Fry
6,322,532 B1	11/2001	D'Sa	6,692,450 B1	2/2004	Coleman
6,325,540 B1	12/2001	Lounsberry et al.	6,699,237 B2	3/2004	Weber
6,325,758 B1	12/2001	Carol et al.	6,716,184 B2	4/2004	Vaezy et al.
6,325,769 B1	12/2001	Klopotek	6,719,449 B1	4/2004	Laughlin
6,325,798 B1	12/2001	Edwards et al.	6,719,694 B2	4/2004	Weng
6,338,716 B1	1/2002	Hossack et al.	6,726,627 B1	4/2004	Lizzi et al.
6,350,276 B1	2/2002	Knowlton	6,733,449 B1	5/2004	Krishnamurthy et al.
6,356,780 B1	3/2002	Licato et al.	6,749,624 B2	6/2004	Knowlton
6,361,531 B1	3/2002	Hissong	6,773,409 B2	8/2004	Truckai et al.
6,370,411 B1	4/2002	Osadchy et al.	6,775,404 B1	8/2004	Pagoulatos et al.
6,375,672 B1	4/2002	Aksan	6,790,187 B2	9/2004	Thompson et al.
6,377,854 B1	4/2002	Knowlton	6,824,516 B2	11/2004	Batten et al.
6,377,855 B1	4/2002	Knowlton	6,825,176 B2	11/2004	White
6,381,497 B1	4/2002	Knowlton	6,835,940 B2	12/2004	Morikawa et al.
6,381,498 B1	4/2002	Knowlton	6,846,290 B2	1/2005	Lizzi et al.
6,387,380 B1	5/2002	Knowlton	6,875,176 B2	4/2005	Mourad et al.
6,390,982 B1	5/2002	Bova et al.	6,882,884 B1	4/2005	Mosk et al.
6,405,090 B1	6/2002	Knowlton	6,887,239 B2	5/2005	Elstrom
6,409,720 B1	6/2002	Hissong	6,889,089 B2	5/2005	Behl
6,413,216 B1	7/2002	Cain et al.	6,896,657 B2	5/2005	Willis
6,413,253 B1	7/2002	Koop	6,902,536 B2	6/2005	Manna
6,413,254 B1	7/2002	Hissong	6,905,466 B2	6/2005	Salgo
6,419,648 B1	7/2002	Vitek	6,918,907 B2	7/2005	Kelly
6,423,007 B2	7/2002	Lizzi et al.	6,920,883 B2	7/2005	Bessette
6,425,865 B1	7/2002	Salcudean	6,921,371 B2	7/2005	Wilson
6,425,867 B1	7/2002	Vaezy	6,932,771 B2	8/2005	Whitmore
6,425,912 B1	7/2002	Knowlton	6,932,814 B2	8/2005	Wood
6,428,477 B1	8/2002	Mason	6,936,044 B2	8/2005	McDaniel
6,428,532 B1	8/2002	Doukas et al.	6,936,046 B2	8/2005	Hissong
6,430,446 B1	8/2002	Knowlton	6,945,937 B2	9/2005	Culp et al.
6,432,057 B1	8/2002	Mazess et al.	6,948,843 B2	9/2005	Laugharn et al.
6,432,067 B1	8/2002	Martin	6,953,941 B2	10/2005	Nakano et al.
6,432,101 B1	8/2002	Weber	6,958,043 B2	10/2005	Hissong
6,436,061 B1	8/2002	Costantino	6,971,994 B1	12/2005	Young et al.
6,438,424 B1	8/2002	Knowlton	6,974,417 B2	12/2005	Lockwood
6,440,071 B1	8/2002	Slayton	6,976,492 B2	12/2005	Ingle
6,440,121 B1	8/2002	Weber	6,992,305 B2	1/2006	Maetzawa et al.
6,443,914 B1	9/2002	Costantino	6,997,923 B2	2/2006	Anderson
6,453,202 B1	9/2002	Knowlton	7,006,874 B2	2/2006	Knowlton
			7,020,528 B2	3/2006	Neev
			7,022,089 B2	4/2006	Ooba
			7,058,440 B2	6/2006	Heuscher et al.
			7,063,666 B2	6/2006	Weng

(56)

References Cited

U.S. PATENT DOCUMENTS

7,070,565 B2	7/2006	Vaezy et al.	8,690,778 B2	4/2014	Slayton et al.
7,074,218 B2	7/2006	Washington et al.	8,690,779 B2	4/2014	Slayton et al.
7,094,252 B2	8/2006	Koop	8,690,780 B2	4/2014	Slayton et al.
7,108,663 B2	9/2006	Talish et al.	8,708,935 B2	4/2014	Barthe et al.
7,115,123 B2	10/2006	Knowlton	8,715,186 B2	5/2014	Slayton et al.
7,122,029 B2	10/2006	Koop et al.	8,726,781 B2	5/2014	Eckhoff et al.
7,142,905 B2	11/2006	Slayton	8,831,710 B2 *	9/2014	Kobayashi 600/478
7,165,451 B1	1/2007	Brooks et al.	2001/0009997 A1	7/2001	Pope
7,179,238 B2	2/2007	Hissong	2001/0009999 A1	7/2001	Kaufman et al.
7,189,230 B2	3/2007	Knowlton	2001/0014780 A1	8/2001	Martin et al.
7,229,411 B2	6/2007	Slayton	2001/0014819 A1	8/2001	Ingle et al.
7,235,592 B2	6/2007	Muratoglu	2001/0031922 A1	10/2001	Weng et al.
7,258,674 B2	8/2007	Cribbs	2001/0039380 A1	11/2001	Larson et al.
7,273,459 B2	9/2007	Desilets	2001/0041880 A1	11/2001	Briskin
7,294,125 B2	11/2007	Phalen et al.	2002/0000763 A1	1/2002	Jones
7,297,117 B2	11/2007	Trucco et al.	2002/0002345 A1	1/2002	Marlinghaus
7,303,555 B2	12/2007	Makin et al.	2002/0040199 A1	4/2002	Klopotek
7,327,071 B2	2/2008	Nishiyama et al.	2002/0040442 A1	4/2002	Ishidera
7,331,951 B2	2/2008	Eshel et al.	2002/0052550 A1	5/2002	Madsen et al.
7,332,985 B2	2/2008	Larson, III et al.	2002/0055702 A1	5/2002	Atala
7,338,446 B2 *	3/2008	MacDonald et al. 600/437	2002/0062077 A1	5/2002	Emmenegger et al.
7,347,855 B2	3/2008	Eshel	2002/0062142 A1	5/2002	Knowlton
RE40,403 E	6/2008	Cho et al.	2002/0072691 A1	6/2002	Thompson et al.
7,393,325 B2	7/2008	Barthe	2002/0082501 A1	6/2002	Emery
7,398,116 B2	7/2008	Edwards	2002/0082528 A1	6/2002	Friedman et al.
7,399,279 B2	7/2008	Abend et al.	2002/0082529 A1	6/2002	Suorsa et al.
7,491,171 B2	2/2009	Barthe et al.	2002/0082589 A1	6/2002	Friedman et al.
7,510,536 B2	3/2009	Foley et al.	2002/0087080 A1	7/2002	Slayton et al.
7,530,356 B2	5/2009	Slayton	2002/0095143 A1	7/2002	Key
7,530,958 B2	5/2009	Slayton	2002/0099094 A1	7/2002	Anderson
7,571,336 B2	8/2009	Barthe	2002/0115917 A1	8/2002	Honda et al.
7,601,120 B2	10/2009	Moilanen et al.	2002/0128648 A1	9/2002	Weber
7,615,015 B2	11/2009	Coleman	2002/0143252 A1	10/2002	Dunne et al.
7,615,016 B2	11/2009	Barthe	2002/0156400 A1	10/2002	Babaev
7,686,763 B2	3/2010	Vaezy et al.	2002/0161357 A1	10/2002	Anderson
7,695,437 B2	4/2010	Quistgaard et al.	2002/0165529 A1	11/2002	Danek
7,758,524 B2	7/2010	Barthe	2002/0168049 A1	11/2002	Schriever
7,789,841 B2	9/2010	Huckle et al.	2002/0169394 A1	11/2002	Eppstein et al.
7,824,348 B2	11/2010	Barthe et al.	2002/0169442 A1	11/2002	Neev
7,846,096 B2	12/2010	Mast et al.	2002/0173721 A1	11/2002	Grunwald et al.
7,857,773 B2	12/2010	Desilets et al.	2002/0193784 A1	12/2002	Mchale et al.
7,875,023 B2	1/2011	Eshel et al.	2002/0193831 A1	12/2002	Smith
7,914,453 B2	3/2011	Slayton et al.	2003/0009153 A1	1/2003	Briskin et al.
7,914,469 B2	3/2011	Torbati	2003/0014039 A1	1/2003	Barzell et al.
7,931,611 B2	4/2011	Novak et al.	2003/0018255 A1	1/2003	Martin
7,955,281 B2	6/2011	Pedersen et al.	2003/0028111 A1	2/2003	Vaezy et al.
7,967,764 B2	6/2011	Lidgren et al.	2003/0028113 A1	2/2003	Gilbert et al.
7,967,839 B2	6/2011	Flock et al.	2003/0032900 A1	2/2003	Ella
8,057,389 B2	11/2011	Barthe et al.	2003/0036706 A1	2/2003	Slayton et al.
8,057,465 B2	11/2011	Sliwa, Jr. et al.	2003/0040739 A1	2/2003	Koop
8,066,641 B2	11/2011	Barthe et al.	2003/0050678 A1	3/2003	Sierra
8,123,707 B2	2/2012	Huckle et al.	2003/0055417 A1	3/2003	Truckai et al.
8,128,618 B2	3/2012	Gliklich et al.	2003/0060736 A1	3/2003	Martin et al.
8,133,180 B2	3/2012	Slayton et al.	2003/0065313 A1	4/2003	Koop
8,133,191 B2	3/2012	Rosenberg et al.	2003/0074023 A1	4/2003	Kaplan
8,166,332 B2	4/2012	Barthe et al.	2003/0083536 A1	5/2003	Eshel
8,197,409 B2	6/2012	Foley et al.	2003/0092988 A1	5/2003	Makin
8,206,299 B2	6/2012	Foley et al.	2003/0097071 A1	5/2003	Halmann et al.
8,211,017 B2	7/2012	Foley et al.	2003/0099383 A1	5/2003	Lefebvre
8,262,591 B2	9/2012	Pedersen et al.	2003/0125629 A1	7/2003	Ustuner
8,273,037 B2	9/2012	Kreindel et al.	2003/0139790 A1	7/2003	Ingle et al.
8,282,554 B2	10/2012	Makin et al.	2003/0171678 A1	9/2003	Batten et al.
8,333,700 B1	12/2012	Barthe et al.	2003/0171701 A1	9/2003	Babaev
8,366,622 B2	2/2013	Slayton et al.	2003/0176790 A1	9/2003	Slayton
8,409,097 B2	4/2013	Slayton et al.	2003/0191396 A1	10/2003	Sanghvi
8,444,562 B2	5/2013	Barthe et al.	2003/0200481 A1	10/2003	Stanley
8,480,585 B2	7/2013	Slayton et al.	2003/0212129 A1	11/2003	Liu et al.
8,506,486 B2	8/2013	Slayton et al.	2003/0212351 A1	11/2003	Hissong
8,523,775 B2	9/2013	Barthe et al.	2003/0212393 A1	11/2003	Knowlton
8,535,228 B2	9/2013	Slayton et al.	2003/0216795 A1	11/2003	Harth
8,585,618 B2	11/2013	Hunziker et al.	2003/0220536 A1	11/2003	Hissong
8,636,665 B2	1/2014	Slayton et al.	2003/0220585 A1	11/2003	Hissong
8,641,622 B2	2/2014	Barthe et al.	2003/0229331 A1	12/2003	Briskin et al.
8,663,112 B2	3/2014	Slayton et al.	2003/0233085 A1	12/2003	Giammarusti
8,672,848 B2	3/2014	Slayton et al.	2003/0236487 A1	12/2003	Knowlton
			2004/0000316 A1	1/2004	Knowlton
			2004/0001809 A1	1/2004	Briskin
			2004/0002705 A1	1/2004	Knowlton
			2004/0010222 A1	1/2004	Nunomura et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2004/0015106 A1	1/2004	Coleman	2006/0074314 A1	4/2006	Slayton
2004/0030227 A1	2/2004	Littrup	2006/0074355 A1	4/2006	Slayton
2004/0039312 A1	2/2004	Hillstead	2006/0079816 A1	4/2006	Barthe
2004/0039418 A1	2/2004	Elstrom et al.	2006/0079868 A1	4/2006	Makin
2004/0041563 A1	3/2004	Lewin et al.	2006/0084891 A1	4/2006	Barthe
2004/0042168 A1	3/2004	Yang et al.	2006/0089632 A1	4/2006	Barthe
2004/0044375 A1	3/2004	Diederich et al.	2006/0089688 A1	4/2006	Panescu
2004/0049134 A1	3/2004	Tosaya et al.	2006/0094988 A1	5/2006	Tosaya et al.
2004/0049734 A1	3/2004	Simske	2006/0111744 A1	5/2006	Makin
2004/0059266 A1	3/2004	Fry	2006/0116583 A1	6/2006	Ogasawara et al.
2004/0068186 A1	4/2004	Ishida et al.	2006/0116671 A1	6/2006	Slayton
2004/0073079 A1	4/2004	Altshuler et al.	2006/0122508 A1	6/2006	Slayton
2004/0073113 A1	4/2004	Salgo	2006/0122509 A1	6/2006	Desilets
2004/0073115 A1	4/2004	Horzewski et al.	2006/0161062 A1	7/2006	Arditi et al.
2004/0073116 A1	4/2004	Smith	2006/0184069 A1	8/2006	Vaitekunas
2004/0073204 A1	4/2004	Ryan et al.	2006/0184071 A1	8/2006	Klopotek
2004/0077977 A1	4/2004	Ella et al.	2006/0189972 A1	8/2006	Grossman
2004/0082857 A1	4/2004	Schonenberger et al.	2006/0206105 A1	9/2006	Chopra
2004/0082859 A1	4/2004	Schaer	2006/0229514 A1	10/2006	Wiener
2004/0102697 A1	5/2004	Evron	2006/0241440 A1	10/2006	Eshel
2004/0105559 A1	6/2004	Aylward et al.	2006/0241442 A1	10/2006	Barthe
2004/0122323 A1	6/2004	Vortman et al.	2006/0241470 A1	10/2006	Novak et al.
2004/0122493 A1	6/2004	Ishibashi et al.	2006/0250046 A1	11/2006	Koizumi et al.
2004/0143297 A1	7/2004	Ramsey	2006/0261584 A1	11/2006	Blackburn
2004/0152982 A1	8/2004	Hwang et al.	2006/0282691 A1	12/2006	Barthe
2004/0158150 A1	8/2004	Rabiner et al.	2006/0291710 A1	12/2006	Wang et al.
2004/0186535 A1	9/2004	Knowlton	2007/0032784 A1	2/2007	Gliklich et al.
2004/0189155 A1	9/2004	Funakubo	2007/0035201 A1	2/2007	Desilets
2004/0206365 A1	10/2004	Knowlton	2007/0055154 A1	3/2007	Torbati
2004/0210214 A1	10/2004	Knowlton	2007/0055155 A1	3/2007	Owen et al.
2004/0217675 A1	11/2004	Desilets	2007/0055156 A1	3/2007	Desilets et al.
2004/0249318 A1	12/2004	Tanaka	2007/0060819 A1 *	3/2007	Altshuler et al. 600/475
2004/0254620 A1	12/2004	Lacoste et al.	2007/0065420 A1	3/2007	Johnson
2004/0267252 A1	12/2004	Washington et al.	2007/0083120 A1	4/2007	Cain et al.
2005/0033201 A1	2/2005	Takahashi	2007/0087060 A1	4/2007	Dietrich
2005/0033316 A1	2/2005	Kertz	2007/0088245 A1	4/2007	Babaev et al.
2005/0038340 A1	2/2005	Vaezy et al.	2007/0088346 A1	4/2007	Mirizzi et al.
2005/0055073 A1	3/2005	Weber	2007/0161902 A1	7/2007	Dan
2005/0061834 A1	3/2005	Garcia et al.	2007/0166357 A1	7/2007	Shaffer et al.
2005/0070961 A1	3/2005	Maki et al.	2007/0167709 A1	7/2007	Slayton
2005/0074407 A1	4/2005	Smith	2007/0208253 A1	9/2007	Slayton
2005/0080469 A1	4/2005	Larson	2007/0219604 A1	9/2007	Yaroslavsky et al.
2005/0091770 A1	5/2005	Mourad et al.	2007/0219605 A1	9/2007	Yaroslavsky et al.
2005/0096542 A1	5/2005	Weng et al.	2007/0238994 A1	10/2007	Stecco et al.
2005/0104690 A1	5/2005	Larson, III et al.	2007/0239075 A1	10/2007	Rosenberg et al.
2005/0113689 A1	5/2005	Gritzky	2007/0239079 A1	10/2007	Manstein et al.
2005/0134314 A1	6/2005	Prather et al.	2007/0239142 A1	10/2007	Altshuler et al.
2005/0137656 A1	6/2005	Malak	2008/0027328 A1	1/2008	Klopotek et al.
2005/0143677 A1	6/2005	Young et al.	2008/0039724 A1	2/2008	Seip et al.
2005/0154313 A1	7/2005	Desilets	2008/0071255 A1	3/2008	Barthe
2005/0154314 A1	7/2005	Quistgaard	2008/0086054 A1	4/2008	Slayton
2005/0154332 A1	7/2005	Zanelli	2008/0097253 A1	4/2008	Pedersen
2005/0154431 A1	7/2005	Quistgaard	2008/0139974 A1	6/2008	Da Silva
2005/0187495 A1	8/2005	Quistgaard	2008/0146970 A1	6/2008	Litman et al.
2005/0191252 A1	9/2005	Mitsui	2008/0167556 A1 *	7/2008	Thompson et al. 600/439
2005/0193451 A1	9/2005	Quistgaard et al.	2008/0183077 A1	7/2008	Moreau-Gobard et al.
2005/0197681 A1	9/2005	Barolet et al.	2008/0188745 A1	8/2008	Chen et al.
2005/0228281 A1	10/2005	Nefos	2008/0195000 A1	8/2008	Spooner et al.
2005/0240170 A1	10/2005	Zhang et al.	2008/0200810 A1	8/2008	Buchalter
2005/0251120 A1	11/2005	Anderson et al.	2008/0200813 A1	8/2008	Quistgaard
2005/0256406 A1	11/2005	Barthe	2008/0214966 A1	9/2008	Slayton
2005/0261584 A1	11/2005	Eshel	2008/0221491 A1	9/2008	Slayton
2005/0261585 A1	11/2005	Makin et al.	2008/0223379 A1	9/2008	Stuker et al.
2005/0267454 A1	12/2005	Hissong	2008/0243035 A1	10/2008	Crunkilton
2005/0288748 A1	12/2005	Li et al.	2008/0269608 A1	10/2008	Anderson et al.
2006/0004306 A1	1/2006	Altshuler	2008/0275342 A1	11/2008	Barthe
2006/0020260 A1	1/2006	Dover et al.	2008/0281206 A1	11/2008	Bartlett et al.
2006/0025756 A1	2/2006	Francischelli	2008/0281236 A1	11/2008	Eshel et al.
2006/0042201 A1	3/2006	Curry	2008/0281237 A1 *	11/2008	Slayton et al. 601/2
2006/0058664 A1	3/2006	Barthe	2008/0281255 A1	11/2008	Slayton
2006/0058671 A1	3/2006	Vitek et al.	2008/0294073 A1	11/2008	Barthe
2006/0058707 A1	3/2006	Barthe	2008/0319356 A1	12/2008	Cain et al.
2006/0058712 A1	3/2006	Altshuler et al.	2009/0005680 A1	1/2009	Jones et al.
2006/0074309 A1	4/2006	Bonnefous	2009/0012394 A1	1/2009	Hobelsberger et al.
2006/0074313 A1	4/2006	Slayton et al.	2009/0043198 A1	2/2009	Milner et al.
			2009/0043293 A1	2/2009	Pankratov et al.
			2009/0069677 A1	3/2009	Chen et al.
			2009/0093737 A1	4/2009	Chomas et al.
			2009/0156969 A1	6/2009	Santangelo

(56)

References Cited

U.S. PATENT DOCUMENTS

2009/0171252 A1 7/2009 Bockenstedt et al.
 2009/0177122 A1 7/2009 Peterson
 2009/0177123 A1 7/2009 Peterson
 2009/0182231 A1 7/2009 Barthe et al.
 2009/0216159 A1 8/2009 Slayton et al.
 2009/0226424 A1 9/2009 Hsu
 2009/0227910 A1 9/2009 Pedersen et al.
 2009/0253988 A1 10/2009 Slayton et al.
 2009/0299175 A1 12/2009 Bernstein et al.
 2009/0318909 A1 12/2009 Debenedictis et al.
 2010/0011236 A1 1/2010 Barthe et al.
 2010/0022919 A1 1/2010 Peterson
 2010/0022922 A1 1/2010 Barthe et al.
 2010/0042020 A1 2/2010 Ben-Ezra
 2010/0049178 A1 2/2010 Deem et al.
 2010/0063422 A1 3/2010 Hynynen et al.
 2010/0066207 A1 3/2010 Saito
 2010/0130891 A1 5/2010 Taggart et al.
 2010/0160782 A1 6/2010 Slayton et al.
 2010/0160837 A1 6/2010 Hunziker et al.
 2010/0168576 A1 7/2010 Poland et al.
 2010/0191120 A1 7/2010 Kraus et al.
 2010/0241034 A1 9/2010 Little
 2010/0241035 A1 9/2010 Barthe et al.
 2010/0280420 A1 11/2010 Barthe et al.
 2010/0286518 A1 11/2010 Lee et al.
 2011/0040171 A1 2/2011 Foley et al.
 2011/0040190 A1 2/2011 Jahnke et al.
 2011/0087099 A1 4/2011 Eshel et al.
 2011/0087255 A1 4/2011 McCormack et al.
 2011/0112405 A1 5/2011 Barthe et al.
 2011/0178444 A1 7/2011 Slayton et al.
 2011/0190745 A1 8/2011 Uebelhoer et al.
 2011/0264012 A1 10/2011 Lautzenhiser et al.
 2012/0004549 A1 1/2012 Barthe et al.
 2012/0016239 A1 1/2012 Barthe et al.
 2012/0029353 A1 * 2/2012 Slayton et al. 600/439
 2012/0035475 A1 2/2012 Barthe et al.
 2012/0035476 A1 2/2012 Barthe et al.
 2012/0046547 A1 2/2012 Barthe et al.
 2012/0053458 A1 3/2012 Barthe et al.
 2012/0111339 A1 5/2012 Barthe et al.
 2012/0143056 A1 6/2012 Slayton et al.
 2012/0165668 A1 6/2012 Slayton et al.
 2012/0165848 A1 6/2012 Slayton et al.
 2012/0197120 A1 8/2012 Makin et al.
 2012/0197121 A1 8/2012 Slayton et al.
 2012/0215105 A1 8/2012 Slayton et al.
 2012/0271294 A1 10/2012 Barthe et al.
 2012/0296240 A1 11/2012 Azhari et al.
 2012/0316426 A1 12/2012 Foley et al.
 2012/0323095 A1 * 12/2012 Baker, Jr. 600/324
 2012/0330194 A1 * 12/2012 Britva et al. 601/2
 2012/0330197 A1 12/2012 Makin et al.
 2012/0330222 A1 12/2012 Barthe et al.
 2012/0330223 A1 12/2012 Makin et al.
 2013/0012755 A1 1/2013 Slayton
 2013/0012816 A1 1/2013 Slayton et al.
 2013/0012838 A1 1/2013 Jaeger et al.
 2013/0012842 A1 1/2013 Barthe
 2013/0018286 A1 1/2013 Slayton et al.
 2013/0046209 A1 2/2013 Slayton et al.
 2013/0066208 A1 3/2013 Barthe et al.
 2013/0066237 A1 3/2013 Smotrich et al.
 2013/0072826 A1 3/2013 Slayton et al.
 2013/0096471 A1 4/2013 Slayton et al.
 2013/0172757 A1 * 7/2013 Frigstad et al. 600/459
 2013/0190659 A1 7/2013 Slayton et al.
 2013/0211258 A1 8/2013 Barthe et al.
 2013/0281853 A1 10/2013 Slayton et al.
 2013/0281891 A1 10/2013 Slayton et al.
 2013/0296697 A1 11/2013 Slayton et al.
 2013/0296700 A1 11/2013 Slayton et al.
 2013/0303904 A1 11/2013 Barthe et al.
 2013/0303905 A1 11/2013 Barthe et al.

2013/0310863 A1 11/2013 Barthe et al.
 2014/0058264 A1 * 2/2014 Baym et al. 600/447
 2014/0082907 A1 3/2014 Barthe
 2014/0142430 A1 5/2014 Slayton et al.
 2014/0148834 A1 5/2014 Barthe et al.
 2014/0180174 A1 6/2014 Slayton et al.
 2014/0187944 A1 7/2014 Slayton et al.
 2014/0188015 A1 7/2014 Slayton et al.
 2014/0188145 A1 7/2014 Slayton et al.

FOREIGN PATENT DOCUMENTS

DE 10219217 11/2003
 DE 10219297 11/2003
 DE 20314479 3/2004
 EP 03196623 A1 6/1989
 EP 0344773 12/1989
 EP 1479412 11/1991
 EP 0473553 4/1992
 EP 0661029 7/1995
 EP 1050322 11/2000
 EP 1234566 8/2002
 EP 1262160 12/2002
 EP 1374944 A 1/2004
 GB 2113099 8/1983
 JP 63036171 2/1988
 JP 03048299 3/1991
 JP 3123559 5/1991
 JP 03136642 6/1991
 JP 4089058 3/1992
 JP 04150847 5/1992
 JP 7080087 3/1995
 JP 07505793 6/1995
 JP 7222782 8/1995
 JP 09047458 2/1997
 JP 11505440 5/1999
 JP 11506636 6/1999
 JP 2000166940 6/2000
 JP 2001170068 6/2001
 JP 2002078764 3/2002
 JP 2002515786 5/2002
 JP 2002521118 7/2002
 JP 2002537939 11/2002
 JP 2003050298 2/2003
 JP 2003204982 7/2003
 JP 2004147719 5/2004
 JP 2005503388 2/2005
 JP 2005527336 9/2005
 JP 2005323213 11/2005
 JP 2006520247 9/2006
 JP 2007505793 A 3/2007
 JP 2009518126 5/2009
 JP 2010517695 5/2010
 KR 1020010024871 3/2001
 KR 100400870 B1 10/2003
 KR 1020060113930 11/2006
 KR 1020070065332 6/2007
 KR 1020070070161 7/2007
 KR 1020070098856 10/2007
 KR 1020070104878 10/2007
 KR 1020070114105 11/2007
 WO 9625888 8/1996
 WO 9639079 A1 12/1996
 WO 9735518 10/1997
 WO 9832379 7/1998
 WO 9933520 7/1999
 WO 9949788 10/1999
 WO 0006032 2/2000
 WO 0015300 3/2000
 WO 0021612 4/2000
 WO 0053113 9/2000
 WO 0128623 4/2001
 WO 0182777 11/2001
 WO 0182778 11/2001
 WO 0187161 11/2001
 WO 0209813 2/2002
 WO 02024050 3/2002
 WO 02092168 A 11/2002
 WO 020292168 11/2002

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	03053266	A	7/2003
WO	03065347		8/2003
WO	03070105		8/2003
WO	03077833		8/2003
WO	03086215		10/2003
WO	03096883		11/2003
WO	03099177		12/2003
WO	03101530		12/2003
WO	2004000116	A	12/2003
WO	2004080147		9/2004
WO	2004110558		12/2004
WO	2005004972	A1	1/2005
WO	2005011804	A	2/2005
WO	2005065408		7/2005
WO	2005090978		9/2005
WO	2006036870		4/2006
WO	2006042163	A	4/2006
WO	2006042168		4/2006
WO	2006042201		4/2006
WO	2006065671		6/2006
WO	2006082573		8/2006
WO	2007067563	A	6/2007
WO	2008024923	A2	2/2008
WO	2008036622	A	3/2008
WO	2009013729		1/2009
WO	2009149390	A1	12/2009
WO	2014055708	A1	4/2014

OTHER PUBLICATIONS

Barthe et al., "Ultrasound therapy system and ablation results utilizing miniature imaging/therapy arrays," *Ultrasonics Symposium*, 2004 IEEE, Aug. 23, 2004, pp. 1792-1795, vol. 3.

Coon, Joshua et al., "Protein identification using sequential ion/ion reactions and tandem mass spectrometry" *Proceedings of the National Academy of Sciences of the USA*, vol. 102, No. 27, Jul. 5, 2005, pp. 9463-9468.

Corry, Peter M., et al., "Human Cancer Treatment with Ultrasound", *IEEE Transactions on Sonics and Ultrasonics*, vol. SU-31, No. 5, Sep. 1984, pp. 444-456.

Daum et al., "Design and Evaluation of a Feedback Based Phased Array System for Ultrasound Surgery," *IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control*, vol. 45, No. 2, Mar. 1998, pp. 431-438.

Davis, Brian J., et al., "An Acoustic Phase Shift Technique for the Non-Invasive Measurement of Temperature Changes in Tissues", *1985 Ultrasonics Symposium*, pp. 921-924.

Gliklich et al., *Clinical Pilot Study of Intense Ultrasound therapy to Deep Dermal Facial Skin and Subcutaneous Tissues*, *Arch Facial Plastic Surgery*, Mar. 1, 2007, vol. 9.

Hassan et al., "Structure and Applications of Poly(vinyl alcohol) Hydrogels Produced by Conventional Crosslinking or by Freezing/Thawing Methods," *advanced in Polymer Science*, 2000, pp. 37-65, vol. 153.

Hassan et al., "Structure and Morphology of Freeze/Thawed PVA Hydrogels," *Macromolecules*, Mar. 11, 2000, pp. 2472-2479, vol. 33, No. 7.

Husseini et al., "The Role of Cavitation in Acoustically Activated Drug Delivery," *J. Control Release*, Oct. 3, 2005, pp. 253-261, vol. 107(2).

Husseini et al., "Investigating the mechanism of acoustically activated uptake of drugs from Pluronic micelles," *BMD Cancer* 2002, 2:20k, Aug. 30, 2002, pp. 1-6.

Jenne, J., et al., "Temperature Mapping for High Energy US—Therapy", *1994 Ultrasonics Symposium*, pp. 1879-1882.

Johnson, S.A., et al., "Non-Intrusive Measurement of Microwave and Ultrasound-Induced Hyperthermia by Acoustic temperature Tomography", *Ultrasonics Symposium Proceedings*, pp. 977-982.

Makin et al., "B-Scan Imaging and Thermal Lesion Monitoring Using Miniaturized Dual-Functionality Ultrasound Arrays," *Ultrasonics Symposium*, 2004 IEEE, Aug. 23, 2004, pp. 1788-1791, vol. 3.

Makin et al., "Miniaturized Ultrasound Arrays for Interstitial Ablation and Imaging," *UltraSound Med. Biol.* 2005, Nov. 1, 2005, pp. 1539-1550, vol. 31(11).

Makin et al., "Confirmal Bulk Ablation and Therapy Monitoring Using Intracorporeal Image-Treat Ultrasound Arrays", *4th International Symposium on Therapeutic Ultrasound*, Sep. 19, 2004.

Manohar et al., "Photoacoustic mammography laboratory prototype: imaging of breast tissue phantoms," *Journal of Biomedical Optics*, Nov./Dec. 2004, pp. 1172-1181, vol. 9, No. 6.

Mast et al., "Bulk Ablation of Soft Tissue with Intense Ultrasound; Modeling nad Experiments," *J. Acoust. Soc. Am.*, Oct. 1, 2005, pp. 2715-2724, vol. 118(4).

Paradossi et al., "Poly(vinyl alcohol) as versatile biomaterial for potential biomedical applications," *Journal of Materials Science: Materials in Medicine*, 2003, pp. 687-691, vol. 14.

Reid, Gavin, et al., "Tandem Mass spectrometry of ribonuclease A and B: N-linked glycosylation site analysis of whole protein ions," *Analytical Chemistry*, Feb. 1, 2002, vol. 74, No. 3, pp. 577-583.

Righetti et al., "Elastographic Characterization of HIFU-Induced Lesions in Canine Livers," *1999, Ultrasound in Med & Bio*, vol. 25, No. 7, pp. 1099-1113.

Mitragotri, Samir, "Healing sound: the use of ultrasound in drug delivery and other therapeutic applications," *Nature Reviews; Drug Delivery*, pp. 255-260, vol. 4.

Sanghvi, N.T., et al., "Transrectal Ablation of Prostrate Tissue Using Focused Ultrasound," *1993 Ultrasonics Symposium*, IEEE, pp. 1207-1210.

Seip, Ralf, et al., "Noninvasive Detection of Thermal Effects Due to Highly Focused Ultrasonic Fields," *IEEE Symposium*, pp. 1229-1232, vol. 2, Oct. 3-Nov. 1993.

Seip, Ralf, et al., "Noninvasive Estimation of Tissue Temperature Response to Heating Fields Using Diagnostic Ultrasound," *IEEE Transactions on Biomedical Engineering*, vol. 42, No. 8, Aug. 1995, pp. 828-839.

Smith, Nadine Barrie, et al., "Non-Invasive in Vivo Temperature Mapping of Ultrasound Heating Using Magnetic Resonance Techniques", *1994 Ultrasonics Symposium*, pp. 1829-1832, vol. 3.

Surry et al., "Poly(vinyl alcohol) cryogel phantoms for use in ultrasound and MR imaging," *Phys. Med. Biol.*, Dec. 6, 2004, pp. 5529-5546, vol. 49.

Syka J. E. P. et al., "Peptide and Protein Sequence Analysis by Electron Transfer Dissociation Mass Spectrometry," *Proceedings of the National Academy of Sciences of USA*, *National Academy of Aceince*, Washington, DC, vol. 101, No. 26, Jun. 29, 2004, pp. 9528-9533.

Ueno, S., et al., "Ultrasound Thermometry in Hyperthermia", *1990 Ultrasonic Symposium*, pp. 1645-1652.

Wang, H., et al., "Limits on Focused Ultrasound for Deep Hyperthermia", *1994 Ultrasonic Symposium*, Nov. 1-4, 1994, pp. 1869-1872, vol. 3.

White et al "Selective Creation of Thermal Injury Zones in the Superficial Musculoaponeurotic System Using Intense Ultrasound Therapy," *Arch Facial Plastic Surgery*, Jan./Feb. 2007, vol. 9, No. 1.

Sassen, Sander, "ATI's R520 architecture, the new king of the hill?" <http://www.hardwareanalysis.com/content/article/1813>, Sep. 16, 2005, 2 pages.

Wasson, Scott, "NVIDIA's GeForce 7800 GTX graphics processor Power MADD," <http://techreport.com/reviews/2005q2/geforce-7800gtx/index.x?pg=1>, Jun. 22, 2005, 4 pages.

European Examination Report in related Application No. 05808908.7 dated Jun. 29, 2009.

European Examination Report in related Application No. 05810308.6 dated Jun. 29, 2009.

European Examination Report in related Application No. 10185100.4 dated Jan. 6, 2014.

European Examination Report in related Application No. 10185120.2 dated Jan. 22, 2014.

Decision of the Korean Intellectual Property Tribunal dated Jun. 28, 2013 regarding Korean Patent No. 10-1142108, which is related to the pending application and/or an application identified in the Table on pp. 2-5 of the information Disclosure Statement herein (English translation, English translation certifications, and Korean decision included).

(56)

References Cited

OTHER PUBLICATIONS

International Search Report and Written Opinion dated Jan. 23, 2014 in Application No. PCT/US2012/046122.
 International Search Report and Written Opinion dated Jan. 23, 2014 in Application No. PCT/US2012/046123.
 International Search Report and Written Opinion dated Jan. 28, 2012 in Application No. PCT/US2012/046327.
 International Search Report and Written Opinion dated Jan. 28, 2013 in Application No. PCT/US2012/046125.
 International Search Report and Written Opinion dated Feb. 14, 2013 in Application No. PCT/US2011/001361.
 International Search Report and Written Opinion dated Feb. 14, 2013 in Application No. PCT/US2011/001362.
 International Search Report and Written Opinion dated Feb. 14, 2013 in Application No. PCT/US2011/001366.
 International Search Report and Written Opinion dated Apr. 6, 2012 in Application No. PCT/US2011/001367.
 Calderhead et al, One Mechanism Behind LED Photo-Therapy for Wound Healing and Skin Rejuvenation: Key Role of the Mast Cell, Laser Therapy, Jul. 2008, pp. 141-148, 17.3.
 European Examination Report in related Application No. 09835856.7 dated Apr. 11, 2004.
 International Search Report and Written Opinion dated Apr. 6, 2012 in Application No. PCT/US2011/001366.
 International Search Report and Written Opinion dated Apr. 12, 2012 in Application No. PCT/US2011/001361.
 Arthur et al., "Non-invasive estimation of hyperthermia temperatures with ultrasound," *Int. J. Hyperthermia*, Sep. 2005, 21(6), pp. 589-600.
 Chen, L. et al., "Effect of Blood Perfusion on the ablation of liver perenchyma with high intensity focused ultrasound," *Phys. Med. Biol.* 38:1661-1673; 1993b.
 Damianou et al., Application of the Thermal Dose Concept for Predicting the Necrosed Tissue Volume During Ultrasound Surgery, 1993 IEEE Ultrasound Symposium, pp. 1199-1202.
 Fry, W.J. et al., "Production of Focal Destructive Lesions in the Central Nervous System with Ultrasound," *J. Neurosurg.*, 11:471-478; 1954.

Harr, G.R. et al., "Tissue Destruction with Focused Ultrasound in Vivo," *Eur. Urol.* 23 (suppl. 1):8-11; 1993.
 Jeffers et al., "Evaluation of the Effect of Cavitation Activity on Drug-Ultrasound Synergisms," 1993 IEEE Ultrasonics Symposium, pp. 925-928.
 Madersbacher, S. et al., "Tissue Ablation in Bening Prostatic Hyperplasia with High Intensity Focused Ultrasound," *Dur. Urol.*, 23 (suppl. 1):39-43; 1993.
 Saad et al., "Ultrasound-Enhanced Effects of Adriamycin Against Murine Tumors," *Ultrasound in Med. & Biol.* vol. 18, No. 8, pp. 715-723 (1992).
 Simon et al., "Applications of Lipid-Coated Microbubble Ultrasonic Contrast to Tumor Therapy," *Ultrasound in Med. & Biol.* vol. 19, No. 2, pp. 123-125 (1993).
 Talbert, D. G., "An Add-On Modification for Linear Array Real-Time Ultrasound Scanners to Produce 3D Displays," *UTS Int'l 1977 Brighton, England (Jun. 28-30, 1977)* pp. 57-67.
 Tata et al., "Interaction of Ultrasound and Model Membrane Systems: Analyses and Predictions," American Chemical Society, *Phys. Chem.* 1992, 96, pp. 3548-3555.
 PCT International Search Report and Written Opinion, PCT/US2014/030779, Sep. 1, 2014, 8 pages.
 European Patent Office, Examination Report, EP 07814933.3, Aug. 5, 2014, 5 pages.
 European Patent Office, Examination Report, EP 05798870.1, Oct. 20, 2014, 5 pages.
 European Patent Office, Examination Report, EP 10185100.4, Oct. 24, 2014, 4 pages.
 European Patent Office, Examination Report, EP 10185112.9, Oct. 24, 2014, 5 pages.
 European Patent Office, Examination Report, EP 10185117.8, Oct. 24, 2014, 5 pages.
 European Patent Office, Examination Report, EP 10185120.2, Oct. 24, 2014, 4 pages.
 Kelly, et al., An Air-Coupled Ultrasonic Matching Layer Employing Half Wavelength Cavity Resonance, 2001 IEEE Ultrasonics Symposium, vol. 2, pp. 965-968.
 European Patent Office, Supplementary Partial European Search Report, Application No. 12814300.5, Mar. 20, 2015, 8 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12

SYSTEMS AND METHODS FOR COUPLING AN ULTRASOUND SOURCE TO TISSUE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims priority to and the benefit of U.S. Provisional Patent Application Ser. No. 61/506,609, entitled "Systems and Methods for Monitoring Ultrasound Power Efficiency," filed Jul. 11, 2011; and U.S. Provisional Patent Application Ser. No. 61/506,610, entitled "Methods and Systems for Controlling Acoustic Energy Deposition into a Medium," filed Jul. 11, 2011; all of which are incorporated by reference herein.

This application is a continuation in part of and claims priority to and the benefit of U.S. patent application Ser. No. 13/136,544, entitled "Systems and Methods for Ultrasound Treatment," filed Aug. 2, 2011, which claims priority to and the benefit of U.S. Provisional Patent Application Ser. No. 61/369,782, entitled "Systems and Methods for Ultrasound Treatment", filed Aug. 2, 2010; U.S. Provisional Patent Application Ser. No. 61/369,793, entitled "System and Method for Treating Sports Related Injuries", filed Aug. 2, 2010; U.S. Provisional Patent Application Ser. No. 61/369,806, entitled "System and Method for Treating Sports Related Injuries", filed Aug. 2, 2010; U.S. Provisional Patent Application Ser. No. 61/370,095, entitled "System and Method for Treating Cartilage", filed Aug. 2, 2010; all of which are incorporated by reference herein.

BACKGROUND

Coupling of a treatment system to tissue is important for clinical efficiency of the desired treatment. In addition, using a treatment system that is not coupled to tissue may cause safety concerns. Further, if a treatment system is not properly coupled to the tissue may cause stability and performance issues. Various contact sensors have been used to determine if a treatment system is coupled to targeted tissue. However, these contact sensors typically use mechanical methods to determine if a treatment system is coupled to the tissue. Accordingly, new approaches for determining whether a treatment system is coupled to targeted tissue are needed.

SUMMARY

Various embodiments described herein provide methods and systems for monitoring ultrasound energy. Various embodiments provide a method of sensing coupling of an ultrasound source to a target. In some embodiments, the method comprises providing an ultrasound sound source comprising a transducer, an acoustically transparent standoff, an acoustic window at a bottom surface of the standoff, and a frequency sweep function coupled to the transducer. In some embodiments, the method can comprise emitting ultrasound energy from the transducer; receiving reflected energy; frequency sweeping the transducer; determining the feedback from the frequency sweep is above a threshold level; and determining of the source is coupled to the target.

In some embodiments, if the feedback from the frequency is above the threshold level, then the source is not coupled to the target. In some embodiments, if the feedback from the frequency is below the threshold level, then the source is coupled to the target.

Various embodiments provide a system for determining whether an ultrasound source is coupled to a target. In some

embodiments, the system comprises an ultrasound source comprising a transducer; an acoustically transparent standoff coupled to the transducer; a half wavelength acoustic window at a bottom surface of the standoff, and a frequency sweep function coupled to the transducer.

Various embodiments provide a system for providing a constant average output of power from an ultrasound source. In some embodiments, the system comprises an ultrasound transducer coupled to a power supply; a controller in communication with the power supply; a chirp function in communication with and operable to monitor the ultrasound transducer; a feedback loop from the chirp function to the controller. In some embodiments, the controller is operable to change a parameter on the transducer based on the feedback to provide a constant average output of power from the ultrasound transducer.

DRAWINGS

The present disclosure will become more fully understood from the description and the accompanying drawings, wherein:

FIG. 1 is a cross sectional view illustrating tissue layers and ultrasound energy directed to a portion of the tissue layers, in accordance with various non-limiting embodiments;

FIG. 2 is a graph illustrating ultrasound efficiency at a frequency, in accordance with various non-limiting embodiments;

FIG. 3 is a graph illustrating ultrasound efficiency at a frequency, in accordance with various non-limiting embodiments;

FIG. 4 is a block diagram illustrating a system in accordance with various non-limiting embodiments;

FIG. 5 is a block diagram illustrating a system in accordance with various non-limiting embodiments;

FIG. 6 is a block diagram illustrating a system in accordance with various non-limiting embodiments.

FIG. 7 is a block diagram illustrating a system in accordance with various non-limiting embodiments;

FIG. 8 is a block diagram illustrating a system in accordance with various non-limiting embodiments;

FIG. 9 is a diagram illustrating a transducer system coupled to tissue in accordance to various non-limiting examples;

FIG. 10 is a diagram illustrating a transducer system not coupled to tissue in accordance to various non-limiting examples;

FIG. 11 is a graph illustrating resistance over time for a transducer system coupled to tissue in accordance with various non-limiting embodiments; and

FIG. 12 is a graph illustrating resistance over time for a transducer system not coupled to tissue in accordance with various non-limiting embodiments.

DESCRIPTION

The following description is merely exemplary in nature and is in no way intended to limit the various embodiments, their application, or uses. As used herein, the phrase "at least one of A, B, and C" should be construed to mean a logical (A or B or C), using a non-exclusive logical "or." As used herein, the phrase "A, B and/or C" should be construed to mean (A, B, and C) or alternatively (A or B or C), using a non-exclusive logical "or." It should be understood that steps within a method may be executed in different order without altering the principles of the present disclosure.

The drawings described herein are for illustrative purposes only of selected non-limiting embodiments and not all possible implementations, and are not intended to limit the scope of any of the various embodiments disclosed herein or any equivalents thereof. It is understood that the drawings are not drawn to scale. For purposes of clarity, the same reference numbers will be used in the drawings to identify similar elements.

The various embodiments may be described herein in terms of various functional components and processing steps. It should be appreciated that such components and steps may be realized by any number of hardware components configured to perform the specified functions. For example, various embodiments may employ various medical treatment devices, visual imaging and display devices, input terminals and the like, which may carry out a variety of functions under the control of one or more control systems or other control devices. In addition, the embodiments may be practiced in any number of medical contexts and that the various embodiments relating to a method and system for acoustic energy deposition in tissue, as described herein, are merely indicative of one of the many applications for the invention. For example, the principles, features and methods discussed may be applied to any medical application. Further, various aspects of the various embodiments may be suitably applied to cosmetic applications. Moreover, some of the embodiments may be applied to cosmetic enhancement of skin and/or various soft tissue layers.

Various embodiments provide methods and systems to adjust a temperature of a transducer, in order to maintain maximum efficiency of power applied by the transducer. Some embodiments provide methods and systems to minimize or eliminate temperature saturation of a transducer during the delivery of power to the transducer. In some embodiments, methods and systems can control a temperature of a transducer to maintain a desired frequency of energy transmission at a maximum power.

Various embodiments provide methods and systems to adjust a temperature of a transducer, in order to maintain maximum efficiency of power applied by the transducer. Some embodiments provide methods and systems to minimize or eliminate temperature saturation of a transducer during the delivery of power to the transducer. In some embodiments, methods and systems can control a temperature of a transducer to maintain a desired frequency of energy transmission at a maximum power.

Some embodiments provide a method of providing ultrasound energy having a stable power output. The method can comprise providing ultrasound energy from an ultrasound transducer; determining a power level threshold of the ultrasound energy; monitoring a power level of the ultrasound energy over time of the ultrasound energy; communicating a power level to a controller; adjusting the frequency of the ultrasound energy upon a change in the power level; and maintaining the power level threshold of the ultrasound energy.

In some embodiments, the method can further comprise emitting the ultrasound energy at a specific frequency and correcting the frequency to the specific frequency upon a change in the power level. In some embodiments, the method can comprise changing power provided to a transducer providing the ultrasound energy based on the adjusting the frequency of the ultrasound energy. In some embodiments, the method can comprise terminating the providing the ultrasound energy upon a change of the power level above the power level threshold.

Some embodiments provide a method of providing ultrasound energy having a stable power output. The method can comprise providing ultrasound energy from an ultrasound transducer; determining a power level threshold of the ultrasound energy; monitoring a temperature of the ultrasound transducer over time; communicating the temperature to a controller; adjusting the frequency of the ultrasound energy upon a change in the temperature; and maintaining the power level threshold of the ultrasound energy.

In some embodiments, the method can further comprise determining a temperature threshold of the ultrasound transducer and terminating the providing ultrasound energy when the temperature is above the temperature threshold.

In some embodiments, the method can further comprise emitting the ultrasound energy at a specific frequency and correcting the frequency to the specific frequency upon the change of temperature. In some embodiments, the method can comprise terminating the providing the ultrasound energy upon a change of the power level above the power level threshold. In some embodiments, the method can further comprise determining a temperature threshold of the ultrasound transducer and terminating the providing ultrasound energy when a temperature of the ultrasound transducer is above the temperature threshold.

Some embodiments provide a method of providing ultrasound energy having a stable power output. The method can comprise providing ultrasound energy from an ultrasound transducer; determining a voltage threshold of the ultrasound energy; monitoring a voltage of the ultrasound transducer over time; communicating the voltage to a controller; adjusting the frequency of the ultrasound energy upon a change in the voltage; and maintaining the power level threshold of the ultrasound energy.

In some embodiments, the method can further comprise determining a temperature threshold of the ultrasound transducer and terminating the providing ultrasound energy when the temperature of the ultrasound transducer is above the temperature threshold.

In some embodiments, the method can further comprise emitting the ultrasound energy at a specific frequency and correcting the frequency to the specific frequency upon the change of voltage. In some embodiments, the method can comprise terminating the providing the ultrasound energy upon a change of the power level above the power level threshold.

Some embodiments provide a method of providing ultrasound energy having a stable power output. The method can comprise providing ultrasound energy from an ultrasound transducer; determining a voltage threshold of the ultrasound energy; monitoring a voltage of the ultrasound transducer over time; communicating the voltage to a controller; adjusting the frequency of the ultrasound energy upon a change in the voltage; monitoring a power level of the ultrasound energy over time of the ultrasound energy; communicating a power level to a controller; adjusting the frequency of the ultrasound energy upon a change in the power level; and maintaining the power level threshold of the ultrasound energy.

In some embodiments, the method can further comprise determining a temperature threshold of the ultrasound transducer and terminating the providing ultrasound energy when the temperature of the ultrasound transducer is above the temperature threshold.

In some embodiments, the method can further comprise emitting the ultrasound energy at a specific frequency and correcting the frequency to the specific frequency upon the change of voltage. In some embodiments, the method can

comprise terminating the providing the ultrasound energy upon a change of the power level above the power level threshold.

Some embodiments provide a method of providing ultrasound energy having a stable power output. The method can comprise providing ultrasound energy from a ultrasound transducer; monitoring a power level of the ultrasound energy over time of the ultrasound energy; communicating a power level to a controller; adjusting the frequency of the ultrasound energy upon a change in the power level; monitoring a temperature of the ultrasound transducer over time; communicating the temperature to a controller; adjusting the frequency of the ultrasound energy upon an change in the temperature; and maintaining the power level threshold of the ultrasound energy.

In some embodiments, the method can further comprise determining a temperature threshold of the ultrasound transducer and terminating the providing ultrasound energy when the temperature of the ultrasound transducer is above the temperature threshold.

In some embodiments, the method can further comprise emitting the ultrasound energy at a specific frequency and correcting the frequency to the specific frequency upon the change of voltage. In some embodiments, the method can comprise terminating the providing the ultrasound energy upon a change of the power level above the power level threshold.

Some embodiments provide a method of providing ultrasound energy having a stable power output. The method can comprise providing ultrasound energy from a ultrasound transducer; determining a voltage threshold of the ultrasound energy; monitoring a voltage of the ultrasound transducer over time; communicating the voltage to a controller; adjusting the frequency of the ultrasound energy upon an change in the voltage; monitoring a power level of the ultrasound energy over time of the ultrasound energy; communicating a power level to a controller; adjusting the frequency of the ultrasound energy upon a change in the power level; monitoring a temperature of the ultrasound transducer over time; communicating the temperature to a controller; adjusting the frequency of the ultrasound energy upon an change in the temperature; and maintaining the power level threshold of the ultrasound energy.

In some embodiments, the method can further comprise determining a temperature threshold of the ultrasound transducer and terminating the providing ultrasound energy when the temperature of the ultrasound transducer is above the temperature threshold.

In some embodiments, the method can further comprise emitting the ultrasound energy at a specific frequency and correcting the frequency to the specific frequency upon the change of voltage. In some embodiments, the method can comprise terminating the providing the ultrasound energy upon a change of the power level above the power level threshold.

In some embodiments, temperature can be monitored by monitoring changes in time of flight of the ultrasound energy from the transducer. In some embodiments, temperature can be monitored by a piezoelectric sensor that may be a portion of transducer, as described herein. In various embodiments, a controller may use a look up table to change a parameter. In some embodiments, controller can employ hardware, software, or a combination of both to change a parameter such as power, voltage or current.

With reference to FIG. 1, a cross sectional view of tissue layers and ultrasound energy directed to at least one of the tissue layers, according to various embodiments of the

present invention, is illustrated. The tissue layers illustrated are skin surface **204**, epidermal layer **202**, dermis layer **206**, fat layer **208**, SMAS layer **210**, and muscle and connective tissue layer **212**. Ultrasound probe **205** transmits ultrasound energy **220** transmitting in ROI **215**. In various embodiments, ultrasound probe **205** is capable of transmitting ultrasound energy **220** transmitting at variable depths in ROI **215**, such as, for example, the depths described herein. Ultrasound probe **205** is capable of transmitting therapeutic ultrasound energy as a single frequency, variable frequencies, or a plurality of frequencies, such as, for example, within the frequency ranges described herein. Ultrasound probe **205** is capable of transmitting ultrasound energy **220** transmitting for variable time periods or to pulse the transmission over time, such as, for example, those time intervals described herein. Ultrasound probe **205** is capable of providing various energy levels of therapeutic ultrasound energy, such as, for example, the energy levels described herein.

Ultrasound probe **205** may be individual hand-held device, or may be part of a treatment system or part of cosmetic enhancement system. The ultrasound probe **205** can provide both therapeutic ultrasound energy and imaging ultrasound energy. However, ultrasound probe **205** may provide only therapeutic ultrasound energy. Ultrasound probe **205** may comprise a therapeutic transducer and a separate imaging transducer. Ultrasound probe **205** may comprise a transducer or a transducer array capable of both therapeutic and imaging applications. According an alternative embodiment, ultrasound probe **205** is coupled directly to one of the tissue layers, as opposed to skin surface **204** to treat the tissue layer. For example, ultrasound probe **205** can be integrated to or attached to a tool, such as, for example, an arthroscopic tool, laparoscopic tool, or an endoscopic tool that may be inserted into a patient's body with minimal invasiveness.

In various embodiments, the ultrasound energy level is in a range of about 0.1 joules to about 500 joules in order to create an ablative lesion. However, the ultrasound energy **108** level can be in a range of from about 0.1 joules to about 100 joules, or from about 1 joules to about 50 joules, or from about 0.1 joules to about 10 joules, or from about 50 joules to about 100 joules, or from about 100 joules to about 500 joules, or from about 50 joules to about 250 joules.

Further, the amount of time ultrasound energy is applied at these levels varies in the range from approximately 1 millisecond to several minutes. However, a range can be from about 1 millisecond to about 5 minutes, or from about 1 millisecond to about 1 minute, or from about 1 millisecond to about 30 seconds, or from about 1 millisecond to about 10 seconds, or from about 1 millisecond to about 1 second, or from about 1 millisecond to about 0.1 seconds, or about 0.1 seconds to about 10 seconds, or about 0.1 seconds to about 1 second, or from about 1 millisecond to about 200 milliseconds, or from about 1 millisecond to about 0.5 seconds.

The frequency of the ultrasound energy can be in a range from about 0.1 MHz to about 100 MHz, or from about 0.1 MHz to about 50 MHz, or from about 1 MHz to about 50 MHz or about 0.1 MHz to about 30 MHz, or from about 10 MHz to about 30 MHz, or from about 0.1 MHz to about 20 MHz, or from about 1 MHz to about 20 MHz, or from about 20 MHz to about 30 MHz.

The frequency of the ultrasound energy can be in a range from about 1 MHz to about 12 MHz, or from about 5 MHz to about 15 MHz, or from about 2 MHz to about 12 MHz or from about 3 MHz to about 7 MHz.

In some embodiments, the ultrasound energy can be transmitted to depths at or below a skin surface in a range from about 0 mm to about 150 mm, or from about 0 mm to about 100 mm, or from about 0 mm to about 50 mm, or from about 0 mm to about 30 mm, or from about 0 mm to about 20 mm, or from about 0 mm to about 10 mm, or from about 0 mm to about 5 mm. In some embodiments, the ultrasound energy can be transmitted to depths below a skin surface in a range from about 5 mm to about 150 mm, or from about 5 mm to about 100 mm, or from about 5 mm to about 50 mm, or from about 5 mm to about 30 mm, or from about 5 mm to about 20 mm, or from about 5 mm to about 10 mm. In some embodiments, the ultrasound energy can be transmitted to depths below a skin surface in a range from about 10 mm to about 150 mm, or from about 10 mm to about 100 mm, or from about 10 mm to about 50 mm, or from about 10 mm to about 30 mm, or from about 10 mm to about 20 mm, or from about 10 mm to about 10 mm.

In some embodiments, the ultrasound energy can be transmitted to depths at or below a skin surface in the range from about 20 mm to about 150 mm, or from about 20 mm to about 100 mm, or from about 20 mm to about 50 mm, or from about 20 mm to about 30 mm. In some embodiments, the ultrasound energy can be transmitted to depths at or below a skin surface in a range from about 30 mm to about 150 mm, or from about 30 mm to about 100 mm, or from about 30 mm to about 50 mm. In some embodiments, the ultrasound energy can be transmitted to depths at or below a skin surface in a range from about 50 mm to about 150 mm, or from about 50 mm to about 100 mm. In some embodiments, the ultrasound energy can be transmitted to depths at or below a skin surface in a range from about 20 mm to about 60 mm, or from about 40 mm to about 80 mm, or from about 10 mm to about 40 mm, or from about 5 mm to about 40 mm, or from about 0 mm to about 40 mm, or from about 10 mm to about 30 mm, or from about 5 mm to about 30 mm, or from about 0 mm to about 30 mm.

In various embodiments, a temperature of tissue receiving the ultrasound energy can be in a range from 30° C. to about 100° C., or from 43° C. to about 60° C., or from 50° C. to about 70° C., or from 30° C. to about 50° C., or from 43° C. to about 100° C., or from 33° C. to about 100° C., or from 30° C. to about 65° C., or from 33° C. to about 70° C., as well as variations thereof.

Also, depending at least in part upon a specific biological effect and the tissue layers that are targeted, temperature of tissue receiving the ultrasound energy within ROI 215 may change in a range from approximately 10° C. to about 15° C. In various embodiments, a temperature of tissue receiving the ultrasound energy is raised to a temperature in a range from about 40° C. to about 55° C., or from about 43° C. to about 48° C., or below a threshold of ablation of the tissue.

Moving to FIG. 2, a graph illustrates efficiency of an ultrasound transducer at specific frequency f_c , in accordance with various embodiments. Efficiency of a transducer is defined as the ratio of the power output in the desired form to the total power input. Mathematically, if P_{in} represents the total power input and P_{out} represents the power output in the desired form, then the efficiency E , as a ratio between 0 and 1, is given by:

$$E = P_{out} / P_{in} \quad \text{Equation 1}$$

If $E\%$ represents the efficiency as a percentage, then:

$$E\% = 100 P_{out} / P_{in} \quad \text{Equation 2}$$

In general, a transducer is not 100% efficient and power is typically lost during the operation of the transducer in the

form of heat. However, for a high-Q transducer, efficiency can approach 100% and heat generated by the transducer is minimized. A transducer is most efficient at specific frequency f_c , as illustrated in FIG. 2. The transducer has the maximum power output at frequency f_c .

When a transducer operates, the transducer heats up over time and the temperature of the transducer changes. As the temperature of the transducer changes, the resonant frequency will shift towards frequency f_p , as illustrated in FIG. 3. This frequency shift decreases the efficiency of the transducer and, the power output from the transducer is significantly lower in the example of FIG. 3 as compared to the example of FIG. 2.

Transducer efficiency decreases due to changes in temperature of the transducer as a function of time. In addition, a change in temperature of the transducer will cause a frequency shift. The frequency shift changes as a function of increasing temperature of the transducer. A frequency shift decreases efficiency and can cause a system to change total power input to make up for a loss of power applied by the transducer. A frequency shift will change the impedance of the transducer.

In various embodiments, systems and methods, described herein, monitor transducer temperature and report changes in temperature to a controller to modify the frequency generation to the transducer. In various embodiments, systems and methods can monitor transducer temperature and report changes in temperature to a controller to modify the total power input to the transducer. In various embodiments, systems and methods can monitor efficiency and controls transducer temperature to prevent energy transmission from a shift in frequency.

In various embodiments, systems and methods can at least one of monitor transducer temperature and control transducer temperature. In various embodiments, systems and methods can operate the transducer to at or near maximum efficiency of power over a period of time. In various embodiments, systems and methods can operate the transducer to at or near maximum efficiency of power as a temperature of the transducer changes. In various embodiments, systems and methods can modify temperature of the transducer to maintain operation at or near maximum efficiency of power. In various embodiments, systems and methods can prevent a change in impedance of the transducer.

In some embodiments, energy emission, such as, an ultrasound emission, can be directed to targeted tissue to initiate a desired treatment to the targeted tissue. If the power of the energy emission, such as, an ultrasound emission, is too high, the targeted tissue can be permanently damaged, which provide pain to the patient being treated. In addition, if the power of the energy emission, such as, an ultrasound emission, is too high, the desired treatment to the targeted tissue may not be effective. If the power of the energy emission, such as, an ultrasound emission, is too low, the desired treatment to the targeted tissue may not be effective.

If the efficiency of the transducer degrades, the power of energy emission decreases. If the temperature of the transducer changes, the efficiency of the transducer changes and the power of energy emission decreases. For the most effective treatment to targeted tissue, power of energy emission is constant. Various embodiments provide methods and systems to provide constant energy emission from transducer 110 that is directed to targeted tissue.

Referring to FIG. 4, system 131 is illustrated, in accordance with some embodiments. System 131 can comprise drivers 102, power sensor 104, transducer 110, controller

115, and oscillator 120. In various embodiments, oscillator 120 generates a frequency which is communicated to drivers 102 to power transducer 110 to produce energy transmission 150 at the frequency. Oscillator 120 can be an oscillator or any frequency generator, now known or later developed. For example, oscillator 120 can be but is not limited to, a function generator, a frequency generator, a waveform generator, a signal generator, pitch generator, a wave generator, or a pulse generator, frequency synthesizer, direct digital synthesizer, or combinations thereof. In some embodiments, oscillator 120 can be combined with or integrated to drivers 102. In some embodiments, oscillator 120 is programmable. In some embodiments, controller 115 can be combined with or integrated to at least one of oscillator 120 and drivers 102. In some embodiments, power sensor 104 can be combined with or integrated to at least one of oscillator 120, controller 115 and drivers 102. In sonic embodiments, power sensor 104 can be combined with or integrated to at least one of oscillator 120, and drivers 102. In some embodiments, power sensor 104 can be combined with or integrated to at least one of controller 115 and drivers 102. In sonic embodiments, power sensor 104 can be combined with or integrated to at least one of oscillator 120, and controller 115. In some embodiments, power sensor 104 can be combined with or integrated to drivers 102. In some embodiments, power sensor 104 can be combined with or integrated to oscillator 120. In some embodiments, power sensor 104 can be combined with or integrated to controller 115.

In some embodiments, power sensor 104 monitors power input from drivers 102 to transducer 110. In some embodiments, power sensor 104 communicates with controller 115, which controls oscillator 120. In some embodiments, controller 115 receives signal from power sensor 104 and controls a frequency generated by oscillator 120 based on the received signal. In some embodiments, power sensor 104 communicates a power level of the power input from drivers 102.

As transducer 110 efficiency of energy transmission 150 degrades, for example as illustrated in FIG. 3, drivers 102 changes the power input to transducer 110. In some embodiments, power sensor 104 detects the change in power input to transducer 110 and communicates with controller 115, which controls oscillator 120 to change in the power level of the power input from supply and/or drivers 102. In some embodiments, oscillator 120 generates a correction to the frequency which is communicated to the drivers 102, which is based on the communication from the power sensor 104. In some embodiments, the correction to the frequency lowers the power level of power input from drivers 102. In some embodiments, energy transmission 150 is corrected to specific frequency f_c as illustrated in FIG. 2. If this correction to specific frequency f_c does not lower the power input from the drivers 102 to transducer 110 below a threshold, power sensor 104 communicates this elevated power level to controller 115, which controls oscillator 120 for another generation of a correction to the frequency. In some embodiments, system 131 comprises a shut off power function, which is initiated if power sensor 104 detects a power level that is above a predetermined threshold. In some embodiments, the shut off power function prevents the damaging or destroying of transducer 110.

In some embodiments, the thickness of the transduction element of transducer 110 may be configured to be uniform. That is, the transduction element may be configured to have a thickness that is generally substantially the same throughout. In another exemplary embodiment, the transduction element may also be configured with a variable thickness,

and/or as a multiple damped device. For example, the transduction element of transducer 110 may be configured to have a first thickness selected to provide a specific operating frequency of a lower range, for example from approximately 1 kHz to 3 MHz. The transduction element may also be configured with a second thickness selected to provide a specific operating frequency of a higher range, for example from approximately 3 to 100 MHz or other frequency ranges described herein.

In yet another exemplary embodiment, transducer 110 may be configured as a single broadband transducer excited with two or more frequencies to provide an adequate output for raising the temperature within ROI 215 to the desired level. Transducer 110 may also be configured as two or more individual transducers, wherein each transducer 110 may comprise a transduction element. The thickness of the transduction elements may be configured to provide specific-operating frequencies in a desired treatment range. For example, in some embodiments, transducer 110 may comprise a first transducer 110 configured with a first transduction element having a thickness corresponding to a specific frequency range of approximately 1 MHz to 3 MHz, and a second transducer 110 configured with a second transduction element having a thickness corresponding to a specific frequency of approximately 3 MHz to 100 MHz or frequency ranges described herein.

Moreover, in some embodiments, any variety of mechanical lenses or variable focus lenses, e.g. liquid-filled lenses, may also be used to focus and or defocus the energy field. For example, transducer 110 may also be configured with an electronic focusing array in combination with one or more transduction elements to facilitate changed flexibility in treating ROI 215. Array may be configured in a manner similar to transducer 110. That is, array may be configured as an array of electronic apertures that may be operated by a variety of phases via variable electronic time delays. Accordingly, the electronic apertures of array may be manipulated, driven, used, configured to produce and/or deliver energy in a manner corresponding to the phase variation caused by the electronic time delay. For example, these phase variations may be used to deliver defocused beams, planar beams, and/or focused beams, each of which may be used in combination to achieve different physiological effects in ROT 215.

Transduction elements may be configured to be concave, convex, and/or planar. For example, transduction elements can be configured to be concave in order to provide focused energy for treatment of ROI 215. In another exemplary embodiment, transduction elements may be configured to be substantially flat in order to provide substantially uniform energy to ROI 215. In addition, transduction elements may be configured to be any combination of concave, convex, and/or substantially flat structures. For example, a first transduction element may be configured to be concave, while a second transduction element may be configured to be substantially flat.

Moreover, transduction element can be any distance from the skin surface 204. In that regard, it can be far away from the skin surface 204 disposed within a long transducer 110 or it can be just a few millimeters from skin surface 204. In certain exemplary embodiments, positioning the transduction element closer to skin surface 204 is better for transmitting ultrasound at high frequencies. Moreover, both two and three dimensional arrays of transduction elements can be used in various embodiments.

In some embodiments, transducer 110 may also be configured as an annular array to provide planar, focused and/or

defocused acoustical energy. For example, in some embodiments, an annular array may comprise a plurality of rings. Rings may be mechanically and electrically isolated into a set of individual elements, and may create planar, focused, or defocused waves. For example, such waves can be specified on-axis, such as by methods of adjusting corresponding phase delays. An electronic focus may be moved along various depth positions in ROI 215, and may enable variable strength or beam tightness, while an electronic defocus may have varying amounts of defocusing. In some embodiments, a lens and/or convex or concave shaped annular array may also be provided to aid focusing or defocusing such that any time differential delays can be reduced. Movement of annular array in one, two or three-dimensions, or along any path, such as through use of probes, motion mechanisms, any conventional robotic arm mechanisms, and the like may be implemented to scan and/or treat a volume or any corresponding space within ROI 215.

In FIG. 5, system 132 is illustrated, in accordance with some embodiments. System 132 can comprise drivers 102, transducer 110, piezoelectric sensor 124, controller 115, and oscillator 120. In some embodiments, piezoelectric sensor 124 can be combined with or integrated to at least one of oscillator 120 and drivers 102. In some embodiments, piezoelectric sensor 124 can be combined with or integrated into oscillator 120. In some embodiments, piezoelectric sensor 124 can be combined with into integrated to drivers 102. In various embodiments, oscillator 120 generates a frequency which is communicated to drivers 102 to power transducer 110 to produce energy transmission 150 at the frequency. In some embodiments, piezoelectric sensor 124 monitors heat generated by transducer 110. In some embodiments, piezoelectric sensor 124 is coupled to transducer 110. In some embodiments, piezoelectric sensor 124 is integrated to transducer 110. For example, piezoelectric sensor 124 may be a portion of transducer 110, which that is isolated or insulation from the rest of transducer 110, and may comprise identical materials as transducer 110. However, in one aspect of this example, piezoelectric sensor 124 has the opposite temperature coefficient of transducer (same coefficient but opposite sign) and the piezoelectric sensor 124 changes temperature at the same rate as transducer 110, thus compensating for changes in temperature of transducer 110.

Piezoelectric sensor 124 can comprise ceramic, or any other material or combination of material described herein. In some embodiments, piezoelectric sensor 124 is configured with a temperature coefficient that is lower than the temperature coefficient of transducer 110. In some embodiments, piezoelectric sensor 124 is configured with temperature coefficient, which is negative. In various embodiments, piezoelectric sensor 124 generates an electric potential in response to a temperature change, and communicates this electric potential to controller 115, which controls oscillator 120. In some embodiments, piezoelectric sensor 124 communicates with oscillator 120. In some embodiments, controller 115 receives signal from piezoelectric sensor 124 and controls a frequency generated by oscillator 120 based on the received signal. In some embodiments, piezoelectric sensor 124 communicates the heat generated by transducer 110, which can be communicated using temperature.

As transducer 110 efficiency of energy transmission 150 degrades, for example as illustrated in FIG. 3, heat generated by transducer 110 changes. For example, drivers 102 changes the power input to transducer 110, which can change the heat generated by transducer 110. In some embodiments, piezoelectric sensor 124 detects the change in

heat generation by transducer 110 and communicates with controller 115, which controls oscillator 120, the change in heat generation. In some embodiments, oscillator 120 generates a correction to the frequency which is communicated to the drivers 102, which is based on the communication from the piezoelectric device 124. In some embodiments, the correction to the frequency lowers the power level of power input from drivers 102, which can lower the amount of heat that is generated by transducer 110. In some embodiments, the correction to the frequency lowers the power level of power input from drivers 102. In some embodiments, energy transmission 150 is corrected to specific frequency f_c as illustrated in FIG. 2. If this correction to specific frequency f_c does not lower the power input from the drivers 102 to transducer 110 below a threshold, piezoelectric sensor 124 communicates this elevated heat generation by transducer 110 to oscillator 124 for another generation of a correction to the frequency. In some embodiments, system 132 comprises a shut off power function, which is initiated if piezoelectric sensor 124 detects a heat generation level or a temperature of transducer 110 is above a predetermined threshold. In some embodiments, the shut off power function prevents the damaging or destroying of transducer 110.

Turning to FIG. 6, system 133 is illustrated, in accordance with some embodiments. System 133 can comprise drivers 102, transducer 110, temperature sensor 127, and oscillator 120. In some embodiments, temperature sensor 127 can be combined with or integrated to at least one of oscillator 120 and drivers 102. In various embodiments, oscillator 120 generates a frequency which is communicated to drivers 102 to power transducer 110 to produce energy transmission 150 at the frequency. In some embodiments, temperature sensor 127 monitors temperature of transducer 110. In some embodiments, temperature sensor 127 is coupled to transducer 110. In some embodiments, temperature sensor 127 is integrated to transducer 110. Temperature sensor 127 can be any suitable temperature sensor, now known or later developed. In some embodiments, temperature sensor 127 communicates with controller 115, which communicates with oscillator 120. In some embodiments, temperature sensor 127 communicates with oscillator 120. In some embodiments, controller 115 receives signal from temperature sensor 127 and controls a frequency generated by oscillator 120 based on the received signal. In some embodiments, temperature sensor 127 communicates the temperature of by transducer 110.

As transducer 110 efficiency of energy transmission 150 degrades, for example as illustrated in FIG. 3, heat generated by transducer 110 changes. For example, drivers 102 changes the power input to transducer 110, which can change the heat generated by transducer 110. In some embodiments, temperature sensor 127 detects the change in heat generation by transducer 110 and communicates with controller 115, which controls oscillator 120, the change in heat generation. In some embodiments, oscillator 120 generates a correction to the frequency which is communicated to the drivers 102, which is based on the communication from the piezoelectric device 124. In some embodiments, the correction to the frequency lowers the power level of power input from drivers 102, which can lower the amount of heat that is generated by transducer 110. In some embodiments, the correction to the frequency lowers the power level of power input from drivers 102. In some embodiments, energy transmission 150 is corrected to specific frequency f_c as illustrated in FIG. 2. If this correction to specific frequency f_c does not lower the power input from

13

the drivers 102 to transducer 110 below a threshold, temperature sensor 127 communicates this elevated heat generation by transducer 110 to oscillator 124 for another generation of a correction to the frequency. In some embodiments, system 132 comprises a shut off power function, which is initiated if temperature sensor 127 detects a heat generation level or a temperature of transducer 110 is above a predetermined threshold. In some embodiments, the shut off power function prevents the damaging or destroying of transducer 110.

Moving to FIG. 7, system 135 is illustrated, in accordance with some embodiments. System 135 can comprise drivers 102, voltage monitor 105, transducer 110, controller 115, and oscillator 120. In various embodiments, oscillator 120 generates a frequency which is communicated to drivers 102 to power transducer 110 to produce energy transmission 150 at the frequency. Oscillator 120 can be an oscillator or any frequency generator, now known or later developed. For example, oscillator 120 can be but is not limited to, a function generator, a frequency generator, a waveform generator, a signal generator, pitch generator, a wave generator, or a pulse generator, frequency synthesizer, direct digital synthesizer, or combinations thereof. In some embodiments, oscillator 120 can be combined with or integrated to drivers 102. In some embodiments, oscillator 120 is programmable. In some embodiments, controller 115 can be combined with or integrated to at least one of oscillator 120 and drivers 102. In some embodiments, voltage monitor 105 can be combined with or integrated to at least one of oscillator 120, controller 115 and drivers 102. In some embodiments, voltage monitor 105 can be combined with or integrated to at least one of oscillator 120, and drivers 102. In some embodiments, voltage monitor 105 can be combined with or integrated to at least one of controller 115 and drivers 102. In some embodiments, voltage monitor 105 can be combined with or integrated to at least one of oscillator 120, and controller 115. In some embodiments, voltage monitor 105 can be combined with or integrated to drivers 102. In some embodiments, voltage monitor 105 can be combined with or integrated to oscillator 120. In some embodiments, voltage monitor 105 can be combined with or integrated to controller 115. In sonic embodiments, voltage monitor 105 monitors voltage of power from drivers 102 to transducer 110. In some embodiments, voltage monitor 105 communicates with controller 115, which controls oscillator 120. In some embodiments, controller 115 receives signal from voltage monitor 105 and controls a frequency generated by oscillator 120 based on the received signal. In some embodiments, voltage monitor 105 communicates a voltage level of the voltage of power from drivers 102.

As transducer 110 efficiency of energy transmission 150 degrades, for example as illustrated in FIG. 3, drivers 102 changes the voltage of power to transducer 110. In some embodiments, voltage monitor 105 detects the increase in voltage of power to transducer 110 and communicates with controller 115, which controls oscillator 120 to change in the voltage level of the voltage of power from supply and/or drivers 102. In some embodiments, oscillator 120 generates a correction to the frequency which is communicated to the drivers 102, which is based on the communication from the voltage monitor 105. In some embodiments, the correction to the frequency lowers the voltage level of voltage of power from drivers 102. In some embodiments, energy transmission 150 is corrected to specific frequency f_c as illustrated in FIG. 2. If this correction to specific frequency f_c does not lower the voltage of power from the drivers 102 to transducer 110 below a threshold, voltage monitor 105 commu-

14

nicates this elevated voltage level to controller 115, which controls oscillator 120 for another generation of a correction to the frequency. In some embodiments, system 135 comprises a shut off power function, which is initiated if voltage monitor 105 detects a voltage level that is above a predetermined threshold. In some embodiments, the shut off power function prevents the damaging or destroying of transducer 110.

FIG. 8 With reference to FIG. 8, system 135 is illustrated, in accordance with some embodiments. System 135 can comprise drivers 102, transducer 110, temperature sensor 127, and oscillator 120. In some embodiments, temperature sensor 127 can be combined with or integrated to at least one of oscillator 120 and drivers 102. In various embodiments, oscillator 120 generates a frequency which is communicated to drivers 102 to power transducer 110 to produce energy transmission 150 at the frequency. In some embodiments, temperature sensor 127 monitors temperature of transducer 110. In some embodiments, temperature sensor 127 coupled to transducer 110. In some embodiments, temperature sensor 127 is integrated to transducer 110. Temperature sensor 127 can be any suitable temperature sensor, now known or later developed. In some embodiments, temperature sensor 127 communicates with controller 115, which communicates with oscillator 120. In some embodiments, temperature sensor 127 communicates with oscillator 120. In some embodiments, controller 115 receives signal from temperature sensor 127 and controls a frequency generated by oscillator 120 based on the received signal. In some embodiments, temperature sensor 127 communicates the temperature of by transducer 110. As transducer 110 efficiency of energy transmission 150 degrades, for example as illustrated in FIG. 3, drivers 102 changes the power to transducer 110, which change the voltage across the transducer 110. In some embodiments, controller 115 detects the change in voltage across transducer 110 and communicates with controller 115. In some embodiments, oscillator 120 generates a correction to the frequency which is communicated to the drivers 102, which is based on the communication from controller 115. In some embodiments, the correction to the frequency lowers the voltage level of voltage across transducer 110. In some embodiments, energy transmission 150 is corrected to specific frequency f_c as illustrated in FIG. 2. If this correction to specific frequency f_c does not lower the voltage across transducer 110 below a threshold, controller 115 communicates this elevated voltage level to oscillator 120 for another generation of a correction to the frequency.

As transducer 110 efficiency of energy transmission 150 degrades, for example as illustrated in FIG. 3, heat generated by transducer 110 changes. For example, drivers 102 changes the power input to transducer 110, which can change the heat generated by transducer 110. In some embodiments, temperature sensor 127 detects the change in heat generation by transducer 110 and communicates with controller 115, which controls oscillator 120, the change in heat generation. In some embodiments, oscillator 120 generates a correction to the frequency which is communicated to the drivers 102, which is based on the communication from the piezoelectric device 124. In some embodiments, the correction to the frequency lowers the power level of power input from drivers 102, which can lower the amount of heat that is generated by transducer 110. In some embodiments, the correction to the frequency lowers the power level of power input from drivers 102. In some embodiments, energy transmission 150 is corrected to specific frequency f_c as illustrated in FIG. 2. If this correction to specific frequency f_c does not lower the power input from

the drivers 102 to transducer 110 below a threshold, temperature sensor 127 communicates this elevated heat generation by transducer 110 to oscillator 124 for another generation of a correction to the frequency. In some embodiments, system 132 comprises a shut off power function, which is initiated if temperature sensor 127 detects a heat generation level or a temperature of transducer 110 is above a predetermined threshold. In some embodiments, the shut off power function prevents the damaging or destroying of transducer 110.

Various embodiments provide a method of sensing coupling of an ultrasound source to a target. In some embodiments, the method comprises providing an ultrasound sound source comprising a transducer, an acoustically transparent standoff, an acoustic window at a bottom surface of the standoff, and a frequency sweep function coupled to the transducer. In some embodiments, the method can comprise emitting ultrasound energy from the transducer; receiving reflected energy; frequency sweeping the transducer; determining the feedback from the frequency sweep is above a threshold level; and determining of the source is coupled to the target.

In some embodiments, if the feedback from the frequency is above the threshold level, then the source is not coupled to the target. In some embodiments, if the feedback from the frequency is below the threshold level, then the source is coupled to the target.

In some embodiments, the window is a half wavelength thick. In some embodiments, the method can further comprise providing constant average output power from the source. In some embodiments, the method can further comprise terminating power to the source. In sonic embodiments, the sweep frequency has a period, which is calculated using a path length of the standoff and the speed of sound. In some embodiments, the method can further comprise comprising providing ultrasound energy to a target.

Various embodiments provide a system for determining whether an ultrasound source is coupled to a target. In some embodiments, the system comprises an ultrasound source comprising a transducer; an acoustically transparent standoff coupled to the transducer; a half wavelength acoustic window at a bottom surface of the standoff, and a frequency sweep function coupled to the transducer.

In some embodiments, the half wavelength acoustic window is a reflector when the ultrasound source is not coupled to the target.

In some embodiments, the half wavelength acoustic window is transparent to ultrasound energy when the ultrasound source is coupled to the target. In some embodiments, the system can further comprise a power to transducer termination function in communication with the frequency sweep function.

In some embodiments, the frequency sweep function provides a constant average output power from the ultrasound source when the ultrasound source is coupled to the target. In some embodiments, the system can further comprise a lens coupled to the ultrasound source.

Various embodiments provide a system for providing a constant average output of power from an ultrasound source. In some embodiments, the system comprises an ultrasound transducer coupled to a power supply; a controller in communication with the power supply; a chirp function in communication with and operable to monitor the ultrasound transducer; a feedback loop from the chirp function to the controller. In some embodiments, the controller is operable

to change a parameter on the transducer based on the feedback to provide a constant average output of power from the ultrasound transducer.

In some embodiments, the system can further comprise a coupling device in acoustic communication with the ultrasound transducer. In some embodiments, the system can further comprise a half wavelength acoustic window in acoustic communication with the ultrasound transducer.

In some embodiments the coupling device contains a medium configured to be transparent to ultrasound energy. In some embodiments, the system can further comprise a contact sensor operable to determine if the ultrasound transducer is coupled to a target. In some embodiments, the controller is operable to control the power supply to change an amount of power provided to the ultrasound transducer.

In various embodiments, ultrasound probe 205 can comprise a tissue contact sensor. In some embodiments, tissue contact sensor communicates whether ultrasound probe 205 is coupled to the ROI 215. The tissue contact sensor may measure a capacity of a skin surface 204 above the ROI 215 and communicate a difference between the capacitance of the contact to the skin surface 204 and the capacitance of air. In some embodiments, the tissue contact sensor is initiated or turned on by pressing ultrasound probe against skin surface 204.

In various embodiments, as illustrated in FIGS. 9 and 10, a coupling device having a coupling sensor system is illustrated. Coupling device 130 comprises enclosure 132 which can be filled with coupling medium 135. Coupling device 130 further comprises a window 140 which is essentially transparent to ultrasound energy. In some embodiments, coupling device 130 comprises transducer 110. In some embodiments, coupling device 130 may comprise matching layer and/or lens 113. Coupling device 130 is part of or connects to probe 205. In some embodiments, transducer 110 is separate from the coupling device 130. In some embodiments, transducer 110 and matching layer and/or lens 113 are separate from coupling device 130. Coupling device 130 comprises path length 144, which is the distance from transducer 110 to window 140.

In some embodiments, coupling device 130 is configured to provide ultrasound energy 150 to ROI 215. In some embodiments, coupling device 130 is configured to provide focused ultrasound energy 150 to ROI 215. In some embodiments, coupling device 130 is configured to provide unfocused ultrasound energy 150 to ROI 215. In some embodiments, coupling device 130 is configured to provide defocused ultrasound energy 150 to ROI 215.

In some embodiments, window 140 is a half wavelength ("λ") thick. In some embodiments, window 140 is a multiple of a half wave length thick, such as, for example, 1.5 wavelength thick. Window 140 can comprise any number of materials that are temperature stable within up to about 150° C. (for example plastics and polymers) or to higher temperatures (for example metals and alloys) and are able to be configured into ultrasound transmissive window having a multiple of a half wave length thick. In some embodiments, window 140 can be configured using a cross linked polystyrene material or a PE imide material.

In some embodiments, enclosure 132 is essentially impermeable to water. Enclosure 132 contains medium 135, which can be water or saline solution or other water based solution, a gel, or a solid. Medium 135 is essentially transparent to acoustic energy. In some embodiments, medium 135 has acoustic impedance very similar to or the same as tissue in

the ROI 215. In some embodiments, medium 135 has acoustic impedance very similar to or the same as skin surface.

In some embodiments, an output from the frequency sweep can be monitored as illustrated in FIGS. 11 and 12. The units for axis of the graphs in FIGS. 11 and 12 are resistance in the y axis and frequency in the x axis. FIG. 11 illustrates the feedback from a frequency sweep when coupling device 130 is coupled to ROI 215 as illustrated in FIG. 9. FIG. 12 illustrates the feedback from a frequency sweep when coupling device 130 is uncoupled (or coupled to air) as illustrated in FIG. 10. This difference in feedback from the frequency sweep can be a contact sensor. If the frequency sweep reports feedback is similar to FIG. 11, probe 205 continues to function providing ultrasound energy 150 to ROI 215. If the frequency sweep reports feedback is similar to FIG. 12, probe 205 is shut down as a safety mechanism and/or to protect the transducer from being damaged or destroyed.

In some embodiments, a DDS synthesizer and be coupler to transducer 110 and configured to frequency sweep transducer 110. In some embodiments, frequency sweep can monitor the constant average output power of transducer 110. In some embodiments, frequency sweep can be a step function of a set of different frequencies. In some embodiments, the frequency sweep is a chirp function. In some embodiments, the step function of a set of different frequencies can comprise a plurality of different frequencies. In some embodiments, the period of each sweep is 50 kHz. This sweep period is calculated using path length 144 equal to 15 mm and a time of flight of 20 microseconds. In some embodiments, the period of each sweep is 23 kHz. This sweep period is calculated using path length 144 equal to 32.6 mm and a time of flight of 43.5 microseconds. Using path length 144 and the time of flight of the ultrasound energy 150, an appropriate sweep period can be calculated for most configurations of coupling device 130.

In some embodiments, an output from the frequency sweep can be monitored as illustrated in FIGS. 11 and 12. The units for axis of the graphs in FIGS. 11 and 12 are resistance in the y axis and frequency in the x axis. FIG. 11 illustrates the feedback from a frequency sweep when coupling device 130 is coupled to ROI 215 as illustrated in FIG. 9. FIG. 11 illustrates the feedback from a frequency sweep when coupling device 130 is uncoupled (or coupled to air) as illustrated in FIG. 10. This difference in feedback from the frequency sweep can be a contact sensor. If the frequency sweep reports feedback is similar to FIG. 11, probe 205 continues to function providing ultrasound energy 150 to ROI 215. If the frequency sweep reports feedback is similar to FIG. 12, probe 205 is shut down as a safety mechanism and/or to protect the transducer from being damaged or destroyed.

In some embodiments, frequency sweep can monitor and adjust output power to achieve a constant average output power, even with variations in the medium 135 temperature and/or transducer 110 temperature. In various embodiments, contact sensor system can be combined with one or more different sensing techniques. For example, contact sensor can be combined with a hall detector. For example, contact sensor can be combined with an optical detector. For example, contact sensor can be combined with a conductive detector. For example, contact sensor can be combined with a piezo electric detector. For example, contact sensor can be combined with a mechanical detector. For example, contact sensor can be combined with a magnetic detector. In various embodiments, contact sensor system can be combined with

at least one of a hall detector, optical detector, an acoustic impedance detector, a conductive detector, a piezo electric detector, a mechanical detector, a magnetic detector, an acoustic impedance detector, and combinations thereof.

In some embodiments, coupling device 130 can comprise a temperature sensor. In some embodiments, coupling device 130 can comprise two temperature sensors. For example, one of the temperature sensors can be in contact with medium 135 and the second temperature sensor can be in contact with transducer 110. In some embodiments, if the temperature as reported by a temperature is above 43° C., probes 205 stop emission of ultrasound energy 150.

The following patents and patent applications are incorporated by reference: US Patent Application Publication No. 20050256406, entitled "Method and System for Controlled Scanning, Imaging, and/or Therapy" published Nov. 17, 2005; US Patent Application Publication No. 20060058664, entitled "System and Method for Variable Depth Ultrasound Treatment" published Mar. 16, 2006; US Patent Application Publication No. 20060084891, entitled "Method and System for Ultra-High Frequency Ultrasound Treatment" published Apr. 20, 2006; U.S. Pat. No. 7,530,958, entitled "Method and System for Combined Ultrasound Treatment" issued May 12, 2009; US Patent Application Publication No. 2008071255, entitled "Method and System for Treating Muscle, Tendon, Ligament, and Cartilage Tissue" published Mar. 20, 2008; U.S. Pat. No. 6,623,430, entitled "Method and Apparatus for Safely Delivering Medicants to a Region of Tissue Using Imaging, Therapy, and Temperature Monitoring Ultrasonic System," issued Sep. 23, 2003; U.S. Pat. No. 7,571,336, entitled "Method and System for Enhancing Safety with Medical Peripheral Device by Monitoring if Host Computer is AC Powered" issued Aug. 4, 2009; US Patent Application Publication No. 20080281255, entitled "Methods and Systems for Modulating Medicants Using Acoustic Energy" published Nov. 13, 2008; US Patent Application Publication No. 20060116671, entitled "Method and System for Controlled Thermal Injury of Human Superficial Tissue," published Jun. 1, 2006; US Patent Application Publication No. 20060111744, entitled "Method and System for Treatment of Sweat Glands," published May 25, 2006; US Patent Application Publication No. 20080294073, entitled "Method and System for Non-Ablative Acne Treatment and Prevention," published Oct. 8, 2009; U.S. Pat. No. 8,133,180, entitled "Method and System for Treating Cellulite," issued Mar. 13, 2012; U.S. Pat. No. 8,066,641, entitled "Method and System for Photoaged Tissue," issued Nov. 29, 2011; U.S. Pat. No. 7,491,171, entitled "Method and System for Treating Acne and Sebaceous Glands," issued Feb. 17, 2009; U.S. Pat. No. 7,615,016, entitled "Method and System for Treating Stretch Marks," issued Nov. 10, 2009; and U.S. Pat. No. 7,530,356, entitled "Method and System for Noninvasive Mastopexy," issued May 12, 2009.

It is believed that the disclosure set forth above encompasses at least one distinct invention with independent utility. While the invention has been disclosed herein, the specific embodiments thereof as disclosed and illustrated herein are not to be considered in a limiting sense as numerous variations are possible. The subject matter of the inventions includes all novel and non-obvious combinations and sub combinations of the various elements, features, functions and/or properties disclosed herein.

Various embodiments and the examples described herein are not intended to be limiting in describing the full scope of systems and methods of this invention. Equivalent changes, modifications and variations of various embodiments, mate-

rials, systems, and methods may be made within the scope of the present invention, with substantially similar results.

The invention claimed is:

1. A method of sensing coupling of an ultrasound source to a target, the ultrasound source comprising a transducer, an acoustically transparent standoff, an acoustic window at a bottom surface of the standoff, and a controller coupled to the transducer, the controller configured to execute a frequency sweep over time function, the method comprising:

emitting an ultrasound energy from the transducer by frequency sweeping over time the transducer using the frequency sweep over time function;

in response to the emitted ultrasound energy, receiving a reflected energy from the acoustic window;

determining, using the reflected energy, a feedback from the frequency sweep;

comparing the feedback with a threshold level; and

determining, based on the comparison, if the ultrasound source is coupled with the target.

2. The method according to claim 1, wherein if the feedback from the frequency sweep is above the threshold level, then the ultrasound source is not coupled to the target.

3. The method according to claim 2, terminating or reducing power to the ultrasound source.

4. The method according to claim 1, wherein if the feedback from the frequency sweep is below the threshold level, then the ultrasound source is coupled to the target.

5. The method according to claim 4, further comprising providing constant average output power from the ultrasound source.

6. The method according to claim 4, the method further comprising transmitting a second ultrasound energy from the ultrasound source to the target.

7. The method according to claim 1, wherein the acoustic window has a thickness that is a half wavelength of the ultrasound energy or a multiple thereof.

8. The method according to claim 1, the standoff comprising a path length defined as the distance that the ultrasound energy travels through the standoff, wherein the

frequency sweep has a frequency span, which is calculated using the path length of the standoff and a speed of sound within the standoff.

9. A system for determining whether an ultrasound source is coupled to a target, the system comprising:

an ultrasound source comprising a transducer;

an acoustically transparent standoff coupled to the transducer;

a half wavelength acoustic window or multiple thereof at a bottom surface of the standoff; and

a controller coupled to the transducer,

wherein the controller is configured to cause the transducer to emit ultrasound energy by frequency sweeping over time the transducer using a frequency sweep over time function;

wherein in response to the emitted ultrasound energy, the transducer is further configured to receive a reflected energy from the half wavelength acoustic window;

wherein the controller is further configured to determine, using the reflected energy, a feedback from the frequency sweep, compare the feedback with a threshold level, and determine, based on the comparison, if the ultrasound source is coupled with the target.

10. The system according to claim 9, wherein the half wavelength acoustic window is a reflector when the ultrasound source is not coupled to the target.

11. The system according to claim 9, wherein the half wavelength acoustic window is transparent to ultrasound energy when the ultrasound source is coupled to the target.

12. The system according to claim 9, the controller further configured to execute a power to transducer termination function in communication with the frequency sweep over time function.

13. The system according to claim 9 wherein the controller provides a constant average output power from the ultrasound source when the ultrasound source is coupled to the target.

14. The system according to claim 9, further comprising a lens coupled to the ultrasound source.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 9,504,446 B2
APPLICATION NO. : 13/547023
DATED : November 29, 2016
INVENTOR(S) : Paul Jaeger et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Specification

Column 10, Line 44 - "ROT" should be -- ROI --

Signed and Sealed this
Twenty-fifth Day of July, 2017

A handwritten signature in dark ink, reading "Joseph Matal". The signature is written in a cursive, flowing style.

Joseph Matal
*Performing the Functions and Duties of the
Under Secretary of Commerce for Intellectual Property and
Director of the United States Patent and Trademark Office*

专利名称(译)	用于将超声源耦合到组织的系统和方法		
公开(公告)号	US9504446	公开(公告)日	2016-11-29
申请号	US13/547023	申请日	2012-07-11
申请(专利权)人(译)	引导治疗系统公司		
当前申请(专利权)人(译)	引导治疗系统公司		
[标]发明人	JAEGER PAUL BARTHE PETER G SLAYTON MICHAEL H		
发明人	JAEGER, PAUL BARTHE, PETER G. SLAYTON, MICHAEL H.		
IPC分类号	A61B8/00 A61N7/02 A61B18/00 A61N7/00		
CPC分类号	A61B8/429 A61B8/56 A61N7/02 A61B2018/00642 A61B2018/00898 A61B2090/378 A61N2007/006 A61N2007/0034 A61N2007/0091 A61N2007/0095 A61N2007/027		
优先权	61/506609 2011-07-11 US 61/506610 2011-07-11 US 61/369782 2010-08-02 US 61/369793 2010-08-02 US 61/369806 2010-08-02 US 61/370095 2010-08-02 US		
其他公开文献	US20130012838A1		
外部链接	Espacenet USPTO		

摘要(译)

本公开提供了用于感测超声源与目标的耦合以及用于提供来自超声源的恒定平均功率输出的系统和方法。该系统和方法可以包括频率扫描功能。该系统和方法还可以包括从声学窗口接收反射能量并使用反射能量确定反馈。该系统和方法还可以包括将反馈与阈值水平进行比较，并使用该比较来确定超声源是否与目标耦合。

