



US007648459B2

(12) **United States Patent**
Takeda et al.

(10) **Patent No.:** **US 7,648,459 B2**
(45) **Date of Patent:** **Jan. 19, 2010**

- (54) **ULTRASONIC PROBE** 7,063,666 B2 * 6/2006 Weng et al. 600/439
- (75) Inventors: **Junichi Takeda**, Kawasaki (JP);
Masashi Ozawa, Yokohama (JP) 2001/0031922 A1 * 10/2001 Weng et al. 600/439
- 2002/0010414 A1 * 1/2002 Coston et al. 604/20
- 2005/0096542 A1 * 5/2005 Weng et al. 600/439
- 2006/0235300 A1 * 10/2006 Weng et al. 600/439
- (73) Assignee: **Panasonic Corporation**, Osaka (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 38 days.

FOREIGN PATENT DOCUMENTS

- (21) Appl. No.: **10/550,835** JP 60-132544 7/1985
- (22) PCT Filed: **Mar. 24, 2004** JP 1-291846 11/1989
- (86) PCT No.: **PCT/JP2004/004045** JP 1989-172800 12/1989
- JP 3-173546 7/1991
- JP 5-220140 8/1993
- JP 6-105844 4/1994
- JP 9-139998 5/1997
- JP 11-347032 12/1999
- (87) PCT Pub. No.: **WO2004/084734**
- PCT Pub. Date: **Oct. 7, 2004**

(Continued)

- (65) **Prior Publication Data**
- US 2006/0241467 A1 Oct. 26, 2006

Primary Examiner—Long V Le
Assistant Examiner—Sanjay Cattungal
(74) *Attorney, Agent, or Firm*—Hamre, Schumann, Mueller & Larson, P.C.

- (30) **Foreign Application Priority Data**
- Mar. 25, 2003 (JP) 2003-083489

(57) **ABSTRACT**


- (51) **Int. Cl.**
A61B 8/00 (2006.01)
- (52) **U.S. Cl.** 600/437; 600/446; 600/459;
310/334; 310/311
- (58) **Field of Classification Search** 600/437-459;
310/334-337, 311; 367/901
- See application file for complete search history.

An ultrasonic probe according to the present invention includes: an ultrasonic element for transmitting and receiving an ultrasonic signal; a signal line for transmitting an electric signal to or from the ultrasonic element; and a ground line for supplying a ground potential to the ultrasonic element. The ultrasonic element is connected electrically with a sensor signal substrate and a sensor ground substrate. These substrates are connected electrically with the signal line and the ground line, respectively, via a cable substrate. The sensor ground substrate and the cable substrate are connected directly or via a relay ground substrate.

- (56) **References Cited**
- U.S. PATENT DOCUMENTS

- 5,295,487 A * 3/1994 Saitoh et al. 600/459
- 5,300,068 A * 4/1994 Rosar et al. 606/34
- 5,810,009 A * 9/1998 Mine et al. 600/459
- 6,100,626 A * 8/2000 Frey et al. 310/334

9 Claims, 5 Drawing Sheets



US 7,648,459 B2

Page 2

FOREIGN PATENT DOCUMENTS			JP	2002-52024	2/2002
JP	2000-115891	4/2000	JP	2003-265470	9/2003
JP	2001-054194	2/2001			
JP	2001-276078	10/2001			
			* cited by examiner		




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

ULTRASONIC PROBE

TECHNICAL FIELD

The present invention relates to an ultrasonic probe for use in an ultrasonic diagnostic apparatus that emits ultrasonic waves to the inside of a body of a subject so as to create and display a tomographic image of the inside of the body based on the ultrasonic waves reflected at a boundary of each body tissue.

BACKGROUND ART

Ultrasonic diagnostic apparatuses transmit and receive ultrasonic waves to and from a living body so as to obtain two-dimensional information on the inside of the living body, and these apparatuses are utilized in various medical fields. Such ultrasonic diagnostic apparatuses are provided with a probe for transmitting ultrasonic waves to the inside of a body of a subject and receiving reflected waves from a body tissue. Such an ultrasonic diagnostic apparatus provided with a probe as a component thereof is disclosed in, for example, Japanese Patent No. 1746663 or the like.

FIG. 5 is a schematic cross-sectional view showing an example of a probe as a component of a conventional ultrasonic diagnostic apparatus. This ultrasonic probe includes a sensor portion 200, a cable portion 201, and a connector portion 202 to be connected to a main body of the ultrasonic diagnostic apparatus (not shown).

The sensor portion 200 includes an ultrasonic element 203 for transmitting and receiving ultrasonic waves, a sensor signal substrate 204 and a sensor ground substrate 205 connected electrically with the ultrasonic element 203, an acoustic matching plate 220 and an acoustic lens 207 provided on an ultrasonic wave transmitting/receiving surface of the ultrasonic element 203, and a backing layer 206 provided on a back surface (surface opposite to the ultrasonic wave transmitting/receiving surface) of the ultrasonic element 203. The sensor portion 200 further includes a sensor connector 217 connected with the sensor signal substrate 204 and the sensor ground substrate 205.

The cable portion 201 includes a plurality of signal wires 209, each including a signal line 209a and a ground line 209b, a cable substrate 208 connected with the signal wires 209, and a cable connector 218 connected with the cable substrate 208. In the cable portion 201, an outer periphery of the signal wires 209 is covered with a cable shield 210 and further is protected by a sheath 211. A shielding plate 219, which is a film formed of an insulating layer 219b and a conductive layer 219a formed on a surface of the insulating layer 219b, is arranged so as to surround the cable substrate 208 and the cable connector 218 as well as a part of an outer periphery of the sensor portion 200, and is connected with the cable shield 210.

The connector portion 202 includes a connector 215 for connecting with the main body and pins 216, each being connected with the signal line 209a or the ground line 209b. These components are accommodated in a connector housing 213. The connector housing 213 is provided with a conductive layer 214 on its inner wall surface. The cable shield 210 is connected with the conductive layer 214 and is to be connected with a frame ground or a signal ground of the main body of the ultrasonic diagnostic apparatus when the probe is connected with the main body of the ultrasonic diagnostic apparatus.

However, in the above conventional example, a ground electrode of the ultrasonic element 203 is connected with the ground line 209b through the sensor ground substrate 205, the

sensor connector 217 as well as the cable connector 218, and the cable substrate 208. Accordingly, due to limitations on the number of connector poles and the like, it is difficult to secure a sufficient number of poles for a ground. When a sufficient number of poles are not secured for a ground, resistance between the sensor ground substrate and the cable substrate increases, and in the case where a noise current flows through the ground due to exposure to an electromagnetic environment, the ground potential varies, and image noise may be caused.

DISCLOSURE OF INVENTION

The present invention solves the above-mentioned conventional problem, and its object is to provide an ultrasonic probe that allows ground resistance in a connecting portion between a sensor portion and a cable portion to be reduced so as to cause less noise.

In order to achieve the above-mentioned object, an ultrasonic probe according to the present invention includes: an ultrasonic element for transmitting and receiving an ultrasonic signal; a signal line for transmitting an electric signal to or from the ultrasonic element; and a ground line for supplying a ground potential to the ultrasonic element.

The ultrasonic probe further includes: a sensor signal substrate and a sensor ground substrate connected electrically with the ultrasonic element; and a cable substrate for electrically connecting the sensor signal substrate and the sensor ground substrate with the signal line and the ground line, respectively,

wherein the sensor ground substrate and the cable substrate are connected directly or via a relay ground substrate.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a cross-sectional view showing an example of an ultrasonic probe according to a first embodiment of the present invention.

FIG. 2 is a cross-sectional view showing an example of an ultrasonic probe according to a second embodiment of the present invention.

FIG. 3 is a cross-sectional view showing an example of an ultrasonic probe according to a third embodiment of the present invention.

FIG. 4 is a development of a sensor ground substrate of the ultrasonic probe according to the third embodiment.

FIG. 5 is a cross-sectional view showing a conventional ultrasonic probe.

DESCRIPTION OF THE INVENTION

In an ultrasonic probe according to the present invention, an ultrasonic element and a ground line are connected electrically, and accordingly a sensor ground substrate connected with the ultrasonic element and a cable substrate connected with the ground line are connected directly or via a relay ground substrate. Therefore, unlike the case where these substrates are connected via a connector, it is possible to avoid an increase in resistance due to limitations on the number of connector poles, resulting in a reduction in ground resistance between the sensor ground substrate and the cable substrate. Consequently, the reduction in ground resistance suppresses a change in ground potential due to a noise current induced by extraneous electromagnetic waves. As a result, an adverse effect on a reception signal due to the change in ground potential is reduced, and image noise can be prevented from being caused.

Preferably, in the above ultrasonic probe, at least a part of the sensor signal substrate is covered with the sensor ground substrate or the relay ground substrate.

Preferably, in the above ultrasonic probe, at least a part of the cable substrate is covered with the sensor ground substrate or the relay ground substrate.

Preferably, in the above ultrasonic probe, a connecting portion between the sensor signal substrate and the cable substrate is covered with the sensor ground substrate or the relay ground substrate.

According to the above-mentioned preferred examples, the sensor ground substrate or the relay ground substrate can function as a shield for shielding at least one of the sensor signal substrate, the cable substrate, and the connecting portion therebetween. Therefore, it is possible to suppress noise from being caused due to extraneous electromagnetic waves, and the ultrasonic probe exhibits increased durability to withstand electromagnetic waves.

Preferably, in the above ultrasonic probe, at least a part of the ultrasonic element is covered with the sensor ground substrate or the relay ground substrate. According to this preferred example, the ultrasonic probe exhibits increased durability to withstand electromagnetic waves.

Preferably, in the above ultrasonic probe, an ultrasonic wave transmitting/receiving surface, and further the ultrasonic wave transmitting/receiving surface and peripheral surfaces of the ultrasonic element are covered with the sensor ground substrate or the relay ground substrate. According to this preferred example, in addition to the effect of increasing durability of the ultrasonic probe to withstand electromagnetic waves, the sensor ground substrate or the relay ground substrate can function as an acoustic matching plate. In this case, there is no need to provide an acoustic matching plate additionally, resulting in an improvement in workability.

In the above preferred example, a plurality of grooves may be formed on a part of the sensor ground substrate or the relay ground substrate that covers the ultrasonic wave transmitting/receiving surface of the ultrasonic element, the grooves dividing the ultrasonic element electrically into a plurality of oscillators.

Hereinafter, embodiments of the present invention will be described with reference to the drawings.

First Embodiment

FIG. 1 is a view showing an example of an ultrasonic probe according to a first embodiment of the present invention. This ultrasonic probe includes a sensor portion **100** for converting an electric signal into an ultrasonic wave and transmitting the same to a living body as well as receiving a reflected wave from the living body and converting the same into an electric signal, a cable portion **101** for transmitting and receiving the electric signal to and from the sensor portion **100**, and a connector portion **102** for connecting the probe with the main body of an ultrasonic diagnostic apparatus.

The sensor portion **100** includes an ultrasonic element **103** and a sensor signal substrate **104** and a sensor ground substrate **105** connected electrically with the ultrasonic element **103**. On an ultrasonic wave transmitting/receiving surface of the ultrasonic element **103**, an acoustic matching plate may be provided so as to transmit and receive an ultrasonic wave efficiently. Further, on the ultrasonic wave transmitting/receiving surface of the ultrasonic element **103**, an acoustic lens **107** is provided so as to converge the ultrasonic wave and increase the resolution in an area of interest in the living body. On a back surface (surface opposite to the ultrasonic wave

transmitting/receiving surface) of the ultrasonic element **103**, a backing layer **106** is provided so as to absorb the ultrasonic wave.

The ultrasonic element **103** is made of a material having piezoelectric properties, such as a piezoelectric ceramic of barium titanate or the like, for example. On a surface of the ultrasonic element **103**, a signal electrode and a ground electrode made of a conductive material such as metal are formed, these electrodes being connected electrically with conductive portions of the sensor signal substrate **104** and the sensor ground substrate **105**, respectively. The arrangement of these substrates is not particularly limited. For example, as shown in FIG. 1, the sensor signal substrate **104** may be arranged so as to cover the entire back surface of the ultrasonic wave element **103**, and the sensor ground substrate **105** may be arranged so as to cover the entire ultrasonic wave transmitting/receiving surface of the ultrasonic element **103**.

As the sensor signal substrate **104**, an insulating substrate with a conductive layer formed on its surface is used. The insulating substrate is made of a polymeric material, such as, for example, epoxy resin, polyimide, polyethylene terephthalate, polysulphone, polycarbonate, polyester, polystyrene, polyphenylene sulfide, and the like. The conductive layer is made of metal, such as, for example, Ni, Cr, Au, Ag, Al, Cu, Ti, and the like. The thickness of the conductive layer is not particularly limited, and is 30 μm or less, for example. The conductive layer is patterned into a predetermined shape, and is connected electrically with the signal electrode of the ultrasonic element. This connection is made via solder and a conductive adhesive or the like or by mechanical contact, for example.

As the sensor ground substrate **105**, an insulating substrate **105a** with a conductive layer **105b** formed on its surface can be used, as in the case of the sensor signal substrate. In particular, when the sensor ground substrate **105** is provided so as to cover the entire ultrasonic wave transmitting/receiving surface of the ultrasonic element **103**, the thickness of the conductive layer is required to be set so as not to inhibit the transmission and reception of the ultrasonic wave. Such a thickness of the conductive layer is 30 μm or less, for example. Further, a substrate made of a conductive material such as metal also may be used as the sensor ground substrate **105**.

Further, as shown in the example in FIG. 1, when the sensor ground substrate **105** is provided so as to cover the entire ultrasonic wave transmitting/receiving surface of the ultrasonic element **103**, a material having an acoustic matching function may be used for the sensor ground substrate **105**, which allows the sensor ground substrate **105** to function as an acoustic matching plate. In such a case, it is possible to reduce the materials to be laminated between the ultrasonic element and the acoustic lens, or to eliminate the need to provide an acoustic matching plate additionally. As a result, acoustic mismatching caused by an adhesive or the like between the sensor ground substrate and the acoustic matching plate can be suppressed, and the ultrasonic probe can be manufactured easily. The material having an acoustic matching function is made of, for example, a polymeric material such as, for example, epoxy resin, polyimide, polyethylene terephthalate, polysulphone, polycarbonate, polyester, polystyrene, polyphenylene sulfide, and the like and a metal material such as, for example, Ni, Cr, Au, Ag, Al, Cu, Ti, and the like that is formed on a piezoelectric plate with a thickness of 30 μm or less, for example. Alternatively, a material having conductive performance, such as a material made of a conductive plastic or graphite, is also useful.

The conductive layer **105b** (in the case of a conductive substrate, the layer corresponds to this substrate) of the sensor ground **105** is connected electrically with the ground electrode of the ultrasonic element **103**. This connection is made via solder and a conductive adhesive or the like or by mechanical contact, for example, as in the case of the conductive layer of the sensor signal substrate **104**.

Preferably, as shown in FIG. 1, the sensor ground substrate **105** is arranged so as to cover at least a part of the sensor signal substrate **104**. This arrangement allows the conductive layer **105b** of the sensor ground substrate **105** to function as a shielding plate for shielding at least a part of the sensor signal substrate **104**, thereby increasing durability to withstand electromagnetic waves. This arrangement can be realized by, for example, drawing the sensor signal substrate **104** and the sensor ground substrate **105** from the ultrasonic element **103** in the same direction (to the left side of the ultrasonic element in the example shown in FIG. 1).

In the example shown in FIG. 1, the ultrasonic element **103** and the conductive portion **105a** of the sensor ground substrate **105** are connected directly. However, a conductive material such as, for example, a graphite plate may be provided between the ultrasonic element **103** and the conductive portion **105a**. The sensor ground substrate **105** is provided over the entire ultrasonic wave transmitting/receiving surface of the ultrasonic element **103**. However, the present invention is not limited thereto, and the sensor ground substrate **105** may be provided only over an end portion of the ultrasonic element **103**. The ultrasonic element **103** and the sensor signal substrate **104** also may be connected directly or via a conductive material.

In the cable portion **101**, a plurality of signal wires **109** are covered with a cable shield **110** and further are protected by a sheath **111**. The cable portion **101** further includes a cable substrate **108** for connecting the signal wires **109** with the sensor signal substrate **104** and the sensor ground substrate **105**.

Each of the signal wires **109** includes a signal line **109a** for transmitting an electric signal from the main body of the ultrasonic diagnostic apparatus (not shown), which performs various ultrasonic signal processing, to the sensor portion or transmitting an electric signal converted from an ultrasonic wave including information on the living body to the main body of the ultrasonic diagnostic apparatus, and a ground line **109b** for supplying the ground potential to the ultrasonic element **103** in the sensor portion. Preferably, the signal wires **109** have a coaxial structure in which central copper wires are surrounded by an inner shielding member such as a metal braided wire. The plurality of signal wires **109** are bundled and protected by the sheath **111**. The sheath **111** can be made of an insulating material such as vinyl chloride, silicon, and the like, for example. Preferably, the cable shield **110** made of, for example, a metal braided wire, a metal foil, or the like is provided between the signal wires **109** and the sheath **111** for the shielding against extraneous electromagnetic waves and the radiation of electromagnetic waves.

The signal wires **109** are connected with the cable substrate **108**. As the cable substrate **108**, an insulating substrate with a conductive layer formed on its surface can be used as in the case of the sensor signal substrate **104**. Further, the cable substrate **108** may be mounted with an electronic circuit. The conductive layer of the cable substrate **108** is patterned into a predetermined shape, which forms a signal pattern and a ground pattern. The signal pattern and the ground pattern of the cable substrate **108** are connected electrically with the signal line and the ground line of the signal wires, respectively.

The signal pattern of the cable substrate **108** further is connected electrically with the conductive layer of the sensor signal substrate **104**. The connection between the cable substrate **108** and the sensor signal substrate **104** can be made, for example, by wire bonding, thermocompression bonding, or via a connector such as a card edge connector or the like.

The ground pattern of the cable substrate **108** further is connected electrically with the conductive layer **105b** of the sensor ground substrate **105**. In the present embodiment, the connection between the ground pattern of the cable substrate **108** and the conductive layer **105b** of the sensor ground substrate **105** is made via a relay ground substrate **112**. As the relay ground substrate **112**, a conductive substrate such as a metal substrate made of, for example, a copper wire, a copper foil film, or the like can be used. The dimensions of the relay ground substrate **112** are not particularly limited. However, in order to reduce the ground resistance further, the relay ground substrate **112** preferably has a large cross sectional area and a short distance between the ground pattern of the cable substrate **108** and the conductive layer **105b** of the sensor ground substrate **105**. In the case where a plurality of the cable substrates **108** are provided, the relay ground substrate **112** connected with each of the cable substrates **108** is connected with the sensor ground substrate **105**.

The relay ground substrate **112** is connected with the conductive layer **105b** of the sensor ground substrate **105**. For this connection, preferably, a drawn end portion (portion to be connected with the relay ground substrate **112**) of the sensor ground substrate **105** is bent, particularly at an angle of 90° or more, and further preferably at an angle of about 180°. This allows the conductive layer **105b** of the sensor ground substrate **105** to be exposed outside, thereby facilitating the connection between the conductive layer **105b** and the relay ground substrate **112**. In order to reduce the ground resistance, preferably, a connection area between the relay ground substrate **112** and the conductive layer **105b** of the sensor ground substrate **105** is as large as possible.

Further, the relay ground substrate **112** is connected with the ground pattern of the cable substrate **108**. Preferably, this connection is made such that the relay ground substrate **112** covers a connecting portion between the sensor signal substrate **104** and the cable substrate **108** as shown in FIG. 1. This arrangement allows the relay ground substrate **112** to function as a shielding plate for shielding the connecting portion between the sensor signal substrate **104** and the cable substrate **108**, thereby increasing durability to withstand electromagnetic waves. As a result, there is no need to provide a shielding plate, and therefore it becomes possible to manufacture the ultrasonic probe easily and downsize the housing. In order to reduce the ground resistance, preferably, a connection area between the relay ground substrate **112** and the ground pattern of the cable substrate **108** is as large as possible.

The connector portion **102** includes a connector **115** for connecting with the main body and pins **116**, each being connected with the signal line **109a** or the ground line **109b**. These components are accommodated in a connector housing **113**. The connector housing **113** can be made of, for example, metal, resin, or the like, and is provided with a conductive layer **114** made of metal or the like on its inner wall surface. The cable shield **110** is connected with a metal portion on an outer periphery of the connector for connecting with the main body, the metal portion being insulated from the pins, or with the conductive layer **114** on the inner surface of the connector housing **113**, and is to be connected with a frame ground or a signal ground of the main body of the ultrasonic diagnostic

apparatus when the ultrasonic probe is connected with the main body of the ultrasonic diagnostic apparatus.

Next, a description will be given of the effects achieved by the ultrasonic probe thus configured.

In the above-described ultrasonic probe, the conductive layer **105b** of the sensor ground substrate **105** and the ground pattern of the cable substrate **108** are connected via the relay ground substrate **112** as described above. Therefore, unlike the case where the conductive layer **105b** and the ground pattern are connected via a connector, it is possible to avoid an increase in resistance due to limitations on the number of connector poles, resulting in a reduction in ground resistance between the sensor ground substrate **105** and the cable substrate **108**. Consequently, the reduction in ground resistance suppresses a change in ground potential due to a noise current induced by extraneous electromagnetic waves. As a result, an adverse effect on a reception signal due to the change in ground potential is reduced, and image noise can be prevented from being caused, resulting in an ultrasonic image with high quality.

The connection between the cable portion **101** and the sensor portion **100** is made at at least two points, i.e., the connecting portion between the cable substrate **108** and the sensor signal substrate **104** and a connecting portion between the cable substrate **108** and the sensor ground substrate **105**. Therefore, the connection strength between the cable portion **101** and the sensor portion **100** is increased. In particular, the use of the relay ground substrate **112** achieves the following effect. That is, even when a tensile stress is applied between the cable substrate **108** and the sensor signal substrate **104**, the tension of the relay ground substrate **112** prevents a break in the ultrasonic probe due to the sensor signal substrate **104** and the cable substrate **108** becoming detached from each other, or the like.

Second Embodiment

The first embodiment has been described by taking as an example the case where the conductive layer of the sensor ground substrate and the ground pattern of the cable substrate are connected via the relay ground substrate. However, in the present embodiment, the conductive layer and the ground pattern may be connected directly with no relay ground substrate provided therebetween. Such an embodiment will be described below.

FIG. 2 is a schematic cross-sectional view showing an example of an ultrasonic probe according to a second embodiment of the present invention. This ultrasonic probe includes a sensor portion **100**, a cable portion **101**, and a connector portion **102** as in the first embodiment.

The sensor portion **100** includes an ultrasonic element **103** and a sensor signal substrate **104** and a sensor ground substrate **105** connected with the ultrasonic element **103**. In the example shown in FIG. 2, the sensor signal substrate **104** is arranged so as to cover an entire back surface of the ultrasonic element **103**, and is drawn from both side surface sides of the ultrasonic element **103**. The sensor ground substrate **105** is arranged so as to cover an entire ultrasonic wave transmitting/receiving surface of the ultrasonic element **103**, and is drawn from both the side surface sides of the ultrasonic element **103**. Thus, the sensor ground substrate **105** can be arranged so as to cover the ultrasonic wave transmitting/receiving surface and both side surfaces of the ultrasonic element **103**. This arrangement allows a conductive layer **105b** of the sensor ground substrate **105** to function as a shielding plate for shielding the ultrasonic element **103**, thereby increasing durability to withstand electromagnetic waves.

The material, the structure, and the like of each of the components of the sensor portion **100** are substantially the same as those in the first embodiment. In particular, in the example shown in the present embodiment, the sensor ground substrate **105** is drawn from both the side surfaces of the ultrasonic element **103** so as to cover the entire ultrasonic wave transmitting/receiving surface reliably. Thus, a significant effect can be achieved when a material having an acoustic matching function is used for the sensor ground substrate **105**.

The cable portion **101** includes a plurality of signal wires **109**, each including a signal line **109a** and a ground line **109b**, a sheath **111**, and cable substrates **108**, each including a signal pattern and a ground pattern, as in the first embodiment. In the example shown in FIG. 2, the two cable substrates **108** are used, each being connected with drawn portions of the sensor signal substrate **104** and the sensor ground substrate **105**, respectively, drawn on both the side surface sides of the ultrasonic element **103**.

The signal pattern of the cable substrate **108** is connected electrically with the signal line **109a** of the signal wire and the sensor signal substrate **104** in the sensor portion. These connections are made in the same manner as in the first embodiment.

The ground pattern of the cable substrate **108** is connected electrically with the ground line **109b** of the signal wire and the sensor ground substrate **105**. In the present embodiment, the ground pattern of the cable substrate **108** and the conductive layer **105b** of the sensor ground substrate **105** are connected directly via solder, for example. Preferably, as shown in FIG. 2, the cable substrate **108** and the sensor ground substrate **105** are connected so that the sensor ground substrate **105** covers at least a part of a connecting portion between the sensor signal substrate **104** and the cable substrate **108**. This arrangement allows the sensor ground substrate **105** to function as a shielding plate for shielding the connecting portion between the sensor signal substrate **104** and the cable substrate **108**, thereby increasing durability to withstand electromagnetic waves. In order to reduce the ground resistance further, preferably, a connection area between the sensor ground substrate **105** and the ground pattern of the cable substrate **108** is as large as possible.

The material, the structure, and the like of each of the components of the cable portion **101** are substantially the same as those in the first embodiment.

Also, the structure of the connector portion **102** is substantially the same as that in the first embodiment, and a description thereof will be omitted.

The above description has been given taking as an example the case where the sensor signal substrate and the sensor ground substrate are drawn from both the side surface sides of the ultrasonic element. However, as in the first embodiment, these substrates may be drawn only from one side surface side of the ultrasonic element.

However, preferably, these substrates are drawn from both the side surface sides of the ultrasonic element, since, as described above, such a structure allows the sensor ground substrate to cover both the side surfaces of the ultrasonic element, thereby increasing durability to withstand electromagnetic waves. In addition, when the substrates are drawn from both the side surface sides, the sensor ground substrate **105** can cover the connecting portion between the cable substrate **108** and the sensor signal substrate **104** entirely as shown in FIG. 2 so as to shield this connecting portion, thereby increasing durability to withstand electromagnetic waves. As a result, there is no need to provide a shielding

plate, and therefore it becomes possible to manufacture the ultrasonic probe easily and downsize the housing.

In the above-described ultrasonic probe, the sensor ground substrate **105** and the cable substrate **108** are connected directly. Therefore, as in the first embodiment, unlike the case where these substrates are connected via a connector, it is possible to avoid an increase in resistance due to limitations on the number of connector poles, resulting in a reduction in ground resistance between the sensor ground substrate and the cable substrate. Consequently, it is possible to suppress a change in ground potential due to a noise current induced by extraneous electromagnetic waves, resulting in an ultrasonic image with high quality.

In particular, in the present embodiment, since the sensor ground substrate **105** and the cable substrate **108** are connected directly, fewer connecting points via solder or the like are required than in the first embodiment using the relay ground substrate. As a result, it is possible to provide good workability for the manufacture and to suppress thermal damage to the cable portion and the sensor portion due to solder or the like.

Further, the connection between the cable portion and the sensor portion is made at at least two points, i.e., the connecting portion between the cable substrate and the sensor signal substrate and a connecting portion between the cable substrate and the sensor ground substrate. Therefore, the connection strength between the cable portion and the sensor portion is increased.

Third Embodiment

As described in the first and second embodiments, a sensor ground substrate can function as a shield.

In order to increase the operability by reducing the size and weight of an ultrasonic probe, a housing for accommodating a sensor portion is required to be downsized. However, when a shielding plate is provided additionally, the housing needs to be provided with enough space therein in view of the shape and thickness of the shielding plate, which makes it difficult to realize a reduction in size and weight. Further, when a cable connector portion is surrounded by a shielding plate, it is impossible to load the portion with a sufficient sealing material, and a structure therein may not be fixed sufficiently. Further, it is impossible to cover an ultrasonic wave transmitting/receiving surface of an ultrasonic element with a shielding plate, and thus it is difficult to prevent the intrusion of electromagnetic waves into the ultrasonic element.

However, as described above, according to one embodiment of the present invention, the sensor ground substrate can function as a shield, which eliminates the need to provide a shielding plate additionally. Accordingly, the above-mentioned problems also can be solved.

In the present embodiment, a description will be given of a configuration that allows the shielding effect of the sensor ground substrate to be increased particularly.

FIG. 3 is a schematic perspective view showing an example of an ultrasonic probe according to a third embodiment of the present invention. This ultrasonic probe has substantially the same structure as in the second embodiment except for the shape of a sensor ground substrate **105**. Thus, a detailed description will be given of the shape of the sensor ground substrate **105**.

As in the second embodiment, a sensor portion includes an ultrasonic element **103** and a sensor signal substrate **104** and the sensor ground substrate **105** connected with the ultrasonic element **103**. The sensor signal substrate **104** is arranged so as

to cover an entire back surface of the ultrasonic element **103**, and is drawn from both side surface sides of the ultrasonic element **103**.

The sensor ground substrate **105** is arranged so as to cover an entire ultrasonic wave transmitting/receiving surface of the ultrasonic element **103**, and is drawn from both the side surface sides of the ultrasonic element **103** as in the case of the sensor signal substrate **104**. Further, as shown in FIG. 3, the sensor ground substrate **105** also covers side surfaces of the ultrasonic element **103** other than the side surfaces over which the sensor signal substrate **104** is drawn, that is, side surfaces adjacent to the side surfaces over which the sensor signal substrate **104** is drawn. This configuration allows the shielding effect of the sensor ground substrate **105** on the ultrasonic element **103** to be increased further.

As in the second embodiment, a cable portion includes a plurality of signal wires **109**, each including a signal line and a ground line, a sheath **111**, and cable substrates **108**, each including a signal pattern and a ground pattern. As shown in FIG. 3, the two cable substrates **108** are used, each being connected with drawn portions of the sensor signal substrate **104** and the sensor ground substrate **105**, respectively, drawn on both the side surface sides.

The ground pattern of the cable substrate **108** is connected electrically with the ground line of the signal wire **109** and the sensor ground substrate **105**. As shown in FIG. 3, the cable substrate **108** and the sensor ground substrate **105** are connected so that the sensor ground substrate **105** covers a connecting portion between the sensor signal substrate **104** and the cable substrate **108** entirely. Further, as shown in FIG. 3, the sensor ground substrate **105** covers not only surfaces of the cable substrate **108** on which the ground pattern is formed but also surfaces perpendicular thereto (i.e., side surfaces). This configuration allows the shielding effect of the sensor ground substrate **105** on the cable substrate **108** to be increased further.

FIG. 4 is a development of the sensor ground substrate **105**. As shown in FIG. 4, the sensor ground substrate **105** is composed of a bottom surface portion, which is a surface that covers the ultrasonic wave transmitting/receiving surface of the ultrasonic element, and side surface portions, all four sides of the bottom surface portion being connected to the side surface portions. In FIG. 4, shaded areas indicate connecting portions with the cable substrate.

Preferably, a plurality of grooves **105c** are formed in the bottom surface portion of the sensor ground substrate. These grooves are formed so as to divide the ultrasonic element electrically into a plurality of oscillators. The grooves weaken mechanical binding between adjacent oscillators or increase independence of mechanical oscillation of the oscillators, thereby improving crosstalk and widening an angle of beam spread. Generally, the grooves are filled with an insulating material such as epoxy resin, silicon, and the like, and a softer filling material increases the independence of the oscillators more.

The sensor ground substrate **105** is arranged so as to surround a periphery (all four sides) of the ultrasonic element **103**, the sensor signal substrate **104**, and the cable substrate **108** with the side surface portions thereof. At this time, preferably, the side surface portions of the sensor ground substrate **105** that are drawn over the side surfaces (side surfaces of the cable substrate **108**) of the ultrasonic element **103** other than the side surfaces over which the sensor signal substrate **104** is drawn are connected with the cable substrate **108** or the other side surface portions of the sensor ground substrate **105** via solder or the like. This connection allows the sensor ground substrate **105** to retain its shape.

11

As described above, in the present embodiment, the sensor ground substrate 105 is arranged so as to surround the periphery of the ultrasonic element 103, the sensor signal substrate 104, and the cable substrate 108. Therefore, the shielding effect of the sensor ground substrate 105 on the ultrasonic element 103, the sensor signal substrate 104, the cable substrate 108, and the connecting portion therebetween is increased. Therefore, it is possible to increase durability to withstand electromagnetic waves, and to reduce a noise current due to the intrusion of electromagnetic waves or the like. As a result, there is no need to provide a shielding plate additionally, and therefore it becomes possible to manufacture the ultrasonic probe easily and downsize the housing.

INDUSTRIAL APPLICABILITY

The ultrasonic probe according to the present invention allows ground resistance between the sensor ground substrate and the cable substrate to be reduced, so that a change in ground potential due to a noise current induced by extraneous electromagnetic waves is suppressed. As a result, an adverse effect on a reception signal due to the change in ground potential is reduced, and noise can be prevented from being caused on an ultrasonic diagnostic image. Therefore, this ultrasonic probe can be applied effectively to ultrasonic diagnostic apparatuses to be utilized in various medical fields.

The invention claimed is:

1. An ultrasonic probe, comprising: a piezoelectric element for transmitting and receiving an ultrasonic signal; a signal line for transmitting an electric signal to or from the piezoelectric element; and a ground line for supplying a ground potential to the piezoelectric element, the ultrasonic probe further comprising:

a sensor signal substrate and a sensor ground substrate connected electrically with the piezoelectric element; and

a cable substrate that electrically connects the sensor signal substrate and the sensor ground substrate with the signal line and the ground line, respectively,

wherein the sensor ground substrate and the cable substrate are connected directly or via a relay ground substrate as a conductive substrate, and

12

at least a part of the cable substrate is covered with the sensor ground substrate or the relay ground substrate.

2. The ultrasonic probe according to claim 1, wherein at least a part of the sensor signal substrate is covered with the sensor ground substrate or the relay ground substrate.

3. The ultrasonic probe according to claim 1, wherein a connecting portion between the sensor signal substrate and the cable substrate is covered with the sensor ground substrate or the relay ground substrate.

4. The ultrasonic probe according to claim 3, wherein the connecting portion between the sensor signal substrate and the cable substrate is covered with the sensor ground substrate or the relay ground substrate entirely.

5. The ultrasonic probe according to claim 1, wherein at least a part of the piezoelectric element is covered with the sensor ground substrate or the relay ground substrate.

6. The ultrasonic probe according to claim 5, wherein an ultrasonic wave transmitting/receiving surface of the piezoelectric element is covered with the sensor ground substrate or the relay ground substrate.

7. The ultrasonic probe according to claim 6, wherein the ultrasonic wave transmitting/receiving surface and peripheral surfaces of the piezoelectric element are covered with the sensor ground substrate or the relay ground substrate.

8. ultrasonic probe according to claim 6, wherein a plurality of grooves are formed on a part of the sensor ground substrate or the relay ground substrate that covers the ultrasonic wave transmitting/receiving surface of the piezoelectric element, the grooves dividing the piezoelectric element electrically into a plurality of oscillators.

9. The ultrasonic probe according to claim 6, wherein the sensor ground substrate is arranged so as to surround a periphery of the piezoelectric element, the sensor signal substrate, and the cable substrate, and a portion of the sensor ground substrate that is drawn over a surface of the piezoelectric element other than a surface connected with the sensor signal substrate is connected with the cable substrate or a part of the sensor ground substrate.

* * * * *

专利名称(译)	超声波探头		
公开(公告)号	US7648459	公开(公告)日	2010-01-19
申请号	US10/550835	申请日	2004-03-24
[标]申请(专利权)人(译)	武田JUNICHI 小泽政志		
申请(专利权)人(译)	武田JUNICHI 小泽政志		
当前申请(专利权)人(译)	柯尼卡美能达, INC.		
[标]发明人	TAKEDA JUNICHI OZAWA MASASHI		
发明人	TAKEDA, JUNICHI OZAWA, MASASHI		
IPC分类号	A61B8/00 G01N29/24 G10K9/18		
CPC分类号	G10K9/18 A61B8/4455		
优先权	2003083489 2003-03-25 JP		
其他公开文献	US20060241467A1		
外部链接	Espacenet USPTO		

摘要(译)

根据本发明的超声波探头包括：超声波元件，用于发送和接收超声波信号；用于向超声波元件发送电信号或从超声波元件发送电信号的信号线；以及用于向超声波元件提供地电位的地线。超声波元件与传感器信号基板和传感器接地基板电连接。这些基板分别通过电缆基板与信号线和地线电连接。传感器接地基板和电缆基板直接连接或通过继电器接地基板连接。

