



US009332961B2

(12) **United States Patent**
Ogawa

(10) **Patent No.:** **US 9,332,961 B2**
(45) **Date of Patent:** **May 10, 2016**

(54) **ULTRASOUND ENDOSCOPE**

(75) Inventor: **Tomoaki Ogawa**, Tokyo (JP)

(73) Assignee: **OLYMPUS CORPORATION**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/471,525**

(22) Filed: **May 15, 2012**

(65) **Prior Publication Data**

US 2012/0226165 A1 Sep. 6, 2012

Related U.S. Application Data

(63) Continuation of application No. PCT/JP2011/075929, filed on Nov. 10, 2011.

(30) **Foreign Application Priority Data**

Nov. 15, 2010 (JP) 2010-255277

(51) **Int. Cl.**

A61B 8/00 (2006.01)

A61B 8/12 (2006.01)

(52) **U.S. Cl.**

CPC .. **A61B 8/445** (2013.01); **A61B 8/12** (2013.01)

(58) **Field of Classification Search**

CPC **A61B 8/12**; **A61B 8/445**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,255,669 A 10/1993 Kubota et al.
5,462,522 A 10/1995 Sakurai et al.

5,499,630 A 3/1996 Hiki et al.
7,815,571 B2 * 10/2010 Deckman et al. 600/439
2003/0045768 A1 3/2003 Hirooka et al.
2004/0049111 A1 3/2004 Hirooka et al.
2007/0232922 A1 * 10/2007 Kohno 600/459
2008/0119738 A1 * 5/2008 Imahashi et al. 600/462

FOREIGN PATENT DOCUMENTS

JP 07-143985 6/1995
JP 2001-224595 8/2001
JP 2002-306489 10/2002
JP 2003-164455 6/2003
JP 2008-253647 10/2008

OTHER PUBLICATIONS

European Search dated May 7, 2013 from corresponding European Patent Application No. 11 84 1126.3.

* cited by examiner

Primary Examiner — Amanda Lauritzen Moher

(74) *Attorney, Agent, or Firm* — Scully, Scott, Murphy & Presser, PC

(57) **ABSTRACT**

An ultrasound endoscope includes: a bending portion; a distal end rigid portion which is located on a distal end side with respect to the bending portion; and a connection portion making up the distal end rigid portion, for connecting the ultrasound observation section with the bending portion, wherein the connection portion is inclined with respect to a central axis of the bending portion, an interface between the connection portion and the bending portion is perpendicular to the central axis, and the connection portion has a swept shape which is obtained by making a cross-section of the interface slide in a direction perpendicular to the central axis while keeping the perpendicularity along a straight line intersecting with the central axis.

5 Claims, 7 Drawing Sheets





FIG. 1



FIG.2**FIG.3**

FIG.4




FIG.5




FIG.6







FIG. 7**FIG. 8**

FIG. 9

1

ULTRASOUND ENDOSCOPE

CROSS REFERENCE TO RELATED
APPLICATION

This application is a continuation application of PCT/JP2011/075929 filed on Nov. 10, 2011 and claims benefit of Japanese Application No. 2010-255277 filed in Japan on Nov. 15, 2010, the entire contents of which are incorporated herein by this reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to an ultrasound endoscope including an ultrasound observation section and a connection portion for connecting the ultrasound observation section with a bending portion in a distal end rigid portion, the distal end rigid portion being located on a distal end side with respect to the bending portion in an insertion portion to be inserted into an interior of a body.

2. Description of the Related Art

There is a well-known ultrasound endoscope which repeatedly transmits ultrasound to an area to be inspected in the interior of the body from an ultrasound transmission/reception section, and receives an echo signal of the ultrasound reflected from the area to be inspected with the ultrasound transmission/reception section, thereby enabling observation of an ultrasound image which is a two-dimensional visible image of the area to be inspected.

Japanese Patent Application Laid-Open Publication No. 2002-306489 discloses a structure for improving puncturability, in which a part of a distal end is inclined.

SUMMARY OF THE INVENTION

To achieve the above-described object, an ultrasound endoscope in an aspect of the present invention includes: a bending portion; a distal end rigid portion which is located on a distal end side with respect to the bending portion; an ultrasound observation section making up the distal end rigid portion; and a connection portion making up the distal end rigid portion, for connecting the ultrasound observation section with the bending portion, wherein the connection portion is inclined with respect to a central axis of the bending portion, an interface between the connection portion and the bending portion is perpendicular to the central axis, and the connection portion has a swept shape which is obtained by making a cross-section of the interface slide in a direction perpendicular to the central axis while keeping the perpendicularity along a straight line intersecting with the central axis.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram to schematically show the distal end side of an insertion portion of an ultrasound endoscope of a first embodiment;

FIG. 2 is a schematic diagram focusing on a part of the insertion portion of FIG. 1;

FIG. 3 is a schematic diagram focusing on a part of the insertion portion of FIG. 9;

FIG. 4 is a diagram to schematically show the distal end side of an insertion portion of an ultrasound endoscope of a second embodiment;

FIG. 5 is a diagram to show the distal end side of the insertion portion of the ultrasound endoscope of the present embodiment, along with the distal end side of a conventional

2

insertion portion shown in FIG. 7 in which a distal end rigid portion along with a bending portion has a linear shape;

FIG. 6 is a diagram to schematically show the distal end side of the insertion portion of the present embodiment of FIG. 5, along with the distal end side of a conventional insertion portion shown in FIG. 8, and the distal end side of an insertion portion in which a connection portion does not have a swept shape and an ultrasound observation section is bent;

FIG. 7 is a diagram to show the distal end side of an insertion portion of a conventional ultrasound endoscope in which a distal end rigid portion along with a bending portion has a linear shape;

FIG. 8 is a diagram to schematically show the distal end side of the conventional insertion portion of FIG. 7; and

FIG. 9 is a diagram to schematically show an example of an ultrasound endoscope in which a connection portion of an insertion portion does not have a swept shape.

DETAILED DESCRIPTION OF THE PREFERRED
EMBODIMENTS

Hereinafter, embodiments of the present invention will be described with reference to the drawings. It is noted that drawings are schematically shown and a relationship between a thickness and a width of each member, a ratio of the thicknesses of respective members, and the like may be different from actual ones, and also it is a matter of course that portions having different dimensional relations and ratios from each other between respective drawings may be included.

First Embodiment

FIG. 1 is a diagram to schematically show the distal end side of an insertion portion of an ultrasound endoscope of the present embodiment, and FIG. 2 is a schematic diagram focusing on a part of the insertion portion of FIG. 1.

As shown in FIG. 1, an ultrasound endoscope 10 is provided with a known bending portion 2 on the distal end side in a direction S with respect to an insertion portion 1 which is to be inserted into the interior of the body, for example, a bronchus, and is also provided with a non-bending distal end rigid portion 5 on the distal end side in the direction S with respect to the bending portion 2. It is noted that since the configuration of the ultrasound endoscope 10 in the rearward in the direction S with respect to the bending portion 2 is well known, description thereof will be omitted.

A principal part of the distal end rigid portion 5 is configured to include an ultrasound observation section 3 and a connection portion 4. The connection portion 4 connects the ultrasound observation section 3 with the bending portion 2.

It is noted that although not shown in FIG. 1, the distal end rigid portion 5 may be provided with an observation section and an image pickup section for observing the interior of the body, an illumination section for illuminating the interior of the body, and the like. Further, the distal end rigid portion 5 may be provided with a below-described protrusion opening 4g (see FIG. 5) which is opened thereon and from which a treatment instrument passed through the insertion portion 1 is protruded.

Further, the connection portion 4 is inclined by an angle $\theta 1$ which is less than 90° , with respect to a central axis J of the bending portion 2 which is parallel with the direction S, as shown in FIG. 1. The angle $\theta 1$ herein refers to an angle on the distal end side in the direction S out of the angles formed between the central axis J of the bending portion 2 and the connection portion 4 as shown in FIG. 1.

3

To be specific, the connection portion **4** is positioned along a straight line Q that intersects with the central axis J at an angle $\theta 1$ as shown in FIG. 1. An interface Z between the connection portion **4** and the bending portion **2** is perpendicular to the central axis J, and is configured to have a swept shape which is obtained by making the cross section of the interface Z slide in a direction perpendicular to the central axis J while keeping its perpendicularity along the straight line Q.

To be more specific, as shown in FIG. 2, the connection portion **4** is formed into a shape in which when taking a b2-b2 cross-section in a direction E at whatever position along the straight line Q, the cross-sectional shape corresponds to the shape of a b1-b1 cross-section of the direction E in the interface Z.

In other words, the connection portion **4** is formed into a shape in which the shape of a b3-b3 cross-section of the connection portion **4** in a direction F which is perpendicular to the straight line Q does not correspond to the b1-b1 cross-section in the direction E of the interface Z.

It is noted that in the present embodiment, the ultrasound observation section **3** is also positioned along the straight line Q which intersects with the central axis J at the angle of $\theta 1$, as shown in FIG. 1.

Here, FIG. 9 is a diagram to schematically show an example of an ultrasound endoscope in which a connection portion of an insertion portion does not have a swept shape, and FIG. 3 is a schematic diagram focusing on a part of the insertion portion of FIG. 9.

As shown in FIGS. 3 and 9, in an endoscope **200** in which a connection portion **204** does not have a swept shape, the connection portion **204** is formed into a shape in which the shape of a b1-b1 cross-section of a direction E in the interface Z corresponds to a b3-b3 cross-section of the connection portion **4** in a direction F as shown in FIG. 3, in an insertion portion **201** having a distal end rigid portion **205**, which includes an ultrasound observation section **203** and the connection portion **204**, and a bending portion **202**.

In other words, the connection portion **204** is formed into a shape in which the shape of a b2-b2 cross-section of the connection portion **204** in the direction E does not correspond to the shape of the b1-b1 cross-section of the direction E in the interface Z at whatever position along the straight line Q of the connection portion **204**.

That is, the connection portion **4** in the present embodiment is formed into a shape in which a straight area along the direction S surrounded by a chain line Y in FIG. 3, which is present in the connection portion **204** not having a swept shape shown in FIG. 3, is formed into a shape which is not present in a proximal end of the connection portion **4**.

It is noted that while the entire connection portion **4** may have a shape obtained by making the interface Z slide along the straight line Q so as to be perpendicular to the central axis J, it may also have a shape in which a part thereof is cut off according to purposes. Moreover, configuration may also be such that a portion which is made to slide so as to be perpendicular to the central axis J and a portion which is made to slide at a certain angle other than perpendicularity with respect to the central axis J may coexist.

In this way, since in the present embodiment, the connection portion **4** has a swept shape, the insertability of the insertion portion **1** is excellent. It is noted that the reason why the insertability of the insertion portion **1** is made excellent by the arrangement that the connection portion **4** has a swept shape will be described later.

4

Second Embodiment

FIG. 4 schematically shows the distal end side of an insertion portion of an endoscope showing the present embodiment.

As shown in FIG. 4, in the present embodiment as well, the connection portion **4** has a swept shape as in the first embodiment described above.

As a result of this, as in the first embodiment, the present embodiment has a configuration in which the insertability of the insertion portion **1** is excellent. It is noted that the reason why the insertability of the insertion portion **1** is made excellent by the arrangement that the connection portion **4** has a swept shape will be described later.

Further, the present embodiment is configured such that the ultrasound observation section **3** is bent (inclined) from the distal end of the connection portion **4** with respect to the connection portion **4** in the direction of an axis J' which is parallel with the central axis J of the bending portion **2**.

As a result of this, the present embodiment has a configuration in which the insertability of the insertion portion **1** is improved than in the first embodiment. It is noted that the reason why the insertability of the insertion portion **1** is improved by the arrangement that the ultrasound observation section **3** is bent will be described later.

Third Embodiment

FIG. 5 is a diagram to show the distal end side of an insertion portion of an ultrasound endoscope of the present embodiment, along with the distal end side of a conventional insertion portion shown in FIG. 7 in which a distal end rigid portion as well as a bending portion has a linear shape. FIG. 6 is a diagram to schematically show the distal end side of the insertion portion of the present embodiment of FIG. 5, along with the distal end side of a conventional insertion portion shown in FIG. 8, and the distal end side of an insertion portion in which a connection portion does not have a swept shape and an ultrasound observation section is bent.

As shown in FIG. 6, the ultrasound observation section **3** may also be inclined at an angle $\theta 2$ with respect to the direction of an axis J' which is parallel with the central axis J of the bending portion **2**. As a result of this, the insertability of the insertion portion **1** will be further improved. It is noted that the reason why the insertability of the insertion portion **1** is improved by the arrangement that the ultrasound observation section **3** is bent at the angle $\theta 2$ will be described later as well.

Further, hereinafter, owing to the arrangement that the connection portion **4** is inclined from the central axis J at an inclination angle $\theta 1$ as shown in FIG. 5, although this is a common structure in the first to third embodiments, it becomes possible to bring a central axis H of a protrusion opening **4g** provided in the area of a chain line D closer to being parallel with the central axis J. That is, it is possible to decrease the inclination angle of the central axis H with respect to the central axis J.

As a result of this, since a treatment instrument can be protruded from the protrusion opening **4g** without being extremely bent along the central axis J, the insertability of the treatment instrument is improved. Further, it is also possible to suppress to a minimum the flexion of a known image guide or a light guide at the connection portion **4**, which is inserted into the vicinity of the protrusion opening **4g** in the insertion portion **1**.

The ultrasound observation section **3** has a known convex type and includes an ultrasound transmission/reception section **3s**, which transmits ultrasound C to an area to be

5

inspected in the interior of the body and receives an echo single of the ultrasound C reflected from the area to be inspected, in a housing 3h which includes an acoustic lens 3n, as shown in FIG. 5. What is described so far is the common structure in the first to third embodiments.

Further, in the present embodiment, the acoustic lens 3n is positioned in the housing 3h such that the transmission direction of ultrasound C corresponds to the direction to the central axis J side.

Further, the ultrasound observation section 3 is positioned in a back face 3m side, which is an opposite direction side of a position at which the ultrasound C transmitted from the ultrasound transmission/reception section 3s intersects with the central axis J, that is, the opposite direction side of the transmission direction of ultrasound C, in the housing 3h with respect to the central axis J as shown in FIG. 5. In other words, a part of the ultrasound observation section 3 will not intersect with the central axis J. Moreover, the inclination angle $\theta 1$ of the connection portion 4 described above is set to be an angle at which a part of the ultrasound observation section 3 will not intersect with the central axis J.

Further, in the present embodiment, as described above, the ultrasound observation section 3 is positioned along a straight line W which intersects with a central axis Y, which is parallel with the central axis J, at an angle $\theta 2$ which is less than 90° and is also less than the inclination angle $\theta 1$ of the connection portion 4.

That is, the ultrasound observation section 3 is inclined with respect to the central axis J at an angle $\theta 2$ and having a swept shape. To be more specific, the inclination angle $\theta 2$ of the ultrasound observation section 3 corresponds to the inclination angle of the back face 3m of the housing 3h. Moreover, the inclination angle $\theta 2$ of the ultrasound observation section 3 is set to be an angle at which a part of the ultrasound observation section 3 will not intersect with the central axis J.

Thus, in the ultrasound endoscope 10 of the present embodiment, the connection portion 4 has a swept shape and the ultrasound observation section 3 has a swept shape as well. As a result of this, when supposing that the length of the ultrasound observation section be t1, and the length of the connection portion 4 be t2 as shown in FIG. 6, the length of the distal end rigid portion 5 in the direction S is shorter by an amount of m3 than the length of the distal end rigid portion 105 of the insertion portion 101 in the ultrasound endoscope 100, in which the distal end rigid portion 105 including a conventional ultrasound observation section 103 and a connection portion 104, and a bending portion 102 are provided in a linear fashion along the central axis J as shown in FIGS. 7 and 9.

Further, as shown in FIG. 6, the length of the distal end rigid portion 5 becomes shorter by an amount of m2 than that of the distal end rigid portion 505 in the ultrasound endoscope 500, in which the insertion portion 501 includes a distal end rigid portion 505 having a connection portion 504 which does not have a swept shape and an ultrasound observation section 503 which is bent without having a swept shape at an angle $\theta 2$, which is less than $\theta 1$ and less than 90° , from the distal end of the connection portion 504. It is noted that the connection portion 504 has a similar configuration to that of the connection portion 204 of the ultrasound endoscope 200.

Further, if a passing diameter r3 when the insertion portion 1 is made to proceed in a direction A while deforming a bronchus in the present embodiment is compared with a passing diameter R2 of an ultrasound endoscope 500 in which the connection portion 504 and the ultrasound observation section 503 do not have a swept shape, the result will be $r3 < r2$.

6

That is, the passing diameter will be smaller in the case where not only the connection portion 4 but also the ultrasound observation section 3 has a swept shape and is being bent, as in the present embodiment.

It is noted that the arrangement that the ultrasound observation section 3 is only being bent at an angle $\theta 2$, which is less than $\theta 1$ and is less than 90° , without having a swept shape will contribute to shortening of the distal end rigid portion 5 and reduction of the passing diameter.

That is, the arrangement that the connection portion 4 only has a swept shape will contribute to shortening of the distal end rigid portion 5 and the reduction of the passing diameter. This is also true with the first and second embodiments described above.

Therefore, as shown in the first to third embodiments described above, the arrangement that the connection portion 4 has a swept shape will allow not only the length of the distal end rigid portion 5 to be shortened, but also the passing diameter r3 to be reduced, thus improving the insertability of the insertion portion 1.

Furthermore, the arrangement that the ultrasound observation section 3 is being bent to be parallel with the central axis J, or so as to have an angle $\theta 2$, or has a swept shape will further improve the insertability of the insertion portion 1.

This is because if the diameter of the insertion portion 1 to be inserted into, for example, a bronchus, that is, the passing diameter for the bronchus has become larger, or the length of the distal end rigid portion 5 in the direction S has become longer, when inserting the insertion portion 1 at a branching portion of superior and middle lobes selectively to either side of the branching portion, it is difficult to insert it into both sides or either one side, thus degrading the selectivity, and it is difficult to insert the insertion portion into a deeper part after inserting into either of superior lobe or middle lobe. Namely, that is because the insertability of the insertion portion is degraded.

Therefore, as the result of realizing reduction of the passing diameter of the insertion portion 1 and shortening of the distal end rigid portion 5 in the direction S, the insertability of the insertion portion 1 is improved.

Throughout the disclosure provided in this application, the term "swept shape" refers to a three-dimensional shape. As an example, FIG. 5 shows the swept shape of connection portion 4 as a three-dimensional shape defined by projecting the boundary of the interface Z along the straight line Q intersecting with the central axis J of the bending portion 2 while maintaining the perpendicularity of the interface Z with respect to the central axis J of the bending portion 2.

It is noted that although the ultrasound endoscope 10 has been shown taking an example of the configuration which is inserted into a bronchus, it can be, as a matter of course, applied to an ultrasound endoscope which is to be inserted into other sites.

What is claimed is:

1. An ultrasound endoscope comprising:

a bending portion having a bending portion central axis, wherein the bending portion is configured to be controlled to bend between:

a first arrangement in which the bending portion central axis is parallel with a predetermined direction; and a second arrangement in which the bending portion central axis is not parallel with the predetermined direction;

an ultrasound observation housing comprising an acoustic lens through which an ultrasound signal is transmitted and an echo signal of the ultrasound signal is received; and

7

a connection portion configured to connect the bending portion and the ultrasound observation housing, wherein an interface connects the bending portion and the connection portion, and

wherein in the first arrangement:

the bending portion central axis is perpendicular to the interface;

a plane is perpendicular to the interface and includes the bending portion central axis;

the plane intersects with a periphery of the interface at a first interface point and a second interface point; and
for each cross-section of the connection portion that is perpendicular to the bending portion central axis:

a periphery of the each cross-section of the connection portion intersects the plane at a first connection portion point and a second connection portion point; and

a first line directly connecting the first connection portion point and the first interface point intersects the bending portion central axis, and a second line directly connecting the second connection portion point and the second interface point intersects the bending portion central axis.

2. The ultrasound endoscope according to claim 1, wherein the ultrasound observation housing is inclined with respect to the connection portion from a distal end of the connection portion.

8

3. The ultrasound endoscope according to claim 2, wherein the ultrasound observation housing is positioned in parallel with the bending portion central axis.

4. The ultrasound endoscope according to claim 2,

wherein the ultrasound observation housing is inclined with respect to the bending portion central axis, and

wherein a first inclination angle formed between the bending portion central axis and an a connection portion central axis of the connection portion is larger than a second inclination angle formed between the connection portion central axis and a ultrasound observation housing central axis of the ultrasound observation housing.

5. The ultrasound endoscope according to claim 4,

wherein the ultrasound observation housing comprises a convex front face and a back face opposite to the convex front face,

wherein the acoustic lens is arranged to the convex front face, and the ultrasound signal is transmitted through the acoustic lens in a direction intersecting the bending portion central axis, and

wherein a third inclination angle formed between the back face of the ultrasound observation housing and the bending portion central axis is equal to the second inclination angle.

* * * * *

专利名称(译)	超声内窥镜		
公开(公告)号	US9332961	公开(公告)日	2016-05-10
申请号	US13/471525	申请日	2012-05-15
[标]申请(专利权)人(译)	奥林巴斯医疗株式会社		
申请(专利权)人(译)	奥林巴斯医疗系统股份有限公司.		
当前申请(专利权)人(译)	OLYMPUS CORPORATION		
[标]发明人	OGAWA TOMOAKI		
发明人	OGAWA, TOMOAKI		
IPC分类号	A61B8/00 A61B8/12		
CPC分类号	A61B8/445 A61B8/12		
优先权	2010255277 2010-11-15 JP		
其他公开文献	US20120226165A1		
外部链接	Espacenet USPTO		

摘要(译)

超声波内窥镜包括：弯曲部分；远端刚性部分，其相对于弯曲部分位于远端侧；构成远端刚性部分的连接部分，用于连接超声波观察部分和弯曲部分，其中连接部分相对于弯曲部分的中心轴线倾斜，连接部分和弯曲部分之间的界面连接部分具有扫掠形状，该扫掠形状是通过使界面的横截面在垂直于中心轴线的方向上滑动同时沿着与中心轴线相交的直线保持垂直而获得的。

