

(19)



(11)

EP 1 915 954 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
15.05.2013 Bulletin 2013/20

(51) Int Cl.:
A61B 17/072 ^(2006.01) **A61B 17/11** ^(2006.01)
A61B 17/115 ^(2006.01)

(21) Application number: **08000603.4**

(22) Date of filing: **14.08.2006**

(54) Surgical stapling instruments including a cartridge having multiple staple sizes

Chirurgische Klammernahtinstrumente mit einer Kassette mit Klammern in mehreren Größen

Instrument pour pose d'agrafes chirurgicales incluant une cartouche dotée de plusieurs dimensions d'agrafes

(84) Designated Contracting States:
DE ES FR GB IE IT

(30) Priority: **15.08.2005 US 204060**

(43) Date of publication of application:
30.04.2008 Bulletin 2008/18

(60) Divisional application:
10011046.9 / 2 322 103
10171289.1 / 2 319 423

(62) Document number(s) of the earlier application(s) in
accordance with Art. 76 EPC:
06016963.8 / 1 754 445

(73) Proprietor: **Covidien LP**
Mansfield, MA 02048 (US)

(72) Inventors:

- **Holsten, Henry E.**
Covington, GA 30016 (US)
- **Viola, Frank J.**
Sandy Hook, CT 06482 (US)
- **Emmons, Clifford L.**
Oakville, CT 06779 (US)

(74) Representative: **Alcock, David et al**
D Young & Co LLP
120 Holborn
London EC1N 2DY (GB)

(56) References cited:
EP-A1- 1 479 346 EP-A2- 1 316 290
WO-A-97/34533 WO-A1-03/094747
FR-A- 2 838 952 US-A- 4 767 044

EP 1 915 954 B1

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

BACKGROUND

1. Technical Field

[0001] The present disclosure relates to surgical stapling instruments and, more particularly, to surgical stapling instruments including a cartridge having multiple staple sizes.

2. Background of Related Art

[0002] There are several known types of surgical stapling instruments specifically adapted for use in various procedures such as end-to-end anastomosis, gastrointestinal anastomosis, endoscopic gastrointestinal anastomosis, and transverse anastomosis. Examples of stapling instruments for these various procedures can be found in U.S. Patent Nos. 5,915,616; 6,202,914; 5,865,361; and 5,964,394.

[0003] Each surgical stapling instrument includes an anvil which is approximated relative to a staple cartridge. The staple cartridge typically has one or more laterally spaced rows of staples which, depending on the particular stapling instrument, may be arranged in a linear or non-linear configuration. The anvil includes staple forming depressions which are aligned with and/or in registration with the staple slots of the staples in the cartridge. In use, each of the surgical stapling-instruments involves the gripping of tissue to be fastened, the ejecting of individual staples, the forcing of staples through the gripped tissue and the closing and/or forming of the staples against the staple forming depressions of the anvil

[0004] A common issue in transecting tissue and/or in anastomosis procedures, employing any one of the surgical stapling instruments disclosed above, is the balance between anastomotic strength and the degree of hemostasis achievable. It is known to include different size staples in a surgical stapling apparatus having a constant gap (i.e. a uniform distance) between an anvil and a staple cartridge.

[0005] EP1316290 discloses a staple fastening assembly (1) that forms the distal portion of a surgical stapling instrument. WO 97/34533 discloses a suturing device having an elongated tubular housing and a suturing apparatus at one end. EP1479346 discloses an instrument having an end effector, an elongate channel, and a pivoting anvil. WO 03/094747 discloses a surgical stapler including a cartridge housing a plurality of different-sized staples. US 4,767,044 discloses an apparatus for substantially simultaneously applying a plurality of surgical fasteners to body tissue including means for preventing all of the fasteners from reaching peak formation force at the same time in order to reduce the maximum force required to operate the apparatus.

SUMMARY

[0006] The present disclosure is directed towards surgical stapling instruments configured to effectuate an improved balance between the anastomotic strength and the degree of hemostasis at the tissue interface. In particular, embodiments of the present disclosure include surgical fasteners of different sizes. Further still, the distance between an anvil member and a staple cartridge (i.e. the gap) varies from a centerline of the staple cartridge to an outer edge of the staple cartridge. Combining the different sizes of surgical fasteners with the varying gap between the anvil member and the staple cartridge improves the anastomotic strength and the degree of hemostasis at the tissue interface.

[0007] Accordingly the present invention provides a replaceable loading unit for a surgical stapling apparatus as defined in claim 1.

[0008] According to one aspect of the disclosure, the surgical stapling instrument includes a first structure defining having an anvil member operatively associated therewith, and a second structure defining a staple cartridge operatively associated therewith. The staple cartridge has a tissue contacting surface with a stepped cross-sectional profile. The tissue contacting surface of the staple cartridge also includes a plurality of retention slots formed therein for retaining a surgical fastener. During operation of the surgical stapling instrument, the anvil member and the staple cartridge can be approximated relative to one another.

[0009] The stepped tissue contact surface of the staple cartridge defines a plurality of tissue contacting surfaces each having a different height. In one embodiment, the stepped tissue contacting surface of the cartridge includes an inner tissue contacting surface having a height, an intermediate tissue contacting surface having a height less than the height of the inner tissue contacting surface, and an outer tissue contacting surface having a height less than the height of the intermediate tissue contacting surface.

[0010] The inner, intermediate, and outer tissue contacting surfaces each include at least one row of retention slots formed therein. A plurality of surgical fasteners is disposed, one each, in each retention slot. Each surgical fastener includes a backspan and a pair of descending legs.

[0011] The surgical fastener retained in the retention slots formed in the inner tissue contacting surface have a first leg length, the surgical fasteners retained in the retention slots formed in the intermediate tissue contacting surface have a second leg length, and the surgical fasteners retained in the retention slots formed in the outer tissue contacting surface have a third leg length. In one embodiment, the surgical fasteners retained in the retention slots formed in the inner tissue contacting surface have a leg length of about 23mm, while the surgical fasteners retained in the retention slots formed in the intermediate tissue contacting surface have a leg length

of about 3.5mm, and the surgical fasteners retained in the-retention slots formed in the outer tissue contacting surface have a leg length of about 4.1mm.

[0012] It is envisioned that the surgical stapling instrument can be a circular-type surgical stapling instrument wherein the anvil member and the staple cartridge can be annular. In one embodiment, the plurality of tissue contacting surfaces decreases in height in a radially outward direction. Accordingly, the inner tissue contacting surface is closest to the center and the outer tissue contacting surface is furthest from the center of the annular staple cartridge. Moreover, surgical fasteners having relatively short leg lengths are retained in the retention slots closest to the center of the annular staple cartridge while surgical fasteners having relatively longer leg lengths are retained in the retention slots furthest from the center of the annular staple cartridge.

[0013] It is further envisioned that the surgical stapling instrument can be a linear-type surgical stapling instrument wherein the anvil member and the staple cartridge are linear. In these instruments, the staple cartridge and/or the anvil member may define a knife cut line. Accordingly, the plurality of tissue contacting surfaces decreases in height in a direction orthogonally outward from the knife cut line. In particular, the inner tissue contacting surface is closest to the knife cut line while the outer tissue contacting surface is furthest from the knife cut line. In addition, surgical fasteners having relatively short leg lengths are retained in the retention slots closest to the knife cut line while surgical fasteners having relatively longer leg lengths are retained in the retention slots furthest from the knife cut line.

[0014] It is envisioned that the anvil member can have a tissue contacting surface with a stepped cross-sectional profile including a plurality of tissue contacting surfaces, wherein each tissue contacting surface has a different height. In addition, each one of the plurality of tissue contacting surfaces can include at least one annular and/or linear row of surgical fastener forming depressions formed therein.

[0015] In one embodiment, the anvil member can have a tissue contacting surface which is shaped (i.e. stepped) to complement the stepped tissue contacting surface of the staple cartridge. In another embodiment, the anvil member can have a tissue contacting surface which is stepped while the tissue contacting surface of the staple cartridge is substantially planar. In yet another embodiment, the anvil member can have a tissue contacting surface which is shaped to substantially complement the stepped tissue contacting surface of the staple cartridge (i.e. the depths of the tissue contacting surfaces of the stepped anvil member are not equal to the heights of the individual tissue contacting surfaces of the tissue contacting surface of the staple cartridge). In still another embodiment, the anvil member can have a tissue contacting surface which is stepped to mirror the tissue contacting surface of the staple cartridge (i.e. the depths of individual tissue contacting surfaces of the tissue con-

tacting surface of the anvil member are substantially equal to the depths of the individual tissue contacting surfaces of the staple cartridge).

[0016] In other embodiments of the present disclosure, a surgical stapling instrument includes an operative tool disposed at one end thereof. The operative tool includes an anvil member and a staple cartridge. The staple cartridge maybe included in a disposable surgical stapling apparatus or in a reusable surgical stapling apparatus. Further still, a replaceable loading unit maybe located in either the disposable or the reusable surgical stapling apparatus. In one embodiment, the replaceable loading unit includes a staple cartridge, while an alternate embodiment of the replaceable loading-unit includes a staple cartridge and an anvil member. In particular, the staple cartridge includes a plurality of surgical fasteners disposed in rows of retention slots. The surgical fasteners may have different leg lengths wherein a plurality of surgical fasteners having substantially the same leg length is disposed in a row. A number of fastener ejection members are disposed in the staple cartridge wherein each fastener ejection member includes a plurality of staple pushers for ejecting the surgical fasteners in cooperation with an actuation mechanism.

[0017] The staple cartridge may include an angled tissue contacting surface that peaks at a centerline of the staple cartridge and tapers towards outer walls of the staple cartridge. Alternatively, the tissue contacting surface of the staple cartridge-may have a surface that is parallel with the bottom surface of the staple cartridge or parallel to a plane defined by the backpans of surgical fasteners disposed in a selected row. The parallel surface of the tissue contacting surface has a width dimension that is sufficient to accommodate at least one row of surgical fasteners. The staple cartridge may include a knife channel.

[0018] In cooperation with the presently disclosed staple cartridge, the anvil member may include a planar tissue contacting surface that is substantially parallel to the bottom surface of the staple cartridge or parallel to a plane defined by the backspans of surgical fasteners disposed in a selected row. In the alternative, the tissue contacting surface of the anvil member may be angled in an opposed manner to the angle of the tissue contacting surface of the staple cartridge. Further still, the tissue contacting surface of the anvil member may have a planar-surface that is substantially parallel to the bottom surface of the staple cartridge or parallel to a plane defined by the backspans of surgical fasteners disposed in a selected row and tapered surfaces that define angles opposite to the angles defined by the tissue contacting surface of the staple cartridge. The parallel surfaces of the anvil member have a width dimension that corresponds to a width dimension of the parallel surface of the staple cartridge.

[0019] It is further contemplated that one embodiment of the surgical stapling apparatus includes structures for supplemental sealing of the fastened layers of tissue. In

one embodiment, the surgical stapling apparatus includes a wound closure assembly having a reservoir and a supply line. The reservoir is adapted for storing a quantity of a wound closure material and is fluidly coupled to the staple cartridge via the supply line for delivering amounts of the wound closure material to the plurality of retention slots.

[0020] The presently disclosed surgical stapling instruments, together with attendant advantages, will be more clearly illustrated below by the description of the drawings and the detailed description of the embodiments.

[0021] Other objects and features of the present disclosure will become apparent from consideration of the following description taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0022] Embodiments of the presently disclosed surgical stapling apparatus are described herein with reference to the accompanying drawings, wherein:

FIG. 1 is a perspective view of a surgical stapling instrument constructed in accordance with the present disclosure;

FIG. 2 is a schematic cross-sectional side elevational view of the distal end portion of the surgical stapling instrument of FIG. 1, as taken through 2--2 of FIG. 1; FIG. 3A is an enlarged schematic representation of the indicated area of FIG. 2, illustrating tissue contacting surfaces in accordance with an alternate embodiment of the present disclosure;

FIG. 3B is an enlarged schematic representation of the indicated area of FIG. 2, illustrating tissue contacting surfaces in accordance with an embodiment which is not within the scope of the invention;

FIG. 3C is an enlarged schematic representation of the indicated area of FIG. 2, illustrating tissue contacting surfaces in accordance with still another embodiment of the present disclosure;

FIG. 3D is an enlarged schematic representation of the indicated area of FIG. 2, illustrating tissue contacting surfaces in accordance with a further embodiment of the present disclosure;

FIG. 4 is a perspective view of an alternative surgical stapling instrument constructed in accordance with the present disclosure;

FIG. 5 is a perspective view of yet another surgical stapling instrument constructed in accordance with the present disclosure;

FIG. 6 is a perspective view of still another surgical stapling instrument constructed in accordance with the present disclosure;

FIG. 6A is a perspective view of a portion of an anvil member of FIG. 6;

FIG. 7 is a schematic cross-sectional side elevational view of the distal end portion of the surgical stapling instruments of FIGS. 4-6, as taken through 7--7 of

each of FIGS. 4-6;

FIG. 7A is a schematic cross-sectional side elevational view of an alternate embodiment of the distal portion of the surgical stapling instrument of FIG. 6

FIG. 8 is a perspective view of a staple cartridge according to another embodiment of the present disclosure;

FIG. 9 is a cross-sectional end view of the staple cartridge of FIG. 8 showing a first arrangement of surgical fasteners;

FIG. 10 is an alternate embodiment of the staple cartridge of FIG. 9 illustrating a second embodiment of the surgical fasteners;

FIG. 11 is an alternate embodiment of an anvil member and the staple cartridge of FIG. 10;

FIG. 12 is a further embodiment of the staple cartridge of FIG. 8;

FIG. 13 is another embodiment of the anvil member and the staple cartridge of FIG. 12;

FIG. 14 is another embodiment of the staple cartridge and anvil member of FIG. 8;

FIG. 15 is alternate embodiment of an anvil member with the staple cartridge of FIG. 14;

and

FIG. 16 is a cross-sectional side elevational view of the resulting tissue interface following the firing of surgical stapling instrument of FIGS. 7 and 10-15.

DETAILED DESCRIPTION OF EMBODIMENTS

[0023] Embodiments of the presently disclosed surgical stapling instruments will now be described in detail with reference to the drawing figures wherein like reference numerals identify similar or identical elements. In the drawings and in the description which follows, the term "proximal", as is traditional, will refer to the end of the surgical stapling instrument which is closest to the operator while the term "distal" will refer to the end of the device which is furthest from the operator.

[0024] The present disclosure relates to a staple cartridge and an anvil member for use in a disposable or re-usable surgical stapling apparatus. The presently disclosed staple cartridge and anvil member, as will be discussed in detail hereinbelow, may be used with any of the surgical stapling apparatus shown in FIGS. 1, 4, 5, or 6. In addition, a replaceable loading unit may be located in either the disposable or the reusable surgical stapling apparatus. In one embodiment, the replaceable loading unit includes a staple cartridge, including any of the staple cartridges disclosed herein. Alternatively, the replaceable loading unit includes the staple cartridge and an anvil member, including any of the anvil members disclosed herein. In combination with the disposable or the reusable surgical stapling apparatus, the replaceable loading unit provides improved flexibility of the respective surgical stapling apparatus in that the respective surgical stapling apparatus is readily adaptable for different stapling procedures.

[0025] Referring now in detail to FIGS. 1-2, in which like reference numerals identify similar or identical elements, a surgical stapling instrument, in accordance with a first embodiment of the disclosure, is generally designated as 100.

[0026] As seen in FIG. 1, surgical stapling instrument 100 includes a handle assembly 102 having at least one pivotable actuating handle member 103, and further includes advancing means 105. Extending from handle assembly 102, there is provided a tubular body portion 104 which may be constructed so as to have a carved shape along its length. Tubular body portion 104 terminates in a fastener ejection member assembly 106 having a circular staple cartridge 118 including a tissue contacting surface 121 disposed at a distal end thereof.

[0027] As seen in FIG. 2, tissue contacting surface 121 is stepped including an outer tissue contacting surface 121a, an intermediate tissue contacting surface 121b, and an inner tissue contacting surface 121c. Each tissue contacting surface 121a-121c has a different height from one another as measured from a bottom surface 131 of a staple pusher or fastener ejection member 130. Specifically, tissue contacting surfaces 121a-121c are planar structures that are substantially parallel to one another, but are not co-planar (i.e. stepped) with one another. In addition, each tissue contacting surface 121a-c defines a planar axis that extends through the respective tissue contacting surface 121a-c. A first wall surface interconnects tissue contacting surfaces 121a and -121b, while a second wall surface interconnects tissue contacting surfaces 121b-and 121c. The first and second wall surfaces are planar structures wherein each wall surface defines a planar axis. In one embodiment, the planar axes-of the wall surfaces are orthogonal to the planar axes of tissue contacting surfaces 121a-c.

[0028] Inner tissue contacting surface 121c has the greatest height, outer-tissue contacting surface 121a has the least height, and intermediate tissue contacting surface 121b has a height between the heights of outer and inner tissue contacting surfaces 121a, 121c. While tissue contacting-surfaces 121a-121c are shown as increasing in height from outer tissue contacting surface 121a to inner tissue contacting surface 121c (i.e. radially inward), it is within the scope of the present disclosure that the heights of each tissue contacting surface can vary depending on the particular surgical procedure. For example, tissue contacting surfaces 121a-121c can increase in height in a radially outward direction, the intermediate tissue contacting surface 121b can be the highest or the lowest tissue contacting surface, or at least two of tissue contacting surface 121a-121c can have the same heights

[0029] In one embodiment, each tissue contacting surface 121a-121c includes a respective annular row 119a-119c of retention slots 123 formed therein. Each retention slot 123 of annular rows 119a-119c is configured and dimensioned to retain a staple or surgical fastener 125 therein. Each surgical fastener 125 includes a backspan (not shown) and a pair of depending legs 25.

In one embodiment, each annular row -119a-119c of slots 123 includes a respective surgical fastener 125a-125c having its own characteristic features.

[0030] As seen in FIG. 2, legs 25a of surgical fasteners 125a have a first leg length, legs 25b of surgical fasteners 125b have a second leg length, and legs 25c of surgical fastener 125c have a third leg length. In particular, surgical fasteners 125a-125c increase in height in a radially outward direction. In one embodiment, legs 25c of surgical fasteners 125c have a leg length of about 23mm, legs 25b of surgical fasteners 125b have a leg length of about 3.5mm, and legs 25a of surgical fasteners 125a have a leg length of about 4.1mm. As such, inner tissue contacting surface 121c has the greatest height and retains surgical fasteners 125c having the shortest leg lengths, and outer tissue contacting surface 121a has the least height and retains surgical fasteners 125a having the longest leg lengths. Having tissue contacting surface 121 step progressively downward at intermediate tissue contacting surface 121b and then again at outer tissue contacting surface 121a results in the formation of surgical fasteners 125b and 125c, respectively. It is envisioned and within the scope of the present disclosure that any number of arrangements are possible.

[0031] While a single annular row 119a-119c of retention slots 123 is shown for each tissue contacting surface 121a-121c, it is envisioned and within the scope of the present disclosure that each tissue contacting surface 121a-121c can include multiple annular rows of retention slots.

[0032] As seen in FIG. 2, a fastener ejection assembly 106 of surgical stapling instrument 100 includes fastener ejection member 130 disposed within staple cartridge 118. Fastener ejection member 130 includes a proximal portion 132 having a generally frusto-conical shape and a distal portion defining concentric rings of peripherally spaced staple pushers 134a-c, each one of which is received within a respective staple retention slot 123 and is cooperative with its respective surgical fastener 125a-c disposed in annular rows 119a-c. In one embodiment, it is envisioned that proximal portion 132 of fastener ejection member 130 is configured and dimensioned to be contacted by a distal end of a driver tube 138. Hence, upon advancing fastener ejection member 130 by advancing driver tube 138, staple pushers 134a-c will pass further into retention slots 123 thereby pushing surgical fasteners 125 contained therein axially outward.

[0033] In an alternate embodiment, staple pushers 134a-c of fastener ejection member 130 have different heights for cooperating with different sized surgical fasteners. In particular, staple pushers 134a-c are sized such that when surgical fasteners 125a-c are disposed in their respective annular rows 119a-c, tips of surgical fasteners 125a-c are located substantially in the same plane despite the difference in leg lengths between each row of surgical fasteners.

[0034] Surgical stapling instrument 100 further includes a circular anvil assembly 108 having an anvil head

109 and an anvil shaft 110 extending from a proximal end thereof and adapted to engage a shaft 111 extending distally from staple cartridge 118. Anvil head 109 includes an annular anvil member 112 disposed at a proximal end thereof, wherein anvil member 112 includes at least one, row of fastener forming depressions 114 formed circumferentially thereabout. In one embodiment, surgical stapling instrument 100 includes three laterally spaced rows of fastener forming depressions 114 formed circumferentially thereabout. Each fastener forming depression 114 is in registration with a corresponding retention slot 123.

[0035] While anvil member 112 is shown in FIG. 2 as having a substantially planar tissue contacting surface, it is envisioned and within the scope of the present disclosure for surgical stapling instrument 100 to have a number of alternate configurations. For example, as seen in FIG. 3A, anvil member 112 can have a tissue contacting surface 112a which is shaped (i.e. stepped) to complement stepped tissue contacting surface 121 of staple cartridge 118. As seen in FIG. 3B, in an embodiment not within the scope of the invention, anvil member 112 can have a tissue contacting surface 112b which is stepped while tissue contacting surface 121 of staple cartridge 118 is substantially planar. In addition, for example, as seen in FIG. 3C, anvil member 112 can have one row of staple pockets 114b that extends a greater distance than staple pockets 114a or 114c into anvil member 112 for accommodating surgical fasteners having a longer leg length or, as seen in FIG. 3D, anvil member 112 can have a tissue contacting surface 112d which is stepped to mirror tissue contacting surface 121 of staple cartridge 118 (i.e. the depths of individual tissue contacting surfaces of tissue contacting surface 112d of anvil member 112 are substantially equal to the depths of the individual tissue contacting surfaces 121 a-121 c of staple cartridge 118).

[0036] The sizes of surgical fasteners 125a-125c are selected and intended for use in gastric firings typically required in bariatric procedures. However, it is envisioned and within the scope of the present disclosure that the sizes of surgical fasteners 125a-125c selected can be chosen for performance in different types of tissue, such as, for example, the colon, bowels, lungs, the bronchus, pulmonary vessels, the liver, and the like.

[0037] In operation, surgical stapling instrument 100 is positioned within a tubular organ in the body of the patient and the ends of the organ to be joined are positioned in a gap between staple cartridge 118 and anvil assembly 108. As is conventional, the ends of the organ may be secured around anvil shaft 110 by a purse string suture prior to approximation of anvil assembly 108 to staple cartridge 118. Surgical stapling instrument 100 is then approximated and fired. An example of a surgical stapling apparatus and methods for its use are disclosed in U.S. Patent No. 5,915,616, currently assigned to Tyco Healthcare Group LP.

[0038] Turning now to FIGS. 4 and 7, a surgical stapling

instrument, of the gastro-intestinal anastomosis type for performing surgical anastomotic stapling, in accordance with another embodiment of the disclosure, is generally designated as 200. Surgical stapling instrument 200 includes a first handle 202 having a jaw 230 defining a staple cartridge receiving section extending from a distal end thereof, a staple cartridge 204 receivable in jaw 203, a second handle 206 having a jaw 205 defining an anvil member receiving section extending from a distal end thereof, and an anvil member 208 operatively associated with jaw 205. First and second handles 202, 206 are configured such that staple cartridge 204 is substantially aligned with anvil member 208.

[0039] As seen in FIG. 7, staple cartridge 204 includes a stepped tissue contacting surface 121 including an outer tissue contacting surface 121 a, an intermediate tissue contacting surface 121 b, and an inner tissue contacting surface 121c, each of which has a different height from one another as measured from a bottom surface 231 of staple cartridge 204. Tissue contacting surfaces 121a-121c are planar structures that are substantially parallel to one another, but are not co-planar with one another. For example, tissue contacting surfaces 121a-121c, as shown in FIG. 7, can decrease in height in a direction orthogonally outward from knife track 222. In embodiments that do not include knife track 222, tissue contacting surfaces 121a-c decrease in height in a direction orthogonally outward from a centerline of staple cartridge 204.

[0040] Each tissue contacting surface 121a-121c includes a respective linear row 119a-119c of retention slots 123 formed therein. Each retention slot 123 of linear rows 119a-119c is configured and dimensioned to retain a surgical fastener 125 therein. Each linear row 119a-119c of slots 123 includes a respective surgical fastener 125a-125c having its own characteristic features.

[0041] As seen in FIG. 7, legs 25a of surgical fasteners 125a have a first leg length of about 4.1mm, legs 25b of surgical fasteners 125b have a second leg length of about 3.5mm, and legs 25c of surgical fasteners 125c have a third leg length of about 2.3mm. In particular, surgical fasteners 125a-125c increase in height in an orthogonally outward direction relative towards optional knife track 222. Knife track 222 is disposed along a centerline of staple cartridge 204, 310, or 412 and is adapted for slidably receiving an optional knife (not shown). Having tissue contacting surface 121 step progressively downward at intermediate tissue contacting surface 121b and then again at outer tissue contacting surface 121a results in the formation of surgical fasteners 125b and 125c, respectively. It is envisioned and within the scope of the present disclosure that any number of arrangements are possible.

[0042] In operation, surgical stapling instrument 200 is fired similarly to and in accordance with other known surgical stapling instruments. An example of a surgical stapling apparatus and methods for its use are disclosed in U.S. Patent 6,202,914, currently assigned to Tyco

Healthcare Group LP.

[0043] Referring additionally to FIG. 16, following the firing of surgical stapling instrument 200, the resulting tissue interface is seen in cross-section. Accordingly, surgical fasteners 125a and 125b (i.e. the two rows of surgical fasteners furthest from knife cut line "C") serve to hold tissues "A" and "B" to one another while surgical fasteners 125c (i.e. the row of surgical fasteners closest to knife cut line "C") serve to provide the hemostasis,

[0044] While surgical stapling instrument 200 is a linear-type surgical stapler, it is envisioned and within the scope of the present disclosure, that surgical stapling instrument 200 can include a tissue contacting surface having a cross-sectional profile for at least one of the anvil member and the staple cartridge which is substantially similar to the tissue contacting surfaces of the anvil member and the staple cartridge of surgical stapling instrument 100, as shown in FIGS. 3A-3D.

[0045] Turning now to FIGS. 5 and 7, a surgical stapling instrument, of the laparoscopic type for performing surgical anastomotic stapling, in accordance with another embodiment of the disclosure, is generally designated as 300. Surgical stapling instrument 300 includes a handle 302, an operative tool 306, and an elongated shaft 304 for interconnecting operative tool 306 to handle 302. In general, operative tool 306 is designed to clamp over and then to staple and divide tissue held therein. Accordingly, as seen in FIG. 5, operative tool 306 is a pair of opposed jaws including an anvil member 308 and a staple cartridge 310 pivotally coupled to one another,

[0046] Staple cartridge 310 of surgical stapling instrument 300 includes a stepped tissue contacting surface 121 similar to tissue contacting surface 121 of staple cartridge 204 of surgical stapling instrument 200. Accordingly, reference is made to FIG. 7 and the above detailed discussion of tissue contacting surface 121 of staple cartridge 204 for an illustration and a discussion of tissue contacting surface 121 of staple cartridge 310 of surgical stapling instrument 300.

[0047] In operation, surgical stapling instrument 300 is fired similarly to and in accordance with other known surgical stapling instruments. For a detailed discussion of the approximation and firing of surgical stapling instrument 300, reference is made to commonly assigned U.S. Patent 5,865,361, currently assigned to Tyco Healthcare Group LP.

[0048] Following the firing of surgical stapling instrument 300 the resulting tissue interface, as seen in cross-section, is substantially similar to the resulting tissue interface, as seen in cross-section, following the firing of surgical stapling instruments 100 and 200. Accordingly, as seen in FIG. 16, surgical fasteners 125a and 125b (i.e. the two rows of surgical fasteners furthest from knife cut line "C") serve to hold tissues "A" and "B" to one another while surgical fasteners 125c (i.e. the row of surgical fasteners closest to knife cut line "C") serve to provide the hemostasis.

[0049] While surgical stapling instrument 300 is a lin-

ear-type surgical stapler as compared to surgical stapling instrument 100, it is envisioned and within the scope of the present disclosure, that surgical stapling instrument 300 can include a tissue contacting surface having a cross-sectional profile for at least one of the anvil and the staple cartridge which is substantially similar to the tissue contacting surfaces of the anvil and the staple cartridge of surgical stapling instrument 100, as shown in FIGS. 3A-3D.

[0050] Turning now to FIGS. 6, 6A, 7, and 7A, a surgical stapling instrument, of the transverse anastomosis type for performing surgical anastomotic stapling, in accordance with yet another embodiment of the disclosure, is generally designated as 400. Surgical stapling instrument 400 includes a handle 402, a barrel 404 extending from handle 402, and an arm 406 extending from the distal end of barrel 404. Surgical stapling instrument 400 further includes an anvil member 408 orthogonally affixed to a distal end of arm 406 and a staple cartridge receiver 410 operatively coupled to the distal end of barrel 404 for holding a disposable staple cartridge 412 thereon. Anvil member 408 is illustrated in further detail in FIG. 6A and includes a tissue contacting surface 420 wherein tissue contacting surface 420 has a plurality of pockets 425 that substantially align with retention slots 123 (FIG. 7). Cooperative alignment between pockets 425 and retention slots 123 form completed surgical fasteners 125 upon actuation of the actuation mechanism in surgical stapling instrument 400.

[0051] Staple cartridge 412 of surgical stapling instrument 400 includes a stepped tissue contacting surface 121 similar to tissue contacting surface 121 of staple cartridge 204 of surgical stapling instrument 200. Accordingly, reference is made to FIG. 7 and the above detailed discussion of tissue contacting surface 121 of staple cartridge 204 for an illustration and a discussion of tissue contacting surface 121 of staple cartridge 412 of surgical stapling instrument 400. Further still, staple cartridge 412 may include knife track 222 for slidably receiving a knife (not shown) therein.

[0052] In a further embodiment of the present disclosure, staple cartridge 412' is illustrated in FIG. 7A and discussed in detail hereinafter. Staple cartridge 412' is similar to staple cartridge 412, but only includes three rows 119a-c of retention slots 123 disposed between outer walls of staple cartridge 412'. As in the previously discussed embodiment, each row 119a-c includes a plurality of surgical fasteners wherein surgical fasteners in row 119a have a different leg length from surgical fasteners disposed in row 119b, while surgical fasteners disposed in row 119c have a leg length that is different from at least one of rows 119a or 119b. This embodiment of the staple cartridge does not include a knife track. The arrangement and interrelationship of tissue contacting surfaces 125a-c is similar to that previously disclosed with reference to FIG. 7.

[0053] In operation, surgical stapling instrument 400 is fired similarly to and in accordance with other known sur-

gical stapling instruments. For a detailed discussion of the approximation and firing of surgical stapling instrument 400, reference is made to commonly assigned U.S. Patent 5,964,394, currently assigned to Tyco Healthcare Group LP.

[0054] Following the firing of surgical stapling instrument 400 the resulting tissue interface, as seen in cross-section, is substantially similar to the resulting tissue interface, as seen in cross-section, following the firing of surgical stapling instruments 100-300. Accordingly, as seen in FIG. 16, surgical fasteners 125a and 125b (i.e. the two rows of surgical fasteners furthest from knife cut line "C") serve to hold tissues "A" and "B" to one another while surgical fasteners 125c (i.e. the row of surgical fasteners closest to knife cut line "C") serve to provide the hemostasis.

[0055] While surgical stapling instrument 400 is a linear-type surgical stapler as compared to surgical stapling instrument 100, it is envisioned and within the scope of the present disclosure, that surgical stapling instrument 400 can include a tissue contacting surface having a cross-sectional profile for at least one of the anvil and the staple cartridge which is substantially similar to the tissue contacting surfaces of the anvil and the staple cartridge of surgical stapling instrument 100, as shown in FIGS. 3A-3D.

[0056] While each of the surgical stapling instruments described above and shown herein are configured and adapted to fire surgical fasteners 125, it is envisioned and within the scope of the present disclosure, that tissue contacting surfaces of surgical instruments used in connection with applying two-part fasteners can also have stepped configurations as shown and described herein. A typical two-part surgical fastener applying instrument is shown and described in commonly assigned U.S. Patent 5,573,169, currently assigned to Tyco Healthcare Group LP, the entire contents of which is incorporated herein by reference.

[0057] In one further embodiment of the present disclosure, as illustrated in FIGS. 8-10, surgical stapling apparatus 300 includes an operative tool 506 disposed at one end of elongated shaft 304. Operative tool 506 includes anvil member 308 and a staple cartridge 510. Staple cartridge 510 may be included in a disposable surgical stapling apparatus or in a reusable surgical stapling apparatus. In particular, staple cartridge 510 includes a tissue contacting surface 520 having a plurality of retention slots 523 disposed therein and arranged in rows that are substantially aligned with a longitudinal axis of staple cartridge 510. As seen in FIG. 8, each row of retention slots 523 is longitudinally offset from an adjacent row of retention slots. In particular, an optional knife channel 530 is disposed along the longitudinal axis of staple cartridge 510 that is adapted for slidably receiving a knife (not shown).

[0058] Referring now to FIG. 9, operative tool 506 is shown in cross-section and illustrates the several components included in staple cartridge 510. Anvil member

308 includes a substantially planar tissue contacting surface 320 that is substantially parallel to a bottom surface 512 or parallel to a plane defined by the backspans of surgical fasteners 125a, 125b, or 125c. Staple cartridge 510 includes outer walls 514 having a first height and inner walls 516 having a second height wherein the second height is greater than the first height. Tissue contacting surface 520 is attached to inner walls 516 and to outer walls 514 and defines an angle with respect to a plane that is orthogonal to inner walls 516. Tissue contacting surface 520 defines a generally curved path between outer walls 514 (i.e. generally convex or elliptical as viewed in cross-section). Additionally, a plurality of surgical fasteners 125a-c are disposed in staple cartridge 510 wherein each row of retention pockets 523 includes a number of substantially identical surgical fasteners (i.e. 125a, 125b, or 125c). Similar to previous embodiments, legs 25a-c of surgical fasteners 125a-c have different lengths. In this embodiment, surgical fasteners 25a have a leg length of about 3.8mm, surgical fasteners 25b have a leg length of about 3.5mm, and surgical fasteners 25c have a leg length of about 2.5mm. As seen in FIG. 9, surgical fasteners 125a-c are disposed in staple cartridge 510 such that surgical fastener 125c are proximate to outer walls 514, surgical fasteners 125a are disposed proximate to inner walls 516, and surgical fasteners 125b are disposed therebetween. In cooperation with the surgical fasteners of varying height, staple cartridge 510 includes fastener ejection members 540 that include staple pushers 542, 544, and 546 of differing heights. Staple pusher 542 has the greatest height dimension, staple pusher 546 has the least height dimension, and staple pusher 544 has a height dimension therebetween. In this embodiment, surgical fasteners 125a-c are arranged to cooperate with staple pushers 546, 544, and 542 respectively. Fastener ejection member 540 is adapted for substantially vertical movement when it cooperatively engages with an actuation mechanism (not shown). An example of a suitable actuation mechanism is disclosed in U.S. Patent 5,865,361 as discussed with reference to previously disclosed surgical stapling instrument 300.

[0059] Alternatively, as shown in FIG. 10, surgical fasteners 125a-c are disposed in staple cartridge 510 such that surgical fasteners 125a are proximate to outer walls 514, surgical fasteners 125c are disposed proximate to inner walls 516, and surgical fasteners 125b are disposed therebetween. Contrary to the previous embodiment, surgical fasteners 125a-c are arranged to cooperate with staple pushers 542, 544, and 546 respectively. After a number of layers of body tissue are positioned between tissue contacting surfaces 320 and 520, the actuation mechanism is actuated for sequentially ejecting surgical fasteners 125a-c through retention slots 523 whereby interaction between surgical fasteners 125a-c and anvil member 308 forms completed surgical fasteners for joining the layers of body tissue.

[0060] When tissue contacting surface 320 of anvil member 308 is repositioned proximate to tissue contact-

ing surface 520 of staple cartridge 510', the amount of pressure applied to the layers of tissue disposed therebetween varies along a plane that is transverse to the longitudinal axis of staple cartridge 510'. Since the distance between tissue contacting surfaces 320 and 520 is at a minimum in the region nearest inner walls 516 (i.e. the centerline of staple cartridge 510') a maximum pressure is applied to the layers of tissue disposed in this region. Conversely, the distance between tissue contacting surfaces 320 and 520 is at a maximum in the region near outer walls 514, a minimum pressure is applied to the layers disposed in this region. In addition, the proximal relationship between anvil member 308 and staple cartridge 510' defines a plurality of gaps therebetween. A first gap is defined between tissue contacting surfaces 320 and 520 (i.e. along the centerline of staple cartridge 510'), while a second gap is defined between tissue contacting surfaces 320 and 520 along outer walls 514. As seen in FIG. 10, the first gap is not equal to the second gap. Further still, a number of other gaps may be defined between tissue contacting surfaces 320 and 520 at other points of reference existing between the centerline and outer walls 514 in staple cartridge 510'. Since tissue contacting surface 520 slopes toward outer walls 514 to define a substantially uniform angle, the pressure applied to the layer of tissue disposed between tissue contacting surfaces 320 and 520 uniformly decreases from inner wall 516 to outer wall 514.

[0061] By angling tissue contacting surface 520 downwards from the centerline of staple cartridge 510', reduced compressive forces are applied to the layers of tissue disposed between tissue contacting surfaces 320 and 520 thereby minimizing trauma to the layers of tissue disposed therebetween. Therefore, layers of tissue disposed between tissue contacting surfaces 320 and 520 will have a minimum thickness nearest knife channel 530 (i.e. nearest the centerline of staple cartridge 510') and a maximum thickness nearest outer walls 514. In addition, anvil member 308 and staple cartridge 510' are dimensioned and arranged such that compressive forces applied to the layers of tissue are minimal thereby further reducing trauma to the layers of tissue. This configuration defines a gap between tissue contacting surfaces 320 and 520 that is a maximum along knife channel 530 (i.e. the centerline of staple cartridge 510 or 510') and a minimum along outer walls of staple cartridge 510 (FIG. 9) or 510' (FIG. 10).

[0062] Further still, this configuration is applicable to similar staple cartridges and anvil members as will be discussed in detail hereinafter with respect to FIGS. 11-15. When anvil member 308 is repositioned into proximity with staple cartridge 510' (i.e. in a pre-fire position) to retain layers of body tissue therebetween, the layers of tissue are compressed. The maximum compression occurs along the centerline (i.e. first or minimum gap) and urges fluid stored in the layers of tissue towards the outer edges of the tissue (i.e. away from the centerline of staple cartridge 510'). By reducing the amount of fluid

retained in the layers of tissue proximal to the centerline, the overall thickness of the tissue layers decreases. The decrease in overall tissue thickness is such that a staple having a shorter leg length (i.e. surgical fastener 125c) is capable of fastening both layers of tissue while minimizing trauma to the fastened layers of tissue. The gap increases towards the outer walls of staple cartridge 510' (i.e. the amount of compression decreases) and surgical fasteners having a longer leg length (i.e. surgical fasteners 125a and 125b) are capable of fastening both layers of tissue.

[0063] Leg lengths of surgical fasteners 125c, 125b, and 125a increase in a direction moving from inner walls 516 towards outer walls 514. By providing surgical fasteners having increasing leg lengths along a plane that is orthogonal to inner walls 516, the completed (i.e. formed) surgical fasteners join increasing thicknesses of tissue without unduly traumatizing the joined layers of tissue.

[0064] In a further embodiment as illustrated in FIG. 11, operative tool 506" includes staple cartridge 510' and anvil member 308'. Staple cartridge 510' was previously discussed in detail hereinabove with reference to FIG. 10. Tissue contacting surface 520 may define a more uniform angle (FIG. 11) than in the embodiments of FIGS. 9 and 10 wherein the angle or pitch of tissue contacting surface is substantially constant between inner walls 516 and outer walls 514. Anvil member 308' includes tissue contacting surface 320' having tapered surfaces 322' and 324'. Surfaces 322' and 324' are connected to outer walls of anvil member 308' while extending inwards (i.e. towards the centerline of staple cartridge 510) and downwards (i.e. towards tissue contacting surface 520) thereby defining an angle. It is envisioned that the angle defined by tapered surfaces 322' and 324' will be substantially similar to the angle defined by tissue contacting surface 520, but in an opposed direction forming a generally V-shaped configuration. Thus, compressive forces applied to the layers of tissue will be further reduced thereby further reducing the trauma to layers of tissue disposed between tissue contacting surfaces 520 and 320'. As in the embodiment of FIG. 10, the maximum pressure applied to the layers of tissue will exist in the region near knife channel 530 while pressures applied to the layers of tissue will decrease uniformly towards outer walls 514. Formation and location of surgical fasteners 125a-c is substantially similar to that of the embodiment of FIG. 10 along with the attendant advantages.

[0065] Referring now to FIG. 12, a further embodiment of the present disclosure is shown as part of operative tool 606. Operative tool 606 includes a staple cartridge 610 and anvil member 308. In this embodiment, tissue contacting surface 620 includes surfaces 622 and 624. Surface 622 is bisected along its longitudinal axis by knife channel 630 and substantially parallel to a bottom surface 612 or parallel to a plane defined by the backspans of surgical fasteners 125a, 125b, or 125c. In addition, surface 622 has a width dimension sufficient to accommo-

date at least one row of retention slots 623 on each side of knife channel 630. Surface 624 connects outer edges of surface 622 to outer walls 614 defining an angle on either side of knife channel 630 with respect to a plane that is substantially orthogonal to inner walls 616 (i.e. substantially parallel to surface 622) and has a width dimension sufficient to accommodate at least one row of retention slots on each side of knife channel 630. Staple cartridge 610 includes a plurality of surgical fasteners 125a-c and fastener ejection members 540 that were previously discussed in detail with respect to FIGS. 9 and 10. In particular, staple cartridge 610 includes the arrangement of surgical fasteners 125a-c and fastener ejection members 540 as described with respect to staple cartridge 510' (FIGS. 10 and 11).

[0066] Similarly to operative tool 506, tissue contacting surface 320 is repositioned proximate to tissue contacting surface 620 of staple cartridge 610. In this arrangement, the amount of pressure applied to the layers of tissue disposed therebetween varies along a plane that is transverse to the longitudinal axis of staple cartridge 610. Specifically, the distance between tissue contacting surface 320 and surface 622 is a minimum, a maximum pressure is applied to the layers of tissue disposed in this region. Conversely, the distance between tissue contacting surface 320 and surfaces 624 is at a maximum in the region near outer walls 614, a minimum pressure is applied to the layers disposed in this region. Since surface 624 slopes toward outer walls 614 to define a substantially uniform angle, the pressure applied to the layers of tissue disposed between tissue contacting surface 320 and surfaces 624 uniformly decreases from an outer edge of surface 622 towards outer wall 614.

[0067] By angling surface 624 downwards from the edge of surface 622, reduced compressive forces are applied to the layers of tissue disposed between tissue contacting surface 320 and surfaces 624 thereby minimizing trauma to the layers of tissue disposed therebetween. Layers of tissue disposed between tissue contacting surfaces 320 and 620 will have a minimum thickness nearest knife channel 630 and a maximum thickness nearest outer walls 614. In addition, anvil member 308 and staple cartridge 610 are dimensioned and arranged such that compressive forces applied to the layers of tissue are minimal thereby further reducing trauma to the layers of tissue.

[0068] Leg lengths of surgical fasteners 125c, 125b, and 125a increase in a direction moving from inner walls 616 towards outer walls 614. By providing surgical fasteners having increasing leg lengths along a plane that is orthogonal to inner walls 616, the completed (i.e. formed) surgical fasteners join increasing thicknesses of tissue without unduly traumatizing the joined layers of tissue.

[0069] In a further embodiment, operative tool 606' is illustrated in FIG. 13. Operative tool 606' includes staple cartridge 610, that was described in detail hereinabove with respect to FIG. 12, and anvil member 608. Anvil

member 608 includes a tissue contacting surface 620 formed from surfaces 632 and 636. Surface 636 is substantially parallel to surface 622 and has a width dimension that is substantially similar to the width dimension of surface 622. Surfaces 632 are tapered and connected to outer walls of anvil member 608 and extend inwards (i.e. towards the centerline of staple cartridge 610) and downwards (i.e. towards tissue contacting surface 620) thereby defining an angle. It is envisioned that the angle defined by tapered surfaces 632 will be substantially similar to the angle defined by surfaces 624, but in an opposed direction. Thus, compressive forces applied to the layers of tissue will be further reduced thereby further reducing the trauma to layers of tissue disposed between surfaces 624 and 632. As in the embodiment of FIG. 10, the maximum pressure applied to the layers of tissue will exist in the region along surface 622 while pressures applied to the layers of tissue will decrease uniformly along surfaces 624 towards outer walls 614. Formation and location of surgical fasteners 125a-c is substantially similar to that of the embodiment of FIG. 12 along with the attendant advantages.

[0070] In yet another embodiment, operative tool 706 is illustrated in FIG. 14. Staple cartridge 710 is similar to staple cartridge 610. The differences between staple cartridges 610 and 710 will be discussed hereinafter. As in staple cartridge 610 (FIG. 12), staple cartridge 710 includes tissue contacting surface 720 formed from surfaces 722 and 724. Surface 722 differs from surface 622 in that it has a width dimension sufficient to accommodate at least two rows of surgical fasteners. As in staple cartridge 610, surfaces 724 are attached to outer edges of surface 722 and outer walls 714 to define angles. The interaction between staple cartridge 710 and anvil member 308 for capturing tissue and forming surgical fasteners is substantially similar to the interaction between staple cartridge 610 and anvil member 308 and, for the sake of brevity, will not be repeated herein.

[0071] In a further embodiment, operative tool 706' is shown in FIG. 15 and includes staple cartridge 710, as described with respect to FIG. 14, and anvil member 708. Anvil member 708 includes a tissue contacting surface 720 formed from surfaces 732 and 736. Surface 736 is substantially parallel to surface 722 and has a width dimension that is substantially similar to the width dimension of surface 722. Surfaces 732 are tapered and connected to outer walls of anvil member 708 and extend inwards (i.e. towards the centerline of staple cartridge 710) and downwards (i.e. towards tissue contacting surface 720) thereby defining an angle. It is envisioned that the angle defined by tapered surfaces 732 will be substantially similar to the angle defined by surfaces 724, but in an opposed direction. Thus, compressive forces applied to the layers of tissue will be further reduced thereby further reducing the trauma to layers of tissue disposed between surfaces 724 and 732. As of FIG. 14, the maximum pressure applied to the layers of tissue will exist in the region along surface 722 while pressures ap-

plied to the layers of tissue will decrease uniformly along surfaces 724 towards outer walls 714. Formation and location of surgical fasteners 125a-c is substantially similar to that of the embodiment of FIG. 14 along with the attendant advantages.

[0072] In FIG. 15, an alternate embodiment of operative tool 706 is illustrated. Operative tool 706 includes staple cartridge 710, as discussed in detail hereinabove, and anvil member 708. Anvil member 708 includes a tissue contacting surface 720 formed from surfaces 732 and 736. Surface 736 is substantially parallel to surface 722 and has a width dimension that is substantially similar to a width dimension of surface 722. Surfaces 732 are tapered and connected to outer walls of anvil member 708 and extend inwards (i.e. towards centerline of staple cartridge 710) and downwards (i.e. towards tissue contacting surface 720) thereby defining an angle. It is envisioned that the angle defined by tapered surfaces 732 will be substantially similar to the angle defined by surfaces 724, but in an opposed direction. Thus, compressive forces applied to the layers of tissue will be further reduced, thereby further reducing the trauma to the layers of tissue disposed between surfaces 724 and 732. As in the embodiment of FIG. 14, the maximum pressure applied to the layers of tissue will exist in the region along surface 722 while pressures applied to the layers of tissue will decrease uniformly along surfaces 724 towards outer walls 714. Formation and location of surgical fasteners 125a-c is substantially similar to that of the embodiment of FIG. 14 along with the attendant advantages.

[0073] Turning now to FIG. 16, a cross-section of the resulting tissue interface, following the firing of staple cartridge 510', is shown. As seen in FIG. 16, the tissue interface has a substantially tapered profile. In particular, surgical fasteners 125a and 125b (i.e. the two rows of surgical fasteners furthest from knife cut line "C") serve to hold tissues "A" and "B" to one another while surgical fasteners 125c (i.e. the row of surgical fasteners closest to knife cut line "C") serve to provide the hemostasis. This resulting cross-section is also applicable to the firing of staple cartridges 610 and 710. When staple cartridge 510 is fired, surgical fasteners 125b and 125c (i.e. the two rows of surgical fasteners furthest from knife cut line "C") serve to hold tissues "A" and "B" to one another while surgical fasteners 125a (i.e. the row of surgical fasteners closest to knife cut line "C") serve to provide the hemostasis.

[0074] In a further embodiment of the present disclosure, as shown in FIGS. 8 and 10, operative tool 506' includes a wound closure assembly 50. Wound closure assembly 50 includes at least one storage device or reservoir 52 and at least one supply line 54. Supply line 54 fluidly couples reservoir 52 to staple cartridge 510' for delivering an amount of a wound closure material "W". In particular, supply line 54 delivers wound closure material "W" into knife channel 530 such that when surgical fasteners 125a-c are formed, wound closure material "W" migrates along the layers of tissue adjacent to tissue con-

tacting surface 520 (i.e. the target site). By providing wound closure material "W" in combination with surgical fasteners 125a-c, the bond formed between the layers of tissue has improved strength.

[0075] Compression of reservoir 52 causes wound closure material "W" contained therein to be urged through supply line 54 and dispensed via knife channel 530. Preferably, wound closure material "W" is dispensed during the staple firing procedure so that wound closure material "W" is dispensed along the length of the staple line and/or a knife cut line. Although wound closure assembly is discussed and illustrated with respect to FIG. 10, it is contemplated that wound closure assembly 50 is adaptable for use with other disclosed embodiments of staple cartridge 510' (i.e. 510, 610, or 710). It is further contemplated that an additional reservoir may be included for wound closure materials formed by combining two substances or that reservoir 52 may include a plurality of internal chambers (shown in phantom) for storing quantities of substances to be combined to form wound closure material "W". Further still, wound closure assembly 50 may be included in surgical stapling apparatus 100 (FIG. 1) wherein at least one opening 56 is disposed in a wall of anvil shaft 110 for dispensing wound closure material "W".

[0076] It is envisioned that wound closure material "W" can include one or a combination of adhesives, hemostats, sealants. Surgical biocompatible wound closure materials which can be employed in or applied the surgical instruments, especially surgical staplers, include adhesives whose function is to attach or hold organs, tissues or structures, sealants to prevent fluid leakage, and hemostats to halt or prevent bleeding. Examples of adhesives which can be employed include protein derived, aldehyde-based adhesive materials, for example, the commercially available albumin/glutaraldehyde materials sold under the trade designation BioGlue™ by Cryolife, Inc. and cyanoacrylate-based materials sold under the trade designations Indermil0 and Derma Bond™ by Tyco Healthcare Group, LP and Ethicon Endosurgery, Inc., respectively. Examples of sealants, which can be employed, include fibrin sealants and collagen-based and synthetic polymer-based tissue sealants. Examples of commercially available sealants are synthetic polyethylene-glycol-based, hydrogel-materials sold under the trade designation CoSeal™ by Cohesion Technologies and Baxter International, Inc. Examples of hemostat materials, which can be employed, include fibrin-based, collagen-based, oxidized,-regenerated cellulose-based and gelatin-based topical hemostats. Examples of commercially available hemostat materials are fibrinogen-thrombin combination materials under sold the trade designations CoStasis™ by Tyco Healthcare Group, LP, and Tisseel™ sold by Baxter International, Inc. Hemostats herein include astringents, e.g., aluminum sulfate, and coagulants.

[0077] It is to be understood that the dispensing of wound closure material "W" can be as a fluid spray of

any suitable volume, including a mist, applied temporarily, continuously, or continually. Particulate material, e.g. a fine powder is contemplated to be a fluid within the scope of this disclosure.

[0078] It is provided that a number of different wound closure materials "W" can be dispensed by wound closure assembly 50 or a combination of the number of different wound closure materials "W". The wound closure material dispensed by wound closure assembly 50 can, for example, be an astringent, such as a sulfate of aluminum, which causes small blood vessels to close and helps the blood to coagulate. It is provided that wound closure material "W" can be an astringent provided in the material commercially available under the trade designation No Nix Styptic Pencils from Requa™, Inc.

[0079] In addition, while each of the surgical stapling instruments described above and shown herein include tissue contacting surfaces having a stepped profile, it is envisioned that any of the surgical stapling instruments disclosed herein can have tissue contacting surfaces having any one of a number of profiles including and not limited to angles, conical, tapered, arcuate and the like, as disclosed in commonly assigned U.S. Patent Application Serial No. 10/411,686, filed on May 11, 2003, entitled "Surgical Stapling Apparatus Including an Anvil and Cartridge Each Having Cooperating Mating Surfaces," currently assigned to Tyco Healthcare Group LP.

[0080] It will be understood that various modifications may be made to the embodiments of the presently disclosed surgical stapling instruments. Therefore, the above description should not be construed as limiting, but merely as exemplifications of embodiments. Those skilled in the art will envision other modifications within the scope of the present disclosure.

Claims

1. A replaceable loading unit for a surgical stapling apparatus having an anvil (108) with an anvil tissue contacting surface (112) defining staple forming depressions (114), said replaceable loading unit comprising a cartridge (118) comprising a plurality of surgical fasteners (125) and a number of fastener ejection members disposed in the cartridge wherein each fastener ejection member includes a plurality of staple pushers (134),

characterised in that the cartridge comprises:

- i) a tissue contact surface (121) defining a plurality of tissue contacting surfaces (121a, 121b, 121c) wherein each tissue contacting surface has a different height so that a gap between the anvil and the cartridge varies,
- ii) the tissue contact surface (121) including a plurality of retention slots (123) formed therein which retain surgical fasteners (125), and
- iii) the legs (25) of the surgical fasteners (125)

being of different lengths such that the tissue contacting surface with the greatest height includes a retention slot retaining the surgical fastener with the shortest leg length and the tissue contacting surface with the least height includes a retention slot retaining the surgical fastener with the longest leg length.

2. The replaceable loading unit of claim 1, wherein the cartridge (118) is a circular staple cartridge (118).
3. The replaceable loading unit of claim 1, wherein the cartridge (118) is a linear staple cartridge (118).
4. The replaceable loading unit of claim 1, wherein the retention slots (123) are arranged in at least one circular row.
5. The replaceable loading unit of claim 1, wherein the retention slots (123) are arranged in at least one linear row.
6. The replaceable loading unit of claim 1, wherein the plurality of tissue contacting surfaces (121) comprises a first tissue contacting surface (121c) and a second tissue contacting surface (121b).
7. The replaceable loading unit of claim 6, wherein the staples (125) in the retention slots (123) of the first tissue contacting surface (121c) have a leg length of about 2.3 millimeters and the staples (125) in the retention slots (123) of the second tissue contacting surface (121b) have a leg length of about 3.5 millimeters.
8. The replaceable loading unit of claim 7, further comprising a third tissue contacting surface (121a), the staples (125) in the retention slots (123) of the third tissue contacting surface (121a) have a leg length of about 4.1 millimeters.
9. The replaceable loading unit of claim 1, wherein the surgical stapling apparatus is a gastro-intestinal stapler.
10. The replaceable loading unit of claim 1, wherein the cartridge (118) defines a knife track (222).
11. The replaceable loading unit of claim 10, wherein, the staples (125) of the first tissue contacting surface are disposed adjacent the knife track (222).
12. The replaceable loading unit of claim 1, wherein the surgical stapling apparatus is a laparoscopic stapler.

Patentansprüche

1. Austauschbare Ladeeinheit für eine chirurgische Klammervorrichtung, die einen Amboss (108) mit einer gewebeberührenden Ambossfläche (112), die klammerbildende Vertiefungen (114) definiert, besitzt, wobei die austauschbare Ladeeinheit einen Einsatz (118) umfasst, der mehrere chirurgische Befestigungen (125) und eine Anzahl von Befestigungsauswurfelementen, die in dem Einsatz angeordnet sind, umfasst, wobei jedes Befestigungsauswurfelement mehrere Klammerschieber (134) enthält,
dadurch gekennzeichnet, dass der Einsatz Folgendes umfasst :

- i) eine Gewebekontaktfläche (121), die mehrere Gewebekontaktflächen (121a, 121b, 121c) definiert, wobei jede Gewebekontaktfläche eine unterschiedliche Höhe aufweist, so dass ein Spalt zwischen dem Amboss und dem Einsatz variiert,
- ii) wobei die Gewebekontaktfläche (121) mehrere darin gebildete Aufbewahrungsschlitze (123) enthält, die chirurgische Befestigungen (125) aufbewahren, und
- iii) wobei die Beine (25) der chirurgischen Befestigungen (125) von verschiedener Länge sind, so dass die Gewebekontaktfläche mit der größten Höhe einen Aufbewahrungsschlitz enthält, der die chirurgischen Befestigungen mit den kürzesten Beinen aufbewahrt, und die Gewebekontaktfläche mit der geringsten Höhe einen Aufbewahrungsschlitz enthält, der die chirurgischen Befestigungen mit den längsten Beinen aufbewahrt.

2. Austauschbare Ladeeinheit nach Anspruch 1, wobei der Einsatz (118) ein kreisförmiger Klammereinsatz (118) ist.
3. Austauschbare Ladeeinheit nach Anspruch 1, wobei der Einsatz (118) ein gerader Klammereinsatz (118) ist.
4. Austauschbare Ladeeinheit nach Anspruch 1, wobei die Aufbewahrungsschlitze (123) in mindestens einer kreisförmigen Reihe angeordnet sind.
5. Austauschbare Ladeeinheit nach Anspruch 1, wobei die Aufbewahrungsschlitze (123) in mindestens einer geraden Reihe angeordnet sind.
6. Austauschbare Ladeeinheit nach Anspruch 1, wobei die mehreren Gewebekontaktflächen (121) eine erste Gewebekontaktfläche (121c) und eine zweite Gewebekontaktfläche (121b) umfassen.

7. Austauschbare Ladeeinheit nach Anspruch 6, wobei die Klammern (125) in den Aufbewahrungsschlitzen (123) der ersten Gewebekontaktfläche (121c) eine Beinlänge von ungefähr 2,3 mm besitzen und die Klammern (125) in den Aufbewahrungsschlitzen (123) der zweiten Gewebekontaktfläche (121b) eine Beinlänge von ungefähr 3,5 mm besitzen.
8. Austauschbare Ladeeinheit nach Anspruch 7, die ferner eine dritte Gewebekontaktfläche (121a) umfasst, wobei die Klammern (125) in den Aufbewahrungsschlitzen (123) der dritten Gewebekontaktfläche (121a) eine Beinlänge von ungefähr 4,1 mm besitzen.
9. Austauschbare Ladeeinheit nach Anspruch 1, wobei die chirurgische Klammervorrichtung eine Magen-Darm-Klammervorrichtung ist.
10. Austauschbare Ladeeinheit nach Anspruch 1, wobei der Einsatz (118) eine Klingenspur (222) definiert.
11. Austauschbare Ladeeinheit nach Anspruch 10, wobei die Klammern (125) der ersten Gewebekontaktfläche an die Klingenspur (222) angrenzend angeordnet sind.
12. Austauschbare Ladeeinheit nach Anspruch 1, wobei die chirurgische Klammervorrichtung eine laparoskopische Klammervorrichtung ist.

Revendications

1. Unité de chargement remplaçable pour un dispositif de pose d'agrafes chirurgicales comprenant une enclume (108) présentant une surface d'enclume de contact de tissu (112) qui définit des dépressions de formation d'agrafes (114), ladite unité de chargement remplaçable comprenant une cartouche (118) contenant une pluralité d'agrafes chirurgicales (125) et un certain nombre d'éléments d'éjection d'agrafe disposés dans la cartouche, dans laquelle chaque élément d'éjection d'agrafe comprend une pluralité de poussoirs d'agrafe (134), **caractérisée en ce que** la cartouche comprend:
- i) une surface de contact de tissu (121) qui définit une pluralité de surfaces de contact de tissu (121a, 121b, 121c), dans laquelle chaque surface de contact de tissu présente une hauteur différente, de telle sorte qu'un espace entre l'enclume et la cartouche varie;
 - ii) la surface de contact de tissu (121) comportant une pluralité de fentes de retenue (123) formées dans celle-ci qui retiennent des agrafes chirurgicales (125); et
 - iii) les branches (25) des agrafes chirurgicales

- (125) présentant des longueurs différentes, de telle sorte que la surface de contact de tissu qui présente la plus grande hauteur comporte une fente de retenue qui retient l'agrafe chirurgicale qui présente la longueur de branche la plus courte, et la surface de contact de tissu qui présente la plus petite hauteur comporte une fente de retenue qui retient l'agrafe chirurgicale qui présente la longueur de branche la plus longue. 10
2. Unité de chargement remplaçable selon la revendication 1, dans laquelle la cartouche (118) est une cartouche d'agrafes circulaire (118). 15
3. Unité de chargement remplaçable selon la revendication 1, dans laquelle la cartouche (118) est une cartouche d'agrafes linéaire (118). 20
4. Unité de chargement remplaçable selon la revendication 1, dans laquelle les fentes de retenue (123) sont agencées en au moins une rangée circulaire. 25
5. Unité de chargement remplaçable selon la revendication 1, dans laquelle les fentes de retenue (123) sont agencées en au moins une rangée linéaire. 30
6. Unité de chargement remplaçable selon la revendication 1, dans laquelle la pluralité de surfaces de contact de tissu (121) comprend une première surface de contact de tissu (121c) et une deuxième surface de contact de tissu (121b). 35
7. Unité de chargement remplaçable selon la revendication 6, dans laquelle les agrafes (125) dans les fentes de retenue (123) de la première surface de contact de tissu (121c) présentent une longueur de branche d'environ 2,3 millimètres, et les agrafes (125) dans les fentes de retenue (123) de la deuxième surface de contact de tissu (121b) présentent une longueur de branche d'environ 3,5 millimètres. 40
8. Unité de chargement remplaçable selon la revendication 7, comprenant en outre une troisième surface de contact de tissu (121a), les agrafes (125) dans les fentes de retenue (123) de la troisième surface de contact de tissu (121a) présentant une longueur de branche d'environ 4,1 millimètres. 45
9. Unité de chargement remplaçable selon la revendication 1, dans laquelle le dispositif de pose d'agrafes chirurgicales est une agrafeuse gastro-intestinale. 50
10. Unité de chargement remplaçable selon la revendication 1, dans laquelle la cartouche (118) définit une trace de couteau (222). 55
11. Unité de chargement remplaçable selon la revendication 10, dans laquelle les agrafes (125) de la première surface de contact de tissu sont disposées à proximité de la trace de couteau (222).
12. Unité de chargement remplaçable selon la revendication 1, dans laquelle le dispositif de pose d'agrafes chirurgicales est une agrafeuse laparoscopique.




FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 4




FIG. 5




FIG. 6




FIG. 6A




FIG. 7




FIG. 7A




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 5915616 A [0002] [0037]
- US 6202914 A [0002]
- US 5865361 A [0002] [0047] [0058]
- US 5964394 A [0002] [0053]
- EP 1316290 A [0005]
- WO 9734533 A [0005]
- EP 1479346 A [0005]
- WO 03094747 A [0005]
- US 4767044 A [0005]
- US 6202914 B [0042]
- US 5573169 A [0056]
- US 41168603 A [0079]

专利名称(译)	外科缝合器械包括具有多种钉尺寸的钉仓		
公开(公告)号	EP1915954B1	公开(公告)日	2013-05-15
申请号	EP2008000603	申请日	2006-08-14
[标]申请(专利权)人(译)	柯惠有限合伙公司		
申请(专利权)人(译)	泰科医疗集团，LP		
当前申请(专利权)人(译)	COVIDIEN LP		
[标]发明人	HOLSTEN HENRY E VIOLA FRANK J EMMONS CLIFFORD L		
发明人	HOLSTEN, HENRY E. VIOLA, FRANK J. EMMONS, CLIFFORD L.		
IPC分类号	A61B17/072 A61B17/11 A61B17/115		
CPC分类号	A61B17/00491 A61B17/068 A61B17/072 A61B17/07207 A61B17/11 A61B17/1114 A61B17/115 A61B17/1155 A61B17/32053 A61B2017/07235 A61B2017/07242 A61B2017/07264 A61B2017/320052		
代理机构(译)	阿尔科克，DAVID		
优先权	11/204060 2005-08-15 US		
其他公开文献	EP1915954A2 EP1915954A3		
外部链接	Espacenet		

摘要(译)

外科缝合器械包括钉仓和砧构件。钉仓包括设置在多排保持槽中的多个外科紧固件。钉仓可具有环形或线性构造的保持槽。钉仓的组织接触表面可以是锥形的或阶梯状的。砧座构件具有组织接触表面，该组织接触表面包括多个口袋，这些口袋布置成与保持槽基本对齐。另外，砧座构件的组织接触表面可以与钉仓的组织接触表面互补。

