



(11) EP 2 335 607 A1

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:
22.06.2011 Bulletin 2011/25

(51) Int Cl.:
A61B 17/11 (2006.01)

(21) Application number: 11161084.6

(22) Date of filing: 14.02.2007

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI
SK TR**
Designated Extension States:
AL BA HR MK RS

(30) Priority: 07.03.2006 IT MI20060410

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:
07703459.3 / 1 991 135

(71) Applicant: **ETHICON ENDO-SURGERY, INC.**
Cincinnati, OH 45242-2839 (US)

(72) Inventors:
• **Bilotti, Federico**
I-04011, Aprilia, Latina (IT)

- **Pastorelli, Alessandro**
I-00136, Roma (IT)
- **Tacchino, Roberto**
I-00144, Roma (IT)
- **D'Arcangelo, Michele**
I-00142, Roma (IT)
- **Thompson, Brian James**
Cincinnati, OH 45226 (US)

(74) Representative: **Leihkauf, Steffen Falk et al
Jacobacci & Partners S.p.A.
Via Senato 8
20121 Milano (IT)**

Remarks:

This application was filed on 05-04-2011 as a divisional application to the application mentioned under INID code 62.

(54) **Anastomotic device**

(57) The present invention relates to an anastomotic device (10) comprising a first ring (20) having a first contact surface (21) and a second ring (30) having a second contact surface (31). The contact surfaces (21, 31) have an undulated shape and coupling means (40) are provided that comprise at least one pin (43) that projects from the contact surface (31) of the second ring (30) in

the axial direction and at least one seat (42) formed on the first ring (20) and suitable to accommodate the pin (43) and the seats (42) act as holes (52) for the passage of guide wires and further holes (53) for the passage of the guide wires run through the inside of the pins (43) such that the rings (20, 30) can be approached to each other by sliding along the guide wires.




FIG.1

Description

[0001] The object of the present invention is an anastomotic device to carry out anastomoses, particularly to carry out anastomoses of the digestive tube or blood vessels.

[0002] According to further aspects, an implant apparatus suitable to implant the anastomotic device and an operation kit comprising the anastomotic device and the implant apparatus are also objects of this invention.

[0003] A known example of an anastomotic device comprising two metallic rings suitable to be approached to each other in the axial direction is disclosed in US 4.233.981. The two rings comprise tips suitable to hold in the desired position the pieces of the conduit walls on which the anastomosis is carried out. The two rings further comprise a screw-nutscrew coupling suitable to fasten both rings to each other, such that the pieces of the conduit walls are clamped therebetween.

[0004] The known devices, such as that described above, are not without drawbacks.

[0005] In fact, they allow obtaining a lumen having a relatively small size as compared with the overall size of the device. Particularly, the operating diameter of the lumen that can be obtained with these known devices has the inner diameter of the rings forming the device as its highest limit.

[0006] This entails the disadvantage of having to operate with relatively large-sized devices in order to carry out the anastomosis operation in a successful manner. The use of small-sized devices would in fact allow creating a potentially insufficient lumen with a consequent risk of stenosis which would make the whole anastomosis operation useless.

[0007] A lumen with an operating inner diameter being limited by the inner diameter of the rings is particularly uncomfortable when the type of operation employed requires the equipment to be withdrawn through the lumen. In this case, in fact, the edge of the lumen just created may be subjected to stress in order to release the equipment. This stress may be traumatic and generate stenosis or other complications during the operation.

[0008] Even if the type of operation does not require any equipment to pass through the lumen, the restraint imposed to the lumen size sensibly affects the effectiveness of the operation, mainly when stenosis or other complications occur.

[0009] Accordingly, the need is felt to have an anastomotic device allowing to overcome, at least partially, said drawbacks.

[0010] The problem at the heart of the present invention is thus to provide an anastomotic device which has such structural and functional characteristics as to meet said requirement.

[0011] This problem is solved by means of an anastomotic device in accordance with claim 1 and by means of a kit in accordance with claim 19. The dependent claims relate to further aspects or embodiments of the

device, apparatus and kit according to the present invention.

[0012] Further characteristics and advantages of the anastomotic device, implant apparatus and kit according to the invention will become apparent from the following description of preferred exemplary embodiments thereof, which are merely illustrative and non-limiting, with reference to the annexed figures, in which:

[0013] Fig. 1 illustrates a perspective view of an embodiment of an anastomotic device in accordance with the present invention;

[0014] Fig. 2 illustrates a perspective view of another embodiment of an anastomotic device in accordance with the present invention;

[0015] Fig. 3.a and 3.b illustrate a ring of an anastomotic device in accordance with the present invention in comparison with a ring of an anastomotic device of a known type;

[0016] Fig. 4 illustrates a ring of an anastomotic device in accordance with the present invention during an implant step;

[0017] Fig. 5 illustrates a view of an anastomotic device in accordance with the present invention being sectioned along a trace similar to that indicated with V-V in Fig. 4;

[0018] Fig. 6 illustrates a view of an anastomotic device in accordance with the present invention being sectioned along a trace similar to that indicated with VI-VI in Fig. 4;

[0019] Fig. 6.a illustrates an enlarged view of the detail indicated with VI.A in Fig. 6;

[0020] Fig. 7 illustrates a perspective view of an apparatus for the implantation of an anastomotic device in accordance with the present invention.

[0021] With reference to said figures, with 10 has been generally designated an anastomotic device in accordance with the present invention. The device 10 comprises a first ring 20 having a first contact surface 21 and a second ring 30 having a second contact surface 31.

[0022] Each of the rings 20 and 30 univocally defines an axis X. The direction of a straight line parallel to the axis X is called the "axial" direction. The direction of a half-line perpendicular to the axis X and originating therefrom is called the "radial" direction. Finally, a circumference centred on the axis X and arranged on plane perpendicular thereto defines the "circumferential" direction.

[0023] In Fig. 1, the rings 20 and 30 are arranged in the configuration of use, such that the respective axes X coincide. The ring 20 and 30 are suitable to be mutually approached to each other in the axial direction, such that the contact surfaces 21 and 31 are approached to each other.

[0024] The contact surfaces 21 and 31 have an undulated shape relative to a planes π perpendicular to the axes X of the rings 20 and 30 (see for example Fig. 5 and 6).

[0025] In other words, while the contact surfaces of the known rings (see for example Fig. 3.b) lay on plane π , the contact surfaces 21 and 31 of the rings 20 and 30 according to the invention deviate from the plane π to lay

on a curved surface (see for example Fig. 3.a).

[0026] This characteristic implies a large number of advantages for an anastomotic device 10 according to the invention as compared with an anastomotic device of a known type having the same size.

[0027] By "same size" is meant herein and below that the rings involved in the comparison (such as those in Fig. 3.a and 3.b) have the same projection in the axial direction (for example, that in Fig. 4).

[0028] As the contact surfaces 21 and 31 diverge from the plane development of the known surfaces, their respective inner edges 22 and 32 are defined by three-dimensional loops which have a greater length (or development) than the plane curve 32' (see Fig. 4) which represents the projection thereof in the axial direction.

[0029] On the other hand, as the known contact surfaces have a plane development, their respective inner edges are defined by bidimensional loops which have a length (or a development) exactly equal to the plane curve which represents the projection thereof in the axial direction.

[0030] The end size of the lumen 80 obtained in the anastomosis directly derive from the length of the inner edges of the contact surfaces. Carrying out the discussion with an effective simplification, the final anastomosis lumen 80 can be considered as having a round shape. The circumference of this round-shaped artificial lumen would have a length equal to the inner edges of the contact surfaces of plane anastomotic rings having a greater size.

[0031] In view of the above, it appears that the anastomotic device 10 according to the invention allows obtaining final lumens having a greater size than those obtained with a known device having the same size.

[0032] Furthermore, the anastomotic device 10 according to the invention allows obtaining final lumens having a greater elasticity than those obtained with a known device.

[0033] With reference to Fig. 3, and with the other conditions being equal, the three-dimensional loop defining the inner edge 32 of the undulated contact surface 31 has a greater length than the length of the plane curve (ellipse) defining the inner edge of the known contact surface.

[0034] The anastomotic device 10 according to the invention, when properly implanted, is capable of holding the rings 20 and 30 close to each other, and thus holding the pieces of the walls 81 of the conduits involved in the anastomosis operation close to each other. The device 10 holds the rings 20 and 30 and the pieces of the walls 81 close to each other due to the clamping force it can ensure.

[0035] Furthermore, the anastomotic device 10 holds the pieces of the walls 81 in the proper mutual position substantially due to the frictional force generated between the contact surfaces 21 and 31 and the walls 81 of the conduits.

[0036] The fact that the contact surfaces 21 and 31 are

not plane determines an increase in their contact area with the conduit walls 81. Accordingly, the total force holding the pieces of the conduit walls 81 in position, and which thus ensures the proper course of the anastomosis operation, is considerably increased.

[0037] With reference to Fig. 3, the undulated contact surface 31 determines a contact area with the conduit walls that is greater than the contact area determined by the known plane contact surface.

[0038] In accordance with an embodiment of the invention, the effect of the frictional force is further facilitated by the provision of knurlings 33 (see for example Fig. 1), pyramidal or conical relieves, or other surface finishing suitable to increase the sliding friction.

[0039] In accordance with an embodiment of the invention, the anastomotic device 10 comprises coupling means 40 that are suitable to generate and maintain a clamping force in the axial direction between the first ring 20 and the second ring 30 when they have been implanted.

[0040] The coupling means 40 are preferably of a snap-type such as illustrated in the annexed figures. The snap coupling means are simply actuated by approaching the rings 20 and 30 to each other and pressing them against each other in the axial direction with the force required to overcome the elastic resistance of the snaps and press the tissues comprised between the rings 20 and 30.

[0041] This characteristic of the snap coupling means is **particularly convenient, since it allows for easy** operation also when one of the two rings (typically the one being in the distal position) cannot be directly accessed by the operator.

[0042] Due to this advantage, the anastomotic device 10 according to the invention, provided with snap coupling means, is **particularly suitable** when the anastomosis operation is carried out following the endoluminal or laparoscopic route, instead of traditional open surgery.

[0043] With reference to the annexed figures, the coupling means 40 comprise two pins 43 projecting from the second ring 30 in the axial direction towards the contact surface 31 facing direction.

[0044] The pins 43 can be made as one piece with the ring 30 or, preferably, they can be assembled thereto.

[0045] For example, the pins 43 can be threaded within suitable seats 34 that are formed on the ring 30.

[0046] Again, the coupling means 40 comprise two seats 42 that are formed on the first ring 20 with axial development. The seats 42 are suitable to house the pins 43 and are provided with elastic tabs 45. The elastic tabs 45 are, in turn, suitable to sequentially engage the teeth 44 and thus run in one way only along the operating coupling tracts 46.

[0047] In view of the description, it will be apparent to those skilled in the art that, after the two rings 20 and 30

have been approached to each other, the pins 43 have been fitted within the seats 42 and the desired clamping force has been applied in the axial direction, the elastic tabs 45 slide along the operating coupling tracts 46 and engage the teeth 44. As the elastic tabs 45 cannot slide in the opposite direction, they prevent the rings from moving away again in the axial direction.

[0048] The embodiment illustrated in the annexed figures comprise two pins 43 and two respective seats 42. Similarly, a different number of pins and seats can be arranged in order to meet particular requirements.

[0049] In the embodiments represented in the annexed figures, the provision of two pins 43, which are stably housed in the seats 42, prevents any possible relative movement between the two rings 20 and 30 in the circumferential direction.

[0050] In other possible embodiments, in which only one pin 43 is provided, the relative movement between the two rings 20 and 30 in the circumferential direction must be otherwise prevented, such as by means of a pin section other than round.

[0051] With particular reference to those embodiments that are intended for endoluminal or laparoscopic use, the anastomotic device 10 comprises holes 52 and 53 suitable for the guide wires to pass therethrough, which are required to carry out the operation. The holes 52 and 53 are formed on both rings 20 and 30, such as to allow the same to be properly approached to each other simply by sliding along the guide wires.

[0052] In the example of the annexed figures, as regards the first ring 20, the seats 42 act as the holes 52 for the guide wires to pass therethrough.

[0053] As regards the second ring 30, the seats 34 of the pins 43 act as the holes 53 for the guide wires to pass therethrough. The holes 53 are then continued within the pins 43.

[0054] The endoluminal or laparoscopic operation method provides, in a manner known per se, that the guide wires allow the two rings 20 and 30 to be properly positioned relative to each other. At the same time, by pulling the guide wires, when desired, a clamping force is provided which acts on the distal ring in the direction of the proximal ring.

[0055] In order to make the clamping effective, an equal and opposite force must be obviously provided, which acts on the proximal ring in the direction of the distal ring. This equal and opposite force is obtained by pushing the proximal ring by means of an implant apparatus 60 according to the invention, which will be described below.

[0056] In accordance with several possible embodiments of the device 10, such as that represented in Fig. 1, the coupling means 40 are formed within the curves defining the inner edges 22 and 32 of the contact surfaces 21 and 31.

[0057] In accordance with several possible embodiments of the anastomotic device 10, such as that in Fig. 6 and 6.a, the surfaces 21 and 31 are mutually inclined.

As may be clearly seen particularly in Fig. 6.a, the mutual inclination of the surfaces is such that a spacing is generated between the contact surfaces 21 and 31 that is variable in the radial direction.

[0058] This development of the contact surfaces 21 and 31 defines a variable development also in the pressure values of the tissues 82 that are comprised between the rings 20 and 30.

[0059] Specifically, the radially innermost region of the surfaces 21 and 31, i.e. the one proximate to the inner edges 22 and 32, gives the highest pressure. In accordance with the device 10 in Fig. 6.a, the pressure decreases in the radial direction towards the outside and reaches a minimum at the outer edges of the surfaces 21 and 31.

[0060] The success or failure of the anastomosis may be determined by the fact of being able to obtain the proper pressure value to be applied by the anastomotic device 10 to the tissues 82.

[0061] In fact, an excessive pressure on the tissues 82 determines a decrease in the blood flow, which leads to the necrosis of these tissues. This event often implies undesired side effects, and consequently, it is preferably avoided. At the same time, an insufficient pressure on the tissues 82 does not allow holding the tissue pieces in an effective manner, and may cause the same to move away from each other. When the tissues move away from each other, the anastomosis experiences the so-called leak effect.

[0062] Setting the proper pressure value upon implantation is made even harder since, practically, the operator imposes a distance between the rings 20 and 30 from which the pressure of the tissues 82 is derived. The pressure value thus depends on the difference between the thickness of the undisturbed tissues 82 and the distance imposed between the rings 20 and 30.

[0063] Due to the possibility of obtaining, in the circumferential direction, a range of pressure values distributed in the radial direction, the user can more easily obtain the proper value.

[0064] Similarly, in order to meet other specific requirements, other profiles can be studied for the radial section of the contact surfaces 21 and 31, such that other developments are obtained for pressure force variation.

[0065] Moreover, the fact that the surfaces 21 and 31 are mutually inclined determines a further increase in the contact region with the conduit walls as compared with the contact region being determined by the plane contact surfaces.

[0066] In accordance with other possible embodiments of the anastomotic device 10, for example that in Fig. 2, a knife 50 is arranged on one of the rings. Advantageously, the knife 50 is arranged at the inner edge of the contact surface.

[0067] In the example from Fig. 2, the knife 50 is arranged on the first ring 20, but nothing prevents it from being arranged on the second ring 30. The knife 50 has such an extension in the axial direction that it can cooperate, when the rings are being approached to each other.

er, with the inner edge 32 of the surface 31. When the two rings 20 and 30 are moved proximate to each other, such as when the device 10 is being implanted, the knife 50 and edge 32 act like an annular shear.

[0068] When the required clamping force is applied, the knife 50 and edge 32 automatically open the desired lumen 80 in the walls 81 of the conduits involved in the anastomosis. Thereby, further surgery is no longer required in order to remove the portion of inner tissue 82 of the desired lumen 80.

[0069] The anastomotic device 10 can be made of any type of material suitable for surgical applications.

[0070] Particularly, both the first ring 20 and the second ring 30 can be made of a non bio-absorbable material, such as a plastic or metallic material. In this case, the anastomotic device 10 is definitively fixed in position in the site where it has been fitted. In this case, the anastomotic device 10 spontaneously detaches and moves away only when it necrotizes the tissue to which it is attached.

[0071] Alternatively, the selection of the material for the whole anastomotic device 10 can be addressed to a bio-absorbable or biofragmentable material, thus providing that the anastomotic device 10 is completely absorbed after a determined period of time.

[0072] Finally, the anastomotic device 10 can be partially made of bio-absorbable or biofragmentable material. Particularly, it is advantageous to provide manufacturing the coupling means 40 of bio-absorbable or biofragmentable material, such that the anastomotic device 10 is allowed to detach from the site in which it has been applied after a determined period of time and move away in a spontaneous manner.

[0073] In the case illustrated in the annexed drawings, the pins 43 and/or the seats 42 and/or the elastic tabs 45 and/or the teeth 44 may be advantageously provided to be made of bio-absorbable or biofragmentable material.

[0074] Due to this characteristic, an anastomosis can be obtained, after the required post-surgery course has elapsed, which is free from any implant of foreign material to the tissues 82 in the vicinity of lumen 80.

[0075] Again, the constriction formed by the rings 20 and 30 about the lumen 80 being eliminated, the latter can freely adopt its final definitive size, in view of what has been discussed above. Due to this final size the anastomosis is definitively provided with all the effectiveness desired during the operation planning step.

[0076] As those skilled in the art will appreciate from the above description, the anastomotic device 10 according to the invention can be used in endoluminal operations, laparoscopy operations or operations carried out by means of open surgery techniques.

[0077] Another aspect of the present invention relates to the apparatus 60 for implanting the anastomotic device 10 as described above. As can be clearly seen in Fig. 7, the implant apparatus 60 has a development that is mainly oriented along an axis. This axis is called herein the

axis "X", because upon use it coincides with the axes of the rings 20 and 30 of the device 10.

[0078] The implantation device 60 is suitable to provide the ring of the device 10 that is placed in a proximal position, i.e. the first ring 20, with an even thrust.

[0079] Particularly, the apparatus 60 comprises a thrust surface 61 that is suitable to rest, in the axial direction, on the service surface 23 opposite the support surface 21 of the ring 20. The thrust surface 61 is totally complementary to the service surface 23, such as to be able to adhere to a wide percentage of the same.

[0080] It is also important that the contact points and/or regions of the thrust surface 61 with the service surface 23 are distributed in a balanced manner, both in the circumferential direction and in the radial direction. This allows maintaining the thrust by the implant apparatus 60 on the ring 20 balanced and preventing the generation of moments and/or forces other than the desired axial force.

[0081] In accordance with an embodiment thereof, the apparatus 60 comprises holes 63 for the guide wires that are used for the operation of endoluminal or laparoscopic implantation of the device 100 to be passed therethrough. The holes 63 allow a proper placement of the ring 20 relative to the implant apparatus 60 simply by means of sliding along the guide wires. In this embodiment, the implant apparatus 60 advantageously comprises means 65 for attachment to a laparoscope or endoscope.

[0082] A further aspect of the present invention relates to a kit 70 comprising an anastomotic device 10 and an apparatus 60 for the implantation of the same.

[0083] To the embodiments of the anastomotic device 10 and the apparatus 60 for the implantation of the same as described above, those skilled in the art, aiming at satisfying contingent and specific needs, may carry out a number of modifications, adaptations and replacements of elements with others functionally equivalent, without however departing from the scope of the claims below.

40

Claims

1. An anastomotic device (10) comprising:

45 - a first ring (20) having a first contact surface (21); and
 - a second ring (30) having a second contact surface (31);
 said first and second rings (20, 30) being suitable to be approached to each other in an axial direction (X) such as to move said contact surfaces (21, 31) towards each other;
 50 - coupling means adapted to couple the first and second rings (20, 30) to each other for said first and second contact surfaces (21, 31) to clamp tissue walls intended to be anastomosed, wherein said contact surfaces (21, 31) have an
 55

undulated shape relative to a plane (π) perpendicular to the axis (X) of said rings (20, 30), **characterized in that** the coupling means (40) comprise at least one pin (43) that projects from the contact surface (31) of the second ring (30) in the axial direction and at least one seat (42) formed on the first ring (20) and suitable to accommodate said at least one pin (43) and; the seats (42) act as holes (52) for the passage of guide wires and further holes (53) for the passage of the guide wires run through the inside of the pins (43) such that the rings (20, 30) can be approached to each other by sliding along the guide wires.

2. The anastomotic device (10) according to the preceding claim, wherein the contact surfaces (21, 31) of the rings (20, 30) lay on a curved surface.

3. The anastomotic device (10) according to any preceding claim, wherein the contact surfaces (21, 31) comprise inner edges (22, 32) that are defined by three-dimensional loops having a greater length than the plane curve (32'), which represents the projection thereof in the direction of the axis X.

4. The anastomotic device (10) according to any preceding claim, wherein the contact surfaces (21, 31) comprise knurlings (33) to increase friction.

5. The anastomotic device (10) according to any preceding claim, wherein the coupling means (40) are suitable to generate and maintain a clamping force in the axial direction between the first ring (20) and the second ring (30).

6. The anastomotic device (10) according to the preceding claim, wherein the coupling means (40) are of a snap type.

7. The anastomotic device (10) according to claim 5 or 6, wherein the pin (43) comprises teeth (44) that are distributed along an operating coupling tract (46).

8. The anastomotic device (10) according to the preceding claim, wherein the seat (42) comprises elastic tabs (45) that are suitable to engage the teeth (44) and slide along the operating coupling tract (46) only in one direction.

9. The anastomotic device (10) according to any one of claims 5 to 8, wherein the pins (43) and the respective seats (42) are in a number of two.

10. The anastomotic device (10) according to any preceding claim, wherein the contact surfaces (21, 31) of the two rings (20 and 30) are mutually inclined.

5 11. The anastomotic device (10) according to the preceding claim, wherein the mutual inclination of the contact surfaces (21, 31) is such that a spacing is provided between the contact surfaces (21, 31), which is variable in the radial direction.

10 12. The anastomotic device (10) according to claim 10, wherein, when the first and second rings (20, 30) are coupled to each other, the contact surfaces (21, 31) define a spacing therebetween which increases radially from a minimum axial spacing between inner edges (22, 32) to a maximum axial spacing between outer edges of said contact surfaces (21, 31) in a radial cross-section with respect to the axis (X).

15 13. The anastomotic device (10) according to any preceding claim, wherein on one of the rings (20, 30) there is arranged a knife (50).

20 14. The anastomotic device (10) according to the preceding claim, wherein the knife (50) is arranged at the inner edge (22, 32) of the contact surface (21, 31).

25 15. The anastomotic device (10) according to claim 13 or 15, wherein the knife (50) has an extension in the axial direction such that it can cooperate, when the rings (20, 30) are being approached, with the inner edge (32, 22) of the contact surface (31, 21) of the other ring (30, 20).

30 16. The anastomotic device (10) according to the preceding claim, wherein the knife (50) that is placed on one of the rings (20, 30) and the inner edge (32, 22) of the contact surface (31, 21) of the other ring (30, 20) act as an annular shear.

35 17. The anastomotic device (10) according to any preceding claim, which is at least partially made of a bio-absorbable or biofragmentable material.

40 18. The anastomotic device (10) according to any one of the preceding claims, wherein the coupling means (40) are **at least partially** made of bio-absorbable or biofragmentable material.

45 19. A kit (70) comprising an anastomotic device (10) according to any claim 1 to 18 and an implant apparatus (60) for implanting the anastomosis device (10) and suitable to provide a thrust to one of the first and second rings (20, 30) of the anastomotic device (10).

50 20. The kit (70) according to claim 19, in which the implant apparatus (60) comprises a thrust surface (61) that is complementary to a wavy service surface (23) opposite the support surface (21) of the first ring (20).

55 21. The kit (70) according to claim 19 or 20, in which the

implant apparatus (60) comprises holes (63) for the passage of said guide wires.

22. The kit (70) according to any one of claims 24 to 26, in which the implant apparatus (60) comprises means (65) for attachment of the implant apparatus (60) to a laparoscope or endoscope. 5

10

15

20

25

30

35

40

45

50

55





FIG. 1

FIG. 2






FIG. 3.a

FIG. 3.b




FIG. 4




FIG. 6





FIG. 6.a






FIG. 7



EUROPEAN SEARCH REPORT

Application Number
EP 11 16 1084

DOCUMENTS CONSIDERED TO BE RELEVANT			CLASSIFICATION OF THE APPLICATION (IPC)
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	
Y	US 2003/153932 A1 (SPENCE ET AL.) 14 August 2003 (2003-08-14) * paragraphs [0294], [0308]; figure 2843H *	1-22	INV. A61B17/11
Y	----- US 3 771 526 A (RUDIE) 13 November 1973 (1973-11-13) * abstract; figures * * column 1, line 66 - column 3, line 22 *	1-22	
Y	----- US 4 294 255 A (GEROC) 13 October 1981 (1981-10-13) * abstract; figures * * column 1, line 59 - column 2, line 40 *	6,7,10, 11	
A	----- * abstract; figures *	1-3,5,9	
Y	----- DE 91 07 166 U1 (REDMANN) 26 September 1991 (1991-09-26)	4,13-16	
A	* the whole document *	1,5-7,9, 19	
Y	----- US 2002/082625 A1 (HUXEL SHAWN T [US] ET AL) 27 June 2002 (2002-06-27)	8,17,18	TECHNICAL FIELDS SEARCHED (IPC)
A	* abstract; figures * * paragraphs [0016], [0 20], [0030] *	1,5-7,9, 19	A61B
A,D	----- US 4 233 981 A (SCHOMACHER) 18 November 1980 (1980-11-18) * column 2, lines 59,60 * * column 3, lines 11-19; figures *	1,5,6,9, 17,18	
The present search report has been drawn up for all claims			
1	Place of search The Hague	Date of completion of the search 12 May 2011	Examiner Giménez Burgos, R
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			
T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 11 16 1084

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

12-05-2011

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
US 2003153932	A1	14-08-2003		NONE		
US 3771526	A	13-11-1973		NONE		
US 4294255	A	13-10-1981		NONE		
DE 9107166	U1	26-09-1991		NONE		
US 2002082625	A1	27-06-2002		NONE		
US 4233981	A	18-11-1980	DE	2657255 A1		29-06-1978

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 4233981 A [0003]

专利名称(译)	吻合器		
公开(公告)号	EP2335607A1	公开(公告)日	2011-06-22
申请号	EP2011161084	申请日	2007-02-14
[标]申请(专利权)人(译)	伊西康内外科公司		
申请(专利权)人(译)	爱惜康内镜手术 , INC.		
当前申请(专利权)人(译)	爱惜康内镜手术 , INC.		
[标]发明人	BILOTTI FEDERICO PASTORELLI ALESSANDRO TACCHINO ROBERTO DARCANGELO MICHELE THOMPSON BRIAN JAMES		
发明人	BILOTTI, FEDERICO PASTORELLI, ALESSANDRO TACCHINO, ROBERTO D'ARCANGELO, MICHELE THOMPSON, BRIAN JAMES		
IPC分类号	A61B17/11		
CPC分类号	A61B17/1114 A61B17/0643 A61B17/11		
优先权	102006901392733 2006-03-07 IT		
外部链接	Espacenet		

摘要(译)

吻合装置技术领域本发明涉及一种吻合装置 (10) , 其包括具有第一接触表面 (21) 的第一环 (20) 和具有第二接触表面 (31) 的第二环 (30) 。接触表面 (21,31) 具有波状形状 , 并且设置有耦合装置 (40) , 其包括至少一个销 (43) , 该销 (43) 在轴向方向上从第二环 (30) 的接触表面 (31) 突出并且至少一个座 (42) 形成在第一环 (20) 上并适于容纳销 (43) , 座 (42) 用作孔 (52) , 用于导丝和另外的孔 (53) 的通道。导丝的通道穿过销 (43) 的内部 , 使得环 (20,30) 可以通过沿导丝滑动而彼此接近。

