

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
16 April 2009 (16.04.2009)

PCT

(10) International Publication Number
WO 2009/046994 A2(51) International Patent Classification:
A61F 2/06 (2006.01) A61F 5/00 (2006.01)
A61B 17/11 (2006.01) A61F 2/04 (2006.01)(74) Agent: KLUNKER,SCHMITT-NILSON.HIRSCH;
Destouchesstrasse 68, 80796 München (DE).(21) International Application Number:
PCT/EP2008/008586

(22) International Filing Date: 10 October 2008 (10.10.2008)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/960,715	11 October 2007 (11.10.2007)	US
60/960,716	11 October 2007 (11.10.2007)	US
60/960,766	12 October 2007 (12.10.2007)	US
60/960,764	12 October 2007 (12.10.2007)	US
60/960,765	12 October 2007 (12.10.2007)	US
60/960,767	12 October 2007 (12.10.2007)	US
60/960,791	15 October 2007 (15.10.2007)	US

(71) Applicant (for all designated States except US): MILUX HOLDING SA [LU/LU]; 12, rue Guillaume Schneider, L-2522 Luxembourg (LU).

(72) Inventor; and

(75) Inventor/Applicant (for US only): FORSELL, Peter [SE/CH]; Aegeristrasse 66, CH-6300 Zug (CH).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv))

Published:

— without international search report and to be republished upon receipt of that report



WO 2009/046994 A2

(54) Title: IMPLANTABLE TISSUE CONNECTOR

(57) Abstract: An implantable tissue connector (1; 1 a) adapted to be connected to a tubular part of living tissue (70; 80) within a patient's body (100) comprises a conduit (2) and at least one flexible sleeve (10) adapted to axially extend and closely fit around at least part of the outer surface (6) of the conduit. The conduit is inserted into the tubular part of living tissue and the flexible sleeve placed over the tubular part of living tissue. Various alternatives are described of how the living tissue may be prevented from slipping off of the conduit.

IMPLANTABLE TISSUE CONNECTOR

Background of the invention

[0001] The present invention relates to an implantable tissue connector that is specifically adapted to be connected to a tubular part of living tissue within a patient's body, such as to the end of the human's large bowel when an artificial exit to the large bowel is to be provided. However, the implantable tissue connector of the present invention is not limited to such application and can be used in connection with many other kinds of tubular living tissue, as will be described in more detail below.

[0002] Connecting the end of the human's large bowel to an artificial exit, such as to a fecal excrements collecting container, or connecting a shortened large bowel to the patient's natural intestinal exit has always proven difficult and often unreliable. Leakage can occur where the connection is not tight over the lifetime. Blood circulation can be prohibited in the end area of the bowel tissue, which can negatively affect the muscle functions and peristaltic movement of the bowel and which can even lead to starvation of the respective portion of the bowel. Furthermore, the peristaltic movement of the bowel will continuously act upon the connection and, thus, the connection can fail over time.

Summary of the invention

[0003] It is therefore an object of the present invention to provide an implantable tissue connector for connecting tubular living tissue in a patient's body, which connection should be reliable over time and not severely harm the living tissue.

[0004] It is a further object to propose different uses for such tissue connector as well as methods for implanting the tissue connector in a patient's body.

[0005] Accordingly, the implantable tissue connector of the present invention comprises a conduit with at least a first and a second end and further having an outer surface on which may be mounted at least one flexible sleeve axially extending around at least part of said conduit. According to a first embodiment, the flexible sleeve is initially mounted on said outer surface either folded or rolled upon itself. According to a second embodiment, the flexible sleeve is initially mounted on said outer surface so as to be foldable upon itself. According to a third, more general embodiment, the flexible sleeve is not initially mounted on the conduit but will be mounted thereon only at the time of implantation of the tissue connector in the patient's body.

[0006] The first end of the conduit of the tissue connector is connected to a tubular part of living tissue by inserting the first end of the conduit into the tubular part of living tissue. Where, according to the first embodiment, the flexible sleeve is mounted on the outer surface of the conduit folded or rolled upon itself, the flexible sleeve is unfolded or unrolled such that at least part of the living tissue extending over the conduit's outer surface is located intermediate the sleeve and the outer surface of the conduit. Where, according to the second embodiment, the flexible sleeve is mounted on the outer surface of the conduit so as to be foldable upon itself, the flexible sleeve is folded upon itself such that at least part of the living tissue is located intermediate the folded sleeve or intermediate the conduit's outer surface and the sleeve. Where, according to the third embodiment, the flexible sleeve is provided separate from the conduit, the sleeve is advanced over the conduit and the respective portion of tubular tissue such that at least part of the living tissue is located intermediate the sleeve and the conduit's outer surface.

[0007] Either way, the tubular tissue is located somewhere between the conduit and the flexible sleeve and can be held in that position in various manners that will be described in the following and that can be applied individually as well as in combination.

[0008] The advantages achieved with the tissue connector according to the present invention comprise a good sealing of the living tissue between the conduit and the flexible sleeve as well as good protection of the living tissue by the flexible

sleeve. This way, the connection can be made reliable over time while also protecting the tissue against harm.

[0009] Where the flexible sleeve overlaps with the living tissue that has been drawn over the first end of the conduit, it is desirable that the flexible sleeve will exert radial pressure upon the tissue. In applications where there is no movement to be expected, this may be sufficient to hold the tissue connector in place. In other instances, where the movement of the tissue material is to be expected, such as when used as a bowel connector, the radial pressure will assist in holding the components in place until they are otherwise fixed against one another. In any case, it is preferable to design the flexible sleeve such that the radial pressure is minimal so as not to prohibit the blood circulation in the living tissue.

[0010] Furthermore, the conduit should be designed such that it is less flexible than the flexible sleeve at least in a radial direction so as to provide support to the sleeve against radial forces, in particular against the sleeve's aforementioned radial pressure. This way, the open internal cross section of the conduit will not be affected by the radial forces caused by the flexible sleeve.

[0011] Another particularly preferred way of reliably connecting the living tissue to the tissue connector involves a flexible sleeve that comprises a porous ingrowth layer allowing ingrowth of living tissue. This will not only strengthen any connection between the tissue connector and the tissue but will also serve to further seal the connection against any leakage.

[0012] The ingrowth layer should be made from a material that stimulates tissue ingrowth. Preferably, the ingrowth layer has a netlike structure that can be penetrated by ingrowing tissue, thereby creating a durable connection between the living tissue and the flexible sleeve. Of course, the ingrowth layer should be made from a biocompatible material, such as Dacron®.

[0013] Another way of reliably fixing the living tissue to the tissue connector consists in suturing the flexible sleeve to the living tissue. Alternatively, the suturing may be performed through the flexible sleeve and an outer wall of the conduit including an interposed portion of the living tissue. Thereby, the tissue is

fixed to both the flexible sleeve and the conduit. Leakage through needle penetrations caused by the suturing, if any, will automatically close over time by overgrowing tissue material.

[0014] It is also possible to perform the suturing through a portion of the living tissue and the outer wall of the conduit before the flexible sleeve is placed over the living tissue. This eliminates any problems of leakage through the penetration holes caused by the suturing as the sleeve will cover and seal such penetration holes.

[0015] Preferably, the thread used for suturing is made from a material that is absorbable by the patient's body. Typically, the thread will be absorbed by the body within about 6 weeks. At that time, however, the tissue ingrowth will be sufficiently advanced to compensate for the loss of strength that was initially provided by the thread.

[0016] Instead or in addition to suturing the flexible sleeve to the conduit by means of a preferably absorbable thread, the sleeve may be fixedly connected to the conduit along an axially extending portion of the sleeve in any other appropriate way. For instance, the conduit and the sleeve may be bonded along at least part of said axially extending portion of the sleeve. A primer may be applied on the conduit's outer surface and/or the flexible sleeve to enhance bonding characteristics.

[0017] The flexible sleeve may comprise a multi-layer material. This is particularly advantageous where the flexible sleeve comprises the aforementioned porous ingrowth layer. For instance, the porous ingrowth layer might itself not be sufficiently stable to be safely handled and pulled over the tubular tissue and/or the porous ingrowth layer might not be able to exert the radial pressure onto the tissue. In either of these cases, it is advantageous to provide the flexible sleeve with a support layer for supporting the porous ingrowth layer.

[0018] The support layer may be made e.g. from polyurethane or from expanded polytetrafluoroethylene (ePTFE). ePTFE is particularly preferred as it can be designed with pores sufficiently large in size so as to allow for the necessary

exchange of particles and/or elements between the underlying tissue and the surrounding area of the patient's body. Furthermore, the support layer may give better protection to the tissue than the ingrowth layer.

[0019] It is preferable when after implantation the support layer forms an outer layer of the flexible sleeve or, at least, that the ingrowth layer will be located radial inward from the support layer. Thus, where the flexible sleeve is mounted on the outer surface of the conduit so as to be foldable up on itself, the ingrowth layer will be located between portions of the support layer when the sleeve is folded upon itself. Alternatively, where the flexible sleeve is mounted on the outer surface of the conduit folded or rolled upon itself, the ingrowth layer will be located radial inward from the support layer when the sleeve is unfolded or unrolled.

[0020] In the regards of materials, both the conduit and the flexible sleeve should preferably be made from biocompatible material. As far as the sleeve is concerned, it preferably comprises polymers, such as polytetrafluoroethylene (PTFE), ePTFE, silicone and/or polyurethane.

[0021] As far as the conduit is concerned, the same and other biocompatible polymer materials can be used, including e.g. polyetheretherketone (PEEK). However, other materials, such as ceramics and metals, in particular titanium and stainless steel, can be used as well and are preferable for their strength.

[0022] The conduit can be substantially longer than the particular portion of the conduit to which the tubular tissue is connected. In that case, it is preferable that the flexible sleeve is located proximately to the respective end of the conduit so that the part of the tissue drawn over the conduit is not excessively large. The larger the overlapping part of the tissue is, the larger may become problems of blood circulation within that part of the tissue.

[0023] The tissue connector may be intended for connecting with one another two different ends of tubular living tissue. In this case, the conduit may have one flexible sleeve at each of the conduit's first and second ends. Again, the flexible sleeves are preferably located proximately to said first and second ends.

[0024] In order to facilitate the step of inserting the end or ends of the conduit into the tubular living tissue, it is advantageous to taper the free end portion of the conduit's end or ends towards the edge of said free end portion. Alternatively or in addition, the free end portion may be provided with a rounded edge. The rounded edge will help to prevent any damage to the living tissue when the tissue is pulled over the free end of the conduit.

[0025] According to another particularly preferred embodiment of the invention, there are provided special elements for preventing the tubular tissue from slipping off of the conduit. Again, these means can be combined with any of the aforementioned options of fixing the living tissue to the tissue connector.

[0026] More particularly, according to this preferred embodiment, the tissue connector comprises at least one bulge extending outwardly from the conduit's outer surface in a circumferential direction of the conduit about at least part of the conduit's circumference. Furthermore, at least one blocking ring is loosely fitted over the outer surface of the conduit with a clearance between the conduit's outer surface and the blocking ring for mounting living tissue within said clearance. The blocking ring has an inner cross sectional diameter which is smaller than or substantially identical to an outer cross sectional diameter of the at least one bulge so as to prevent the blocking ring from slipping over the bulge when living tissue is mounted within the clearance.

[0027] When the tissue connector is implanted in a human being or animal, the living tissue will be pulled over the conduit's outer surface including the bulge. Then the blocking ring will be advanced from the other side of the bulge over the living tissue towards the bulge such that at least part of the living tissue is located intermediate the conduit's outer surface and the blocking ring. This has the effect that, when the tissue tends to slip off of the conduit, it will carry the blocking ring towards and against the bulge. By this action, the living tissue will be compressed between the bulge and the blocking ring, thereby preventing any further slippage. This effect is self-enhancing with increasing slipping force. As the force tends to decrease again, the compression force will decrease accordingly so that blood circulation within the living tissue will not be negatively affected longer than necessary.

[0028] The size of the clearance in a radial direction depends upon the intended use of the tissue connector, i.e. upon the thickness of the tubular living tissue to which the tissue connector is connected. Accordingly, the size may be at average between 0.1 to 0.4 mm, 0.4 to 0.8 mm, 0.8 to 1.3 mm, 1.3 to 2 mm, 2 to 3 mm, 3 to 4 mm, 4 to 5 mm, over 5 mm. The clearance should be slightly smaller than the thickness of the living tissue so as not to severely affect blood circulation within the living tissue but nevertheless ensure sufficient frictional contact.

[0029] While the cross-sectional diameter of the blocking ring should preferably be smaller than the cross-sectional diameter of the bulge, it can in some instances be identical or even somewhat larger than this because the thickness of the living tissue, even in a compressed state, adds up to the cross-sectional diameter of the bulge so that altogether the blocking ring is prevented from slipping over the bulge. Therefore, in case of particularly thick living tissue, the inner cross-sectional diameter of the blocking ring may be even somewhat larger than the outer cross-sectional diameter of the bulge.

[0030] Of course, it is again preferable to make the blocking ring from a biocompatible material, in particular those materials mentioned above that are also suitable for the conduit.

[0031] Where the tissue connector is intended to connect two different ends of tubular living tissue material, it may have two of the aforementioned bulges, preferably located proximally to the respective ends of the conduit, with preferably at least two blocking rings located intermediate the two bulges. Of course, more than one blocking ring and/or more than one bulge may be provided for each end of the conduit.

[0032] As mentioned at the outset, the use of the tissue connector of the present invention is not limited to its application at the end of the human's large bowel. It can be advantageously used in many other applications.

[0033] For instance, the tissue connector may be fitted into a human's esophagus. In this case, the conduit of the tissue connector should have an inner

diameter of between 2 and 3.5 cm to provide for a snug fit. The clearance between the conduit and the blocking ring should be in the range of 2.5 to 5 mm.

[0034] Where the tissue connector is connected to a human's trachea, the inner diameter should be chosen between 1.5 and 2.5 cm, depending upon the position where at the human's trachea it is to be connected, in order to provide for a snug fit. The clearance between the conduit and the blocking ring should be in the range of 1 to 2 mm.

[0035] Where the tissue connector is fitted into a human stomach, the inner diameter of the conduit can vary with enlarged boundaries. The clearance between the conduit and the blocking ring should be in the range of 3.5 to 5 mm.

[0036] The tissue connector may also be fitted into a human's gall bladder or its connecting outlet channels. In that case, the conduit should have an inner diameter of between 0.5 and 1.3 cm. The clearance between the conduit and the blocking ring should be in the range of 0.5 to 1.5 mm.

[0037] In case that the tissue connector is fitted into a human's small bowel, the inner diameter of the conduit should be between 2 and 3 cm. The clearance between the conduit and the blocking ring should be in the range of 3 to 4 mm.

[0038] In case of the human's large bowel, whose diameter is highly stretchable, the inner diameter of the conduit should be between 3 and 5.5 cm to provide for a snug fit. The clearance between the conduit and the blocking ring should be in the range of 2 to 3.5 mm.

[0039] The tissue connector may also be fitted into a human's urethra. In this case, the conduit should have an inner diameter of between 0.4 and 0.8 cm. The clearance between the conduit and the blocking ring should be in the range of 0.5 to 1.5 mm.

[0040] Also, the tissue connector may be fitted into an human's ureter, in which case the inner diameter of the conduit should be chosen between 0.4 and 0.7 cm.

The clearance between the conduit and the blocking ring should be in the range of 2 to 4 mm.

[0041] The tissue connector may also be connected to the kidney. In order to snuggly fit it into a human's pelvic part of the kidney, the inner diameter of the conduit should be in the range of 1 and 5 cm, depending upon the position where at the human's pelvic it is to be connected. The clearance between the conduit and the blocking ring should be in the range of 0.5 to 1.5 mm.

[0042] The tissue connector may also be fitted into a human's blood vessel. In this case, the inner diameter of the conduit should be chosen approximately similar to the inner diameter of the respective blood vessel. As an example, the inner diameter may be chosen between 0.1 and 0.5 cm in the case of particularly small blood vessels. The tissue connector may as well be connected to the human's aorta or the heart's atrium or ventricle, in which case the inner diameter of the conduit is in the range of 2 to 3 cm. The clearance between the conduit and the blocking ring should be in the range of 1 to 2 mm.

[0043] The tissue connector may also be used as an intermediate piece to replace a part of tubular living tissue and may as well be used to connect different types of tubular living tissue, such as where a biological transplant of a third party's body is to be connected to the organs of a patient.

[0044] The tissue connector may particularly be used and be adapted for connecting it to at last one of an implantable reservoir, an implantable pump, an implantable motor, an implantable medical device and a biological transplant. The artificial items may even form a part of the tissue connector, either integrally formed therewith or separately connected thereto. The reservoir, pump, motor and/or medical device may also be incorporated in the tissue connector between the first and second ends of the conduit.

[0045] The biological transplant may be any transplant, such as a transplanted heart to be connected by means of the tissue connector to the patient's aorta and/or to other blood vessels (pulmonary arteria etc.).

[0046] Instead of being artificial, the aforementioned reservoir may consist of a biological transplant, but it may as well be made from tissue material of the patient into whom the reservoir is to be implanted. For instance, the reservoir may be a fecal excrements collecting container, such as a urine bladder or an intestine.

[0047] The reservoir may also be a reservoir for medical drugs for the patient's needs and is preferably adapted to be filled with at least one medical drug. Such medical drug reservoir may or may not be connected to a medical device, such as an implantable drug delivery device, which medical device may additionally include a pump for pumping the drug from the reservoir into the patient's body and possibly a motor for the pump.

[0048] Any other implantable medical devices may also be connected to the organs of the patient by means of the tissue connector, with or without a pump, motor and/or reservoir. Examples of these are an artificial heart, a penile prothesis, an artificial urine bladder, an artificial urethra, an artificial esophagus, an artificial trachea and the like. Examples of biological transplants include a urine bladder, an intestine, a urethra, a ureter, a kidney, a bowel, a heart, an esophagus, a trachea, a blood vessel and the like.

[0049] The tissue connector of the present invention can be implanted in a human being or animal either in open surgery or by subcutaneous surgery. In either case, the skin will have to be cut before free-dissecting an appropriate location within the patient's body adjacent to the tubular living tissue and, after the conduit of the tissue connector has been connected with one or both ends to the tubular tissue, at least the skin will have to be sutured at the end of the surgery.

[0050] Where the tissue connector is implanted by subcutaneous surgery, the steps of cutting the skin and free-dissecting the appropriate location within the patient's body comprise the steps of

- inserting a needle-like tube into the patient's body, such as the patient's thorax or abdomen,
- filling through said needle gas into the patient's body, i.e. into the thorax cavity or abdomen cavity,

- cutting a key-hole,
- inserting at least one, preferably two, laparoscopic trocars through the key-hole towards said location,
- advancing one or more medical instruments and a camera through the at least one trocar towards said location, i.e. into the thorax or abdomen, and
- dissecting an area of the tubular part of living tissue with the aid of the dissecting tool.
- The tissue connector may be supplied to said location through the at least one trocar or through a separate incision.

[0051] The invention will now be described in more detail in context with some preferred embodiments of the invention as shown in the accompanying drawings.

Brief description of the drawings

[0052] Figure 1 shows an exemplary view of a patient with one tissue connector connected to the patient's aorta and another tissue connector connected to the end of the patient's large bowel.

[0053] Figures 2a and 2b show a cross-section of a first embodiment of the tissue connector in the state of mounting and in the connected state.

[0054] Figures 3a and 3b show a cross-section of an alternative of the first embodiment of the tissue connector in the state of mounting and in the connected state.

[0055] Figures 4a and 4b show a second embodiment of the tissue connector in the state mounting and in the connected state.

[0056] Figure 5 shows an alternative for mounting living tissue on a free end of the tissue connector.

[0057] Figures 6a and 6b show a combination of an embodiment similar to the one shown in Figures 2a and 2b with additional mounting means as shown in figure 5.

[0058] Figure 7 shows a specific embodiment of a tissue connector with two ends thereof connected to living tissue.

[0059] Figure 1 schematically shows a body 100 of a patient with a first tissue connector 1 connected to the end of the patient's large bowel 50 and a second tissue connector 1a interconnecting two pieces of the patient's aorta 60. The tissue connector 1 may either connect the large bowel 50 to the patient's anus or to an artificial anus which may include an excrements collecting container. The tissue connector 1a may include between its two ends a heart valve, a blood pump, a drug delivery device or the like.

[0060] The tissue connectors 1 and 1a shown in Figure 1 represent only a few of many different possible locations and applications of the tissue connector within the human's or, alternatively, an animal's body. Further examples of possible applications have already been outlined further above.

[0061] Figures 2a and 2b show a first embodiment of the tissue connector 1 in the state of mounting the tissue connector to a tubular part of living tissue 70. The tissue connector 1 comprises a conduit 2 with a first end 3 and a second end 4. In Figure 2a, the first end 3 of the conduit 2 has already been inserted into an end portion of living tissue 70. The inner cross section of the conduit 2 is selected to approximately match the inner cross section of the tubular living tissue 70 so as not to obstruct any flow of material. The thickness of the wall 5 of the conduit, which is typically circular, is chosen to provide sufficient strength so that it does not collapse under the forces that will act upon the conduit during use, while providing sufficient flexibility where needed. On the other hand, the thickness should not be chosen too large since the living tissue will have to be stretched over the outer surface 6 of the conduit 2 without damage and without excessively affecting blood circulation within the end portion 71 of the living tissue 70.

[0062] The wall 5 of conduit 2 is tapered towards its leading edge 7. In addition, the leading edge 7 is rounded. These two measures prevent damage to the living tissue 70 when the conduit 2 is inserted into the end portion 71 of the living tissue 70.

[0063] The second end 4 may serve and be adapted to be connected to an implantable medical device, an implantable reservoir, an implantable pump, an implantable motor or a combination of the afore mentioned items (generally designated with 200). It may also be connected to any other implantable device 200. The implantable device 200 may even form a part of the tissue connector 1, either integrally or attached thereto.

[0064] The implantable device 200 may also be a medical device replacing one or more of the patient's organs, such as an artificial urine bladder, a fecal excrement's collecting container, an artificial urethra, an artificial heart, an artificial esophagus, an artificial trachea or the like. Alternatively, the second end 4 of the conduit 2 may be connected to a biological implant obtained from a third party's body, such as a urine bladder, an intestine, a urethra, a ureter, a kidney, a bowel, a heart, an esophagus, a trachea, a blood vessel or the like.

[0065] The device 200 may also comprise a flow restrictor for partial or complete restriction of flow through the conduit. This can be suitable e.g. in the case where the tissue connector is located at the end of the patient's large bowel.

[0066] The device 200 may also be placed between the tissue connector 1 and a second tissue connector 1b with conduit 2b, as is indicated in Figure 2a by dotted lines. This arrangement is practical where the device 200 has to be placed at a location within one of the patient's organs, such as in a blood vessel, in which case the blood vessel would be divided and the device 200 placed between the two tissue connectors 1 and 1b connected to the respective free ends of the divided blood vessel. As an example, the device 200 could include a flow restrictor, such as an artificial heart valve, or a drug delivery reservoir.

[0067] Apart from the conduit 2 and the optional device 200, the tissue connector 1 of the embodiment shown in Figure 2a has a flexible sleeve 10 axially extending and closely fitted around a part of the outer surface 6 of the conduit 2. The flexible sleeve 10 may be delivered separately from the conduit 2 and placed over the conduit's outer surface 6 shortly before implantation into the patient's body. However, it is preferred to provide the conduit 2 with the flexible sleeve 10 as a

unitary item, the flexible sleeve 10 preferably fixed to the outer surface 6 by means of bonding, welding and/or clamping. In the case of bonding, it can be advisable to pretreat the outer surface 6 e.g. with a primer, depending upon the material combination to be bonded together.

[0068] In Figure 2a, the flexible sleeve 10 is rolled upon itself and can be unrolled over the portion 71 of living tissue 70 so as to cover, seal and protect that portion 71 on the first end 3 of the conduit 2, as is shown in Figure 2b. The tissue portion 71 and the overlapping part 11 of flexible sleeve 10 are fixed to the first end 3 of the conduit 2 by suturing threads 20 therethrough and through the wall 5 of the conduit 2, as is indicated in Figure 2b by dotted lines.

[0069] The flexible sleeve 10 is a multilayer material comprising a porous ingrowth layer to allow ingrowth of living tissue. For that, it has a netlike structure. On top of the ingrowth layer 11 there is provided a support layer 12. The support layer 12 may have one or more of various functions. One possible function is to provide support to the ingrowth layer 11 so as to ease handling and/or prevent fusing of the ingrowth layer. Also, the support layer 12 may provide some tension, thereby exerting a compressive force in a radial direction so as to slightly clamp the tissue portion 71 against the outer surface 6 of the conduit 2. For that, the support layer should have an appropriate elasticity. Finally, the support layer may provide protection for the tissue portion 71.

[0070] Preferably, the support layer should be porous so that exchange between the tissue portion 71 and the surrounding area within the patient's body is possible. This is an important aspect for the ingrowth of living tissue material into the ingrowth layer 11. Expanded polytetrafluoroethylene (ePTFE) is particularly suitable, as it is flexible, inert and can be made with any desired porosity. Other biocompatible polymers, such as polyurethane and the like, are suitable as well.

[0071] Figures 3a and 3b show an alternative of the first embodiment of the tissue connector which differs from the connector shown in Figures 2a and 2b solely by the fact that the flexible sleeve 10 is not rolled upon itself but, instead, folded upon itself. By unfolding the folded sleeve 10, it can be placed over the

tissue portion 71 in the same manner as discussed above in relation to Figures 2a, 2b, as is shown in Figure 3b.

[0072] Figures 4a and 4b show a second embodiment of a tissue connector where the flexible sleeve 10 is arranged such that it is foldable upon itself. More particularly, the first end 3 of the conduit 2 is inserted in the tissue portion 71 of living tissue 70 to an extent that it overlaps a first portion 13 of the flexible sleeve 10. The remaining portion 14 of the flexible sleeve 10 not being covered by the tissue portion 71 is rolled upon itself and can be unrolled so as to cover the tissue portion 71. As a result shown in Figure 4b, the flexible sleeve 10 is folded upon itself with the tissue portion 71 placed intermediate the folded sleeve 10.

[0073] Different to the embodiments described before, suturing the tissue portion 71 to the wall 5 of the conduit 2 is carried out before the tissue portion 71 is covered with the remaining part 14 of the flexible sleeve 10. The remaining part 14 thereby seals any penetration holes caused by the suturing.

[0074] In an alternative of the second embodiment, not shown, the first end 3 of the conduit 2 will be inserted in the tissue portion 71 only so far that the tissue portion 71 does not overlap with the flexible sleeve 10. Thus, after unrolling the flexible sleeve 10, only a part of the folded sleeve 10 will cover the tissue portion 71.

[0075] Furthermore, also not shown, the remaining part 14 of the sleeve 10 is not necessarily rolled upon itself, as shown in Figure 4a, but may lay flat against the outer surface 6 of the conduit 2, similar to the embodiment shown in Figure 3a.

[0076] As will be recognized, the portion 13 of the flexible sleeve 10 is arranged in a circumferential groove provided in the outer surface 6 of the conduit 2. It is advantageous when the depth of the groove corresponds to the thickness of the flexible sleeve 10. This will facilitate introducing the first end 3 of the conduit 2 into the living tissue 70.

[0077] Figure 5 shows a possibility of fixing the conduit 2, such as the conduit's second end 4, to a tubular part of living tissue 80 or to a hose that belongs or

leads to a medical device, reservoir, or the like. Accordingly, at least one bulge 15 extends outwardly from the conduit's outer surface 6 in a circumferential direction of the conduit 2 about at least a part of the conduit's circumference. Furthermore, at least one blocking ring 30 loosely fitting over the outer surface 6 of the conduit 2 with a clearance between the outer surface 6 and the blocking ring 30 is provided for mounting the tubular living tissue 80 (or alternatively the hose) within the clearance. The blocking ring has an inner cross-sectional diameter which is about the same as the outer cross-sectional diameter of the bulge 15. This prevents the blocking ring from slipping over the bulge when the living tissue 80, as shown in Figure 5, is mounted within the clearance.

[0078] When an axial force tends to pull the tubular living tissue 80 from the outer surface 6 of the conduit 2, the blocking ring 30 will move with the tubular tissue 80, thereby compressing the tubular tissue 80 against the bulge 15, so as to prevent any further slippage of the tubular tissue 80 over the bulge 15. This is a self-enhancing effect.

[0079] This kind of locking mechanism can be combined with any of the aforementioned embodiments of the tissue connector. Of these variants, only one shall exemplary be described in the following in relation to Figures 6a and 6b. The embodiment shown in Figures 6a and 6b substantially correspond to the embodiment of Figures 2a and 2b, where the flexible sleeve 10 is rolled upon itself and then unrolled to cover the tubular tissue 80 which, in this case, is pulled over the second end 4 of the conduit 2 sufficiently far so as to extend also over the bulge 15. After the flexible sleeve 10 has been unrolled over the tubular tissue 80, the blocking ring 30 is pushed over the flexible sleeve against the bulge 15. After a while, the threads 20 sutured to the tubular tissue 80 and the wall 5 of the conduit 2 (Figure 6a) will have been absorbed by the patient's body and, about during the same time, living tissue will have formed in and connect the tubular tissue 80 to the ingrowth layer 11 of the flexible sleeve 10. Therefore, as the tubular tissue 80 tends to be pulled off of the second end 4 of the conduit 2, the blocking ring 30 will also be moved, press the tubular tissue 80 and the flexible sleeve 10 against the bulge 15 and thereby prohibit any further slippage of the tubular tissue 80 over the bulge 15. The friction coefficient between the blocking ring 30 and the outer

surface of the flexible sleeve should be higher than the friction coefficient which the conduit's outer surface 6 has in relation to the tubular tissue 80.

[0080] Note that the flexible sleeve 10 in its unrolled state as shown in Figure 6b must not necessarily extend over the bulge 15 but can end a distance away from the bulge. In that situation, the blocking ring 30 would not clamp the sleeve 10 against the bulge 15.

[0081] The afore mentioned embodiments have mainly been described in relation to a tissue connector of which only one of the two ends is intended to be connected to tubular living tissue. However, as has also been mentioned before, there are various applications where the tissue connector may connect two pieces of tubular living tissue, such as when bridging two pieces of identical tubular living tissue or connecting tubular living tissue with tissue of a biological transplant. For that, the second end 4 of the tissue connector's conduit 2 can be designed according to any of the aforementioned embodiments. Fig. 7 gives just an example of how such tissue connector could be designed. Accordingly, two flexible sleeves 10 are integrally formed to form a single flexible sleeve 10a, with each of the sleeves 10 being rolled upon itself, similar to the embodiment shown in Fig. 2a. The two flexible sleeves 10 can, of course, be provided separately. Furthermore, a bulge 15 and a blocking ring 30 can be provided at one or both of the conduit's ends 3 and 4. Also, a medical device, flow restrictor or the like can be incorporated intermediate the two ends 3 and 4.

CLAIMS**FLEXIBLE SLEEVE**

1. An implantable tissue connector adapted so as to be connectable to a tubular part of living tissue within a patient's body, comprising
 - a conduit having at least a first and a second end and further having an outer surface, and
 - at least one flexible sleeve adapted to axially extend and closely fit around at least part of said outer surface of the conduit.
2. The tissue connector of claim 1, wherein said flexible sleeve is mounted on said outer surface either folded or rolled upon itself or so as to be foldable upon itself.
3. The tissue connector of any of claims 1 or 2, wherein the conduit is made from a biocompatible material.
4. The tissue connector of claim 3, wherein the biocompatible material of the conduit is a material of the following group of materials comprising: titanium, stainless steel, ceramics, polytetrafluoroethylene (PTFE), expanded polytetrafluoroethylene (ePTFE), polyetheretherketone (PEEK), silicone, polyurethane, polypropylene, other biocompatible polymer material.
5. The tissue connector of any of claims 1 to 4, wherein the flexible sleeve is made from a biocompatible material.
6. The tissue connector of claim 5, wherein the biocompatible material of the flexible sleeve comprises at least one polymer.
7. The tissue connector of claim 6, wherein the at least one polymer is a polymer of the following group of polymers comprising: polytetrafluoroethylene, silicone, polyurethane, expanded polytetrafluoroethylene (ePTFE).

8. The tissue connector of any of claims 1 to 7 including claim 2, wherein, where the flexible sleeve is mounted on the outer surface of the conduit so as to be foldable upon itself, the flexible sleeve, when folded upon itself, will exert radial pressure.
9. The tissue connector of claim 8, wherein, when implanted in a patient's body with the sleeve folded upon itself, the tissue connector is adapted to exert said radial pressure on any living tubular tissue placed intermediate the folded sleeve.
10. The tissue connector of any of claims 1 to 7 including claim 2, wherein, where the flexible sleeve is mounted on the outer surface of the conduit folded or rolled upon itself, the flexible sleeve, when unfolded or unrolled, will exert radial pressure.
11. The tissue connector of claim 10, wherein, when implanted in a patient's body with the sleeve unfolded or unrolled, the tissue connector is adapted to exert said radial pressure on any living tubular tissue placed intermediate the sleeve and the outer surface of the conduit.
12. The tissue connector of any of claims 9 or 11, wherein said radial pressure is minimal such that blood circulation in living tissue is not prohibited.
13. The tissue connector of any of claims 1 to 12, wherein the conduit is less flexible than the flexible sleeve at least in a radial direction so as to provide support to the sleeve against radial forces.
14. The tissue connector of any of claims 1 to 13, wherein the flexible sleeve comprises a porous ingrowth layer allowing ingrowth of living tissue.
15. The tissue connector of claim 14, wherein the ingrowth layer has a net-like structure.
16. The tissue connector of any of claims 14 or 15, wherein the ingrowth layer is made from Dacron®.

17. The tissue connector of any of claims 1 to 16, wherein the flexible sleeve comprises a multilayer material.
18. The tissue connector of any of claims 14 to 16, wherein the flexible sleeve further comprises a support layer for supporting said porous ingrowth layer.
19. The tissue connector of claim 17, wherein the support layer is made from expanded polytetrafluoroethylene (ePTFE) or polyurethane.
20. The tissue connector of any of claims 15 to 19 including claim 2, wherein, where the flexible sleeve is mounted on the outer surface of the conduit so as to be foldable upon itself, the ingrowth layer will be located between portions of the support layer when the sleeve is folded upon itself.
21. The tissue connector of any of claims 15 to 19 including claim 2, wherein, where the flexible sleeve is mounted on the outer surface of the conduit folded or rolled upon itself, the ingrowth layer will be located radial inward from the support layer when the sleeve is unfolded or unrolled.
22. The tissue connector of any of claims 1 to 21, wherein the conduit and the flexible sleeve are fixedly connected to each other along an axially extending portion of the sleeve.
23. The tissue connector of claim 22, wherein the conduit and the flexible sleeve are bonded along at least part of said axially extending portion of the sleeve.
24. The tissue connector of claim 23, comprising a primer on at least one of the conduit and the flexible sleeve to enhance bonding characteristics.
25. The tissue connector of any of claims 1 to 24, wherein the at least one flexible sleeve is located proximately to said first end of the conduit.
26. The tissue connector of any of claims 1 to 25, wherein the conduit has at least two of said flexible sleeves.

27. The tissue connector of claim 26, wherein the at least two flexible sleeves are each located proximately to one of said at least first and second ends of the conduit.
28. The tissue connector of any of claims 1 to 27, wherein the first end of the conduit has a free end portion and tapers towards the edge of said free end portion.
29. The tissue connector of any of claims 1 to 28, wherein the first end of the conduit has a free end portion with a rounded edge.

BULGE AND RING

30. The tissue connector of any of claims 1 to 29, further comprising
 - at least one bulge extending outwardly from the conduit's outer surface in a circumferential direction of the conduit about at least a part of the conduit's circumference, and
 - at least one blocking ring loosely fitting over the outer surface of the conduit with a clearance between the outer surface and the blocking ring for mounting tubular living tissue or a hose within the clearance, said blocking ring having an inner cross sectional diameter which is smaller than or substantially identical to an outer cross sectional diameter of the at least one bulge so as to prevent the blocking ring from slipping over the bulge when living tissue or a hose is mounted within the clearance.
31. The tissue connector of claim 30, wherein the blocking ring is made from a biocompatible material.
32. The tissue connector of claim 31, wherein the biocompatible material of the blocking ring is a material of the following group of materials comprising: titanium, stainless steel, ceramics, polytetrafluoroethylene, silicone, polyurethane.

33. The tissue connector of any of claims 30 to 32, wherein the at least one bulge is located proximately to said first end of the conduit.
34. The tissue connector of any of claims 30 to 33, wherein the conduit has at least two of said bulges with at least two of said blocking rings located intermediate said at least two bulges.
35. The tissue connector of claim 34, wherein the at least two bulges are each located proximate one of said at least first and second ends of the conduit.
36. The tissue connector of any of claims 30 to 35, wherein – depending upon the intended use – the clearance is in the range of one of the following ranges: 0.1 to 0.4 mm, 0.4 to 0.8 mm, 0.8 to 1.3 mm, 1.3 to 2 mm, 2 to 3 mm, 3 to 4 mm, 4 to 5 mm, over 5 mm.

COMMON FEATURES

37. The tissue connector of any of claims 1 to 36, wherein said second end of the conduit is adapted for connecting the tissue connector to at least one of the following items: an implantable reservoir, an implantable pump, an implantable motor, an implantable medical device, a biological transplant.
38. The tissue connector of any of claims 1 to 37, wherein between the first and second ends of the conduit or connected to the second end of the conduit, there is provided at least one of the following items: a reservoir, a pump, a motor, a medical device.
39. The tissue connector of claim 38, wherein the reservoir is artificial or a biological transplant or made from tissue material of a patient into whom the reservoir is to be implanted.
40. The tissue connector of any of claims 37 to 39, wherein the reservoir is a fecal excrements collecting container.

41. The tissue connector of claim 40, wherein the fecal excrements collecting container comprises one of the following: a urine bladder, an intestine.
42. The tissue connector of any of claims 37 to 39, wherein the reservoir is adapted to be filled with at least one medical drug for patient needs.
43. The tissue connector of claim 38, wherein said medical device is a device of the following group of devices comprising: a drug delivery system, an artificial urine bladder, a fecal excrements collecting container, an artificial urethra, an artificial heart, an artificial esophagus, an artificial trachea.
44. The tissue connector of claim 38, wherein said biological transplant is a transplant of the following group of transplants comprising: a urine bladder, an intestine, a urethra, a ureter, a kidney, a bowel, a heart, an esophagus, a trachea, a blood vessel.
45. The tissue connector of any of claims 1 to 44, comprising a flow restrictor for partial or complete restriction of flow through the conduit.
46. The tissue connector of any of claims 1 to 45, wherein the conduit has an inner diameter of between 0.1 and 0.5 cm.
47. The tissue connector of any of claims 1 to 45, wherein the conduit has an inner diameter of between 0.5 and 1 cm.
48. The tissue connector of any of claims 1 to 45, wherein the conduit has an inner diameter of between 1 and 2 cm.
49. The tissue connector of any of claims 1 to 45, wherein the conduit has an inner diameter of between 2 and 3 cm.
50. The tissue connector of any of claims 1 to 45, wherein the conduit has an inner diameter of between 3 and 4 cm.

51. The tissue connector of any of claims 1 to 45, wherein the conduit has an inner diameter of 4 cm or over.
52. The tissue connector of any of claims 1 to 45, wherein said conduit is sized so as to be snuggly fitted into a human's esophagus.
53. The tissue connector of any of claims 1 to 45, wherein said conduit is sized so as to be snuggly fitted into a human's trachea.
54. The tissue connector of any of claims 1 to 45, wherein said conduit is sized so as to be snuggly fitted into a human's stomach.
55. The tissue connector of any of claims 1 to 45, wherein said conduit is sized so as to be snuggly fitted into a human's gall bladder or its connecting outlet channels.
56. The tissue connector of any of claims 1 to 45, wherein said conduit is sized so as to be snuggly fitted into a human's small bowel.
57. The tissue connector of any of claims 1 to 45, wherein said conduit is sized so as to be snuggly fitted into a human's large bowel.
58. The tissue connector of any of claims 1 to 45, wherein said conduit is sized so as to be snuggly fitted into a human's urethra.
59. The tissue connector of any of claims 1 to 45, wherein said conduit is sized so as to be snuggly fitted into a human's ureter.
60. The tissue connector of any of claims 1 to 45, wherein said conduit is sized so as to be snuggly fitted into a human's pelvic part of the kidney.
61. The tissue connector of any of claims 1 to 45, wherein said conduit is sized so as to be snuggly fitted into a human's blood vessel.

62. The tissue connector of claim 61, wherein said conduit is sized so as to be snuggly fitted into the human's aorta or the heart's atrium or ventricle.

USE

63. A use of the tissue connector of any of claims 1 to 45 as a connector to the human's esophagus.
64. A use of the tissue connector of any of claims 1 to 45 as a connector to the human's trachea.
65. A use of the tissue connector of any of claims 1 to 45 as a connector to the human's stomach.
66. A use of the tissue connector of any of claims 1 to 45 as a connector to the human's gall bladder or its connecting outlet channels.
67. A use of the tissue connector of any of claims 1 to 45 as a connector to the human's small bowel.
68. A use of the tissue connector of any of claims 1 to 45 as a connector to the human's large bowel.
69. A use of the tissue connector of any of claims 1 to 45 as a connector to the human's urethra.
70. A use of the tissue connector of any of claims 1 to 45 as a connector to the human's ureter.
71. A use of the tissue connector of any of claims 1 to 45 as a connector to the human's pelvic part of the kidney.
72. A use of the tissue connector of any of claims 1 to 45 as a connector to the human's blood vessel.

73. The use of the tissue connector of claim 72 as a connector to the human's aorta or the heart's atrium or ventricle.
74. A use of the tissue connector of any of claims 1 to 45 as a connector between the human's kidney and a reservoir.
75. A use of the tissue connector of any of claims 1 to 45 as a connector between the human's intestine and a reservoir.
76. The use of the tissue connector of any of claims 74 or 75, wherein the reservoir is artificial or a biological transplant.

METHOD OF TREATMENT (IMPLANTATION)

77. A method of treating a human being or an animal by implanting the tissue connector of any of claims 1 to 36 in a patient's body, comprising the steps of
 - cutting the skin,
 - free-dissecting a location within the patient's body adjacent to a tubular part of living tissue,
 - connecting the first end of the conduit of the tissue connector to a first section of the tubular part of living tissue by inserting the first end of the conduit into the first section of the tubular part of living tissue and, where the flexible sleeve is mounted on the outer surface of the conduit so as to be foldable upon itself, folding the flexible sleeve upon itself such that at least part of the living tissue is located intermediate the folded sleeve or intermediate the conduit's outer surface and the sleeve or, where the flexible sleeve is mounted on the outer surface of the conduit folded or rolled upon itself, unfolding or unrolling the flexible sleeve such that at least part of the living tissue is located intermediate the sleeve and the outer surface of the conduit, and
 - suturing at least the skin after connecting the living tissue to the tissue connector has been completed.

78. A method of treating a human being or an animal by implanting the tissue connector of any of claims 30 to 36 in a patient's body, comprising the steps of
 - cutting the skin,
 - free-dissecting a location within the patient's body adjacent a tubular part of living tissue,
 - connecting the first end of the conduit of the tissue connector to a first section of the tubular part of living tissue by inserting the first end of the conduit including the bulge into the first section of the tubular part of living tissue and, where the flexible sleeve is mounted on the outer surface of the conduit so as to be foldable upon itself, folding the flexible sleeve upon itself such that at least part of the living tissue is located intermediate the folded sleeve or intermediate the conduit's outer surface and the flexible sleeve or, where the flexible sleeve is mounted on the outer surface of the conduit folded or rolled upon itself, unfolding or unrolling the flexible sleeve such that at least part of the living tissue is located intermediate the sleeve and the outer surface of the conduit, and advancing the blocking ring over the living tissue towards the bulge such that at least part of the living tissue is located intermediate the conduit's outer surface and the blocking ring, and
 - suturing at least the skin after connecting the living tissue to the tissue connector has been completed.
79. The method of claim 78, wherein during the step of folding the flexible sleeve upon itself a portion of the sleeve is unrolled.
80. The method of claim 78, wherein, after the step of folding the sleeve upon itself or after the step of unfolding or unrolling the sleeve, the sleeve is fixed to the living tissue by suturing.
81. The method of any of claims 77 to 80, wherein suturing is performed through an outer wall of the conduit including a portion of the living tissue.
82. The method of any of claims 80 or 81, wherein a thread is used for suturing which is made from a material that is absorbable by a patient's body.

83. The method of any of claims 77 to 82, comprising the step of connecting the second end of the conduit of the tissue connector to a different type of living tissue.
84. The method of any of claims 77 to 82, comprising the step of connecting the second end of the conduit of the tissue connector to a second section of said tubular part of living tissue.
85. The method of claim 84, wherein the step of connecting the second end of the conduit of the tissue connector to the second section of tubular part of living tissue comprises the steps of inserting the second end of the conduit into the second section of the tubular part of living tissue and, where a second of said at least one flexible sleeve is mounted on the outer surface of the conduit so as to be foldable upon itself, folding the second flexible sleeve upon itself such that at least part of the second section of the tubular part of living tissue is located intermediate the folded second flexible sleeve or intermediate the conduit's outer surface and the flexible sleeve or, where the second flexible sleeve is mounted on the outer surface of the conduit folded or rolled upon itself, unfolding or unrolling the second flexible sleeve such that at least part of the second section of the tubular part of the living tissue is located intermediate the second flexible sleeve and the outer surface of the conduit.
86. The method of claim 85 including claim 78, wherein the step of inserting the second end of the conduit into the second section of the tubular part of living tissue includes inserting the bulge into the second section of the tubular part of living tissue.
87. The method of any of claims 77 to 86, wherein the human's throat is selected as the tubular part of living tissue.
88. The method of any of claims 77 to 86, wherein the human's trachea is selected as the tubular part of living tissue.

89. The method of any of claims 77 to 86, wherein the human's small bowel is selected as the tubular part of living tissue.
90. The method of any of claims 77 to 86, wherein the human's large bowel is selected as the tubular part of living tissue.
91. The method of any of claims 77 to 86, wherein the human's urethra is selected as the tubular part of living tissue.
92. The method of any of claims 77 to 86, wherein the human's ureter is selected as the tubular part of living tissue.
93. The method of any of claims 77 to 86, wherein the pelvic part of a human's kidney is selected as the tubular part of living tissue.
94. The method of any of claims 89 to 93, wherein the steps of cutting the skin and free-dissecting a location within the patient's body comprise the steps of:
 - inserting a needle-like tube into the abdomen of a patient's body,
 - filling the thorax with gas thereby expanding the abdominal cavity,
 - positioning at least two laparoscopic trocars in the patient's body,
 - inserting a camera into the abdomen through one of the trocars,
 - inserting a dissecting tool through another one of the trocars, and
 - dissecting an area of the tubular part of living tissue with the aid of the dissecting tool.
95. The method of any of claims 89 to 93, wherein the step of free-dissecting a location within the patient's body comprises opening the patient's abdomen for open surgery.
96. The method of any of claims 77 to 86, wherein a human's blood vessel is selected as the tubular part of living tissue.
97. The method of any of claims 77 to 86, wherein the human's aorta is selected as the tubular part of living tissue.

98. The method of any of claims 96 to 97, wherein the steps of cutting the skin and free-dissecting a location within the patient's body comprises the steps of:
 - inserting a needle-like tube into the thorax of a patient's body,
 - filling the thorax with gas thereby expanding the thorax cavity,
 - positioning at least two laparoscopic trocars in the patient's body,
 - inserting a camera into the thorax through one of the trocars,
 - inserting a dissecting tool through another one of the trocars, and
 - dissecting an area of the tubular part of living tissue with the aid of the dissecting tool.
99. The method of any of claims 96 to 97, wherein the step of free-dissecting a location within the patient's body comprises opening the patient's thorax for open surgery.
100. The method of any of claims 77 to 93 or 96, wherein the steps of cutting the skin, free-dissecting the location adjacent the tubular part of living tissue and connecting the tissue connector to the tubular part of living tissue comprise:
 - inserting a needle-like tube into the patient's body,
 - filling through said needle gas into the patient's body,
 - cutting a key-hole,
 - inserting at least one laparoscopic trocar through the key-hole towards said location,
 - advancing one or more medical instruments and a camera through the at least one trocar towards said location,
 - dissecting said location, and
 - supplying the tissue connector to said location through the at least one trocar or through a separate incision.






FIG 3A




FIG 3B




FIG 4A




FIG 4B




FIG 5




FIG 6A




FIG 6B





FIG 7



专利名称(译)	植入式组织连接器		
公开(公告)号	EP2211774A2	公开(公告)日	2010-08-04
申请号	EP2008837628	申请日	2008-10-10
[标]申请(专利权)人(译)	米卢克斯控股股份有限公司		
申请(专利权)人(译)	MILUX HOLDING SA		
当前申请(专利权)人(译)	KIRK推广有限公司.		
[标]发明人	FORSELL PETER		
发明人	FORSELL, PETER		
IPC分类号	A61F2/06 A61B17/11 A61F5/00 A61F2/04 A61M39/10 A61F2/00 A61M1/10		
CPC分类号	A61F2/064 A61B17/1114 A61B2017/1107 A61F2/04 A61F2002/045 A61M1/1008 A61M1/12		
优先权	60/960764 2007-10-12 US 60/960765 2007-10-12 US 60/960766 2007-10-12 US 60/960767 2007-10-12 US 60/960716 2007-10-11 US 60/960715 2007-10-11 US 60/960791 2007-10-15 US		
其他公开文献	EP2211774B1		
外部链接	Espacenet		

摘要(译)

适于连接到患者体内的活组织 (70; 80) 的管状部分的可植入的组织连接器 (1; 1a) 包括导管 (2) 和至少一个柔性套管 (10) , 所述柔性套管轴向延伸并紧密配合在导管的外表面 (6) 的至少一部分周围。将导管插入活组织的管状部分中 , 并将柔性套管放置在活组织的管状部分上。描述了如何防止活组织从导管滑脱的各种替代方案。