



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
11.02.2009 Bulletin 2009/07

(51) Int Cl.:
A61B 17/28 (2006.01) A61B 17/32 (2006.01)

(21) Application number: **08170110.4**

(22) Date of filing: **17.02.2005**

(84) Designated Contracting States:
DE FR GB

(30) Priority: **27.02.2004 US 548747**

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:
05713752.3 / 1 718 224

(71) Applicant: **APPLIED MEDICAL RESOURCES CORPORATION**
Rancho Santa Margarita, CA 92688 (US)

(72) Inventors:
• **Johnson, Gary Mr**
Mission Viejo, CA 92692 (US)

• **Alhberg, Russell E**
Rancho Santa Margarita, CA 92688 (US)
• **Okihisa, David**
Irvine, CA 92602 (US)
• **Bak-Boychuck, Gregory I**
Laguna Niguel, CA 92677 (US)

(74) Representative: **Fitchett, Stuart Paul**
Saunders & Dolleymore
9 Rickmansworth Road
Watford
Hertfordshire WD18 0JU (GB)


Remarks:

This application was filed on 27-11-2008 as a divisional application to the application mentioned under INID code 62.

(54) **System and Method for Actuating a Laparoscopic Surgical Instrument**

(57) The invention is directed to a pin and slot design where the driving slots are moved from the tips to the actuation rod in one aspect of the invention. As a result, the back end of each blade or tip can be dramatically reduced in area so that during full deflection, very little or no part of the blade or tip extends beyond the outside diameter of the shaft. This ensures that nothing catches on the blades or tips during grasper use and the shrink tubing found on the scissors would not be deformed. This can be done because the area for the slots is not needed. Moreover, the usable area for the drive slots on the blade or tip of the actuation rod is maximized to the overall diameter of the outer tube or shaft which provides additional leverage to the blades or tips. In addition, the depth of each slot can be varied such that during actuation, increased tension can be put on the blades or tips throughout the cut. More specifically, the surgical instrument of the invention comprises an elongate tube extending along an axis including an actuation rod coaxially slidable within the elongate tube, a first tip including a first pin formed on a proximal end surface of the first tip, and a second tip including a second pin formed on a proximal end surface of the second tip, the second tip pivotally connected to the first tip at a common pivot pin operably connected to the elongate tube to open and close the tips in response to movement of the actuation rod. The actuation rod has a slot to accept the pins of the

first and second tips, the slot has camming surfaces for the pins to slide within the slot, and the proximal ends of the tips extend minimally outside the diameter of the elongate tube during actuation of the tips.



Description

BACKGROUND OF THE INVENTION

Field of the Invention

[0001] This invention generally relates to laparoscopic surgical instruments and, in particular, to a system and method for actuating the tips of a laparoscopic surgical instrument.

Description of Prior Art

[0002] Laparoscopic surgical instruments or devices that use actuating blades or tips are typically activated by some mechanical means. In most cases, the surgical instruments or devices use an actuation rod to translate motion from a handle at one end to a tip at the opposite end of the device. Common to laparoscopic scissors and graspers is an actuation rod that includes a pin that works in conjunction with a slot in the tips. Moving the actuation rod cams the pin in the slot which opens and closes the tips.

[0003] The blades or tips typically have slots proximal to the pivot and because of this configuration, the back end of the blades or tips need to be quite large. When used on a grasper and the tips are in their open position, the back end of the tips extend out beyond the outside diameter of the grasper shaft and look like "wings." This may be a problem for the user and, in particular, the patient as they can catch or interfere on tissue or other devices during use.

[0004] When used on scissors, these wings will most likely be covered up with a plastic shrink tubing to insulate all the metal components during electro-surgical cautery. However, when the blades or tips are open, the wings can stretch and deform the shrink tubing. This can be problematic in that when the scissors is withdrawn from the trocar, the deformed tubing may not relax and it may catch on the end of the cannula, thereby pulling the trocar out of the patient. Accordingly, there is a need in the art for an improved system and method for actuating the blades or tips of laparoscopic instruments so as to minimize the adverse wing effect.

SUMMARY OF THE INVENTION

[0005] The invention is directed to a pin and slot design where the driving slots are moved from the blades or tips to the actuation rod in one aspect of the invention. As a result, the back end of each blade or tip can be dramatically reduced in area so that during full deflection, very little or no part of the blade or tip extends beyond the outside diameter of the outer tube or shaft. This ensures that nothing catches on the blades or tips during grasper use and the shrink tubing found on the scissors would not be deformed. This can be done because the area for the slots is not needed. Moreover, the usable area for

the drive slots on the blade or tip of the actuation rod is maximized to the overall diameter of the outer tube or shaft which provides additional leverage to the blades or tips. In addition, the depth of the slot can be varied such that increased tension can be placed on the blades or tips during actuation.

[0006] More specifically, the invention is directed to a surgical instrument comprising an elongate tube extending along an axis including an actuation rod coaxially slidable within the elongate tube, a first tip including a first pin formed on a proximal end surface of the first tip, and a second tip including a second pin formed on a proximal end surface of the second tip, the second tip pivotally connected to the first tip at a common pivot pin operably connected to the elongate tube to open and close the tips in response to movement of the actuation rod. With this aspect, the actuation rod has a slot to accept the pins of the first and second tips, the slot has camming surfaces for the pins to slide within the slot, and the proximal ends of the tips extend minimally outside the diameter of the elongate tube during actuation of the tips. In another aspect, the proximal ends of the tips do not extend outside the diameter of the elongate tube during actuation of the tips. The actuation rod can be formed by machining, stamping, overmolding, casting, or metal injection molding. The pins can be formed on the proximal end surfaces of the tips by press fitting, threading, welding or bonding. The actuation rod can be a tongue actuation rod or a fork actuation rod. With the fork actuation rod, the rod can include a through slot on each side of the rod, which may be curved and transverse to one another. The tongue actuation rod can also include two curved and transverse slots on opposing sides of the tongue. It is appreciated that the slots can be open-ended or closed-ended. As stated above, the slot may have a depth that varies along the length of the slot. In particular, the different depth of the slot provides different tension along the tip. In another aspect, the tongue actuation rod includes means for ratcheting the tips into a desired position; the ratcheting means may include a series of detents.

[0007] These and other features and advantages of the invention will become more apparent with a discussion of the embodiments in reference to the associated drawings.

DESCRIPTION OF THE DRAWINGS

[0008]

FIG. 1 illustrates a perspective view of a laparoscopic view of a surgical instrument of the prior art;
FIG. 2 illustrates a side cutaway view of a tool mechanism of the surgical instrument of FIG. 1 in the open position;
FIG. 3 is an exploded perspective view of FIG. 2;
FIGS. 4(a) - 4(c) illustrate a perspective view of a laparoscopic surgical instrument of the invention, a perspective view of a blade or tip of the tool mech-

anism of the invention, and a side view of FIG. 4(a), respectively;

FIG. 5 illustrates a perspective view of an assembled surgical instrument of the invention having mobile tips and an actuation rod;

FIGS. 6(a) and 6(b) illustrate a fork actuation rod and a tongue actuation rod of the invention, respectively; FIGS. 7(a) and 7(b) illustrate a perspective view and a side view of the fork actuation rod having slots on both sides of the fork end;

FIGS. 7(c) and 7(d) illustrate a perspective view and a side view of an actuation rod having a slot with an open end in accordance with another aspect of the invention;

FIGS. 7(e) and 7(f) illustrate a perspective view and a side view of an actuation rod having a curved slot in accordance with another aspect of the invention; FIGS. 8(a) and 8(b) illustrate a side view and a cross-section view of an actuation rod having an angled slot in accordance with another aspect of the invention;

FIG. 8(c) illustrates a slot in an actuation rod having a detent or elevation shift to temporarily lock or ratchet the tips into a desired position in accordance with another aspect of the invention;

FIG. 8(d) illustrates a slot in an actuation rod having a locking mechanism in accordance with another aspect of the invention;

FIG. 9 illustrates a perspective view of an assembled surgical instrument having a fixed tip and a mobile tip in accordance with another aspect of the invention; and

FIG. 10 illustrates an actuation rod that is split into at least two pieces to provide independent motion to the tips in accordance with another aspect of the invention.

DESCRIPTION OF THE INVENTION

[0009] Referring to FIG. 1, there is shown a perspective view of a laparoscopic surgical instrument 100 of the prior art as shown in U.S. Patent No. 5,626,609, which is incorporated herein by reference. The surgical instrument 100 typically comprises a handle assembly 10 having a fixed handle 12 and a pivoting handle 14. Extending from the handle assembly 10 is a shaft assembly 20 comprising an outer tube 22 and an inner actuation rod 24. The actuation rod 24 slides in the outer tube 20 in a coaxial relationship. The outer tube 22 may be secured to the fixed handle 12, while the actuation rod 24 may be secured to the pivoting handle 14. Attached at a distal end of the shaft assembly 20 is a tool mechanism 30, which comprises of a lower jaw 32 and an upper jaw 34. The tool mechanism 30 is connected to the shaft assembly 20 at pivot point 36 through linkage mechanism 40. During use, as the actuation rod 24 slides within the outer tube 22, the linkage mechanism 40 is actuated to pivot jaws 32 and 34 about pivot point 36 to open and close

the jaws.

[0010] Referring to FIGS. 2 and 3, there is shown a tool mechanism 30a of the prior art which includes, for example, a first scissor blade 32a and a second scissor blade 34a. In this embodiment, a housing member 50 is attached to the outer tube 22, and the tool mechanism 30a is attached to the housing member 50. As the handles move, the actuation rod 24 slides through the outer tube 22 towards the tool mechanism 30a. As illustrated in FIG. 2, scissor blades 32a, 34a are provided with cam slots 38 and 39, respectively, which slots accept a bearing post 60 which is attached to inner rod 24. As the rod 24 moves, the bearing post 60 slides within cam slots 38, 39 to pivot blades 32a, 34a about pivot pin 36a to open and close the blades. A drawback of this tool mechanism 30a is when the blades 32a, 34a are open, the tail end of the blades pass through slot 70 in housing member 50 to allow the blades to open. That is, the tail end of the blades 32a, 34a extend out beyond the outside diameter of the surgical instrument and look like "wings." This may be a problem for the user as they can catch or interfere on tissue or other devices during use. Moreover, when the blades 32a, 34a are open, the wings can stretch and deform the plastic shrink tubing that is used to insulate the shaft assembly 20. For example, this can be problematic in that when the instrument is withdrawn from a trocar after a procedure, the deformed tubing may not relax and it may catch on the end of the cannula, thereby pulling the trocar out of the patient.

[0011] Referring to FIGS. 4(a) - 4(c), there is shown a surgical instrument 200 in accordance with a first aspect of the invention having a tool mechanism 210 including a first blade or tip 212 and a second blade or tip 214, each of which has a pin 218 and 216, respectively, formed at the proximal end. The pins 218, 216 are fixed, typically by welding, to blades or tips 212, 214 and extend outwardly of the surface of the back end of the blades or tips 212, 214. The blades or tips 212, 214 are overlapped in a scissors configuration and are held in a pivotal relationship with an outer tube by a common pin 220. A novel feature of the invention is it includes the tool mechanism 210 that interacts with a slotted actuation rod 224 as further explained below. It is appreciated that because the blades or tips 212, 214 include pins 218, 216, rather than slots, much area is not needed on the back ends. This is beneficial because the "wingspan" of the blades or tips 212, 214 when opened is minimized if not eliminated. In addition, the overall strength of the blades or tips 212, 214 and the rod 224 is maximized because both the rod and the blades are integral or are single piece components.

[0012] The fork actuation rod 224 can be formed in a number of different ways. For example, the desired features can be machined from a solid rod or tube of a desired diameter. In another aspect, a strip of metal can be stamped with the desired slots at the end, then the tube can be rolled into a particular diameter where the slotted end can form a "fork". In yet another aspect, the fork

features at the end of the actuation rod can be overmolded onto a shaft to provide a cost effective component.

[0013] As to the tongue actuation rod, it can be formed in a similar way to the fork actuation rod. More specifically, machining the detail in the tip is an option as is overmolding the detail. The end of the actuation rod can also be formed as a separate part, i.e., molded, machined, cast, MIM, etc., with the feature detail in it and then attached to a standard length shaft by means of a thread, snap, adhesive, welding process or some other attachment method.

[0014] Referring to FIG. 5, there is shown a perspective view of the tool mechanism 210 of FIG. 4 being connected to the actuation rod 224. It is appreciated that there are numerous methods of manufacturing the blades or tips 212, 214. For example, the blades or tips 212, 214 can be formed from conventional stamping and then heat treated. In another example, the blades or tips 212, 214 can be formed from a blank of pre-hardened material and then EDM cut, waterjet cut, laser cut or even machined to obtain the final shape. It should be noted that pins 218, 216 in the back ends of the blades or tips 212, 214 can be formed directly onto the blades or pins themselves, or they can be added after the pins have been manufactured.

[0015] The pins 218, 216 can be locked in any one or a combination of the following ways: press-fitted, swaged, threaded and/or welded. To manufacture the pin as part of the blades or tips 212, 214, a multitude of processes can be used. A sheet of material can be machined to include a pivot hole as well as the pin. The sheet can then be heat treated and sent to a form grinder, which can grind one profile of the blade or tip. The ground plate can then be sent to be EDM cut and the second profile can be cut out. This type of process can yield numerous components, with the drive pin integrally located, with relatively low cost.

[0016] There are also additional processes that can yield the entire part from a minimum number of operations. These can include but are not limited to metal injection molding (MIM), casting, and powder metallurgy (PM). The final blade can also then be sent to be sharpened or other post processing.

[0017] The following is a discussion of the pin and slot design of the invention, where there are a number of advantages which can be realized. For example,

(1) The back end of each blade or tip is reduced in area so that during full deflection, very little or no part of the blade or tip extends beyond the outside diameter of the outer tube or shaft. This ensures that nothing catches on the blades or tips during grasper use and the shrink tubing found on scissors would not be deformed. This can be done because the area for the slots is not needed;

(2) The usable area for the drive slots on the blade or tip of the actuation rod is maximized to the overall diameter of the outer tube or shaft which provides

additional leverage to the blades or tips; and (3) If channels are used on the actuation rod, the depth of the channels can be varied such that increased tension can be placed on the blades during actuation.

[0018] Moreover, by moving the slot from the blades or tips to the actuation rod, the "wingspan" of the blades can be reduced or eliminated because the back end does not need to encase the slot, but rather a small pin which minimizes the chance of catching on tissue, other instruments or suture.

[0019] Referring to FIGS. 6(a) and 6(b), there are shown the end of the actuation rod which can be a fork design 224a or a tongue design 224b. With the fork design 224a, a through slot 226 can be formed on each side of the rod 224a. The back end of the blades or tips can be inserted into the rod where the pin of the first blade or tip can be locked into the first slot and the pin of the second blade or tip can be locked into the opposing second slot. The blades or tips can be fixed by a common pivot point on the outer tube or shaft. When the actuation rod is moved in one direction, the blades or tips will cam via the pins and the slots 226. The pin that locks each blade or tip into the shaft can be integral to the blades or tips or they can be separate components. Similarly to the fork design 224a, the tongue design 224b can include a slot 226 on each side of the tongue as further discussed below.

[0020] Referring to FIGS. 7(a) and 7(b), there are shown a perspective view and a side view of the actuation rod 224 incorporating slots 226 on both sides of the tongue end, respectively. As explained above, the blades or tips can have pins on the back end that nest in the slots of the rod. The rod may be pushed forward or pulled backwards to cam the blades or tips, which are pivoted by a common pivot point that is attached to the outer tube or shaft. In some cases, it is beneficial to have different slot designs to actuate the tips to different openings, at different speeds, for different length tips and for varying force. Referring to FIGS. 7(c) and 7(d), the slots 226 can include an open or closed end slot (or combination of both) as desired. FIGS. 7(e) and 7(f) illustrate an actuation rod having a curved slot in accordance with another aspect of the invention. It is appreciated that as the jaw providing the blades or tips of the invention articulates a pivot point, the distance between the pin and slot and the hinge vary depending on the actuation rod position. Accordingly, the curved slot of the invention can be used to compensate for this phenomenon and provide for a more linear relation between the actuation rod and the jaw motion. For example, the slot can be shaped to provide for more control as the blades or tips are nearing the closed position, and greater acceleration as the blades or tips are near the opened position. With this aspect, the instrument can be tuned to provide the desired instrument control and user feedback.

[0021] In another embodiment of the invention as illus-

trated in FIGS. 8(a) and 8(b), a slot 226b for the tongue can be formed such that it has an angle to it. In other words, the depth of the slot 226b at one end ('B') 227 may be deeper or shallower than at the other end ('A') 228. This is beneficial because as the actuation rod 224 is pulled, and the blades or tips close, the pins camming in the slots can be forced apart by the angle at the bottom surface of the slots. This would spread the back end of the blades or tips which in turn push the front of the blades or tips together putting more tension along the cutting surface.

[0022] In yet another aspect of the invention as illustrated in FIG. 8(c), there is shown a slot 226c having a detent or elevation shift 229 to temporarily "lock" or "ratchet" the blade or tip into a desired position without affecting the linear motion of the jaws relative to the handle actuation. FIG. 8(d) illustrates that a slot 226d can also be formed with different cross sections, e.g., slot 226d having a locking mechanism with a dovetail profile 230. With this embodiment, the mating pin on the blades or tips can match the slot to "lock" it in.

[0023] In another aspect of the invention as illustrated in FIG. 9, both blades or tips 212, 214 do not need to be mobile. That is, one blade 212 may be fixed while the other blade 214 may actuate. The mobile blade 214 may contain a pin 300 and an actuation rod 302 that would contain only one slot to actuate the blade 214.

[0024] Referring to FIG. 10, there is shown another aspect of the invention where the slots or channels 226 can be of any of the above-described design, however, the actuation rod is split into a plurality of multiple pieces 224c, 224d to provide independent motion to the blades or tips. This would be useful if the blades or tips need to be articulated at different speeds, or over different distances.

[0025] In accordance with further aspect of the invention, there is provided:

1. A surgical instrument, comprising:

an elongate tube extending along an axis including an actuation rod coaxially operable within the elongate tube;
a first tip including a first cam slot with a first camming surface; and
a second tip including a second cam slot with a second camming surface, the second tip pivotally connected to the first tip at a common pivot pin operably connected to the elongate tube to open and close the tips in response to movement of the actuation rod,
the actuation rod including a third slot to hold a floating drive pin, the floating drive pin being placed through the first and second cam slots, and the
proximal ends of the tips extend minimally outside the diameter of the elongate tube during actuation of the tips.

2. The surgical instrument of clause 1, wherein the proximal ends of the tips do not extend outside the diameter of the elongate tube during actuation of the tips.

3. The surgical instrument of clause 1, wherein the third slot is a vertical slot.

4. The surgical instrument of clause 1, wherein the elongate tube further comprises a floating drive pin slot at the proximal portion of the tube.

5. A surgical instrument, comprising: a shaft assembly extending along an axis including a rotatable outer shaft and a coaxial inner rod; a first tip including a first pin formed on a proximal end surface of the first tip; and a second tip including a second pin formed on a proximal end surface of the second tip, the second tip pivotally connected to the first tip at a common pivot pin operably connected to the shaft assembly to open and close the tips in response to movement of the outer shaft, the outer shaft having a slot to accept the pins of the first and second tips, the slot having camming surfaces for the pins to slide within the slot, and the proximal ends of the tips extend minimally outside the diameter of the shaft assembly during actuation of the tips.

6. The surgical instrument of clause 5, wherein the proximal ends of the tips do not extend minimally outside the diameter of the shaft assembly during actuation of the tips.

7. The surgical instrument of clause 5, wherein the tips are actuated by rotating the outer shaft.

8. The surgical instrument of clause 5, wherein the outer shaft is formed of a plurality of components.

9. The surgical instrument of clause 9, wherein the slot is a through slot or a channel.

10. The surgical instrument of clause 9, wherein the slot is curved.

11. The surgical instrument of clause 5, wherein the outer shaft further comprises a second slot transverse to the first slot to accept the second of the two pins of the first and second tips.

[0026] It will be understood that many other modifications can be made to the various disclosed embodiments without departing from the spirit and scope of the invention. For these reasons, the above description should not be construed as limiting the invention, but should be interpreted as merely exemplary of preferred embodiments.

Claims

1. A surgical instrument, comprising:

an elongate tube extending along an axis including an actuation rod coaxially slidable within the elongate tube;
a first tip including a first pin formed on a proximal

- end surface of the first tip; and
 a second tip including a second pin formed on
 a proximal end surface of the second tip, the
 second tip pivotally connected to the first tip at
 a common pivot pin operably connected to the
 elongate tube to open and close the tips in re-
 sponse to movement of the actuation rod,
 the actuation rod having a slot to accept the pins
 of the first and second tips, the slot having cam-
 ming surfaces for the pins to slide within the slot,
 and the proximal ends of the tips extend mini-
 mally outside the diameter of the elongate tube
 during actuation of the tips. 5 10
2. The surgical instrument of claim 1, wherein the prox- 15
 imal ends of the tips do not extend outside the diam-
 eter of the elongate tube during actuation of the tips.
3. The surgical instrument of claim 1, wherein the ac- 20
 tuation rod is formed by machining, stamping, over-
 molding, casting, or metal injection molding.
4. The surgical instrument of claim 1, wherein the ac-
 tuation rod is a tongue actuation rod or a fork actu-
 ation rod. 25
5. The surgical instrument of claim 4, wherein the fork
 actuation rod includes a through slot on each side
 of the rod. 30
6. The surgical instrument of claim 5, wherein the slots
 are curved.
7. The surgical instrument of claim 5, wherein the
 through slots are transverse to one another. 35
8. The surgical instrument of claim 4, wherein the
 tongue actuation rod includes two transverse slots
 on opposing sides of the tongue. 40
9. The surgical instrument of claim 8, wherein the slots
 are curved.
10. The surgical instrument of claim 5 or claim 8, wherein
 at least one of the slots is an open-end slot or a closed
 end slot. 45
11. The surgical instrument of claim 8, wherein the
 tongue actuation rod includes means for ratcheting
 the tips into a desired position. 50
12. The surgical instrument of claim 11, wherein the
 ratcheting means includes a series of detents.
13. The surgical instrument of claim 1, wherein the pins 55
 are formed on the proximal end surfaces of the tips
 by press fitting, threading, welding or bonding.
14. The surgical instrument of any preceding claim,
 wherein the proximal ends of the tips do not extend
 outside the diameter of the elongate tube during ac-
 tuation of the tips.










FIG. 2
PRIOR ART

FIG. 3
PRIOR ART










FIG. 6A




FIG. 6B





FIG. 7C





FIG. 7D

FIG. 7E





FIG. 7F

FIG. 8A





FIG. 8B





FIG. 8C








FIG. 8D








FIG. 10



EUROPEAN SEARCH REPORT

Application Number
EP 08 17 0110

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	DE 200 01 492 U1 (AESCULAP AG & CO. KG) 21 June 2000 (2000-06-21) * page 7 - page 11 * * figures 2-5 *	1-10,13, 14	INV. A61B17/28 A61B17/32
X	DE 201 21 161 U1 (OLYMPUS WINTER & IBE GMBH) 4 April 2002 (2002-04-04) * page 1 - page 7 * * figure 1 *	1-10,13, 14	
X	US 5 496 347 A (HASHIGUCHI ET AL) 5 March 1996 (1996-03-05) * column 5, line 23 - column 11, line 59 * * figures 1-23 *	1-10,13, 14	
X	US 6 007 561 A (BOURQUE ET AL) 28 December 1999 (1999-12-28) * figures 1-5,7-10 * * column 3, line 22 - column 5, line 7 * * column 6, line 21 - column 7, line 24 *	1-10,13, 14	
A	DE 203 09 774 U1 (AESCULAP AG & CO. KG) 2 October 2003 (2003-10-02) * page 9, line 2 - page 13, line 26 * * figures 1-4 *	5-7	TECHNICAL FIELDS SEARCHED (IPC) A61B
4 The present search report has been drawn up for all claims			
Place of search The Hague		Date of completion of the search 17 December 2008	Examiner Compos, Fabien
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03.82 (P04C01)



Application Number

EP 08 17 0110

CLAIMS INCURRING FEES

The present European patent application comprised at the time of filing claims for which payment was due.

☐ Only part of the claims have been paid within the prescribed time limit. The present European search report has been drawn up for those claims for which no payment was due and for those claims for which claims fees have been paid, namely claim(s):

☒ No claims fees have been paid within the prescribed time limit. The present European search report has been drawn up for those claims for which no payment was due.

LACK OF UNITY OF INVENTION

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

☐ All further search fees have been paid within the fixed time limit. The present European search report has been drawn up for all claims.

☐ As all searchable claims could be searched without effort justifying an additional fee, the Search Division did not invite payment of any additional fee.

☐ Only part of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the inventions in respect of which search fees have been paid, namely claims:

☐ None of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the invention first mentioned in the claims, namely claims:

☐ The present supplementary European search report has been drawn up for those parts of the European patent application which relate to the invention first mentioned in the claims (Rule 164 (1) EPC).

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 08 17 0110

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

17-12-2008

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 20001492	U1	21-06-2000	NONE
DE 20121161	U1	04-04-2002	NONE
US 5496347	A	05-03-1996	NONE
US 6007561	A	28-12-1999	AU 733633 B2 17-05-2001
		AU 6144298 A	26-08-1998
		BR 9807202 A	04-12-2001
		CA 2280486 A1	13-08-1998
		EP 1011463 A1	28-06-2000
		JP 2001510381 T	31-07-2001
		WO 9834543 A1	13-08-1998
		US 5893874 A	13-04-1999
DE 20309774	U1	02-10-2003	NONE

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 5626609 A [0009]

专利名称(译)	用于致动腹腔镜手术器械的系统和方法		
公开(公告)号	EP2022417A1	公开(公告)日	2009-02-11
申请号	EP2008170110	申请日	2005-02-17
[标]申请(专利权)人(译)	应用医疗资源		
申请(专利权)人(译)	应用医疗资源CORPORATION		
当前申请(专利权)人(译)	应用医疗资源CORPORATION		
[标]发明人	JOHNSON GARY MR ALHBERG RUSSELL E OKIHISA DAVID BAK BOYCHUCK GREGORY I		
发明人	JOHNSON, GARY MR ALHBERG, RUSSELL E OKIHISA, DAVID BAK-BOYCHUCK, GREGORY I		
IPC分类号	A61B17/28 A61B17/32 A61B17/04		
CPC分类号	A61B17/3201 A61B17/1608 A61B17/29 A61B17/32 A61B17/320016 A61B2017/2932 A61B2017/2934 A61B2017/2936		
优先权	60/548747 2004-02-27 US		
其他公开文献	EP2022417B1		
外部链接	Espacenet		

摘要(译)

本发明涉及一种销和槽设计，其中在本发明的一个方面中，驱动槽从尖端移动到致动杆。结果，每个叶片或尖端的后端的面积可以显著减小，使得在完全偏转期间，叶片或尖端的很少或没有部分延伸超过轴的外径。这确保了在抓紧器使用期间刀片或尖端上没有任何物体卡住，并且剪刀上的收缩管不会变形。这可以完成，因为不需要插槽的区域。此外，刀片或致动杆尖端上的驱动槽的可用区域最大化为外管或轴的总直径，这为刀片或尖端提供了额外的杠杆作用。另外，每个槽的深度可以改变，使得在致动期间增加在切割过程中，可以在刀片或尖端上施加张力。更具体地，本发明的手术器械包括沿轴线延伸的细长管，所述轴包括在细长管内可同轴滑动的致动杆，第一尖端包括形成在第一尖端的近端表面上的第一销，第二尖端包括形成在第二尖端的近端表面上的第二销，第二尖端在公共枢轴销处可枢转地连接到第一尖端，该公共枢轴销可操作地连接到细长管以响应于致动杆的运动而打开和关闭尖端。致动杆具有用于接纳第一和第二尖端的销的槽，该槽具有凸轮表面，用于销在槽内滑动，并且尖端的近端在致动期间最小地延伸到细长管的直径之外。提示。




FIG. 5