



(11)

**EP 2 528 512 B1**

(12)

## EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention  
of the grant of the patent:  
**11.04.2018 Bulletin 2018/15**

(21) Application number: **11737828.1**

(22) Date of filing: **31.01.2011**

(51) Int Cl.:  
**A61B 17/122** <sup>(2006.01)</sup> **A61B 17/128** <sup>(2006.01)</sup>

(86) International application number:  
**PCT/US2011/023205**

(87) International publication number:  
**WO 2011/094700 (04.08.2011 Gazette 2011/31)**

### (54) **SURGICAL CLAMP**

CHIRURGISCHE KLEMME

PINCE CHIRURGICALE

(84) Designated Contracting States:  
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB  
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO  
PL PT RO RS SE SI SK SM TR**

(30) Priority: **29.01.2010 US 299725 P**

(43) Date of publication of application:  
**05.12.2012 Bulletin 2012/49**

(73) Proprietor: **Advanced Bariatric Technology, LLC**  
**Coral Gables, FL 33134 (US)**

(72) Inventors:  
• **JACOBS, Moises**  
**Miami, FL 33156 (US)**  
• **ARMENTEROS, Jesús, R.**  
**Santo Domingo (DO)**  
• **BARKER, Garrett**  
**Meridian, TX 76665 (US)**  
• **FRENCH, C., Kenneth**  
**Cranfills Gap, TX 76376 (US)**

(74) Representative: **Müller Schupfner & Partner**  
**Patent- und Rechtsanwaltspartnerschaft mbB**  
**Schellerdamm 19**  
**21079 Hamburg (DE)**

(56) References cited:  
**EP-A2- 0 220 643 EP-A2- 1 600 108**  
**WO-A1-00/78234 WO-A1-98/33437**  
**WO-A1-99/11179 DE-U1- 29 822 558**  
**US-A- 4 274 415 US-A- 5 156 609**  
**US-A- 5 236 437 US-A1- 2005 216 042**  
**US-A1- 2008 033 457 US-A1- 2008 275 480**  
**US-B2- 7 261 725**  
  
• **KAPCZYNSKI.: 'Surgical Instruments 101An**  
**Introduction to KMedic Certified Instruments',**  
**[Online] 1997, page B6, XP008172530 Retrieved**  
**from the Internet:**  
**<URL:http://Jwww.teleflexmedicaloem.com/pdf/**  
**surgical\_instruments.pdf> [retrieved on**  
**2011-03-20]**

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

**EP 2 528 512 B1**

## Description

**[0001]** The present disclosure relates generally to surgical clamps and surgical clamp installation tools.

## BACKGROUND

**[0002]** Recently, there has been increased interest in employing surgical clamps to partition sections of a stomach. An example of a bariatric surgical clamp can be found in Jacobs et al., U.S. Patent Application No. 1 1/984,452 and Jacobs et al., U.S. Patent Application No. 1 1/797,537. EP 0220643 A2 discloses a surgical clip and installation device. EP 1600108 A2 discloses a device and clamp for occluding a hollow anatomical structure. WO 98/33437 A1 discloses a surgical instrument for clamping onto tissue of a patient. WO 00/78234 A1 discloses replaceable pads having a mesh for use with surgical clamps. US 2008/033457 A1 discloses a system for occluding an endocardial surface with a ring or clip occluder. DE 29822558 U1 discloses a u-shaped clip. US 5156609 discloses an endoscopic stapling device for closing internal openings in a patient. WO 99/11179 A1 discloses a surgical clamp having improved traction devices on opposing jaws of the clamp. US 4274415 discloses a surgical clip and tool for stopping circulation of blood in a blood vessel.

## SUMMARY

**[0003]** The surgical clamp of the present invention is described in claim 1. Preferred embodiments are disclosed in the sub-claims. In one embodiment, a surgical clamp is configured to operate with an installation tool. The clamp includes two elongated members with a bight portion that joins the two elongated members at a proximal end of the clamp and is configured to bias the two elongated members in an open position at a distal end of the clamp. The bight portion has one or more engagement features. A clasp mechanism at the distal end of the clamp includes a male component or first component disposed on one of the two elongated members and a female component or second component disposed on the other of the two elongated members at the distal end. The installation tool may include an elongated member with a proximal end and a distal end that has an engagement feature. A handle in this one embodiment may be connected to the proximal end of the installation tool, while a head at the distal end may be configured to receive and/or engage the proximal end of the clamp and may also be operable to articulate in at least one plane.

**[0004]** Further embodiments and apparatuses, including other areas of applicability, will become apparent from the description provided herein.

## DRAWINGS

**[0005]** For a more complete understanding of various

embodiments of the present invention and the advantages thereof, reference is now made to the following brief description, taken in connection with the accompanying drawings and detailed description, wherein like reference numerals represent like parts, in which:

Figure 1 is a view of an embodiment of a surgical clamp engaged with a surgical clamp installation tool having an articulating head;

Figure 2 is a set of views illustrating engagement of the surgical clamp to the articulating head of the surgical clamp installation tool at Figures 2(a), 2(b), and 2(c), and actuation of the clamp at Figure 2(d) to a closed position at Figure 2(e), and illustrating a six-sided view of the clamp, including a top view at Figure 2(f), a left side view at Figure 2(g), a bottom view at Figure 2(h), a right side view at Figure 2(i), a view facing the distal end at Figure 2(j), and a view facing the proximal end at Figure 2(k);

Figure 3 is a set of views illustrating the surgical clamp installation tool from six sides with the right side of the housing of the handle shown removed, including a left side view at Figure 3(a), a top view at Figure 3(b), a right side view at Figure 3(c), a bottom view at Figure 3(d), a view facing the distal end at Figure 3(e), and a view facing the proximal end at Figure 3(f);

Figure 4(a) is a perspective view illustrating an exemplary surgical clamp installation tool with the right side of the housing of the handle shown removed; Figures 4(b), 4(c), 4(d), and 4(e) provide side cutaway views of various aspects of an example of the surgical clamp installation tool;

Figure 5 is a view of another embodiment of a surgical clamp engaged with another example of a surgical clamp installation tool having an articulating head;

Figure 6A is a top view of a rigid member having a male clasp end for the clamp of Figure 5;

Figure 6B is a side view of the rigid member of Figure 6A having the male clasp end for the clamp of Figure 5;

Figure 6C is a side view showing the male clasp end of Figure 6B in greater detail;

Figure 6D is a cross-sectional view showing a cross-section of the rigid member of Figure 6A.

Figure 7A is a top view of a rigid member having a female clasp end for the clamp of Figure 5;

Figure 7B is a side view of the rigid member of Figure 7A having the female clasp end for the clamp of Figure 5;

Figure 7C is a side view showing the female clasp end of Figure 7B in greater detail;

Figure 7D is a cross-sectional view showing a cross-section of the rigid member of Figure 7A.

Figure 8A is a top view of a spring member of the clamp of Figure 5;

Figure 8B is a side view of the spring member for

the clamp of Figure 5;

Figure 8C is a cross-sectional, close-up view showing a cross-section of the spring member of Figure 8B;

Figure 8D is a proximal end view of the spring member of Figure 5;

Figure 9A is a side view of the clamp of Figure 5;

Figure 9B is a bottom view of the clamp of Figure 5;

Figure 9C is a proximal end view of the clamp of Figure 5;

Figure 9D is a perspective view of the clamp of Figure 5;

Figure 10 is a view illustrating the surgical clamp installed in a substantially vertical position on a human stomach;

Figure 11 is a flow diagram illustrating an example of a method for clamping an internal organ, the method not forming part of the claimed invention;

Figure 12 is a flow diagram illustrating another example of a method for clamping an internal organ;

Figure 13 is a view of yet another embodiment of a surgical clamp engaged with yet another example of a surgical clamp installation tool having an articulating head;

Figure 14 is a perspective view of the surgical clamp of Figure 13.

Figure 15(a) is a top view of the surgical clamp of Figure 14.

Figure 15(b) is a left view of the surgical clamp of Figure 14.

Figure 15(c) is a bottom view of the surgical clamp of Figure 14.

Figure 15(d) is a right view of the surgical clamp of Figure 14.

Figure 15(e) is a proximal spring end on view of the surgical clamp of Figure 14.

Figure 15(f) is a distal latch end on view of the surgical clamp of Figure 14.

Figure 16 is a detailed view of a latch end of a bottom arm of the surgical clamp of Figure 14.

Figure 17(a) is a top view of the surgical clamp installation tool of Figure 13.

Figure 17(b) is a left view of the surgical clamp installation tool of Figure 13.

Figure 17(c) is a bottom view of the surgical clamp installation tool of Figure 13.

Figure 17(d) is a right view of the surgical clamp installation tool of Figure 13.

Figure 17(e) is a proximal handle end on view of the surgical clamp installation tool of Figure 13.

Figure 17(f) is a distal head end on view of the surgical clamp installation tool of Figure 13.

Figure 18 is a detailed left side view of a handle end of the surgical clamp installation tool Figure 13 in which the left side of the handle housing is shown removed.

Figure 19 is a perspective view of the surgical clamp of Figure 14 having a silicone sleeve engaged there-

with.

Figure 20 is a perspective view of the silicone sleeve of Figure 19 in a disengaged state.

Figure 21 is a bottom view of the silicone sleeve of Figure 20.

Figure 22 is a proximal end-on view of the silicone sleeve of Figure 20.

Figure 23 is a top view of the silicone sleeve of Figure 20.

Figure 24 is a left side view of the silicone sleeve of Figure 20.

Figure 25 is a cross-sectional view of a distal end of the silicone sleeve of Figure 23.

Figure 26 is a cross-sectional view of a proximal end of the silicone sleeve of Figure 24.

Figure 27 is a cross sectional view of a proximal end of Figure 23.

Figure 28 is a flow diagram illustrating a method of performing endoscopic surgery utilizing the silicone sleeve, clamp, and installation tool of Figures 13-27.

**[0006]** For Figures 5-9, dimensions are given in inches. However, it should be understood that various embodiments are not limited to the dimensions provided. Such dimensions are purely illustrative. It is noted that one inch corresponds to 25.4 mm. For Figures 4(b), 4(c), 17(a)-17(d), 21, 23, and 24, broken lines indicate variability in length of the discontinuous portions.

#### DETAILED DESCRIPTION

**[0007]** The following description is merely exemplary in nature and is not intended to limit the present disclosure, application, or uses. Additionally, the drawings contained herein are not drawn to scale, and may be provided in a variety of different dimensions, shapes and configurations. Any provided dimensions are provided only to illustrate a particular exemplary implementation, and in no way construed to limit the present invention absent an explicit recitation of such dimensions and then only with respect to the claim or claims reciting the dimension or dimensions.

**[0008]** Referring to Figure 1, an embodiment of a surgical clamp 100 engages with an example of a surgical clamp installation tool 102. In these embodiments, the clamp 100 and the installation tool 102 are designed for performing bariatric surgery through a surgical trochar. The clamp 100, in a preferred embodiment, may be approximately fifteen to thirty centimeters in length to accommodate partitioning of a human stomach. To accommodate insertion through a trochar, the closed clamp 100 will preferably have a diameter or circumference less than fifteen millimeters over the entirety of its length or along the majority of its length. A non-handle section of the installation tool 102 intended for insertion through the trochar has a similar diameter or a smaller diameter. It is envisioned that other embodiments of the clamp and examples of the installation tool can be of other sizes. It

is additionally envisioned that the clamp may be articulated in at least one plane to provide different angles and lengths of partition to the stomach. It is also envisioned that other embodiments of the clamp examples of the installation tool can be for clamping other parts of the human body and/or for clamping other types of bodies or structures.

**[0009]** Referring to Figure 2, the surgical clamp 100 has two elongated members 104A and 104B. A bight portion 106 joins the two elongated members at a proximal end of the clamp 100 and biases the two elongated members in an open position at a distal end of the clamp 100. As used herein, a bight is a loop, bend, hinge, corner angle, hollow, fold, or similar structure. The bight portion has a slotted aperture 108 such as that shown in Figure 2(b). A clasp mechanism, has a male component 110 disposed on one of the two elongated members at the distal end, and a female component 112 disposed on the other of the two elongated members at the distal end.

**[0010]** Particularly to partially partition a stomach in performing bariatric surgery, spacing between the two elongated members 104A and 104B effects two or more clamp sections as best shown in Figure 2(e). At least one of the sections is a partition forming section 105A located nearer the distal end of the clamp 100 than the proximal end of the clamp 100. At least another of the sections is a passage forming section 105B located nearer the proximal end of the clamp 100, such as near the bight portion 106, than the distal end of the clamp 100.

**[0011]** In order to reduce injury to the partitioned organ, a padding material 116 is connected to one or more of the two elongated members. For example, padding material 116 can connect to the elongated member 104B at least at a location corresponding to at least part of the partition forming section. In some embodiments, the padding material can be composed predominantly of silicone or fully of silicone. It is also envisioned that the opposing limbs of the clamp may be fitted with magnets to facilitate closure. The engagement feature at the proximal end of the clamp 100 is a slotted aperture 108 as shown in Figure 2(b) having a width and a length larger in size than the width. The length of the slotted aperture is oriented perpendicular with reference to a longitudinal axis of the clamp 100. It is envisioned that other types of engagement features can be employed, such as a socket, a loop, a hook, a clasp, a string, magnetic, etc.

**[0012]** In some embodiments, the male component 110 of the clasp at the distal end of the clamp can be an end of the elongated member 104A that flares away from a longitudinal axis of the clamp when the clamp is forced to a closed position. Accordingly, the female component 112 can be a loop attached to the end of the elongated member 104B and disposed to engage the male component 110 of the elongated member 104A when the clamp is forced to the closed position. This can be seen more clearly in connection with Figure 2(e). It is envisioned that other types of clasp components can be employed, such as those found in a hinge, such as a living hinge, hook

and loop, spring ring, lobster or trigger, toggle, tube, bolt and bolt hole, screw and threaded aperture, or any other type of closure arrangement.

**[0013]** Returning to Figure 1 and referring generally to both Figure 1 and Figure 2, the clamp 100, in use, engages with the installation tool by the slotted aperture 108. For example, the installation tool 102 has an elongated member, such as a pull-rod 138, having a proximal end and a distal end that has an engagement feature. The distal end of the elongated member of the installation tool 102 engages with the proximal end of the clamp 100 through the slotted aperture 108 of the bight portion 106. In some examples the engagement feature takes the form of a T-bar 118. This T-bar 118 is sized and shaped to allow insertion thereof through the slotted aperture 108 to engage the clamp 100.

**[0014]** The installation tool 102 may include a lever radially engaged with the pull-rod at its proximal end at a handle 122 that may be configured as a thumbwheel 120 that extends out of the handle 122 of the installation tool 102 through an aperture. While the T-bar 118 is inserted through the slotted aperture 108, actuating the thumbwheel 120 can cause the T-bar 118 to rotate ninety degrees as illustrated in one embodiment from a first position shown in Figure 2(c) and in a second position as shown in Figure 2(d).

**[0015]** At this point, retracting the pull rod, which may be achieved by squeezing a trigger 128 to retract the pull rod, forces the proximal end of the clamp 100 up against and progressively further between guide members of the surgical clamp installation tool 102, such as a pair of wedges 124A and 124B, formed in the articulating head of the installation tool 102. A curvature or incline imparted to the articulating head of the installation tool 102 by the pair of wedges can be keyed to a curvature or incline of the bight portion 106 of the clamp 100 in such a way that fully or more fully retracting the pull-rod forces the normally open clamp 100 to a closed position such as that shown in Figure 2(e).

**[0016]** Turning to Figures 2(f) - 2(k), the various clamp features can be readily appreciated. These features include bight portion 106, slotted aperture 108, male component 110, female component 112, and padding material 116. It should be readily understood that the padding material 116 can be configured as a pair sleeves as shown, but that other configurations may also be employed. Moreover, non-linear shapes may be utilized for various types of applications in clamping various types of organs, as desired.

**[0017]** Turning now to Figure 3 and referring generally to Figure 1 and Figure 3, retraction of the pull-rod of the installation tool 102 is accomplished by actuation or movement of another lever or trigger that is engaged to the proximal end of the pull-rod, such as through an axial engagement. This lever can be configured as the trigger 128 that extends out of the handle 122 through an aperture or slotted opening. The shape of the handle and disposition of the trigger are, preferably, ergonomically

configured to allow the surgeon to hold the installation tool parallel to the ground near waist level to grip the handle 122 and the trigger 128 in one hand. The thumbwheel 120 is disposed to be within easy reach of the thumb of that hand to facilitate holding of the clamp 100 by the surgeon in the other hand while engaging the clamp to the articulating head 126. The thumbwheel 120 may be conveniently adjusted to rotate the T-bar 118 to a desired position to lock the T-bar 118 to the clamp 100 at the bight portion 106 through the slotted aperture 108. In one embodiment, the thumbwheel 120 may rotate the T-bar 118 by ninety degrees.

**[0018]** Once the surgeon has rotated and retracted the pull-rod using T-bar 118 and trigger 128 with one hand, the surgeon's other hand becomes free for other tasks, such as actuating yet another lever protruding from the handle 122 and configured, for example, as a dial 130. With the clamp 100 pulled closed or partially closed against the pair of wedges, the head 126 can be articulated from side to side by rotating this dial 130. The motion of the articulating head 126 through rotation of the dial 130 is illustrated in one embodiment in the top view of the installation tool 102 in Figure 3(b) at arrow 300 showing a range of motion or articulation in one embodiment.

**[0019]** Turning now to Figure 4, in some embodiments, turning the dial 130 can turn a hub 132 or connector inside or adjacent the handle 122 that is connected to a pair of guidelines 134A and 134B. These guidelines 134A and 134B, together with pull-rod 138, may extend through an elongated, rigid sleeve, such as a cylindrical tube 136, for connection on either side of a swivel mount of the articulating head 126. It is envisioned that the guidelines can be flexible or rigid, that the cylindrical tube 136 can be rigid or semi-rigid, and that the pull-rod 138 can be rigid or semi-rigid. By semi-rigid, it is meant that the pull-rod 138 can be flexible or partially flexible at least in the plane of articulation along at least part of its length near the distal end of the installation tool 102, but still axially and rotationally rigid or semi-rigid along its length. Thus, when the installation tool 102 and clamp 100 are held parallel to the ground, the pull-rod 138 can be rotated and retracted by actuation of the thumbwheel 120 and trigger 128, and the head 126 can be articulated in a plane orthogonal to the gravity vector by manipulation of the dial 130. The plane of articulation may be adjustable in certain embodiments, or may be set in a desired plane that is not orthogonal to the gravity vector.

**[0020]** Turning now to Figure 5, other embodiments of the clamp 200 and installation tool 202 can include a clamp 200 made of multiple pieces, a longer main tube 204, and a thumb lever 206 on the dial 130 to articulate the head of the tool 102 that is attached to the clamp 200. In some embodiments, the clamp 200 can be a three-piece clamp. A ratchet release 208 can also be provided on the installation tool 202 that, when pressed, allows the pull rod to extend, which in turn will release the clamp 200 allowing it to reopen. In other words, as the surgeon presses on the trigger 210, causing the pull-rod to retract

and the clamp 200 to close, a ratchet mechanism catches the trigger 210 in the pressed in position. Thus, the pull-rod will remain retracted and clamp 200 will not reopen even if the surgeon releases pressure on the trigger 210.

**[0021]** Turning now to Figure 6, and referring generally to Figures 6A-6D, one piece of a three-piece clamp can be a rigid member 212 having a male clasp end 214. As will be described further below with reference to Figure 9, this rigid member 212 serves as one of the elongated members of the clamp 200 for forming the partition that divides the stomach. It can be made of plastic, metal, or any other rigid material. An example material is hardened titanium. Figure 6(c) demonstrates an exemplary contour of male clasp end 214, while Figure 6(d) demonstrates an exemplary contour rigid member 212. It should be readily understood that the exemplary contour of rigid member 212 renders it concave on an inner surface to be disposed toward an outer surface of an organ to be clamped, and convex on an outer surface for engagement with a spring component. However, other shapes may be used as desired.

**[0022]** Turning next to Figure 7, and referring generally to Figures 7A-7D, another piece of the three-piece clamp can be a rigid member 216 having a female clasp end 218 that includes a hinged loop 220. As will be described further below with reference to Figure 9, this rigid member 216 serves as one of the elongated members of the clamp for forming the partition that divides the stomach. It can be made of plastic, metal, or any other rigid material. An example material is hardened titanium. Similarly, the loop 220 can be made of various materials, an example of which is titanium wire.

**[0023]** Turning next to Figure 8, and referring generally to Figures 8A-8D, a third piece of the three-piece clamp can be a spring member 222 having a slotted bight portion 224. As will be further described below with reference to Figure 9, the spring member engages with the rigid members to form the clamp and provides the bight portion that permits formation of a passage between the two partitioned regions of the clamped stomach. It can be made of plastic, metal, or any other springy material. An example material is spring tempered titanium.

**[0024]** Turning now to Figure 9, and referring generally to Figures 9A-9D, the three-piece clamp can be assembled by engaging the rigid members 212 and 216 to the spring member 222. For example, the rigid members can be welded or coupled to arms of spring member at various locations 226. In one embodiment, the rigid members 212 and 216 can be attached to interior surfaces of the arms of spring member 222, with the loop 220 arranged to hinge towards and engage the male clasp end 214 of the distal end of rigid member 212. Thus, the rigid members 212 and 216 are employed to form a partition, while the spring member 222 forms a passage between the partitioned regions of an organ or body as shown in Figure 10. These rigid members 212 and 216 may be of non-uniform thickness to accommodate gradual closing of the clamp from the proximal end towards the distal end in

such a manner that a non-uniform thickness of an organ, such as walls of a stomach, can be clamped without injury. Alternatively or additionally, sleeves of padding material can be slid over the arms of the clamp, and the padding material can be of non-uniform thickness as desired. It is envisioned that rigid members 212 and 216 and padding material of varying lengths, contours, and thicknesses may be provided to accommodate needs of different patients as desired.

**[0025]** Turning now to Figure 10, some examples of the surgical clamp installation tool can be used to install the clamp 100 within an abdominal cavity in order to perform bariatric surgery. In particular, the clamp can be positioned, closed, and latched to partition the stomach into a small vertical pouch 500 and an excluded section 502. The vertical pouch 500 receives food at 504, but the food is not able to enter the excluded section 502. Using the installation tool 102 (or 202) to engage with the bight portion 106 of the clamp 100, the clamp 100 may be installed in a substantially vertical position on the stomach in one embodiment. That is, if the human patient having the clamp 100 installed were to stand upright, the longitudinal axis of the clamp 100 would be substantially parallel to the gravity vector. Thus, a passage forming section formed in the bottom of the stomach by the clamp allows gastric juices to flow at 506 from the excluded section 502 into the vertical pouch 500.

**[0026]** Turning to Figure 11, a method for clamping an internal organ can include inserting a surgical clamp through an opening into a body of a living organism at block 150. Then the two elongated members of the surgical clamp are positioned on opposite sides of an internal organ of the living organism at block 152. At block 154, closing and latching the surgical clamp to partition a cavity inside the internal organ includes clamping the exterior of the internal organ with the two elongated members.

**[0027]** As mentioned above, the internal organ can be a human stomach. In this case, closing and latching the clamp can include installing the clamp in a substantially vertical or angled position with a passage forming section of the clamp located towards a bottom of the stomach. This positioning can create a small, vertical stomach pouch and thereby limit the intake of food into an excluded section or portion of the stomach, but still allow gastric juices from the excluded portion of the stomach to flow into the vertical stomach pouch. This partitioning can alter the production of hormones, enzymes and chemicals that affect metabolism, energy levels, hunger, digestion, and absorption of nutrients that are affected by exclusion of gastric fundus and body of the stomach by the partitioning. Sheathing the elongated members of the clamp in silicone padding material along a majority of their length is intended to reduce trauma and/or necrosis of the stomach or other internal organ and enable successful reversal of the surgery. Thus, the method can further include reversing the surgery by removing the clamp.

**[0028]** Inserting the surgical clamp can include performing natural orifice transluminal endoscopic surgery

(NOTES). Alternatively, or additionally, it can include performing a combination of NOTES and an assistant trochar placed into an abdominal cavity. This combination can include two or more of a conventional, laparoscopic, NOTES, and one port technique. The NOTES technique can include at least one of transgastric, transvaginal, transrectal, transcolonic, or combinations thereof. The one port technique is used for the introduction of several instruments, and encompasses a one port abdominal (including umbilical), perineal, retroperitoneal approaches, or combinations thereof.

**[0029]** Turning to Figure 12, a method for clamping an internal organ can include engaging a surgical clamp to a head of a surgical clamp installation tool at block 160. At block 162, the surgical clamp installation tool can be employed to close the clamp and insert the clamp through an opening in a body cavity of a living organism. Then the tool can be employed at block 164 to reopen the clamp and to position elongated members of the clamp on opposite sides of an internal organ within the body cavity. Next, at block 166, the tool can be employed to close the clamp upon the internal organ and thereby partition a cavity inside the internal organ. The limbs, arms, or elongated members of the clamp close in such a fashion as causing a gradual diminishing space between the two limbs, as the space opening extends proximally, accounting for the different thickness of the stomach. The clamp closes in a fashion that exerts enough pressure to maintain the opposite walls closed to each other without creating damage/trauma/ischemia to the stomach or other organ walls themselves. Then at block 168, the clamp can be latched to fix it in position to partition the internal organ and the cavity inside the internal organ. Also, at block 170, the clamp can be disengaged from the head of the surgical clamp installation tool, and the tool can be retracted from the body cavity at block 172. It is envisioned that the clamp may be configured to latch automatically when the clamp is fully closed. Alternatively, the tool may first be disengaged and removed, and the clamp subsequently latched using an additional tool. Moreover, additional steps may be employed to secure the clamp in place, such as using sutures.

**[0030]** As already described above, padding material can be employed on surfaces of the elongated members of the surgical clamp to reduce damage to the internal organ that would prevent reversal of the surgical procedure. In other embodiments, the thickness or surface contour of the elongated members or arms of the surgical clamp may be provided to align with the particular organ or body being clamped so as to provide the desired pressure or force at each location of the organ or body being clamped. Additionally, engaging the surgical clamp to the head of the surgical clamp installation tool may include passing a T-bar adjacent the end of a pull rod of the installation tool through a slotted aperture formed in a bight portion of the clamp, and rotating the T-bar using a lever or dial. Also, employing the surgical clamp installation tool to close and reopen the clamp may include operating

a lever or trigger on a handle of the installation tool to pull and release the pull rod. Further, employing the surgical clamp installation tool to position the elongated members of the surgical clamp may include manipulating a dial on a handle of the installation tool to articulate the head from side to side in a desired plane(s).

**[0031]** Turning now to Figure 13, another embodiment of a surgical clamp 600 and surgical installation tool 602 is similar in structure and function to those embodiments described above. One notable difference from the embodiments previously described is that the articulating head 604 of the surgical installation tool 602 is keyed with a curvature or radius configured to hold the clamp 600 securely in place while permitting the clamp 600 to remain in an open position. This configuration permits a surgeon holding the installation tool 602 in one hand to hold the clamp 600 securely in the articulating head 604 of the tool 602 while pressing the distal ends of the clamp 600 together with the other end for entry to a trochar. Once the distal ends of the clamp 600 have entered the trochar, the trochar then holds the ends shut, and permitting the surgeon free use of the other hand. Upon entry to the abdominal cavity, the clamp naturally springs open for engagement with a bodily organ, such as the stomach, and the surgeon can articulate the head from side to side while it is held securely in the head 604 while still in the open position. Once in position, the surgeon can close the clamp using sutures and/or by applying pressure externally or internally using other surgical tools. Thus, the installation tool 602 may not be employed to close the clamp on an internal organ of the patient, but may be employed to hold, insert, and articulate the clamp into position.

**[0032]** Referring now to Figure 14, clamp 600 can have a three piece design similar to that described above. In other words, it can have a spring member 606 that is comprised predominantly of spring steel, and that is engaged with lower and upper rigid members 608 and 610. These rigid members 608 and 610 can be comprised primarily of titanium, and they can have a concavity that increases their rigidity. In addition, suture holes 612A-612E can be provided in upper rigid member 610, as well as in an upper portion of spring member 606. A surgeon can employ these suture holes 612 to secure the clamp 600 in place on a stomach or other bodily organ. It is envisioned that additional or alternative suture holes 612 can be provided, such as in lower rigid member 608 and lower portion of spring member 606, and that positions of the suture holes 612 can be different from those shown. However, as will be more fully described below with reference to Figures 19-27, the placement of suture holes in the upper rigid member 608 and upper portion of spring member 606 can permit suturing of the clamp 600 in place prior to application of a silicone sleeve (see Figures 19-27) that slides onto the clamp via the un-sutured lower rigid member 608 and lower portion of spring member 606. Yet, once the sleeve is installed, it should be understood that additional suture holes 612 provided in lower

rigid member 608 and/or lower portion of spring member 606 may prove useful in a subsequent application of additional sutures.

**[0033]** Turning now to Figures 15(a)-15(f) and referring generally thereto, it should be appreciated that a double row of suture holes 612A-612H can be provided in spring member 606 and upper rigid member 610, a distal portion of which can exhibit a male clasp feature 614 positioned to engage a female clasp feature, such as a wire loop 616, of lower rigid member 608. Suture holes 612D and 612E can be positioned on spring member 606 at a location that lies between a position at which upper rigid member 610 is engaged to spring member 606, and a position at which a slot 618 is formed in a bight portion of spring member 606. In the case that the distal end of upper rigid member 610 exhibits a male clasp feature 614, such as a planular curvature away from a plane in which the upper rigid member 610 predominantly lies, a complimentary female clasp feature can be exhibited by a distal end of lower rigid member 608, such as the aforementioned rectangular wire loop 616 engaged by a hinge formation 620 provided in the distal end of lower rigid member 608. It should be readily understood that the same functionality can be achieved if upper rigid member 610 exhibits the female clasp feature, and lower rigid member 608 exhibits male clasp feature 614. Thus, the positions of the clasp features can be reversed in other embodiments.

**[0034]** Turning now to Figure 16, another additional feature of clamp 600 can be a detent that is 622 formed in hinge formation 620, and that engages wire loop 616 of the female clasp feature. This detent 622 can be positioned on the hinge formation 620 at a location that is most distal when the clamp 600 is held in a closed position, and it can be sized and shaped to hold the wire loop 616 in a lowered position at which the loop 616 lies in a plane parallel to a plane in which lower rigid member 608 predominantly lies. A similar or identical detent (not shown) can be provided on an opposite side of hinge formation 620, and it can be similarly distally positioned to assist in holding the wire loop 616 in the aforementioned lowered position. This lowered position allows the clamp 600 to be inserted through a trochar and guided to enclose a bodily organ, such as a stomach, at which point the aforementioned silicone sleeve (see Figures 19-27) can be partially applied. Then, before the silicone sleeve is fully engaged to the clamp 600, wire loop 616 can be forced out of detent 622 into a raised position at which it engages the male clasp feature 614 of the clamp 600.

**[0035]** Before raising the wire loop 616, it is envisioned that the clamp 600 can be pressed into a closed position by use of two or more graspers inserted into the abdominal cavity through additional trochars (i.e., multiport technique). Then, a suture tag pre-applied to wire loop 616 can be used to force wire loop 616 out of detent 622 into the raised position, resulting in the wire loop 616 engaging the male clasp feature 614 and holding the clamp 600

in the closed position without assistance from the two or more graspers. Alternatively or additionally, it is envisioned that closing and latching of the clamp 600 can be achieved by utilizing any suitable endoscopic surgical tools and techniques as will be readily apparent to one skilled in the art from the present disclosure.

**[0036]** Turning now to Figures 17(a)-17(f) and referring generally thereto, an endoscopic surgical installation tool for engaging and manipulating the clamp can be similar to those described above. For example, the installation tool can have a handle 650, trigger 652, pull rod, T-bar 654, cylindrical tube 656, dial 658 (e.g., with thumb lever), hub, guidelines, and articulating head 604 that are identical or similar to those described above. However, as previously described, a curvature or incline imparted to the head 604 by wedges of the head 604 can be keyed to a bight portion of the previously described clamp so as to hold the clamp in a fully open or predominantly open position when T-bar 654 has been fully retracted by actuation of trigger 652. Additionally, a latch release 660 can be provided that can extend from both sides of handle 650 for ergonomic, ambidextrous operation.

**[0037]** Turning now to Figure 17, the latch release 660 can have a hinged plate with a retention spring that forces the latch release 660 upwards to engage a latch 662 provided at a proximal end of pull rod 664. In use, a surgeon can engage the T-bar to the clamp 600 by rotating the clamp 600 and/or installation tool in a common longitudinal axis until the T-bar fits through the notch in the bight portion of the clamp 600, and then rotating the clamp 600 and/or installation tool an integer multiple of ninety degrees until a length direction of the T-Bar is perpendicular to a length direction of the notch. Then, actuation of trigger 652 can retract pull rod until opposing latch surfaces (e.g., edges, extensions, faces, flanges, gouges, hooks, inclines, ledges, lips, notches, overhangs, projections, protrusions, ribs, ridges, skirts, serrations, slits, slots, teeth, wedges, and combinations thereof) of the latch 662 and release 660 can catch and hold the pull rod 664 in a fully retracted or predominantly retracted position.

**[0038]** Once the latch 662 is engaged, the clamp 600 is ready to be inserted into an inflated abdominal cavity through a trochar as described above, and a seal provided between cylindrical tube 656 and clevis 668 can prevent out gassing from the abdominal cavity through the head 604 and/or cylindrical tube 656. Alternatively, the seal can be provided anywhere inside cylindrical tube 656. In some embodiments, the seal is achieved by using a circular silicone die having a slit and a hole in the middle, with the pull rod 664 threaded through the hole.

**[0039]** Once the clamp 600 is in position within the abdominal cavity to enclose and partition the stomach or other organ, pressing down on latch release 660 can permit automatic extension of pull rod 664 by action of a torsion spring provided to trigger screw 666 to force deactuation of trigger 652. The T-bar can then be disengaged from the clamp by rotating the installation tool

along its longitudinal axis an integer multiple of ninety degrees and removing it from the trochar. Thus, it should be apparent that, in some embodiments, the pull rod may not be configured to rotate as in alternative embodiments described above, but only to retract and to extend.

**[0040]** Turning now to Figure 19, a silicone sleeve 700 can be configured to engage clamp 600. In some embodiments, silicone sleeve 700 can be formed to cover primarily an upper arm and both ends of clamp 600. This silicone sleeve 700 can be used as padding to protect surrounding organs from irritation or damage. Thickness of the silicone can be varied for different applications, such as partitioning an organ, stomach, or vessel.

**[0041]** Turning now to Figures 20-27 and referring generally thereto, the silicone sleeve 700 can have tubular section 702 at a proximal end that slides onto the lower arm of clamp and can be manipulated into position to encapsulate the previously described bight portion of the clamp. The clamp can then be closed and latched as described above. Presuming that the upper arm of the clamp has already been sutured to the organ, stomach, or vessel, a distal end of the sleeve 700 can then be engaged to encapsulate the distal end of the clamp. For this purpose, the distal end of the sleeve 700 can be configured as a latch cap 704 that is form fitted to the closed latch features (see Fig. 25). A padding strip 706 situated between the tubular section 702 and latch cap 704 can be sized to a length of the clamp so as to be stretched taught across the upper arm of the clamp once the sleeve 700 is installed. A slot engaging feature 708 formed inside of tubular section 702 can be provided to engage with the previously described slot in the bight portion of the clamp by plugging the slot, and thus hold the tubular section of the sleeve 700 in place on the bight portion of the clamp.

**[0042]** Turning now to Figure 28, a method of performing surgery can begin at step 750 by engaging the previously described clamp to the previously described surgical installation tool in one or more of the previously described manners. Thereafter, the clamp can be inserted through a trochar at step 752, and positioned to enclose an organ (e.g., stomach, vessel, etc.) at step 754. Next, at step 756, an upper arm of the clamp can be sutured to the organ through suture holes supplied in the clamp as previously described, and the installation tool can be disengaged and removed from the trochar at step 758. Thereafter, the previously described silicone sleeve can be slid over a lower arm of the clamp at step 760 as previously described, and the clamp can be closed and latched at step 762. Finally, at step 764, a latch cap of the silicone sleeve can be fit over the latch of the clamp, and additional sutures can be applied if desired. It should be understood that the sequence of the aforementioned steps can vary in additional or alternative embodiments, and that additional or alternative steps can be employed as will be readily apparent to one skilled in the art.

**[0043]** A number of additional and alternative embodiments of the surgical clamp can have characteristics that



are different from those described above. For example, it is envisioned that a surgical clamp not intended for bariatric surgery might not have a passage forming section, and that such a clamp might be smaller or larger, depending on the purpose of the clamp. For example, the clamp can be one-tenth of an inch (2,54 mm) in length to partition a blood vessel, or twenty-two centimeters in length to partition a stomach. Moreover, the clamp can be configured to partition any internal organ, and can vary in length accordingly between these two example lengths, or be longer or shorter as required. Also, the guide members might have one or more protrusions aligned with the engagement feature and configured for insertion into the slot formed in the bight portion of the clamp. Moreover, it is envisioned that the installation tool can be integrated with an endoscope and/or surgical robot, and that appropriate robotic elements can be included in place of or in addition to those described above.

## Claims

### 1. A surgical clamp (100) comprising:

at least two elongated members (104A, 104B) each having an elongated length, wherein at least one surface of the at least two elongated members has a padding material (116) positioned adjacent at least a portion of the surface; a bight portion (106) joining said two elongated members at a proximal end of the surgical clamp and biasing said two elongated members in an open position at a distal end of the surgical clamp, wherein said bight portion has at least one engagement feature formed therein, wherein the engagement feature comprises a slotted aperture (108) formed through a proximal surface of the bight portion and having a length oriented perpendicular to a longitudinal axis of the surgical clamp; wherein the length of the slotted aperture is greater than the width of the slotted aperture; and a clasp mechanism having a male component (110) disposed on one of the two elongated members at the distal end of the surgical clamp and a female component (112) disposed on the other of the two elongated members at the distal end of the surgical clamp.

2. The surgical clamp of claim 1, wherein the at least two elongated members are attached to elongated members of a spring component that serves as the bight portion.

3. The surgical clamp of claim 2, wherein the elongated members are comprised of titanium, and a surface of the at least two elongated members of the surgical clamp is curved and contacts at least one of the elon-

gated members of the spring component.

4. The surgical clamp of claim 1, wherein spacing between the interior surfaces of said at least two elongated members includes a partition forming section (105A) located nearer the distal end of the surgical clamp than the proximal end of the surgical clamp, and a passage forming section (105B) located nearer the proximal end of the surgical clamp than the distal end of the surgical clamp.

5. The surgical clamp of claim 4, wherein the bight portion includes a spring portion that serves at least partially as the passage forming section.

6. The surgical clamp of claim 5, wherein said padding material is connected to at least one of the two elongated members at least at a location on the surface corresponding to at least part of the partition forming section.

7. The surgical clamp of claim 1, wherein the male component of the clasp mechanism corresponds to an end (614) of the elongated member that flares away from a longitudinal axis of the surgical clamp when the surgical clamp is placed in a closed position, and the female component of the clasp mechanism corresponds to a loop (616) disposed to engage the end of the elongated member when the surgical clamp is placed in the closed position, and a hinge formation (620) engaging the loop has a detent (622) distally positioned to retain the loop in a plane parallel to a plane in which a longitudinal axis of the clamp predominately lies when the clamp is closed.

8. The surgical clamp (100) of claim 1 being adapted for use in clamping an internal organ.

9. The surgical clamp as set forth in claim 8, wherein the internal organ is a human stomach.

10. The surgical clamp as set forth in claim 9, wherein the clamping of the internal organ is part of:

a laparoscopic surgery;  
a open conventional surgery;  
a single site surgery;  
a natural orifice transluminal endoscopic surgery (NOTES); or  
a combination of NOTES and an assistant trochar placed into an abdominal cavity.

11. The surgical clamp as set forth in claim 10, wherein the combination of NOTES and an assistant trochar includes two or more of a conventional, laparoscopic, NOTES, and one port technique.

12. The surgical clamp as set forth in claim 10, wherein

the NOTES technique includes at least one of transgastric, transvaginal, transrectal, transcolonic, or combinations thereof.

13. The surgical clamp as set forth in claim 8, wherein the two elongated members are composed of hardened titanium and attached by welding to interior surfaces of a spring member (222) made of steel, wherein said spring member comprises said bight portion.

#### Patentansprüche

1. Eine chirurgische Klemme (100), umfassend wenigstens zwei langgestreckte Elemente (104A, 104B) mit jeweils einer langgestreckten Länge, wobei wenigstens eine Oberfläche der wenigstens zwei langgestreckten Elemente ein Polsterungsmaterial (116) aufweist, das wenigstens einem Teil der Oberfläche angrenzend angeordnet ist; einen gebogenen Abschnitt (106), der besagte zwei langgestreckte Elemente an einem proximalen Ende der chirurgischen Klemme verbindet und besagte zwei langgestreckte Elemente in eine offene Position an einem distalen Ende der chirurgischen Klemme vorspannt, wobei besagter gebogener Abschnitt wenigstens ein darin geformtes Eingreifmerkmal besitzt, wobei das Eingreifmerkmal eine geschlitzte Öffnung (108) umfasst, die durch eine proximale Oberfläche des gebogenen Abschnitts gebildet wird und eine Länge besitzt, die senkrecht zu einer Längsachse der chirurgischen Klemme verläuft, wobei die Länge der geschlitzten Öffnung größer als die Breite der geschlitzten Öffnung ist; und einen Klemmmechanismus mit einer männlichen Komponente (110), die auf einem der zwei langgestreckten Elemente am distalen Ende der chirurgischen Klemme angeordnet ist, und einer weiblichen Komponente (112), die auf dem anderen der beiden langgestreckten Elemente am distalen Ende der chirurgischen Klemme angeordnet ist.
2. Die chirurgische Klemme nach Anspruch 1, wobei die wenigstens zwei langgestreckten Elemente an langgestreckten Elementen einer Federkomponente befestigt sind, die als der gebogene Abschnitt dient.
3. Die chirurgische Klemme nach Anspruch 2, wobei die langgestreckten Elemente aus Titan bestehen und eine Oberfläche der wenigstens zwei langgestreckten Elemente der chirurgischen Klemme gekrümmt ist und mit wenigstens einem der langgestreckten Elemente der Federkomponente in Kontakt steht.
4. Die chirurgische Klemme nach Anspruch 1, wobei der Zwischenraum zwischen den Innenseiten von

besagten wenigstens zwei langgestreckten Elementen der chirurgischen Klemme einen Teilungsbildenden Abschnitt (105A), der näher zum distalen Ende der chirurgischen Klemme als zum proximalen Ende der chirurgischen Klemme liegt, und einen Durchgangbildenden Abschnitt (105B), der näher zum proximalen Ende der chirurgischen Klemme als zum distalen Ende der chirurgischen Klemme liegt, umfasst.

5. Die chirurgische Klemme nach Anspruch 4, wobei der gebogene Abschnitt ein Federteil umfasst, das wenigstens zum Teil als der Durchgangbildende Abschnitt dient.
6. Die chirurgische Klemme nach Anspruch 5, wobei besagtes Polsterungsmaterial mit wenigstens einem der zwei langgestreckten Elemente wenigstens an einer Stelle auf der Oberfläche verbunden ist, die wenigstens einem Teil des Teilungsbildenden Abschnitts entspricht.
7. Die chirurgische Klemme nach Anspruch 1, wobei die männliche Komponente des Klemmmechanismus einem Ende (614) des langgestreckten Elements entspricht, das sich von einer Längsachse der chirurgischen Klemme weg erstreckt, wenn die chirurgische Klemme in eine geschlossene Position gebracht ist, und die weibliche Komponente des Klemmmechanismus einer Schlaufe (616) entspricht, die so angeordnet ist, um das Ende des langgestreckten Elements zu greifen, wenn die chirurgische Klemme in die geschlossene Position gebracht ist, und eine gelenkige Anordnung (620), die die Schlaufe umgreift, eine distal positionierte Arretierung (622) besitzt, um die Schlaufe in einer Ebene parallel zu einer Ebene zu halten, in der eine Längsachse der Klemme vorwiegend liegt, wenn die Klemme geschlossen ist.
8. Die chirurgische Klemme (100) nach Anspruch 1, die für eine Verwendung bei Klemmung eines inneren Organs angepasst ist.
9. Die chirurgische Klemme wie in Anspruch 8 dargelegt, wobei das innere Organ ein menschlicher Magen ist.
10. Die chirurgische Klemme wie in Anspruch 9 dargelegt, wobei die Klemmung des inneren Organs ein Teil ist von:
  - einer laparoskopischen Operation;
  - einer offenen herkömmlichen Operation;
  - einer Operation an einem einzigen Ort;
  - einer transluminalen endoskopischen Operation über eine natürliche Körperöffnung (NOTES); oder

einer Kombination aus NOTES und einem in eine Bauchhöhle eingebrachten Hilfstrokar.

11. Die chirurgische Klemme wie in Anspruch 10 dargelegt, wobei die Kombination aus NOTES und einem Hilfstrokar zwei oder mehrere einer herkömmlichen, laparoskopischen, NOTES- und Single-Port-Technik umfasst.
12. Die chirurgische Klemme wie in Anspruch 10 dargelegt, wobei die NOTES-Technik wenigstens eine transgastrische, transvaginale, transrektale, transcolonische Technik oder Kombinationen davon umfasst.
13. Die chirurgische Klemme wie in Anspruch 8 dargelegt, wobei die zwei langgestreckten Elemente aus gehärtetem Titan bestehen und durch Schweißen der Innenflächen eines aus Stahl hergestellten Federelements (222) verbunden sind, wobei besagtes Federelement besagten gebogenen Abschnitt umfasst.

#### Revendications

1. Pince chirurgicale (100) comprenant :

au moins deux éléments allongés (104A, 104B) ayant chacun une longueur allongée, au moins une surface des au moins deux éléments allongés ayant une matière de garniture (116) positionnée adjacente à au moins une partie de la surface ;  
une partie anse (106) reliant lesdits deux éléments allongés au niveau d'une extrémité proximale de la pince chirurgicale et sollicitant lesdits deux éléments allongés dans une position ouverte au niveau d'une extrémité distale de la pince chirurgicale, ladite partie anse ayant au moins un élément d'engagement formé à l'intérieur de celle-ci, l'élément d'engagement comprenant une ouverture fendue (108) formée à travers une surface proximale de la partie anse et ayant une longueur orientée perpendiculairement à un axe longitudinal de la pince chirurgicale ; la longueur de l'ouverture fendue étant supérieure à la largeur de l'ouverture fendue ; et  
un mécanisme d'attache ayant un composant mâle (110) disposé sur l'un des deux éléments allongés au niveau de l'extrémité distale de la pince chirurgicale et un composant femelle (112) disposé sur l'autre des deux éléments allongés au niveau de l'extrémité distale de la pince chirurgicale.

2. Pince chirurgicale selon la revendication 1, dans la-

quelle les au moins deux éléments allongés sont fixés à des éléments allongés d'un composant ressort qui sert de partie anse.

3. Pince chirurgicale selon la revendication 2, dans laquelle les éléments allongés sont composés de titane, et une surface des au moins deux éléments allongés de la pince chirurgicale est incurvée et entre en contact avec au moins un des éléments allongés du composant ressort.
4. Pince chirurgicale selon la revendication 1, dans laquelle l'espacement entre les surfaces intérieures desdits au moins deux éléments allongés comprend une section de formation de cloison (105A) située plus près de l'extrémité distale de la pince chirurgicale que de l'extrémité proximale de la pince chirurgicale, et une section de formation de passage (105B) située plus près de l'extrémité proximale de la pince chirurgicale que de l'extrémité distale de la pince chirurgicale.
5. Pince chirurgicale selon la revendication 4, dans laquelle la partie anse comprend une partie ressort qui sert au moins partiellement de section de formation de passage.
6. Pince chirurgicale selon la revendication 5, dans laquelle ladite matière de garniture est reliée à au moins un des deux éléments allongés au moins à un emplacement sur la surface correspondant à au moins une partie de la section de formation de cloison.
7. Pince chirurgicale selon la revendication 1, dans laquelle le composant mâle du mécanisme d'attache correspond à une extrémité (614) de l'élément allongé qui s'évase par rapport à un axe longitudinal de la pince chirurgicale lorsque la pince chirurgicale est placée dans une position fermée, et le composant femelle du mécanisme d'attache correspond à une boucle (616) disposée pour engager l'extrémité de l'élément allongé lorsque la pince chirurgicale est placée dans la position fermée, et une formation de charnière (620) engageant la boucle à un cran (622) positionné de manière distale pour retenir la boucle dans un plan parallèle à un plan dans lequel un axe longitudinal de la pince s'étend principalement lorsque la pince est fermée.
8. Pince chirurgicale (100) selon la revendication 1, qui est adaptée pour une utilisation dans le clampage d'un organe interne.
9. Pince chirurgicale selon la revendication 8, dans laquelle l'organe interne est un estomac humain.
10. Pince chirurgicale selon la revendication 9, dans la-

quelle le clamage de l'organe interne fait partie de :

une chirurgie laparoscopique ;  
 une chirurgie ouverte classique ;  
 une chirurgie par site unique ; 5  
 une chirurgie endoscopique transluminale d'orifice naturel (NOTES) ; ou  
 une combinaison de NOTES et d'un trocart d'aide placé dans une cavité abdominale. 10

11. Pince chirurgicale selon la revendication 10, dans laquelle la combinaison de NOTES et d'un trocart d'aide comprend au moins deux parmi une technique classique, une technique laparoscopique, une technique NOTES et une technique par un orifice. 15

12. Pince chirurgicale selon la revendication 10, dans laquelle la technique NOTES est au moins une parmi des techniques transgastrique, transvaginale, transrectale, transcolonne ou des combinaisons de celles-ci. 20

13. Pince chirurgicale selon la revendication 8, dans laquelle les deux éléments allongés sont composés de titane durci et fixés par soudage à des surfaces intérieures d'un élément ressort (222) fait d'acier, ledit élément ressort comprenant ladite partie anse. 25

30


35

40


45

50


55




**Figure - 1**



**Figure - 2(a)**



**Figure - 2(b)**



**Figure - 2(c)**




Figure - 2(d)







Figure - 2(e)




*Figure - 2(f)*



*Figure - 2(g)*



*Figure - 2(h)*



*Figure - 2(i)*






Figure - 2(j)







Figure - 2(k)




**Figure - 3(a)**




**Figure - 3(b)**




**Figure - 3(c)**




**Figure - 3(d)**





**Figure - 3(f)**



**Figure - 3(e)**



**Figure - 4(a)**






Figure - 5




Figure – 6A




Figure – 6B






Figure – 6D

Figure – 6C







**Figure – 7A**




**Figure – 7B**




**Figure – 7D**



**Figure – 7C**



**Figure – 8A**



**Figure – 8B**




Figure – 8C






Figure – 8D



**Figure – 9A**

**Figure – 9C**



**Figure – 9B**






Figure – 9D




**Figure - 10**




**Figure - 11**






**Figure - 12**



**Figure - 13**



**Figure - 14**




Figure – 15(a)




Figure – 15(b)




Figure – 15(c)






Figure – 15(d)








**Figure – 15(f)**

**Figure – 15(e)**




**Figure - 16**






**Figure - 17(f)**




**Figure - 17(e)**




**Figure - 18**







**Figure - 19**



**Figure - 20**



**Figure - 21**



**Figure - 22**




Figure - 23






Figure - 24





**Figure - 28**

**REFERENCES CITED IN THE DESCRIPTION**

*This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.*

**Patent documents cited in the description**

- US 11984452 A, Jacobs [0002]
- US 11797537 A, Jacobs [0002]
- EP 0220643 A2 [0002]
- EP 1600108 A2 [0002]
- WO 9833437 A1 [0002]
- WO 0078234 A1 [0002]
- US 2008033457 A1 [0002]
- DE 29822558 U1 [0002]
- US 5156609 A [0002]
- WO 9911179 A1 [0002]
- US 4274415 A [0002]

专利名称(译)	手术夹和手术夹安装工具		
公开(公告)号	<a href="#">EP2528512A1</a>	公开(公告)日	2012-12-05
申请号	EP2011737828	申请日	2011-01-31
[标]申请(专利权)人(译)	高级肥胖症治疗技术公司		
申请(专利权)人(译)	BARIATRIC先进科技有限责任公司		
当前申请(专利权)人(译)	BARIATRIC先进科技有限责任公司		
[标]发明人	JACOBS MOISES ARMENTEROS JESUS R BARKER GARRETT FRENCH C KENNETH		
发明人	JACOBS, MOISES ARMENTEROS, JESÚS, R. BARKER, GARRETT FRENCH, C., KENNETH		
IPC分类号	A61B17/06 A61B17/122 A61B17/128		
CPC分类号	A61B17/122 A61B17/1285 A61B2017/00473 A61B2017/00477 A61B2017/00818 A61B2017/00862 A61B2017/00876		
代理机构(译)	MÜLLER & PARTNER Schupfuer		
优先权	61/299725 2010-01-29 US		
其他公开文献	EP2528512A4 EP2528512B1		
外部链接	<a href="#">Espacenet</a>		

#### 摘要(译)

在某些实施例中，外科夹具可以配置成与外科手术安装工具一起操作。夹具可以具有两个细长构件，其具有弯曲部分，该弯曲部分在夹具的近端处连接两个细长构件并且可以将两个细长构件偏置在远端处的打开位置。弯曲部分可以具有一个或多个接合特征，例如开槽孔或其他接合或连接特征。夹具远端处的扣紧机构可具有设置在两个细长构件中的一个上或附近的凸形或第一部件，以及设置在所述两个细长构件中的另一个上的所述两个细长构件上或附近的凹形或第二部件。钳。安装工具可包括细长构件，细长构件具有近端和远端，远端具有接合特征以接合夹具，例如在弯曲部分处。在一个实施例中的手柄可以设置在安装工具的近端处，而远端处的头部可以配置成接收和/或接合夹具的近端，并且还可以可操作以在至少一个中进行关节运动。平面。