



(11)

EP 3 653 136 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
20.05.2020 Bulletin 2020/21

(51) Int Cl.:
A61B 17/072 (2006.01)

(21) Application number: **19215299.9**

(22) Date of filing: **26.12.2013**

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

(30) Priority: **03.01.2013 US 201313733815**

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:
13870240.2 / 2 925 244

(71) Applicant: **JustRight Surgical, LLC
Louisville CO 80027 (US)**

(72) Inventors:
• **MATA, Vincent
Louisville, CO 80027 (US)**

• **BACHMAN, Alan
Louisville, CO 80027 (US)**
• **GRANGER, Richard
Louisville, CO 80027 (US)**

(74) Representative: **Gillespie, Richard
Inventorship
Suite 10050
5 Fitzwilliam Square
Dublin 2, D02 R744 (IE)**

Remarks:


This application was filed on 11-12-2019 as a divisional application to the application mentioned under INID code 62.

(54) MEDICAL DEVICE FOR USE IN LAPAROSCOPIC SURGERY

(57) A medical device comprising an actuator, an extension portion, and a tissue interaction portion. The extension portion is coupled to the actuator and comprises at least first and second telescoping sections with each telescoping section having (i) at least one extended hook section having a head portion and a neck portion, and (ii) at least one body section being one of coupled and integrated to the at least one extended hook section. The

at least one extended hook section of the first telescoping section is operatively coupled to the body section of the second telescoping section. The tissue interaction portion is operatively coupled to the extension portion and comprises at least one of a gripping mechanism, a stapling mechanism, and a cutting mechanism. The actuator is adapted to control at least one of the extension portion and tissue interaction portion.

FIG.9



EP 3 653 136 A1

Description

FIELD OF THE INVENTION

[0001] This invention is related to medical devices. Specifically, but not intended to limit the invention, embodiments of the invention are related to a medical device adapted to extend and provide gripping, cutting, and stapling features.

BACKGROUND OF THE INVENTION

[0002] Surgical staplers are currently designed for use in adult medical procedures. Using current surgical staplers in children creates various problems as aspects of the stapler are often larger than needed or desired. For example, during a pediatric laparoscopic surgery, a greater than desired cannula and/or incision size may be implemented when an adult stapler is used.

[0003] Additional features of surgical staplers may not be designed with pediatric surgeries in mind. For example, a stapling mechanism and any associated gripping and cutting devices may be inappropriately sized and/or may operate ineffectively or inefficiently during pediatric procedures. Due to the decreased size of current surgical pediatric staplers, current staplers may not have sufficient structural support for various procedures and may therefore buckle when the stapler is attempted to be applied during a pediatric surgical procedure.

SUMMARY OF THE INVENTION

[0004] In order to overcome these and other deficiencies in current medical devices, a medical device was developed that is adapted to properly apply a coupling mechanism to tissue while also cutting the tissue. One such embodiment comprises a medical device comprising an actuator, an extension portion operatively coupled to the actuator, and a tissue interaction portion operatively coupled to the extension portion. In one embodiment, the extension portion comprises at least a first and a second telescoping section. Each of the first and a second telescoping section comprises at least one extended hook section and a body section. Each of the at least one extended hook section comprises a head portion and a neck portion. The body section one is one of coupled and integrated to the extended hook section. Furthermore, the extended hook section of the first telescoping section is operatively coupled to the body section of the second telescoping section. The tissue interaction portion may be operatively coupled to the extension portion, with the tissue interaction portion comprising at least one of a gripping mechanism, a stapling mechanism, and a cutting mechanism. The actuator in one embodiment is adapted to control at least one of the extension portion, gripping mechanism, stapling mechanism, and cutting mechanism.

[0005] Another embodiment of the invention comprises

es a method of using a medical device. One such method comprises performing a first function on a device actuator. A single-use mechanism may then be moved from a first location to a second location, and a second function may be performed on the device actuator. A first section of a medical device extension portion may then be moved from a first retracted location to a second extended location and a plurality of extension portion telescoping sections may be extended. A coupling device may then be attached to tissue, and the tissue may be cut.

[0006] Yet another embodiment of the invention comprises a tissue coupling system. One tissue coupling system comprises an actuator and a plurality of telescoping sections operatively coupled to the actuator. Each of the telescoping sections may comprise an upper section, a lower section, at least one upper section slot, and at least one lower section slot. A tissue coupling device may be coupled to at least one of the plurality of telescoping sections. Furthermore, the at least one upper section slot is adapted to receive one of a portion of another telescoping section and the tissue coupling device.

[0007] Illustrative embodiments of the present invention that are shown in the drawings are summarized herein. These and other embodiments are more fully described in the Detailed Description section. It is to be understood, however, that there is no intention to limit the invention to the forms described in this Summary of the Invention or in the Detailed Description. One skilled in the art can recognize that there are numerous modifications, equivalents, and alternative constructions that fall within the spirit and scope of the invention as expressed in the claims.

BRIEF DESCRIPTION ON THE DRAWINGS

[0008] Various objects and advantages and a more complete understanding of the present invention are apparent and more readily appreciated by reference to the following Detailed Description and to the appended claims when taken in conjunction with the accompanying Drawings, where like or similar elements are designated with identical reference numerals throughout the several views and wherein:

FIG. 1 illustrates a side view of a medical device according to one embodiment of the invention;
FIG. 2 illustrates a side-view of section A from FIG. 1 with an outer sheath being removed from the device according to one embodiment of the invention;
FIG. 3 illustrates an isometric view of a telescoping section device according to one embodiment of the invention;
FIG. 4 illustrates an isometric view of operatively coupled and extended first and second telescoping sections according to one embodiment of the invention;
FIG. 5 illustrates an isometric view of operatively coupled and retracted first and second telescoping

sections according to one embodiment of the invention;

FIG. 6A illustrates a side view of a tissue interaction portion and a portion of an extension portion having an outer sheath removed, of a medical device, according to one embodiment of the invention;

FIG. 6B illustrates a side view of a tissue interaction portion having a plurality of cut-outs according to one embodiment of the invention;

FIG. 7 illustrates a side view of a tissue interaction portion in a having an open clamping section according to one embodiment of the invention;

FIG. 8 illustrates an isometric view of a portion of a tissue interaction portion having at least a clamping section removed, and an extension portion in a retracted location with an outer sheath being removed according to one embodiment of the invention;

FIG. 9 illustrates an isometric view of a tissue interaction portion and a section of an extension portion in an extended location with an outer sheath and clamping section being removed according to one embodiment of the invention;

FIG. 10A illustrates a side view of an extension portion and a portion of a tissue interaction portion, with an outer sheath being removed, in a retracted location according to one embodiment of the invention;

FIG. 10A' illustrates an isometric view of section 10A' in FIG. 10A according to one embodiment of the invention;

FIG. 10B illustrates a side view of an extension portion and a portion of a tissue interaction portion, with an outer sheath being removed, in an extended location according to one embodiment of the invention;

FIG. 10B' illustrates an isometric view of section 10B' in FIG. 10B according to one embodiment of the invention;

FIG. 11A illustrates a side view of section 11 in FIG. 10A with a clamping sheath and a locking sheath removed according to one embodiment of the invention;

FIG. 11B illustrates a side view of section 11 in FIG. 10A with a locking sheath removed according to one embodiment of the invention;

FIG. 12 illustrates a close-up isometric view of the locking sheath and staple rod according to one embodiment of the invention;

FIG. 13 illustrates another close-up isometric view of the locking sheath and staple rod according to one embodiment of the invention;

FIG. 14 illustrates an isometric view of a clamping section undercarriage according to one embodiment of the invention;

FIG. 15 illustrates an isometric view of a staple pusher, staple rods and cutting mechanism according to one embodiment of the invention;

FIG. 16 illustrates a flowchart that depicts a method that may be carried out in connection with the embodiments described herein;

FIG. 17 illustrates a close-up isometric view of a transparent locking sheath, and a clamping sheath and staple rod according to one embodiment of the invention; and

FIG. 18 illustrates a locking sheath interacting with a clamping sheath according to one embodiment of the invention.

DETAILED DESCRIPTION

10

[0009] Turning first to FIG. 1, seen is an embodiment of a medical device 100. Medical device 100 comprises an actuator 110, an extension portion 120 operatively coupled to the actuator 110, and a tissue interaction portion 130 operatively coupled to the extension portion 120. The term operatively is used throughout the specification and claims to describe something that produces an effect. For example, here the extension portion 120 is operatively coupled to the actuator 110 and the tissue interaction portion 130 is operatively coupled to the extension portion 120. Therefore, and as described below, each of these coupled portions of the device 100 are adapted to produce an effect between the coupled portions.

25

[0010] Turning to FIG. 2, seen is a close-up view of a section of the extension portion 220 and the tissue interaction portion 130, as seen in Box "A" from FIG. 1, but with the outer sheath 122 seen in FIG. 1 removed from the extension portion 120. The outer sheath 122 may comprise a protective sheath and may keep one or more of the telescoping sections 224 as seen in FIG. 2, properly aligned. A clamping sheath 1050, as described below, with references to FIG. 10A, and elsewhere, has also been removed from the extension portion 220 in FIG. 2. However, the locking sheath 260 remains. As seen, one embodiment of the extension portion 220 comprises a plurality of telescoping sections 224. At least two of the telescoping sections 224 may comprise a first and a second telescoping section. One embodiment of the medical device 220 may comprise two or more telescoping sections 224. The telescoping section 224 reference numeral, and/or any other reference numeral, may be shown with one or more prime symbols: "'".

35

[0011] Turning now to FIG. 3, seen is one example of a telescoping section 324. It is contemplated that other types of telescoping sections 324 may be used. The telescoping section 324 seen in Fig. 3 comprises an attachment section 326 and a body section 328. The attachment section 324 may be adapted to couple to another

40

telescoping section 324, while the body section 328 may be adapted to receive the attachment section 324 of another telescoping section 324. The attachment section 326 may comprise at least one extended hook section that comprises a head portion 327 and a neck portion

45

329. The head portion 327 may comprise at least one extension section 321 extending radially outward from an attachment section longitudinal axis 325. In FIG. 3, the extension section 321 extends outward in a substan-

tially vertical direction. However, the extension section 321 may extend in a substantially horizontal direction and/or any other direction relative to the attachment section longitudinal axis 325.

[0012] The body section 228 may either couple or integrate to one or more portions of the extended hook section. The term "couple," "coupling," or any variation thereof within the specification and claims refers to joining two separate items together. One type of coupling may involve using a coupling mechanism such as, but not limited, to, a bolting device. However, other coupling mechanisms such as latching, magnetic, or other coupling mechanisms may be used, where appropriate. Alternatively, where otherwise stated, coupling may also refer to "integrated." The term "integrated" or any variation thereof within the specification and claims refers to combining two or more parts to create a whole and single, indivisible part, where appropriate.

[0013] In one embodiment, the body section 328 may comprise at least one body section notch 323 adapted to slidably receive at least a portion of the attachment section 326. For example, and as seen in FIG. 4, a proximal end 431' of the body section notch 423' of a first telescoping section 424' may receive the head portion 427" of a second telescoping section 424" when the telescoping sections 424 are in an extended setting 432 as seen in FIG. 4. The extended setting 432 and retracted setting 534 seen in FIG. 5 may also be referred to as an extension section extended setting 432 and retracted setting 534. Returning now to FIG. 3, seen is a notch lip 335. The notch lip 335 may comprise a forward edge 336 which may interact with a trailing edge 337 of the head portion 327. Returning to FIG. 4, the interaction between the notch lip 435 of the first telescoping section 424' may prevent the head portion 427" of the second telescoping section 424" from sliding out of the notch 423' and may therefore keep the first and second telescoping sections coupled.

[0014] Turning now to FIG. 5, seen are a first telescoping section 524' and a second telescoping section 524" in a retracted setting 534. In moving from the extended setting 432 seen in FIG. 4 to the retracted setting 524 in FIG. 5, or vice versa, the head portion 527" of the second telescoping section 524" may slide along the notch 523' between the proximal end 531' and the distal end 533' of the notch 523'. In the retracted setting 534, a leading edge 536" of the head 527" may interact with a rear notch edge 537'. The leading edge 436" and rear notch edge 437' are also seen in FIG. 4. Similarly, a leading edge 538" of a body section 528" of the second telescoping section 524" may interact with a trailing edge 539' of the body section 528' of the first telescoping section 524'. The term interact may refer to "contacting" with the contacting substantially preventing further movement of one or more of the telescoping sections 524', 524" in a specific direction such as, but not limited to, preventing additional movement of the second telescoping section 524" in a direction the second telescoping section 524" is moving

prior to interacting with the edge 537' and lip 435, respectively. As such, in returning to FIG. 2, shown is an attachment section 226 of at least one first telescoping section 224' operatively coupled to the body section 338 of at least one second telescoping section 224" in an extended setting 232.

[0015] Turning now to FIGS. 6A, 6B and 7, seen is the tissue interaction portion 630, 730 of the medical device 100 seen in FIG. 1. The tissue interaction portion 630 comprises a base section 662 and a clamping section 664. The clamping section 664 individually or together with the base section 662 may also be referred to as a gripping mechanism. Other gripping mechanisms not using a clamping section 664 and a base section 662 are contemplated. For example, two pivotable clamping sections 664 may be used. The view in FIG. 6B is of an "overclamped" closed clamping section 664. Such an overclamped closed clamping section 664 may comprise a bend 665 in the closed clamping section 664 due to a distal portion 666 of the clamping section 664 pressing against an upper surface 667 of the base section 662 upon rotating down from the open position seen in FIG. 7 to the closed position seen in FIG. 6B.

[0016] Seen in FIG. 7 the view is of an open clamping section 764. Switching between the open clamping section 764 and closed clamping section 664, and vice versa, may be obtained by performing one or more actions at the actuator 110, as seen in FIG. 1. For example a user of the device 100 may either pull or push at least one of a first actuator trigger 112' and one or more second actuator triggers 112''. Seen in FIG. 6A is a view of the tissue interaction portion 630 as the clamping section 664 initial touches the base section 662. Through the use of the actuator 110 and a biasing device (not shown) such as, but not limited to, a spring, a clamping/telescoping connector 645 may interact with the clamping section 664 to open and close the clamping section 664. The position of the clamping/telescoping connector 645 seen in FIG. 6A is the mid-way point between the open position seen in FIG. 7 and the closed position of FIGS. 6B.

[0017] In one embodiment, the open clamping section 764 seen in FIG. 7 may be used as a clamping section starting point in selecting a desired tissue to interact with. For example, the desired tissue may be placed between the open clamping section 764 and the base section 762. Upon actuating the trigger 112, as seen in FIG. 1, the clamping section 764 may close, with a bottom clamping section surface 761 being located proximal a base section top surface 763, and the tissue being placed between the clamping section 764 and the top surface 763. It is contemplated that throughout the specification, where appropriate, the term "tissue" may comprise any internal or external part of a human, or even in an animal in a veterinary design. In one embodiment, the term "tissue" may refer to connective, muscle, nervous or epithelial tissue. It may also refer to organs or bones, or any other item contemplated but not listed or described above.

[0018] Turning now to FIG. 8, seen is one embodiment

of the tissue interaction portion 830 and extension portion 820 in the open position seen in FIG. 7. In FIG. 8, the outer sheath 722 and clamping section 764 from FIG. 7 have been removed. Other portions of the medical device 800 may also have been removed in order to facilitate proper viewing of internal aspects of the device 800 in FIG. 8. Similarly, in other figures, one or more portions of the device 100 may be removed to facilitate proper viewing of the device 100 or device section. Returning now to FIGS. 8, 9 and 2, a medical device 800 may further comprise a cutting mechanism 840-240-940. The cutting mechanism 840 may comprise one or more metal or composite medical cutting blades. As seen in FIGS. 7 and 8, when the clamping section 764 is in an open mode, the cutting mechanism 840 may be located in a distal section 842 of the tissue interaction portion 830.

[0019] The tissue interaction portion 830 comprises the clamping/telescoping connector 845. In the open position, which may also be referred to as an open mode, seen in FIG. 8, the clamping/telescoping connector 845 may be located in a first position. In the first position, a distal end 847 of the clamping/telescoping connector 845 is located proximate to a base section notch leading edge 846. As seen in FIGS. 6A, 8 and 9, upon closing the clamping section 664, the distal end 647-847-947 of the clamping/telescoping connector 945 may travel from the leading edge 646-846-946 to a base section notch trailing edge 648-848-948. The leading edge 646-846-946 and trailing edge 648-848-948 may be opposing ends of at least one base section notch 849-949, as seen in FIGS. 8 and 9.

[0020] Seen in FIG. 9 is a pair of base section notches 949 located on opposing outer edges of the distal portion 942 of the base section 962. Greater or lesser notches 949 are contemplated. One of the notches 949 may be adapted to receive the clamping/telescoping connector 945. Other designs of the tissue interaction portion 930 adapted to interact with the telescoping portion 920 and/or the clamping/telescoping connector 945 besides the notch 949 are contemplated. For example, in one embodiment the clamping/telescoping connector 945 may be adapted to interact with the telescoping sections 224 seen in FIG. 2 and/or the clamping section 764 seen in FIG. 7. In one embodiment, as the telescoping sections 224 switch from the extended setting 432 of FIG. 4 to the retracted setting 534 of FIG. 5, the clamping/telescoping connector 945 interacts with the clamping section 664 to close the clamping section 664.

[0021] Returning again to FIG. 9, one portion of the clamping/telescoping connector 945 may slide along the notch 949 from the leading edge 946 to the trailing edge 948 upon closing the clamping section 664. Such movement of the clamping/telescoping connector 945 may also lead to interaction of the clamping/telescoping connector 945 with the clamping sheath 950. For example, upon changing the clamping section 764 from the open position seen in FIG. 7 to the closed position seen in FIGS. 6A and 6B, the clamping sheath 850 may be

pushed from a first location/position, as seen in FIG. 8, to a second location/position, as seen in FIG. 9. FIG. 10A also shows the clamping sheath 1050 and clamping/telescoping connector 1045 located in a first location and 5 first position, while FIG. 10B shows the clamping sheath 1050 and clamping/telescoping connector 1045 in a second location and second position. Moving from the first location to the second location may position a first clamping sheath notch 1051 to interact with a locking sheath tab 1052 after staples have been fired in the tissue interaction portion 1030, as seen in FIG. 10A', which is a close up of box 10A' from FIG. 10A. For example, after the staples have been fired, the locking sheath 1060 may retract to the position seen in FIG. 10A'. If the locking sheath 1060 attempts to move towards the tissue interaction portion 1030, moving to and past the position seen in FIG. 10B', the locking sheath tab 1052 interacts with a notch 1051 wall, preventing the locking sheath 1060 and coupled staple rod 1154, as seen in FIG. 11, from 10 moving.

[0022] Also seen in FIG. 10A are boxes 11 and 11'. A close-up view of box 11 without the clamping sheath 1050 may be seen in FIG. 11B. FIG. 11A is the same view as seen in FIG. 11B, but without the clamping sheath 1150. 15 Each of FIGS. 11A and 11B comprise the clamping position seen in FIG. 10B and are aligned in a manner similar to FIG. 1, with the actuator 110 being located to the left of FIGS. 11A and 11B and the tissue interaction portion 130 being located to the right of FIGS. 11A and 11B, as FIGS. 11A and 11B are displayed and aligned. Similar alignment of the device 100 may be associated with the other figures, unless otherwise stated.

[0023] As seen in FIG. 11B, in addition to the first locking sheath tab 1152-1052 discussed in reference to FIGS. 10A to 10B' above, the clamping sheath 1150 may also comprise a second locking sheath tab 1153 and a third locking sheath tab 1198. The second locking sheath tab 1153 and third locking sheath tab 1198 may interact with the staple rod 1154. For example, as seen in FIG. 40 11A, a forward edge 1171 of the third locking sheath tab 1198 may contact a leading surface 1172 of a raised staple rod surface 1173. In one such embodiment, the staple rod 1154 moves towards the tissue interaction portion 130 seen in FIG. 1 when use of (i) a coupling mechanism such as, but not limited to a stapling mechanism, and/or (ii) a cutting mechanism such as, but not limited to, a blade, is desired at the tissue interaction portion 130 and a trigger 112 is activated at the actuator 110, as seen in FIG. 1. In one such case, the leading surface 1172 45 contacts the forward edge 1171, moving the clamping sheath 1150 along with the staple rod 1154 towards the tissue interaction portion 130. It is contemplated, although the terms "edge," "surface" or similar terms are used throughout the specification and/or claims, such terms are not intended to limit the disclosure to any specific design or feature type.

[0024] Turning now to FIG. 12, seen is one example of a start position of the locking sheath 1260 and staple

rod 1254 upon initiating the coupling mechanism and/or cutting mechanism. One coupling mechanism may comprise a stapling device. In one such embodiment, as the staple rod 1254 moves toward the tissue interaction device 130, the leading surface 1256-1356 interacts with and pushes the locking sheath 1260 forward from the FIG. 12 position to the position seen in FIG. 13. The position of the staple rod 1354 seen in FIG. 13 is the position where the staple rod 1354 begins to interact with the at least one cutting mechanism 1340. In one embodiment, the at least one cutting mechanism 1340 may comprise a sharpened blade, with FIG. 13 showing a distal end 1388 of the blade and a first cutout 678' of FIG. 6 showing a proximal end 689 of the blade, with the proximal end comprising a blade edge. Therefore, in one embodiment, the cutting mechanism 640-1340 extends from the staple rod 1354 to the tissue interaction portion 130. In one such embodiment, the cutting mechanism 640-1340 may also extend through a middle notch 339' of the telescoping section 324 seen in FIG. 3, while staple pushers 1574-274, as seen in FIGS. 15 and 2, may extend through the outer notches 339.

[0025] Returning now to FIG. 13, as seen, upon contacting the cutting mechanism 1340, the staple rod 1354 is adapted to continue to push the cutting mechanism 1340. As seen in FIG. 6, the cutting mechanism 640 may be moved from the position seen in the first cutout 678' of FIG. 6 to the position seen in the third cutout 678" of FIG. 6. During the movement of the staple rod 1354, as seen in FIG. 13, two or more staple pushers 674, as seen in FIG. 6, may also be transitioned along a substantially similar movement. For example, turning now to FIG. 15, seen is one embodiment comprising two staple pushers 1574 coupled to the staple rod 1554. FIG. 15 may be a starting position of the staple pushers 1574 and cutting mechanism 1540 prior to movement of the staple rod 1554. In one such embodiment, the staple pushers 1574 may comprise a raised leading section 1591 and a raised following section 1592 so that as the staple rod 1554 extends towards the tissue interaction portion 630 seen in FIG. 6 (and subsequently retracting), the staple pushers 1554 will substantially move with the movement of the staple rod 1554. However, since the cutting mechanism 1540 only comprises the raised following section 1592, the cutting mechanism 1540 will only begin to move upon contacting the raised leading surface 1156-1256-1556, as seen in FIGS. 11A, 12 and 15. The movement of the cutting mechanism 1540 is delayed in one embodiment relative to the staple pushers 1574. Therefore, the staple pushers 1574 may begin movement at a first time and the cutting mechanism 1540 may move at a second time, or vice versa. In one embodiment, the staple rod 1554 may also be referred to herein as a "rod" or a "at least one rod," and similar references. Similarly, at least a portion of the staple pushers 1574 may be referred to herein as a stapling shaft and at least a portion of the cutting mechanism 1540 may be referred to as a "cutting shaft."

[0026] Being pushed by the staple rod 1354, and continuing to move towards the tissue interaction device 630, an opposing end of the at least one cutting mechanism 1340, which may comprise a wedge 676, as seen in a first cutout 678' of FIG. 6, may move from the first wedge position seen in the first cutout 678' through the second wedge position seen in the second cutout 678", and to the third wedge position seen in the third cutout 678". In one embodiment, the third wedge position is proximate a base section distal end 677. It is also contemplated that the wedge 676 and the cutting mechanism 640 may be adapted to extend towards the base section distal end 677 through one or more grooves or bores that may extend longitudinally through the base section 662. Such grooves or bores may be seen in FIGS. 8 and 9. Within one of the one or more grooves or bores which the wedge 676 is adapted to extend through may be a staple 681 resting on a staple base 679, as shown in the second cutout 678". The wedge 676 may contact the staple base 679, forcing the staple base 679 and attached staple 681 upward toward the clamping section 664. Upon reaching the tissue clamped between the clamping section 664 and the base section 662, the staple may pierce the tissue and secure the tissue upon contacting an undercarriage of the clamping section 664. Seen in FIG. 14 is one example of a clamping section undercarriage 1478. The cutting mechanism 40 seen in FIG. 13 may subsequently cut the tissue and traveling through a clamping section notch 1479 in the process.

[0027] The cutting mechanism 640 may also extend through one of the notches 339 seen in FIG. 3. For example, the cutting mechanism 640 may extend through a middle notch 339'. FIG. 6B shows one portion of the cutting mechanism 640 through the first cutout 678'. The cutting mechanism 640 may travel from the first cutting mechanism position seen in the first cutout 678' to the second cutting mechanism position seen in the third cutout 678", cutting the tissue, and traveling through a clamping section notch 1479 in the process.

[0028] In one embodiment, the wedges 676 of the one or more staple pushers 674 may travel through the tissue interaction portion 130 seen in FIG. 1 before the cutting mechanism 640. This may be accomplished by initiating movement of the cutting mechanism 640 towards the tissue interaction portion 630 after movement of the one or more staple pushers 674 is initiated towards the tissue interaction portion 630. For example, the staple rod 1554 may first move from a first staple rod position seen in FIG. 15 to a second staple rod position seen in FIG. 13 before the cutting mechanism 1540-1340 begins to move. During this movement of the staple rod 1554 from the first position of FIG. 15 the wedge 676 may move from the first position seen in the first cutout 678' to the third position seen in the third cutout 678", operatively contacting the staples 681 in the process. The movement of the cutting mechanism 640 from the first position seen in the first cutout 678' to the second position seen in the second cutout 678" may be delayed relative to the move-

ment of the wedge 676 from the first position seen in the first cutout 678' to the second position seen in the third cutout 678". Therefore, the tissue clamped between the clamping section 664 and the base section 662 may be stapled before it is cut. The clamping section 1464 is also seen in FIG. 14.

[0029] When the cutting mechanism 640 and the wedge 676 are extended to the position seen in the third cut out 678", the staple rod 1754 may be fully extended towards the tissue interaction section 630. It is contemplated that throughout the specification and claims, though the term "extended" and "telescoping" are used to describe movement of various device features, the actual features of the device 100 may not be extendable or telescoping device features, the terms may simply refer to the device features moving to a different location. For example, as described above with reference to FIGS. 11A and 11B, and in further referring to FIGS. 1 and 17, as the staple rod 1754 extends towards the tissue interaction portion 130, the locking sheath 1760 may be coupled to the staple rod 1754 and may therefore travel with the staple rod 1754 towards the tissue interaction section 130. Upon retraction of the staple rod 1754, occurring after the staples 681 are coupled to the tissue and the cutting mechanism 640 is actuated, an action may occur at the actuator 110 in order to retract the staple pusher 1754. As seen in FIG. 17, a rear leading edge 1797 of the staple pusher 1754 may contact the second locking sheath tab 1753 and push the locking sheath 1760 upon the staple rod 1754 being retracted, retracting the locking sheath 1760 along with the staple pusher 1754. In retracting the locking sheath 1760, the first locking sheath tab 1152 of the locking sheath 1760 will eventually reach a first clamping sheath notch 1851-1051. As seen in FIGS. 18 and 10, the first clamping sheath notch 1851-1051 prevents the locking sheath 1060-1860 from returning towards the tissue interaction portion 130 as the tab 1052 would contact an edge of the notch 1051 if attempted to do so. Therefore, the locking sheath is kept in place upon retracting, and limiting the device 100 to a single use.

[0030] Therefore, a first action on the actuator 110 of FIG. 1 or another actuator known in the art, may move the tissue interaction portion 630-730 from the open position seen in FIG. 7 to the closed position seen in FIGS. 6A and 6B. Such first action, or a second action on the actuator 110 may also move the staple rod 1554 seen in FIG. 15 towards the tissue interaction portion 630, 730. Such movement of the staple rod 1554 also moves the clamping sheath 1560, staple pushers 1574, and cutting mechanism 1540 towards the tissue interaction portion 130. Upon release of the first or second action, or upon a third action at the actuator 110, the staple rod 1154 and clamping sheath 1150 move from the position seen in FIG. 11B to the position seen in FIG. 18, retracting the staple pushers 1574 and cutting mechanism 1540, preventing extension of the staple rod 1154 a second time. Such a mechanism may be referred to herein as a single

application device. Additionally, it is contemplated that the movement of the rod 1554, sheath 1560, pushers 1574 and cutting mechanism 1540 described herein may be substantially parallel to the longitudinal axis 325 seen in FIG. 3.

[0031] Turning now to FIG. 16, seen is a method 1691 of using a medical device 100. One method 1691 starts at 1601 and at 1611 comprises performing a first function on the device actuator 110. It is contemplated that at least one first function may comprise use of the one or more triggers 112 seen in FIG. 1.

[0032] At step 1621 the method 1691 comprises moving the single-use mechanism described above from a first location to a second location. The single-use mechanism 15 may also comprise the clamping sheath 1050. Moving the clamping sheath 1050 from the first location to the second location may comprise moving the clamping sheath 1050 from the first location seen in FIG. 10A to the second location seen in FIG. 10B.

[0033] At 1631 the method 1691 may comprise performing a second function on the device actuator 110. One second function may comprise a function similar to the first function such as, but not limited to, using one or more triggers 112. Upon performing the second function,

25 and as seen at step 1641, the method 1691 may comprise moving a first section of a medical device extension portion 120 from a first retracted location to a second extended location. The medical device extension portion 220 may comprise the staple rod 254 and telescoping sections 224 seen in FIG. 2. Moving the staple rod 254 and telescoping sections 224 from a first retracted location to a second extended location may comprise moving the staple rod 1554 from an initial starting position (i.e., the first retracted location), as seen in FIG. 15, to a fully

35 extended position (i.e., the second extended location), as seen in FIGS. 11A and 11B. The movement of the staple rod 1154-1554 from the first position to the second position may comprise moving the staple rod distal end 1193-1593 towards the tissue interaction portion 130, as seen in FIG. 1. It should be noted that FIGS. 11A, 11B, and 15 may have one or more portions of the device 100 seen in FIG. 1 removed in order to better view other portions of the device 100. Specifically, at least the telescoping sections 224 have been removed from FIGS. 11A,

45 11B, and 15 in order to provide a clearer representation of the operation of the staple rod 1154-1554, cutting mechanism 1540-1140, staple pushers 1574, and clamping sheath 1150-1550. It is fully understood that as the staple pusher 254 moves towards the tissue interaction portion 230, as seen in FIG. 2, the staple pusher 254 will interact with the one or more telescoping sections 224 such that upon performing the second function, the one or more telescoping sections 224 move from the first retracted position, as seen in FIG. 4 to the second extended

50 position seen in FIG. 5. Therefore, as shown in step 1651, the method 1691 further comprises extending a plurality of extension portion telescoping sections 224.

[0034] As the staple rod 254 moves towards the tissue

interaction portion 230, and as seen in FIG. 15 and described above, the staple rod 254 may push against the raised leading section 1591 of the one or more staple pushers 1574, moving the one or more staple pushers 1574 towards and through the tissue interaction portion 230. As seen in FIG. 6B, upon the staple rod pushing the one or more staple pushers 674, a wedge 676 portion of the staple pusher 674 may move from the location seen in the first cutout 678' to the position seen in the third cutout 678", encountering the staple base 679 seen in the second cutout 678" in the process. The wedge 676 would then push the staple base 679 and coupled staple 681 towards the tissue located between the clamping section 664 and the base section 662. The staple 681 may then attach to the tissue. In one embodiment, the staple 681 and/or staple base 679 may comprise a coupling device, and at step 1661 the method comprises attaching the coupling device to the tissue.

[0035] Returning now to FIGS. 2 and 15, as the staple rod 254-1554 moves from the position seen in FIG. 15 toward the tissue interaction portion 230, the staple pusher 1254, as seen in FIG. 12 will approach the cutting mechanism 1240, and eventually interact with the cutting mechanism 1354, as seen in FIG. 13. At this point, as seen in step 1671 of the method 1691, and returning now to FIG. 6B, the cutting mechanism 640 is pushed towards the distal end 677 of the base section 662 of the tissue interaction portion 630, cutting the tissue as it travels to the location seen in the third cutout 678".

[0036] The method 1691 may further comprise moving a first section of a medical device extension portion 120, as seen in FIG. 1, from a first retracted location to a second extended location. The first section may comprise a rod, herein referred to as at least one staple rod 254, also referred to herein as at least one stapling shaft. Such a staple rod 254 may move from a first stapling shaft location such as, but not limited to the stapling shaft position seen in FIG. 15 and the location of the staple pusher 674 seen in the first cutout 678' to a second stapling shaft location, such as, but no limited to the location of the staple pusher 654 seen in the third cutout 678" and the staple rod 1354 seen in FIG. 13.

[0037] In one embodiment, the step 1661 of attaching a coupling device to tissue may further comprise interacting at least one stapling shaft proximal end with at least one staple receiving device. For example the wedge 676 may comprise a proximal end and the base section 679 may comprise a staple receiving device.

[0038] The single-use mechanism may also be referred to as the clamping sheath 1050 and/or the locking sheath 1060, and the clamping sheath 1050 may be referred to as an inner clamping sheath. In the method 1691, a third function on the device actuator 110 seen in FIG. 1 may retract the staple rod 254 from the second extended location. The inner clamping sheath 1050 and the locking sheath 1060 may prevent the rod 254 from returning to the first retracted location by coupling the rod 254 to the locking sheath 1060 and the locking sheath

1060 to the clamping sheath 1050. The inner clamping sheath 1060 may prevent the rod 254 from returning to the first retracted location by coupling the rod 254 to the clamping sheath 1050 at a retracted location.

5 **[0039]** Extending at least one staple pusher 1574, also referred to herein as a stapling shaft, from a first stapling shaft location to a second stapling shaft location may comprise positioning the at least one stapling shaft in at least one notch 339 located in the plurality of extension portion telescoping sections 324, as seen in FIG. 3, and sliding at least a portion of the at least one stapling shaft through the at least one notch 339. Similarly, the cutting mechanism 640 may be referred to herein as at least one cutting shaft, which may be positioned in at least one notch 339 and at least a portion of the at least one cutting shaft may be slid through the at least one notch 339. The outer sheath 122 may prevent buckling of the extension portion telescoping sections.

[0040] The device 100 described above, or at least a portion thereof, may also be referred to herein as a tissue coupling system. For example, the tissue coupling system may also comprise the actuator 110 and the plurality of telescoping sections 432 operatively coupled to the actuator 110, as seen in FIGS. 1 and 4. Alternatively, the tissue coupling system may only comprise the extension portion 220 as seen, for example, in FIG. 2 and/or the tissue interaction portion 630 of FIG. 6, for example. Each of the telescoping sections 432 may comprise an upper section 401 and a lower section 403, as seen in FIG. 4. The upper section 401 may comprise at least one upper section slot 423, while the lower section 403 may comprise at least one lower surface slot 439. The tissue coupling device 130 seen in FIG. 1 and elsewhere may be coupled to at least one of the plurality of telescoping sections 432. Each of the at least one upper section slot 423 may be adapted to receive one of a portion of another telescoping section 432 and at least a portion of the tissue interaction portion 130. In one embodiment, at least one tissue interaction portion 130 may be referred to as a tissue coupling device.

[0041] The tissue coupling device may couple to one or more of a plurality of telescoping sections 432. One or more telescoping sections may be added to and/or removed from the tissue coupling system to one of shorten and lengthen the tissue coupling system. For example, one or more of the plurality of telescoping sections 432 may be one of added to and removed from the tissue coupling system to access a desired tissue.

[0042] In one embodiment, the tissue coupling system may further comprise a locking mechanism adapted to limit use of the tissue coupling device to user-specified number of actions. For example, the locking mechanism may comprise the locking sheath 1050, coupling sheath 1060, and/or the staple rod 1154. At least one of the sheaths may comprise at least one, or a plurality of tabs, as shown and discussed above with respect to FIG. 11. Each of the plurality of tabs may be adapted to interact with another sheath and/or a rod such as, but not limited

to, the staple rod 1154. At least one of the tabs may interact with a notch of another sheath.

[0043] The embodiment may be adapted to release the locking mechanism at the actuator and re-fire the additional staples. In other embodiments where the tissue coupling device comprises a tissue stapler, a user-specified number of actions may comprise a single-use before resetting occurs - such as, but not limited to, inserting additional staples 681 into the device.

[0044] In conclusion, embodiments of the present invention provide for a single gesture to change a mobile computing device mode of operation. Those skilled in the art can readily recognize that numerous variations and substitutions may be made in the invention, its use and its configuration to achieve substantially the same results as achieved by the embodiments described herein. Accordingly, there is no intention to limit the invention to the disclosed exemplary forms. Many variations, modifications and alternative constructions fall within the scope and spirit of the disclosed invention as expressed in the claims.

[0045] The following clauses set out further illustrative aspects useful for understanding the appended claims:

(1) A medical device comprising,

an actuator;

an extension portion operatively coupled to the actuator, the extension portion comprising a first telescoping section and a second telescoping section,

each of the first telescoping section and second telescoping sections having,
at least one extended hook section, the at least one extended hook section having a head portion and a neck portion, and a body section, the body section being one of coupled and integrated to the at least one extended hook section, and wherein, the at least one extended hook section of the first telescoping section is operatively coupled to the body section of the second telescoping section;

a tissue interaction portion operatively coupled to the extension portion, the tissue interaction portion comprising at least one of,

a gripping mechanism,
a stapling mechanism, and
a cutting mechanism; and wherein,

the actuator is adapted to control at least one of the extension portion, gripping mechanism, stapling mechanism, and cutting mechanism.

(2) The medical device of clause 1 further comprising

ing,

a clamping sheath wherein, the clamping sheath at least partially encapsulates the extension portion; and wherein,

the second telescoping body section comprises at least one notch adapted to receive the at least one extended hook section of the first telescoping section; and

the at least one notch of the second telescoping section and the clamping sheath operatively confine the first telescoping section at least one extended hook section to the second telescoping section at least one notch.

(3) The medical device of clause 2 wherein, the at least one notch of the second telescoping section comprises at least one longitudinally-aligned notch;

the extension portion further comprises at least one rod operatively coupled to at least one of the first telescoping section and the second telescoping section; and further comprising,
a single-application device, the single-application device being adapted to limit use of at least one of the gripping mechanism, stapling mechanism, and cutting mechanism to a single use.

(4) The medical device of clause 3 wherein, the single-application device comprises a locking sheath, the locking sheath being adapted to operatively interact with the at least one rod and the clamping sheath.

(5) The medical device of clause 3 wherein, the stapling mechanism comprises,

one or more stapling shafts, and one or more staples; and
the one or more stapling shafts comprise a distal end and a proximal end,

the distal end is adapted to interact with the at least one rod; and
the proximal end comprises a wedge adapted to operatively interact with the one or more staples.

(6) The medical device of clause 3, wherein, the cutting mechanism comprises one or more cutting shafts, the one or more cutting shafts comprising, a distal end adapted to interact with the at least one rod; and
a proximal end comprising at least one sharp edge.

(7) The medical device of clause 1 further comprising a longitudinal axis; and wherein,
at least a portion of the cutting mechanism is adapted to initiate moving substantially parallel to the longi-

tudinal axis at a first period of time; and at least a portion of the stapling mechanism is adapted to initiate moving substantially parallel to the longitudinal axis at a second period of time, the second period of time being different from the first period of time. 5

(8) A method of using a medical device comprising, performing a first function on a device actuator; moving a single-use mechanism from a first location to a second location; performing a second function on the device actuator; 10 moving a first section of a medical device extension portion from a first retracted location to a second extended location; extending a plurality of extension portion telescoping sections; attaching a coupling device to tissue; and cutting the tissue. 15

(9) The method of clause 8 wherein, the first section of the medical device comprises a rod; moving a first section of a medical device extension portion from a first retracted location to a second extended location comprises extending, 20 at least one stapling shaft from a first stapling shaft location to a second stapling shaft location, and the staple rod from the first retracted location to the second extended location; attaching a coupling device to tissue comprises, 25 interacting at least one stapling shaft proximal end with at least one staple receiving device, and attaching one or more staples to the tissue. 30

(10) The method of clause 9, wherein, the single-use mechanism comprises an inner clamping sheath; and further comprising, 40 performing a third function on the device actuator; retracting the staple rod from the second extended location; and using the inner clamping sheath to prevent the rod from returning to the first retracted location. 45

(11) The method of clause 10 wherein, using the inner clamping sheath to prevent the rod from returning to the first retracted location comprises coupling the rod to the clamping sheath at a second retracted location. 50

(12) The method of clause 9 wherein, extending at least one stapling shaft from a first stapling shaft location to a second stapling shaft location comprises, 55 positioning the at least one stapling shaft in at least one notch located in the plurality of extension portion telescoping sections; and sliding at least a portion of the at least one stapling shaft through the at least one notch. 60

(13) The method of clause 12 further comprising, positioning at least one cutting shaft in the at least one notch; and sliding at least a portion of the at least one cutting shaft through the at least one notch. 65

(14) The method of clause 8 wherein, extending the plurality of extension portion telescoping sections comprises, using a sheath to prevent buckling of the extension portion telescoping sections. 70

(15) A tissue coupling system comprising, an actuator; a plurality of telescoping sections operatively coupled to the actuator, wherein, each of the telescoping sections comprises, 75 an upper section, a lower section, at least one upper section slot, and at least one lower section slot, 80 a tissue coupling device coupled to at least one of the plurality of telescoping sections; and wherein, each at least one upper section slot is adapted to receive one of, 85 a portion of another telescoping section, and the tissue coupling device. 90

(16) The tissue coupling system of clause 15 wherein, one or more of the plurality of telescoping sections are one or added to and removed from the tissue coupling system to, 95 one of shorten and lengthen the tissue coupling system; and access tissue. 100

(17) The tissue coupling system of clause 15, further comprising a locking mechanism adapted to limit use of the tissue coupling device to a user-specified number of actions. 105

(18) The tissue coupling system of clause 17, wherein, the tissue coupling device comprises a tissue stapler; and the user-specified number of actions comprises a single-use. 110

(19) The tissue coupling system of clause 15 further comprising at least one sheath, the at least one

sheath comprising a plurality of tabs, each of the plurality of tabs adapted to interact with one of another sheath and a rod.

(20) The tissue coupling system of clause 19, wherein, at least one of each of the plurality of tabs interacts with a notch of another sheath. 5

Claims

1. A device for use in laparoscopic surgery, comprising:

a distal end having a tissue interaction portion 15 (130);

a proximal end having a device actuator (110); a protective sheath (122) having a distal end and a proximal end and extending at least partially between the tissue interaction portion (130) and the device actuator (110); and

a plurality of telescoping sections (254) positioned in and movable relative to the protective sheath (122) between an extended configuration (432), wherein a body section (528') of a first one of the telescoping sections (424') is spaced apart from a body section (528") of a second one of the telescoping sections (424"), and a retracted configuration (534) wherein the body section (528') of the first one of the telescoping sections (424') is in contact with the body section (528") of the second one of the telescoping sections (424"), wherein:

the plurality of telescoping sections (254) are movable from the extended configuration (432) in response to a manipulation of the device actuator (110); and the tissue interaction portion (130) is configured to interact with tissue in response to the manipulation of the device actuator (110). 40

2. The device of claim 1, wherein:

the tissue interaction portion (130) comprises at least one of a gripping mechanism, a clamping section, a coupling mechanism, or a cutting mechanism. 45

3. The device of claim 2, wherein:

the at least one of the gripping mechanism, the clamping section, the coupling mechanism, or the cutting mechanism is configured to interact with tissue in response to the manipulation of the device actuator. 50

4. The device of claim 1, wherein:

the device actuator comprises a rod (1554) configured to move the telescoping sections in response to the manipulation. 55

5. The device of claim 4, further comprising:

a cutting mechanism (640); and at least one staple pusher (1574) positioned in the protective sheath (122), wherein: the at least one staple pusher (1574) is translatable in response to translation of the rod (1554), wherein: the rod (1554) is further configured to move the cutting mechanism (640).

6. The device of claim 5, wherein:

the at least one staple pusher (1574) comprises a raised leading section (1591) and a raised following section (1592) configured to enable distal and proximal movement of the at least one staple pusher (1574) in response to distal and proximal movement of the rod (1554); and the cutting mechanism (1540) comprises a raised following section (1592), whereby movement of the cutting mechanism (1540) is delayed relative to movement of the at least one staple pusher (1574).

7. The device of claim 1, further comprising:

a cutting mechanism (640) positioned in the protective sheath (122) and slidable relative to the protective sheath (122) and through a lower section slot (439) in at least one of the plurality of telescoping sections (424', 424")

8. The device of claim 7, wherein:

the first one of the plurality of telescoping sections (424') further comprises an attachment section (326); and the second one of the plurality of telescoping sections (424") further comprises a body section notch (323) adapted to slidably receive the attachment section (326) of the first one of the plurality of telescoping sections (424'), whereby: the first one and the second one of the plurality of telescoping sections (424', 424") remain coupled in the extended configuration (432) and the retracted configuration (534).

9. The device of claim 8, wherein:

the protective sheath (122), the attachment section (326), and the body section notch (323) are adapted to limit the plurality of telescoping sections (424', 424") to sliding motion.

10. The device of claim 8, wherein:

the device actuator comprises a rod (1554) configured to move the telescoping sections in response to the manipulation,

the rod (1554), the attachment section (326) and the body section notch (323) are adapted to enable movement from the retracted configuration (534) to the extended configuration (432) in response to a second manipulation of the device actuator (110). 5

11. The device of claim 1, further comprising:
at least one of a locking sheath (1060) or a clamping sheath (1050) configured to limit the device to a single use. 10

15

20

25

30

35

40

45

50

55

FIG.1




FIG.2




FIG.3




FIG. 4




FIG.5




FIG.6A




FIG.6B




FIG.7




FIG.8




FIG.9




FIG. 10A




FIG. 10B




FIG. 10B'




FIG. 10A'




FIG. 11A




FIG. 11B





FIG.12






FIG.14




FIG. 15




FIG.16




FIG.17





FIG. 18





EUROPEAN SEARCH REPORT

Application Number
EP 19 21 5299

5

DOCUMENTS CONSIDERED TO BE RELEVANT																		
	Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim															
10	A	US 2012/080332 A1 (SHELTON IV FREDERICK E [US] ET AL) 5 April 2012 (2012-04-05) * paragraphs [0004], [0383] - [0385]; figures 60,61,62,63 *	1															
15	A	----- EP 1 604 607 A1 (HENKE SASS WOLF GMBH [DE]) 14 December 2005 (2005-12-14) * figure 11D *	1															
20	A	----- WO 2012/040981 A1 (SHANGHAI CHUANGYI MEDICAL DEVICE TECH CO LTD [CN]; ZHANG ZUREN [CN]; Z) 5 April 2012 (2012-04-05) * figures 2,10,11,12 *	1															
25	A	----- US 5 865 361 A (MILLIMAN KEITH L [US] ET AL) 2 February 1999 (1999-02-02) * column 13, line 30; figures 40-44 *	1															
30	A	----- US 2011/290851 A1 (SHELTON IV FREDERICK E [US]) 1 December 2011 (2011-12-01) * figures 157,158160 *	1															
35	A	----- US 2010/193567 A1 (SCHEIB CHARLES J [US] ET AL) 5 August 2010 (2010-08-05) * figure 43 *	1															
40	A	----- US 2005/222616 A1 (RETHY CSABA L [US] ET AL) 6 October 2005 (2005-10-06) * paragraph [0210]; figures 4-9 *	1															
45	A	----- WO 2010/027693 A2 (KILLION DOUGLAS P [US]; VIDLUND ROBERT M [US]; CATES CHRISTOPHER U [US] 11 March 2010 (2010-03-11) * figures 34,35 *	1															
50	3	The present search report has been drawn up for all claims	-/-															
55	3	<table border="1"> <tr> <td>Place of search Munich</td> <td>Date of completion of the search 6 April 2020</td> <td>Examiner Assion, Jean-Charles</td> </tr> </table>	Place of search Munich	Date of completion of the search 6 April 2020	Examiner Assion, Jean-Charles	<table border="1"> <tr> <td colspan="2">CATEGORY OF CITED DOCUMENTS</td> </tr> <tr> <td>X : particularly relevant if taken alone</td> <td>T : theory or principle underlying the invention</td> </tr> <tr> <td>Y : particularly relevant if combined with another document of the same category</td> <td>E : earlier patent document, but published on, or after the filing date</td> </tr> <tr> <td>A : technological background</td> <td>D : document cited in the application</td> </tr> <tr> <td>O : non-written disclosure</td> <td>L : document cited for other reasons</td> </tr> <tr> <td>P : intermediate document</td> <td>& : member of the same patent family, corresponding document</td> </tr> </table>	CATEGORY OF CITED DOCUMENTS		X : particularly relevant if taken alone	T : theory or principle underlying the invention	Y : particularly relevant if combined with another document of the same category	E : earlier patent document, but published on, or after the filing date	A : technological background	D : document cited in the application	O : non-written disclosure	L : document cited for other reasons	P : intermediate document	& : member of the same patent family, corresponding document
Place of search Munich	Date of completion of the search 6 April 2020	Examiner Assion, Jean-Charles																
CATEGORY OF CITED DOCUMENTS																		
X : particularly relevant if taken alone	T : theory or principle underlying the invention																	
Y : particularly relevant if combined with another document of the same category	E : earlier patent document, but published on, or after the filing date																	
A : technological background	D : document cited in the application																	
O : non-written disclosure	L : document cited for other reasons																	
P : intermediate document	& : member of the same patent family, corresponding document																	

EPO FORM 1503 03.82 (P04C01)



EUROPEAN SEARCH REPORT

5

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 19 21 5299

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

06-04-2020

10	Patent document cited in search report	Publication date	Patent family member(s)		Publication date
15	US 2012080332 A1	05-04-2012	AU	2011307269 A1	28-03-2013
			AU	2011307270 A1	21-03-2013
			AU	2011307271 A1	28-03-2013
20			AU	2011307282 A1	28-03-2013
			AU	2011307283 A1	28-03-2013
			AU	2011307292 A1	28-03-2013
			AU	2011307376 A1	07-03-2013
25			AU	2011307377 A1	07-03-2013
			AU	2011307378 A1	02-05-2013
			AU	2011307379 A1	21-02-2013
30			AU	2011307380 A1	21-02-2013
			AU	2011307381 A1	07-03-2013
			AU	2011308695 A1	04-04-2013
35			AU	2011308705 A1	04-04-2013
			AU	2011308710 A1	11-04-2013
			AU	2011308711 A1	11-04-2013
			AU	2011308716 A1	11-04-2013
40			AU	2011308760 A1	28-03-2013
			AU	2011308765 A1	04-04-2013
			CA	2811954 A1	05-04-2012
45			CA	2811960 A1	05-04-2012
			CA	2811961 A1	05-04-2012
			CA	2811968 A1	05-04-2012
			CA	2812211 A1	05-04-2012
			CA	2812213 A1	05-04-2012
			CA	2812221 A1	05-04-2012
50			CA	2812535 A1	05-04-2012
			CA	2812537 A1	05-04-2012
			CA	2812541 A1	05-04-2012
			CA	2812546 A1	05-04-2012
			CA	2812773 A1	05-04-2012
			CA	2813205 A1	05-04-2012
55			CA	2813206 A1	05-04-2012
			CA	2813209 A1	05-04-2012
			CA	2813210 A1	05-04-2012
			CA	2813221 A1	05-04-2012
			CA	2813222 A1	05-04-2012
			CA	2813414 A1	05-04-2012
			CN	103118606 A	22-05-2013
			CN	103124525 A	29-05-2013
			CN	103124527 A	29-05-2013
			CN	103124528 A	29-05-2013
			CN	103140177 A	05-06-2013
			CN	103140179 A	05-06-2013
			CN	103140181 A	05-06-2013
			CN	103140182 A	05-06-2013

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

55

page 1 of 6

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 19 21 5299

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

06-04-2020

10	Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		CN	103153202 A	12-06-2013
		CN	103153205 A	12-06-2013
		CN	103153206 A	12-06-2013
15		CN	103153207 A	12-06-2013
		CN	103153208 A	12-06-2013
		EP	2621345 A1	07-08-2013
		EP	2621346 A1	07-08-2013
		EP	2621352 A1	07-08-2013
20		EP	2621353 A1	07-08-2013
		EP	2621354 A1	07-08-2013
		EP	2621355 A1	07-08-2013
		EP	2621357 A2	07-08-2013
		EP	2621358 A2	07-08-2013
		EP	2621359 A2	07-08-2013
25		EP	2621361 A1	07-08-2013
		EP	2621363 A1	07-08-2013
		EP	2621364 A1	07-08-2013
		EP	2621365 A2	07-08-2013
		EP	2621366 A1	07-08-2013
30		EP	2621367 A2	07-08-2013
		EP	2621368 A1	07-08-2013
		EP	2621369 A2	07-08-2013
		EP	2621370 A1	07-08-2013
		EP	2621371 A1	07-08-2013
35		EP	2621372 A1	07-08-2013
		EP	2621376 A2	07-08-2013
		EP	3406204 A1	28-11-2018
		EP	3443913 A1	20-02-2019
		PL	2621352 T3	30-04-2015
		PL	2621357 T3	28-02-2019
		PL	2621361 T3	31-08-2018
40		PL	2621364 T3	31-10-2017
		US	2012080332 A1	05-04-2012
		US	2012080333 A1	05-04-2012
		US	2012080334 A1	05-04-2012
		US	2012080335 A1	05-04-2012
		US	2012080344 A1	05-04-2012
45		US	2012080345 A1	05-04-2012
		US	2012080478 A1	05-04-2012
		US	2012080479 A1	05-04-2012
		US	2012080480 A1	05-04-2012
		US	2012080481 A1	05-04-2012
50		US	2012080482 A1	05-04-2012
		US	2012080483 A1	05-04-2012
		US	2012080484 A1	05-04-2012
		US	2012080485 A1	05-04-2012

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

55

page 2 of 6

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 19 21 5299

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

06-04-2020

10	Patent document cited in search report	Publication date	Patent family member(s)	Publication date
15			US 2012080486 A1	05-04-2012
			US 2012080487 A1	05-04-2012
			US 2012080496 A1	05-04-2012
			US 2012080499 A1	05-04-2012
20			US 2012080500 A1	05-04-2012
			US 2012080501 A1	05-04-2012
			US 2012080502 A1	05-04-2012
			US 2012080503 A1	05-04-2012
25			WO 2012044550 A1	05-04-2012
			WO 2012044551 A1	05-04-2012
			WO 2012044552 A2	05-04-2012
			WO 2012044553 A2	05-04-2012
			WO 2012044554 A1	05-04-2012
30			WO 2012044555 A2	05-04-2012
			WO 2012044630 A1	05-04-2012
			WO 2012044631 A1	05-04-2012
			WO 2012044632 A2	05-04-2012
35			WO 2012044634 A1	05-04-2012
			WO 2012044643 A2	05-04-2012
			WO 2012044644 A2	05-04-2012
			WO 2012044653 A1	05-04-2012
40			WO 2012044654 A2	05-04-2012
			WO 2012044815 A1	05-04-2012
			WO 2012044820 A1	05-04-2012
			WO 2012044838 A1	05-04-2012
			WO 2012044844 A2	05-04-2012
45			WO 2012044848 A1	05-04-2012
			WO 2012044853 A1	05-04-2012
			WO 2012044854 A1	05-04-2012
			WO 2012044859 A1	05-04-2012
50	EP 1604607	A1 14-12-2005	AT 341271 T	15-10-2006
			CN 1723835 A	25-01-2006
			DE 102004027850 A1	05-01-2006
			EP 1604607 A1	14-12-2005
			ES 2273299 T3	01-05-2007
			US 2005272978 A1	08-12-2005
55	WO 2012040981	A1 05-04-2012	CN 102440820 A	09-05-2012
			WO 2012040981 A1	05-04-2012
	US 5865361	A 02-02-1999	AU 750646 B2	25-07-2002
			CA 2304750 A1	01-04-1999
			CA 2552427 A1	01-04-1999
			CA 2571468 A1	01-04-1999
			CA 2571576 A1	01-04-1999

EPO FORM P0459
For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

page 3 of 6

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 19 21 5299

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

06-04-2020

10	Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		CA	2571579 A1	01-04-1999
		CA	2666604 A1	01-04-1999
		DE	69836436 T2	27-09-2007
15		EP	1021130 A1	26-07-2000
		EP	1762190 A2	14-03-2007
		EP	2113207 A2	04-11-2009
		EP	2156796 A1	24-02-2010
		EP	2286736 A1	23-02-2011
		EP	2298185 A2	23-03-2011
20		EP	2298186 A2	23-03-2011
		EP	2316348 A1	04-05-2011
		EP	2818124 A1	31-12-2014
		EP	3009079 A1	20-04-2016
		ES	2275317 T3	01-06-2007
25		ES	2335523 T3	29-03-2010
		ES	2372662 T3	25-01-2012
		ES	2398916 T3	22-03-2013
		ES	2399116 T3	26-03-2013
		ES	2399811 T3	03-04-2013
		ES	2557032 T3	21-01-2016
30		JP	4257029 B2	22-04-2009
		JP	4500342 B2	14-07-2010
		JP	4500343 B2	14-07-2010
		JP	4500344 B2	14-07-2010
		JP	5084061 B2	28-11-2012
		JP	2001517473 A	09-10-2001
35		JP	2008086786 A	17-04-2008
		JP	2008086787 A	17-04-2008
		JP	2008086788 A	17-04-2008
		JP	2008100085 A	01-05-2008
		JP	2010148890 A	08-07-2010
		JP	2010234061 A	21-10-2010
40		US	5865361 A	02-02-1999
		US	6079606 A	27-06-2000
		US	6241139 B1	05-06-2001
		US	6330965 B1	18-12-2001
		US	2002117533 A1	29-08-2002
45		US	2004108357 A1	10-06-2004
		US	2005067460 A1	31-03-2005
		US	2006049229 A1	09-03-2006
		US	2006255090 A1	16-11-2006
		US	2008041916 A1	21-02-2008
		US	2009261142 A1	22-10-2009
50		US	2010237131 A1	23-09-2010
		US	2011233260 A1	29-09-2011
		US	2012043368 A1	23-02-2012

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

55

page 4 of 6

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 19 21 5299

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

06-04-2020

10	Patent document cited in search report	Publication date	Patent family member(s)	Publication date		
15			US 2012055974 A1	08-03-2012		
			US 2012241495 A1	27-09-2012		
			US 2012305627 A1	06-12-2012		
			US 2013140342 A1	06-06-2013		
			US 2014110454 A1	24-04-2014		
			US 2015090766 A1	02-04-2015		
			US 2015209041 A1	30-07-2015		
			US 2017112498 A1	27-04-2017		
			WO 9915086 A1	01-04-1999		

20	US 2011290851 A1 01-12-2011		BR 112013030566 A2	27-09-2016		
			CN 103747748 A	23-04-2014		
			CN 107625541 A	26-01-2018		
			EP 2713897 A1	09-04-2014		
			EP 3009094 A1	20-04-2016		
			EP 3539481 A1	18-09-2019		
			EP 3539498 A1	18-09-2019		
			PL 2713897 T3	29-01-2016		
			US 2011290851 A1	01-12-2011		
			US 2014191014 A1	10-07-2014		
25			US 2014191015 A1	10-07-2014		
			US 2017311949 A1	02-11-2017		
			US 2018317918 A1	08-11-2018		
			US 2019343518 A1	14-11-2019		
			WO 2012166468 A1	06-12-2012		

			US 2010193567 A1 05-08-2010			
			AU 2010210789 A1	25-08-2011		
			BR PI1008732 A2	08-03-2016		
			CA 2751377 A1	12-08-2010		
30			CN 102368960 A	07-03-2012		
			EP 2393427 A1	14-12-2011		
			EP 3292826 A1	14-03-2018		
			EP 3542735 A1	25-09-2019		
			JP 5752607 B2	22-07-2015		
			JP 2012516752 A	26-07-2012		
			PL 2393427 T3	30-05-2018		
			RU 2011136722 A	10-03-2013		
			US 2010193567 A1	05-08-2010		
			WO 2010090934 A1	12-08-2010		
35			-----			
			US 2005222616 A1 06-10-2005			
			US 2005222616 A1	06-10-2005		
			US 2007125828 A1	07-06-2007		
			US 2008116244 A1	22-05-2008		
			US 2008302854 A1	11-12-2008		
			US 2010193570 A1	05-08-2010		
40			US 2010282817 A1	11-11-2010		

			US 2005222616 A1 06-10-2005			
			US 2007125828 A1	07-06-2007		
			US 2008116244 A1	22-05-2008		
			US 2008302854 A1	11-12-2008		
45			US 2010193570 A1	05-08-2010		
			US 2010282817 A1	11-11-2010		

			US 2005222616 A1 06-10-2005			
			US 2007125828 A1	07-06-2007		
50			US 2008116244 A1	22-05-2008		
			US 2008302854 A1	11-12-2008		
			US 2010193570 A1	05-08-2010		
			US 2010282817 A1	11-11-2010		

55	EPO FORM P0459	For more details about this annex : see Official Journal of the European Patent Office, No. 12/82				

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 19 21 5299

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

06-04-2020

10	Patent document cited in search report	Publication date	Patent family member(s)		Publication date
15			US	2012085808 A1	12-04-2012
			US	2013306703 A1	21-11-2013
			US	2016338702 A1	24-11-2016
			US	2019159777 A1	30-05-2019
20	WO 2010027693 A2 11-03-2010	AU 2009288440 A1 CA 2734269 A1 CR 20110105 A EP 2330981 A2 EP 2430982 A2 JP 5616891 B2 JP 2012501220 A US 2010211000 A1 US 2013338707 A1 WO 2010027693 A2	AU	2009288440 A1	11-03-2010
			CA	2734269 A1	11-03-2010
			CR	20110105 A	24-10-2011
			EP	2330981 A2	15-06-2011
			EP	2430982 A2	21-03-2012
			JP	5616891 B2	29-10-2014
			JP	2012501220 A	19-01-2012
			US	2010211000 A1	19-08-2010
			US	2013338707 A1	19-12-2013
			WO	2010027693 A2	11-03-2010
25	US 2005023324 A1 03-02-2005	AU 2004220721 A1 AU 2010241206 A1 BR PI0406039 A CA 2485021 A1 CN 1606968 A EP 1523944 A1 US 2005023324 A1	AU	2004220721 A1	05-05-2005
			AU	2010241206 A1	25-11-2010
			BR	PI0406039 A	28-06-2005
			CA	2485021 A1	15-04-2005
			CN	1606968 A	20-04-2005
			EP	1523944 A1	20-04-2005
			US	2005023324 A1	03-02-2005
30	US 5673841 A 07-10-1997	AU 696699 B2 CA 2165399 A1 DE 69525602 D1 DE 69525602 T2 EP 0717959 A2 JP 4153537 B2 JP H08336540 A JP 2006289110 A US 5632432 A US 5669544 A	AU	696699 B2	17-09-1998
			CA	2165399 A1	20-06-1996
			DE	69525602 D1	04-04-2002
			DE	69525602 T2	18-07-2002
			EP	0717959 A2	26-06-1996
			JP	4153537 B2	24-09-2008
			JP	H08336540 A	24-12-1996
			JP	2006289110 A	26-10-2006
			US	5632432 A	27-05-1997
			US	5669544 A	23-09-1997
35		US 5673840 A US 5673841 A US 5680982 A US 5692668 A US 5826776 A	US	5673840 A	07-10-1997
			US	5673841 A	07-10-1997
			US	5680982 A	28-10-1997
			US	5692668 A	02-12-1997
			US	5826776 A	27-10-1998
40					
45					
50					

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

55

page 6 of 6

专利名称(译)	腹腔镜手术医疗设备		
公开(公告)号	EP3653136A1	公开(公告)日	2020-05-20
申请号	EP2019215299	申请日	2013-12-26
[标]发明人	MATA VINCENT BACHMAN ALAN GRANGER RICHARD		
发明人	MATA, VINCENT BACHMAN, ALAN GRANGER, RICHARD		
IPC分类号	A61B17/072		
CPC分类号	A61B17/07207 A61B2017/00336 A61B2017/00991 A61B2017/2901 A61B2017/320052 A61B2090/0814 A61B17/3205		
代理机构(译)	吉莱斯皮RICHARD		
优先权	13/733815 2013-01-03 US PCT/US2013/077801 2013-12-26 WO		
外部链接	Espacenet		

摘要(译)

一种医疗装置，包括致动器，延伸部分和组织相互作用部分。延伸部分联接到致动器并且包括至少第一伸缩部分和第二伸缩部分，每个伸缩部分具有 (i) 至少一个具有头部和颈部的延伸的钩部分，以及 (ii) 至少一个主体部分。至少其中之一与至少一个延伸的钩部分相结合并形成一体。第一伸缩部分的至少一个延伸的钩部分可操作地联接到第二伸缩部分的主体部分。组织相互作用部分可操作地联接到延伸部分，并且包括抓握机构，缝合机构和切割机构中的至少一个。致动器适于控制延伸部分和组织相互作用部分中的至少一个。

FIG.9

