



US007207990B2

(12) **United States Patent**
Lands et al.

(10) **Patent No.:** **US 7,207,990 B2**
(45) **Date of Patent:** ***Apr. 24, 2007**

(54) **LAPAROSCOPIC BIPOLAR
ELECTROSURGICAL INSTRUMENT**

(58) **Field of Classification Search** 606/46,
606/48-52, 170, 207, 208
See application file for complete search history.

(75) Inventors: **Michael John Lands**, Clearwater, FL
(US); **Stephen Wade Lukianow**,
Boulder, CO (US); **Donald Robert**
Loeffler, Louisville, CO (US); **James**
Steven Cunningham, Boulder, CO (US);
Kate Ryland Lawes, Superior, CO
(US); **Daniel Lee Trimberger, II**,
Greeley, CO (US); **Mathew Erle**
Mitchell, Boulder, CO (US); **Jenifer**
Serafin Kennedy, Boulder, CO (US)

(73) Assignee: **Sherwood Services Ag**, Schaffhausen
(CH)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **11/169,927**

(22) Filed: **Jun. 29, 2005**

(65) **Prior Publication Data**

US 2006/0009764 A1 Jan. 12, 2006

Related U.S. Application Data

(63) Continuation of application No. 10/243,274, filed on
Sep. 13, 2002, now Pat. No. 6,960,210, which is a
continuation of application No. 09/591,330, filed on
Jun. 9, 2000, now Pat. No. 6,451,018, which is a
continuation of application No. 08/970,472, filed on
Nov. 14, 1997, now Pat. No. 6,228,083.


(51) **Int. Cl.**
A61B 18/14 (2006.01)

(52) **U.S. Cl.** **606/50; 606/46; 606/48;**
606/51; 606/207; 606/208

(56) **References Cited**

U.S. PATENT DOCUMENTS

371,664 A	10/1887	Brannan et al.
702,472 A	6/1902	Pignolet
728,883 A	5/1903	Downes
1,586,645 A	6/1926	Bierman
2,002,594 A	5/1935	Wappler et al.
2,011,169 A	8/1935	Wappler
2,031,682 A	2/1936	Wappler et al.
2,176,479 A	10/1939	Willis
2,305,156 A	12/1942	Grubel
2,632,661 A	3/1953	Cristofv
2,668,538 A	2/1954	Baker
2,796,065 A	6/1957	Kapp
3,459,187 A	8/1969	Pallotta
3,643,663 A	2/1972	Sutter
3,651,811 A	3/1972	Hildebrandt et al.
3,862,630 A	1/1975	Balamuth
3,866,610 A	2/1975	Kletschka
3,911,766 A	10/1975	Fridolph et al.
3,920,021 A	11/1975	Hiltebrandt
3,921,641 A	11/1975	Hulka
3,938,527 A	2/1976	Rioux et al.
3,952,749 A	4/1976	Fridolph et al.
4,005,714 A	2/1977	Hiltebrandt
4,074,718 A	2/1978	Morrison, Jr.
4,088,134 A	5/1978	Mazzariello
4,165,746 A	8/1979	Burgin
4,300,564 A	11/1981	Furihata
4,370,980 A	2/1983	Lottick
4,416,276 A	11/1983	Newton et al.
4,452,246 A	6/1984	Bader et al.
4,492,231 A	1/1985	Auth
4,552,143 A	11/1985	Lottick
4,574,804 A	3/1986	Kurwa
4,597,379 A	7/1986	Kihn et al.
4,600,007 A	7/1986	Lahodny et al.
4,655,216 A	4/1987	Tischer
4,657,016 A	4/1987	Garito et al.
4,662,372 A	5/1987	Sharkany et al.
4,671,274 A	6/1987	Sorochenko
4,685,459 A	8/1987	Xoch et al.
D295,893 S	5/1988	Sharkany et al.



US 7,207,990 B2

Page 2

D295,894 S	5/1988	Sharkany et al.	5,496,317 A	3/1996	Goble et al.
4,763,669 A	8/1988	Jaeger	5,496,347 A	3/1996	Hashiguchi et al.
4,827,929 A	5/1989	Hodge	5,499,997 A	3/1996	Sharpe et al.
4,887,612 A	12/1989	Esser et al.	5,509,922 A	4/1996	Aranyi et al.
4,938,761 A	7/1990	Ensslin	5,514,134 A	5/1996	Rydell et al.
4,985,030 A	1/1991	Melzer et al.	5,527,313 A	6/1996	Scott et al.
5,007,908 A	4/1991	Rydell	5,531,744 A	7/1996	Nardella et al.
5,026,370 A	6/1991	Lottick	5,536,251 A	7/1996	Evard et al.
5,099,840 A	3/1992	Goble et al.	5,540,684 A	7/1996	Hassler, Jr.
5,116,332 A	5/1992	Lottick	5,540,685 A	7/1996	Parins et al.
5,147,357 A	9/1992	Rose et al.	5,540,715 A	7/1996	Katsaros et al.
5,151,102 A	9/1992	Xamiyama et al.	5,558,672 A	9/1996	Edwards et al.
5,176,695 A	1/1993	Dulebohn	5,569,241 A	10/1996	Edwards
5,190,541 A	3/1993	Abele et al.	5,569,243 A	10/1996	Kortenbach et al.
5,197,964 A	3/1993	Parins	5,571,100 A	11/1996	Goble et al.
5,215,101 A	6/1993	Jacobs et al.	5,573,424 A	11/1996	Poppe
5,217,457 A	6/1993	Delahuerga et al.	5,573,535 A	11/1996	Viklund
5,217,458 A	6/1993	Parins	5,582,611 A	12/1996	Tsukagoshi et al.
5,219,354 A	6/1993	Choudhury et al.	5,585,896 A	12/1996	Yamazaki et al.
5,244,462 A	9/1993	Delahuerga et al.	5,590,570 A	1/1997	LeMaire, III et al.
5,250,047 A	10/1993	Rydell	5,601,601 A	2/1997	Tal et al.
5,258,006 A	11/1993	Rydell et al.	5,603,711 A	2/1997	Parins et al.
5,261,918 A	11/1993	Phillips et al.	5,603,723 A	2/1997	Aranyi et al.
5,275,615 A	1/1994	Rose	5,626,578 A	5/1997	Tihon
5,277,201 A	1/1994	Stern	5,626,609 A	5/1997	Zvenyatsky et al.
5,282,799 A	2/1994	Rydell	5,630,833 A	5/1997	Katsaros et al.
5,290,286 A	3/1994	Parins	5,637,110 A	6/1997	Pennybacker et al.
5,304,203 A	4/1994	El-Mallawany et al.	5,643,294 A	7/1997	Tovey et al.
5,308,357 A	5/1994	Lichtman	5,647,869 A	7/1997	Goble et al.
5,318,589 A	6/1994	Lichtman	5,647,871 A	7/1997	Levine et al.
5,324,289 A	6/1994	Eggers	5,649,959 A	7/1997	Hannam et al.
5,330,471 A	7/1994	Eggers	5,658,281 A	8/1997	Heard
5,334,183 A	8/1994	Wuchinich	5,662,667 A	9/1997	Knodel
5,334,215 A	8/1994	Chen	5,667,526 A	9/1997	Levin
5,336,221 A	8/1994	Anderson	5,674,220 A	10/1997	Fox et al.
5,342,359 A	8/1994	Rydell	5,681,282 A	10/1997	Eggers et al.
5,342,381 A	8/1994	Tidemand	5,693,051 A	12/1997	Schulze et al.
5,342,393 A	8/1994	Stack	5,695,522 A	12/1997	LeMaire, III et al.
5,352,222 A	10/1994	Rydell	5,700,261 A	12/1997	Brinkerhoff
5,354,271 A	10/1994	Voda	5,702,390 A	12/1997	Austin et al.
5,356,408 A	10/1994	Rydell	5,707,369 A	1/1998	Vaitekunas et al.
5,366,477 A	11/1994	LeMarie, III et al.	5,709,680 A	1/1998	Yates et al.
5,383,897 A	1/1995	Wholey	5,716,366 A	2/1998	Yates
5,389,098 A	2/1995	Tsuruta et al.	5,720,744 A	2/1998	Eggleston et al.
5,389,104 A	2/1995	Hahnen et al.	5,727,428 A	3/1998	LeMaire, III et al.
5,391,166 A	2/1995	Eggers	5,735,848 A	4/1998	Yates et al.
5,391,183 A	2/1995	Janzen et al.	5,743,906 A	4/1998	Parins et al.
5,403,312 A	4/1995	Yates et al.	5,755,717 A	5/1998	Yates et al.
5,411,519 A	5/1995	Tovey et al.	5,766,130 A	6/1998	Selmonosky
5,411,520 A	5/1995	Nash et al.	5,766,166 A	6/1998	Hooven
5,413,571 A	5/1995	Katsaros et al.	5,766,170 A	6/1998	Eggers
5,415,657 A	5/1995	Taymor-Luria	5,769,849 A	6/1998	Eggers
5,422,567 A	6/1995	Matsunaga	5,776,128 A	7/1998	Eggers
5,423,810 A	6/1995	Goble et al.	5,776,130 A	7/1998	Buyse et al.
5,425,739 A	6/1995	Jessen	5,779,701 A	7/1998	McBrayer et al.
5,429,616 A	7/1995	Schaffer	5,792,137 A	8/1998	Carr et al.
5,431,674 A	7/1995	Basile et al.	5,792,177 A	8/1998	Kaseda
5,437,292 A	8/1995	Kipshidze et al.	5,797,938 A	8/1998	Paraschac et al.
5,438,302 A	8/1995	Goble	5,797,958 A	8/1998	Yoon
5,441,517 A	8/1995	Kensey et al.	5,800,449 A	9/1998	Wales
5,443,463 A	8/1995	Stern et al.	5,810,808 A	9/1998	Eggers
5,443,464 A	8/1995	Russell et al.	5,810,811 A	9/1998	Yates et al.
5,443,480 A	8/1995	Jacobs et al.	5,814,043 A	9/1998	Shapeton
5,445,638 A	8/1995	Rydell et al.	5,817,093 A	10/1998	Williamson, IV et al.
5,445,658 A	8/1995	Durrfeld et al.	5,820,630 A	10/1998	Lind
5,451,224 A	9/1995	Goble et al.	5,827,271 A	10/1998	Buyse et al.
5,456,684 A	10/1995	Schmidt et al.	5,827,279 A	10/1998	Hughett et al.
5,458,598 A	10/1995	Feinberg et al.	5,827,281 A	10/1998	Levin
5,460,629 A	10/1995	Shlain et al.	5,833,690 A	11/1998	Yates et al.
5,462,546 A	10/1995	Rydell	5,843,080 A	12/1998	Fleenor et al.
5,472,443 A	12/1995	Cordis et al.	5,849,022 A	12/1998	Sakashita et al.
5,478,351 A	12/1995	Meade et al.	5,853,412 A	12/1998	Mayenberger
5,484,436 A	1/1996	Eggers et al.	5,876,401 A	3/1999	Schulze et al.

5,891,141 A	4/1999	Rydell	6,425,896 B1	7/2002	Baltschun et al.
5,891,142 A	4/1999	Eggers et al.	6,440,144 B1	8/2002	Bacher
5,893,863 A	4/1999	Yoon	6,443,970 B1	9/2002	Schulze et al.
5,893,875 A	4/1999	O'Connor et al.	6,451,018 B1	9/2002	Lands et al.
5,902,301 A	5/1999	Olig	6,458,128 B1	10/2002	Schulze
5,906,630 A	5/1999	Anderhub et al.	6,458,130 B1	10/2002	Frazier et al.
5,908,420 A	6/1999	Parins et al.	6,464,702 B2	10/2002	Schulze et al.
5,913,874 A	6/1999	Berns et al.	6,464,704 B2	10/2002	Schmaltz et al.
5,921,984 A	7/1999	Sutcu et al.	6,511,480 B1	1/2003	Tetzlaff et al.
5,935,126 A	8/1999	Riza	6,585,735 B1	7/2003	Frazier et al.
5,944,718 A	8/1999	Dafforn et al.	6,602,252 B2	8/2003	Mollenauer
5,951,549 A	9/1999	Richardson et al.	6,620,161 B2	9/2003	Schulze et al.
5,954,720 A	9/1999	Wilson et al.	6,626,901 B1	9/2003	Treat et al.
5,961,514 A	10/1999	Long et al.	6,652,521 B2	11/2003	Schulze
5,976,132 A	11/1999	Morris	6,660,072 B2	12/2003	Chatterjee
5,984,939 A	11/1999	Yoon	6,682,527 B2	1/2004	Strul
5,989,277 A	11/1999	LeMaire, III et al.	6,682,528 B2	1/2004	Frazier et al.
6,004,335 A	12/1999	Vaitekunas et al.	6,695,840 B2	2/2004	Schulze
6,010,516 A	1/2000	Hulka	6,726,686 B2	4/2004	Buyse et al.
6,024,741 A	2/2000	Williamson et al.	6,733,498 B2	5/2004	Paton et al.
6,024,744 A	2/2000	Kese et al.	6,743,229 B2	6/2004	Buyse et al.
6,033,399 A	3/2000	Gines	6,770,072 B1	8/2004	Truckai et al.
6,039,733 A	3/2000	Buyse et al.	D496,997 S	10/2004	Dycus et al.
6,041,679 A	3/2000	Slater et al.	D499,181 S	11/2004	Dycus et al.
6,050,996 A	4/2000	Schmaltz et al.	6,860,880 B2	3/2005	Treat et al.
6,053,914 A	4/2000	Eggers et al.	6,926,716 B2	8/2005	Baker et al.
6,053,933 A	4/2000	Balazs et al.	6,929,644 B2	8/2005	Truckai et al.
D424,694 S	5/2000	Tetzlaff et al.	6,942,662 B2	9/2005	Goble et al.
D425,201 S	5/2000	Tetzlaff et al.	6,960,210 B2	11/2005	Lands et al.
RE36,795 E	7/2000	Rydell	2002/0013583 A1	1/2002	Camran et al.
6,083,223 A	7/2000	Baker	2002/0099372 A1	7/2002	Schulze et al.
6,086,586 A	7/2000	Hooven	2002/0107517 A1	8/2002	Witt et al.
6,090,107 A	7/2000	Borgmeier et al.	2002/0111624 A1	8/2002	Witt et al.
6,096,037 A	8/2000	Mulier et al.	2002/0188294 A1	12/2002	Couture et al.
6,099,550 A	8/2000	Yoon	2003/0014052 A1	1/2003	Buyse et al.
6,102,909 A	8/2000	Chen et al.	2003/0014053 A1	1/2003	Nguyen et al.
6,110,171 A	8/2000	Rydell	2003/0018331 A1	1/2003	Dycus et al.
6,113,596 A	9/2000	Hooven et al.	2003/0018332 A1	1/2003	Schmaltz et al.
6,113,598 A	9/2000	Baker	2003/0032956 A1	2/2003	Lands et al.
H1904 H	10/2000	Yates et al.	2003/0069571 A1	4/2003	Treat et al.
6,126,658 A	10/2000	Baker	2003/0078578 A1	4/2003	Truckai Csaba et al.
6,152,923 A	11/2000	Ryan	2003/0109875 A1	6/2003	Tetzlaff et al.
6,174,309 B1	1/2001	Wrublewski et al.	2003/0139741 A1	7/2003	Goble et al.
6,179,834 B1	1/2001	Buyse et al.	2003/0139742 A1	7/2003	Wampler et al.
6,179,837 B1	1/2001	Hooven	2003/0158549 A1	8/2003	Swanson
6,183,467 B1	2/2001	Shapeton et al.	2003/0181910 A1	9/2003	Dycus et al.
6,187,003 B1	2/2001	Buyse et al.	2003/0199869 A1	10/2003	Johnson et al.
6,190,386 B1	2/2001	Rydell	2003/0216732 A1	11/2003	Truckai et al.
6,193,718 B1	2/2001	Kortenbach et al.	2003/0220637 A1	11/2003	Truckai et al.
6,206,877 B1	3/2001	Kese et al.	2003/0229344 A1	12/2003	Dycus et al.
6,224,593 B1	5/2001	Ryan et al.	2003/0236325 A1	12/2003	Bonora
6,228,080 B1	5/2001	Gines	2003/0236326 A1	12/2003	Bonora
6,228,083 B1	5/2001	Lands et al.	2004/0030330 A1	2/2004	Brassell et al.
6,267,761 B1	7/2001	Ryan	2004/0030332 A1	2/2004	Knowlton et al.
6,270,508 B1	8/2001	Klieman et al.	2004/0049185 A1	3/2004	Latterell et al.
6,273,887 B1	8/2001	Yamauchi et al.	2004/0082952 A1	4/2004	Dycus et al.
6,277,117 B1	8/2001	Tetzlaff et al.	2004/0087943 A1	5/2004	Dycus et al.
6,280,458 B1	8/2001	Boche et al.	2004/0115296 A1	6/2004	Duffin
6,283,961 B1	9/2001	Underwood et al.	2004/0116924 A1	6/2004	Dycus et al.
D449,886 S	10/2001	Tetzlaff et al.	2004/0116979 A1	6/2004	Truckai et al.
6,322,561 B1	11/2001	Eggers et al.	2004/0122423 A1	6/2004	Dycus et al.
6,334,860 B1	1/2002	Dorn	2004/0143263 A1	7/2004	Schechter et al.
6,334,861 B1	1/2002	Chandler et al.	2004/0147925 A1	7/2004	Buyse et al.
6,350,264 B1	2/2002	Hooven	2004/0162557 A1	8/2004	Tetzlaff et al.
6,352,536 B1	3/2002	Buyse et al.	2004/0176762 A1	9/2004	Lawes et al.
D457,958 S	5/2002	Dycus et al.	2004/0193153 A1	9/2004	Sarter et al.
D457,959 S	5/2002	Tetzlaff et al.	2004/0225288 A1	11/2004	Buyse et al.
6,387,094 B1	5/2002	Eitenmuller	2004/0230189 A1	11/2004	Keppel
6,398,779 B1	6/2002	Buyse et al.	2004/0236325 A1	11/2004	Tetzlaff et al.
6,402,747 B1	6/2002	Lindemann et al.	2004/0243125 A1	12/2004	Dycus et al.
6,409,728 B1	6/2002	Ehr et al.	2004/0249371 A1	12/2004	Dycus et al.
H2037 H	7/2002	Yates et al.	2004/0249374 A1	12/2004	Tetzlaff et al.
6,419,675 B1	7/2002	Gallo, Sr.	2004/0250419 A1	12/2004	Sremcich et al.

2004/0254573	A1	12/2004	Dycus et al.	JP	5-40112	2/1993
2005/0004564	A1	1/2005	Wham et al.	JP	06343644	A2 12/1994
2005/0004568	A1	1/2005	Lawes et al.	JP	07265328	A2 10/1995
2005/0004570	A1	1/2005	Chapman et al.	JP	08056955	A2 3/1996
2005/0021025	A1	1/2005	Buyse et al.	JP	08252263	A2 10/1996
2005/0021026	A1	1/2005	Baily	JP	09010223	A2 1/1997
2005/0021027	A1	1/2005	Shields et al.	JP	11244298	A2 9/1999
2005/0033278	A1	2/2005	McClurken et al.	JP	2000342599	A2 12/2000
2005/0101951	A1	5/2005	Wham et al.	JP	2000350732	A2 12/2000
2005/0101952	A1	5/2005	Lands et al.	JP	2001008944	A2 1/2001
2005/0107784	A1	5/2005	Moses et al.	JP	2001029356	A2 2/2001
2005/0107785	A1	5/2005	Dycus et al.	JP	2001128990	A2 5/2001
2005/0113818	A1	5/2005	Sartor et al.	RU	4013867	10/1973
2005/0113819	A1	5/2005	Wham et al.	SU	401367	11/1974
2005/0113826	A1	5/2005	Johnson et al.	WO	WO 92/06642	4/1992
2005/0113827	A1	5/2005	Dumbauld et al.	WO	WO 94/06524	A 4/1994
2005/0113828	A1	5/2005	Shields et al.	WO	WO 94/08524	A 4/1994
2005/0119655	A1	6/2005	Moses et al.	WO	WO 95/02369	1/1995
2005/0149151	A1	7/2005	Orszulak et al.	WO	WO 95/07662	3/1995
2006/0079891	A1	4/2006	Arts et al.	WO	WO 96/022056	7/1996
2006/0161150	A1	7/2006	Keppel	WO	WO 96/13218	9/1996
2006/0167450	A1	7/2006	Johnson et al.	WO	WO 97/00646	1/1997
2006/0167452	A1	7/2006	Moses et al.	WO	WO 97/00647	1/1997
2006/0173452	A1	8/2006	Buyse et al.	WO	WO 97/10764	3/1997
2006/0189980	A1	8/2006	Johnson et al.	WO	WO 97/24073	7/1997
2006/0189981	A1	8/2006	Dycus et al.	WO	WO 97/24993	7/1997
2006/0190035	A1	8/2006	Hushka et al.	WO	WO 98/27880	7/1998
2006/0217709	A1	9/2006	Couture et al.	WO	WO 99/03407	1/1999
2006/0224158	A1	10/2006	Odom et al.	WO	WO 99/03408	1/1999

FOREIGN PATENT DOCUMENTS

CA	2104423	2/1994	WO	WO 99/03409	1/1999
DE	2415263	10/1975	WO	WO 99/12488	3/1999
DE	8712328	3/1988	WO	WO 99/40857	8/1999
DE	29616210	1/1997	WO	WO 99/40861	8/1999
DE	19608716	4/1997	WO	WO 99/040861	8/1999
DE	19751108	5/1999	WO	WO 99/51158	10/1999
EP	0364216 A1	4/1990	WO	WO 99/066850	12/1999
EP	518230 A1	12/1992	WO	WO 99/66850 A	12/1999
EP	0 541 930 B1	5/1993	WO	WO 00/24330	5/2000
EP	0572131	12/1993	WO	WO 00/24331	5/2000
EP	584787 A1	3/1994	WO	WO 00/41638	7/2000
EP	0623316 A1	11/1994	WO	WO 00/53112	9/2000
EP	0624348 A2	11/1994	WO	WO 01/17448 A	3/2001
EP	0650701 A1	5/1995	WO	WO 01/54604	8/2001
EP	0694290 A3	3/1996	WO	WO 02/07627	1/2002
EP	0717966 A1	6/1996	WO	WO 02/080783	10/2002
EP	0754437 A3	3/1997	WO	WO 02/080784	10/2002
EP	853922 A1	7/1998	WO	WO 02/080785	10/2002
EP	0875209 A1	11/1998	WO	WO 02/080786	10/2002
EP	0878169 A1	11/1998	WO	WO 02/080793	10/2002
EP	0887046 A3	1/1999	WO	WO 02/080794	10/2002
EP	0923907 A1	6/1999	WO	WO 02/080795	10/2002
EP	0986990 A1	3/2000	WO	WO 02/080796	10/2002
EP	1034747 A1	9/2000	WO	WO 02/080797	10/2002
EP	1034748 A1	9/2000	WO	WO 02/080798	10/2002
EP	1025807 A3	10/2000	WO	WO 02/080799	10/2002
EP	1034746 A3	10/2000	WO	WO 02/081170	10/2002
EP	1050278 A1	11/2000	WO	WO 03/101311	12/2003
EP	1053719 A1	11/2000	WO	WO 04/032777	4/2004
EP	1053720 A1	11/2000	WO	WO 2004/032777	4/2004
EP	1055399 A1	11/2000	WO	WO 04/052221	6/2004
EP	1055400 A1	11/2000	WO	WO 2004/052221	6/2004
EP	1080694 A1	3/2001	WO	WO 04/073490	9/2004
EP	1082944 A1	3/2001	WO	WO 04/082495	9/2004
EP	1159926 A2	12/2001	WO	WO 2004/073490	9/2004
EP	1330991 A1	7/2003	WO	WO 2004/082495	9/2004
EP	1486177 A2	6/2004	WO	WO 04/098383	11/2004
EP	1532932 A1	5/2005	WO	WO 2004/098383	11/2004
GB	2214430 A	6/1989	WO	WO 04/103158	12/2004
JP	501068	9/1984			
JP	502328	3/1992			

WO WO 2004/103158 12/2004

OTHER PUBLICATIONS

- Sigel et al. "The Mechanism of Blood Vessel Closure by High Frequency Electrocoagulation" *Surgery Gynecology & Obstetrics*, Oct. 1965 pp. 823-831.
- Bergdahl et al. "Studies on Coagulation and the Development of an Automatic Computerized Bipolar Coagulator" *J. Neurosurg.* vol. 75, Jul. 1991, pp. 148-151.
- Kennedy et al. "High-burst-strength, feedback-controlled bipolar vessel sealing" *Surgical Endoscopy* (1998) 12: 876-878.
- Peterson et al. "Comparison of Healing Process Following Ligation with Sutures and Bipolar Vessel Sealing" *Surgical Technology International* (2001).
- Linehan et al. "A Phase I Study of the LigaSure Vessel Sealing System in Hepatic Surgery" Section of HPB Surger, Washington University School of Medicine, St. Louis MO, Presented at AHPBA, Feb. 2001.
- Johnson et al. "Evaluation of the LigaSure Vessel Sealing System in Hemorrhoidectomy" American College of Surgeons (ACS) Clinica Congress Poster (2000).
- Sayfan et al. "Sutureless Closed Hemorrhoidectomy: A New Technique" *Annals of Surgery* vol. 234 No. 1 Jul. 2001 pp. 21-24.
- Heniford et al. "Initial Results with an Electrothermal Bipolar Vessel Sealer" *Surgical Endoscopy* (2000) 15:799-801.
- Heniford et al. "Initial Research and Clinical Results with an Electrothermal Bipolar Vessel Sealer" Oct. 1999.
- McLellan et al. "Vessel Sealing for Hemostasis During Pelvic Surgery" Int'l Federation of Gynecology and Obstetrics FIGO World Congress 2000, Washington, D.C.
- Levy et al. "Use of a New Energy-based Vessel Ligation Device During Vaginal Hysterectomy" Int'l Federation of Gynecology and Obstetrics (FIGO) World Congress 1999.
- Crawford et al. "Use of the LigaSure Vessel Sealing System in Urologic Cancer Surger" *Grand Rounds in Urology* 1999 vol. 1 Issue 4 pp. 10-17.
- Rothenberg et al. "Use of the LigaSure Vessel Sealing System in Minimally Invasive Surgery in Children" Int'l Pediatric Endosurgery Group (IPEG) 2000.
- Palazzo et al. "Randomized clinical trial of Ligasure versus open haemorrhoidectomy" *British Journal of Surgery* 2002, 89, 154-157.
- "Innovations in Electrosurgery" Sales/Product Literature; Dec. 31, 2000.
- LigaSure Vessel Sealing System, the Seal of Confidence In General, Gynecologic, Urologic, and Laparoscopic Surgery Sales/Product Literature; Jan. 2004.
- Carbonell et al., "Comparison of theGyrus PlasmaKinetic Sealer and the Valleylab LigaSure Device in the Hemostasis of Small, Medium, and Large-Sized Arteries" Carolinas Laparoscopic and Advanced Surgery Program, Carolinas Medical Center, Charlotte, NC 2003.
- "Reducing Needlestick Injuries in the Operating Room" Sales/Product Literature 2001.
- Chung et al., "Clinical Experience of Sutureless Closed Hemorrhoidectomy with LigaSure" *Diseases of the Colon & Rectum* vol. 46, No. 1 Jan. 2003.
- Strasberg et al., "Use of a Bipolar Vessel-Sealing Device for Parenchymal Transection During Liver Surgery" *Journal of Gastrointestinal Surgery*, vol. 6, No. 4, Jul./Aug. 2002 pp. 569-574.
- Paul G. Horgan, "A Novel Technique for Parenchymal Division During Hepatectomy" *The American Journal of Surgery*, vol. 181, No. 3, Apr. 2001 pp. 236-237.
- W. Scott Helton, "LigaSure Vessel Sealing System: Revolutionary Hemostatis Product for General Surgery" Sales/Product Literature 1999.
- Michael Choti, "Abdominoperineal Resection with the LigaSure Vessel Sealing System and LigaSure Atlas 20 cm Open Instrument" *Innovations That Work*, Jun. 2003.
- Craig Johnson, "Use of the LigaSure Vessel Sealing System in Bloodless Hemorrhoidectomy" *Innovations That Work*, Mar. 2000.
- Muller et al., "Extended Left Hemicolectomy Using the LigaSure Vessel Sealing System" *Innovations That Work*, Sep. 1999.
- Herman et al., "Laparoscopic Intestinal Resection With the LigaSure Vessel Sealing System: A Case Report" *Innovations That Work*, Feb. 2002.
- Carus et al., "Initial Experience With The LigaSure Vessel Sealing System in Abdominal Surgery" *Innovations That Work*, Jun. 2002.
- Levy et al. "Randomized Trial of Suture Versus Electrosurgical Bipolar Vessel Sealing in Vaginal Hysterectomy" *Obstetrics & Gynecology*. vol. 102, No. 1, Jul. 2003.
- Levy et al., "Update on Hysterectomy—New Technologies and Techniques" *OBG Management*, Feb. 2003.
- Barbara Levy, "Use of a New Vessel Ligation Device During Vaginal Hysterectomy" FIGO 2000, Washington, D.C.
- McLellan et al. "Vessel Sealing For Hemostasis During Gynecologic Surgery" Sales/Product Literature 1999.
- Sengupta et al., "Use of a Computer-Controlled Bipolar Diathermy System in Radical Prostatectomies and Other Open Urological Surgery" *ANZ Journal of Surgery* (2001) 71.9 pp. 538-540.
- Olsson et al. "Radical Cystectomy in Females" *Current Surgical Techniques in Urology*, vol. 14, Issue 3, 2001.
- E. David Crawford "Use of a Novel Vessel Sealing Technology in Management of the Dorsal Venous Complex" Sales/Product Literature 2000.
- Jarrett et al., "Use of the LigaSure Vessel Sealing System for Peri-Hitar Vessels in Laparoscopic Nephrectomy" Sales/Product Literature 2000.
- E. David Crawford "Evaluation of a New Vessel Sealing Device in Urologic Cancer Surgery" Sales/Product Literature 2000.
- Joseph Ortenberg "LigaSure System in Laparoscopic 1st and 2nd Stage Orchiopexy" *Innovations That Work*, Nov. 2002.
- Koyle et al., "Laparoscopic Paloma Varicocele Ligation in Children and Adolescents" *Pediatric Endosurgery & Innovative Techniques*, vol. 6, No. 1, 2002.
- Dulemba et al. "Use of a Bipolar Electrothermal Vessel Sealer in Laparoscopically Assisted Vaginal Hysterectomy" Sales/Product Literature; Jan. 2004.
- Johnson et al. "Evaluation of a Bipolar electrothermal Vessel Sealing Device in Hemorrhoidectomy" Sales/Product Literature; Jan. 2004.
- Int'l Search Report PCT/US98/18640.
- Int'l Search Report PCT/US98/23950.
- Int'l Search Report PCT/US99/24869.
- Int'l Search Report PCT/US01/11218.
- Int'l Search Report PCT/US01/11340.
- Int'l Search Report PCT/US01/11420.
- Int'l Search Report PCT/US02/01890.
- Int'l Search Report PCT/US02/11100.
- Int'l Search Report PCT/US04/03436.
- Int'l Search Report PCT/US04/13273.
- Int'l Search Report PCT/US04/15311.
- Int'l Search Report EP 98944778.
- Int'l Search Report EP 98958575.
- Int'l Search Report EP 04027314.
- Int'l Search Report EP 04027479.
- Int'l Search Report EP 04027705.
- Int'l Search Report EP 04013772.
- Int'l Search Report EP 05013463.4 dated Sep. 28, 2005.
- Int'l Search Report EP 05019130.3 dated Oct. 18, 2005.
- Int'l Search Report EP 05020665.5 dated Feb. 16, 2006.
- Int'l Search Report EP 05020666.3 dated Feb. 17, 2006.
- Int'l Search Report EP 05021779.3 dated Jan. 18, 2006.
- Int'l Search Report EP 05021197.8 dated Jan. 31, 2006.
- Int'l Search Report EP 05021937.7 dated Jan. 13, 2006.
- Int'l Search Report—extended—EP 05021937.7 dated Mar. 6, 2006.
- Int'l Search Report EP 05023017.6 dated Feb. 16, 2006.
- Int'l Search Report EP 05021780.1 dated Feb. 9, 2006.
- Int'l Search Report EP 06002279.5 dated Mar. 22, 2006.
- Int'l Search Report PCT/US98/18640 dated Dec. 17, 1998.
- Int'l Search Report PCT/US98/23950 dated Dec. 29, 1998.
- Int'l Search Report PCT/US99/24869 dated Feb. 3, 2000.
- Int'l Search Report PCT/US01/11218 dated Aug. 3, 2001.

International Search Report PCT/US01/11224 dated Nov. 13, 2001.
Int'l Search Report PCT/US01/11340 dated Aug. 7, 2001.
Int'l Search Report PCT/US01/11420 dated Oct. 8, 2001.
Int'l Search Report PCT/US02/01890 dated Jul. 17, 2002.
Int'l Search Report PCT/US02/11100 dated Jul. 9, 2002.
Int'l Search Report PCT/US04/03436 dated Oct. 5, 2004.
Int'l Search Report PCT/US04/13273 dated Nov. 22, 2004.
Int'l Search Report PCT/US04/15311 dated Nov. 18, 2004.
Int'l Search Report EP 98944778 dated Oct. 31, 2000.
Int'l Search Report EP 98958575.7 dated Sep. 20, 2002.
Int'l Search Report EP 04027314 dated Mar. 10, 2005.
Int'l Search Report EP 04027479 dated Mar. 8, 2005.
Int'l Search Report EP 04027705 dated Feb. 3, 2005.
Int'l Search Report EP 04013772 dated Apr. 1, 2005.

Primary Examiner—Lee S. Cohen


(57)


ABSTRACT


A laparoscopic bipolar electrosurgical instrument can apply a large closure force between its jaws without damaging the small yoke assembly. The instrument comprises: a first jaw having a first flange with a first slot, and a second jaw having a second flange with a second slot, wherein the first and

second jaws are located at a distal end of the instrument and comprise an electrically conductive material for conducting bipolar electrosurgical current therebetween; a yoke attached to a pushrod and positioned to electrically insulate the first flange from the second flange, the yoke having a first side facing the first flange and a second side facing the second flange, the yoke further comprising a first shoulder and a second shoulder, a first pin located on the first side and movably engaged with the first slot; a second pin located on the second side and movably engaged with the second slot; the first slot and the second slot shaped such that an angle, subtended by the first and second jaws, decreases with distal motion of the pushrod, and first and second cul-de-sacs positioned respectively in the first and second slots to relieve shear stresses on the first and second pins approximately when the first and second shoulders respectively engage the first and second flanges to provide a closure force between the first and second jaws.

8 Claims, 5 Drawing Sheets











FIG. 6





FIG. 7



LAPAROSCOPIC BIPOLAR ELECTROSURGICAL INSTRUMENT

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 10/243,274 filed on Sep. 13, 2002 now U.S. Pat. No. 6,960,210 which is a continuation of U.S. application Ser. No. 09/591,330 filed on Jun. 9, 2000, now U.S. Pat. No. 6,451,018 which is a continuation of U.S. application Ser. No. 08/970,472 filed on Nov. 14, 1997, now U.S. Pat. No. 6,228,083, the entire contents of all of these applications are herein incorporated by reference in their entirety.

FIELD OF THE INVENTION

This relates to an electrosurgical instrument for performing laparoscopic surgical procedures, and more particularly to a laparoscopic electrosurgical instrument that is capable of grasping vessels and vascular tissue with sufficient force between two bipolar jaws to seal the vessel or vascular tissue.

BACKGROUND OF THE DISCLOSURE

Laparoscopic surgical instruments are used to perform surgical operation without making large incisions in the patient. The laparoscopic instruments are inserted into the patient through a cannula, or port that has been made with a trocar. Typical sizes for cannulas range from three millimeters to twelve millimeters. Smaller cannulas are usually preferred, and this presents a design challenge to instrument manufacturers who must find ways to make surgical instruments that fit through the cannulas.

Certain surgical procedures require cutting blood vessels or vascular tissue. This sometimes presents a problem for surgeons because it is difficult to suture blood vessels using laparoscopic tools. Very small blood vessels, in the range below two millimeters in diameter, can often be closed using standard electrosurgical techniques. If a larger vessel is severed, it may be necessary for the surgeon to convert the laparoscopic procedure into an open-surgical procedure and thereby abandon the benefits of laparoscopy.

Several journal articles have disclosed methods for sealing small blood vessels using electrosurgery. An article entitled *Studies on Coagulation and the Development of an Automatic Computerized Bipolar Coagulator*, J. Neurosurg., Volume 75, July 1991, describes a bipolar coagulator which is used to seal small blood vessels. The article states that it was not possible to safely coagulate arteries with a diameter larger than 2 to 2.5 mm. A second article is entitled *Automatically Controlled Bipolar Electrocoagulation—"COA-COMP"*, Neurosurg. Rev. (1984), pp. 187-190. This article describes a method for terminating electrosurgical power to the vessel so that charring of the vessel walls can be avoided.

It has been recently determined that electrosurgical methods may be able to seal larger vessels using an appropriate electrosurgical power curve, coupled with an instrument capable of applying a large closure force to the vessel walls. It is thought that the process of coagulating small vessels is fundamentally different than electrosurgical vessel sealing. Coagulation is defined as a process of desiccating tissue wherein the tissue cells are ruptured and dried. Vessel sealing is defined as the process of liquefying the collagen in the tissue so that it crosslinks and reforms into a fused

mass. Thus, coagulation of small vessels is sufficient to permanently close them. Larger vessels need to be sealed to assure permanent closure.

It would be desirable to have a surgical tool capable of applying electrosurgical energy, capable of applying a large closure force to the vessel walls, and also capable of fitting through a cannula. A large closure force between the jaws typically requires a large moment about the pivot for each jaw. This presents a challenge because the first and second pins have a small moment arm with respect to the pivot of each jaw. A large force, coupled with a small moment arm, is undesirable because the large forces may shear the first and second pins. It is also undesirable to increase the moment arm of the first and second pins because the physical size of the yoke might not fit through a cannula.

Several bipolar laparoscopic instruments are known. For example, U.S. Pat. No. 3,938,527 discloses a bipolar laparoscopic instrument for tubal cauterization. U.S. Pat. No. 5,250,047 discloses a bipolar laparoscopic instrument with a replaceable electrode tip assembly. U.S. Pat. No. 5,445,638 discloses a bipolar coagulation and cutting forceps with first and second conductors extending from the distal end. U.S. Pat. No. 5,391,166 discloses a bipolar endoscopic instrument having a detachable working end. U.S. Pat. No. 5,342,359 discloses a bipolar coagulation device.

The present invention solves the problem of providing a large closure force between the jaws of a laparoscopic bipolar electrosurgical instrument, using a compact design that fits through a cannula, without risking structural failure of the instrument yoke.

SUMMARY OF THE INVENTION

The present invention is an instrument for applying bipolar electrosurgical current to tissue in a laparoscopic operation with the added benefit of providing a large closure force between the instrument jaws. The large closure force may be particularly useful for vessel sealing operations. An advantage of the present invention is that tissue can be grasped and clamped with a relatively large closure force without damage to the yoke. The yoke is capable of transmitting the large closure force to the instrument jaws while being small enough to fit through a cannula.

The laparoscopic bipolar electrosurgical instrument comprises first and second jaws having, respectively, first and second flanges with first and second slots. The instrument is electrically connected to an electrosurgical generator, and conducts bipolar electrosurgical current to the first and second jaws. A yoke is attached to a pushrod and positioned to electrically insulate the first flange from the second flanges. First and second pins on the yoke are designed to engage the first and second slots, respectively, in a cam-follower arrangement that opens and closes the jaws with linear motion of the yoke. The yoke is preferably a "push yoke" which means that linear motion of the yoke in the direction of the distal end of the instrument will cause the jaws to close together.

The yoke has first and second shoulders that are spaced apart from the first and second flanges until the jaws are in close arcuate proximity to each other. At that point, the first and second shoulders engage the first and second flanges, whereby further distal motion of the yoke applies a force to the first and second flanges that creates a moment about the pivot of each jaw. In general, the cam-follower arrangement of pins and slots may be designed to provide coarse motion of the jaws with relatively small forces. Large closure forces, once the jaws are relatively close together, may be obtained

by pressing the shoulders against the flanges. The first and second pins move into cul-de-sacs in the first and second slots to protect them from large shear stresses when the shoulders are applying relatively large forces to the flanges. Thus, the first and second pins may be made from an electrically insulative material that is not designed to handle large shear stresses, large closure forces may be obtained, and the entire assembly may be compact and fit through a cannula.

A method of making the laparoscopic bipolar electrosurgical instrument is described, comprising the following steps: forming a first jaw having a first flange with a first slot, and a second jaw having a second flange with a second slot; attaching a yoke to a pushrod; electrically insulating the first flange from the second flange with the yoke; engaging first and second pins with the first and second slots; positioning first and second cul-de-sacs respectively in the first and second slots to relieve shear stresses on the first and second pins at a subtended angle approximately wherein first and second shoulders engage the first and second flanges.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a laparoscopic bipolar electrosurgical instrument.

FIG. 2 is a perspective view of the distal end and jaws of the instrument in FIG. 1.

FIG. 3 is an exploded view of the distal end shown in FIG. 2.

FIG. 4 is perspective view of the distal end of the instrument with the jaws removed.

FIG. 5 is another perspective of FIG. 4.

FIG. 6 is a side view of an electrical spring contact.

FIG. 7 is a front view of the spring contact shown in FIG. 6.

DETAILED DESCRIPTION OF THE INVENTION

A laparoscopic bipolar electrosurgical instrument 10 is shown in FIG. 1. The instrument 10 has a proximal end 11 with a handle 14 for holding and manipulating the instrument 10. A distal end 12 on the instrument 10 is used for surgical manipulation of tissue. The instrument 10 comprises an elongate tube 13 that is sized to fit through a cannula for laparoscopic operations, and in different embodiments may be sized to fit through either a five or seven millimeter cannula.

A portion of the distal end 12 of the instrument 10 is shown in FIG. 2. A first jaw 15 and a second jaw 16 are shown in an open position. An angle α is subtended by the jaws 15 and 16. Closing of the jaws 15 and 16 is defined as a reduction of the angle α subtended by the jaws 15 and 16. Similarly, opening of the jaws 15 and 16 is defined as an enlargement of the angle α . The angle α is zero when the jaws 15 and 16 are closed together. The center of rotation for the first jaws 15 is at the first pivot 41, and the center of rotation for the second jaw 16 is at the second pivot 42. The first pivot 41 is located on an outer nose piece 32, and fits in a first pivot hole 43 located on the first flange 18. The second pivot 42 is located on an inner nose piece 31, and fits in a second pivot hole 44 located on the second flange 20.

Pieces that comprise the distal end 12 of the instrument 10 are shown in an exploded view in FIG. 3. The first jaw 15 and the second jaw 16 are shown separated from a yoke 17. The first jaw 15 has a first flange 18 and a first slot 19 therewithin. The second jaw 16 has a second flange 20 and

a second slot 21 therewithin. Each jaw 15 and 16 is preferably formed from a single piece of stainless steel or other electrically conductive material.

Referring again to FIG. 3, the yoke 17 is attached to a pushrod 22. The yoke 17 is preferably formed from an electrically insulative material such as plastic. A first side 23 of the yoke 17 faces the first flange 18. A second side 24 of the yoke 17 faces the second flange 20. When the yoke 17 is positioned between the flanges 18 and 20, the yoke 17 also acts to electrically insulate the first jaw 15 from the second jaw 16. In this manner, bipolar electrosurgical current can be conducted through tissue grasped by the jaws 15 and 16 without short circuiting between the flanges 18 and 20.

A first pin 25 is located on the first side 23 to movably engage with the first slot 19. Similarly, a second pin 26 is located on the second side 24 to movably engage with the second slot 21. Each pin and slot combination works as a cam-follower mechanical linkage. Motion of the pushrod 22 moves the yoke 17 causing pins 25 and 26 to slide within their respective slots 19 and 21. The slots 19 and 21 are angled with respect to the distal ends of the jaws 15 and 16 such that the jaws 15 and 16 move in an arcuate fashion toward and away from each other. The pins 25 and 26 are different from the pivots 41 and 42. The pins 25 and 26 provide a force against the walls of the slots 19 and 21, creating a moment about the pivots 41 and 42.

The slots 19 and 21 are arranged such that distal motion of the pushrod 22 causes the jaws 15 and 16 to move together. Distal motion of the pushrod 22 is defined as motion in the direction of the distal end 12 of the instrument 10. Once the jaws 15 and 16 are closed together, the present invention holds the jaws 15 and 16 together with a compressive force on the pushrod 22.

One of the advantages of this invention is that shear forces on the pins 25 and 26 can be offloaded to prevent mechanical failure when large forces are being transmitted to the jaws 15 and 16. Each slot 19 and 20 has a cul-de-sac 27 and 28, respectively, as shown in FIG. 3. The first cul-de-sac 27 is an enlargement of the first slot 19 near its distal end. The second cul-de-sac 28 is an enlargement of the second slot 21 near its distal end. The cam-follower motion of the pins 25 and 26 in the slots 19 and 21 will bring the pins 25 and 26 into their respective cul-de-sac 27 and 28. This position of the pins 25 and 26 leaves a very small moment arm between the pins 25 and 26 and the pivots 41 and 42. The yoke 17 has shoulders 29 and 30 that can provide a relatively large moment about the pivots 41 and 42 to effect a high closure force between the jaws 15 and 16 without a high shear forces on the pins 25 and 26, as described below.

Once the pins 25 and 26 are in the cul-de-sacs 27 and 28, the force from the yoke is transmitted to the flanges 18 and 20 by a first shoulder 29 and a second shoulder 30. The shoulders 29 and 30 abut the proximal end of the flanges 18 and 20 to cause the jaws 15 and 16 to close together. The pivots 41 and 42 are preferably made of metal and can withstand relatively high shear forces. In contrast, pins 25 and 26 are preferably made of plastic and will break under relatively high shear forces. Thus, the shoulders 29 and 30 provide a moment about the pivots 41 and 42, thereby avoiding the necessity of applying high shear forces to the pins 25 and 26 when the moment arm from the pins 25 and 26 would be small. There is an angle α at which the pins 25 and 26 enter their respective cul-de-sacs 27 and 28 and the shoulders 29 and 30 abut the flanges 18 and 20. The angle α at which the forgoing occurs is preferably around three degrees.

5

The bipolar electrosurgical instrument 10 has first and second poles of alternating potential that are conducted along the instrument 10 and through tissue that is grasped between the jaws 15 and 16. The first pole is conducted from the proximal end 11 toward the distal end 12 along the pushrod 22. The second pole is conducted from the proximal end 11 toward the distal end 12 along the tube 13. The outer surface of the tube 13 is preferably coated with an electrically insulative material. There is also preferably an electrically insulative barrier between the pushrod 22 and the tube 13 to prevent short circuits in the instrument 10.

In the preferred embodiment, the distal end of the instrument 10 comprises an inner nose piece 31 and an outer nose piece 32, as shown in FIG. 2. The inner nose piece 31 is electrically connected with the pushrod 22, while the outer nose piece 32 is electrically connected with the tube 13. The inner nose piece 31 and the outer nose piece 32 capture the yoke 17, along with the first and second flanges 18 and 20, as shown in FIG. 2. The yoke 17 moves axially, along an axis defined by the tube, in a space between the inner and outer nose pieces 31 and 32. A spacer stake 33 maintains the separation of the nose pieces 31 and 32 at their distal ends. The nose pieces 31 and 32 provide lateral support for the flanges 18 and 20 to help ensure that the pins 25 and 26 remain within the slots 19 and 21.

The preferred embodiment also comprises an inner insulator 34 and an outer insulator 35 for maintaining electrical insulation between the poles. The outer insulator 35 is seated between the tube 13 and the inner nose 31, as shown in FIGS. 2 and 4. The inner insulator 34 is seated between the tube 13 and the pushrod 22. In this manner, the outer nose piece 32 can provide electrical continuity between the tube 13 and the second jaw 16, while the inner nose piece 34 can provide electrical continuity between the pushrod 22 and the first jaw 15. Since the pushrod 22 is slidably mounted within the tube 13, the preferred embodiment has a spring contact 36, as shown in FIGS. 6 and 7, mounted on the pushrod 22 to maintain an electrical connection with the inner nose piece 34 during axial motion.

The first and second jaws 15 and 16 each have ridges 37 and 38 at their distal ends that preferably nest together. The jaws 15 and 16 also have seal surfaces 39 and 40, as shown in FIG. 2. The width of the seal surfaces 39 and 40 is a parameter that affects the quality of the surgical outcome. The closure force between the jaws 15 and 16 varies along the length of the seal surfaces 39 and 40, with the largest force at the distal tip and the smallest force at the proximal end of the seal surfaces 39 and 40. It has been found through experimentation that good vessel sealing results are obtained when the closure force in grams divided by the width in millimeters is in the range of 400 to 650. Since the closure force varies with the length of the seal surfaces 39 and 40, it has been found to be advantageous to taper the width of the seal surfaces 39 and 40 along their length, with the widest width at the proximal end and the narrowest width at the distal end. This design allows the jaws 15 and 16 to apply a relatively constant closure force per unit width, preferably 525 grams per millimeter width.

A method of making a laparoscopic bipolar electrosurgical instrument 10 is also herein described. The method comprises the step of forming a first jaw 15 having a first flange 18 with a first slot 19, and a second jaw 16 having a second flange 20 with a second slot 21. The jaws 15 and 16 are preferably formed in a casting process, although it is also possible to machine the jaws 15 and 16 from stock. The casting process may include injecting powdered metal under pressure into a mold, and then applying heat.

6

Other steps in the method include attaching a yoke 17 to a pushrod 22, and electrically insulating the first flange 18 from the second flange 20 with the yoke 17. The yoke 17 is preferably an injection molded plastic part with features including a first shoulder 29 and a second shoulder 30.

During assembly of the distal portion 6 the instrument 10, steps in the method include engaging a first pin 25 with the first slot 19, and engaging a second pin 26 with the second slot 21. The slots 19 and 21 are shaped such that a subtended angle α between the first and second jaws 15 and 16 decreases with distal motion of the pushrod 17, and the slots 19 and 20 are formed with cul-de-sacs 27 and 28 positioned to relieve shear stresses on the first and second pins 25 and 26 at the subtended angle α approximately wherein the first and second shoulders 29 and 30 engage the first and second flanges 18 and 20.

Further steps in the method comprise: surrounding at least a portion of the pushrod 22 with an electrically conductive tube 13; electrically insulating the tube 13 from the pushrod 22; electrically connecting an inner nose piece 31 to the pushrod 22, and electrically connecting an outer nose piece 32 to the tube 13, wherein the inner nose piece 31 and the outer nose piece 32 capture the yoke 17 along with the first and second flanges 18 and 20 to conduct bipolar electrosurgical current to the first and second jaws 15 and 16. In the preferred embodiment, there is a step of electrically connecting the pushrod 22 and the inner nose piece 31 with a spring contact 36.

The method of making the instrument 10, in some embodiments, includes the steps of tapering the width of the seal surfaces 39 and 40 along the length of each of the first and second jaws 15 and 16.

While a particular preferred embodiment has been illustrated and described, the scope of protection sought is in the claims that follow.

What is claimed is:

1. A first and second jaw member assembly for use with a bipolar endoscopic instrument, comprising:
 - a first jaw member and a second jaw member;
 - a yoke which electrically insulates the a first jaw member and the a second jaw member during activation, the yoke including:
 - first and second pins which cooperate with an actuator to rotate a respective jaw member from a first position to a second position upon linear reciprocation of the yoke; and
 - first and second shoulder portions which are conformed to correspondingly abut a respective jaw member in the second position to offload forces on the first and second pins when said yoke is linearly reciprocated.
2. The first and second jaw member assembly according to claim 1 wherein the first jaw member is adapted to be connected to a first electrical potential and the second jaw member is adapted to be connected to a second electrical potential.
3. The first and second jaw member assembly according to claim 2 wherein the first and second jaw members are movable from a first position in spaced relation relative to one another to a second position wherein the first and second jaw members cooperate to conduct bipolar energy through tissue held therebetween.

4. The first and second jaw member assembly according to claim 1 wherein the first and second shoulder portions offload pressure on the first and second pins during clamping and sealing of tissue.

7

5. The first and second jaw member assembly according to claim 1 further comprising: inner and outer nose pieces which are configured to capture the yoke and conduct bipolar electrosurgical energy to the first and second jaw members.

6. The first and second jaw member assembly according to claim 1 wherein the first and second jaw members each include ridges which correspondingly nest when the jaw members are disposed in the second position.

8

7. The first and second jaw member assembly according to claim 1 wherein each of the first and second jaw members includes a seal surface which is tapered along its respective length.

5 8. The first and second jaw member assembly according to claim 7 wherein the closure force is approximately constant between the jaw members along the length thereof.

* * * * *

专利名称(译)	腹腔镜双极电外科仪器		
公开(公告)号	US7207990	公开(公告)日	2007-04-24
申请号	US11/169927	申请日	2005-06-29
[标]申请(专利权)人(译)	地政MICHAEL J LUKIANOW STEPHEN W LOEFFLER DONALD - [R CUNNIGHAM JAMES 小号 劳斯凯特 - [R TRIMBERGER DANIEL 大号 II 米切尔 MATHEW KENNEDY 珍妮弗 小号		
申请(专利权)人(译)	地政MICHAEL J LUKIANOW STEPHEN W LOEFFLER DONALD - [R CUNNIGHAM JAMES 小号 劳斯凯特 - [R TRIMBERGER DANIEL 大号 II 米切尔 MATHEW KENNEDY 珍妮弗 小号		
当前申请(专利权)人(译)	SHERWOOD SERVICES AG		
[标]发明人	LANDS MICHAEL JOHN LUKIANOW STEPHEN WADE LOEFFLER DONALD ROBERT CUNNIGHAM JAMES STEVEN LAWES KATE RYLAND TRIMBERGER II DANIEL LEE MITCHELL MATHEW ERLE KENNEDY JENIFER SERAFIN		
发明人	LANDS, MICHAEL JOHN LUKIANOW, STEPHEN WADE LOEFFLER, DONALD ROBERT CUNNIGHAM, JAMES STEVEN LAWES, KATE RYLAND TRIMBERGER, II, DANIEL LEE MITCHELL, MATHEW ERLE KENNEDY, JENIFER SERAFIN		
IPC分类号	A61B18/14 A61B18/12		
CPC分类号	A61B18/1445		
审查员(译)	COHEN , LEE S.		
其他公开文献	US20060009764A1		
外部链接	Espacenet USPTO		
摘要(译)			

腹腔镜双极电外科器械可在其钳口之间施加大的闭合力而不损坏小轭组件。该器械包括：第一钳口，具有带有第一槽的第一凸缘；以及第二钳口，具有带有第二槽的第二凸缘，其中第一和第二钳口位于器械的远端并包括导电材料用于在其间传导双极电外科电流；轭连接到推杆并且定位成使第一凸缘与第二凸缘电绝缘，轭具有面向第一凸缘的第一侧和面向第二凸缘的第二侧，轭还包括第一肩部和第二肩部，第一销位于第一侧并可移动地与第一槽接合；第二销位于第二侧并可移动地与第二槽接合；第一狭槽和第二狭槽成形为使得第一和第二钳口对向的角度随着推杆的远侧运动而减小，并且第一和第二穹顶分别定位在第一和第二狭槽中以减轻剪切应力大致当第一和第二肩部分别接合第一和第二凸缘时，在第一和第二销上，以在第一和第二夹爪之间提供闭合力。

