



US009155558B2

(12) **United States Patent**
Albrecht et al.

(10) **Patent No.:** **US 9,155,558 B2**
(45) **Date of Patent:** ***Oct. 13, 2015**

(54) **INSUFFLATING OPTICAL SURGICAL INSTRUMENT**

(75) Inventors: **Jeremy J. Albrecht**, Rancho Santa Margarita, CA (US); **John R. Brustad**, Rancho Santa Margarita, CA (US); **Scott V. Taylor**, Rancho Santa Margarita, CA (US); **Gary M. Johnson**, Rancho Santa Margarita, CA (US); **Nabil Hilal**, Rancho Santa Margarita, CA (US)

(73) Assignee: **Applied Medical Resources Corporation**, Rancho Santa Margarita, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/356,260**

(22) Filed: **Jan. 23, 2012**

(65) **Prior Publication Data**

US 2012/0123202 A1 May 17, 2012

Related U.S. Application Data

(63) Continuation of application No. 12/766,118, filed on Apr. 23, 2010, now Pat. No. 8,128,590, which is a continuation of application No. 11/170,567, filed on Jun. 29, 2005, now Pat. No. 7,708,713, which is a

(Continued)

(51) **Int. Cl.**

A61B 17/34 (2006.01)

A61M 13/00 (2006.01)

A61B 19/00 (2006.01)

(52) **U.S. Cl.**

CPC **A61B 17/3417** (2013.01); **A61B 17/3474** (2013.01); **A61M 13/003** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC A61M 13/00; A61M 13/003; A61B 17/3417; A61B 2017/3454; A61B 17/3474

USPC 604/23, 26
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

RE682 E 4/1859 Peale
184,573 A 11/1876 Becker

(Continued)

FOREIGN PATENT DOCUMENTS

BE 1 006 811 12/1994
CA 2 170 841 9/1997

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 10/745,262, filed Dec. 23, 2003; Title: "Catheter With Conduit Traversing Tip" (abandoned).

(Continued)

Primary Examiner — Theodore Stigell

Assistant Examiner — Benjamin Koo


(74) *Attorney, Agent, or Firm* — Rimas Lukas

(57)

ABSTRACT

An insufflating surgical instrument adapted for movement across an abdominal wall to insufflate an abdominal region of a patient is disclosed. The instrument comprises a shaft having an insufflation channel extending between a proximal end and a distal end, the insufflation channel being adapted for connection to a source of fluid under pressure at the proximal end. A tip is at the distal end and a vent hole is formed in the tip being in connection with the insufflation channel and adapted to expel fluid under pressure to insufflate the abdominal region. The tip is formed of a transparent material to facilitate visualization of the abdominal wall and region. The shaft includes a lumen extending along the axis between the proximal end and the distal end to enable insertion of a laparoscope. The lumen and insufflation channel may be formed as separate channels or as one shared channel.

13 Claims, 13 Drawing Sheets



Related U.S. Application Data

continuation-in-part of application No. 10/956,167,
filed on Oct. 1, 2004, now Pat. No. 7,947,058.

- (60) Provisional application No. 60/584,302, filed on Jun. 29, 2004.

(52) **U.S. Cl.**

CPC *A61B17/3462* (2013.01); *A61B 17/3494*
(2013.01); *A61B 19/5212* (2013.01); *A61B*
2017/346 (2013.01); *A61B 2017/349* (2013.01);
A61B 2017/3454 (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

207,932 A	9/1878	Alvord	4,386,179 A	5/1983	Sterling
224,513 A	2/1880	Burdon	4,414,966 A	11/1983	Stednitz
396,754 A	1/1889	Mayfield	4,429,856 A	2/1984	Jackson
764,322 A	7/1904	Wiegand	4,436,519 A	3/1984	O'Neill
1,147,408 A	7/1915	Kelis	4,493,444 A	1/1985	Deli Bon et al.
1,672,258 A	6/1928	Hippenmeyer	4,498,902 A	2/1985	Ash et al.
1,727,495 A	9/1929	Wappler	4,524,805 A	6/1985	Hoffman
1,845,727 A	2/1932	Slaughter	4,535,773 A	8/1985	Yoon
2,102,274 A	12/1937	Larimore	4,535,808 A	8/1985	Johanson
2,189,343 A	2/1940	Fritz	4,537,593 A	8/1985	Alchas
2,301,338 A	11/1942	Smith	4,567,882 A	2/1986	Heller
2,434,594 A	1/1948	Schultz	4,601,710 A	7/1986	Moll
2,441,143 A	5/1948	Gracey	4,750,877 A	6/1988	McFarlane
2,646,701 A	7/1953	Lietin	4,762,130 A	8/1988	Fogarty et al.
2,699,770 A	1/1955	Fourestier et al.	4,779,613 A	10/1988	Hashiguchi et al.
2,764,148 A	9/1956	Sheldon	4,803,999 A	2/1989	Liegner
2,764,149 A	9/1956	Sheldon	4,813,400 A	3/1989	Washizuka et al.
2,769,355 A	11/1956	Henry	4,850,393 A	7/1989	Lashomb
2,877,368 A	3/1959	Sheldon	4,869,717 A *	9/1989	Adair 604/506
2,932,294 A	4/1960	Fourestier et al.	4,895,431 A	1/1990	Tsujluchi et al.
3,005,468 A	10/1961	Erwin et al.	4,901,142 A	2/1990	Ikuno et al.
3,021,834 A	2/1962	Sheldon	4,956,143 A	9/1990	McFarlane
3,033,226 A	5/1962	Allen	4,959,067 A	9/1990	Muller
3,042,022 A	7/1962	Sheldon	4,972,827 A	11/1990	Kishi et al.
3,224,320 A	12/1965	Knudsen	4,978,350 A	12/1990	Wagenknecht
3,277,922 A	10/1966	Eisel	5,017,057 A	5/1991	Krutygor
3,279,460 A	10/1966	Sheldon	5,030,210 A	7/1991	Alchas
3,357,433 A	12/1967	Fourestier et al.	5,041,100 A	8/1991	Rowland et al.
3,385,553 A	5/1968	Braun	5,057,082 A	10/1991	Burchette, Jr.
3,417,745 A	12/1968	Sheldon	5,066,288 A	11/1991	Deniego et al.
3,437,747 A	4/1969	Sheldon	5,098,379 A	3/1992	Conway
3,459,189 A	8/1969	Alley et al.	5,098,388 A	3/1992	Kulkashi et al.
3,556,085 A	1/1971	Takahashi	5,104,316 A	4/1992	McSpadden
3,613,684 A	10/1971	Sheridan	5,104,388 A	4/1992	Quackenbush
3,653,338 A	4/1972	Sauey	5,104,389 A	4/1992	Deem et al.
3,791,379 A	2/1974	Storz	5,114,407 A	5/1992	Burbank
3,817,251 A	6/1974	Hasson	5,116,547 A	5/1992	Tsukahara et al.
3,821,956 A	7/1974	Gordhamer	5,147,376 A	9/1992	Pianetti
3,870,036 A	3/1975	Fiore	5,159,920 A	11/1992	Condon et al.
3,961,621 A	6/1976	Northaved	5,163,941 A	11/1992	Garth et al.
3,971,385 A	7/1976	Corbett	5,178,186 A	1/1993	Levasseur
3,994,287 A	11/1976	Turp	5,186,972 A	2/1993	Williams et al.
3,994,301 A	11/1976	Agris	5,197,955 A	3/1993	Stephens et al.
4,028,987 A	6/1977	Wilson	5,207,656 A	5/1993	Kranys
4,112,932 A	9/1978	Chiulli	5,217,441 A	6/1993	Shichman
4,126,291 A	11/1978	Gilbert et al.	5,221,163 A	6/1993	Nishimura
4,150,929 A	4/1979	Brandt	5,240,397 A	8/1993	Fay et al.
4,168,882 A	9/1979	Hopkins	5,246,425 A	9/1993	Hunsberger et al.
4,180,068 A	12/1979	Jacobsen et al.	5,250,068 A	10/1993	Ideguchi et al.
4,191,191 A	3/1980	QAubum	5,256,149 A	10/1993	Banik et al.
4,222,375 A	9/1980	Martinez	5,258,003 A	11/1993	Ciaglia
4,248,214 A	2/1981	Hannah et al.	5,269,316 A	12/1993	Spitainy
4,254,762 A	3/1981	Yoon	5,271,380 A	12/1993	Riek et al.
4,269,192 A	5/1981	Matsuo	5,279,567 A	1/1994	Ciaglia et al.
4,274,771 A	6/1981	Nishimura	5,288,290 A	2/1994	Brody
4,285,618 A	8/1981	Shanley	5,290,276 A	3/1994	Sewell
4,299,230 A	11/1981	Kubota	5,290,585 A	3/1994	Elton
4,311,138 A	1/1982	Sugarman	5,292,310 A *	3/1994	Yoon 604/158
4,319,563 A	3/1982	Kubota	5,300,033 A	4/1994	Miller
4,356,826 A	11/1982	Kubota	5,330,432 A *	7/1994	Yoon 604/164.12
			5,334,150 A	8/1994	Kaali
			5,342,382 A	8/1994	Brinkerhoff
			5,350,364 A	9/1994	Stephens et al.
			5,370,624 A	12/1994	Edwards et al.
			5,372,588 A	12/1994	Farley
			5,374,253 A	12/1994	Burns, Sr. et al.
			5,380,291 A	1/1995	Kaali
			5,387,197 A	2/1995	Smith
			5,389,077 A	2/1995	Melinyshyn et al.
			5,391,153 A	2/1995	Haber et al.
			5,391,248 A	2/1995	Brain
			5,392,766 A	2/1995	Masterson et al.
			5,405,328 A	4/1995	Vidal et al.
			5,407,427 A	4/1995	Zhu et al.
			5,431,151 A	7/1995	Riek et al.
			5,441,041 A	8/1995	Sauer et al.
			5,443,484 A	8/1995	Kirsch et al.
			5,445,615 A	8/1995	Yoon et al.
			5,454,791 A	10/1995	Tovey et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

5,480,410 A	1/1996	Cuschieri et al.	6,203,559 B1	3/2001	Davis
5,510,065 A	4/1996	McFarlane	6,203,745 B1	3/2001	Wachsmann et al.
5,540,711 A	7/1996	Kieturakis et al.	6,206,823 B1 *	3/2001	Kolata et al. 600/129
5,542,845 A	8/1996	Jenkins	6,221,061 B1	4/2001	Engelson et al.
5,549,546 A	8/1996	Schneider et al.	6,228,059 B1	5/2001	Astarita
5,551,947 A	9/1996	Kaai	6,228,063 B1	5/2001	Aboul-Hosn
5,562,696 A	10/1996	Nobles et al.	6,270,484 B1	8/2001	Yoon
5,569,291 A	10/1996	Privitera	6,302,873 B1	10/2001	Moenning
5,569,292 A	10/1996	Scwemberger et al.	6,319,266 B1	11/2001	Stellon
5,577,993 A	11/1996	Zhu et al.	6,355,014 B1	3/2002	Zadno-Azizi et al.
5,591,186 A	1/1997	Wurster et al.	6,387,043 B1	5/2002	Yoon
5,591,192 A	1/1997	Privitera et al.	6,462,111 B1	10/2002	Singh et al.
5,593,402 A	1/1997	Patrick	6,468,228 B1	10/2002	Topel et al.
5,603,720 A	2/1997	Kieturakis	6,478,806 B2	11/2002	McFarlane
5,609,562 A	3/1997	Kaali	6,508,759 B1	1/2003	Taylor et al.
5,609,604 A	3/1997	Schwemberger et al.	6,520,939 B2	2/2003	Lafontaine
5,613,954 A	3/1997	Nelson et al.	6,656,160 B1	12/2003	Taylor et al.
5,622,462 A	4/1997	Gakhar et al.	6,656,198 B2	12/2003	Tsonton et al.
5,630,805 A	5/1997	Ternamian	6,685,630 B2	2/2004	Sauer et al.
5,634,908 A	6/1997	Loomas	6,764,107 B1	7/2004	Obahi et al.
5,658,236 A	8/1997	Sauer	6,770,731 B2	8/2004	Mason et al.
5,662,615 A	9/1997	Blake, III	6,835,201 B2	12/2004	O'Heeron
5,662,673 A	9/1997	Kieturakis	6,884,253 B1	4/2005	McFarlane
5,676,611 A	10/1997	Foster	6,887,194 B2	5/2005	Hart et al.
5,685,820 A	11/1997	Riek et al.	6,902,541 B2	6/2005	McNally et al.
5,695,462 A	12/1997	Sutcu et al.	6,939,296 B2	9/2005	Ewers et al.
5,697,947 A	12/1997	Wolf	7,008,979 B2	3/2006	Schottman et al.
5,720,730 A	2/1998	Blake, III	7,037,303 B2	5/2006	Beaufore et al.
5,720,761 A	2/1998	Kaali	7,056,294 B2	6/2006	Khairkhahan et al.
5,735,867 A	4/1998	Golser et al.	7,056,329 B2	6/2006	Kerr
5,738,628 A	4/1998	Sierocuk	7,070,586 B2	7/2006	Hart et al.
5,743,881 A	4/1998	Demco	7,182,752 B2	2/2007	Stubbs
5,746,734 A	5/1998	Domandy, Jr. et al.	7,344,519 B2	3/2008	Wing et al.
5,752,970 A	5/1998	Yoon et al.	7,370,709 B2	5/2008	Williamson, Jr.
5,759,185 A	6/1998	Grinberg	7,470,255 B2	12/2008	Stearns et al.
5,779,697 A	7/1998	Glowa et al.	7,563,250 B2	7/2009	Wenchell
5,779,967 A	7/1998	Hull	7,686,823 B2	3/2010	Pingleton et al.
5,785,693 A	7/1998	Halninig	7,708,713 B2	5/2010	Albrecht et al.
5,792,112 A	8/1998	Hart et al.	7,758,603 B2	7/2010	Taylor et al.
5,797,888 A	8/1998	Yoon et al.	7,794,644 B2	9/2010	Taylor et al.
5,797,944 A	8/1998	Nobles et al.	7,811,253 B2	10/2010	Hart et al.
5,817,061 A	10/1998	Goodwin et al.	7,942,862 B2	5/2011	Hart et al.
5,817,062 A	10/1998	Flom et al.	7,947,058 B2	5/2011	Kahle et al.
5,836,957 A	11/1998	Shulz	8,007,477 B2	8/2011	Johnson et al.
5,842,971 A	12/1998	Yoon	8,028,395 B2	10/2011	Taylor et al.
5,860,996 A	1/1999	Urban et al.	8,105,285 B2	1/2012	Hart et al.
5,871,474 A	2/1999	Hermann et al.	8,152,828 B2	4/2012	Taylor et al.
5,876,202 A	3/1999	Berlin	8,282,663 B2	10/2012	Smith
5,884,639 A	3/1999	Chen	8,317,815 B2	11/2012	Mastri et al.
5,891,013 A	4/1999	Thompson	2002/0013597 A1	1/2002	McFarlane
5,893,865 A	4/1999	Swindle	2002/0026207 A1	2/2002	Stellon et al.
5,904,699 A	5/1999	Schwemberger et al.	2002/0133188 A1	9/2002	O'Heeron et al.
5,913,818 A	6/1999	Co et al.	2002/0183715 A1	12/2002	Mantell et al.
5,922,351 A	7/1999	Daher	2002/0183775 A1	12/2002	Tsonton et al.
5,924,452 A	7/1999	Szpapa et al.	2003/0023201 A1	1/2003	Aboul-Hosn
5,941,852 A	8/1999	Dunlap et al.	2003/0032755 A1	2/2003	Gomey et al.
5,957,884 A	9/1999	Hooven	2003/0059263 A1	3/2003	Chen
5,957,888 A	9/1999	Hinchliffe	2003/0187471 A1	10/2003	Cooper
5,968,060 A	10/1999	Kellogg	2004/0015185 A1	1/2004	Ewers et al.
5,976,079 A	11/1999	Volz et al.	2004/0082969 A1	4/2004	Kerr
5,976,168 A	11/1999	Chin	2004/0093000 A1	5/2004	Kerr
5,980,809 A	11/1999	Crain et al.	2004/0093018 A1	5/2004	Johnson et al.
5,984,941 A	11/1999	Wilson	2004/0106942 A1	6/2004	Taylor et al.
6,001,084 A	12/1999	Riek	2004/0108623 A1	6/2004	Deeter et al.
6,007,481 A	12/1999	Riek et al.	2004/0167559 A1	8/2004	Taylor et al.
6,019,776 A	2/2000	Preissman	2004/0199127 A1	10/2004	Jensen et al.
6,024,551 A	2/2000	Yamaguchi	2004/0204671 A1	10/2004	Stubbs et al.
6,030,406 A	2/2000	Davis	2004/0230155 A1	11/2004	Blanco et al.
6,043,310 A	3/2000	Liu et al.	2004/0230217 A1	11/2004	O'Heeroon
6,053,194 A	4/2000	Nelson et al.	2004/0254517 A1	12/2004	Quiroz-Mercado et al.
6,068,637 A	5/2000	Popov et al.	2005/0033237 A1	2/2005	Fentress et al.
6,077,481 A	6/2000	Ichida et al.	2005/0033246 A1	2/2005	Ahlberg et al.
6,092,551 A	7/2000	Bennett	2005/0038466 A1	2/2005	O'Heeron et al.
6,168,355 B1	1/2001	Wardell	2005/0059865 A1	3/2005	Kahle
6,179,528 B1	1/2001	Wardell	2005/0065543 A1	3/2005	Kahle et al.
			2005/0070850 A1	3/2005	Albrecht
			2005/0107803 A1	5/2005	Guanche
			2005/0107816 A1	5/2005	Pingleton et al.
			2005/0113533 A1	5/2005	Shaikh et al.

(56)

References Cited**U.S. PATENT DOCUMENTS**

2005/0149094	A1	7/2005	Kashara et al.	
2005/0149096	A1	7/2005	Hilal et al.	
2005/0159711	A1	7/2005	Kathrani et al.	
2005/0216028	A1	9/2005	Hart et al.	
2005/0227610	A1	10/2005	Zukor et al.	
2005/0273133	A1	12/2005	Schluzas et al.	
2005/0283122	A1	12/2005	Nordgren	
2005/0288622	A1	12/2005	Albrecht et al.	
2006/0030755	A1	2/2006	Ewers et al.	
2006/0041270	A1	2/2006	Lenker et al.	
2006/0047284	A1	3/2006	Gresham	
2006/0058570	A1	3/2006	Rapach et al.	
2006/0074374	A1	4/2006	Gresham	
2006/0118189	A1	6/2006	Trekulve et al.	
2006/0224174	A1	10/2006	Smith et al.	
2006/0264991	A1	11/2006	Johnson	
2006/0264992	A1 *	11/2006	Franer et al.	606/167
2007/0027453	A1	2/2007	Hart et al.	
2007/0075465	A1	4/2007	Taylor et al.	
2007/0088277	A1	4/2007	McGinley	
2007/0239108	A1	10/2007	Albrecht et al.	
2008/0065021	A1	3/2008	Jenkins et al.	
2008/0086074	A1	4/2008	Taylor et al.	
2008/0086093	A1	4/2008	Steppe et al.	
2009/0137943	A1	5/2009	Steams et al.	
2010/0025045	A1	2/2010	Lake et al.	
2014/0114339	A1 *	4/2014	Pingleton et al.	606/190

FOREIGN PATENT DOCUMENTS

DE	0365049	12/1922
DE	1616107	4/1971
DE	2218901	10/1973
DE	2538758	3/1977
DE	29 29 233	1/1980
DE	2929233	1/1980
DE	2922239	12/1980
DE	4020956	1/1991
DE	4133073	4/1992
DE	4035146	5/1992
DE	4116648	11/1992
DE	29521431	4/1997
DE	19541041	5/1997
DE	19718086	11/1998
DE	19819432	11/1999
EP	0135364	3/1985
EP	0312787	4/1989
EP	0347140	12/1989
EP	0369936	5/1990
EP	0369937	5/1990
EP	0474124	3/1992
EP	0548612	6/1993
EP	0556056	8/1993
EP	0724864	8/1996
EP	1582158	10/2005
EP	2229897	9/2010
EP	2233090	9/2010
FR	1370580	8/1964
GB	2 124 970	2/1984
GB	186 005	9/1992
GB	2 313 316	11/1997
JP	408127661	5/1996
JP	2001-137253	5/2001
SU	0942730	7/1982
SU	0942730	8/1987
SU	1328658	8/1987
SU	1329769	8/1987
WO	WO 93/25148	12/1993
WO	WO 96/01132	1/1996
WO	WO 96/10361	4/1996
WO	WO 97/40758	11/1997
WO	WO 98/33536	8/1998
WO	WO 99/02089	1/1999
WO	WO 99/15084	4/1999

WO	WO 00/18306	4/2000
WO	WO 00/54648	9/2000
WO	WO 01/08563	2/2001
WO	WO 02/01998	1/2002
WO	WO 02/34108	5/2002
WO	WO 03/026512	4/2003
WO	WO 03/032819	4/2003
WO	WO 03/096879	11/2003
WO	WO 2004/037097	5/2004
WO	WO 2004/093699	11/2004
WO	WO 2005/063134	7/2005
WO	WO 2007/093957	8/2007

OTHER PUBLICATIONS

Co-Pending U.S. Appl. No. 12/750,372, filed Mar. 30, 2010, title: "Bladeless Obturator".

Co-Pending U.S. Appl. No. 11/549,872, filed Oct. 16, 2006, title: "Surgical Devices, Systems and Methods Thereof Having Gel Material, Gel Coatings, or Gel Lubricants".

Co-Pending U.S. Appl. No. 13/565,972, filed Aug. 3, 2012, title: "Bladeless Optical Obturator".

Co-Pending U.S. Appl. No. 13/356,260, filed Jan. 23, 2012, title: "Insufflating Optical Surgical Instrument".

Co-Pending U.S. Appl. No. 13/078,750, filed Apr. 1, 2011 title "Surgical Access Apparatus and Method".

Co-Pending U.S. Appl. No. 12/569,652, filed Sep. 29, 2009; title "First-Entry Trocar System".

Co-Pending U.S. Appl. No. 12/359,964, filed Jan. 26, 2009, title: "Insufflating Access System".

Co-Pending U.S. Appl. No. 13/462,330, filed May 2, 2012, title: "Low-Profile Surgical Universal Access Port".

Co-Pending U.S. Appl. No. 13/411,244, filed Mar. 2, 2012, title: "Blunt Tip Obturator".

Co-Pending U.S. Appl. No. 13/586,825, filed Aug. 15, 2012, title: "Blunt Tip Obturator".

Co-Pending U.S. Appl. No. 11/868,883, filed Oct. 8, 2007; Title: "Visual Insufflation Port".

International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US04/032346, dated May 20, 2008.

International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US2005/022716 mailed Nov. 22, 2005.

International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US2006/060013, mailed Apr. 24, 2008.

International Bureau of WIPO, The International Preliminary Report on Patentability for International Application No. PCT/US2009/058792, titled First Entry Trocar System, dated Mar. 29, 2011.

International Bureau of WIPO, The International Preliminary Report on Patentability for International Application No. PCT/US2007/080724, titled "Visual Insufflation Port", dated Apr. 7, 2009.

International Bureau of WIPO, The International Preliminary Report on Patentability for International Application No. PCT/US2009/32026, titled "Insufflating Access System", dated Jul. 27, 2010.

International Bureau of WIPO, The International Preliminary Report on Patentability for International Application No. PCT/US2004/000695, titled "Surgical Access Apparatus and Method", dated Jul. 22, 2005.

International Bureau of WIPO, The International Preliminary Report on Patentability for International Application No. PCT/US2004/04883, titled "Surgical Access Apparatus and Method", dated Sep. 9, 2005.

International Searching Authority, International Search Report and Written Opinion for International Application No. PCT/US2004/000695, titled "Surgical Access Apparatus and Method", mailed Jan. 12, 2005.

International Searching Authority, International Search Report and Written Opinion for International Application No. PCT/US2004/04883, titled "Surgical Access Apparatus and Method", mailed Mar. 31, 2005.

(56)

References Cited

OTHER PUBLICATIONS

International Searching Authority, International Search Report and Written Opinion for International Application No. PCT/US2002/06759, titled "Bladeless Obturator", mailed Jul. 12, 2002.

International Searching Authority, International Search Report and Written Opinion for International Application No. PCT/US2005/022716, titled "Insufflating Optical Surgical Instrument", mailed Nov. 22, 2005.

International Searching Authority, International Search Report and Written Opinion for International Application No. PCT/US04/32346, titled Bladeless Optical Obturator, mailed May 20, 2008.

International Searching Authority, International Search Report and Written Opinion for International Application No. PCT/US2009/32026, titled "Insufflating Access System", mailed Mar. 23, 2009.

International Searching Authority, International Search Report and Written Opinion for International Application No. PCT/US2007/080724, titled "Visual Insufflation Port", mailed Apr. 16, 2008.

International Searching Authority/US, International Search Report and the Written Opinion of the International Searching Authority dated May 27, 2009, for International Application No. PCT/US2009/037863, titled "Instrument Seal with Inverting Shroud", mailed May 27, 2009.

The International Searching Authority, The International Search Report and the Written Opinion for International Application No. PCT/US2009/058792, titled "First Entry Trocar System", mailed Dec. 23, 2009.

International Searching Authority, International Search Report and Written Opinion for International Application No. PCT/US2012/036119, titled "Low-Profile Surgical Universal Access Port", mailed Nov. 7, 2012.

European Patent Office, Supplementary European Search Report for European Patent Application No. EP 02706494.8, titled "Bladeless Obturator", dated Jun. 24, 2008.

European Patent Office, Supplementary European Search Report for European Patent Application No. EP 03753017.7, titled "Blunt Tip Obturator", dated Nov. 21, 2008.

European Patent Office, Supplementary European Search Report for European Patent Application No. EP 047122378, titled "Surgical Access Apparatus and Method", dated May 19, 2008.

European Patent Office, Supplementary European Search Report for European Patent Application No. EP 07843973.4, titled "Visual Insufflation Port" dated Oct. 4, 2008.

European Patent Office, Supplementary European Search Report for European Patent Application No. EP 04793965.7, titled "Bladeless Optical Obturator", dated Apr. 16, 2010.

European Patent Office, Supplementary European Search Report for European Patent Application No. EP 11154547.1, titled "Blunt Tip Obturator", dated Mar. 22, 2011.

European Patent Office, European Search Report for European Application No. 11191191.3, titled "Bladeless Obturator" dated Feb. 29, 2012.

European Patent Office, European Search Report for European Application No. 11191179.8, titled "Bladeless Obturator", dated Feb. 21, 2012.

European Patent Office, European Search Report for European Application No. 11191193.9, titled "Bladeless Obturator", dated Mar. 5, 2012.

European Patent Office, European Search Report for European Application No. 11191187.1, titled Bladeless Obturator, dated Feb. 23, 2012.

European Patent Office, European Search Report for European Application No. 11191184.8, titled "Bladeless Obturator", dated Feb. 23, 2012.

European Patent Office, European Search Report for European Application No. 11191189.7, titled "Bladeless Obturator", dated Feb. 24, 2012.

European Patent Office, European Search Report for European Application No. 11191175.6, titled "Bladeless Obturator", dated Feb. 21, 2012.

European Patent Office, European Search Report for European Application No. 047017314, titled "Surgical Access Apparatus and Method", dated Mar. 30, 2007.

Taut, Inc., ADAPT—Asymmetrical Dilating Access Port, Geneva Illinois.

Karl Storz, The Karl Storz Ternamian EndoTIP (TM) System, date: Aug. 27, 2001.

Karl Storz, ZEROCART Trocar with eccentric tip, Recklinghausen, Germany, date Mar. 7, 2001.

Ethicon Endo-Surgery, Inc., ENDOPATH Minimally Invasive Access, date: 2001.

European Patent Office, Invitation to Pay Additional Fees for International Application No. PCT/US2012/036119, titled "Low-Profile Surgical Universal Access Port", mailed Jul. 13, 2012.

European Patent Office, European Search Report for European Application No. 12187933, titled "Insufflating Optical Surgical Instrument", dated Nov. 20, 2012.

European Patent Office, European Search Report for European Application No. 12187929, titled "Insufflating Optical Surgical Instrument", dated Nov. 20, 2012.

U.S. Appl. No. 10/489,403, filed Mar. 11, 2004; Title: Bladeless Obturator.

U.S. Appl. No. 10/514,313, filed Nov. 12, 2004; Title: Blunt Tip Obturator.

U.S. Appl. No. 10/956,167, filed Oct. 3, 2003; Title: Bladeless Optical Obturator.

U.S. Appl. No. 10/745,262, filed Dec. 23, 2003; Title: Catheter With Conduit Traversing Tip.

U.S. Appl. No. 11/868,883, filed Oct. 8, 2007; Title: Visual Insufflation Port.

U.S. Appl. No. 10/346,846, filed Jan. 17, 2003; Title: Surgical Access Apparatus and Method.

U.S. Appl. No. 10/805,864, filed Mar. 22, 2004; Title: Surgical Access Port and Method.

The International Bureau of WIPO, International Preliminary Report on Patentability for international application No. PCT/US2005/022716, mailed Jan. 18, 2007.

* cited by examiner







FIG. 1
PRIOR ART










FIG. 6A










FIG. 7A





FIG. 7B






FIG. 8E




FIG. 8D




FIG. 8C




FIG. 8B




FIG. 8A




FIG. 14C




FIG. 14B




FIG. 14A




FIG. 8F




FIG. 9




FIG. 10




FIG. 11




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 12D




FIG. 12E







FIG. 12F






FIG. 16







FIG. 17A

FIG. 17B





1

INSUFFLATING OPTICAL SURGICAL INSTRUMENT

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of non-provisional application Ser. No. 12/766,118, filed Apr. 23, 2010, entitled "Insufflating Optical Surgical Instrument" now U.S. Pat. No. 8,128,590, which is a continuation of non-provisional application Ser. No. 11/170,567, filed Jun. 29, 2005, now U.S. Pat. No. 7,708,713, issued May 5, 2010, entitled "Insufflating Optical Surgical Instrument", which is a non-provisional application claiming the priority of provisional application Ser. No. 60/584,302, filed on Jun. 29, 2004, entitled "Insufflating Optical Surgical Instrument," which is fully incorporated herein by reference. This non-provisional application is also filed as a continuation-in-part application claiming the priority of patent application Ser. No. 10/956,167, filed on Oct. 1, 2004, entitled "Bladeless Optical Obturator," which is fully incorporated herein by reference.

FIELD OF THE INVENTION

This invention generally relates to surgical instruments and, in particular, to surgical instruments providing visual entry and visual insufflation.

BACKGROUND OF THE INVENTION

Laparoscopic surgery of the abdominal area typically requires the introduction of an insufflation gas into the peritoneal cavity of the patient. The insufflation gas is usually pressurized to about 10 mm Hg above atmospheric pressure. This in turn lifts the abdominal wall away from the organs underlying it. Cannulas having seals are then placed at various locations through the abdominal wall to allow the use of a laparoscope and operating instruments. It is well known that establishing access to a non-inflated peritoneal cavity can be a very dangerous part of any laparoscopic procedure. The most common method to achieve insufflation is to pass a sharp needle through the abdominal wall and into the abdominal region, and then inject a gas through the needle and into the region thereby creating an enlarged or ballooned cavity to accommodate a laparoscopic procedure. Unfortunately, insertion of the needle has been required without any visual aid to facilitate location of the sharp needlepoint. In order to reduce the probability of inadvertent penetration of delicate internal organs in this "blind" procedure, the sharp insufflation needle has been provided with a spring-loaded and retractable safety mechanism.

The safety mechanisms associated with most insufflation needles consist of a blunt or rounded member disposed within the lumen of the needle, and biased by a spring to an extended position beyond the needle tip. This spring must be responsive to the insertion pressure during placement of the needle but must be capable of immediately moving forward when that pressure is relieved. This is a highly mechanical event at best and offers less than optimal arrangement. As pointed out above, a drawback of this procedure is it is performed blindly. A consequence of this blind insertion is the surgeon may inadvertently damage the organs and tissues underlying the abdominal wall such as major blood vessels and the intestinal tract. Once access is gained, it can take several minutes for the gas to insufflate the abdomen and while this is happening the surgeon may be unaware of any complications caused by the insertion of the needle.

2

Another commonly used method of gaining initial access to the peritoneal cavity is by using a procedure known as the Hasson technique. This method involves making a mini-laparotomy and using the fingers to bluntly dissect the tissues of the abdominal wall and thereby creating an access similar to an open surgical procedure. This method is generally considered to be safer but not without risks, and results in an access site that is not well suited for the subsequent introduction and use of a laparoscopic cannula. The cannula is typically held in place with an additional device that allows the cannula to be tied down with sutures to prevent it from slipping out of the abdominal wall. This also leaves a large defect and is difficult to perform in large abdominal walls.

Some surgeons have used trocars designed for use with laparoscopes for the initial entry into the peritoneal cavity. These devices allow the placement of a laparoscope through the internal diameter of the trocar and have a trocar tip that is made of clear plastic to allow the surgeon to visualize the passage of the tip through the abdominal wall. However, in order to allow the subsequent introduction of insufflation gas through the cannula, the trocar and cannula must be inserted all the way through the wall of the abdomen and this in turn can be potentially dangerous as the tip of the trocar may have to advance as much as one inch beyond the distal surface of the abdominal wall and into the underlying anatomical structures. As such, there remains a need in the art for an improved surgical instrument that provides visual entry and visual insufflation, and that minimizes the risks of damaging organs, tissues and vessels underlying a body wall.

SUMMARY OF THE INVENTION

The invention is directed to surgical instruments providing visual entry and visual insufflation with minimal risks of injury to organs, tissues and vessels underlying a body wall. It is appreciated that the concept of the invention may be applied to any surgical instrument that provides the ability to insufflate under direct vision of the site of insufflation, regardless of the size of the instrument and the type of insufflation fluid. More specifically, the surgical instrument provides the ability to transfer an insufflation fluid such as CO₂ or saline from outside a patient to inside a surgical cavity under vision. The insufflation fluid may be transferred inside a lumen, along a body channel or through a coiled tube of a surgical instrument or scope used for vision.

In a first embodiment of the invention, an insufflating surgical instrument adapted for movement across an abdominal wall to insufflate an abdominal region of a patient is disclosed comprising a shaft having an insufflation channel extending along an axis between a proximal end and a distal end, the insufflation channel being adapted for connection to a source of fluid under pressure at the proximal end. The insufflating surgical instrument further comprises a tip at the distal end of the shaft and at least one vent hole formed at the tip or the shaft being in connection with the insufflation channel and being adapted to expel the fluid under pressure to insufflate the abdominal region. In one aspect, at least one of the tip and the shaft is formed of a transparent material to facilitate visualization of the abdominal wall and the abdominal region. With this aspect, the shaft and the tip are configured to enable insertion of a laparoscope. In particular, the shaft includes a lumen extending along the axis between the proximal end and the distal end to enable insertion of the laparoscope. The lumen and insufflation channel may be formed as separate channels or as one shared channel. The insufflating surgical instrument may further comprise a second vent hole being in connection with the insufflation channel and formed along the

shaft. It is appreciated that the tip may be blunt, the shaft and the tip may be integrally formed, and the vent hole may be of any geometric shape including round, oval, square and rectangular. With this aspect, at least one of the tip and the shaft may be formed of a translucent or a transparent material such as polycarbonate. The blunt tip may further comprise a marker to indicate when the vent hole has been positioned for insufflation. More specifically, the marker indicates the point where the vent hole has penetrated the abdominal wall. The shaft of the invention may further comprise a scope lock to prevent the laparoscope from being inserted too far into the shaft and block at least one of the insufflation channel and the vent hole. In another aspect, the tip may be sharp, pointed or bladed to facilitate penetration of body tissue.

The insufflating surgical instrument may further comprise a seal housing disposed at the proximal end of the shaft. The seal housing comprises a septum seal and a plurality of leaflets forming an instrument seal in the presence of a laparoscope, and providing a zero seal in the absence of an instrument. The thickness of the leaflets may be formed to a desired dimension to create a pressure release mechanism that inverts and releases pressure if the abdominal pressure within the patient undergoes a sudden spike. The septum seal may be formed of an elastomeric material including Kraton, silicone and the like. The seal housing may further comprise a duckbill or a double duckbill valve distal of the leaflets to further limit gas or fluid escape.

In another aspect of the invention, an insufflating surgical instrument adapted for penetrating an abdominal wall to insufflate an abdominal region of a patient is disclosed comprising a shaft having an insufflation channel extending along an axis between a proximal end and a distal end, the insufflation channel being adapted for connection to a source of fluid under pressure at the proximal end. The insufflating surgical instrument further comprises a tip at the distal end of the shaft, the tip having a first, closed position during penetration of the abdominal wall and a second, opened position to expel the fluid under pressure to insufflate the abdominal region after penetration of the abdominal wall. The tip may be a flip-top that automatically opens upon traversing the abdominal wall or a flapper valve that opens to the second position when gas or fluid is introduced at the source and into the insufflation channel. The insufflating surgical instrument may further comprise a retention member for connecting the shaft and the flip-top. The flip-top may be a two-piece flip-top, the flapper valve may be a reverse flapper valve or a spring-based flapper valve, and the retention member may be one of a spring, a spring wire, an offset hinge or a living hinge. In another aspect, the tip may comprise at least two petals that reposition to the side of the shaft in the second insufflation position.

Another aspect of the invention is a laparoscopic insufflating surgical instrument adapted for movement across an abdominal wall to insufflate an abdominal region of a patient comprising an elongate tube having a distal tip, an insufflation channel extending between a proximal end and a distal end, the elongate tube being adapted for connection to a source of fluid under pressure at the proximal end, and being adapted at the distal end to expel the fluid under pressure to insufflate the abdominal region, and an optical element disposed at the distal end of the elongate tube to facilitate visualization of the abdominal wall and the abdominal region. With this aspect, the distal tip is defined by a curved surface, the distal tip being translucent or transparent, and the optical element being a light or an endoscope. It is appreciated that the insufflating surgical instrument may be an insufflating Veress needle.

Another aspect of the invention is directed to a laparoscopic insufflating surgical instrument adapted for movement

across an abdominal wall to insufflate an abdominal region of a patient comprising an elongate tube having a proximal end and a distal end, an optical element disposed at the distal end of the elongate tube to facilitate visualization of the abdominal wall and the abdominal region of the patient, and an insufflation channel having a proximal end and a distal end extending along the proximal end and the distal end of the elongate tube, the insufflation channel being adapted for connection to a source of fluid under pressure at the proximal end, and to expel the fluid under pressure to insufflate the abdominal region at the distal end. With this aspect, the insufflation channel is formed into a coil around the elongate tube. It is further appreciated that the distal end of the elongate tube may be tapered to form a generally cone-tipped end.

In yet another aspect of the invention, there is disclosed an insufflating surgical instrument adapted for movement across an abdominal wall to insufflate an abdominal region of a patient, the surgical instrument comprising an insufflating cannula having a wall forming a first lumen extending along an axis between a proximal end and a distal end, and a first insufflation channel formed in the wall extending along the axis between the proximal end and the distal end and being adapted for connection to a source of fluid under pressure at the proximal end. The insufflating surgical instrument further comprises an insufflating trocar having a shaft with a second lumen extending along the axis between a proximal end and a distal end, a second insufflation channel formed at the distal end and being adapted for alignment with the first insufflation channel of the cannula to expel the fluid under pressure to insufflate the abdominal region, and a tip at the distal end of the shaft, and at least one vent hole formed at the tip of the trocar being in connection with the second insufflation channel of the trocar. The insufflating surgical instrument may further comprise a laparoscope adapted for insertion at the proximal end of the trocar and advanced to the distal end as the trocar is placed through the abdominal wall.

Another aspect of the invention is directed to a method for using an insufflating surgical instrument to create access across an abdominal cavity and to insufflate an abdominal region of a patient, the method comprising providing a transparent shaft having a lumen and an insufflation channel extending along an axis between a proximal end and a distal end, the insufflation channel being adapted for connection to a source of fluid under pressure at the proximal end, a tip at the distal end of the shaft, and at least one vent hole formed at the tip or the shaft being in connection with the insufflation channel and adapted to expel the fluid under pressure to insufflate the abdominal region; moving the shaft across the abdominal wall to place the distal end of the shaft in the abdominal region; and expelling gas or fluid under pressure through the insufflation channel to insufflate the abdominal region of the patient. The method for using the insufflating surgical instrument may further comprise the step of visualizing the abdominal cavity through the lumen of the shaft.

These and other features of the invention will become more apparent with a discussion of the various embodiments in reference to the associated drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included in and constitute a part of this specification, illustrate the embodiments of the invention and, together with the description, explain the features and principles of the invention. In the drawings:

FIG. 1 illustrates a typical laparoscopic abdominal surgery of the prior art.

FIG. 2 illustrates a perspective view of an insufflation needle of the prior art.

FIG. 3 illustrates a perspective view of an insufflating optical trocar in accordance with a first embodiment of the invention.

FIGS. 4(a) and 4(b) illustrate cross-sectional views of an insufflating optical trocar in accordance with another embodiment of the invention.

FIG. 5 illustrates a perspective view of a septum seal for use with the insufflating optical trocar of the invention.

FIG. 6(a)-6(d) illustrate cross-sectional views of the septum seal for use with the insufflating optical trocar of the invention.

FIGS. 7(a) and 7(b) illustrate the insufflating optical trocar and cannula of the invention.

FIGS. 8(a)-8(f) illustrate different geometric shapes and patterns of the vent hole of the invention.

FIG. 9 illustrates an insufflating needle having a transparent distal tip and insufflating vent in accordance with another embodiment of the invention.

FIG. 10 illustrates an insufflating scope having a transparent distal tip and insufflating vent in accordance with another embodiment of the invention.

FIG. 11 illustrates an insufflating scope sleeve having a transparent distal tip and insufflating vent in accordance with another embodiment of the invention.

FIGS. 12(a)-12(f) illustrate additional tip designs of an insufflating optical surgical instrument in accordance with additional aspects of the invention.

FIGS. 13(a) and 13(b) illustrate a coiled insufflating optical trocar and a coiled insufflating optical trocar with a coiled tip, respectively, in accordance with additional embodiments of the invention.

FIGS. 14(a)-14(c) illustrate flip-top or flip-tip designs of insufflating optical surgical instruments in accordance with additional embodiments of the invention.

FIGS. 15(a)-15(c) illustrate cross-sectional views of insufflating valve vents in accordance with additional embodiments of the invention.

FIG. 16 illustrates a blunt tip insufflating optical instrument having an advanceable lumen in accordance with another embodiment of the invention.

FIGS. 17(a) and 17(b) illustrate an insufflating surgical instrument including an insufflating optical trocar and a cannula having a gas channel for transferring insufflation gas to the trocar in accordance with another embodiment of the invention.

FIG. 18 illustrates an insufflating blade actuating optical trocar in accordance with another embodiment of the invention.

FIGS. 19(a)-19(i) illustrate additional tip designs in accordance to other aspects of the invention to facilitate penetration of body tissue.

DETAILED DESCRIPTION OF THE INVENTION

Referring to FIG. 1, there is shown a typical laparoscopic abdominal surgery where an inflation needle 10 is inserted through a body or abdominal wall 15 and into an abdominal cavity 25. A gas is passed through the needle 10 to create a space within the abdominal cavity 25. This procedure is referred to as insufflation. The needle 10 is referred to as an insufflation needle and the gas supply is referred to as an insufflation gas. The insufflation needle 10 is placed through the body wall 15 blindly. In other words, there is no direct visualization of the procedure from the inside of the body wall 15. As explained earlier, the current procedure may inadvertently

damage organs and tissues underlying the body or abdominal wall 15 such as major blood vessels and the intestinal tract. It is not uncommon for there to be internal structures attached to the internal side of the body wall 15. This is especially so in the case of the abdominal cavity 25. Portions of the intestines, colon and bowel may be attached to the abdominal wall 15. These attachments are referred to as adhesions.

Adhesions represent a potential complication in laparoscopic surgery. This is especially the case as the procedure is initiated using a sharp or pointed instrument such as the insufflation needle 10. The delicate internal structures that may be attached by adhesions may inadvertently be pierced by the introduction of the insufflation needle 10. This can be very serious and may go undetected for some time.

Referring to FIG. 2, the typical insufflation needle 10 comprises an elongate tubular body 12, a proximal connecting housing 14, a sharp, pointed distal tip 16 and a spring, biased internal blunt core 18 with a blunt end 24 that extends beyond the sharp distal tip 16 under the influence of an extended compression spring 20. A typical placement of the insufflation needle 10 requires a user to push the sharp distal tip 16 into the abdominal wall 15, which pushes the blunt core 18 proximally, then continues to push until the distal end 22 is through the body wall 15. At that point, the blunt end 24 moves forward and thereby protects delicate structures from being inadvertently punctured by the sharp distal tip 16 of the needle 10. The safety of such a device depends to a large extent on the design and integrity of the spring 20 since the sharp distal tip 16 remains within the established internal region or body cavity 25.

Referring to FIG. 3, there is shown a perspective view of an insufflating optical instrument or trocar 30 in accordance with a first embodiment of the invention. The insufflating optical trocar 30 is designed to separate tissue fibers during insertion through the body wall 15. The insufflating optical trocar 30 includes a shaft 34 having a lumen extending substantially along an axis between a proximal end and a distal end, a handle 35 disposed at the proximal end of the shaft 34, and a blunt tip 32 disposed at the distal end of the shaft 34. The shaft 34 of the insufflating optical trocar 30 is sized and configured for disposition within a working channel of a cannula system as described in co-pending application Bladeless Optical Obturator, which is herein incorporated by reference. With this disposition, the insufflating optical trocar 30 functions to penetrate a body or abdominal wall to provide the cannula with access across the body wall 15 and into the body cavity 25, such as the peritoneal or abdominal cavity.

In one aspect of the invention, the shaft 34 and tip 32 are integrally formed of a transparent material to enable visualization of tissue during the insertion of the insufflating optical trocar 30 through the body wall 15. The insufflating optical trocar 30 is configured to enable the insertion of a conventional laparoscope, which typically includes an imaging element and fiber optic light fibers. The tip 32 further includes at least one vent hole 36, and preferably two or more vent holes one on each side of the tip 32, for the insufflation gas to transfer from the inside of the trocar 30 into the body or abdominal cavity 25. The vent hole 36 may be chamfered on the proximal side such that the vent hole does not core tissue as the insufflating optical trocar 30 enters through the body wall 15.

The shaft 34 includes at least one shaft vent 38 and preferably a plurality of shaft vents 38 along the axis between the proximal end and the distal end. It is appreciated that vent holes 36 and shaft vents 38 may be of any geometric shape including round, oval, square, rectangular, etc., as illustrated

in FIGS. 8(a)-8(c) and may be configured in different patterns such as a waffle pattern as illustrated in FIG. 8(f). Furthermore, the tip 32 may be an open tip 180 or a non-coring tip 182 as illustrated in FIGS. 8(d) and 8(e), respectively, to allow the transfer of insufflation gas into the body cavity 25. Advan- 5 tages of the shaft vents 38 include supporting a plurality of core pins during the injection molding process of the shaft 34 to provide a uniform part thickness, and allowing the insufflation gas to transfer from the inner diameter of the cannula and seal housing into the inner diameter of the insufflating optical trocar 30 and consequently out of the vent holes 36 at tip 32.

Referring to FIGS. 4(a) and 4(b), there are shown side cross-sectional views of an insufflating optical trocar 40 in accordance with another embodiment of the invention. The insufflating optical trocar 40 includes a shaft 34b having a lumen extending substantially along an axis between a proximal end and a distal end, and a blunt tip 32b disposed at the distal end. The insufflating optical trocar 40 further includes at least one gas channel 42 extending along the length of the shaft 34b to provide rapid gas transfer through the insufflating optical trocar 40 when a scope has been placed within the inner diameter. It is appreciated that there may be more than one gas channel 42 extending along the length of the shaft 34b to provide rapid gas transfer through the trocar 40. It is further 25 appreciated that the gas channel 42 may be formed as a separate channel or as the same channel for inserting the scope, that is, by increasing the inner diameter of the shaft 34b to be bigger than the diameter of the scope. More specifically, even if the scope and gas share the same channel, the gas channel 42 assures that there is sufficient cross-sectional area for the gas to travel along the side of the scope and down to the vent hole(s) 36b even when the scope is in place.

The tip 32b may further include a marker 46 to be used as a visible reference point. The marker 46, together with an area indicated by reference number 44 as shown in FIG. 4A, depict the down vent of the insufflating optical trocar 40 that transfers the gas from the gas channel 42 of the trocar 40 to the vent holes 36b at tip 32b. For example, as the trocar 40 is being placed through the abdominal wall 15, at some point the tip 32b of the trocar 40 will penetrate the peritoneum. Once the peritoneum can be seen through the tip 32b and once the peritoneum is above the visible marker 46, the insufflation gas can be turned on and insufflation can begin. As such, this marks the point where the vent hole 36b is within the abdominal cavity. Once the insufflation gas has created sufficient space between the abdominal wall and the organ bed, the remainder of the insufflating optical trocar 40 including the cannula system can then be fully inserted to an operative position.

The insufflating optical trocar 40 may further include a scope stop 48 as illustrated in FIG. 4(b) to keep a scope from being inserted into the taper of the inner diameter of the trocar 40. The scope stop 48 may further include a ledge that further prevent the possibility of the scope from being inserted too far into the trocar and consequently block the distal portion of the gas channel 42.

Referring to FIG. 5, there is shown a perspective view of a septum seal 50 to be used with the insufflating optical trocar of the invention. The septum seal 50 includes a tubular body 52, a septum ring 53 and a plurality of leaflets 54 formed by a slit 56 providing an instrument seal when a scope is inserted into the insufflating optical trocar and a zero seal when the scope is withdrawn from the trocar. In addition, the thickness of the leaflets 54 can be controlled such that a pressure release 65 mechanism can be created and consequently allowing the leaflets 54 to invert and release pressure if the abdominal

pressure within the patient undergoes a sudden spike. Referring to FIGS. 6(a)-6(d), there are shown cross-sectional views of the septum seal 50 of FIG. 5. The septum seal 50 further includes a retaining ledge 58, which allows the septum seal 50 to be attached to the cap or handle 35 of the insufflating optical trocar, and also serves as a sealing surface. Reference number 59 illustrates a sealing surface between the septum seal 50 and the cap or handle of the insufflating optical trocar. The septum seal 50 may further comprise a duckbill or double duckbill valve placed distally of the leaflets 54 to further limit gas or fluid escape.

During use, the insufflating optical trocar 30 is first inserted into a seal housing 84 and cannula 70 as illustrated in FIG. 7(a). A conventional laparoscope 72 is then inserted into the proximal end of the insufflating optical trocar 30 and advanced to the distal end of the trocar 30. An endoscopic video camera is attached to the proximal end of the laparoscope 72. The trocar 30 is then axially advanced by the surgeon through the body wall 15. As the surgeon advances the cannula 70 and trocar 30 through the body wall 15, the surgeon can visually observe tissue of the body wall 15 as it is being separated via a video monitor, which is connected to the endoscopic video camera. The surgeon can also readily determine when the body wall 15 has been completely traversed by the trocar 30. Once the trocar 30 has traversed the body wall 15, the trocar 30 and laparoscope 72 may be removed which leaves the cannula 70 disposed across the body wall 15 to provide an access channel into the body cavity 25 for the insertion of laparoscopic instrumentation.

As illustrated in FIG. 7(a), the insufflating optical trocar 30 is designed for use with the seal housing 84 and cannula 70. The tip 32 may be blunt and does not include any sharp edges, piercing points or blades. With this aspect of the invention, the tip 32 of the bladeless insufflating optical trocar 30 is transparent and generally hollow. This enables a clear view through the distal tip of the insufflating optical trocar 30 and increases the visibility of tissue as it is being traversed. The obturator shaft 34 with the integral tip 32 may be formed of a transparent material such as polycarbonate. The septum seal 50, which may be formed of a material such as Kraton, silicone and the like, may be snap fitted onto the proximal end of the obturator shaft 34. The seal housing 84 may further include a handle attachment 35 including a cannula seal, which may be formed of a plastic material such as polycarbonate, that operates to attach the trocar 30 to the cannula 70 so as to maintain axial position during insertion. The diameter of the shaft 34 can range from about 2 mm to 50 mm and is designed to fit within the seal housing 84 and cannula 70.

Referring to FIG. 7(b), the cannula 70 is designed to releasably attach to the seal housing 84 via cannula seal 80a, 80b. As the shaft 34 is inserted into the seal housing 84 and cannula 70, the cannula seal 80a, 80b passively engages the seal housing 84 and serves to axially lock the shaft 34 to the seal housing 84 and cannula 70. To release the shaft 34 from the seal housing 84 and cannula 70, outboard tabs on shaft 34 are depressed inwardly and the shaft 34 is then free to be slidably removed. The shaft 34 includes axial key members 37 (see FIG. 3) at its proximal end which are designed to mate with axial keyways on the seal housing 84. As the shaft 34 is inserted into the seal housing 84 and cannula 70, the shaft 34 is rotated slightly to align key members 37 with the keyways and then advanced until the cannula seal 80a, 80b engages the seal housing 84. The key members 37 serve to rotationally index the shaft 34 to the seal housing 84. In another aspect, cannula 70 may further include distal cannula seal 82 formed at a distal portion of cannula 70 and shaft 34 so as to further limit gas or fluid escape.

In another aspect of the invention, the insufflating optical trocar **30** may include a laparoscope lock **86** having an elastomeric element. The addition of the elastomeric element would enhance the frictional engagement with the laparoscope **72**. An example of an elastomeric element would be a silicone O-ring sized with an inside diameter smaller than the outside diameter of the laparoscope **72**. The laparoscope lock **86** could either rotate freely to enable the laparoscope **72** to rotate freely relative to the shaft **34** or the laparoscope lock **86** could be rotationally fixed to prevent the laparoscope **72** from rotating relative to the shaft **34**.

In another aspect of the invention, a process of placing and using the insufflating optical trocar of the invention is described. First, the skin around the area to be operated on is incised appropriately for the size of the cannula **70**. An insufflation gas line **90**, which is attached to the seal housing **84**, the insufflating optical trocar **30** and the laparoscope **72** are then inserted into the cannula **70**. At this point the gas supply is still turned off. The assembled device is then advanced through the body or abdominal wall **15** under direct vision until it is observed that just the tip **32** of the device has penetrated the peritoneal cavity. The device is then held in place and the flow of insufflation gas is begun. The gas will flow through the tip **32** and into the peritoneal cavity until the cavity is sufficiently distended by gas pressure. The surgeon then completes the insertion of the insufflating optical trocar **30** until the cannula **70** is in an appropriate or desired position. The insufflating optical trocar **30** and laparoscope **72** may then be removed. At this point, the surgeon may elect to reinsert just the laparoscope **72** through the seal housing **84** and thereby allow observation of the abdominal cavity and subsequent insertions of additional laparoscopic instrumentation.

As explained earlier, an indicator line or marker **46** as shown in FIG. **4(a)** may be located on tip **32** to be viewed by laparoscope **72** to indicate when the device has advanced far enough into the body cavity to begin insufflation. The coincidence of anatomical features with the indicator line or marker **46** may indicate the correct position to begin insufflation. The indicator line or marker **46** could be circumferential in nature and when the peritoneal layer, as it is being penetrated, forms a coincident circle with respect to the indicator line **46**, the surgeon can begin insufflating. Another method is to employ an O-ring seal. Additionally, it is preferred that a zero seal be present on the trocar to prevent escape of the gas when the trocar is used to place cannulas without the laparoscope **72**. A double duckbill valve **88** would work well too for this application as would a single duckbill, a flapper valve or a slit valve.

It is appreciated that the above-described concept may be applied to any surgical instruments providing visual entry and visual insufflation, regardless of size or type of fluid transfer as further described in the following exemplary embodiments of the invention. For example, FIG. **9** illustrates an insufflating needle **190** in accordance with another aspect of the invention comprising an elongate tubular body **192** having an insufflation channel extending along an axis between a proximal end and a distal end, a transparent distal tip **194** operably attached to the distal end of the tubular body **192**, and at least one insufflating vent hole **196** formed at the distal tip **194** or tubular body **192** and being in connection with the insufflation channel. The insufflating needle **190** may further include an insufflation-controlling device **198** such as a stopcock and a sealing mechanism **200** at the proximal end of the tubular body **192**. A small diameter scope **202** may be inserted at the proximal end of the tubular body **192** and then advanced to the distal end of the tubular body **192** as the insufflating needle

190 such as an insufflating Veress needle is placed through an abdominal wall. In yet another aspect of the invention as illustrated in FIG. **10**, an insufflating scope **210** comprises an elongate body **212** having an insufflation channel **224** extending along an axis between a proximal end and a distal end, a transparent tip **214** operably attached to the distal end of the elongate body **212** and having at least one insufflating vent hole **216** being in connection with the insufflation channel **224**, and a handle **218** formed at the proximal end of the elongate body **212**. The insufflating scope **210** may further include an insufflation-controlling device **220** such as a stopcock at the proximal end of the elongate body **212** or on the handle **218**. The elongate body **212** includes an optical element **222** that directs light to the tip **214** and at least one insufflation channel **224** to transfer the insufflation gas into the surgical cavity.

Referring to FIG. **11**, there is shown an insufflating scope sleeve **230** in accordance with another embodiment of the invention. The insufflating scope sleeve **230** comprises a flexible sleeve **232** having a proximal end and a distal end, a transparent tip **234** operably attached to the distal end of the flexible sleeve **232** and having at least one insufflating vent hole **236**, and a handle **238** attached to the proximal end of the flexible sleeve **232**. The insufflating sleeve **230** may further include an insufflation-controlling device **240** such as a stopcock and a sealing mechanism **242** at the proximal end of the insufflating sleeve **230**. A scope **244** may be inserted at the proximal end of the insufflating scope sleeve **230** and then advanced to the distal end of the insufflating scope sleeve **230** as the insufflating scope sleeve **230** is placed through an abdominal wall.

Referring to FIGS. **12(a)**-**12(f)**, there are shown additional tip designs **32o**-**32s** in accordance with other aspects of the invention to facilitate penetration of a body tissue. FIG. **12(a)** illustrates a spoon-shaped or asymmetric tip **32o** having at least one vent hole **36o**; FIGS. **12(b)** and **12(c)** illustrate a generally domed or conical shaped tip **32p** having plastic or metal blades **33p** along an axis of the shaft and at least one vent hole **36p**; FIG. **12(d)** illustrates a blunt tip **32q** having at least one vent hole **36q**; FIG. **12(e)** illustrates a generally domed or conical shaped tip **32r** having at least one bladed fin **33r** and at least one vent hole **36r**; and FIG. **12(f)** illustrates a generally conical shaped tip **32s** having at least one vent hole **36s** at the distal tip. It is appreciated that tips **32o**, **32p**, **32r** and **32s** have a sharp, pointed or bladed tip and/or edge to facilitate penetration of body tissue. In yet other aspects of the invention, the surface of the tip may have at least one tissue engaging raised pattern on the surface. The surface operates to facilitate insertion of the insufflating surgical instrument or optical trocar with a reduced penetration force and minimize tenting of the body wall. The surface may further facilitate separation of different layers of the body wall and provides proper alignment of the tip between the layers. In another aspect of the invention, the tip may have an outer surface extending distally to a blunt point and includes a pair of side sections separated by an intermediate section, and wherein the side sections extend from the blunt point radially outwardly with progressive positions proximally along the axis. The side sections may include a distal portion in proximity to the blunt point and a proximal portion in proximity to the tubular body, and the distal portion of the side sections being twisted radially with respect to the proximal portion of the side sections.

FIGS. **13(a)** and **13(b)** illustrate a coiled insufflating optical trocar **250** and a coiled insufflating optical trocar with a coiled tip **260**, respectively, in accordance with additional embodiments of the invention. The coiled insufflating optical

trocar **250** comprises a shaft **34t** having a lumen and a hollow coiled tube or gas channel **42t** wrapped substantially along the length of the shaft **34t** to provide gas transfer into the body cavity. An advantage of this aspect of the invention is coiling also helps to keep the trocar from moving about inside a body cavity. The coiled insufflating optical trocar **250** may further include an insufflation-controlling device **240** such as a stop-cock at the proximal end of the coiled insufflating optical trocar **250**. A scope may be inserted at the proximal end of the coiled insufflating optical trocar **250** and then advanced to the distal end of the trocar **250** as the trocar **250** is placed through an abdominal wall. The coiled insufflating optical trocar with coiled tip **260** as shown in FIG. **13(b)** is similar to the coiled insufflating optical trocar **250** but further includes a tip **32u** and a hollow coiled tube or gas channel **42u** that wraps around the tip **32u** and substantially along the length of the shaft **34u**.

Referring to FIGS. **14(a)**-**14(c)**, there are shown additional tip designs **32v**-**32x** in accordance to other aspects of the invention. For example, the tip **32v** as illustrated in FIG. **14(a)** comprises a flip-top **272** and a conical body **270** that operates to move from a first, penetrating position to a second, insufflating position when the body wall has been traversed. The tip **32v** may further comprise a retention member for connecting the flip-top **272** and the conical body **270**. The retention member may be one of a spring, a spring wire, an offset hinge or a "living" hinge. Other flip-top or flip-tip designs as described in co-pending U.S. patent application Ser. No. 10/805,864, entitled "Surgical Access Port and Method of Using Same," filed Mar. 22, 2004, which is herein incorporated by reference, may also be used with the insufflating concept of the invention. In yet another aspect of the invention, the tip **32w** as illustrated in FIG. **14(b)** comprises a two-piece flip-top **282a**, **282b** that operates to move from a first, penetrating position to a second, insufflating position when the body wall has been traversed. In particular, the tip **32w** may comprise at least two or more parts or petals that reposition to the side of the shaft **34w** in the second, insufflating position. FIG. **14(c)** illustrates the tip **32x** in accordance with another aspect of the invention comprising a two-stage flip-top **290** that operates to move from a penetrating position to an insufflating position and then to an instrument access position. In particular, the two-stage flip-top **290** comprises a distal flip portion **292** and a proximal flip portion **294**. In the first stage, the distal flip portion **292** moves from a penetrating position to an open or insufflating position once the body wall has been traversed. Once insufflation has been achieved, the proximal flip portion **294** moves to an open or instrument access position in the second stage. The tip **32x** may further comprise retention members for connecting between the distal flip portion **292** and the proximal flip portion **294**, and between the proximal flip portion **294** and the shaft **34x**.

FIGS. **15(a)**-**15(c)** illustrate insufflating valve vents in accordance with additional aspects of the invention. More specifically, FIG. **15(a)** illustrates an insufflating valve vent **300** formed at the distal end of the shaft **34**. The insufflating valve vent **300** is formed of an elastic material to allow gas such as CO₂ to be introduced from the inside of the shaft **34** to a body cavity. It is appreciated that when there is no gas, the elastic material of the insufflating valve vent **300** causes it to close so as to provide an airtight seal. FIG. **15(b)** illustrates an insufflating flapper valve **310** formed at tip **32y** of an insufflating optical trocar. The insufflating flapper valve **310** comprises at least one flapper valve vent **312** that operates to open when a gas such as CO₂ is introduced in the shaft **34**. It is appreciated that when there is no gas, the flapper valve vent **312** closes to provide a tight seal. Similarly to FIG. **15(b)**,

FIG. **15(c)** illustrates an insufflating reverse flapper valve **320** formed at tip **32z** of an insufflating optical trocar. The insufflating reverse flapper valve **320** comprises at least one flapper valve vent **322** that remains close or shut by tissue during insertion, and once peritoneum is passed, pressure by a gas such as CO₂ would then open the reverse flapper valve **320** to allow the transfer of the gas into a body cavity. It is appreciated that each of the above flapper valve vents may be spring loaded to operate like a Veress needle.

FIG. **16** illustrates a blunt tip insufflating optical instrument **400** in accordance with another embodiment of the invention. The blunt tip insufflating optical instrument **400** comprises an elongate tubular body **410** extending along an axis between a proximal end and a distal end, a blunt tip optical obturator or separator **420** to be inserted through the tubular body **410** and into a body cavity, and an advanceable insufflation channel **430** extending along the length of the tubular body **410** and into the body cavity. The blunt tip optical obturator or separator **420** operates to provide visibility down to the peritoneum at which time the insufflation channel **430** may be advanced through the peritoneum to provide gas and/or saline to the body cavity until sufficient space is achieved. Once gas and/or saline have been sufficiently introduced, the blunt tip optical obturator **420** and tubular body **410** may be advanced into the body cavity. A feature of this aspect of the invention is the insufflation channel **430** may be advanced ahead of the blunt tip optical obturator or separator **420** to puncture peritoneum to transfer gas such as CO₂ to the body cavity.

Referring to FIGS. **17(a)** and **17(b)**, there are shown illustrations of an insufflating surgical instrument **500** in accordance with another embodiment of the invention. The insufflating surgical instrument **500** comprises an insufflating optical trocar **502** and a cannula **520**. The insufflating optical trocar **502** comprises a shaft **504** having a lumen extending along an axis between a proximal end and a distal end, a tip **506** disposed at a distal end of the shaft, at least one vent hole **508** to introduce gas from the cannula **520** into the body or abdominal cavity as further discussed below, and a gas channel **510** formed in either the shaft **504** or the tip **506** and operably connected to the at least one vent hole **508** to allow gas transfer from the cannula **520** to the insufflating optical trocar **502**. The cannula **520** comprises at least one cannula gas channel **522** extending along its longitudinal axis to transfer gas to the trocar gas channel **510** after insertion of the insufflating optical trocar **502** into the cannula **520**. In other words, the cannula gas channel **522** is encased as a lumen in the cannula wall. During operation, the transfer of gas only takes place if there is an alignment between the cannula gas channel **522** and the trocar gas channel **510** as illustrated in FIGS. **17(a)** and **17(b)**. A scope **525** may be inserted at the proximal end of the insufflating optical trocar **502** and then advanced to the distal end of the trocar **502** as the trocar **502** is placed through an abdominal wall.

In yet another aspect of the invention, FIG. **18** illustrates an insufflating blade actuating optical instrument **600** in accordance with another embodiment of the invention. The insufflating blade actuating optical instrument **600** comprises an elongate tubular member **602** extending along a longitudinal axis between a proximal end and a distal end, an optical member **604** operably attached at the distal end of the elongate member **602**, at least one blade member **606** being longitudinally movable between deployed and nondeployed positions, an actuating mechanism **608** operably attached at the proximal end of the tubular member **602** for moving the blade member **606** between the deployed and nondeployed positions, and at least one insufflating vent **610** formed in the

13

optical member **604** to transfer insufflation gas from outside a body cavity to inside the body cavity. A scope may be inserted at the proximal end of the insufflating blade actuating optical instrument **600** and then advanced to the distal end of the instrument **600** as the insufflating blade actuating optical instrument **600** is placed through an abdominal wall.

Referring to FIGS. **19(a)**-**19(i)**, there are shown additional tip designs **32aa**-**32ii** in accordance to other aspects of the invention to facilitate penetration of a body tissue. Each of these tip designs includes at least one vent hole (**36aa**-**36ii**) at the distal tip to introduce insufflation gas into a body cavity. It is appreciated that some of these tips have a sharp, pointed or bladed tip and/or edge to facilitate penetration of body tissue.

It is appreciated that the above described surgical instruments and devices can be used to access not only the peritoneal cavity but can be used for preperitoneal hernia repair, retroperitoneal operations including back and kidney operations, percutaneous kidney operations, thoracic surgery and arthroscopic access. In addition to gas such as carbon dioxide, it is appreciated that other fluids such as air, water and saline can also be introduced into a body cavity with the technique of the invention. It is appreciated that operating scopes may be modified such that a lumen may be used to introduce insufflation fluid. Accordingly, it is understood that many other modifications can be made to the various disclosed embodiments without departing from the spirit and scope of the invention. For these reasons, the above description should not be construed as limiting the invention, but should be interpreted as merely exemplary embodiments.

The invention claimed is:

1. A surgical instrument adapted for movement across an abdominal wall to insufflate the abdominal region of a patient, comprising:

a cannula having a wall forming a first lumen extending along an axis between a proximal end and a distal end; and

an elongate tube comprising a wall forming a second lumen extending between a proximal end and a distal end; the elongate tube being insertable into and removable from the first lumen of the cannula; the elongate tube and the cannula forming an insufflation channel, the elongate tube comprising a tapered distal tip at the distal end of the elongate tube; the tapered distal tip being configured to penetrate tissue; at least one vent hole formed in both the tapered distal tip and along the elongate tube; each; the vent hole being in connection with the insufflation channel; the insufflation channel being adapted for channeling insufflation fluid under pressure along the elongate tube from the proximal end and out the vent hole in the tapered distal tip;

wherein the elongate tube is configured for insertion of a laparoscope into the second lumen of the elongate tube; and

wherein the insufflation channel, first lumen of the cannula, and second lumen of the elongate tube are interconnected as one shared channel and configured to provide transfer of insufflation fluid while a laparoscope is inserted within the second lumen of the elongate tube.

14

2. The surgical instrument of claim **1** wherein the distal end of the elongate tube is tapered to form a generally cone-shaped tip.

3. The surgical instrument of claim **1** further including an optical element disposed at the distal end of the elongate tube.

4. The surgical instrument of claim **3** wherein the optical element is a light or endoscope.

5. The surgical instrument of claim **1** wherein the at least one of the tip and the elongate tube is formed of a transparent or translucent material.

6. The surgical instrument of claim **1** wherein the tip is blunt.

7. The surgical instrument of claim **1** wherein a first vent hole is formed in the elongate tube and a second vent hole is formed in the tip.

8. A surgical instrument, comprising:

a cannula having a wall forming a first lumen extending along an axis between a proximal end and a distal end; and

an elongate tube comprising a wall forming a second lumen extending between a proximal end and a distal end; the elongate tube being insertable into and removable from the first lumen of the cannula; the elongate tube and the cannula forming an insufflation channel, the elongate tube comprising a transparent tapered distal tip at the distal end of the elongate tube; the tapered distal tip being configured to penetrate tissue; at least one vent hole formed in both the transparent tapered distal tip and along the elongate tube; each; the vent hole being in connection with the insufflation channel, first lumen of the cannula; the insufflation channel being adapted for channeling insufflation fluid under pressure along the elongate tube from the proximal end and out the vent hole in the transparent tapered distal tip; and

wherein the elongate tube is configured to enable insertion of a laparoscope into the second lumen of the elongate tube; and

wherein the insufflation channel and second lumen of the elongate tube are interconnected as one shared channel and configured to provide transfer of insufflation fluid while a laparoscope is inserted within the second lumen of the elongate tube.

9. The surgical instrument of claim **8** further including an optical element disposed at the distal end of the elongate tube configured for visualization through the tip from inside the lumen.

10. The surgical instrument of claim **9** wherein the optical element is a light or endoscope.

11. The surgical instrument of claim **8** wherein the transparent tip includes a cross-sectional area that increases with increasingly proximal cross-sections taken perpendicular to a longitudinal axis of the elongate tube.

12. The surgical instrument of claim **8** wherein a first vent hole is formed in the elongate tube and a second vent hole is formed in the tip.

13. The surgical instrument of claim **8** wherein the tip is tapered to form a generally cone-shaped tip.

* * * * *

专利名称(译)	充气光学手术器械		
公开(公告)号	US9155558	公开(公告)日	2015-10-13
申请号	US13/356260	申请日	2012-01-23
[标]申请(专利权)人(译)	应用医疗资源		
申请(专利权)人(译)	应用医疗资源CORPORATION		
当前申请(专利权)人(译)	应用医疗资源CORPORATION		
[标]发明人	ALBRECHT JEREMY J BRUSTAD JOHN R TAYLOR SCOTT V JOHNSON GARY M HILAL NABIL		
发明人	ALBRECHT, JEREMY J. BRUSTAD, JOHN R. TAYLOR, SCOTT V. JOHNSON, GARY M. HILAL, NABIL		
IPC分类号	A61B17/34 A61M13/00 A61B19/00		
CPC分类号	A61B17/3417 A61B17/3474 A61M13/003 A61B17/3462 A61B2017/3454 A61B19/5212 A61B2017/346 A61B2017/349 A61B17/3494 A61B1/06 A61B90/361 A61M2202/0007 A61M2202/02 A61M2202/0468 A61M2205/3337		
优先权	60/584302 2004-06-29 US		
其他公开文献	US20120123202A1		
外部链接	Espacenet USPTO		

摘要(译)

本发明公开了一种吹气手术器械，其适于穿过腹壁移动以吹入患者的腹部区域。该器械包括轴，该轴具有在近端和远端之间延伸的注气通道，注气通道适于连接到近端压力下的流体源。尖端位于远端，并且在尖端中形成通气孔，该通气孔与吹气通道连接并适于在压力下排出流体以吹入腹部区域。尖端由透明材料形成，以便于腹壁和区域的可视化。轴包括在近端和远端之间沿轴线延伸的内腔，以便能够插入腹腔镜。内腔和吹入通道可以形成为单独的通道或一个共用通道。

