









US 20140323807A1

(19) **United States**(12) **Patent Application Publication**
Mastri et al.(10) **Pub. No.: US 2014/0323807 A1**(43) **Pub. Date: Oct. 30, 2014**(54) **DEVICES FOR AND METHODS OF
PERFORMING MINIMALLY-INVASIVE
SURGICAL PROCEDURES THROUGH A
SINGLE INCISION**(60) Provisional application No. 61/104,501, filed on Oct.
10, 2008.**Publication Classification**(71) Applicant: **SurgiQuest, Inc.**, Milford, CT (US)(51) **Int. Cl.**
A61B 17/34 (2006.01)(72) Inventors: **Dominick Mastri**, Bridgeport, CT (US);
Kurt Azarbarzin, Fairfield, CT (US)(52) **U.S. Cl.**
CPC **A61B 17/3423** (2013.01); **A61B 17/3462**
(2013.01); **A61B 2017/00986** (2013.01)(21) Appl. No.: **14/329,497**USPC **600/204**(22) Filed: **Jul. 11, 2014****Related U.S. Application Data**(60) Division of application No. 12/577,179, filed on Oct.
10, 2009, now Pat. No. 8,795,235, which is a continu-
ation-in-part of application No. 11/786,832, filed on
Apr. 13, 2007, now Pat. No. 7,806,870, which is a
continuation-in-part of application No. 11/544,856,
filed on Oct. 6, 2006, now Pat. No. 7,798,998.(57) **ABSTRACT**

The present invention relates to surgical access devices (or surgical access ports) and related methods. More particularly, the present invention relates to such devices that are advantageously adapted for use in single-incision laparoscopic surgical ("SILS") procedures. The present invention also relates to kits and methods involving such surgical access devices.










Fig. 7














Fig. 8

Fig. 9













Fig. 24




Fig. 25





Fig. 26







Fig. 29





Fig. 30

Fig. 32





Fig. 31






Fig. 33




Fig. 34







Fig. 35








Fig. 42




Fig. 43




Fig. 44




Fig. 45




Fig. 46





Fig. 47






Fig. 49




Fig. 50




Fig. 51




Fig. 52




Fig. 53




Fig. 54




Fig. 55




Fig. 56




Fig. 57




Fig. 58




Fig. 60

Fig. 61





Fig. 62




Fig. 63




Fig. 64




Fig. 65




Fig. 66

**DEVICES FOR AND METHODS OF
PERFORMING MINIMALLY-INVASIVE
SURGICAL PROCEDURES THROUGH A
SINGLE INCISION**

**CROSS-REFERENCE TO RELATED
APPLICATIONS**

[0001] The application is a continuation-in-part of U.S. patent application Ser. No. 11/786,832, filed Apr. 13, 2007, which is a continuation-in-part of U.S. patent application Ser. No. 11/544,856, filed Oct. 6, 2006. This application also claims the benefit of priority to U.S. Patent Application Ser. No. 61/104,501, filed Oct. 10, 2008. The disclosure of each of the foregoing applications is incorporated herein by reference in its entirety.

BACKGROUND

[0002] 1. Field of the Invention

[0003] The present invention relates to surgical access devices (or surgical access ports) and related methods. More particularly, the present invention relates to such devices that are advantageously adapted for use in single-incision laparoscopic surgical ("SILS") procedures. The present invention also relates to kits and methods involving such surgical access devices.

[0004] 2. Description of the Related Art

[0005] Increasingly, techniques are being developed for performing minimally invasive surgical procedures with a single incision, in order to reduce trauma and reduce the amount of scarring of a patient. It is often difficult to insert multiple traditional surgical instruments simultaneously through a single incision, due to mutual interference, and lack of available space. It has therefore become necessary to develop devices, systems and procedures to facilitate such approaches. The present invention provides a many outstanding challenges in the art.

SUMMARY

[0006] The purpose and advantages of the present invention will be set forth in and apparent from the description that follows. Additional advantages of the invention will be realized and attained by the devices and methods particularly pointed out in the written description and claims hereof, as well as from the appended drawings.

[0007] In accordance with one aspect of the invention, a method of performing a laparoscopic surgical procedure is providing, comprising the steps of, creating an incision in a patient to access a surgical site, inserting a first surgical access port into the incision, inserting a second surgical access port into the incision, and inserting a third surgical access port between the second and third surgical access ports, at least one access port having a length longer than at least one other surgical access port.

[0008] One or more of the surgical access ports can include an elongated body with opposed proximal and distal end portions, the body having a central lumen extending therethrough and having a resilient bulb portion formed between the proximal and distal end portions thereof, wherein the resilient bulb portion is adapted and configured to transition between a first condition in which the bulb portion has a first diameter and a first length and a second condition in which the bulb portion has a second diameter that is less than the first diameter and a second length that is greater than the first

length, and optionally a telescoping guide tube assembly disposed within the central lumen of the body, wherein the guide tube assembly is adapted and configured to transition between a first length corresponding to the first condition of the bulb portion and a second length corresponding to the second condition of the bulb portion.

[0009] The aforementioned surgical procedures can be any desired, including a hysterectomy or cholecystectomy, for example.

[0010] In accordance with another aspect of the invention, a kit for performing a minimally invasive surgical procedure is provided, having a plurality of surgical access ports. Each access port can include an elongated body with opposed proximal and distal end portions, the body having a central lumen extending therethrough and having a resilient bulb portion formed between the proximal and distal end portions thereof, wherein the resilient bulb portion is adapted and configured to transition between a first condition in which the bulb portion has a first diameter and a first length and a second condition in which the bulb portion has a second diameter that is less than the first diameter and a second length that is greater than the first length, and optionally, a telescoping guide tube assembly disposed within the central lumen of the body, wherein the guide tube assembly is adapted and configured to transition between a first length corresponding to the first condition of the bulb portion and a second length corresponding to the second condition of the bulb portion, wherein at least one of the surgical access ports has an overall length longer than at least one of the other surgical access ports provided in the kit.

[0011] With such kits, three access ports can be included, one of the access ports being longer than the remaining two access ports. Likewise, four access ports can be included, two of the access ports being longer than the remaining two access ports.

[0012] If desired, at least one of the plurality of access ports can be adapted and configured for nesting with at least one other of the plurality of access ports. For example, the housings at the proximal ends thereof can be configured to facilitate mutual close placement thereof. Accordingly, such housings can be provided with a minimally-sized housing in diameter and/or height in whole, or in a portion thereof, for example.

[0013] In accordance with the invention, if insufflation capability is desired through the access port or ports, only one port having insufflation capability is required to provide such capability. Accordingly, kits can be provided having only one port with such capability. Minimizing a number of insufflation ports on the set of devices minimizes the size of the devices without ports, thus enhancing close-positioning of adjacent ports.

[0014] In accordance with the foregoing aspects, the following features can be incorporated therewith, as desired. The bulb portion can have, for example, a generally spherical, generally ovoid, or other shape configuration in the first condition. The bulb portion of the access port body can be formed at least in part from an elastomeric material, such as silicone rubber. The bulb portion can have an outer surface with a substantially convex arcuate contour. The proximal end portion of the access port body can have a substantially constant outer diameter. Further, the bulb portion in the first condition can include an expanded diameter, or can be substantially straight. Additionally or alternatively, the bulb portion can

include one or more circumferential longitudinally spaced ribs or longitudinal circumferentially-spaced ribs.

[0015] An insert sleeve can be disposed within the distal end portion of the access port body for engaging a distal end portion of the trocar and can be arranged at the distal end of the access port body, forming a tip thereof. Such insert sleeve can be formed from a material having a greater rigidity than the access port body, and can be, for example, Nylon. The insert sleeve can include a plurality of proximally extending expandable guide fingers for lining an inner surface of the bulb portion to accommodate or facilitate insertion of the trocar. Additionally, if desired, an elongated guide tube can be provided, which extends through the proximal portion of the access port body and at least partially into the bulb portion of the access port body.

[0016] Further, if desired, a substantially rigid generally planar flange portion can be associated with the proximal end portion of the access port body, and can define an access port communicating with the lumen of the access port body. Such access port can have a conically tapering lead-in surface. If provided, the insertion device can include a handle with releasable locking means for releasably engaging aforementioned flange portion.

[0017] If desired or required, the proximal portion of the access port body can be provided with longitudinal, circumferentially spaced ribs formed on an outer surface of the body, for inhibiting elongation of the proximal end portion of the access port body during the transition from the first condition of the bulb portion to the second condition of the bulb portion. Alternatively or additionally, the proximal portion of the access port body can be provided with circumferential, longitudinally spaced ribs formed on an outer surface of the body, for inhibiting circumferential expansion of the proximal end portion of the access port body during the transition from the first condition of the bulb portion to the second condition of the bulb portion. Additionally or alternatively, the body can be provided with circumferential, longitudinally spaced ribs formed on an outer surface of the body, for inhibiting removal of the bulb portion from an abdominal wall of a patient.

[0018] In accordance with the invention, a seal member can be disposed within the lumen, in the proximal end portion of the access port body. Such seal member can be, for example, a duckbill-type valve, ball valve, or a fluid seal as set forth, for example in U.S. patent application Ser. No. 11/517,929 filed Sep. 8, 2006. Such seal member can include both an annular sealing portion for sealing against an instrument shaft inserted therethrough and a duckbill-type sealing portion for sealing the port in the absence of an instrument inserted therethrough. Such seal members can consist of include molded elastomeric part, or, alternatively, two separate parts. Additionally or alternatively, an integrally formed seal can be provided within the lumen, in the proximal end portion of the access port body. Such seal can be, for example, a protrusion provided on the wall of the lumen, to seal a space between the wall of the lumen and a surgical instrument. Alternatively or additionally, sealing can be accomplished by way of a collapsible region defined in the proximal end portion of the body such that the collapsible region can be collapsed by an outside force, to seal the lumen. Such outside force can be, for example, force exerted by the abdominal wall of a patient.

[0019] The body can be provided with a first engagement means in the distal end portion thereof, such that a distal end portion of a trocar can engage the first engagement means.

Such engagement means can be tabs, which are configured and arranged to be grasped by the trocar, or alternatively, a substantially rigid stepped element, for engaging a mating portion of the trocar. If desired, the body can be provided with second engagement means in the proximal end portion thereof, with a proximal end of the trocar, obturator or other insertion device being adapted for engaging the second engagement means.

[0020] In the foregoing embodiments, the trocar or insertion device preferably has a length greater than the first length of the bulb portion of the body, and therefore causes extension of the bulb portion to the second length. If a second engagement means is arranged in the proximal end portion of the body, for engagement with a proximal end portion of the trocar or insertion device, the insertion device can maintain the access port body in the second condition while engaged therewith.

[0021] In accordance with another preferred embodiment of the subject invention, there is provided a surgical access device that includes, among other things, a telescoping guide tube assembly disposed within the central lumen of the access port body for accommodating the elongated insertion device. The guide tube assembly is adapted and configured to transition between a first length corresponding to the first condition of the bulb portion and a second length corresponding to the second condition of the bulb portion. In addition, the insertion device is configured to extend through the guide tube assembly and releasably engage the guide tube assembly to facilitate the transition of the access device from the first condition of the bulb portion to the second condition of the bulb portion.

[0022] Preferably, the telescoping guide tube assembly includes a proximal tube section and a distal tube section. The proximal tube section is fixed relative to the access port body and the distal tube section is adapted to translate relative to the proximal tube section. The distal tube section of the guide tube assembly includes a nosepiece that extends from the distal end portion of the access port body and has a tapered outer surface. Preferably, the tapered outer surface of the nosepiece merges into the bulb portion of the access port body, to provide a smooth transition between the two structures. The guide tube assembly has an interior engagement ring therein for mating with an exterior engagement ring provided on the insertion device.

[0023] The access port body also includes a plurality of axially spaced apart annular retaining ribs. The plurality of axially spaced apart annular retaining ribs includes two different rib structures. These include a first rib structure having a horizontal ledge and an angularly inclined riser and a second rib structure having a generally V-shaped cross-section.

[0024] In addition, the access port includes a proximal housing portion that includes an inlet opening communicating with the guide tube assembly. The housing portion has an interior chamber that houses a seal member designed to interact with the insertion device or a surgical device inserted through the access port. The seal member preferably includes a duckbill seal portion and an annular wiper seal portion.

[0025] The insertion device used to facilitate the transition of the bulb portion between the first and second conditions includes a proximal handle assembly and an elongated trocar shaft that extends distally from the handle assembly. The handle assembly preferably includes means for engaging the proximal housing portion of the access port. In this regard, the proximal housing portion of the access port includes a proximal engagement flange and the handle assembly of the inser-

tion device includes a pair of opposed pivoting latching arms for releasably engaging the flange of the access port.

[0026] Preferably, the pivoting locking arms of the handle assembly are normally biased into a latching position by spring arms or the like disposed within the handle assembly. The insertion device preferably has a tissue-penetrating tip at the distal end of the trocar shaft. The tissue-penetrating tip preferably includes at least two cutting surfaces or facets, and more preferably, the facets define optical lens areas for visualization during the tissue penetration procedure.

[0027] In addition, the handle assembly includes means for receiving a laparoscope that would communicate with the optical lens areas of the trocar tip. In this regard, the handle assembly includes means for securing the position of a laparoscope relative to the insertion device. Preferably, the means for securing the position of the laparoscope relative to the insertion device includes a rotatable cam lock that interacts with a silicone washer designed to compressively engage an outer periphery of the laparoscope. These and other unique features of the access device and the insertion device will become more readily apparent from the following detailed description of the preferred embodiments of the invention taken in conjunction with the associated figures.

[0028] In accordance with still another aspect of the invention, a method of forming an access port in a patient is provided. The method includes the steps of providing an access port in accordance with the invention, as set forth herein; providing an insertion device configured to engage the distal end portion of the access port body; extending the insertion device into the central lumen of the access port body so as to engage the distal end portion of the access port body; elongating the access port with the insertion device, the end of the insertion device being engaged with the distal end portion of the access port body; inserting the access port and insertion device through an abdominal wall of a patient to a predetermined position, while maintaining the access port in an elongated configuration; and removing the insertion device from the access port, allowing the access port to revert to the first configuration, with the bulb portion of the access port engaging an interior surface of the abdominal wall.

[0029] The method can further include the step of performing surgery by inserting a surgical instrument through the lumen of the access port, and through an optional rigid member associated with a portion of the body. The method can further include sealing the central lumen, either upon itself, or between the access port and a surgical instrument. Such sealing can occur by radially inwardly directed force acting on the access port, exerted by the abdominal wall of the patient.

[0030] Additionally or alternatively, the step of elongating the access port with the insertion device can further include engaging the insertion device with a first engagement means at the distal end of the access port and elongating the port along the insertion device. Additionally or alternatively, the method can further include the step of engaging a second engaging means associated with the proximal end of the access port with a corresponding engagement means on the insertion device to selectively maintain the access port body in an elongated configuration.

[0031] In accordance with the invention, the step of inserting the port can include inserting the access port through the abdominal wall with the insertion device in engagement with the first and second engagement means of the access port. The methods set forth herein can further include removing the access port from the abdominal wall. Such removal can

include reengaging the insertion device with the first and second engagement means to elongate the access port body, and withdrawing the elongated access port from the abdominal wall.

[0032] It is to be understood that both the foregoing general description and the following detailed description are exemplary and are intended to provide further explanation of the invention claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

[0033] The accompanying drawings, which are incorporated in and constitute part of this specification, are included to illustrate and provide a further understanding of the devices and methods of the invention. Together with the description, the drawings serve to explain the principles of the invention, wherein:

[0034] FIG. 1 is an isometric view of a first representative embodiment of a surgical access device in accordance with the present invention, including an insertion device and an access port;

[0035] FIG. 2 is an isometric view of the access port of FIG. 1;

[0036] FIG. 3 is a partial cross-sectional view of the surgical access device of FIG. 1, showing the insertion device advancing through the access port;

[0037] FIG. 4 is a detail view of region 4 in FIG. 3;

[0038] FIG. 5 is a partial cross-sectional view of the surgical access device of FIG. 1, showing the insertion effecting extension of the through the access port, the figure also illustrating an initial insertion being made through an abdominal wall by the insertion device;

[0039] FIG. 6 is a detail cross-sectional view of the initial insertion of the surgical access device, the figure also illustrating the engagement between the insertion device and access port at the distal end of the surgical access device;

[0040] FIG. 7 is a partial cross sectional view illustrating the surgical access device of FIG. 1, inserted through the abdominal wall, with the insertion device partially withdrawn from the access port;

[0041] FIG. 8 is a partial cross sectional view illustrating the surgical access device of FIG. 1, inserted through the abdominal wall, with the insertion almost fully withdrawn from the access port;

[0042] FIG. 9 is a cutaway view the access port of the surgical access device of the preceding figures, illustrating the access port in use, with a surgical instrument inserted therethrough;

[0043] FIG. 10 is an isometric view of another embodiment of an access port of a surgical access device in accordance with the invention, having longitudinal ribs on a neck portion thereof;

[0044] FIG. 11 is a partial cross-sectional view of the access port of FIG. 10, taken along line 11-11 of FIG. 10;

[0045] FIG. 12 is a cross-sectional view of the access port of the access port of FIG. 10, taken along line 12-12 of FIG. 10;

[0046] FIG. 13 is a cutaway view of the access port of FIG. 10, shown in an elongated configuration, with an insertion device inserted therein;

[0047] FIG. 14 is a cutaway view of a further embodiment of an access port in accordance with the invention, having inwardly projecting guide fingers for facilitating insertion of surgical instruments through the access port;

[0048] FIG. 15 is a partial cross-sectional view of the access port of FIG. 14;

[0049] FIG. 16 is a cutaway view of the access port of FIG. 14, shown in an elongated configuration, with an insertion device inserted therein;

[0050] FIG. 17 is a cutaway view of a further embodiment of an access port in accordance with the invention, having a valve and a central guide tube for facilitating insertion of surgical instruments through the access port;

[0051] FIG. 18 is a partial cross-sectional view taken along line 18-18 of the access port of FIG. 17;

[0052] FIG. 19 is a partial cross-sectional view taken along line 18-18 of the access port of FIG. 17, shown in an elongated configuration, having an insertion device inserted therein;

[0053] FIG. 20 is a cutaway view of still another embodiment of an access port in accordance with the invention, including a reinforcing backstop for engagement with an insertion device in accordance with the invention;

[0054] FIG. 21 is a partial cross-sectional view of the access port of FIG. 20, taken along line 21-21;

[0055] FIG. 22 is an isometric view of a surgical access device in accordance with the invention, including the access port of FIG. 20, and an insertion device having a latching mechanism for engaging the access port;

[0056] FIG. 23 is an isometric view illustrating the surgical access device of FIG. 22, showing the access port in an elongated configuration in engagement with an insertion device, prepared for insertion through the abdominal wall of a patient;

[0057] FIG. 24 is an isometric view of a further embodiment of an access port in accordance with the invention, having a relatively longer neck portion than foregoing embodiments;

[0058] FIG. 25 is an isometric view of an additional embodiment of an access port in accordance with the invention, having a tip with flexible anchor elements provided thereon, for securing the tip to the access port body, and optionally for guiding surgical instruments through the lumen of the access port;

[0059] FIG. 26 is an isometric view of still another embodiment of an access port in accordance with the invention, having a flange reinforcing element provided thereon;

[0060] FIG. 27 is an isometric view of another embodiment of an access port in accordance with the invention, having a guide tube, valve and flange reinforcing element;

[0061] FIG. 28 is an exploded view of the access port of FIG. 27;

[0062] FIG. 29 is a cross-sectional view taken along line 29-29 of the access port of FIG. 27, shown in a non-elongated configuration;

[0063] FIG. 30 is a detail view of region 30 in FIG. 29;

[0064] FIG. 31 is a detail view of region 31 in FIG. 29;

[0065] FIG. 32 is a cross-sectional view of the access port of FIG. 27, shown in an elongated configuration with an insertion device inserted in the access port;

[0066] FIG. 33 is an isometric view of a further embodiment of an access port in accordance with the invention, having a generally flared configuration in the distal end portion thereof and circumferential ribs arranged thereon;

[0067] FIG. 34 is a partial cross-sectional view of the access port of FIG. 33;

[0068] FIG. 35 is a partial cross-sectional view of the access port of FIG. 33, shown in an elongated configuration with an insertion device inserted in the access port;

[0069] FIG. 36 is an isometric view of yet another access port in accordance with the invention, having a generally flared configuration in the distal end portion thereof with longitudinal ribs extending the length of the body thereof;

[0070] FIG. 37 is a partial cross-sectional view of the access port of FIG. 36;

[0071] FIG. 38 is a partial cross-sectional view of the access port of FIG. 36, shown in an elongated configuration with an insertion device inserted in the access port;

[0072] FIG. 39 is an isometric view of still another access port in accordance with the invention, having longitudinal ribs in a neck portion and circumferential ribs in the distal end portion thereof;

[0073] FIG. 40 is a partial cross-sectional view of the access port of FIG. 39;

[0074] FIG. 41 is a partial cross-sectional view of the access port of FIG. 39, shown in an elongated configuration with an insertion device inserted in the access port;

[0075] FIG. 42 is an isometric view of a further embodiment of access port in accordance with the invention, which access port has an enlarged, generally barb-shaped region and a plurality of barb-shaped ribs to inhibit pullout of the access port from the abdominal wall of a patient;

[0076] FIG. 43 is an exploded view of the access port of FIG. 42, illustrating the various components thereof;

[0077] FIG. 44 is a side view of the access port of FIG. 42, illustrating in hidden line the arrangement of internal components thereof;

[0078] FIG. 45 is a front view of the access port of FIG. 42, also illustrating in hidden line the arrangement of internal components thereof;

[0079] FIG. 46 is a perspective view of another embodiment of the elastomeric surgical access device of the subject invention, shown in a relaxed or unstretched condition in which the anchoring bulb has a first diameter and a first length;

[0080] FIG. 47 is a perspective view of the elastomeric surgical access device of FIG. 46, shown in an elongated or stretched condition in which the anchoring bulb has a second diameter less than the first diameter and a second length greater than the first length;

[0081] FIG. 48 is a cross-sectional view of the elastomeric surgical access device of the subject invention taken along line 48-48 of FIG. 46;

[0082] FIG. 49 is a cross-sectional view of the elastomeric surgical access device of the subject invention taken along line 49-49 of FIG. 47;

[0083] FIG. 50 is a perspective view of an insert device designed to deploy the elastomeric surgical access device of FIG. 46, which includes a handle assembly and a longitudinally extending trocar having a tissue-piercing tip;

[0084] FIG. 51 is cross-sectional view of the insert device of the subject invention taken along line 51-51 of FIG. 50;

[0085] FIG. 52 is a perspective view of the insert device of FIG. 50 together with the surgical access device of FIG. 46 in an unstretched condition;

[0086] FIG. 53 is cross-sectional view taken along line 53-53 of FIG. 52 showing the insert device of FIG. 50 together with the surgical access device of FIG. 46 in an unstretched condition;

[0087] FIG. 54 is a perspective view of the insert device of FIG. 50 together with the surgical access device of FIG. 46 in an elongated stretched condition;

[0088] FIG. 55 is cross-sectional view taken along line 55-55 of FIG. 54 showing the insert device of FIG. 50 together with the surgical access device of FIG. 46 in an elongated stretched condition;

[0089] FIG. 56 is a side, cutaway view illustrating three access ports in accordance with the invention inserted through a single incision formed in the abdominal wall of a patient;

[0090] FIG. 57 is an isometric cutaway view of the arrangement of the three access ports of FIG. 56, inserted through a single incision formed in the abdominal wall of a patient;

[0091] FIG. 58 is a cross-sectional view of one surgical access port of FIG. 56, taken across line 58-58 of FIG. 56;

[0092] FIG. 59 is an isometric view of a surgical access port having a low-profile for use in conjunction with single-incision surgeries;

[0093] FIG. 60 is an isometric view of the surgical access port of FIG. 59, in a longitudinally extended configuration;

[0094] FIG. 61 is an isometric view of a further embodiment of a surgical access port having a low-profile for use in conjunction with single-incision surgeries;

[0095] FIG. 62 is a cross-sectional view of the surgical access port of FIG. 61, taken along line 62-62 thereof;

[0096] FIG. 63 is a close-up view of a distal end portion of the surgical access port of FIG. 61;

[0097] FIG. 64 is an isometric partial cutaway view of three surgical access devices in accordance with the embodiment of FIG. 61 inserted through a small single incision, such as through an incision made through the umbilicus of a patient, to minimize scarring;

[0098] FIG. 65 is an isometric partial cutaway view of four surgical access devices in accordance with the embodiment of FIG. 61 inserted through a single linear incision, wherein mutual nesting permits close positioning of adjacent ports; and

[0099] FIG. 66 is a kit in accordance with the invention having a plurality of surgical access ports, also in accordance with the invention.

DETAILED DESCRIPTION

[0100] Reference will now be made in detail to the selected embodiments of the invention, examples of which are illustrated in the accompanying drawings. The devices and methods presented herein relate to providing a surgical access port to allow insertion and removal of surgical instruments during a procedure. The present invention is particularly suited for use in minimally-invasive surgical procedures of the abdomen, and is suitable for procedures where the abdominal cavity is pressurized with insufflation gas.

[0101] For purpose of explanation and illustration, and not limitation, an isometric view of an exemplary embodiment of a surgical access device in accordance with the invention is shown in FIG. 1 and is designated generally by reference character 100. Other embodiments of surgical access devices in accordance with the invention, or aspects thereof, are provided in FIGS. 2-34, as will be described.

[0102] FIGS. 1-9 illustrate the surgical access device 100, and components thereof alone, and in conjunction with an abdominal wall (i.e., 530 of FIGS. 5-9) of a patient, additionally illustrating the steps of insertion and use the surgical access device 100. The surgical access device 100 includes, generally, an access port 110 and an inserter 120. The access port is at least partially flexible in its construction, and depending on the particular embodiment can be primarily

composed of one or more flexible materials. The access port includes a body 118, with a proximal flange 101 and distal tip 107 arranged thereon, at opposed ends thereof. The body 118 includes bulb portion 105 and a neck portion 103, each of which defines a respective portion of a lumen 106 passing therethrough. Upon insertion, as will be understood, the bulb portion 105 assists in anchoring the access port 110 into the abdominal wall 530 (e.g., in FIG. 8) of the patient, while the neck portion 103 maintains a passageway through the abdominal wall 530.

[0103] The insertion device 120 includes a handle 121 for gripping by a user, a shaft 123, and a distal tip 125. The tip 125 can include an engagement feature, such as the stepped portion illustrated, which engages a mating stepped interior of the distal tip 107 of the access port 110. The insertion device can include a cutting tip at its distal end, or can have a blunt tip at the end thereof. The insertion device 120, therefore, can be a trocar, a blunt-tip obturator, or a visualization device (e.g., an obturator with a visualization tip and a channel to receive an endoscope), for example. The flange 101, serves multiple purposes. Firstly, the flange 101 serves as a location for a user to grip when preparing the access port 110 for insertion. Secondly, the flange 101 acts as a stop to abut the outer surface (skin) of the patient's abdominal wall, preventing the entire access port 110 from passing through the incision made to insert the access port. Further, the flange 101 can be provided with a lead in surface 102, which helps guide the insertion device 120, or other instruments therein and therethrough.

[0104] The tip 107 is provided at the distal end of the body 118 of the access port 110. The tip 107 is insert molded, adhered, or otherwise secured to the body 118, details of which are set forth below in connection with other embodiments. Since the tip 107 must securely engage the insertion device 120, the tip 107 is preferably made of a relatively rigid material. However, although illustrated as extending distally from the body 118, the tip can be provided within the body 118, near the distal end thereof, if desired. As such, the tip 107 can be concealed from view, while still having the necessary rigidity to withstand forces exerted by the insertion device 120, for example. Variations of the bulb portion 105, neck portion 103, tip 107 and flange 101 are described below in connection with other embodiments. Naturally, these specific features can be interchanged and combined as needed or desired.

[0105] FIG. 4 is a detail view of the respective region of FIG. 3. As can be seen, the lead in surface 102 can facilitate insertion of a surgical instrument. Additionally, an integral O-ring seal 104 is provided, which seals between an instrument shaft (illustrated as insertion device shaft 123), and the access port 110. Thus, egress of insufflation gas is inhibited. Naturally, such feature can be applied to any embodiment set forth herein. Additionally, the precise configuration of the seal 104 can vary, if desired, but the seal 104 can, as illustrated, be a simple projection of the seal 104 from the neck portion 103 of the access port 110. Moreover, a plurality of seals, such as seal 104 can be provided in series to further enhance sealing capability.

[0106] As shown in FIGS. 5 and 6, in use, the insertion device 120 is inserted through the lumen 106 of the access port 110, with the tip 125 of the insertion device 120, passing through and engaging the tip 107, preventing proximal movement of the tip 107, relative to the insertion device 120 (FIG. 6). Next, the flange 101 is pulled proximally by the user, toward the handle 121 of the insertion device 120, longitudinally

nally elongating the access port **110**, reducing its cross-sectional profile, to facilitate insertion (e.g., in FIG. 5). The access port **110** is maintained in an elongated configuration during insertion, as the surgical access device passes through the abdominal wall **530** of the patient. Because the access port **110** includes a flexible material, the access port **110** can be additionally radially compressed by the abdominal wall during insertion.

[0107] The surgical access device **100** is urged through the abdominal wall **530** of the patient until the flange **100** meets the surface **531**, or skin of the abdominal wall **530**. FIG. 7 illustrates the surgical access device **100** in such a position, with the insertion device **120** slightly withdrawn from the access port **110**. As the insertion device is withdrawn, the bulb portion **105**, now held within the abdominal cavity **535**, reverts toward its original configuration, expanding in diameter. The bulb portion **105**, therefore, engages the inside surface **532** of the abdominal wall **530**. If the access port **110** is configured in such a way that the neck **103** elongates during insertion, upon release of tension in the access port applied by the insertion device **120**, the neck **103** attempts to contract, thereby pulling the bulb portion **105** toward the flange **101**, helping secure the access port **110** to the abdominal wall **530**. If provided, however, ribs (e.g., ribs **1004** shown in FIG. 10) can inhibit the elongation of the neck **103**, allowing the force exerted in longitudinally elongating the access port **110** to be focused on reducing the cross sectional profile of the bulb portion **105**. Advantageously, as the bulb reverts to its original configuration with the bulb expanded in diameter, the surgical access port foreshortens, the benefits of which will be described below.

[0108] FIG. 9 illustrates the access port **100** of FIGS. 1-8, with a surgical instrument **930** inserted therethrough. As illustrated, the flange **101** maintains engagement with the upper and lower surfaces **531**, **532** of the abdominal wall **530**, even when the access port **110** is manipulated to angle an instrument. Because the surgical access port foreshortens during insertion and is firmly held in place relative to the abdominal wall by the bulb portion **105** and flange **101**, the length of the access device interacting with the surgical instrument is minimized and the forces, which must be exerted to angle and manipulate the surgical instrument can therefore be reduced. Further, as can be seen, access ports in accordance with the invention can be sized such that contact is maintained between the interior neck wall **913** and the shaft **933** of the instrument **930**, thereby maintaining an airtight seal. Additional seal elements, such as one or more internal ribs, can be arranged circumferentially on the inner wall **913** of the neck **103**, if desired. If a plurality of ribs are provided, they can be longitudinally spaced from one another so as to provide even greater sealing.

[0109] In this embodiment, upon withdrawal of the instrument **930**, the abdominal wall **530**, which continually exerts an inward force on the access port **110**, causes the lumen **106** in the region of the neck **103** to close, thus sealing the lumen **106**, inhibiting escape of insufflation gas from the surgical cavity (e.g., a pneumoperitoneum). Such behavior can be seen, for example, in FIG. 8, illustrating withdrawal of the insertion device **120** from the access port **110**. This occurs if the neck portion **103** is configured so as to allow this to happen. For example, the material selection must be such that the neck region is sufficiently compliant, compressible and/or collapsible to be affected by the force of the abdominal wall

530—that is, not excessively rigid. For this reason, it may be desirable to not include longitudinal ribs (e.g., ribs **1004** shown in FIG. 10).

[0110] In other instances, however, ribs or other stiffening means may be desirable. As an alternative to ribs, if desired, a material having directional reinforcement can be utilized, such as a fiber-reinforced polymer. As such, the access port **110** can be formed so as to have longitudinal resistance to elongation, for example at the neck **103**, while still easily collapsing radially, so as to seal between the access port and a surgical instrument.

[0111] It should be noted, that if the neck **103** of the access port **110** is configured so as to be relatively compliant, the neck can adapt to different sizes of surgical instruments inserted therethrough—expanding to the appropriate size to accommodate each tool.

[0112] FIGS. 10-13 illustrate an alternate embodiment of a surgical access device in accordance with the invention, designated generally by reference number **1000**, which access device **1000** includes an insertion device **1020** and access port **1010**. The access port **1010** is similar to the access port **110** of FIGS. 1-9 in many respects. However, in this embodiment, the bulb portion **1005** is more spherical than that of access port **110**, which itself is somewhat more elongate in shape. Naturally, the precise shape can be tailored as seen appropriate. The more spherical shape of the bulb portion **1005** of the access port **1010** of FIGS. 10-13 is particularly advantageous in areas where reduced clearance is present, such as, for example, along lateral sides of the abdominal cavity. In the medial portion of the abdominal cavity, particularly if the abdominal cavity is insufflated, more space is available than is available in the lateral regions of the abdominal cavity. The shortened shape of the bulb portion **1005**, allows placement of the access port **1010**, and allows manipulation of the access port **1010** and tools inserted therethrough, within the cavity.

[0113] Additionally, elongation-prevention ribs **1004** are provided on the neck **1003**. As evident, particularly from the cross-sectional view of FIG. 12, the increased cross-sectional area of the neck **1003** affords increased resistance to the applied tension needed to elongate the access port **1010** prior to insertion, while not substantially affecting the ability of the neck **1003** to contract or expand radially. As mentioned briefly above, all or a portion of the access port **1010** can be composed of one or more materials having directional properties. For example, the neck **1003** can be provided with reinforcing fibers embedded within the material thereof. Such fibers can be as rigid as desired, to impart the desired properties on the access port.

[0114] Alternatively or additionally, the bulb **1005** or flange **1001** can similarly include materials having directional properties. If, for example, the bulb **1005** is reinforced or is otherwise composed of material(s) having directional properties, when tension is applied to the access port **1010** the bulb **1005** will simply deform to a point, elongating as a whole, but without the material itself elongating or “stretching.” Thus, it can therefore be understood that elongation or “stretching” of the material itself used for this and other access ports described herein, is not essential to practice of the invention.

[0115] FIG. 12 is a cross-sectional view taken across the neck **1003** of the access port **1010** of FIG. 10. The ribs **1004** of the neck **1003** are evident thereon, and the tip **1007** can be seen though the lumen **1006** of the access port **1010**. FIG. 13 illustrates the access port **1010** of FIG. 10 in an elongated

configuration. As can be seen, the relatively spherical shape of the bulb portion **1005** does not yield an access port **1010** that is incapable of assuming a low-profile shape.

[0116] FIGS. 14-16 illustrate a further embodiment of an access port **1410** in accordance with the invention. The general shape of the access port **1410** is similar to that of the access port **1010** of FIGS. 10-13. The access port **1410** includes a flange **1501** with a lead-in surface **1502**, a body **1518** having a neck portion **1503** with longitudinal ribs **1504**, and a bulb portion **1505**. A distal tip **1507** is also provided thereon for engaging an insertion device.

[0117] However, the access port **1410**, and more specifically the tip **1507**, includes axially inwardly and radially outwardly directed flexible fingers **1508**, which are provided to line the distal end portion of the lumen **1506**, defined within the bulb portion **1505**. The fingers **1508** serve to guide surgical instruments toward the lumen of the tip **1507**, so as to more easily pass through the access port **1410** and into surgical cavity. While the access port body **1518** (i.e., the bulb **1505** and the neck **1503**) may be made of a material that is relatively soft to allow flexure, the fingers **1508** and additionally the tip **1507** itself can be made of a relatively rigid material. Such material preferably also has a relatively low coefficient of friction against materials used in surgical instruments (e.g., metals and plastics), so that the instruments are easily guided through the lumen and into the surgical cavity.

[0118] The fingers **1508** also serve to reinforce the distal end portion of the bulb portion **1505**, if they are embodied such that they are at least partially secured to the bulb **1505**. Alternatively, they can simply be in contact with the inner surface **1506** of the bulb **1505**, resiliently contacting the surface **1506**. In the illustrated embodiment, particularly as seen in FIG. 15, the fingers **1508** each include a longitudinal, inwardly projecting portion **1519**, extending from the tip **1507**. The longitudinal portion **1519** is connected to a second, angled portion **1517** at a resilient hinge **1520**, the geometry of which is configured to maintain the angled portion **1517** of each finger **1508** in abutment with the interior surface **1506** of the bulb portion **1505**, if the fingers **1508** are not already secured thereto. The hinge **1520** can be a so-called living hinge, defined in the material of the finger **1508** by a reduced thickness region, for example. Alternatively, the fingers **1508** and hinges **1520** can simply be made of material that is flexible enough to bend during elongation of the access port **1410**.

[0119] With reference to FIG. 16, it can be seen that when the access port **1410** is elongated to result in a reduced cross-sectional profile prior to insertion, the fingers **1508** flex in conjunction with the bulb **1505**. The relative dimensions of the fingers **1508** can be selected as desired. For example, the fingers can widen toward their distal ends (distal with respect to the tip **1507**), in order to better guide instruments through the lumen **1506**. When in the elongated state, as shown in FIG. 16, such widened fingers can lay adjacently to one another, or can be configured to overlap one another. As such, the fingers cover an increased area, while the access port **1410** is in a first configuration (FIGS. 14, 15), and still allow the elongated, reduced profile configuration of FIG. 16.

[0120] With reference to FIGS. 17-19, a further embodiment of an access port **1710** in accordance with the invention is provided. The access port **1710** includes a proximal flange **1701**, a neck **1703** having longitudinal ribs **1704**, and a bulb portion **1705** terminating in a distal tip **1707**. The distal tip

1707 is attached to the bulb **1705** in this embodiment by extensions **1709**, which provide a location for the material of the bulb **1705** to engage the tip **1707**. Such engagement can be effected, for example, by way of insert molding the tip **1707** with the material of the body (i.e., the bulb **1705** and neck **1703**). In the case of the flange **1701**, as with other flanges set forth herein in connection with other embodiments, the flange **1701** can be molded integrally with the neck **1703** and bulb **1705** portions.

[0121] The access port **1710** of FIGS. 17-19 differs from the forgoing embodiments in that the access port **1710** includes a guide tube **1711** and a valve **1709** provided in the lumen **1706** thereof. The guide tube is provided with a proximal flange **1819**, which rests in a recess formed in the flange **1701** of the access port **1710**. The flange **1819** of the guide tube **1711** maintains the tube **1711** in place, and can be insert molded, adhered or otherwise attached to the access port body. The tube **1711** serves as a guide during insertion of surgical instruments, helping lead the instruments toward the tip **1707**, reducing the chances that such instruments will veer toward the inner wall **1706** of the bulb **1705**, which might delay the surgical procedure being performed. The guide tube **1711** is also preferably made out of material having a relatively low coefficient of friction, with respect to the surgical instruments being inserted therethrough, in order to further facilitate insertion of surgical instruments.

[0122] The valve **1709**, is shown as a duckbill type valve, but can be of any type desired. Alternatively or additionally, a ball valve and/or a fluid seal can be utilized, as set forth, for example in U.S. patent application Ser. No. 11/517,929 filed Sep. 8, 2006, which is incorporated herein by reference in its entirety. The valve **1709** is arranged within the guide tube **1711** and serves to reduce leakage of insufflation gas from the surgical cavity (e.g., a pneumoperitoneum), when instruments are removed from the access port **1710**. While certain of the foregoing embodiments, such as the access port **110** of FIGS. 1-9, seal upon removal of an instrument due to the compressive forces exerted by the abdominal wall, the guide tube **1711**, which is relatively rigid, prevents this embodiment from sealing in that manner. Accordingly, the valve **1709** is provided to seal when an instrument is removed from the access port **1710**.

[0123] FIGS. 20-23 illustrate a surgical access device, including an access port **2010** and an insertion device **2220**. The access port **2010** is similar in many respects to the foregoing access ports, with the exception of a reinforcing backstop **2012** provided on the underside of the flange **2001**. The backstop **2012** rigidifies the flange **2001**, and provides a secure surface for engagement with locking pawls **2223a**, **2223b** of the insertion device **2220**. The pawls **2223a**, **2223b** are preferably resiliently biased toward a closed position, where protrusions **2225** at the distal end thereof engage the backstop **2012**, inhibiting removal of the insertion device **2220** from the access port **2010**. A user can disengage the pawls **2223a**, **2223b** by depressing the release end **2224** of the pawls **2223a**, **2223b**, which pivot the protrusions **2225** away from the access port **2010** and the backstop **2012**.

[0124] While the above-described latching mechanism can be incorporated into any of the embodiments set forth herein, the access port **2010** illustrated includes a flange **2001**, which holds the backstop **2012**, a neck **2003** having longitudinal ribs **2004**, a bulb portion **2005**, and a tip **2007**, secured to the bulb portion **2005** with extensions **2008**.

[0125] In use, the user places the insertion device 2220 through the lumen 2006 of the access port 2010, elongating the access port 2010 until the pawls 2223a, 2223b engage the backstop 2012 (See FIG. 23). The access device is then inserted through the abdominal wall of the patient. The user then depresses the release ends 2224 of the pawls 2223a, 2223b, and withdraws the insertion device 2220 from the access port 2010, allowing the access port 2010 to revert toward its original configuration (as in FIG. 20, for example). The access port may deviate slightly from its original configuration when inserted because of the forces acting on the access port 2010. However, it is to be understood that the configuration of the access port 2010 prior to elongation is very similar to that of the access port 2010 when inserted through the abdominal wall.

[0126] FIGS. 24-26 illustrate further embodiments of access ports 2410, 2510 and 2610 in accordance with the invention, each of which includes an extended neck portion 2403. The extended neck portion 2403 can be particularly advantageous when the access ports 2410, 2510 and 2610 are used in a patient having a relatively thick layer of abdominal fat, or an otherwise thick abdominal wall. The access port 2410 of FIG. 24 is substantially similar to many of the foregoing embodiments, with the exception of the elongated neck portion 2403. A proximal flange 2401 is connected to the elongated neck 2403, which in-turn includes longitudinal ribs 2404. The bulb 2405 extends from the neck portion 2403 and terminates in the distal tip 2407, which is connected thereto via extensions 2408.

[0127] The access port 2510 of FIG. 25 differs from that of FIG. 24, in the connection between the tip 2507 and the bulb portion 2505. While the construction of the flange 2401, neck portion 2403, and ribs 2404 is identical to that of the access port 2410 of FIG. 24, the tip 2507 includes anchor elements 2508, which extend into and are at least partially embedded into the material of the bulb 2505. The anchor elements 2508 include a longitudinal, inwardly oriented spine 2519 and one or more transverse protrusions 2518, which are embedded into the wall of the bulb 2505. The spine 2519, if desired, can be embedded within the bulb 2505, or can be arranged such that it is exposed to the lumen 2406 of the access port to aid passage of surgical instruments through the access port 2510.

[0128] The access port 2610 of FIG. 26 includes a configuration having an identical bulb 2505, tip 2507 and anchor elements 2508 to those of the embodiment of FIG. 25. Similarly, the neck 2403 is identical to each of the embodiments of FIGS. 24 and 25. The access port 2610 of FIG. 26 includes a rigid flange reinforcement 2612 arranged at the proximal end of the access port 2610. The flange reinforcement 2612 is provided, and in this case, recessed into the flange 2601 to impart increased rigidity to the flange 2601. While the flange 2601 can be integrally formed, e.g., molded, with the neck 2403 and bulb 2505 without such reinforcement 2612, such material may be undesirably soft to alone provide adequate rigidity for the flange 2601, because the flange 2601 must be pulled by a user when preparing the access port 2610 for insertion.

[0129] FIGS. 27-31 illustrate an access port 2710 in accordance with the invention composed of a plurality of components. As with the access port 1710 of FIGS. 17-19, the access port 2710 includes a guide tube 2711, a valve 2709, and a body 2718, which in-turn includes a flange 2701, neck 2703, bulb 2705, and terminates in a tip 2707. The valve 2709 resides within the guide tube 2711, which in-turn is inserted

into the body 2718 of the access port 2710. A proximal flange 2713 of the guide tube 2711 is received by a recess 2813 defined in the flange 2701 of the access port body 2718.

[0130] The access port 2710 additionally includes a flange reinforcement 2712, having a lead in surface 2702 to help guide insertion of surgical instruments. As with the access port 2610 of FIG. 26, the flange reinforcement 2712 imparts additional rigidity to the flange 2701. The flange reinforcement 2712 can be applied to the proximal surface of the flange 2701, or partially or fully recessed therein, as in the access port 2610 of FIG. 26. The individual components can be mutually secured by way of any suitable means, including, but not limited to heat welding, ultrasonic welding, solvent welding, adhesive, cohesive or, if desired, mechanical interlocking features. FIG. 31, which is a detail view of the respective portion of FIG. 29, illustrates an intermediate bonding material 3140, which can be an adhesive, for example. In a preferred embodiment, the bonding material 3140 is a material that melts upon application of heat energy, thereby mutually bonding the components of the access port 2710. As best seen in FIG. 30, which is a detail view of the respective region of FIG. 29, the tip 2707 includes an interior step 3009, which engages a mating component on the tip 125 of the insertion device (e.g., see FIG. 32). As can be seen, FIG. 29 illustrates the access port 2710 in a first configuration, prior to insertion through the abdominal wall, and FIG. 32 illustrates the access port 2710 in a second configuration, prepared for insertion through the abdominal wall of the patient.

[0131] FIG. 33 is an isometric view of a further embodiment of an access port 3310 in accordance with the invention, having a generally flared configuration in the distal end portion of the body 3318. The flared region constitutes a bulb 3305, in that the expanded diameter of this region generally resembles such a configuration, and acts to anchor the access port 3310 in the abdominal wall of the patient. The access port 3310 includes a proximal flange 3301, with a flange reinforcing element 3312 arranged thereon, and a distal tip 3307 connected by the body 3318. Longitudinal ribs 3304 are formed on the neck portion 3303, and include a distal taper 3314 so that the ribs gradually approach the contour of the bulb portion 3305, as the diameter of the body 3318 increases toward the distal end of the access port 3310.

[0132] Circumferential ribs 3315 further increase the diameter of the bulb portion 3305, providing additional anchoring capability. While the foregoing embodiments can be made from elastomeric materials or non-elastomeric materials, this embodiment preferably includes a material having a predetermined degree of elasticity, particularly because the relative diameter of the bulb portion 3305 to the remainder of the body 3318 of the access port 3310 is not as great as in many of the foregoing embodiments. Accordingly, when elongated, the material of the access port 3310 will stretch, and while the bulb 3305 decreases in profile, the ribs 3315, which are part of the bulb 3305, will also stretch longitudinally, effecting a reduction in their cross-sectional profile.

[0133] FIG. 34 is a partial cross-sectional view of the access port of FIG. 33 and FIG. 35 is a partial cross-sectional view of the access port 3310 of FIG. 33, shown in an elongated configuration with an insertion device 120 inserted in the access port.

[0134] FIG. 36 is an isometric view of a further embodiment of an access port 3610 in accordance with the invention, also having a generally flared configuration in the distal end portion of the body 3618. The flared region constitutes a bulb

3605, which serves to anchor the access port **3610** in the abdominal wall of the patient. The access port **3610** includes a proximal flange **3301**, with a flange reinforcing element **3312** arranged thereon, and a distal tip **3607**, joined via the body **3618**, as with the foregoing embodiment of FIG. **33**. Longitudinal ribs **3604** are formed on the body **3618**, which extend along the length thereof. The ribs **3604** include an increased height portion **3614** toward the distal end thereof, superimposed at an increased diameter portion of the body **3618**. This embodiment also preferably includes a material having at least some degree of elasticity. Accordingly, when elongated, the material of the access port **3610** will stretch, with the bulb **3605** and ribs **3604** decreasing in profile.

[0135] FIG. **37** is a partial cross-sectional view of the access port of FIG. **36** and FIG. **38** is a partial cross-sectional view of the access port of FIG. **36**, shown in an elongated configuration with an insertion device **120** inserted in the access port **3610**.

[0136] FIG. **39** is an isometric view of still another access port **3910** constructed in accordance with the invention, having longitudinal ribs **3904** in a neck portion **3903** and circumferential ribs **3915** in the distal bulb portion **3905** thereof. A tip **3907** is also provided, which is connected to the flange **3301** and reinforcing member **3312** by the body **3918** of the access port **3910**. The ribs **3904** in the neck portion **3903** serve the purpose of preventing excessive elongation of the neck portion, when preparing the access port **3910** for insertion. The circumferential ribs **3915** in the bulb portion **3905** serve to resist unintended pullout of the access port **3910** from the abdominal wall of the patient. Therefore, it should be noted that as used herein, the term “bulb” refers to a region of expanded diameter, but which does not necessarily resemble a “bulb” shape. Accordingly, when elongated, the material of the access port **3910** will stretch, and while the bulb **3905** decreases in profile, the ribs **3915**, which are part of the bulb portion **3905**, will also stretch longitudinally, effecting a reduction in their cross-sectional profile, thereby facilitating insertion of the access port **3910** into the abdominal wall of the patient.

[0137] FIG. **40** is a partial cross-sectional view of the access port **3910** of FIG. **39**, and FIG. **41** is a partial cross-sectional view of the access port **3910** of FIG. **39**, shown in an elongated configuration with an insertion device **120** inserted in the access port.

[0138] FIGS. **42-45** illustrate an access port **4210** in accordance with the invention composed of a plurality of components, similar to the access port **2710** of FIGS. **27-31**. The access port **4210** includes a guide tube **4211**, a valve **4209**, and a body **4218**, which in-turn includes a flange **4201**, neck **4203**, bulb **4205**, and terminates in a tip **4207**. The valve **4209** resides within the guide tube **4211**, which in-turn resides in the body **4218** of the access port **4210**. A proximal flange **4213** (FIGS. **43-45**) of the guide tube **4211** resides in a recess defined in the flange **4201** of the access port **4210**.

[0139] The access port **4210** further includes a flange reinforcement **4212**, having a lead in surface **4202** to help guide insertion of surgical instruments therethrough. As with other access ports set forth herein, the flange reinforcement **4212** helps impart rigidity to the flange **4201**. The flange reinforcement **4212** can be applied to the proximal surface of the flange **4201**, or partially or fully recessed therein.

[0140] In this embodiment, as best seen in the exploded view of FIG. **43**, for example, the proximal flange **4213** of the guide tube **4211** is relatively large, and in combination with

the enlarged flange reinforcement **4212**, secures the valve **4209** to the body **4218** of the access port **4210** by engaging the valve **4209** therebetween.

[0141] As also can be seen in FIGS. **42-45**, the bulb **4205** includes a single distal enlarged portion **4216**, having an angled, generally barbed shape, and a plurality of ribs **4217** arranged along the length of the body **4218**, which also have a generally barbed shape. Such shape, due to the angled contours thereof, enables relatively easy insertion, while still resisting pullout of the access port **4210** from the patient's abdominal wall.

[0142] As with foregoing embodiments, the individual components of the access port **4210** can be mutually secured by way of any suitable means, including, but not limited to heat welding, ultrasonic welding, solvent welding, adhesive, cohesive or, if desired, mechanical interlocking elements.

[0143] In order to remove an access port in accordance with the invention from the body of a patient, one can pull the proximal flange (e.g., flange **101** of FIG. **8**) away from the abdominal wall. The counteracting force exerted by the abdominal wall will cause the surgical access port, and particularly the bulb portion (e.g., bulb **105** of FIG. **8**) to elongate for removal from the body cavity into which it was inserted. Alternatively, in order to remove the port, the insertion device, or a similar blunt-tipped tool for engaging the distal end portion of the access port, can be inserted into the access port to elongate the access port for removal. The latter method, however, may be preferred in order to minimize trauma to the abdominal wall of the patient.

[0144] Referring now to FIGS. **46** through **49**, there is illustrated another embodiment of the surgical access device of the subject invention, which is designated generally by reference numeral **5000**. Access device **5000** is functionally similar to the previously described access devices in that it is adapted and configured to transition between a relaxed or unstretched condition shown in FIGS. **46** and **48** and an elongated or stretched condition shown in FIGS. **47** and **49**, facilitated by a unique insertion device shown in FIG. **50**. The construction of access device **5000** differs from the previously described access devices in certain respects, as described in more detail hereinbelow.

[0145] Access device **5000** includes an elongated body portion **5100** and a proximal seal housing **5110**. Seal housing **5110** has a funnel shaped opening **5112** for receiving a trocar or surgical device and in interior cylindrical chamber **5115** for supporting a sealing member **5114** (see FIG. **48**). As best seen in FIGS. **48-49**, seal member **5114** is a one-piece seal assembly that includes a proximal seal section **5114a** in the form of a wiper seal and a distal valve seal section **5114b** in the form of a duckbill seal. The duckbill seal may be a single plane valve as shown or a double plane valve having two intersecting duckbills.

[0146] The seal housing **5110** of access device **5000** also includes a tubular insufflation port **5116** for mating with a source of pressurized fluid by way of a luer lock fitting or a similar type of connective arrangement known in the medical arts. The insufflation port **5116** of proximal seal housing **5110** includes a removable cap **5118** that is connected to the seal housing **5110** by a living hinge **5125** so that the cap **5118** does not become displaced during a surgical procedure and can be easily reused.

[0147] The body portion **5100** of access device **5000** includes an axially extendable elastomeric sheath **5120** defining a pathway for permitting minimally invasive access to the

abdominal cavity of a patient by a surgical device. The elastomeric sheath **5120** has a generally radially outwardly tapering cross-sectional configuration, in its unstretched condition, shown in FIG. **48**. The proximal end portion of the sheath **5120** has a flange section **5122** of increased thickness (relative to the body portion of the sheath) that is secured to the proximal housing **5110** by an underplate **5124**. A radially enlarged anchoring bulb **5128** is formed adjacent the distal end of sheath **5120** for securing the access device **5000** against the interior wall of the abdominal cavity, once it has been deployed.

[**0148**] The elastomeric sheath **5120** of access device **5000** includes a plurality of axially spaced apart annular retaining ribs **5130**. More particularly, the sheath **5120** includes two types of alternating ribs **5130**, including a first type **5132** that has a horizontal ledge **5132a** and an angularly inclined riser **5132b** and a second type **5134** that has a generally V-shaped cross-section. The ledged ribs **5132** prevent movement of the sheath **5120** in a proximal direction during use, as does the V-shaped ribs **5134**, although to a lesser extent. The V-shaped ribs **5134** differ from the ledged ribs **5132** in that they have the same wall thickness as the sheath **5120** itself, and thus more easily flatten out when the sheath **5120** is stretched during deployment, thereby reducing insertion resistance, as best seen in FIG. **48**.

[**0149**] Access device **5000** further includes telescoping guide tubes that include an inner tube **5136** and an outer tube **5138**. Together, the telescoping guide tubes **5136**, **5138** define a passage for a trocar during deployment of the access device **5000** and a pathway for the introduction of surgical instruments. The proximal end of the outer tube **5138** is preferably integrally formed with the proximal housing portion **5110** of access device **5000**. However, it is envisioned that the outer guide tube **5138** could be separate from and secured to the housing portion **5110**. The distal end of the inner tube **5136** extends from the distal end of sheath **5120** and defines a tapered nosepiece **5140** for the access device **5000**. The nosepiece **5140** provides a smooth transition surface to the radially enlarged anchoring bulb **5128**.

[**0150**] As discussed above and throughout this specification, an insertion device is utilized to effectuate the transition of the access device **5000** between the unstretched and stretched conditions shown in FIGS. **52** and **54**, respectively. An embodiment of the insertion device of the subject invention is illustrated in FIGS. **50** and **51**, and is designated generally by reference numeral **6000**. Together, the insertion device **6000** and the access device **5000** form a cooperative system for gaining ready access to the abdominal cavity of a patient in order to perform a laparoscopic surgical procedure.

[**0151**] Insertion device **6000** includes a proximal handle assembly **6100** that includes a barrel section **6112** and depending ergonomically shaped grip section **6114**. An elongated trocar shaft **6116** extends distally from the barrel section **6112** of handle assembly **6100**. The distal tip **6118** of trocar shaft **6116** is preferably adapted and configured to pierce through tissue, including the abdominal wall, and thus includes at least two cutting facets **6118a**, **6118b**.

[**0152**] It is also envisioned and well within the scope of the subject disclosure, that trocar shaft **6116** can be configured as an optical trocar assembly for purposes of visualizing the penetration into the abdominal cavity. Thus, the distal tissue-piercing tip **6118** of trocar shaft **6116** may include at least two optical facets or viewing windows **6118a**, **6118b** that communicate with light transmitting structures within the trocar

shaft (not shown). Trocar shaft **6116** also includes a medial engagement collar **6120** having circumferentially spaced apart fingers **6122** for interfingering or otherwise meshing with a complementary spaced apart fingers **5152** of a collar **5150** provided at the proximal end of the inner guide tube **5136** of access device **5000**, as best seen in FIG. **55**.

[**0153**] It is envisioned that the engagement collar **6120** on trocar shaft **6116** could be alternatively located at the distal end of the shaft, adjacent the cutting tip **6118**, and the complementary collar **5150** could be located at the distal end of the inner guide tube **5136**. The cooperative engagement of collars **5150** and **6120** effectively prevents relative radial movement of the trocar shaft **6116** and body portion **5120**, caused by the torque transmitting by handle assembly **6100** during use.

[**0154**] Referring now to FIG. **51**, the proximal end of the trocar shaft **6116** has a flared end section **6124** that serves to axially secure the trocar shaft **6116** within the barrel section **6112** of housing assembly **6100**. Handle assembly **6100** further includes a pair of latching arms **6126** and **6128** for releasably engaging a flange **5170** formed at the proximal end of access device housing **5110**, as best seen in FIGS. **52** and **53**. The latching arms **6126**, **6128** pivot about respective pivot pins **6136**, **6138** and have respective inwardly facing engagement fingers **6126a**, **6128a** and respective integral biasing legs **6126b**, **6128b** that urge the latching arms **6126** and **6128** into a latching position. The latching arms **6126**, **6128** are released from the latching position by depressing the opposing integrally formed buttons **6126c**, **6128c**, which cause the latching arms **6126**, **6128** to pivot away from one another.

[**0155**] Referring to FIGS. **51** and **53**, the handle assembly **6100** of insertion device **6000** is adapted and configured to receive a laparoscope (not shown) used to communicate with the optical piercing tip **6118** of trocar shaft **6116**. More particularly, the proximal end of barrel section **6112** has a reception port **6130** for receiving a laparoscope.

[**0156**] In addition, the handle assembly **6100** of insertion device **6000** includes a mechanism for securing the position of a laparoscope relative to the handle assembly **6100** of the insertion device **6000**. This mechanism includes a rotatable barrel cam **6132** having a cam slot **6134** that interacts with a corresponding cam follower (not shown). The barrel cam **6132** is rotated by way of a toggle switch **6136**, which causes a corresponding axial translation of the barrel **6132**. When the barrel cam **6132** moves in a distal direction, it axially compresses an aligned silicone washer **6135** against an aligned hard plastic retaining washer **6138**. The silicone washer **6135** is restricted from expanding radially outwardly by the walls of the housing assembly **6100**. Consequently, upon becoming axially compressed against hard plastic washer **6138**, the pliable silicone washer **6135** will compress radially inwardly against the outer surface of the tubular laparoscope extending there through. As a result, the laparoscope is maintained in a fixed position with respect to the barrel section **6112** of handle assembly **6100**.

[**0157**] In use, trocar tip **6118** and shaft **6116** are inserted into the proximal opening of access device **5000**, as illustrated in FIG. **52**. As the trocar shaft **6116** is inserted, the fingers **6122** on collar **6120** (see FIG. **50**) engage corresponding fingers **5152** of collar **5150**, at the proximal end of inner guide tube **5136** (see FIG. **48**). Engagement of fingers **6122** and **5152** orients the inner guide tube **5136** and trocar shaft **6116** in a key and slot style. Housing **5110** is then drawn toward handle assembly **6100** to elongate and stretch elongate body portion **5100**, until the latching arms **6126**, **6128** engage

flange **5170** to releasably lock the access device in the elongated configuration shown in FIGS. **49**, **54** and **55**).

[0158] The length of the trocar shaft **6116** from collar **6120** to penetration tip **6118** is selected so that the penetrating tip extends out of the inner guide tube to protrude from the end of the elongated body portion with the elongated body portion in the stretched position shown in FIGS. **54** and **55**. Advantageously, because the fingers **6122** and **5152** at a location proximal to the trocar tip **6118** permits the trocar tip and the nosepiece **5140** to be configured to have a low profile and a very smooth gradual transition from trocar tip **6118** to the elongated body **5100** across nosepiece **5140**. Engagement of fingers **6122** and **5152** also acts to extend the inner and outer guide tubes **5136**, **5138** within the elongated body portion **5100**.

[0159] With the elongated body portion **5100** mounted to the trocar **6116** as shown in FIG. **54**, the access device **5000** is ready for use. The device **5000** may be inserted through the abdominal wall until the trocar tip **6118** enters the abdomen. If desired, an optical device such as an endoscope may be optionally inserted through a central bore of the trocar shaft **6116** to permit visualization through the optical window portions of the trocar tip **6118**, to observe insertion of the trocar through the abdominal wall into the abdomen. With the trocar tip **6118** positioned inside the abdomen, the latching arms **6126**, **6128** are released from flange **5170**, which permits elongated body portion **5120** to resiliently return toward its initial unstretched configuration.

[0160] The elongated body portion **5120** may or may not return all the way to the original unstretched position, depending upon the thickness and gripping force of the surrounding tissue. However, the elongated body portion **5120** will return sufficiently toward the initial unstretched configuration so that the bulb portion **5128** expands radially outward to help secure or otherwise anchor the access device **5000** within the incision for surgery. The ribs **5130** variously disposed along the body portion **5120** also resume their rest position, extending radially outward from the body portion **5120** to assist in securing the access device **5000** relative to the patient's body.

[0161] At such a time, guide tubes **5136**, **5138** return toward the nested configuration shown in FIG. **48**. In this configuration, the access device **5000** presents a desirably low profile relative to the skin, so that instruments can be inserted and removed without obstruction from adjacent access devices. Thus, surgical instruments may be inserted and removed in the ordinary course of laparoscopic surgery to perform a surgical procedure. Guide tubes **5136**, **5138** guide the surgical instruments into the body and protect the elastomeric elongated body portion **5120** from damage or puncture due to engagement with instruments having aggressively configured tips (such as clip appliers, staplers, etc.).

[0162] After surgery is complete, the trocar tip **6118** may be reinserted into the access device **5000** to elongate and stretch the elongated body **5120** for ease of removal from the patient's body. Alternatively, it is contemplated that the access device **5000** may simply be pulled out of the body, such as by grabbing and pulling on housing **5110**. As the housing is pulled away from the body, elongate body **5120** will partially elongate and stretch against the resistance of the tissue until the bulb portion **5128** and ribs **5130** stretch sufficiently to slip out of the tissue and be removed.

[0163] Surgical access devices in accordance with the invention can serve many purposes, only one of which is use

in minimally-invasive surgical procedures. It should be appreciated by those skilled in the art, that access ports in accordance with the invention can be used wherever access, particularly sealable access, into a body cavity is needed.

[0164] The specific dimensions of surgical access devices, including access ports, in accordance with the invention can be selected as needed. Specifically, it is envisioned that a wide variety of sizes will be available to a user to enable the user to select the most appropriately dimensioned device for the patient and procedure at hand. The overall length of access ports in accordance with the invention can vary, as well as the relative lengths of the neck portions, diameters and lengths of bulb portions, dimensions of the flange dimensions of the access port, and the like. It is envisioned that the access ports set forth herein can replace typical rigid cannulas. Accordingly, general dimensions similar to such typical rigid cannulas are possible, although an operative (during surgery) length of the surgical access port, which is less than that of typical cannulas, is preferable.

[0165] Materials for access ports in accordance with the invention can include, as set forth above, plastics, composites, elastomers or metals if necessary, for any component or components thereof. For example, the flange and or tip can be reinforced by rigid plastic or metal components. As set forth above, materials having directional properties may be desirable.

[0166] FIG. **56** is a side, cutaway view illustrating three access ports **700a, b**, in accordance with the invention inserted through a single incision **740** formed in the abdominal wall **730** of a patient. FIG. **57** is an isometric cutaway view of the illustrated arrangement, and FIG. **58** is a cross-sectional view of one surgical access port **700a**, taken across line **58-58** of FIG. **56**. The set of elastomeric surgical access ports **700a, b**. As illustrated, for example, the central access port **700a** is preferably longer than the two outer access ports **700b**, which are used together, in accordance with the invention. Advantageously, the elastomeric surgical access ports **700a, b**, minimize protrusion beyond the inner surface **735** of the abdominal wall **730** of the patient. Access devices **700a, b**, which can be constructed in accordance with one or more of U.S. patent application Ser. No. 11/786,832 and U.S. patent application Ser. No. 11/544,856, are extended longitudinally during insertion to reduce the insertion profile of the access device **700a, b**, but are allowed to contract longitudinally following insertion, due to the inherent elasticity of the body of the access device. When contracted, the distal portions **712**, **722** of the access devices **700a, b** engage the inner surface **735** of the abdominal wall **730** or other anatomy, and thus do not interfere with anatomy, instruments or other access devices, in the operative space **737** any more than necessary, while still ensuring secure engagement with the abdominal wall **730** or other anatomical structure.

[0167] Although in the illustrations of FIGS. **56-57**, the center access device **700a** is longer than the outer access devices **700b**, it is to be understood that this embodiment is only for the purpose of providing an illustration, and that any number of access ports can be provided in any orientation, in accordance with the invention. For example, the outer access devices **700b** can be longer and nest above the inner access device **700a**, or one of the end access devices **700b** can extend over the central access device **700a**, with the remaining end access device **700b** remaining even with the inner access device **700a**. Of course, any number of access ports—for example fewer or greater than three, can be provided. For

example, a fourth access port can be nested above either the right or left access devices **700b** (as illustrated in FIG. **65**) and so on. Moreover, the extent of overlap between mutually nested adjacent access devices **700a,b** can be adjusted to suit the specific situation. That is, the spacing between adjacent access devices can be adjusted as necessary, depending on the precise requirements of the procedure being performed, while the arrangement can afford relative movement between adjacent access devices.

[0168] Devices in accordance with the invention, providing an extendible and nesting capabilities reduces the incision length while allowing the surgeon to manipulate the access devices **700a,b** as necessary, while maintaining anchoring with the abdominal wall **730** or other anatomical structure, which is afforded by a distal bulb portion **719**, **729** and engagement elements **718**, **728** provided along the outer portion of each respective access device **700a,b**.

[0169] As illustrated, one or more luer connections **727** can be provided on one or more access devices (e.g. device **700a**) for providing insufflation or alternatively irrigation fluids. The luer connections **717** can be omitted from some access devices, as with the outer access devices **700b**. Alternatively, insufflation can be removed from the access devices **700a,b** entirely and performed by way of a separate insufflation device, such as another access device or a veress needle, for example.

[0170] As best illustrated in FIG. **57**, an incision **740** is formed in the abdominal wall **730** of the patient. Then, a plurality of access ports **700a,b** are sequentially inserted into the incision **740** in a nested configuration, to minimize the lateral space required by multiple ports **700a,b**. Such an arrangement also facilitates manipulation of instruments **791** through the ports **700a,b** being used. As mentioned, it is to be understood that although three ports are shown, any plurality of ports can be utilized in this configuration to achieve the advantages of the invention—namely, reduced incision length, which results in reduced trauma to the patient, and less scarring, and easier manipulation of instruments **791**.

[0171] Each of the access ports **700a,b** illustrated are formed, in-part, of an elastomeric material, but it is to be understood that different access devices (e.g., ports, trocars) of different materials can be used in combination with those described and illustrated herein, if so desired. Each of the illustrated access ports **700a,b** includes an elongated body **720** with opposed proximal and distal end portions, which defines a longitudinal axis. The body **720** has a central lumen extending therethrough, which in-turn includes a resilient bulb portion **719**, **729** formed between the proximal and distal end portions of the body **720**. The resilient bulb portion **719**, **729** is adapted and configured to transition between a first condition in which the bulb portion **719**, **729** has a first diameter and a first length and a second condition in which the bulb portion **719**, **729** has a second diameter and a second length. The second diameter of the bulb portion **719**, **729** is less than the first diameter, and the second length of the bulb portion **719**, **729** is greater than the first length. In accordance with the invention, the access devices used can incorporate an internal guide tube **713**, which tubes can be configured to extend longitudinally when the access device extends.

[0172] In accordance with one aspect of the invention, multiple identical access devices can be used, with certain ones of such access devices remaining in a fully or partially extended state during use, with others remaining in a contracted or predominantly contracted state.

[0173] Alternatively, a combination of access devices **700** having different relaxed lengths can be utilized—particularly a combination of “long” access devices **700a** and “short” access devices **700b**, the long access device being longer than the short access device by an amount sufficient to allow the long access device **700a** to remain in a relaxed position while sitting beyond the short access device **700b** by a distance sufficient to allow a proximal end portion of the short access **700b** device to nest below the proximal end portion of the long access device **700a**.

[0174] FIG. **59** is an isometric view of a surgical access port **800** having a low-profile proximal end housing for use in conjunction with single-incision surgeries, and FIG. **60** is an isometric view of the surgical access port **800** shown in a longitudinally extended configuration. One or more such access devices **800** can be utilized, that have a proximal end portion **815** that is particularly adapted for utilization in a nested configuration. Such proximal end portions **815** can include a low-profile housing, which can include one or more chambers for providing insufflation or irrigation fluids, or the like, or for evacuation of such fluids. A height dimension **892** of the widest portion of the access port **800** housing is minimized in accordance with the invention. Such dimension **892** can be on the order of about 1.0 cm, for example. Alternatively, such access devices **800** can include one or more valves, and/or a non-mechanical fluidic seals, such as those described in U.S. patent Ser. No. 11/517,929, for example, which application is incorporated herein by reference in its entirety.

[0175] The subject invention is particularly advantageous for performing laparoscopic abdominal procedures, allowing for sealed insertion of multiple instruments at the same time, while minimizing trauma and scarring. For example, in the case of a hysterectomy, an incision can be made in the lower portion of the abdomen to provide access to a patient's uterus. The relevant instruments can be inserted through the surgical access devices **700a,b**, including but not limited to endoscopes, scalpels, graspers, morsellators, cautery devices, clamps, specimen retrieval pouches, and the like.

[0176] FIGS. **61-66** illustrate a further embodiment of a surgical access port **900** having a low-profile for use in conjunction with single-incision surgeries. FIG. **62** is a cross-sectional view of the surgical access port **900**, taken along line **62-62**.

[0177] The surgical access port **900** includes an overall low-profile housing **930**, which as illustrated includes upper **930a** and lower **930b** halves. The elastomeric body **920** is supported at one end by the housing **930** and at the distal end by a nosepiece **940**, in-turn supported by an inner telescoping guide tube **913** having upper **913a** and lower **913b** telescoping portions. The access port **900** includes an insufflation connection **917**. In accordance with the invention, however, the port **900** can be provided without such feature. As discussed above, a kit can be provided with one or more ports having an insufflation connection, and one or more ports being provided without an insufflation connection, as shown for example in FIGS. **64**, **65** and **66**.

[0178] The access port **900** includes in the housing **930** thereof, a connection feature **970** to facilitate connection with an insertion device, and one or more flat portions **935** for aligning the housing **930** with an insertion device. Advantageously, this feature also reduces the size of the housing **930** somewhat to permit close positioning of adjacent ports **900**.

The configuration of the housing 930 and the connection feature 970 permit an overall low profile of the access port 900 during insertion.

[0179] The housing 930 is also provided with a guide portion 933, to protect the upper seal member 914 from sharp surgical instruments, and to maintain the position thereof, within the housing 930, inhibiting inversion of the seal member 914. The upper seal member 914 is preferably configured to seal against a shaft of an instrument inserted therethrough, while a lower seal member 909 is preferably adapted to seal a central lumen of the access port in the absence of a surgical instrument.

[0180] FIG. 64 is an isometric partial cutaway view showing three surgical access devices in accordance with the embodiment of FIG. 61 inserted through a small single incision 940, such as through an incision made through the umbilicus of a patient, to minimize scarring;

[0181] FIG. 65 is an isometric partial cutaway view showing four surgical access devices in accordance with the embodiment of FIG. 61 inserted through a single linear incision 940, wherein mutual nesting permits close positioning of adjacent ports 900a,b.

[0182] FIG. 66 is a kit 1000 in accordance with the invention having a plurality of surgical access ports 900a,b, in a package 990, in accordance with the invention.

[0183] Any of the surgical access devices set forth above can be used in connection with the methods and kits hereof, without limitation, in keeping with the invention. It is to be understood that any feature disclosed in connection with one embodiment of the subject devices can be incorporated into another embodiment in accordance with the invention, without limitation, except where features are mutually exclusive. Such features include, for the purpose of providing non-limiting examples, optional features, materials, construction and assembly features and/or steps, sealing configurations, body configurations, guide tube configurations, inserter-coupling elements, and/or insufflation capability-related features.

[0184] It is to be understood that the subject invention can advantageously be applied to various surgical procedures. The devices, systems and methods of the present invention, as described above and shown in the drawings, provide for advantageous devices, kits and methods therefor. It will be apparent to those skilled in the art that various modifications and variations can be made in the devices, kits and methods of the present invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention include all such modifications and variations.

1-4. (canceled)

5. A kit for performing a minimally invasive surgical procedure having a plurality of surgical access ports, each port comprising:

- a) an elongated body with opposed proximal and distal end portions, the body having a central lumen extending therethrough and having a resilient bulb portion formed between the proximal and distal end portions thereof, wherein the resilient bulb portion is adapted and configured to transition between a first condition in which the bulb portion has a first diameter and a first length and a second condition in which the bulb portion has a second

diameter that is less than the first diameter and a second length that is greater than the first length;

- b) a telescoping guide tube assembly disposed within the central lumen of the body, wherein the guide tube assembly is adapted and configured to transition between a first length corresponding to the first condition of the bulb portion and a second length corresponding to the second condition of the bulb portion, wherein at least one of the surgical access ports has an overall length longer than at least one of the other surgical access ports provided in the kit; and

- c) a proximal housing operatively associated with the proximal end portion of the elongated body, wherein the proximal housing of at least one of the plurality surgical access ports includes a connective fitting for connecting that access port to a source of insufflation fluid.

6. The kit of claim 5, wherein three access ports are included in the kit, one of the access ports being longer than the remaining two access ports.

7. The kit of claim 5, wherein four access ports are included in the kit, two of the access ports being longer than the remaining two access ports.

8. The kit of claim 5, wherein at least one of the plurality of access ports is adapted and configured for nesting the proximal housings of the plurality of access ports.

9. A kit for performing a laparoscopic surgical procedure through a single incision, comprising:

- a plurality of surgical access ports each having a proximal housing that includes an engagement flange for engaging with an insertion device, wherein at least one of the access ports includes a connective fitting for connecting that access port to a flexible fluid conduit.

10. A kit as recited in claim 9, further comprising a packaging enclosure for supporting the plurality of access ports.

11. A kit as recited in claim 9, further comprising an insertion device having a handle assembly with latching arms for releasably engaging the engagement flange on the housing of each access port.

12. A kit as recited in claim 9, wherein three access ports are provided in the kit and one of the three access ports includes a connective fitting.

13. A kit as recited in claim 9, wherein three access ports are provided in the kit and two of the three access ports includes a connective fitting.

14. A kit for performing a laparoscopic surgical procedure through a single incision, comprising:

- a) three access ports each having a proximal housing that includes an engagement flange for engaging with an insertion device, wherein at least one of the three access ports includes a connective fitting for connecting with a flexible fluid conduit;
- b) an insertion device having a handle assembly with latching arms for releasably engaging the engagement flange on the housing of each of the three access ports; and
- c) a packaging enclosure for supporting the three access ports and the insertion device.

15. A kit as recited in claim 14, wherein two of the three access ports includes a connective fitting for connecting with a flexible fluid conduit.

* * * * *

专利名称(译)	通过单个切口进行微创外科手术的装置和方法		
公开(公告)号	US20140323807A1	公开(公告)日	2014-10-30
申请号	US14/329497	申请日	2014-07-11
[标]申请(专利权)人(译)	瑟吉奎斯特公司		
申请(专利权)人(译)	SURGIQUEST INC.		
当前申请(专利权)人(译)	SURGIQUEST INC.		
[标]发明人	MASTRI DOMINICK AZARBARZIN KURT		
发明人	MASTRI, DOMINICK AZARBARZIN, KURT		
IPC分类号	A61B17/34		
CPC分类号	A61B17/3423 A61B17/3462 A61B2017/00986 A61B2017/3486 A61B2017/3443 A61B2017/3447 A61B2017/347 A61B2017/00991 A61B17/3421 A61B17/3431 A61B17/3439 A61B17/3498 A61B90/361 A61M39/0247 A61M39/045 A61M2039/0279 A61M2039/0291		
优先权	61/104501 2008-10-10 US		
外部链接	Espacenet USPTO		

摘要(译)

本发明涉及外科进入装置 (或外科进入端口) 和相关方法。更具体地 , 本发明涉及有利地适用于单切口腹腔镜手术 (“SILS”) 手术的这种装置。本发明还涉及涉及这种手术进入装置的套件和方法。

