



US007922062B2

(12) **United States Patent**
Cole et al.

(10) **Patent No.:** **US 7,922,062 B2**
(45) **Date of Patent:** **Apr. 12, 2011**

(54) **ENDOSCOPIC STAPLING DEVICES AND METHODS**

(75) Inventors: **David Cole**, San Mateo, CA (US);
Andrew Smith, San Francisco, CA (US)

(73) Assignee: **Barosense, Inc.**, Durham, NC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 248 days.

(21) Appl. No.: **12/053,010**

(22) Filed: **Mar. 21, 2008**

(65) **Prior Publication Data**

US 2009/0236389 A1 Sep. 24, 2009

Related U.S. Application Data

(62) Division of application No. 12/050,169, filed on Mar. 18, 2008.

(51) **Int. Cl.**
A61B 17/068 (2006.01)

(52) **U.S. Cl.** **227/176.1; 227/19; 227/180.1; 606/139; 606/153; 606/219**

(58) **Field of Classification Search** **227/175.1, 227/176.1, 180.1, 178.1; 606/151, 163, 139, 606/219**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,408,865 A	3/1922	Cowell
3,663,965 A	5/1972	Lee et al.
4,134,405 A	1/1979	Smit
4,207,890 A	6/1980	Mamajek et al.
4,246,893 A	1/1981	Berson
4,315,509 A	2/1982	Smit
4,331,277 A	5/1982	Green

4,403,604 A	9/1983	Wilkinson et al.
4,416,267 A	11/1983	Garren et al.
4,417,360 A	11/1983	Moasser
4,441,215 A	4/1984	Kaster
4,467,804 A	8/1984	Hardy et al.
4,485,805 A	12/1984	Foster, Jr.

(Continued)

FOREIGN PATENT DOCUMENTS

CH 680263 A5 7/1992

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 12/050,169, Cole et al.

(Continued)


Primary Examiner — Scott A Smith

(74) *Attorney, Agent, or Firm* — King & Spalding LLP;
Peter J. Dehlinger; Kathleen A. Frost

(57) **ABSTRACT**

Described herein are endoscopic staplers used to apply one or more fasteners to body tissue. In one embodiment, a fastener-applying device, which is preferably a stapler, is passed transorally into the stomach and used to plicate stomach tissue by engaging tissue from inside of the stomach and drawing it inwardly. In the disclosed embodiments, the tissue is drawn inwardly into a vacuum chamber, causing sections of serosal tissue on the exterior of the stomach to be positioned facing one another. The disclosed staplers allow the opposed sections of tissue to be moved into contact with one another, and preferably deliver staples for maintaining contact between the tissue sections at least until serosal bonds form between them. Each of these steps may be performed wholly from the inside of the stomach and thus can eliminate the need for any surgical or laparoscopic intervention. After one or more plications are formed, medical devices may optionally be coupled to the plication(s) for retention within the stomach.

10 Claims, 22 Drawing Sheets



U.S. PATENT DOCUMENTS

4,501,264 A	2/1985	Rockey	6,120,534 A	9/2000	Ruiz
4,607,618 A	8/1986	Angelchik	6,146,416 A	11/2000	Andersen et al.
4,641,653 A	2/1987	Rockey	6,159,146 A	12/2000	El Gazayerli
4,648,383 A	3/1987	Angelchik	6,159,238 A	12/2000	Killion et al.
4,694,827 A	9/1987	Weiner et al.	6,197,022 B1	3/2001	Baker
4,723,547 A	2/1988	Kullas et al.	6,206,930 B1	3/2001	Burg et al.
4,747,849 A	5/1988	Galtier	6,245,088 B1	6/2001	Lowery
4,846,836 A	7/1989	Reich	6,251,132 B1	6/2001	Ravenscroft et al.
4,848,367 A	7/1989	Avant et al.	6,254,642 B1	7/2001	Taylor
4,899,747 A	2/1990	Garren et al.	6,258,120 B1	7/2001	McKenzie et al.
4,925,446 A	5/1990	Garay et al.	6,264,700 B1	7/2001	Kilcoyne et al.
4,946,440 A	8/1990	Hall	6,287,334 B1	9/2001	Moll et al.
4,969,896 A	11/1990	Shors	6,302,917 B1	10/2001	Dua et al.
4,997,084 A	3/1991	Opie et al.	6,358,197 B1	3/2002	Silverman
5,006,106 A	4/1991	Angelchik	6,416,522 B1	7/2002	Strecker
5,037,021 A	8/1991	Mills et al.	6,425,916 B1	7/2002	Garrison et al.
5,061,275 A	10/1991	Wallsten et al.	6,454,785 B2	9/2002	De Hoyos Garza
5,084,061 A	1/1992	Gau et al.	6,460,543 B1	10/2002	Forsell
5,088,979 A	2/1992	Filipi et al.	6,461,366 B1	10/2002	Seguin
5,163,952 A	11/1992	Froix	6,494,888 B1	12/2002	Laufer et al.
5,211,658 A	5/1993	Clouse	6,494,895 B2	12/2002	Addis
5,234,454 A	8/1993	Bangs	6,503,264 B1	1/2003	Birk
5,246,456 A	9/1993	Wilkinson	6,506,196 B1	1/2003	Laufer et al.
5,259,399 A	11/1993	Brown	6,527,784 B2	3/2003	Adams et al.
5,263,629 A	11/1993	Trumbull et al.	6,540,789 B1	4/2003	Silverman et al.
5,290,217 A	3/1994	Campos	6,544,291 B2	4/2003	Taylor
5,306,300 A	4/1994	Berry	6,547,801 B1	4/2003	Dargent et al.
5,314,473 A	5/1994	Godin	6,558,400 B2	5/2003	Deem et al.
5,327,914 A	7/1994	Shlain	6,558,429 B2	5/2003	Taylor
5,345,949 A	9/1994	Shain	6,572,627 B2	6/2003	Gabbay
5,401,241 A	3/1995	Delany	6,572,629 B2	6/2003	Kaloo
5,403,326 A	4/1995	Harrison et al.	6,575,896 B2	6/2003	Silverman
5,405,377 A	4/1995	Cragg	6,592,596 B1	7/2003	Geitz
5,431,673 A	7/1995	Summers et al.	6,596,023 B1	7/2003	Nunez et al.
5,486,187 A	1/1996	Schneck	6,607,555 B2	8/2003	Patterson et al.
5,514,176 A	5/1996	Bosley, Jr.	6,627,206 B2	9/2003	Lloyd
5,535,935 A	7/1996	Vidal et al.	6,632,227 B2	10/2003	Adams
5,562,239 A	10/1996	Boiarski et al.	6,663,639 B1	12/2003	Laufer et al.
5,571,116 A	11/1996	Bolanos et al.	6,675,809 B2	1/2004	Stack et al.
5,593,434 A	1/1997	Williams	7,229,428 B2	4/2004	Gannoe et al.
5,597,107 A	1/1997	Knodel et al.	6,740,098 B2	5/2004	Abrams et al.
5,609,624 A	3/1997	Kalis	6,740,121 B2	5/2004	Geitz
5,628,786 A	5/1997	Banas et al.	7,223,277 B2	5/2004	DeLegge
5,630,539 A	5/1997	Pyley et al.	6,746,460 B2	6/2004	Gannoe et al.
5,647,526 A	7/1997	Green et al.	6,755,869 B2	6/2004	Geitz
5,653,743 A	8/1997	Martin	6,764,518 B2	7/2004	Godin
5,662,713 A	9/1997	Andersen et al.	6,773,440 B2	8/2004	Gannoe et al.
5,673,841 A	10/1997	Schulze et al.	6,773,441 B1	8/2004	Laufer et al.
5,674,241 A	10/1997	Bley et al.	6,790,214 B2	9/2004	Kraemer et al.
5,706,998 A	1/1998	Pyley et al.	6,790,237 B2	9/2004	Stinson
5,709,657 A	1/1998	Zimmon	6,821,285 B2	11/2004	Laufer et al.
5,720,776 A	2/1998	Chuter et al.	6,835,200 B2	12/2004	Laufer et al.
5,749,918 A	5/1998	Hogendijk et al.	6,845,776 B2	1/2005	Stack et al.
5,762,255 A	6/1998	Chrisman et al.	6,932,838 B2	8/2005	Schwartz et al.
5,771,903 A	6/1998	Jakobsson	6,960,233 B1	11/2005	Berg et al.
5,785,684 A	7/1998	Zimmon	6,966,875 B1	11/2005	Longobardi
5,792,119 A	8/1998	Marx	6,981,978 B2	1/2006	Gannoe
5,820,584 A	10/1998	Crabb	6,981,980 B2	1/2006	Sampson et al.
5,839,639 A	11/1998	Sauer et al.	6,994,715 B2	2/2006	Gannoe et al.
5,848,964 A	12/1998	Samuels	7,011,094 B2	3/2006	Rapacki et al.
5,855,311 A	1/1999	Hamblin et al.	7,020,531 B1	3/2006	Colliou et al.
5,855,601 A	1/1999	Bessler et al.	7,025,791 B2	4/2006	Levine et al.
5,856,445 A	1/1999	Korsmeyer	7,033,373 B2	4/2006	de la Torre et al.
5,861,036 A	1/1999	Godin	7,033,384 B2	4/2006	Gannoe et al.
5,868,141 A	2/1999	Ellias	7,037,344 B2	5/2006	Kagan et al.
5,887,594 A	3/1999	LoCicero, III	7,056,305 B2	6/2006	Garza
5,897,562 A	4/1999	Bolanos et al.	7,066,945 B2	6/2006	Hashiba et al.
5,910,144 A	6/1999	Hayashi	7,083,629 B2	8/2006	Weller et al.
5,922,019 A	7/1999	Hankh et al.	7,090,699 B2	8/2006	Geitz
5,947,983 A	9/1999	Solar et al.	7,097,650 B2	8/2006	Weller et al.
5,993,473 A	11/1999	Chan et al.	7,097,665 B2	8/2006	Stack et al.
5,993,483 A	11/1999	Gianotti	7,111,627 B2	9/2006	Stack et al.
6,016,848 A	1/2000	Egres, Jr.	7,112,186 B2	9/2006	Shah
6,051,015 A	4/2000	Maahs	7,120,498 B2	10/2006	Imran et al.
6,086,600 A	7/2000	Kortenbach	7,121,283 B2	10/2006	Stack et al.
6,098,629 A	8/2000	Johnson et al.	7,146,984 B2	12/2006	Stack et al.
6,102,922 A	8/2000	Jakobsson et al.	7,147,140 B2	12/2006	Wukusick et al.
6,113,609 A	9/2000	Adams	7,152,607 B2	12/2006	Stack et al.
			7,160,312 B2	1/2007	Saadat et al.



7,172,613 B2	2/2007	Wazne	2005/0004430 A1	1/2005	Lee et al.
7,175,638 B2	2/2007	Gannoe et al.	2005/0004681 A1	1/2005	Stack et al.
7,175,660 B2	2/2007	Cartledge et al.	2005/0033326 A1	2/2005	Briganti et al.
7,211,114 B2	5/2007	Bessler et	2005/0033345 A1	2/2005	DeLegge
7,214,233 B2	5/2007	Gannoe et al.	2005/0049718 A1	3/2005	Dann et al.
7,220,237 B2	5/2007	Gannoe et al.	2005/0075654 A1	4/2005	Kelleher
7,220,284 B2	5/2007	Kagan et al.	2005/0080444 A1	4/2005	Kraemer et al.
7,229,453 B2	6/2007	Anderson et al.	2005/0085787 A1	4/2005	Laufer et al.
7,255,675 B2	8/2007	Gertner et al.	2005/0096673 A1	5/2005	Stack et al.
7,261,722 B2	8/2007	McGuckin, Jr. et al.	2005/0096750 A1	5/2005	Kagan et al.
7,288,101 B2	10/2007	Deem et al.	2005/0149114 A1	7/2005	Cartledge et al.
7,306,614 B2	12/2007	Weller et al.	2005/0159769 A1	7/2005	Alverdy
7,315,509 B2	1/2008	Jeong et al.	2005/0177181 A1	8/2005	Kagan et al.
7,316,716 B2	1/2008	Egan	2005/0183732 A1	8/2005	Edwards
7,320,696 B2	1/2008	Gazi et al.	2005/0192599 A1	9/2005	Demarais
7,326,207 B2	2/2008	Edwards	2005/0192615 A1	9/2005	Torre et al.
7,335,210 B2	2/2008	Smit	2005/0216040 A1	9/2005	Gertner et al.
7,354,454 B2	4/2008	Stack et al.	2005/0216042 A1	9/2005	Gertner
7,431,725 B2	10/2008	Stack et al.	2005/0240279 A1	10/2005	Kagan et al.
7,461,767 B2	12/2008	Viola et al.	2005/0247320 A1	11/2005	Stack et al.
2001/0011543 A1	8/2001	Forsell	2005/0250980 A1	11/2005	Swanstrom et al.
2001/0020189 A1	9/2001	Taylor	2005/0251158 A1	11/2005	Sadat et al.
2001/0020190 A1	9/2001	Taylor	2005/0251162 A1	11/2005	Rothe et al.
2001/0021796 A1	9/2001	Silverman et al.	2005/0256533 A1	11/2005	Roth et al.
2001/0044595 A1	11/2001	Reydel et al.	2005/0256587 A1	11/2005	Egan
2002/0022851 A1	2/2002	Kalloo et al.	2005/0261712 A1	11/2005	Balbierz et al.
2002/0055757 A1	5/2002	Torre et al.	2005/0267405 A1	12/2005	Shah
2002/0072761 A1	6/2002	Abrams et al.	2005/0267499 A1	12/2005	Stack et al.
2002/0082621 A1	6/2002	Schurr et al.	2005/0267595 A1	12/2005	Chen et al.
2002/0099439 A1	7/2002	Schwartz et al.	2005/0267596 A1	12/2005	Chen et al.
2002/0183767 A1	12/2002	Adams et al.	2005/0273060 A1	12/2005	Levy et al.
2002/0183768 A1	12/2002	Deem et al.	2006/0015006 A1	1/2006	Laurence et al.
2003/0009236 A1	1/2003	Godin	2006/0020278 A1	1/2006	Burnett et al.
2003/0040804 A1	2/2003	Stack et al.	2006/0058829 A1	3/2006	Sampson et al.
2003/0040808 A1	2/2003	Stack et al.	2006/0129094 A1	6/2006	Shah
2003/0065359 A1	4/2003	Weller et al.	2006/0151568 A1	7/2006	Weller et al.
2003/0093117 A1	5/2003	Saadat	2006/0155259 A1	7/2006	MacLay
2003/0109892 A1	6/2003	Deem et al.	2006/0155311 A1	7/2006	Hashiba et al.
2003/0120289 A1	6/2003	McGuckin, Jr. et al.	2006/0178560 A1	8/2006	Saadat et al.
2003/0158569 A1	8/2003	Wazne	2006/0178691 A1	8/2006	Binmoeller
2003/0191476 A1	10/2003	Smit	2006/0195139 A1	8/2006	Gertner
2003/0199989 A1	10/2003	Stack et al.	2006/0253142 A1	11/2006	Bjerken
2003/0199990 A1	10/2003	Stack et al.	2006/0271076 A1	11/2006	Weller et al.
2003/0199991 A1	10/2003	Stack et al.	2006/0282095 A1	12/2006	Stokes et al.
2003/0208209 A1	11/2003	Gambale et al.	2006/0287734 A1	12/2006	Stack et al.
2003/0220660 A1	11/2003	Kortenbach et al.	2007/0010864 A1	1/2007	Dann et al.
2004/0006351 A1	1/2004	Gannoe et al.	2007/0032800 A1	2/2007	Ortiz et al.
2004/0024386 A1	2/2004	Deem et al.	2007/0043384 A1	2/2007	Ortiz et al.
2004/0030347 A1	2/2004	Gannoe et al.	2007/0055292 A1	3/2007	Ortiz et al.
2004/0044353 A1	3/2004	Gannoe	2007/0060932 A1	3/2007	Stack et al.
2004/0044354 A1	3/2004	Gannoe et al.	2007/0149994 A1	6/2007	Sosnowski et al.
2004/0044357 A1	3/2004	Gannoe et al.	2007/0175488 A1	8/2007	Cox et al.
2004/0044364 A1	3/2004	DeVries et al.	2007/0191870 A1	8/2007	Baker et al.
2004/0082963 A1	4/2004	Gannoe et al.	2007/0191871 A1	8/2007	Baker et al.
2004/0088023 A1	5/2004	Imran et al.	2007/0198074 A1	8/2007	Dann et al.
2004/0092892 A1	5/2004	Kagan et al.	2007/0219571 A1	9/2007	Balbierz et al.
2004/0092974 A1	5/2004	Gannoe et al.	2007/0239284 A1	10/2007	Skerven et al.
2004/0093091 A1	5/2004	Gannoe et al.	2007/0260327 A1	11/2007	Case et al.
2004/0098043 A1	5/2004	Trout	2007/0276432 A1	11/2007	Stack et al.
2004/0107004 A1	6/2004	Levine et al.	2008/0033574 A1	2/2008	Bessler et al.
2004/0117031 A1	6/2004	Stack et al.	2008/0065122 A1	3/2008	Stack et al.
2004/0138761 A1	7/2004	Stack et al.	2008/0190989 A1	8/2008	Crews et al.
2004/0143342 A1	7/2004	Stack et al.	2008/0195226 A1	8/2008	Williams et al.
2004/0148034 A1	7/2004	Kagan et al.	2008/0208355 A1	8/2008	Stack et al.
2004/0153167 A1	8/2004	Stack et al.	2008/0294179 A1	11/2008	Balbierz et al.
2004/0158331 A1	8/2004	Stack et al.	2009/0024143 A1	1/2009	Crews et al.
2004/0162568 A1	8/2004	Saadat et al.	2009/0030284 A1	1/2009	Cole et al.
2004/0172141 A1	9/2004	Stack et al.	2009/0125040 A1	5/2009	Hambly et al.
2004/0172142 A1	9/2004	Stack et al.			
2004/0186502 A1	9/2004	Sampson et al.			
2004/0210243 A1	10/2004	Gannoe et al.			
2004/0215216 A1	10/2004	Gannoe et al.			
2004/0220682 A1	11/2004	Levine et al.			
2004/0225183 A1	11/2004	Michlitsch et al.			
2004/0225305 A1	11/2004	Ewers et al.			
2004/0236419 A1	11/2004	Milo			
2004/0243152 A1	12/2004	Taylor et al.			
2004/0243223 A1	12/2004	Kraemer et al.			
2004/0267378 A1	12/2004	Gazi et al.			
FOREIGN PATENT DOCUMENTS					
EP	0 775 471	A1	5/1997		
EP	1492478		1/2005		
EP	1 602 336	A2	12/2005		
FR	2768324	A1	3/1999		
JP	09-168597		6/1997		
WO	WO 91/01117	A1	2/1991		
WO	WO 97/47231	A2	12/1997		
WO	WO 00/12027	A1	3/2000		
WO	WO 00/32137	A1	6/2000		


WO	WO 00/78227	A1	12/2000
WO	WO 01/41671		6/2001
WO	WO 01/45485	A2	6/2001
WO	WO 01/49359	A1	7/2001
WO	WO 01/66018	A1	9/2001
WO	WO 01/85034	A1	11/2001
WO	WO 01/89393	A1	11/2001
WO	WO 02/060328	A1	8/2002
WO	WO 03/017882		3/2003
WO	WO 03/086246		10/2003
WO	WO 03/086247		10/2003
WO	WO 03/090633		11/2003
WO	WO 03/094784	A2	11/2003
WO	WO 03/094785		11/2003
WO	WO 03/099137	A2	12/2003
WO	WO 2004/019765		3/2004
WO	WO 2004/019787		3/2004
WO	WO 2004/032760	A2	4/2004
WO	WO 2004/037064		5/2004
WO	WO 2004/041133		5/2004
WO	WO 2004/064680		8/2004
WO	WO 2004/064685		8/2004
WO	WO 2004/080336		9/2004
WO	WO 2004/110285	A1	12/2004
WO	WO 2005/037152	A1	4/2005
WO	WO 2005/079673	A2	9/2005
WO	WO 2005/096991	A1	10/2005
WO	WO 2005/105003		11/2005
WO	WO 2006/016894	A1	2/2006
WO	WO 2006/055365	A2	5/2006
WO	WO 2006/127593		11/2006
WO	WO 2007/041598	A1	4/2007
WO	WO 2008/030403		3/2008
WO	WO 2008/033409		3/2008
WO	WO 2008/033474		3/2008
WO	WO2008/141288	A1	11/2008




OTHER PUBLICATIONS

The International Search report and Written Opinion for PCT application PCT/US2008/008726, Oct. 16, 2008, 13 pages (2008).

The International Search report and Written Opinion for PCT application PCT/US2007/019833, Dec. 9, 2007, 11 pages (2007).
 The International Search report for PCT application PCT/US2008/063440, search report dated Aug. 1, 2008, 11 pages (2007).
 The International Search report and Written Opinion for PCT application PCT/US2007/019940, Mar. 20, 2008, 12 pages (2008).
 Stecco, K. et al., "Trans-Oral Plication Formation and Gastric Implant Placement in a Canine Model", Stecco Group, San Jose and Barosnese, Inc., Redwood City, California (2004).
 Stecco, K. et al., "Safety of a Gastric Restrictive Implant in a Canine Model", Stecco Group, San Jose and Barosnese, Inc., Redwood City, California (2004).
 International Search Report from PCT Patent Application No. PCT/US2002/027177 mailed Feb. 14, 2003.
 International Search Report from PCT Patent Application No. PCT/US2003/004378 mailed Aug. 13, 2003.
 International Search Report from PCT Patent Application No. PCT/US2003/033605 mailed Mar. 29, 2004.
 International Search Report from PCT Patent Application No. PCT/US2003/033606 mailed Mar. 29, 2004.
 International Search Report from PCT Patent Application No. PCT/US2003/004449 mailed Aug. 13, 2003.
 International Search Report from PCT Patent Application No. PCT/US2004/006695 mailed Sep. 8, 2004.
 International Search Report from PCT Patent Application No. PCT/US2004/033007 mailed Feb. 9, 2005.
 International Search Report from PCT Patent Application No. PCT/US2005/014372 mailed Jul. 28, 2005.
 International Search Report from PCT Patent Application No. PCT/US2006/019727 mailed Apr. 19, 2007.
 International Search Report from PCT Patent Application No. PCT/US2006/038684 mailed Feb. 14, 2007.
 International Search Report from PCT Patent Application No. PCT/US2007/019227 mailed Feb. 20, 2008.
 International Search Report from PCT Patent Application No. PCT/US2008/008729 mailed Aug. 18, 2009.
 Felsner, et al., "Mucosal apposition in endoscopic suturing", Gastrointestinal Endoscopy, vol. 58, No. 6, pp. 867-870, (2003).










FIG. 4




FIG. 5







FIG. 6



**FIG. 8****FIG. 9**




FIG. 10




FIG. 11A




FIG. 11B




FIG. 11C




FIG. 11D




FIG. 11E









FIG. 12








FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21













FIG. 22










FIG. 29




FIG. 30A




FIG. 30B




FIG. 31A




FIG. 31B




FIG. 31C




FIG. 31D




FIG. 31E




FIG. 33




FIG. 32C




FIG. 32B






FIG. 32A



ENDOSCOPIC STAPLING DEVICES AND METHODS

This application is a divisional of U.S. patent application Ser. No. 12/050,169, filed Mar. 18, 2008, entitled ENDO-SCOPIC STAPLING DEVICES AND METHODS, and is incorporated herein by reference.

FIELD OF THE INVENTION

The present invention relates generally to the field of systems and methods for performing endoscopic surgery, and specifically to systems and methods for endoscopic stapling of tissue within body cavities.

BACKGROUND OF THE INVENTION

An anatomical view of a human stomach S and associated features is shown in FIG. 1A. The esophagus E delivers food from the mouth to the proximal portion of the stomach S. The z-line or gastro-esophageal junction Z is the irregularly-shaped border between the thin tissue of the esophagus and the thicker tissue of the stomach wall. The gastro-esophageal junction region G is the region encompassing the distal portion of the esophagus E, the z-line, and the proximal portion of the stomach S.

Stomach S includes a fundus F at its proximal end and an antrum A at its distal end. Antrum A feeds into the pylorus P which attaches to the duodenum D, the proximal region of the small intestine. Within the pylorus P is a sphincter that prevents backflow of food from the duodenum D into the stomach. The middle region of the small intestine, positioned distally of the duodenum D, is the jejunum J.

FIG. 1B illustrates the tissue layers forming the stomach wall. The outermost layer is the serosal layer or "serosa" S and the innermost layer, lining the stomach interior, is the mucosal layer or "mucosa" MUC. The submucosa SM and the multi-layer muscularis M lie between the mucosa and the serosa.

There are a number of applications for endoscopic application of fasteners such as staples to tissue within a body cavity. Some of those applications involve forming tissue structures such as plications or folds in tissue of the body cavity.

Several prior applications, including International Application No. WO 2005/037152 having an international filing date of Oct. 8, 2004 and U.S. application Ser. No. 11/439,461, filed May 23, 2006 (both incorporated herein by reference) describe methods according to which medical implants are coupled to tissue structures formed within the stomach. According to these applications, devices for inducing weight loss (e.g. by restricting and/or obstructing flow of food into the stomach, and/or by occupying a portion of the stomach volume) may be coupled to tissue tunnels or plications formed from stomach tissue.

For example, U.S. application Ser. No. 11/439,461 describes a restrictive and/or obstructive implant system for inducing weight loss. In one embodiment, flexible loops are coupled to tissue plications formed in the gastroesophageal junction region of the stomach. An implant, such as a flow restrictive and/or obstructive implant, is passed through the loops 2 and thus retained in the stomach.

In other instances, tissue plications may themselves be sufficient to provide the necessary treatment. For example, the plications may be used to reduce stomach volume or form a flow restriction within the stomach as disclosed in WO 2005/037152 and in Applicants' co-pending application Ser.

No. 11/542,457, filed Oct. 3, 2006, U.S. Publication No. 2007-0219571, which is incorporated herein by reference.

Other types of implants may be coupled to such plications or other tissue structures for a variety of purposes. These implants include, but are not limited to prosthetic valves for the treatment of gastro-esophageal reflux disease, gastric stimulators, pH monitors and drug eluting devices that release drugs, biologics or cells into the stomach or elsewhere in the GI tract. Such drug eluting devices might include those which release leptin (a hormone which creates feelings of satiety), Ghrelin (a hormone which creates feelings of hunger), octreotide (which reduces Ghrelin levels and thus reduces hunger), Insulin, chemotherapeutic agents, natural biologics (e.g. growth factor, cytokines) which aid in post surgery trauma, ulcers, lacerations etc. Still other implants might be of a type which might provide a platform to which specific cell types can adhere, grow and provide biologically-active gene products to the GI tract, and/or a platform for radiation sources that can provide a local source of radiation for therapeutic purposes, or provide a platform whereby diagnostic ligands are immobilized and used to sample the GI tract for evidence of specific normal or pathological conditions, or provide an anchor point for imaging the GI tract via cameras and other image collecting devices.

The prior applications listed above, address the desirability of forming tissue plications, pockets or tunnels in a way that regions of serosal tissue (i.e. the tissue on the exterior surface of the stomach) are retained in contact with one another. Over time, adhesions formed between the opposed serosal layers create strong bonds that can facilitate retention of the plication/pocket/tissue over extended durations, despite the forces imparted on them by stomach movement and implanted devices.

Regardless of the application for which a plication is being formed, it is highly desirable to form that plication using steps carried out from within the stomach using instruments passed down the esophagus, rather than using more invasive surgical or laparoscopic methods. The present application describes endoscopic staplers which may be passed transorally into the stomach and used to form serosal-to-serosal plications in a stomach wall.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a schematic illustration of a human stomach and a portion of the small intestine.

FIG. 1B is a cross-sectional perspective view of a portion of a stomach wall, illustrating the layers of tissue forming the wall.

FIG. 2 illustrates an endoscopic stapling system.

FIGS. 3A-3C are perspective views showing the stapler head of the stapling system of FIG. 2 in three different positions.

FIG. 4 is a perspective view of the stapler head, with the membrane removed.

FIG. 5 is a perspective view of the proximal end of the staple housing of the stapler head of FIG. 4.

FIG. 6 is a perspective view of the distal end of the staple housing of the stapler head of FIG. 4.

FIG. 7 is an exploded perspective view showing elements advanceable within the staple housing during compression and stapling operations.

FIG. 8 is a plan view of a staple reinforcement device.

FIG. 9 is a side elevation view of a staple cartridge.

FIG. 10 is a perspective view of the staple housing similar to FIG. 6, but showing some of the elements of FIG. 7 within the housing.

FIGS. 11A-11D are a series of schematic representations of the hydraulic chamber and pistons, illustrating operation of an exemplary hydraulic system during tissue compression and stapling.

FIG. 11E is similar to FIG. 11D and shows an alternative piston configuration.

FIG. 12 is a perspective view of the anvil housing of the stapler head of FIG. 4.

FIG. 13 is a perspective view of the anvil support.

FIG. 14 is a plan view of the anvil.

FIG. 15A is a cross-sectional side view of the cutting device and a first embodiment of a cutting board.

FIG. 15B is a cross-sectional side view of the cutting device and a second embodiment of a cutting board.

FIG. 16 is a perspective view of the hinged arm assemblies of the stapler head of FIG. 4.

FIG. 17 is a top plan view of the stapler head of FIG. 4 in the streamlined position for introduction into the body. Both the membrane and the membrane raiser are not shown for purposes of clarity.

FIG. 18 is similar to FIG. 17 and illustrates hidden features of FIG. 17.

FIG. 19 is a perspective view of the stapler head in an intermediate, partially expanded, position.

FIG. 20 is a plan view similar to FIG. 17 but showing the stapler head in the intermediate position.

FIG. 21 is similar to FIG. 20 and illustrates hidden features of FIG. 20.

FIG. 22 is a perspective view of the stapler head in a fully expanded, full compression position.

FIG. 23 is a plan view similar to FIG. 20 but showing the stapler head in the full compression position.

FIG. 24 is similar to FIG. 23 and illustrates hidden features of FIG. 24.

FIGS. 25A-25C are perspective views showing the staple housing, cartridge and a portion of the membrane raiser. These figures illustrate the steps of detaching a staple cartridge from the staple housing.

FIG. 26 is a perspective view of the stapler of FIG. 2, with the staple head removed.

FIG. 27A is a plan view of the articulating section of the stapler of FIG. 2, showing the drive fluid lines.

FIG. 27B shows a drive fluid line having an alternate longitudinally expandable shape.

FIG. 28 is a cross-sectional side view of the handle of the stapler of FIG. 2.

FIG. 29 is a perspective view of the handle of the stapler of FIG. 2.

FIGS. 30A and 30B are plan views of the proximal face of the staple housing, showing a method for attaching the end plate of the stapler handle to the staple housing.

FIGS. 31A-31E are a series of drawings schematically illustrating use of the system of FIG. 2 to form a plication in a stomach.

FIGS. 32A-32C are a series of perspective views illustrating use of the stapler of FIG. 2 to acquire, compress, and then staple stomach wall tissue to form a plication in the stomach. The membrane is not shown in these drawings.

FIG. 33 is a top plan view of a plication formed in body tissue.

FIGS. 34 and 35 are perspective views of an alternative stapler head equipped to carry additional tools.

DETAILED DESCRIPTION OF THE DRAWINGS

The present application describes endoscopic fastener-applying devices which in preferred embodiments may be passed transorally into the stomach and used to plicate stomach tissue.

In the disclosed embodiments, tissue is drawn inwardly into a vacuum chamber, although tissue may be drawn inwardly using other components (e.g. graspers) that do not involve the use of a vacuum. When a portion the interior stomach wall is drawn inwardly, sections of serosal tissue on the exterior of the stomach are positioned facing one another. The disclosed fastener applying device allows the opposed sections of tissue to be moved into contact with one another, and delivers fasteners that will hold the tissue sections together until at least such time as serosal bonds form between them. Each of these steps may be performed wholly from the inside of the stomach and thus can eliminate the need for any surgical or laparoscopic intervention. After one or more plications is formed, medical devices (including, but not limited to any of the types listed above) may be coupled to the plication(s) for retention within the stomach.

The disclosed embodiments include an optional feature that forms a hole or cut in a plication using the fastener-applying device. This hole or cut might be formed so that a portion of a medical implant may be passed through or linked to the hole/cut, or it may be formed so as to provoke a healing response that will contribute to the strength of the resulting tissue bond.

In the description of the embodiments given below, the fastener-applying devices are described as being staplers, and exemplary methods are given with respect to the formation of plications in stomach tissue. It should be understood, however, that the embodiments described herein include features having equal applicability for applying other types of fasteners, and for applying staples or other fasteners for purposes other than formation of plications. The disclosed embodiments and methods will also find use in parts of the body outside the GI system. Additionally, although the disclosed embodiment features circular stapling and cutting of a concentric hole, modifications are conceivable in which linear stapling can be accomplished, as well as circular or linear stapling without cutting.

FIG. 2 illustrates one embodiment of a system 10 for tissue stapling that is suitable for endoscopic use, as well as surgical or laparoscopic use if desired.

Generally speaking, system 10 includes a stapler 12 having a stapler head 14 positioned on a distal portion of a shaft 16. A handle 18 on the shaft 16 controls articulation of the stapler head 14 and actuation of the tissue acquisition, tissue compression, and stapling functions of the stapler head 14. Vacuum and fluid sources 20, 25 are fluidly coupled to the handle 18 for use in tissue acquisition, compression and stapling as discussed below. The vacuum source 20 may be the "house vacuum" accessible through a coupling on the wall of the operating room, or an auxiliary suction pump. The stapler may include a switch 21 allowing the user to control airflow between the vacuum source and stapler.

The fluid source 25 may be a single source of drive fluid (e.g. water, saline, oil, gas) or multiple sources, but in each case the fluid source preferably includes two actuators separately used to control flow into each of two hydraulic lines (one for tissue compression and one for stapling). An endoscope 22 insertable through a lumen in the shaft 16 permits visualization of the plication procedure. The system may optionally include an overtube, such an endoscopic guide tube 23, having a lumen for receiving the stapler 12.

Referring to FIG. 3A, a covering or membrane 24 encloses the stapler head 14 to form a vacuum chamber within the stapler head 14. The side exposed to the tissue to be plicated remains uncovered by the membrane 24 to allow tissue to be drawn into the chamber during use. For example, the membrane 24 may include a side opening 26 as shown in FIG. 3B.

Membrane **24** is preferably formed of silicone, elastomeric material, or any other inelastic or elastic flexible or deformable biocompatible material capable of forming a vacuum chamber that will expand in volume to accommodate tissue drawn into the chamber.

At least a portion of the membrane is at least partially transparent. In being at least partially transparent, the membrane is formed of a material, or includes sections of material, that will allow the user to see through the membrane well enough to confirm (via endoscopic observation) that an appropriate volume of tissue has been acquired into the stapler head prior to staple application. The opening **26** may be surrounded by a reinforced section **27** formed of material that will strengthen the area around the opening **26**. Reinforced section **27** may be formed of a thicker section of the membrane material, and/or a higher durometer material. Alternatively, reinforcing ribs or other structures or elements may be formed into or onto the membrane material, or embedded in the membrane material.

Stapler Head

The stapler head **14** is designed to have a minimum profile during insertion to the plication site, and to then transform into a much larger profile device having a large internal volume. For example, in one embodiment the vacuum chamber might have an initial internal volume of 0.2 cubic inches, and an expanded volume of 0.6 cubic inches (i.e. the internal chamber volume after subtracting the volume occupied by the stapler head components positioned within the vacuum chamber). This large internal volume allows a large volume of tissue to be drawn into the vacuum chamber and stapled. In this way, the stapler head creates a large plication without requiring invasive techniques for insertion. The unique features of the stapler head allow in situ volumetric expansion of the stapler head using a minimum of motion and force input.

Features of the stapler head are shown in FIGS. 4-10. For clarity, the membrane is not shown in these figures. Referring to FIG. 4, stapler head **14** generally includes a first member comprising a proximal staple housing **28**, a second member comprising a distal anvil housing **30**, and at least one elongate member but preferably a pair of hinged arm assemblies **32**.

The staple housing and anvil housing are arranged to allow tissue to be compressed between contact surfaces on each of the staple housing and the anvil housing. In the disclosed embodiment, the contact surfaces are on a staple holding portion of the staple housing and an anvil on the anvil housing.

The arm assemblies **32** extend between the staple housing **28** and anvil housing **30** on opposite sides of the stapler head **14**. Proximal and distal pins **34**, **36** pivotally couple each arm assembly **32** to the staple housing **28** and the anvil housing **30**. An expansion member comprising a membrane raiser **37** also extends between the staple housing **28** and the anvil housing **30**. Although the membrane **24** is not shown in FIG. 4, it should be understood that the membrane raiser **37** is positioned opposite the opening **26** (FIG. 3B) in the membrane. In the illustrated embodiment, membrane raiser **37** includes a link **38** pivotally mounted to the staple housing by a pin **42**, a corresponding link **40** pivotally mounted to the anvil housing by pin **44**, and spring wires **46** coupling the links **38**, **40** to one another.

Staple Housing

Turning to a more detailed discussion of the stapler head components, the staple housing **28** can be seen separated from other components in FIGS. 5 and 6. As shown in FIG. 5, proximal face **48** of the staple housing includes input ports **50a**, **50b** through which fluid is directed for hydraulic actuation of the tissue compression, stapling, and optional cutting

operations of the stapler head. Seals **51** surround the ports **50a**, **50b** to minimize fluid leakage.

Vacuum ports **52** are fluidly coupled to a vacuum source **20** (FIG. 2) that is selectively activated to create negative pressure in the vacuum chamber for tissue acquisition. The vacuum ports **52** are connected to the vacuum source **20** by flexible tubing (not shown) in the stapler shaft **16** (FIG. 2). Mounting holes **54** are used to mount the stapler head **14** to the shaft **16**.

The staple housing **28** includes upper and lower sections **58a**, **58b** above and below open side sections **56**. The upper section **58a** includes a recess **60** within which the pivot pin **42** for link **38** (FIG. 4) is mounted. As best shown in FIG. 6, bores **62** are positioned in the upper and lower sections **58a**, **58b** to receive pins **34** (FIG. 4) that serve as the proximal pivot points for arm assemblies **32**. Guide slots **64** extend longitudinally through the upper and lower sections **58a**, **58b**.

Referring to FIG. 6, a hydraulic chamber **66** is disposed within the staple housing **28**. Within the hydraulic chamber **66** (FIG. 6) is a dedicated hydraulic circuit for driving the tissue compression and stapling functions of the stapler. Chamber **66** is fluidly coupled to the fluid input ports **50a**, **50b** (FIG. 5). As will be discussed in detail in connection with FIGS. 11A-11D, fluid driven into the hydraulic chamber **66** via input ports **50a**, **50b** sequentially advances a system of hydraulic pistons (not shown) that act on other components to compress the tissue, and that drive the staples and cutting element through the compressed tissue.

FIG. 7 illustrates components of the stapler head that are driven by the hydraulic system for compression, stapling, and cutting. For clarity, these components are shown separated from the staple housing and from each other. In this discussion, the components that are driven by the hydraulic system will be described. The hydraulic system itself is described in a later section in connection with FIGS. 11A-11D.

In particular, FIG. 7 illustrates a drive member which takes the form of a disk **68** in the staple housing. In the assembled housing, disk **68** is positioned such that it will be pushed distally by a hydraulic compression piston (not shown). The drive member is coupled to the arm assemblies **32**, anvil housing, and staple housing so that advancing the drive member distally effects tissue compression by bringing the contact surfaces of the staple housing and anvil housing relatively towards one another.

Disk **68** includes mounting bores **70**, a central opening **72**, and alignment posts **74**. Referring briefly to FIG. 10, in the assembled stapler head, disk **68** is coupled to the stapler housing **28** using pins **84** that extend through the housing's guide slots **64** and through mounting bores **70** in the disk **68**.

A portion of the staple housing **28** contains staples to be fired into the tissue. The staples are contained within a staple holder on the staple housing. The staple holder may have a number of different configurations. For example, it may be an integral portion of the staple housing, or a separate part mounted or attached to the staple housing, and/or it may be moveable relative to the body of the staple housing to effect tissue compression prior to stapling. In any of these examples, the staple holder may be a removeable/replaceable cartridge, and/or it may be refillable by inserting additional staples into it. In other embodiments, the staple holder may be neither replaceable nor refillable.

In the disclosed embodiment, the staple holder is a removeable staple cartridge **78** that can be replaced with another cartridge after staple firing. In this embodiment, the staple cartridge is moveable relative to the body of the staple housing to compress the tissue prior to staple firing.

Referring again to FIG. 7, staple cartridge 78 is positionable within the staple housing, distal to the disk 68, such that distal advancement of the disk by the compression piston pushes the cartridge distally to compress tissue disposed between the cartridge and anvil. Grooves 79 on the exterior of the cartridge slide over corresponding ones of the alignment posts 74 during insertion of the cartridge into the stapler head. FIG. 10 shows the alignment posts prior to loading of a cartridge into the staple housing. As shown, the alignment posts 74 may have tapered ends to facilitate loading of the cartridge over the posts.

Again referring to FIG. 7, cartridge 78 includes a number of staple locations 80, each housing a staple. The staple cartridge is equipped with bosses 81 to retain a staple line reinforcement device 83 of the type shown in FIG. 8 and disclosed in detail in commonly-owned U.S. application Ser. No. 11/542,457, entitled ENDOSCOPIC PLICATION DEVICES AND METHODS, filed Oct. 3, 2006, and published Sep. 20, 2007 as US 2007-0219571. To summarize briefly, this type of reinforcement device 83 may be a ring or other element positionable against the distal face of the staple cartridge. When the ring is placed on the cartridge, openings 85 in the ring align with prongs of some of the staples in the cartridge. When staples are driven from the cartridge, these prongs pass through associated ones of the openings 85 and capture the ring 83 against the adjacent body tissue.

Referring to FIGS. 7 and 9, a number of undercut bosses 81 on the anvil-facing side of the cartridge may be used to lock the reinforcement device 83 in place on the face of the staple cartridge. Other positive shapes, such as mushrooms, hooks, and tilted bosses could be used to accomplish the same end. Negative shapes, such as pockets or grooves formed into the surface of the cartridge, may also be employed to engage corresponding features on the reinforcement device 83. As another alternative, the reinforcement device may be held in place on the cartridge using adhesives.

A cutter element 86 extends through the central opening 72 (FIG. 7) of the disk 68. The cutter element is shown as a tubular punch having a sharpened wall and a lumen 87, but may be provided in alternative forms. A staple pusher 76 is mounted to the cutter element, distally of the disk as can be seen in the assembled view of FIG. 10. Staple pusher 76 includes pusher elements 82 proportioned to slide into the cartridge's staple locations 80 as the staple pusher 76 is advanced into the staple cartridge 78, thus driving the staples from the cartridge. A hydraulically-driven staple piston (not shown in FIG. 7) in the hydraulic chamber 66 is coupled to the cutter element 86 such that advancement of the stapler piston advances the staple pusher 76 and cutter element 86 in a distal direction.

Fluid Drive System

The fluid drive system used to actuate compression, stapling and cutting may be configured in various ways. The following paragraphs describe one exemplary configuration for the fluid drive system, which in this embodiment is a hydraulic system. FIGS. 11A and 11B schematically show the fluid flow in the hydraulic chamber 66 of the staple housing 28 during both compression and stapling stages of actuation. Referring to FIG. 11A, compression piston 106 is disposed within hydraulic chamber 66. Disk 68 (also shown in FIGS. 7 and 10) is positioned in contact with or slightly distal to piston 106. Compression piston 106 is generally cup-shaped, having a rear wall 108 and a side wall 110 enclosing an interior 111. O-ring seals 112 are spaced-apart on a proximal portion of the side wall 110. Channels 114 are formed through the side wall 110, between the o-ring seals 112.

A second piston, referred to as the staple piston 116, is positioned in the interior 111 of compression piston 106, against the rear wall 108. Although not shown in FIGS. 11A-11D, cutting element 86 (FIG. 7), with the staple pusher 76 thereon, is positioned in contact with or slightly distal to the staple piston 116. An o-ring seal 118 surrounds a portion of the staple piston 116 that is distal to the channels 114 in the compression piston.

A first fluid channel 120 extends from fluid port 50a in the stapler housing 28 to a proximal section of the hydraulic chamber 66. A second fluid channel 122 extends from fluid port 50b in the stapler housing to a more distal section of the hydraulic chamber 66. Fluid flow from port 50a and fluid channel 120 against the compression piston cylinder is shown in FIG. 11A. Fluid pressure within the hydraulic chamber 66 advances the compression piston 106, with the stapler piston 116 within it, in a distal direction. FIG. 11B shows the compression piston 106 approaching the end of its travel. Once the compression piston reaches the end of its travel as shown in FIG. 11C, channel 114 in the compression piston 106 aligns with channel 122 in the housing, allowing fluid introduced through fluid port 50b to enter the interior of the compression piston 106 via channel 122. The fluid entering the interior of the compression piston drives the staple piston 116 distally as shown in FIG. 11D. In an alternative embodiment shown in FIG. 11E, a third piston 117 is provided for separately driving the cutting element 86. In this embodiment, fluid introduced into a third drive fluid port 50c causes advancement of the third piston 117. The pistons 106, 116 and 117 and associated fluid paths may be arranged so that fluid cannot enter the interior of the stapler piston to advance the cutting piston 117 until compression piston 106 has traveled to the tissue-compression position and stapler piston 116 has in turn traveled to the stapling position.

The anvil housing (identified by numeral 30 in FIG. 4) will next be described with reference to FIG. 12. The anvil housing 30 includes mounting bores 88 for receiving pivot pins 36 at the distal end of the hinged arm assemblies 32. The upper section of the anvil housing 30 includes a section 94 through which the pivot pin 44 for link 40 (FIG. 4) is mounted.

A central bore 90 extends longitudinally through the anvil housing 30. An anvil support 92 is longitudinally slidable within the bore. Both the bore 90 and the anvil support 92 are preferably formed to have non-circular cross-sections (such as the illustrated rectangular cross-section) with flat bearing surfaces to prevent rotation of the piston within the bore.

FIG. 13 shows the anvil support 92 separated from the anvil housing 30. The distal portion of the anvil support 92 is split into upper and lower plates 95a, b. Plate 95a has a bore 93 axially aligned with a similar bore in plate 95b. The proximal portion of the anvil support 92 carries the anvil 96. As shown in FIG. 14, anvil 96 includes a plurality of indentations 98 positioned such when staples are driven from the staple cartridge, each staple leg engages one of the indentations, which causes the staple leg to fold. A central opening 97 extends through the anvil 96 and is contiguous with a lumen in the anvil support 92.

The anvil 96 and the staple cartridge 78 (FIG. 7) are the two parts of the stapler head which exert force on the tissue to be stapled. As shown in FIGS. 9 and 14, the preferred anvil and cartridge are designed to use a minimal amount of material surrounding the indentations 98 of the anvil 96 and the staple locations 80 of the cartridge 78—so that the amount of anvil/cartridge surface area contacting the tissue is as small as possible. When subjected to a constant force, a smaller footprint will damage less tissue than would a larger footprint, since a smaller area of tissue is squeezed between the anvil

and cartridge. However, the tissue that does get squeezed experiences more pressure from the given force because the force is distributed over a smaller area. In other words, the minimized footprint creates more pressure on the tissue with less force. This is advantageous from a mechanical standpoint because the stapler head need not supply or withstand as much force as would be needed with a larger-footprint cartridge and anvil.

Referring to FIG. 7, in the illustrated embodiments, the staple cartridge 78 has an outer wall that tracks the contours of the staples housed within it, thus forming a number of pedals 73 surrounding the outer staple positions or slots 80a, with the grooves 79 disposed between the pedals, adjacent to the inner staple positions 80b. Rather than providing each staple position to be fully surrounded by cartridge material, the staple positions 80a, 80b preferably each include a back wall 71a and a retaining element attached to the wall and positioned to retain a staple between the retaining element and the back wall. In FIG. 7, the retaining element comprises a pair of wings 71b that curve inwardly from the back wall 71 to define a slot that is sufficiently bounded to retain a staple within the staple position, but that is preferably not bounded around its full circumference. The anvil has a similar pedal arrangement, as shown in FIG. 13.

Referring again to FIG. 13, a plate 99 is positioned on the anvil 96 such that the distally-advancing cutting element 86 will advance into contact with the plate 99 during tissue cutting. In one embodiment, the plate 99 may be seated within the opening 97 in the anvil. The plate 99, which will also be referred to as the "cutting board", has a hole 101 in it which relieves the pressure of the captured tissue and prevents hydraulic locking, a condition in which the punch and plate create a closed volume. If it is desired to move the cutting element 86 after contact is made, pressure will increase inside this closed volume and it will resist further motion. This may prevent or adversely affect tissue cutting.

The cutting board is preferably designed so as to not serve as a hard stop against advancement of the cutting element 86. If the cutting element 86 is stopped by the cutting board, the stapling piston will also be stopped and incomplete staple formation may result. Therefore, it is preferred that the cutting element 86 is allowed to penetrate or displace the cutting board during and after the tissue is cut.

FIGS. 15A and 15B illustrate the cutting element 86 advanced into contact with two different embodiments of cutting boards. In the FIG. 15A embodiment, the material of cutting board 99a is a relatively soft material, such as an elastomeric silicone, which is cut by the advancing cutting element as shown. This material allows the sharp distal end of the cutting element to move into the cutting board during the final stage of staple formation. In the FIG. 15B embodiment, the cutting board 99b can be made of a harder material positioned with a compressible object such as an elastomeric spring 99c behind it. In the figure, this spring is an o-ring. Advancement of the cutting element 86 against the cutting board 99b causes the cutting board to be displaced distally against the spring 99c. The advancing cutting element 86 experiences increasing resistance as the o-ring is compressed. Other spring shapes and materials, such as coiled wire, spring washers and leaf springs can be used to achieve the same result. The chamfer 99d on the surface of the cutting board 99b may help to align the cutting element 86 as it is forced into contact with the cutting board.

Arm Assemblies

Following is a discussion of the features of the arm assemblies 32. FIG. 16 shows the arm assemblies 32 separated from the other elements of the stapler head. In general, each arm

assembly has a first arm section pivotally coupled to the staple housing and a second arm section pivotally coupled between the first arm section and the anvil housing. While not present in the illustrated embodiment, additional arm sections may be positioned between the first and second arm sections.

Each arm assembly includes a proximal arm 100 and a distal arm 102 joined to one another to form a hinge 104. Each of the proximal arms 100 has a longitudinal cutout 108 and a spreader arm 110 pivotally mounted within the cutout 108. The distal end of each spreader arm 110 includes a bore 112. Pin 84 is positioned within the bore 112. As disclosed in connection with FIG. 10, this pin 84 extends through the disk 68 and has ends that ride within the slots 64 (FIG. 6) on the lower and upper sections of the stapler housing. Longitudinal movement of the disk 68 within the stapler housing will thus advance the pins 84 within their corresponding slots 64, causing the spreader arms 110 to pivot relative to the pins 84 and to thus drive the arm assemblies 32 outwardly. Additional specifics concerning movement of the arm assemblies 32 is set forth in the section entitled Stapler Head Operation.

Distal arms 102 of the arm assemblies include pins 36 which, as discussed, are pivotally mounted to the anvil housing 30 (FIG. 4). A pair of drive links 114 are provided, each of which has a first end pivotally attached to a corresponding one of the distal arms 102 and a second end pivotally coupled to a common pin 116. In the assembled stapler head, pin 116 is positioned in the bores 93 of the upper and lower plates 95a, 95b of the anvil support (see plates 95a, b in FIG. 12). As detailed in the Stapler Head Operation section below, when the spreader arms 110 drove the arm assemblies 32 outwardly, drive links 114 act on the pin 116 to push the anvil support in a proximal direction, causing the anvil to advance proximally towards the staple cartridge.

Stapler Head Operation

The following discussion centers on the manner in which the arm assemblies function to expand the vacuum chamber and to compress tissue that has been drawn into the chamber using suction. As an initial step preceding chamber expansion, the stapler head is positioned with the opening 26 in the membrane 24 in contact with tissue at the location at which plication creation is desired. Vacuum source 20 (FIG. 2) is activated to apply vacuum to the inside of the vacuum chamber defined by the membrane. Tissue in contact with the opening 26 (FIG. 3B) will be drawn into the vacuum chamber between the staple housing 28 and the anvil housing 30. After the tissue is drawn in, the stapler profile is changed, expanding the volume of the chamber within the membrane.

The streamlined position of the stapler head 28 prior to expansion is shown in FIGS. 4, 17 and 18. In particular, the hinged arm assemblies 32 and membrane raisers 37 are in generally straight orientations. The proximal arms 100 serve as the drive arms for chamber expansion and tissue compression. Motion of these arms is initiated when water under pressure is forced into the hydraulic circuit of the staple housing. Referring to FIG. 19, the fluid pressure advances disk 68 (by action of the compression piston 106, not shown in FIG. 19). Disk 68 in turn pushes the staple cartridge 78 toward the anvil 96 as shown in FIGS. 19-21, causing the staple cartridge 78 to extend further from the staple housing 28.

Both the disk 68 and the arm spreaders 110 are coupled to the pins 84. For this reason, the longitudinal movement of the disk 68 within the stapler housing 28 will carry the pins 84 distally within their corresponding slots 64. The arm spreaders 110 will consequently pivot relative to the pins 84, driving the proximal arms 100 outwardly. Outward movement of proximal arms 100 at hinge 104 causes the distal arms 102 to

also pivot outwardly at hinge **104**, forming an angle between the proximal and distal arms **100, 102**. Naturally, formation of the angle between the arms **100, 102** shortens the effective length between the remote ends of the arms, causing the distal pins **36** of the distal arms **102** to carry the anvil housing **30** towards the staple cartridge. The pivoting movement of the distal arms **102** further causes drive links **114** to act on pin **116** to push the anvil support in a proximal direction. This moves the anvil support relative to the anvil housing in a proximal direction at the same time the anvil housing is also moving proximally.

In essence, one motion, that of the hydraulically driven compression piston, creates at least three motions, illustrated by arrows **A1, A2** and **A3** in FIGS. **19-21**. These three motions include: the staple cartridge **78** moving relative to the staple housing in a direction towards the anvil **96** (arrow **A1**), the anvil housing **30** moving toward the staple housing **28** (arrow **A2**) and the anvil **96** itself moving relative to the anvil housing **30** in a direction towards the cartridge (arrow **A3**). This compound motion of the anvil toward the staple cartridge enables a small displacement of the compression piston to quickly compress tissue in the grip of stapler. The multiplication of motion also enhances force transmission between the two housings by keeping the angle at hinge **104**, between the proximal (driven) arm and the distal (drive) arm, as large as possible.

The relative motion of the two housings **28, 30** toward each other also drives upward links **38, 40** and their interconnecting spring wires **46** on the top of the stapler head **14**. Together, the links and spring wires raise the top of the membrane, creating more volume to accommodate expansion of the tissue during compression.

Compression of the tissue is halted when the pins **84** traveling in slots **64** in the staple housing **28** reach the limit of travel, as shown in FIGS. **22-24**. Thus, the slots and associated components are dimensioned to set the desired separation distance between the tissue contact surfaces on the stapler side and the anvil side of the stapler head. Exemplary separation distances for use in stomach wall plications might include approximately 0.06-0.07 inches (e.g. for use with staples having legs of 5.5 mm length) or 0.109 inches for 6.5 mm leg length staples. Application of additional pressure into the hydraulic circuit will not compress the tissue any further.

Moreover, because of the piston arrangement, the stapling function is effectively locked out until tissue compression is complete. With this arrangement, fluid introduced via the fluid port **50b** (FIG. **11A**) into the staple fluid channel **122** prior to completion of tissue compression will leak until the two o-rings **112** of the compression piston **106** are straddling the inlet **114**. This design prevents premature staple firing.

At the fully compressed position, the arm spreaders **110** are nearly perpendicular to the longitudinal centerline of the stapler head. Once tissue is compressed between cartridge **78** and anvil **96**, the tissue is ready for stapling.

Stapling is initiated by introducing hydraulic fluid through port **50b** (FIG. **5**). The staple piston advances, pushing cutting element **86** (FIGS. **7** and **10**) towards the anvil **96**. Because the staple pusher **76** is mounted to the cutter **86**, this action carries the staple pusher **76** through the cartridge **78** where it simultaneously pushes all staples through the tissue. Staple piston travel is limited by internal stops, and is preset to yield optimal staple formation.

During compression, as the angle at the hinge **104** of arm assemblies **32** reaches its minimum, the force required to resist separation of the staple and anvil housings increases. These forces increase further when the forces of staple crushing are exerted on the anvil by the staple piston. To compen-

sate, the arm spreaders **110** serve as displacement struts to channel at least a portion of these forces into the disk **68**. These forces, if not reacted by the pusher disk, would pull in the arms **100, 102** and potentially release the compression on the tissue, causing incomplete staple formation or tissue cutting. In this way, a truss-like structure is created for force displacement.

When staples have been formed, staple pressure is released and a spring (not shown) returns the staple pusher **72** to its base position. Releasing fluid pressure will allow the deflected spring wires **46** on membrane raiser **37** to return the staple head to its minimum profile configuration and release the plication from the stapler. Once outside the patient, the used staple cartridge can be ejected and a new one installed.

FIGS. **25A-25C** illustrate one method for retaining a removable staple cartridge **78** within the staple housing. The cartridge is spring-loaded into the staple housing and retained by two latches **170** (one visible), each pivotable relative to a fulcrum **172**. As shown, the fulcrum **172** may be coupled to the disk **68** by pin **84**. Each latch **170** includes a catch **174** which engages a corresponding catch **176** on the cartridge. The latch **170** is preferably spring biased to urge the catch **174** inwardly towards the cartridge.

Depressing the proximal end **175** of each latch **170** as shown by arrow **P** in FIG. **25B** pivots the latch against this bias, causing ejection of the staple cartridge. A new staple cartridge may then be positioned with its grooves **79** aligned with alignment posts **74** as shown in FIG. **25C** and then pushed towards the staple housing. As the new cartridge slides into position, catch **174** rides over the tapered proximal portion **178** of the catch **176**. Once catch **174** passes over the distal end **180** of the catch **176**, it drops inwardly towards the cartridge due to its spring bias, thus engaging the cartridge. When the cartridge is properly seated, a click will be felt or heard as the latches engage the new cartridge.

Stapler Shaft and Handle

Referring again to FIG. **2**, the stapler shaft **16** connecting the handle **18** and the stapler head **14** is flexible enough to conform to the curvature of the upper digestive tract, yet maintains the ability to transmit enough torque to rotate the stapler head. The shaft is formed with sufficient stiffness to allow it to be pushed down esophageal guide tube **23**. Suitable materials include

FIG. **26** shows a distal portion of the shaft **16**, with the stapler head removed from the shaft. As shown, shaft **16** includes an endoscope lumen **124** through which an endoscope is advanced to allow visualization of a stapling operation. Side lumens **126** may also be provided for receiving other instruments useful during the procedure.

An articulating section **128** is positioned at the distal end of the shaft **16**, between the shaft **16** and the stapler head **14** so as to allow the stapler head to be articulated relative to the shaft. Tubing coupled to the vacuum source and the source of hydraulic fluid extends from the handle and through the shaft **16** and the articulating section **128**.

FIG. **27A** shows one configuration that may be used for the hydraulic fluid lines **130**. During use, the hydraulic fluid lines are subjected to significant deflection and elongation in the articulating section of the stapler. They are also subjected at times to fluid pressure which may be in excess of 1000 psi. Typically, hydraulic lines in industrial applications are flexible and have a working loop of extra tubing that accommodates length changes during use. The illustrated configuration for the hydraulic lines is a lower profile solution particularly suitable for an endoscopic device having space constraints. A preferred hydraulic line is a tube **130** having a portion that is shaped into a longitudinally expandable shape so that it can

accommodate effective length changes during bending. The longitudinally expandable portion of the tube is preferably disposed within the articulating section **128** of the stapler **12**. In a preferred design, the longitudinally expandable shape is a coil shape as shown in FIG. **27A**. In alternate embodiments, the tube **130** may be formed into other longitudinally expandable shapes, such as regular or irregular undulating shapes (FIG. **27B**).

The preferred material for the tubes **130** is stainless steel hypotube, although other materials may instead be used. In the preferred stapler configuration, two drive fluid lines are provided, one for actuating tissue compression, and the other for staple application (and cutting when used). In the present embodiment, the tubes are coiled together as shown in FIG. **27A**. In alternate embodiments, two or more coiled tubes may be nested one inside the other. As the articulating section bends, it forces the coiled tubes **130** to bend and to change length in response to bending. The coiled tubes behave just as coiled wires would during these motions and are thus able to change length, deflect, and follow the contour of the articulating section without compromising flow through the lumens of the tubes or imparting undue stress to the connections at either end of the hydraulic system.

The longitudinally expandable shapes for the fluid lines may be suitable for use in allowing delivery of fluid to the operative ends of other types of articulating medical devices, such as catheters or endoscopic devices for delivering therapeutic agents or irrigation fluids past an articulating or bendable section of the device.

Referring again to FIG. **26**, articulating section **128** is comprised of a spine formed of a plurality of links **132** strung over a pair of pull cables **134** (only one shown in FIG. **26**). In one embodiment, engagement of the pull cables allows the stapler head **14** to be articulated in two directions through a range of motion of approximately 90 degrees in one direction (see FIG. **3B**) to 175 degrees in the opposite direction (see FIG. **3C**). Each pull cable is anchored at or near the stapler head, such as at the distalmost link **132** of the stapler housing **28**.

The more proximal portions of the pull cables **134** extend the length of the shaft **16** and terminate in the handle **18**. Referring to FIG. **28**, the handle **18** includes a rotating knob **136** that may be selectively rotated in a clockwise or counterclockwise to articulate the stapler head up or down. Rotation in one direction applies tension to one of the pull cables to cause the stapler head to bend downwardly, whereas rotation in the opposite direction puts tension on the other cable, causing the head to bend upwardly.

In a preferred handle configuration, the knob **136** includes an internal threaded bore **138**. Knob **136** is partially restrained within the handle **18** so that it remains fixed within the handle but can rotate freely. A carriage **140** having a threaded exterior surface is positioned within the threaded bore **128** of the knob. The threads within the bore **138** are engaged with the threads on the carriage **140** so that rotation of the knob causes the carriage **140** to translate, but not rotate, within the handle.

Each of the two pull cables, identified in FIG. **28** as cables **134a** and **134b**, is terminated on a different member in the handle. Cable **134a** is mounted on the sliding carriage and cable **134b** is mounted to a stationary part of the handle **18**. Each cable extends through a corresponding sheath. Cable **134a** extends through a sheath **135a** having a proximal end fixed to a stationary part of the handle **18**. Cable **134b** extends through a sheath **135b** having a proximal end mounted to the sliding carriage.

The cables **134a,b** and sheaths **135a,b** are arranged such that translation of the carriage in one direction will cause

deflection of the stapler head in one direction, and translation of the carriage on the other direction will deflect the stapler head in another direction.

Referring to FIG. **28**, if knob **136** is rotated to causes the carriage **140** to translate to the left of the page, cable **134a** will be tensioned and cable **134b** will slacken, causing the stapler head to articulate in a first direction (e.g. upwardly). Rotation of the knob **136** in the opposite direction will advance the carriage to the right of the page, releasing tension on cable **134a** and pushing sheath **135b** over the cable **134b** towards the distal end of the staple head, causing articulation in the second direction (e.g. downwardly) as the sheath **135b** is advanced against a distal portion of the shaft **16**. The proximal portion of sheath **135b** is provided with sufficient working length prevent it from being placed under tension when the carriage moves distally. The positioning of the knob is advantageous in that the hand movement required for stapler articulation is always the same, regardless of the rotational orientation of the stapler. Also, the use of the threaded knob can prevent unintentional relaxation of the deflection angle, even if the knob is provided without a lock to retain its rotational position.

Referring to FIGS. **28** and **29**, the endoscope lumen **124** extends along the center axis of the stapler. The positioning of the lumen and the coaxial relationship of the articulation knob in relative to the endoscope **124** allows the endoscope and stapler to be rotated independently without one interfering with one another. Thus, if the user chooses to change the rotational orientation of the stapler head **14** within the body, s/he may rotate the handle **18** and shaft **16** while maintaining the rotational position of the endoscope.

For cost efficiency, the stapler **12** may be designed to permit the stapler head **14** to be discarded while allowing the shaft **16** and handle **18** to be sterilized and re-used. One mechanism for removably coupling the stapler head to the shaft **16** is illustrated, although others are readily conceivable (e.g. a slip coupling type arrangement). Referring to FIG. **26**, an end plate **142** is mounted to the distalmost one of the links **132**. Each of the end plate **142** and the corresponding rear surface of the stapler head are provided with latch features that allow the end plate and stapler head to be engaged to one another.

End plate **142** includes a cantilevered pin **144** having a peg **145** (which may be a spring pin), a central opening **146**, and a pair of u-shaped catches **148** along its edges. Hydraulic feed holes **156a, b** are formed through the end plate **142**. The hydraulic tubes that deliver hydraulic fluid to the stapler head (see tubes **130** of FIG. **27**) are preferably welded to the end plate to allow fluid from the tubes to be directed through the feed holes **156a, b**.

FIGS. **30A** and **30B** show the rear surface **48a** of the staple housing, which has been somewhat modified relative to FIG. **5**. In this variation of the rear surface **48a**, the hydraulic input ports **50a, 50b** are repositioned as shown. Additionally, the rear surface **48a** has been modified to include a pair of catches in the form of undercut bosses **150**, plus an aligning pin **152**, and a hole **154**.

FIGS. **30A** and **30B** show the end plate **142** positioned against the rear surface **48a** of the staple housing. The other features of the articulating section **128** are not shown in FIGS. **30A** and **30B** for clarity. To attach the stapler head to the shaft **16**, the plate **142**, attached to the handle assembly, is pressed against the rear surface **48a** of the staple housing as shown in FIG. **30A**. As the plate is pushed, it is rotated in a clockwise direction, causing the peg **145** (FIG. **26**) of the cantilevered pin **144** to engage hole **154** in the rear surface of the staple housing. When this latch is engaged, hydraulic feed holes

15

156a, b of the end plate 142 are lined up with the hydraulic inlets 50a, 50b on the staple head as shown in FIG. 30B. At the same time, portions of the end plate surrounding u-shaped catches 148 slide beneath the undercut bosses 152. Pressing the plate compresses the face-sealing o-rings surrounding the hydraulic input ports 50a, 50b. Compression on the o-rings is maintained by engagement of the catches and the undercut bosses overhanging the end plate. To remove the stapler head from the housing, the stapler housing is twisted in a counter-clockwise direction to disengage the end plate 142 from the rear surface 48a. The stapler shaft and handle may then be sterilized in preparation for mounting of a fresh stapler head.

Exemplary Procedure

One example of a method for using the system 10 will next be described in the context of formation of plications in stomach wall tissue.

As an initial step (FIG. 2), endoscopic guide tube 23 is advanced into the stomach via the mouth and esophagus. The endoscope 22 is inserted into the endoscope channel in the stapler handle (not shown) and advanced down the lumen of the stapler handle. The stapler/endoscope are simultaneously passed through the endoscopic guide tube towards the stomach. Once the stapler and endoscope reach the gastroesophageal junction region of the stomach, the position of the stapler is maintained while the endoscope is advanced further into the stomach.

The stapler head 14 is advanced to the desired depth and location in the stomach. Using the articulation controls on the stapler handle, the angular orientation of the stapler head is adjusted to allow positioning of the stapler head 12 at the pre-identified target tissue as shown in FIG. 31A. The opening 26 in the membrane 24 is positioned against the target tissue. The endoscope 22 is placed in a retroflexed position as shown.

The vacuum source 20 (FIG. 2) is coupled to the vacuum port on the handle external to the body, and vacuum pressure is applied to draw tissue through the opening 26 and into the vacuum chamber defined by membrane 24 as shown in FIGS. 31B and 32A. Acquisition of the target tissue will be readily identified endoscopically through the wall of transparent membrane 24 on the stapler head.

The fluid source (is shown) is coupled to the handle. Once it has been visually confirmed that a sufficient amount of tissue has been acquired, fluid is introduced to cause compression of the tissue and expansion of the arm assemblies 32 and membrane raiser 37 as shown in FIGS. 32B and 31C. As can be seen, the expansion of the arm assemblies and the membrane allows a large volume of tissue to be acquired into the vacuum chamber and displaced further into the chamber during tissue compression.

Once the tissue has been compressed, additional hydraulic fluid is introduced to cause stapling and cutting of the tissue as shown in FIGS. 31D and 32C, forming a plication P. The compression and stapling hydraulic sources are then deactivated to release fluid pressure within the hydraulic circuit. With the hydraulic pressure relieved, the spring wires of the membrane raiser 37 help to restore the stapler head 14 to its original streamlined configuration, allowing the stapler head to be withdrawn from the tissue as shown in FIG. 31E. The stapler head may be articulated relative to the shaft to assist in moving the stapler head away from the plication P.

In a preferred plication configuration shown in FIG. 33 the staples 158 are arranged in two concentric rings of five staples, with the staple reinforcement device 83 retained by the staples and distributing forces around the staple pattern as shown. The plication P includes a hole H formed by the

16

cutting element, through which various implants or anchors for various implants can be placed.

If multiple plications are needed, the stapler 12 is briefly withdrawn from the endoscopic guide tube and the staple cartridge is replaced in the manner described in connection with FIGS. 25A-25C. The procedure is repeated until all desired plications have been formed.

The system may be packaged with instructions for use instructing the user to use the various disclosed features to perform a stapling procedure using methods disclosed herein.

Alternate Embodiments

The basic architecture of the stapler disclosed above can be used as a foundation for other stapling tools. FIGS. 34-35 show a modified stapler in which the membrane and membrane raiser have been removed, and in which the staple housing 28 has been modified for the attachment of tools. As shown in FIG. 34, the staple housing 28 includes a pair of grooves 160 proportioned to receive tools 162. Tools 162 may be seated in these grooves 160 and mounted to the staple housing as shown in FIG. 35. This attachment will provide for a stable base from which to actuate the tools. The tools may be self-articulating, or the staple housing 28 may be equipped with devices 164 for moving the tools between streamlined positions for insertion of the assembly into a body cavity, and a deployed position such as that shown in FIG. 35. Tools similar to those in FIG. 35 might be used for tissue acquisition, by reaching between the cartridge and anvil and used to engage tissue and pull the tissue into position between the cartridge and anvil so that it may be stapled, or otherwise affected by various features added to or in place of the anvil and cartridge. Procedures which may benefit from adaptation of the stapler include, but are not limited to gastroplasty, stoma adjustment, polypectomy, lead placement, bleeding control, perforation or hole closure, biopsy and tumor removal.

The disclosed systems provide convenient embodiments for carrying out the disclosed compression and stapling functions. However, there are many other widely varying instruments or systems may alternatively be used within the scope of the present invention. Moreover, features of the disclosed embodiments may be combined with one another and with other features in varying ways to produce additional embodiments. Thus, the embodiments described herein should be treated as representative examples of systems useful for forming endoscopic tissue plications, and should not be used to limit the scope of the claimed invention.

Any and all patents, patent applications and printed publications referred to above, including those relied upon for purposes of priority, are incorporated herein by reference.

We claim:

1. A medical instrument for forming a tissue fold, comprising:
 - a head including:
 - a covering defining a vacuum chamber, the covering having an opening positionable in contact with tissue to be fastened such that application of suction to the vacuum chamber draws the tissue into the vacuum chamber;
 - first and second members at least partially disposed within the vacuum chamber, the first and second members being moveable relative to one another along an axis toward a compression position to compress tissue drawn into the vacuum chamber between the two members;
 - a driver operable to move the two members toward their compression position; and

17

structure coupling the first member and the second members, operable to extend outwardly away from said axis as the two members are moved toward their compression position, thereby to expand the chamber in the region between the two members and increase the area of a tissue fold that can be drawn into the chamber as the two members are moved toward their compression position.

2. The medical instrument of claim 1, wherein the coupling structure includes an arm assembly having a first section pivotally coupled to the first member and a second section pivotally coupling the arm assembly's first section to the second member, and said first and second sections are designed to pivot outwardly as the two members are moved toward their compression position.

3. The medical instrument of claim 2, wherein the coupling structure includes a pair of said arm assemblies coupling the two members on opposite side regions of the two members.

4. The medical instrument of claim 2, which further includes an expansion member coupled to the first and second members such that movement of the first and second members toward their compression position moves the expansion member outwardly away from said axis.

5. The medical instrument of claim 4, wherein said expansion member includes a spring member having a natural bias tending to move the expansion member toward said axis.

6. The medical instrument according to claim 1, for use in stapling a tissue fold captured between the two members, wherein the first member includes a staple housing carrying at least one staple, the second member includes an anvil, and said driver is operable to eject a staple from the staple housing, through a tissue fold, and against said anvil, when the two members are moved to their compression position.

18

7. The medical instrument of claim 1, for use in stapling a tissue fold captured between the two members, wherein the first member includes a staple housing that is movable within the first member and that carries at least one staple, the second member includes an anvil carried within the second member, said driver is operable to move said staple housing within the first member from a retracted toward and extended position, and said coupling structure includes an arm assembly operatively coupling the staple housing in the first member to the second member, such that movement of the drive member from its retracted to its extended position is effective to (i) move the staple housing within the first member toward the anvil and (ii) move the second member toward the first member.

8. The medical instrument of claim 7, wherein said anvil is movable within second member, and the second member includes drive links operatively connected to the arm assembly for moving the anvil toward the first member, independent of movement of the second member toward the first member, when the drive member is moved from its retracted to extended position.

9. The medical instrument of claim 7, wherein the drive member includes a disc that travels within the first member, and carries a pin that moves within a slot in the first member, thereby limiting the extent of travel of the drive member toward its extended position to the extent of travel allowed for the pin within the slot.

10. The medical instrument of claim 9, further comprising at least one arm spreader pivotally connecting the disc to the arm assembly for spreading the arm assembly outwardly as the disc travels from its retracted to its extended position.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,922,062 B2
APPLICATION NO. : 12/053010
DATED : April 12, 2011
INVENTOR(S) : David Cole and Andrew Smith

Page 1 of 1


It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Claim 2, column 17, line 9, "structure includes and arm assembly having a first section" should be changed to --structure includes an arm assembly having a first section--.

Claim 7, column 18, line 7, "first member from a retracted toward and extended position," should be changed to --first member from a retracted position toward an extended position,--.

Claim 8, column 18, line 16, "movable within second member, and the second member" should be changed to --movable within the second member, and the second member--.

Signed and Sealed this
Sixteenth Day of August, 2011

A handwritten signature in black ink that reads "David J. Kappos". The signature is written in a cursive, flowing style with a large initial 'D' and 'K'.

David J. Kappos
Director of the United States Patent and Trademark Office

专利名称(译)	内窥镜缝合装置和方法		
公开(公告)号	US7922062	公开(公告)日	2011-04-12
申请号	US12/053010	申请日	2008-03-21
[标]申请(专利权)人(译)	COLE DAVID ANDREW SMITH		
申请(专利权)人(译)	COLE DAVID ANDREW SMITH		
当前申请(专利权)人(译)	BOSTON SCIENTIFIC SCIMED , INC.		
[标]发明人	COLE DAVID SMITH ANDREW		
发明人	COLE, DAVID SMITH, ANDREW		
IPC分类号	A61B17/068		
CPC分类号	A61B17/072 A61B17/115 A61F5/0083 A61B2017/00818 A61B2017/306 A61B2017/07271 A61B17/32053 A61B17/064 A61B2017/00539 A61F5/0013		
其他公开文献	US20090236389A1		
外部链接	USPTO		

摘要(译)

本文描述了用于将一个或多个紧固件施加到身体组织的内窥镜缝合器。在一个实施例中，紧固件施加装置（优选地是订书机）经口部通入胃中并用于通过从胃内部接合组织并将其向内拉入而使胃组织复位。在所公开的实施例中，组织被向内抽入真空室，使得胃外部上的浆膜组织的部分彼此面对地定位。所公开的订书机允许组织的相对部分移动成彼此接触，并且优选地递送钉以维持组织部分之间的接触，至少直到在它们之间形成浆膜结合。这些步骤中的每一个可以完全从胃内部进行，因此可以消除对任何手术或腹腔镜介入的需要。在形成一个或多个褶皱之后，可任选地将医疗装置连接到褶皱以保留在胃内。

