



US009659345B2

(12) **United States Patent**
Razzaque et al.

(10) **Patent No.:** **US 9,659,345 B2**
(45) **Date of Patent:** ***May 23, 2017**

(54) **SYSTEM AND METHOD OF PROVIDING REAL-TIME DYNAMIC IMAGERY OF A MEDICAL PROCEDURE SITE USING MULTIPLE MODALITIES**

(71) Applicant: **INNEROPTIC TECHNOLOGY, INC.**, Hillsborough, NC (US)

(72) Inventors: **Sharif A Razzaque**, Chapel Hill, NC (US); **Kurtis P Keller**, Hillsborough, NC (US); **Andrei State**, Chapel Hill, NC (US); **Caroline K Green**, Chapel Hill, NC (US); **Jeremy D Ackerman**, Port Jefferson Station, NY (US)

(73) Assignee: **InnerOptic Technology, Inc.**, Hillsborough, NC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 732 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/936,951**

(22) Filed: **Jul. 8, 2013**

(65) **Prior Publication Data**

US 2014/0016848 A1 Jan. 16, 2014

Related U.S. Application Data

(63) Continuation of application No. 12/760,274, filed on Apr. 14, 2010, now Pat. No. 8,482,606, which is a (Continued)

(51) **Int. Cl.**
H04N 7/18 (2006.01)
G06T 3/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **G06T 3/0087** (2013.01); **A61B 1/0005** (2013.01); **A61B 1/042** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC A61B 1/0005; A61B 1/042; A61B 1/313; A61B 8/12; A61B 8/463; A61B 8/5238; G06T 3/0087; H04N 7/181
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,556,079 A 1/1971 Omizo
4,058,114 A 11/1977 Soldner
(Continued)

FOREIGN PATENT DOCUMENTS

AU 7656896 A 5/1997
AU 9453898 A 4/1999
(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 11/828,826, filed Jul. 26, 2007, Keller et al.
(Continued)


Primary Examiner — Nhon Diep

(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson & Bear, LLP

(57) **ABSTRACT**

A system and method of providing composite real-time dynamic imagery of a medical procedure site from multiple modalities which continuously and immediately depicts the current state and condition of the medical procedure site synchronously with respect to each modality and without undue latency is disclosed. The composite real-time dynamic imagery may be provided by spatially registering multiple real-time dynamic video streams from the multiple modalities to each other. Spatially registering the multiple real-time dynamic video streams to each other may provide a continuous and immediate depiction of the medical procedure site with an unobstructed and detailed view of a region of interest at the medical procedure site at multiple depths. As such, a surgeon, or other medical practitioner, may view a single, accurate, and current composite real-time

(Continued)



dynamic imagery of a region of interest at the medical procedure site as he/she performs a medical procedure, and thereby, may properly and effectively implement the medical procedure.

17 Claims, 8 Drawing Sheets

Related U.S. Application Data

continuation of application No. 11/833,134, filed on Aug. 2, 2007, now Pat. No. 7,728,868.

- (60) Provisional application No. 60/834,932, filed on Aug. 2, 2006, provisional application No. 60/856,670, filed on Nov. 6, 2006.

(51) **Int. Cl.**

A61B 1/00 (2006.01)

A61B 1/04 (2006.01)

A61B 8/12 (2006.01)

A61B 8/00 (2006.01)

A61B 8/08 (2006.01)

A61B 1/313 (2006.01)

(52) **U.S. Cl.**

CPC *A61B 8/12* (2013.01); *A61B 8/463* (2013.01); *A61B 8/5238* (2013.01); *H04N 7/181* (2013.01); *A61B 1/313* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

RE30,397 E	9/1980	King	5,446,798 A	8/1995	Morita et al.
4,249,539 A	2/1981	Vilkomerson et al.	5,447,154 A	9/1995	Cinquin et al.
4,294,544 A	10/1981	Altschuler et al.	5,452,024 A	9/1995	Sampsel
4,390,025 A	6/1983	Takemura et al.	5,457,493 A	10/1995	Leddy et al.
4,407,294 A	10/1983	Vilkomerson	5,474,073 A	12/1995	Schwartz et al.
4,431,006 A	2/1984	Trimmer et al.	5,476,096 A	12/1995	Olstad et al.
4,567,896 A	2/1986	Barnea et al.	5,483,961 A	1/1996	Kelly et al.
4,583,538 A	4/1986	Onik et al.	5,488,431 A	1/1996	Gove et al.
4,620,546 A	11/1986	Aida et al.	5,489,952 A	2/1996	Gove et al.
4,671,292 A	6/1987	Matzuk	5,491,510 A	2/1996	Gove
4,839,836 A	6/1989	Fonsalas	5,494,039 A	2/1996	Onik et al.
4,862,873 A	9/1989	Yajima et al.	5,503,152 A	4/1996	Oakley et al.
4,884,219 A	11/1989	Waldren	5,505,204 A	4/1996	Picot et al.
4,899,756 A	2/1990	Sonek	5,515,856 A	5/1996	Olstad et al.
4,911,173 A	3/1990	Terwilliger	5,517,990 A	5/1996	Kalfas et al.
4,945,305 A	7/1990	Blood	5,526,051 A	6/1996	Gove et al.
5,076,279 A	12/1991	Arenson et al.	5,526,812 A	6/1996	Dumoulin et al.
5,078,140 A	1/1992	Kwoh	5,529,070 A	6/1996	Augustine et al.
5,078,142 A	1/1992	Siczek et al.	5,531,227 A	7/1996	Schneider
5,095,910 A	3/1992	Powers	5,532,997 A	7/1996	Pauli
5,109,276 A	4/1992	Nudelman et al.	5,541,723 A	7/1996	Tanaka
5,158,088 A	10/1992	Nelson et al.	5,558,091 A	9/1996	Acker et al.
5,161,536 A	11/1992	Vikomerson et al.	5,568,811 A	10/1996	Olstad
5,193,120 A	3/1993	Gamache et al.	5,570,135 A	10/1996	Gove et al.
5,209,235 A	5/1993	Brisken et al.	5,579,026 A	11/1996	Tabata
5,249,581 A	10/1993	Horbal et al.	5,581,271 A	12/1996	Kraemer
5,251,127 A	10/1993	Raab	5,588,948 A	12/1996	Takahashi et al.
5,261,404 A	11/1993	Mick et al.	5,608,468 A	3/1997	Gove et al.
5,265,610 A	11/1993	Darrow et al.	5,608,849 A	3/1997	King, Jr.
5,271,400 A	12/1993	Dumoulin et al.	5,611,345 A	3/1997	Hibbeln
5,307,153 A	4/1994	Maruyama et al.	5,611,353 A	3/1997	Dance et al.
5,309,913 A	5/1994	Kormos et al.	5,612,753 A	3/1997	Poradish et al.
5,323,002 A	6/1994	Sampsel et al.	5,625,408 A	4/1997	Matsugu et al.
5,371,543 A	12/1994	Anderson	5,628,327 A	5/1997	Unger et al.
5,383,454 A	1/1995	Bucholz	5,629,794 A	5/1997	Magel et al.
5,394,875 A	3/1995	Lewis et al.	5,630,027 A	5/1997	Venkateswar et al.
5,411,026 A	5/1995	Carol	5,647,361 A	7/1997	Damadian
5,433,198 A	7/1995	Desai	5,647,373 A	7/1997	Paltiel et al.
5,433,739 A	7/1995	Sluijter	5,660,185 A	8/1997	Shmulewitz et al.
5,443,489 A	8/1995	Ben-Haim	5,662,111 A	9/1997	Cosman
			5,699,444 A	12/1997	Palm
			5,701,898 A	12/1997	Adam et al.
			5,701,900 A	12/1997	Shehada et al.
			5,726,670 A	3/1998	Tabata et al.
			5,728,044 A	3/1998	Shan
			5,758,650 A	6/1998	Miller et al.
			5,766,135 A	6/1998	Terwilliger
			5,784,098 A	7/1998	Shoji et al.
			5,792,147 A	8/1998	Evans et al.
			5,793,701 A	8/1998	Wright et al.
			5,797,849 A	8/1998	Vesely et al.
			5,807,395 A	9/1998	Mulier et al.
			5,810,008 A	9/1998	Dekel et al.
			5,817,022 A	10/1998	Vesely
			5,820,554 A	10/1998	Davis et al.
			5,820,561 A	10/1998	Olstad et al.
			5,829,439 A	11/1998	Yokosawa et al.
			5,829,444 A	11/1998	Ferre et al.
			5,851,183 A	12/1998	Bucholz
			5,870,136 A	2/1999	Fuchs et al.
			5,891,034 A	4/1999	Bucholz
			5,920,395 A	7/1999	Schulz
			5,961,527 A	10/1999	Whitmore, III et al.
			5,967,980 A	10/1999	Ferre et al.
			5,991,085 A	11/1999	Rallison et al.
			6,016,439 A	1/2000	Acker
			6,019,724 A	2/2000	Gronningsaeter et al.
			6,048,312 A	4/2000	Ishrak et al.
			6,064,749 A	5/2000	Hirota et al.
			6,091,546 A	7/2000	Spitzer
			6,095,982 A	8/2000	Richards-Kortum et al.
			6,099,471 A	8/2000	Torp et al.
			6,108,130 A	8/2000	Raj
			6,122,538 A	9/2000	Sliwa, Jr. et al.
			6,122,541 A	9/2000	Cosman et al.
			6,160,666 A	12/2000	Rallison et al.
			6,167,296 A	12/2000	Shahidi
			6,181,371 B1	1/2001	Maguire, Jr.
			RE37,088 E	3/2001	Olstad et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,216,029 B1	4/2001	Paltieli	7,245,746 B2	7/2007	Bjaerum et al.
6,241,725 B1	6/2001	Cosman	7,248,232 B1	7/2007	Yamazaki et al.
6,245,017 B1	6/2001	Hashimoto et al.	7,261,694 B2	8/2007	Torp et al.
6,246,898 B1	6/2001	Vesely et al.	7,313,430 B2	12/2007	Urquhart et al.
6,248,101 B1	6/2001	Whitmore, III et al.	7,331,932 B2	2/2008	Leitner
6,261,234 B1	7/2001	Lin	7,351,205 B2	4/2008	Szczzech et al.
6,341,016 B1	1/2002	Malione	7,379,769 B2	5/2008	Piron et al.
6,348,058 B1	2/2002	Melkent et al.	7,385,708 B2	6/2008	Ackerman et al.
6,350,238 B1	2/2002	Olstad et al.	7,392,076 B2	6/2008	Moctezuma de la Barrera
6,352,507 B1	3/2002	Torp et al.	7,398,116 B2	7/2008	Edwards
6,379,302 B1	4/2002	Kessman et al.	7,466,303 B2	12/2008	Yi et al.
6,385,475 B1	5/2002	Cinquin et al.	7,480,533 B2	1/2009	Cosman et al.
6,442,417 B1	8/2002	Shahidi et al.	7,505,809 B2	3/2009	Strommer et al.
6,447,450 B1	9/2002	Olstad	7,588,541 B2	9/2009	Floyd et al.
6,456,868 B2	9/2002	Saito et al.	7,652,259 B2	1/2010	Kimchy et al.
6,470,207 B1	10/2002	Simon et al.	7,662,128 B2	2/2010	Salcudean et al.
6,471,366 B1	10/2002	Hughson et al.	7,678,052 B2	3/2010	Torp et al.
6,477,400 B1	11/2002	Barrick	7,728,868 B2	6/2010	Razzaque et al.
6,478,793 B1	11/2002	Cosman et al.	7,797,032 B2	9/2010	Martinelli et al.
6,503,195 B1	1/2003	Keller et al.	7,798,965 B2	9/2010	Torp et al.
6,511,418 B2	1/2003	Shahidi et al.	7,833,168 B2	11/2010	Taylor et al.
6,517,485 B2	2/2003	Torp et al.	7,833,221 B2	11/2010	Voegele et al.
6,518,939 B1	2/2003	Kikuchi	7,846,103 B2	12/2010	Cannon, Jr. et al.
6,527,443 B1	3/2003	Vilsmeier	7,876,942 B2	1/2011	Gilboa
6,529,758 B2	3/2003	Shahidi	7,889,905 B2	2/2011	Higgins et al.
6,537,217 B1	3/2003	Bjaerum et al.	7,901,357 B2	3/2011	Boctor et al.
6,545,706 B1	4/2003	Edwards et al.	7,912,849 B2	3/2011	Ohrn et al.
6,546,279 B1	4/2003	Bova et al.	7,920,909 B2	4/2011	Lyon et al.
6,551,325 B2	4/2003	Neubauer et al.	7,962,193 B2	6/2011	Edwards et al.
6,570,566 B1	5/2003	Yoshigahara	7,976,469 B2	7/2011	Bonde et al.
6,575,969 B1	6/2003	Rittman, III et al.	8,023,712 B2	9/2011	Ikuma et al.
6,579,240 B2	6/2003	Bjaerum et al.	8,038,631 B1	10/2011	Sanghvi et al.
6,587,711 B1	7/2003	Alfano et al.	8,041,413 B2	10/2011	Barbagli et al.
6,591,130 B2	7/2003	Shahidi	8,050,736 B2	11/2011	Piron et al.
6,592,522 B2	7/2003	Bjaerum et al.	8,052,636 B2	11/2011	Moll et al.
6,594,517 B1	7/2003	Nevo	8,066,644 B2	11/2011	Sarkar et al.
6,597,818 B2	7/2003	Kumar et al.	8,073,528 B2	12/2011	Zhao et al.
6,604,404 B2	8/2003	Paltieli et al.	8,086,298 B2	12/2011	Whitmore, III et al.
6,616,610 B2	9/2003	Steininger et al.	8,135,669 B2	3/2012	Olstad et al.
6,626,832 B1	9/2003	Paltieli et al.	8,137,281 B2	3/2012	Huang et al.
6,652,462 B2	11/2003	Bjaerum et al.	8,147,408 B2	4/2012	Bunce et al.
6,669,635 B2	12/2003	Kessman et al.	8,152,724 B2	4/2012	Ridley et al.
6,676,599 B2	1/2004	Torp et al.	8,167,805 B2	5/2012	Emery et al.
6,689,067 B2	2/2004	Sauer et al.	8,216,149 B2	7/2012	Oonuki et al.
6,695,786 B2	2/2004	Wang et al.	8,221,322 B2	7/2012	Wang et al.
6,711,429 B1	3/2004	Gilboa et al.	8,228,028 B2	7/2012	Schneider
6,725,082 B2	4/2004	Sati et al.	8,257,264 B2	9/2012	Park et al.
6,733,458 B1	5/2004	Steins et al.	8,296,797 B2	10/2012	Olstad et al.
6,764,449 B2	7/2004	Lee et al.	8,340,379 B2	12/2012	Razzaque et al.
6,766,184 B2	7/2004	Utzinger et al.	8,350,902 B2	1/2013	Razzaque et al.
6,768,496 B2	7/2004	Bieger et al.	8,482,606 B2	7/2013	Razzaque et al.
6,775,404 B1	8/2004	Pagoulatos et al.	8,554,307 B2	10/2013	Razzaque et al.
6,782,287 B2	8/2004	Grzeszczuk et al.	8,585,598 B2	11/2013	Razzaque et al.
6,783,524 B2	8/2004	Anderson et al.	8,641,621 B2	2/2014	Razzaque et al.
6,827,723 B2	12/2004	Carson	8,670,816 B2	3/2014	Green et al.
6,863,655 B2	3/2005	Bjaerum et al.	8,690,776 B2	4/2014	Razzaque et al.
6,873,867 B2	3/2005	Vilsmeier	8,831,310 B2	9/2014	Razzaque et al.
6,875,179 B2	4/2005	Ferguson et al.	9,107,698 B2	8/2015	Razzaque et al.
6,881,214 B2	4/2005	Cosman et al.	9,282,947 B2	3/2016	Razzaque et al.
6,895,268 B1	5/2005	Rahn et al.	9,364,294 B2	6/2016	Razzaque et al.
6,915,150 B2	7/2005	Cinquin et al.	9,398,936 B2	7/2016	Razzaque et al.
6,917,827 B2	7/2005	Kienzle, III	2001/0007919 A1	7/2001	Shahidi
6,923,817 B2	8/2005	Carson et al.	2001/0016804 A1	8/2001	Cunningham et al.
6,936,048 B2	8/2005	Hurst	2001/0041838 A1	11/2001	Holupka et al.
6,947,783 B2	9/2005	Immerz	2001/0045979 A1	11/2001	Matsumoto et al.
6,968,224 B2	11/2005	Kessman et al.	2002/0010384 A1	1/2002	Shahidi et al.
6,978,167 B2	12/2005	Dekel et al.	2002/0032772 A1	3/2002	Olstad et al.
7,008,373 B2	3/2006	Stoianovici et al.	2002/0049375 A1	4/2002	Strommer et al.
7,033,360 B2	4/2006	Cinquin et al.	2002/0077540 A1	6/2002	Kienzle, III
7,072,707 B2	7/2006	Galloway, Jr. et al.	2002/0077543 A1	6/2002	Grzeszczuk et al.
7,077,807 B2	7/2006	Torp et al.	2002/0105484 A1	8/2002	Navab et al.
7,093,012 B2	8/2006	Olstad et al.	2002/0135673 A1	9/2002	Favalora et al.
7,110,013 B2	9/2006	Ebersole et al.	2002/0138008 A1	9/2002	Tsujita et al.
7,171,255 B2	1/2007	Holupka et al.	2002/0140814 A1	10/2002	Cohen-Solal et al.
7,209,776 B2	4/2007	Leitner	2002/0156375 A1	10/2002	Kessman et al.
			2002/0198451 A1	12/2002	Carson
			2003/0040743 A1	2/2003	Cosman et al.
			2003/0073901 A1	4/2003	Simon et al.
			2003/0135119 A1	7/2003	Lee et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2003/0163142 A1 8/2003 Paltieli et al.
 2003/0164172 A1 9/2003 Chumas et al.
 2003/0231789 A1 12/2003 Willis et al.
 2004/0034313 A1 2/2004 Leitner
 2004/0078036 A1 4/2004 Keidar
 2004/0095507 A1 5/2004 Bishop et al.
 2004/0116810 A1 6/2004 Olstad
 2004/0147920 A1 7/2004 Keidar
 2004/0152970 A1 8/2004 Hunter et al.
 2004/0181144 A1 9/2004 Cinquin et al.
 2004/0215071 A1 10/2004 Frank et al.
 2004/0238732 A1 12/2004 State et al.
 2004/0243146 A1 12/2004 Chesbrough et al.
 2004/0243148 A1 12/2004 Wasielewski
 2004/0249281 A1 12/2004 Olstad
 2004/0249282 A1 12/2004 Olstad
 2004/0254454 A1 12/2004 Kockro
 2005/0010098 A1 1/2005 Frigstad et al.
 2005/0085717 A1 4/2005 Shahidi
 2005/0085718 A1 4/2005 Shahidi
 2005/0090742 A1 4/2005 Mine et al.
 2005/0111733 A1 5/2005 Fors et al.
 2005/0159641 A1 7/2005 Kanai
 2005/0182316 A1 8/2005 Burdette et al.
 2005/0192564 A1 9/2005 Cosman et al.
 2005/0219552 A1 10/2005 Ackerman et al.
 2005/0222574 A1 10/2005 Giordano et al.
 2005/0251148 A1 11/2005 Friedrich
 2006/0004275 A1 1/2006 Vija et al.
 2006/0020204 A1 1/2006 Serra et al.
 2006/0036162 A1 2/2006 Shahidi et al.
 2006/0052792 A1 3/2006 Boettiger et al.
 2006/0058609 A1 3/2006 Olstad
 2006/0058610 A1 3/2006 Olstad
 2006/0058674 A1 3/2006 Olstad
 2006/0058675 A1 3/2006 Olstad
 2006/0100505 A1 5/2006 Viswanathan
 2006/0122495 A1 6/2006 Kienzle
 2006/0184040 A1 8/2006 Keller et al.
 2006/0193504 A1 8/2006 Salgo et al.
 2006/0229594 A1 10/2006 Francischelli et al.
 2006/0235290 A1 10/2006 Gabriel et al.
 2006/0235538 A1 10/2006 Rochetin et al.
 2006/0241450 A1 10/2006 Da Silva et al.
 2006/0253030 A1 11/2006 Altmann et al.
 2006/0253032 A1 11/2006 Altmann et al.
 2006/0271056 A1 11/2006 Terrill-Grisoni et al.
 2006/0282023 A1 12/2006 Leitner
 2006/0293643 A1 12/2006 Wallace et al.
 2007/0002582 A1 1/2007 Burwell et al.
 2007/0016035 A1 1/2007 Hashimoto
 2007/0032906 A1 2/2007 Sutherland et al.
 2007/0073155 A1 3/2007 Park et al.
 2007/0078346 A1 4/2007 Park et al.
 2007/0167699 A1 7/2007 Lathuiliere et al.
 2007/0167701 A1 7/2007 Sherman
 2007/0167705 A1 7/2007 Chiang et al.
 2007/0167771 A1 7/2007 Olstad
 2007/0167801 A1 7/2007 Webler et al.
 2007/0225553 A1 9/2007 Shahidi
 2007/0239281 A1 10/2007 Gotte et al.
 2007/0244488 A1 10/2007 Metzger et al.
 2007/0255136 A1 11/2007 Kristofferson et al.
 2007/0270718 A1 11/2007 Rochetin et al.
 2007/0276234 A1 11/2007 Shahidi
 2008/0004481 A1 1/2008 Bax et al.
 2008/0004516 A1 1/2008 DiSilvestro et al.
 2008/0030578 A1 2/2008 Razzaque et al.
 2008/0039723 A1 2/2008 Suri et al.
 2008/0051910 A1 2/2008 Kammerzell et al.
 2008/0091106 A1 4/2008 Kim et al.
 2008/0114235 A1 5/2008 Unal et al.
 2008/0161824 A1 7/2008 McMillen
 2008/0200794 A1 8/2008 Teichman et al.
 2008/0208031 A1 8/2008 Kurpad et al.

2008/0208081 A1 8/2008 Murphy et al.
 2008/0214932 A1 9/2008 Mollard et al.
 2008/0232679 A1 9/2008 Hahn et al.
 2008/0287794 A1 11/2008 Li et al.
 2008/0287805 A1 11/2008 Li
 2008/0287837 A1 11/2008 Makin et al.
 2009/0024030 A1 1/2009 Lachaine et al.
 2009/0118724 A1 5/2009 Zvuloni et al.
 2009/0131783 A1 5/2009 Jenkins et al.
 2009/0137907 A1 5/2009 Takimoto et al.
 2009/0226069 A1 9/2009 Razzaque et al.
 2009/0234369 A1 9/2009 Bax et al.
 2009/0312629 A1 12/2009 Razzaque et al.
 2010/0045783 A1 2/2010 State et al.
 2010/0198045 A1 8/2010 Razzaque et al.
 2010/0208963 A1 8/2010 Kruecker et al.
 2010/0268067 A1 10/2010 Razzaque et al.
 2010/0268072 A1 10/2010 Hall et al.
 2010/0268085 A1 10/2010 Kruecker et al.
 2010/0298705 A1 11/2010 Pelissier et al.
 2010/0305448 A1 12/2010 Dagonneau et al.
 2010/0312121 A1 12/2010 Guan
 2010/0331252 A1 12/2010 Hamrick
 2011/0043612 A1 2/2011 Keller et al.
 2011/0046483 A1 2/2011 Fuchs et al.
 2011/0046486 A1 2/2011 Shin et al.
 2011/0057930 A1 3/2011 Keller
 2011/0082351 A1 4/2011 Razzaque et al.
 2011/0130641 A1 6/2011 Razzaque et al.
 2011/0137156 A1 6/2011 Razzaque et al.
 2011/0201915 A1 8/2011 Gogin et al.
 2011/0201976 A1 8/2011 Sanghvi et al.
 2011/0230351 A1 9/2011 Fischer et al.
 2011/0237947 A1 9/2011 Boctor et al.
 2011/0238043 A1 9/2011 Kleven
 2011/0251483 A1 10/2011 Razzaque et al.
 2011/0274324 A1 11/2011 Clements et al.
 2011/0282188 A1 11/2011 Burnside et al.
 2011/0288412 A1 11/2011 Deckman et al.
 2011/0295108 A1 12/2011 Cox et al.
 2011/0301451 A1 12/2011 Rohling
 2012/0035473 A1 2/2012 Sanghvi et al.
 2012/0059260 A1 3/2012 Robinson
 2012/0071759 A1 3/2012 Hagy et al.
 2012/0078094 A1 3/2012 Nishina et al.
 2012/0101370 A1 4/2012 Razzaque et al.
 2012/0108955 A1 5/2012 Razzaque et al.
 2012/0143029 A1 6/2012 Silverstein et al.
 2012/0143055 A1 6/2012 Ng et al.
 2012/0165679 A1 6/2012 Orome et al.
 2012/0259210 A1 10/2012 Harhen et al.
 2013/0030286 A1 1/2013 Alouani et al.
 2013/0044930 A1 2/2013 Li et al.
 2013/0079770 A1 3/2013 Kyle, Jr. et al.
 2013/0132374 A1 5/2013 Olstad et al.
 2013/0151533 A1 6/2013 Udupa et al.
 2013/0178745 A1 7/2013 Kyle et al.
 2014/0078138 A1 3/2014 Martin et al.
 2014/0180074 A1 6/2014 Green
 2014/0275810 A1 9/2014 Keller et al.
 2014/0343404 A1 11/2014 Razzaque et al.
 2016/0117857 A1 4/2016 State et al.
 2016/0166334 A1 6/2016 Razzaque
 2016/0166336 A1 6/2016 Razzaque
 2016/0196694 A1 7/2016 Lindeman

FOREIGN PATENT DOCUMENTS

AU 1719601 A 6/2001
 AU 9036301 A 3/2002
 AU 2003297225 A1 7/2004
 AU 2001290363 B2 2/2006
 BR 0113882 A 7/2003
 CA 2420382 C 4/2011
 DE 60126798 T2 10/2007
 EP 0 427 358 5/1991
 EP 1955284 8/2008
 JP S63-290550 A 11/1988
 JP H07-116164 A 5/1995

(56)

References Cited

FOREIGN PATENT DOCUMENTS

JP	2005-058584	3/2005
JP	2005-323669	11/2005
JP	2009-517177	4/2009
WO	WO 96/05768	2/1996
WO	WO 97/15249	5/1997
WO	WO 97/17014	5/1997
WO	WO 99/26534	6/1999
WO	WO 01/39683	6/2001
WO	WO 03/032837	4/2003
WO	WO 03/034705	4/2003
WO	PCT/US2003/17987	12/2003
WO	WO 03/105289	12/2003
WO	WO 2005/010711	2/2005
WO	WO 2007/019216	2/2007
WO	WO 2007/067323 A2	6/2007
WO	WO 2007/067323 A3	9/2007
WO	WO 2008/017051	2/2008
WO	WO 2009/094646	7/2009
WO	WO 2010/057315	5/2010
WO	WO 2010/096419	8/2010
WO	WO 2009/063423	10/2010
WO	WO 2011/014687	2/2011
WO	WO 2012/169990	12/2012
WO	WO 2013/116240	8/2013

OTHER PUBLICATIONS

"3D Laparoscope Technology," http://www.inneroptic.com/tech_3DL.htm, copyright 2007 InnerOptic Technology, Inc. printed Sep. 19, 2007, 2 pages.

"Cancer Facts & Figures 2004," www.cancer.org/downloads/STT/CAFF_finalPWSecured.pdf, copyright 2004 American Cancer Society, Inc., printed Sep. 19, 2007, 60 pages.

"David Laserscanner ←Latest News ←Institute for Robotics and Process Control ←Te . . .," <http://www.rob.cs.tu-bs.de/en/news/david>, printed Sep. 19, 2007, 1 page.

"Laser scanned 3d model Final" video, still image of video attached, <http://www.youtube.com/watch?v=DaLgIgmUf8>, copyright 2007 YouTube, LLC, printed Sep. 19, 2007, 2 pages.

"Olympus Endoscopic Ultrasound System," www.olympusamerica.com/msg_section/download_brochures/135_b_gfum130.pdf, printed Sep. 20, 2007, 20 pages.

"Point Grey Research Inc.—Imaging Products—Triclops SDK Samples," <http://www.ptgrey.com/products/triclopsSDK/samples.asp>, copyright 2007 Point Grey Research Inc., printed Sep. 19, 2007, 1 page.

"Robbins, Mike—Computer Vision Research—Stereo Depth Perception," <http://www.compumike.com/vision/stereodepth.php>, copyright 2007 Michael F. Robbins, printed Sep. 19, 2007, 3 pages.

"Rue, Registered Ultrasound-Endoscope," copyright 2007 InnerOptic Technology, Inc., 2 pages.

Advertisement, "Inspeck 3DC 3D Capturor," Inspeck 3DC 3D Capturor (www.inspeck.com), 1998.

Advertisement, "Virtual 3D High Speed Non-Contact Surface Perception," Virtual 3-D Technologies Corporation (www.virtual3dtech.com), Dec. 21, 1998.

Advertisements, "Virtuoso," Visual Interface, Inc. (www.visint.com), Dec. 21, 1998.

Akka, "Automatic Software Control of Display Parameters for Stereoscopic Graphics Images," SPIE vol. 1669: Stereoscopic Displays and Applications III, pp. 31-38 (1992).

Ali et al., "Near Infrared Spectroscopy and Imaging to Probe Differences in Water Content in Normal and Cancer Human Prostate Tissues," Technology in Cancer Research & Treatment; Oct. 2004; 3(5):491-497; Adenine Press.

Aylward et al., Analysis of the Parameter Space of a Metric for Registering 3D Vascular Images, in W. Niessen and M. Viergever (Eds.): MICCAI 2001, LNCS 2208, pp. 932-939, 2001.

Aylward et al., Registration and Analysis of Vascular Images, International Journal of Computer Vision 55(2/3), 123-138, 2003.

Aylward, et al., Intra-Operative 3D Ultrasound Augmentation, Proceedings of the IEEE International Symposium on Biomedical Imaging, Washington, Jul. 2002.

Azuma, "A Survey of Augmented Reality," Presence: Teleoperators and Virtual Environments 6, 4:1-48 (Aug. 1997).

Bajura, Michael et al. "Merging Virtual Objects with the Real World: Seeing Ultrasound Imagery within the Patient," Computer Graphics, Proceedings of SIGGRAPH 1992, vol. 26(2), pp. 203-210, available from www.cs.unc.edu/~fuchs/publications/MergVirtObjs92.pdf, printed Sep. 20, 2007, 8 pages.

Benavides et al., "Multispectral digital colposcopy for in vivo detection of cervical cancer," Optics Express; May 19, 2003; 11(10) Optical Society of America; USA.

Beraldin, J.A. et al., "Optimized Position Sensors for Flying-Spot Active Triangulation Systems," Proceedings of the Fourth International Conference on a 3-D Digital Imaging and Modeling (3DIM), Banff, Alberta, Canada, Oct. 6-10, 2003, pp. 334-341, NRC 47083, copyright 2003 National Research Council of Canada, <http://it-iti.nrc-cnrc.gc.ca/it-iti-publications-iti/docs/NRC-47083.pdf>, printed Sep. 19, 2007, 9 pages.

Billinghurst, M. et al., Research Directions in Handheld AR; Int. J. of Virtual Reality 5(2),51-58 (2006).

Bishop, Azuma et al., "Improving Static and Dynamic Registration in an Optical See-Through HMD," Paper Presented at SIGGRAPH '94 Annual Conference in Orlando, FL (1994).

Blais, F., "Review of 20 Years of Range Sensor Development," Journal of Electronic Imaging, 13(1): 231-240, Jan. 2004, NRC 46531, copyright 2004 National Research Council of Canada, <http://it-iti.nrc-cnrc.gc.ca/it-iti-publications-iti/docs/NRC-46531.pdf>, printed Sep. 19, 2007, 14 pages.

Bouguet, Jean-Yves, "Camera Calibration Toolbox for Matlab," www.vision.caltech.edu/bouguetj/calib_doc, printed Sep. 20, 2007, 5 pages.

Buxton et al.; "Colposcopically directed punch biopsy: a potentially misleading investigation," British Journal of Obstetrics and Gynecology; Dec. 1991; 98:1273-1276.

Cancer Prevention & Early Detection Facts & Figures 2004; National Center for Tobacco-Free Kids; 2004; American Cancer Society; USA.

Cantor et al., "Cost-Effectiveness Analysis of Diagnosis and Management of Cervical Squamous Intraepithelial Lesions," Diagnostic Strategies for SILs; Feb. 1998; 91(2):270-277.

Catalano et al., "Multiphase helical CT findings after percutaneous ablation procedures for hepatocellular carcinoma," Abdom. Imaging, 25(6),2000, pp. 607-614.

Chiriboga et al., "Infrared Spectroscopy of Human Tissue. IV. Detection of Dysplastic and Neoplastic Changes of Human Cervical Tissue via Infrared Microscopy," Cellular and Molecular Biology; 1998; 44(1): 219-229.

Crawford, David E. et al., "Computer Modeling of Prostate Biopsy: Tumor Size and Location—Not Clinical Significance—Determine Cancer Detection," Journal of Urology, Apr. 1998, vol. 159(4), pp. 1260-1264, 5 pages.

Deering, Michael "High Resolution Virtual Reality," Proceedings of SIGGRAPH '92, Computer Graphics, 26(2), 1992, pp. 195-202.

Depiero et al., "3-D Computer Vision Using Structured Light: Design, Calibration and Implementation Issues," The University of Tennessee, pp. 1-46, (1996).

Dodd, G.D. et al. "Minimally invasive treatment of malignant hepatic tumors: at the threshold of a major breakthrough," Radiographies 20(1),2000, pp. 9-27.

Drascic et al., "Perceptual Issues in Augmented Reality," SPIE vol. 2653: Stereoscopic Displays and Virtual Reality Systems III, pp. 123-134 (Feb. 1996).

Fahey et al., "Meta-analysis of Pap Test Accuracy," American Journal of Epidemiology; 1995 141(7):680-689; The John Hopkins University School of Hygiene and Public Health; USA.

Foxlin et al., "An Inertial Head-Orientation Tracker with Automatic Drift Compensation for Use with HMD's," Proceedings of the 1994 Virtual Reality Software and Technology Conference, Aug. 23-26, 1994, Singapore, pp. 159-173 (1994).

(56)

References Cited

OTHER PUBLICATIONS

- Fronheiser et al., Real-Time 3D Color Doppler for Guidance of Vibrating Interventional Devices, IEEE Ultrasonics Symposium, pp. 149-152 (2004).
- Fuchs, Henry et al. "Augmented Reality Visualization for Laparoscopic Surgery," Proceedings of Medical Image Computing and Computer-Assisted Intervention (MICCAI) 1998, pp. 934-943, available from www.cs.unc.edu/~fuchs/publications/AugRealVis_LaparoSurg98.pdf, printed Sep. 20, 2007, 10 pages.
- Fuchs, et al.: "Virtual Environments Technology to Aid Needle Biopsies of the Breast," Health Care in the Information Age, Ch. 6, pp. 60-61, Presented in San Diego, Jan. 17-20, 1996, published by IOS Press and Ohmsha Feb. 1996.
- Garrett, William F. et al., "Real-Time Incremental Visualization of Dynamic Ultrasound Volumes Using Parallel BSP Trees," Proceedings of IEEE Visualization 1996, pp. 235-240, available from www.cs.unc.edu/~andrei/pubs/1996_VIS_dualBSP_Mac.pdf, printed Sep. 20, 2007, 7 pages.
- Georgakoudi et al., "Trimodal spectroscopy for the detection and characterization of cervical precancers in vivo," American Journal of Obstetrics and Gynecology; Mar. 2002; 186(3):374-382; USA.
- Herline et al., Surface Registration for Use in Interactive, Image-Guided Liver Surgery, Computer Aided Surgery 5:11-17 (2000).
- Holloway, R.; Registration Error Analysis for Augmented Reality; Presence: Teleoperators and Virtual Environments 6(4), 413-432 (1997).
- Hornung et al., "Quantitative near-infrared spectroscopy of cervical dysplasia in vivo," Human Reproduction; 1999; 14(11):2908-2916; European Society of Human Reproduction and Embryology.
- Howard, M.D., et al.: "An Electronic Device for Needle Placement during Sonographically Guided Percutaneous Intervention", Radiology 2001; 218:905-911.
- InnerAim Brochure; 3D Visualization Software for Simpler, Safer, more Precise Aiming, Published no earlier than Apr. 1, 2010.
- InVision System Brochure; A "GPS" for Real-Time 3D Needle Visualization & Guidance, Published no earlier than Mar. 1, 2008.
- InVision User Manual; Professional Instructions for Use, Published no earlier than Dec. 1, 2008.
- Jacobs, Marco C. et al., "Managing Latency in Complex Augmented Reality Systems," ACM SIGGRAPH Proceedings of the Symposium of Interactive 3D Graphics 1997, pp. 49-54, available from www.cs.unc.edu/~us/Latency/ManagingRelativeLatency.html, printed Sep. 20, 2007, 12 pages.
- Kanbara et al., "A Stereoscopic Video See-through Augmented Reality System Based on Real-time Vision-Based Registration," Nara Institute of Science and Technology, pp. 1-8 (2000).
- Lass, Amir, "Assessment of Ovarian Reserve," Human Reproduction, 2004, vol. 19(3), pp. 467-469, available from <http://humrep.oxfordjournals.org/cgi/reprint/19/3/467>, printed Sep. 20, 2007, 3 pages.
- Lee et al., "Modeling Real Objects Using Video See-Through Augmented Reality," Presence, 11(2):144-157 (Apr. 2002).
- Leven et al., DaVinci Canvas: A Telerobotic Surgical System with Integrated, Robot-Assisted, Laparoscopic Ultrasound Capability, in J. Duncan and G. Gerig (Eds.): MICCAI 2005, LNCS 3749, pp. 811-818, 2005.
- Levy, et al., An Internet-Connected, Patient Specific, Deformable Brain Atlas Integrated into a Surgical Navigation System, Journal of Digital Imaging, vol. 10, No. 3, Suppl. 1 Aug. 1997: pp. 231-237.
- Livingston, Mark A. et al., "Magnetic Tracker Calibration for Improved Augmented Reality Registration," Presence: Teleoperators and Virtual Environments, 1997, vol. 6(5), pp. 532-546, available from www.cs.unc.edu/~andrei/pubs/1997_Presence_calibr.pdf, printed Sep. 20, 2007, 14 pages.
- Matsunaga et al., "The Effect of the Ratio Difference of Overlapped Areas of Stereoscopic Images on each Eye in a Teleoperation," Stereoscopic Displays and Virtual Reality Systems VII, Proceedings of SPIE, 3957:236-243 (2000).
- Meehan, Michael et al., "Effect of Latency on Presence in Stressful Virtual Environment," Proceedings of IEEE Virtual Reality 2003, pp. 141-148, available from <http://www.cs.unc.edu/~eve/pubs.html>, printed Sep. 20, 2007, 9 pages.
- Milgram et al., "Adaptation Effects in Stereo due to Online Changes in Camera Configuration," SPIE vol. 1669-13, Stereoscopic Displays and Applications III, pp. 1-12 (1992).
- Mitchell et al., "Colposcopy for the Diagnosis of Squamous Intraepithelial lesions: A metaanalysis," Obstetrics and Gynecology; Apr. 1998; 91(4):626-631.
- Nakamoto et al., 3D Ultrasound System Using a Magneto-optic Hybrid Tracker for Augmented Reality Visualization in Laparoscopic Liver Surgery, in T. Dohi and R. Kikinis (Eds.): MICCAI 2002, LNCS 2489, pp. 148-155, 2002.
- Nordstrom et al., "Identification of Cervical Intraepithelial Neoplasia (CIN) Using UV-Excited Fluorescence and Diffuse-Reflectance Tissue Spectroscopy," Lasers in Surgery and Medicine; 2001; 29; pp. 118-127; Wiley-Liss, Inc.
- Ohbuchi et al. "An Incremental Volume Rendering Algorithm for Interactive 3D Ultrasound Imaging", UNC-CH Computer Science Technical Report TR91-003, (1991).
- Ohbuchi et al., "Incremental Volume Reconstruction and Rendering for 3D Ultrasound Imaging," Visualization in Biomedical Computing, SPIE Proceedings, pp. 312-323, (Oct. 13, 1992).
- Ohbuchi, "Incremental Acquisition and Visualization of 3D Ultrasound Images," Ph.D. Dissertation, UNC-CH Computer Science Technical Report TR95-023, (1993).
- PCT, International Search Report and Written Opinion, re PCT Application No. PCT/US07/75122, mailing date Aug. 20, 2008.
- PCT, International Preliminary Report on Patentability, re PCT Application No. PCT/US07/75122, mailing date Mar. 3, 2009.
- PCT, International Search Report and Written Opinion, re PCT Application No. PCT/US2010/024378, mailing date Oct. 13, 2010.
- PCT, International Search Report and Written Opinion, re PCT Application No. PCT/US2010/043760, mailing date Mar. 3, 2011.
- PCT, The International Search Report and Written Opinion of the International Searching Authority, mailed Sep. 9, 2009, for case PCT/US2009/032028.
- Progue, Brian W. et al., "Analysis of acetic acid-induced whitening of high-grade squamous intraepithelial lesions," Journal of Biomedical Optics; Oct. 2001; 6(4):397-403.
- Raij, A.B., et al., Comparing Interpersonal Interactions with a Virtual Human to Those with a Real Human; IEEE Transactions on Visualization and Computer Graphics 13(3), 443-457 (2007).
- Raz et al, Real-Time Magnetic Resonance Imaging-Guided Focal Laser Therapy in Patients with Low-Risk Prostate Cancer, European Urology 58, pp. 173-177. Mar. 12, 2010.
- Robinet et al., "A Computational Model for the Stereoscopic Optics of a Head-Mounted Display," SPIE vol. 1457, Stereoscopic Displays and Applications II, pp. 140-160 (1991).
- Rolland et al., Towards Quantifying Depth and Size Perception in Virtual Environments, Presence: Teleoperators and Virtual Environments, Winter 1995, vol. 4, Issue 1, pp. 1-21 and 24-49.
- Rosenthal, Michael et al., "Augmented Reality Guidance for Needle Biopsies: An Initial Randomized, Controlled Trial in Phantoms," Proceedings of Medical Image Analysis, Sep. 2002, vol. 6(3), pp. 313-320, available from www.cs.unc.edu/~fuchs/publications/AugRealGuida_NeedleBiop02.pdf, printed Sep. 20, 2007, 8 pages.
- Rosenthal, Michael et al., "Augmented Reality Guidance for Needle Biopsies: A Randomized, Controlled Trial in Phantoms," Proceedings of MICCAI 2001, eds. W. Niessen and M. Viergever, Lecture Notes in Computer Science, 2001, vol. 2208, pp. 240-248, available from www.cs.unc.edu/~us/AugmentedRealityAssistance.pdf, printed Sep. 20, 2007, 9 pages.
- Splechtna, Fuhrmann A. et al., Comprehensive calibration and registration procedures for augmented reality; Proc. Eurographics Workshop on Virtual Environments 2001, 219-228 (2001).
- State et al., "Case Study: Observing a Volume Rendered Fetus within a Pregnant Patient," Proceedings of IEEE Visualization 1994, pp. 364-368, available from www.cs.unc.edu/~fuchs/publications/cs-ObservVolRendFetus94.pdf, printed Sep. 20, 2007, 5 pages.

(56)

References Cited

OTHER PUBLICATIONS

- State et al., "Interactive Volume Visualization on a Heterogenous Message-Passing Multicomputer," Proceedings of 1995 Symposium on Interactive 3D Graphics, 1995, pp. 69-74, 208, available from www.cs.unc.edu/~andrei/pubs/1995_I3D_vol2_Mac.pdf, printed Sep. 20, 2007.
- State et al., "Simulation-Based Design and Rapid Prototyping of a Parallax-Free, Orthoscopic Video See-Through Head-Mounted Display," Proceedings of International Symposium on Mixed and Augmented Reality (ISMAR) 2005, available from www.cs.unc.edu/~andrei/pubs/2005_ISMAR_VSTHMD_design.pdf, printed Sep. 20, 2007, 4 pages.
- State et al., "Stereo Imagery from the UNC Augmented Reality System for Breast Biopsy Guidance" Proc. Medicine Meets Virtual Reality (MMVR) 2003 (Newport Beach, CA, Jan. 22-25, 2003).
- State et al., "Superior Augmented Reality Registration by Integrating Landmark Tracking and Magnetic Tracking," ACM SIGGRAPH Computer Graphics, Proceedings of SIGGRAPH 1996, pp. 429-438, available from www.cs.princeton.edu/courses/archive/fall101/cs597d/papers/state96.pdf, printed Sep. 20, 2007, 10 pages.
- State et al., "Technologies for Augmented Reality Systems: Realizing Ultrasound-Guided Needle Biopsies," Computer Graphics, Proceedings of SIGGRAPH 1996, pp. 429-438, available from www.cs.princeton.edu/courses/archive/fall101/cs597d/papers/state96.pdf, printed Sep. 20, 2007.
- State, Andrei "Exact Eye Contact with Virtual Humans." Proc. IEEE International Workshop on Human Computer Interaction 2007 (Rio de Janeiro, Brazil, Oct. 20, 2007), pp. 138-145.
- Takagi et al., "Development of a Stereo Video See-through HMD for AR Systems," IEEE, pp. 68-77 (2000).
- Ultraguide 1000 System, Ultraguide, www.ultraguideinc.com, 1998.
- Van Staveren et al., "Light Scattering in Intralipid-10% in the wavelength range of 400-1100 nm," Applied Optics; Nov. 1991; 30(31):4507-4514.
- Viola et al., "Alignment by Maximization of Mutual Information," International Journal of Computer Vision, vol. 24, No. 2, pp. 1-29 (1997).
- Viola, Paul A., Alignment by Maximization of Mutual Information, Ph.D. Dissertation, MIT-Artificial Intelligence Laboratory Technical Report No. 1548 (Jun. 1995).
- Ware et al., "Dynamic Adjustment of Stereo Display Parameters," IEEE Transactions on Systems, Man and Cybernetics, 28(1):1-19 (1998).
- Watson et al., "Using Texture Maps to Correct for Optical Distortion in Head-Mounted Displays," Proceedings of the Virtual Reality Annual Symposium '95, IEEE, pp. 1-7 (1995).
- Welch, Hybrid Self-Tracker: An Inertial/Optical Hybrid Three-Dimensional Tracking System, University of North Carolina Chapel Hill Department of Computer Science, TR 95-048 (1995).
- Yinghui et al., Real-Time Deformation Using Modal Analysis on Graphics Hardware, Graphite 2006, Kuala Lumpur, Malaysia, Nov. 29-Dec. 2, 2006.
- Zitnick et al., "Multi-Base Stereo Using Surface Extraction," Visual Interface Inc., (Nov. 24, 1996).
- Caines, Judy S. et al. Stereotaxic Needle Core Biopsy of Breast Lesions Using a Regular Mammographic Table with an Adaptable Stereotaxic Device, American Journal of Roentgenology, vol. 163, No. 2, Aug. 1994, pp. 317-321. Downloaded from www.ajronline.org on Jul. 10, 2013.
- Dumoulin, C.L. et al. Real-Time Position Monitoring of Invasive Devices Using Magnetic Resonance, Magnetic Resonance in Medicine, vol. 29, Issue 3, Mar. 1993, pp. 411-415.
- Jolesz, Ferenc A, M.D., et al. Mri-Guided Laser-Induced Interstitial Thermotherapy: Basic Principles, SPIE Institute on Laser-Induced Interstitial Thermotherapy (LITT), Jun. 22-23, 1995, Berlin, Germany.
- Kadi, A Majeed, et al., Design and Simulation of an Articulated Surgical Arm for Guiding Stereotactic Neurosurgery, Spie vol. 1708 Applications of Artificial Intelligence X: Machine Vision and Robotics (1992). Downloaded from: <http://proceedings.spiedigitallibrary.org/> on Jul. 11, 2013.
- Kato, Amami, et al., A frameless, armless navigational system for computer-assisted neurosurgery, Journal of Neurosurgery, vol. 74, No. 5, May 1991, pp. 845-849.
- PCT International Search Report and Written Opinion, re PCT Application No. PCT/U52013/023678, mailed Jun. 13, 2013.
- Screenshots from video produced by the University of North Carolina, produced circa 1992.
- Badler et al., "Simulating Humans: Computer Graphics, Animation, and Control," Oxford University Press (1993).
- Fuchs, et al.: "Optimizing a Head-Tracker Stereo Display System to Guide Hepatic Tumor Ablation," Departments of Computer Sciences and Radiology, and School of Medicine, University of North Carolina at Chapel Hill; InnerOptic Technology, Inc. 2008.
- Fuhrmann et al. "Comprehensive calibration and registration procedures for augmented reality," Proc. Eurographics Workshop on Virtual Environments 2001, 9 pages (2001).
- StereoMirror Technology Webpage, http://www.planar.com/products/flatpanel_monitors/stereoscopic/ (Printed Dec. 29, 2011).
- Keller et al., "What is it in Head Mounted Displays (MDs) that really make them all so terrible?," pp. 1-8 (1998).
- Lee, et al., "Modeling Real Objects Using Video See-Through Augmented Reality," Proceedings of the Second International Symposium on Mixed Reality, ISMR 2001, pp. 19-26 (Mar. 14-15, 2001).
- State et al., "Superior Augmented Reality Registration by Integrating Landmark Tracking and Magnetic Tracking," ACM SIGGRAPH Computer Graphics, Proceedings of SIGGRAPH 1996, 10 pages (Aug. 1996).
- State, et al.: Contextually Enhanced 3D Visualization for Multi-Born Tumor Ablation Guidance, Departments of Computer Science and Radiology, and School of Medicine, University of North Carolina at Chapel Hill; InnerOptic Technology, Inc. 2008, Chapel Hill, NC, pp. 70-77.
- Symons et al., "What are You Looking at? Acuity for Triadic Eye Gaze," J. Gen. Psychology 131(4), pp. 451-469 (2004).
- Takacs et al., "The Virtual Human Interface: A Photorealistic Digital Human," IEEE Computer Graphics and Applications 23(5), pp. 38-45 (2003).
- Takayama et al., "Virtual Human with Regard to Physical Contact and Eye Contact," Entertaining Computing 2005, LNCS, vol. 3711, pp. 268-278 (2005).
- U.S. Appl. No. 15/041,868 including its ongoing prosecution history, including without limitation Office Actions, Amendments, Remarks, and any other potentially relevant documents, Feb. 11, 2016, Fuchs et al.
- U.S. Appl. No. 15/068,323, including its ongoing prosecution history, including without limitation Office Actions, Amendments, Remarks, and any other potentially relevant documents, Mar. 11, 2016, Razzaque et al.
- U.S. Appl. No. 15/182,346, including its ongoing prosecution history, including without limitation Office Actions, Amendments, Remarks, and any other potentially relevant documents, Jun. 14, 2016, Razzaque et al.
- U.S. Appl. No. 15/199,630, including its ongoing prosecution history, including without limitation Office Actions, Amendments, Remarks, and any other potentially relevant documents, Jun. 30, 2016, Razzaque et al.
- U.S. Appl. No. 15/175,981, including its ongoing prosecution history, including without limitation Office Actions, Amendments, Remarks, and any other potentially relevant documents, Jul. 7, 2016, Razzaque et al.





FIG. 1

**FIG. 2**




FIG. 3A




FIG. 3B






FIG. 3C







FIG. 5






FIG. 7A




FIG. 7B




FIG. 7C




FIG. 8

SYSTEM AND METHOD OF PROVIDING REAL-TIME DYNAMIC IMAGERY OF A MEDICAL PROCEDURE SITE USING MULTIPLE MODALITIES

RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 12/760,274 entitled "System and Method of Providing Real-Time Dynamic Imagery of a Medical Procedure Site Using Multiple Modalities," filed Apr. 14, 2010, which is a continuation of U.S. patent application Ser. No. 11/833,134 entitled "System and Method of Providing Real-Time Dynamic Imagery of a Medical Procedure Site Using Multiple Modalities", filed Aug. 2, 2007, now issued as U.S. Pat. No. 7,728,868, which claims priority benefit to U.S. Provisional Application Ser. No. 60/834,932 entitled "Spatially Registered Ultrasound and Endoscopic Imagery," filed Aug. 2, 2006, and U.S. Provisional Application Ser. No. 60/856,670 entitled "Multiple Depth-Reconstructive Endoscopies Combined With Other Medical Imaging Modalities, And Other Related Technological Details," filed Nov. 6, 2006, the disclosures of all of which are incorporated in their entirety for all purposes.

FIELD OF THE INVENTION

The present invention is directed to a system and method of providing composite real-time dynamic imagery of a medical procedure site using multiple modalities. One or more of the modalities may provide two-dimensional or three-dimensional imagery.

BACKGROUND OF THE INVENTION

It is well established that minimally-invasive surgery (MIS) techniques offer significant health benefits over their analogous laparotomic (or "open") counterparts. Among these benefits are reduced trauma, rapid recovery time, and shortened hospital stays, resulting in greatly reduced care needs and costs. However, because of limited visibility to certain internal organs, some surgical procedures are at present difficult to perform using MIS. With conventional technology, a surgeon operates through small incisions using special instruments while viewing internal anatomy and the operating field through a two-dimensional monitor. Operating below while seeing a separate image above can give rise to a number of problems. These include the issue of parallax, a spatial coordination problem, and a lack of depth perception. Thus, the surgeon bears a higher cognitive load when employing MIS techniques than with conventional open surgery because the surgeon has to work with a less natural hand-instrument-image coordination.

These problems may be exacerbated when the surgeon wishes to employ other modalities to view the procedure. A modality may be any method and/or technique for visually representing a scene. Such modalities, such as intraoperative laparoscopic ultrasound, would benefit the procedure by providing complementary information regarding the anatomy of the surgical site, and, in some cases, allowing the surgeon to see inside of an organ before making an incision or performing any other treatment and/or procedure. But employing more than one modality is often prohibitively difficult to use. This is particularly the case when the modalities are video streams displayed separately on separate monitors. Even if the different modalities are presented in a picture-in-picture or side-by-side arrangement on the

same monitor, it would not be obvious to the surgeon, or any other viewer, how the anatomical features in each video stream correspond. This is so because, the spatial relationship between the areas of interest at the surgical site, for example, surface, tissue, organs, and/or other objects imaged by the different modalities, are not aligned to the same view perspectives. As such, the same areas of interest may be positioned and oriented differently between the different modalities. This is a particular problem for modalities like ultrasound, wherein anatomical features do not obviously correspond to the same feature in optical (or white-light) video.

The problems may be further exacerbated in that the surgical site is not static but dynamic, continually changing during the surgery. For example, in laparoscopic surgery, the organs in the abdomen continually move and reshape as the surgeon explores, cuts, stitches, removes and otherwise manipulates organs and tissues inside the body cavity. Even the amount of gas inside the body cavity (used to make space for the surgical instruments) changes during the surgery, and this affects the shape or position of everything within the surgical site. Therefore, if the views from the modalities are not continuous and immediate, they may not accurately and effectively depict the current state and/or conditions of the surgical site.

While there is current medical imaging technology that superimposes a video stream using one modality on an image dataset from another modality, the image dataset is static and, therefore, not continuous or immediate. As such, the image dataset, must be periodically updated based on the position of the subject, for example the patient, and/or anatomical or other features and/or landmarks. Periodically updating and/or modifying the image dataset may introduce undue latency in the system, which may be unacceptable from a medical procedure standpoint. The undue latency may cause the image being viewed on the display by the surgeon to be continually obsolete. Additionally, relying on the positions of the subject, and/or anatomical or other features and/or landmarks to update and/or modify the image being viewed, may cause the images from the different modalities to not only be obsolete but, also, non-synchronous when viewed.

Accordingly, there currently is no medical imaging technology directed to providing composite real-time dynamic imagery from multiple modalities using two or more video streams, wherein each video stream from each modality may provide a real-time view of the medical procedure site to provide a continuous and immediate view of the current state and condition of the medical procedure site. Also, there currently is no medical imaging technology directed to providing composite imagery from multiple modalities using two or more video streams, wherein each video stream may be dynamic in that each may be synchronized to the other, and not separately to the position of the subject, and/or anatomical or other features and/or landmarks. As such, there is currently no medical imaging technology that provides composite real-time, dynamic imagery of the medical procedure site from multiple modalities.

Therefore, there is a need for a system and method of providing composite real-time dynamic imagery of a medical procedure site from multiple medical modalities, which continuously and immediately depicts the current state and condition of the medical procedure site and does so synchronously with respect to each of the modalities and without undue latency.

SUMMARY OF THE INVENTION

The present invention is directed to a system and method of providing composite real-time dynamic imagery of a

3

medical procedure site from multiple modalities which continuously and immediately depicts the current state and condition of the medical procedure site synchronously with respect to each modality and without undue latency. The composite real-time dynamic imagery may be provided by spatially registering multiple real-time dynamic video streams from the multiple modalities to each other. Spatially registering the multiple real-time dynamic video streams to each other may provide a continuous and immediate depiction of the medical procedure site with an unobstructed and detailed view of a region of interest at the medical procedure site. As such, a surgeon, or other medical practitioner, may view a single, accurate, and current composite real-time dynamic imagery of a region of interest at the medical procedure site as he/she performs a medical procedure, and thereby, may properly and effectively implement the medical procedure.

In this regard, a first real-time dynamic video stream of a scene based on a first modality may be received. A second real-time dynamic video stream of the scene based on a second modality may also be received. The scene may comprise tissues, bones, instruments, and/or other surfaces or objects at a medical procedure site and at multiple depths. The first real-time dynamic video stream and the second real-time dynamic video stream may be spatially registered to each other. Spatially registering the first real-time dynamic video stream and the second real-time dynamic video stream to each other may form a composite representation of the scene. A composite real-time dynamic video stream of the scene may be generated from the composite representation. The composite real-time dynamic video stream may provide a continuous and immediate depiction of the medical procedure site with an unobstructed and detailed view at multiple depths of a region of interest at the medical procedure site. The composite real-time dynamic video stream may be sent to a display.

The first real-time dynamic video stream may depict the scene from a perspective based on a first spatial state of a first video source. Also, the second real-time dynamic video stream may depict the scene from a perspective based on a second spatial state of a second video source. The first spatial state may comprise a displacement and an orientation of the first video source, while the second spatial state may comprise a displacement and an orientation of the second video source. The first spatial state and the second spatial state may be used to synchronously align a frame of the second real-time dynamic video stream depicting a current perspective of the scene with a frame of the first real-time dynamic video stream depicting a current perspective of the scene. In this manner, the displacement and orientation of the first video source and the displacement and orientation of the second video source may be used to accurately depict the displacement and orientation of the surfaces and objects in the scene from both of the current perspectives in the composite representation.

The first modality may be two-dimensional or three-dimensional. Additionally, the first modality may comprise endoscopy, and may be selected from a group comprising laparoscopy, hysteroscopy, thoroscopy, arthroscopy, colonoscopy, bronchoscopy, cystoscopy, proctosigmoidoscopy, esophagogastroduodenoscopy, and colposcopy. The second modality may be two-dimensional or three dimensional. Additionally, the second modality may comprise one or more modalities selected from a group comprising medical ultrasonography, magnetic resonance, x-ray imaging, computed tomography, and optical wavefront imaging. As such, a plurality, comprising any number, of video sources,

4

modalities, and real-time dynamic video streams is encompassed by the present invention.

Those skilled in the art will appreciate the scope of the present invention and realize additional aspects thereof after reading the following detailed description of the preferred embodiments in association with the accompanying drawing figures.

BRIEF DESCRIPTION OF THE DRAWING FIGURES

The accompanying drawing figures incorporated in and forming a part of this specification illustrate several aspects of the invention, and together with the description serve to explain the principles of the invention.

FIG. 1 is a schematic diagram illustrating an exemplary real-time dynamic imaging system, wherein a first real-time, dynamic video stream of a scene may be received from a first video source, and a second real-time dynamic video stream of the scene may be received from a second video source, and wherein the first real-time dynamic video stream and the second real-time dynamic video stream may be spatially registered to each other, according to an embodiment of the present invention;

FIG. 2 is a flow chart illustrating a process for generating a composite real-time dynamic video stream of the scene by spatially registering the first real-time dynamic video stream and the second real-time dynamic video stream according to an embodiment of the present invention;

FIGS. 3A, 3B, and 3C are graphical representations of the spatial registering of a frame of the first real-time dynamic video stream and a frame of the second real-time dynamic video stream to form a composite representation of the scene, according to an embodiment of the present invention;

FIGS. 4A and 4B illustrate exemplary arrangements, which may be used to determine the spatial relationship between the first video source and the second video source using the first spatial state and the second spatial state, according to an embodiment of the present invention;

FIG. 5 is a schematic diagram illustrating an exemplary real-time dynamic imaging system at a medical procedure site, wherein the first video source and the second video source are co-located, and wherein the first video source may comprise an endoscope, and wherein the second video source may comprise an ultrasound transducer, according to an embodiment of the present invention;

FIG. 6 is a schematic diagram illustrating an exemplary real-time dynamic imaging system at a medical procedure site wherein the first video source and the second video source are separately located and wherein an infrared detection system to determine the first spatial state and the second spatial state may be included, according to an embodiment of the present invention;

FIGS. 7A, 7B, and 7C are photographic representations of a frame from a laparoscopy-based real-time dynamic video stream, a frame of a two-dimensional medical ultrasonography-based real-time dynamic video stream, and a frame of a composite real-time dynamic video stream resulting from spatially registering the laparoscopy-based real-time dynamic video stream and the two-dimensional medical ultrasonography-based real-time dynamic video stream, according to an embodiment of the present invention; and

FIG. 8 illustrates a diagrammatic representation of a controller in the exemplary form of a computer system adapted to execute instructions from a computer-readable medium to perform the functions for spatially registering the first real-time dynamic video stream and the second real-

time dynamic video stream for generating the composite real-time dynamic video stream according to an embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The embodiments set forth below represent the necessary information to enable those skilled in the art to practice the invention and illustrate the best mode of practicing the invention. Upon reading the following description in light of the accompanying drawing figures, those skilled in the art will understand the concepts of the invention and will recognize applications of these concepts not particularly addressed herein. It should be understood that these concepts and applications fall within the scope of the disclosure and the accompanying claims.

The present invention is directed to a system and method of providing composite real-time, dynamic imagery of a medical procedure site from multiple modalities which continuously and immediately depicts the current state and condition of the medical procedure site synchronously with respect to each modality and without undue latency. The composite real-time dynamic imagery may be provided by spatially registering multiple real-time dynamic video streams from the multiple modalities to each other. Spatially registering the multiple real-time dynamic video streams to each other may provide a continuous and immediate depiction of the medical procedure site with an unobstructed and detailed view of a region of interest at the medical procedure site. As such, a surgeon, or other medical practitioner, may view a single, accurate, and current composite real-time dynamic imagery of a region of interest at the medical procedure site as he/she performs a medical procedure, and thereby, may properly and effectively implement the medical procedure.

In this regard, a first real-time dynamic video stream of a scene based on a first modality may be received. A second real-time dynamic video stream of the scene based on a second modality may also be received. The scene may comprise tissues, bones, instruments, and/or other surfaces or objects at a medical procedure site and at multiple depths. The first real-time dynamic video stream and the second real-time dynamic video stream may be spatially registered to each other. Spatially registering the first real-time dynamic video stream and the second real-time dynamic video stream to each other may form a composite representation of the scene. A composite real-time dynamic video stream of the scene may be generated from the composite representation. The composite real-time dynamic video stream may provide a continuous and immediate depiction of the medical procedure site with an unobstructed and detailed view at multiple depths of a region of interest at the medical procedure site. The composite real-time dynamic video stream may be sent to a display.

The first real-time dynamic video stream may depict the scene from a perspective based on a first spatial state of a first video source. Also, the second real-time dynamic video stream may depict the scene from a perspective based on a second spatial state of a second video source. The first spatial state may comprise a displacement and an orientation of the first video source, while the second spatial state may comprise a displacement and an orientation of the second video source. The first spatial state and the second spatial state may be used to synchronously align a frame of the second real-time dynamic video stream depicting a current perspective of the scene with a frame of the first real-time

dynamic video stream depicting a current perspective of the scene. In this manner, the displacement and orientation of the first video source and the displacement and orientation of the second video source may be used to accurately depict the displacement and orientation of the surfaces and objects from both of the current perspectives in the composite representation.

The first modality may be two-dimensional or three-dimensional. Additionally, the first modality may comprise laparoscopy, and may be selected from a group comprising laparoscopy, hysteroscopy, thoroscopy, arthroscopy, colonoscopy, bronchoscopy, cystoscopy, proctosigmoidoscopy, esophagogastroduodenoscopy, and colposcopy. The second modality may be two-dimensional or three dimensional. Additionally, the second modality may comprise one or more modalities selected from a group comprising medical ultrasonography, magnetic resonance, x-ray imaging, computed tomography, and optical wavefront imaging. As such, a plurality, comprising any number, of video sources, modalities, and real-time dynamic video streams is encompassed by embodiments of the present invention. Therefore, the first imaging modality may comprise a plurality of first imaging modalities and the second imaging modality may comprise a plurality of second imaging modalities.

FIG. 1 illustrates a schematic diagram of an exemplary real-time dynamic imagery system **10** for generating a composite real-time dynamic video stream of a scene from a first real-time dynamic video stream based on a first modality and a second real-time dynamic video stream based on a second modality, according to an embodiment of the present invention. FIG. 2 is a flow chart illustrating a process for generating the composite real-time dynamic video stream of a scene in the system **10** according to an embodiment of the present invention. Using a first real-time dynamic video stream based on a first modality and a second real-time dynamic video stream based on a second modality to generate a composite real-time dynamic video stream may provide a continuous and immediate depiction of the current state and condition of the scene, and at multiple depths and with unobstructed depiction of details of the scene at those depths. For purposes of the embodiment of the present invention, immediate may be understood to be 500 milliseconds or less.

Accordingly, as the scene changes the first real-time dynamic video stream and the second real-time dynamic video stream may also change, and, as such, the composite real-time dynamic video stream may also change. As such, the composite real-time dynamic video stream may be immediate in that when viewed on a display, the composite real-time dynamic video stream may continuously depict the actual current state and/or condition of the scene and, therefore, may be suitable for medical procedure sites, including, but not limited to, surgical sites. By viewing a single, accurate, and current image of the region of interest, the surgeon, or the other medical practitioner, may properly and effectively implement the medical procedure while viewing the composite real-time dynamic imagery.

In this regard, the system **10** of FIG. 1 may include a controller **12** which may comprise a spatial register **14** and a composite video stream generator **16**. The controller **12** may be communicably coupled, to a display **18**, a first video source **20**, and a second video source **22**. The first video source **20** and the second video source **22** may comprise an instrument through which an image of the scene may be captured and/or detected. Accordingly, the first video source **20** and the second video source **22** capture and/or detect images of the scene from their particular perspectives. The

first video source **20** may have a first spatial state and the second video source **22** may have a second spatial state. In this manner, the first spatial state may relate to the perspective in which the image is captured and/or detected by the first video source **20**, and the second spatial state may relate to the perspective in which the image is captured and/or detected by the second video source **22**.

The first spatial state may be represented as $[F_{\rho,\phi}]$, and the second spatial state may be represented as $[S_{\rho,\phi}]$. In FIG. 1, “ ρ ” may refer to three-dimensional displacement representing x,y,z positions, and “ ϕ ” may refer to three-dimensional orientation representing roll, pitch, and yaw, with respect to both the first video source **20** and the second video source **22**, as the case may be. By employing $[F_{\rho,\phi}]$ and $[S_{\rho,\phi}]$, the perspective of the first video source **20** viewing the scene and the perspective of the second video source **22** viewing the scene may be related to the three-dimensional displacement “ ρ ” and the three-dimensional orientation “ ϕ ” of the first video source **20** and the second video source **22**, respectively.

Accordingly, the first video source **20** and the second video source **22** capture and/or detect images of the scene from their particular perspectives. The scene may comprise a structure **24**, which may be an organ within a person’s body, and a region of interest **26** within the structure **24**. The region of interest **26** may comprise a mass, lesion, growth, blood vessel, and/or any other condition and/or any detail within the structure **24**. The region of interest **26** may or may not be detectable using visible light. In other words, the region of interest **26** may not be visible to the human eye.

The first video source **20** produces the first real-time dynamic video stream of the scene, and the second video source produces the second real-time dynamic video stream of the scene. The first real-time dynamic video stream of the scene may be a two-dimensional or three-dimensional video stream. Similarly, the second real-time dynamic video stream of the scene may be a two-dimensional or three-dimensional video stream.

FIG. 2 illustrates the process for generating a composite real-time dynamic video stream of the scene that may be based on the first real-time dynamic video stream and the second real-time dynamic video stream according to an embodiment of the present invention. The controller **12** may receive the first real-time dynamic video stream of a scene based on a first modality from a first video source having a first spatial state (step **200**). The first modality may for example comprise two-dimensional or three-dimensional endoscopy. Additionally, the first modality may be any type of endoscopy such as laparoscopy, hysteroscopy, thoroscopy, arthroscopy, colonoscopy, bronchoscopy, cystoscopy, proctosigmoidoscopy, esophagogastroduodenoscopy, and colposcopy. The controller **12** also may receive the second real-time dynamic video stream of the scene based on a second medical modality from a second video source having a second spatial state (step **202**). The second modality may comprise one or more of two-dimensional or three-dimensional medical ultrasonography, magnetic resonance imaging, x-ray imaging, computed tomography, and optical wavefront imaging. Accordingly, the present invention is not limited to only two video sources using two modalities to produce only two real-time dynamic video streams. As such, a plurality, comprising any number, of video sources, modalities, and real-time dynamic video streams is encompassed by the present invention.

The controller **12** using the spatial register **14** may then spatially register the first real-time dynamic video stream and the second real-time dynamic video stream using the

first spatial state and the second spatial state to align the first real-time dynamic video stream and the second real-time dynamic video stream to form a real-time dynamic composite representation of the scene (step **204**). The controller **12** using the composite video stream generator **16** may generate a composite real-time dynamic video stream of the scene from the composite representation (step **206**). The controller **12** may then send the composite real-time dynamic video stream to a display **18**.

Please note that for purposes of discussing the embodiments of the present invention, it should be understood that the first video source **20** and the second video source **22** may comprise an instrument through which an image of the scene may be captured and/or detected. In embodiments of the present invention in which an imaging device such as a camera, for example, may be fixably attached to the instrument, the first video source **20** and the second video source **22** may be understood to comprise the imaging device in combination with the instrument. In embodiments of the present invention in which the imaging device may not be fixably attached to the instrument and, therefore, may be located remotely from the instrument, the first video source **20** and the second video source **22** may be understood to comprise the instrument and not the imaging device.

Spatially registering the first real-time dynamic video stream and the second real-time dynamic video stream may result in a composite real-time dynamic video stream that depicts the scene from merged perspectives of the first video source **20** and the second video source **22**. FIGS. 3A, 3B, and 3C illustrate graphical representations depicting exemplary perspective views from the first video source **20** and the second video source **22**, and a sequence which may result in the merged perspectives of the first real-time dynamic video stream and the second real-time dynamic video stream, according to an embodiment of the present invention. FIGS. 3A, 3B, and 3C provide a graphical context for the discussion of the computation involving forming the composite representation, which results from the spatial registration of the first real-time dynamic video stream and the second real-time dynamic video stream.

FIG. 3A may represent the perspective view of the first video source **20**, shown as first frame **28**. FIG. 3B may represent the perspective view of the second video source **22**, shown as second frame **30**. FIG. 3C shows the second frame **30** spatially registered with the first frame **28** which may represent a merged perspective and, accordingly, a composite representation **32**, according to an embodiment of the present invention. The composite real-time dynamic video stream may be generated from the composite representation **32**. Accordingly, the composite representation may provide the merged perspective of the frame of the scene depicted by the composite real-time dynamic video stream.

The first frame **28** may show the perspective view of the first video source **20** which may use a first medical modality, for example endoscopy. The first frame **28** may depict the outside of the structure **24**. The perspective view of the structure **24** may fill the first frame **28**. In other words, the edges of the perspective view of the structure **24** may be co-extensive and/or align with the corners and sides of the first frame **28**. The second frame **30** may show the perspective view of the second video source **22** which may be detected using a second medical modality, for example medical ultrasonography. The second frame **30** may depict the region of interest **26** within the structure **24**. As with the perspective view of the structure in the first frame **28**, the perspective view of the region of interest **26** may fill the

second frame 30. The edges of the region of interest 26 may be co-extensive and/or align with the sides of the second frame 30.

Because the perspective view of the structure 24 may fill the first frame 28, and the perspective view of the region of interest 26 may fill the second frame 30, combining the first frame 28 as provided by the first video source 20 with the second frame 30 as provided by the second video source 22 may not provide a view that accurately depicts the displacement and orientation of the region of interest 26 within the structure 24. Therefore, the first frame 28 and the second frame 30 may be synchronized such that the composite representation 32 accurately depicts the actual displacement and orientation of the region of interest 26 within the structure 24. The first frame 28 and the second frame 30 may be synchronized by determining the spatial relationship between the first video source 20 and the second video source 22 based on the first spatial state and the second spatial state. Accordingly, if the first spatial state and/or the second spatial state change, the first frame 28 and/or the second frame 30 may be synchronized based on the changed first spatial state and/or changed the second spatial state. In FIG. 3C, the first frame 28 and the second frame 30 may be synchronized by adjusting the second frame 30 to be co-extensive and/or aligned with the corners and the sides of the first frame 28. The spatial relationship may then be used to spatially register the second frame 30 with the first frame 28 to form the composite representation 32. The composite representation 32 may then depict the actual displacement and orientation of the region of interest 26 within the structure 24 synchronously with respect to the first real-time dynamic video stream and the second real-time video stream.

Spatially registering the first real-time dynamic video stream and the second real-time dynamic video stream may be performed using calculations involving the first spatial state of the first video source 20, and the second spatial state of the second video source 22. The first spatial state and the second spatial state each comprise six degrees of freedom. The six degrees of freedom may comprise a displacement representing x, y, z positions which is collectively referred to herein as "ρ," and orientation representing roll, pitch, and yaw which is collectively referred to herein as "φ." Accordingly, the first spatial state may be represented as $[F_{\rho,\phi}]$, and the second spatial state may be represented as $[S_{\rho,\phi}]$. The first spatial state and the second spatial state may be used to determine the spatial relationship between the first video source 20 and the second video source 22, which may be represented as $[C_{\rho,\phi}]$.

The first spatial state $[F_{\rho,\phi}]$ may be considered to be a transformation between the coordinate system of the first video source 20 and some global coordinate system G, and the second spatial state $[S_{\rho,\phi}]$ may be considered to be a transformation between the coordinate system of the second video source 22 and the same global coordinate system G. The spatial relationship $[C_{\rho,\phi}]$, then, may be considered as a transformation from the coordinate system of the second video source 22, to the coordinate system of the first video source 20.

As transforms, $[C_{\rho,\phi}]$, $[F_{\rho,\phi}]$, and $[S_{\rho,\phi}]$ may each be represented in one of three equivalent forms:

- 1) Three-dimensional displacement "ρ" as [tx, ty, tz] and three-dimensional orientation "φ" as [roll, pitch, yaw]; or
- 2) Three-dimensional displacement "ρ" as [tx, ty, tz] and three-dimensional orientation "φ" as a unit quaternion [qx, qy, qz, qw]; or

3) A 4-by-4 (16 element) matrix.

Form 1 has the advantage of being easiest to use. Form 2 has the advantage of being subject to less round-off error during computations, for example it avoids gimbal lock, a mathematical degeneracy problem. Form 3 is amendable to modern computer-graphics hardware, which has dedicated machinery for composing, transmitting, and computing 4-by-4 matrices.

In some embodiments, where the first video source 20 and second video source 22 do not move with respect to each other, the spatial relationship $[C_{\rho,\phi}]$ between the first video source 20 and the second video source 22 is constant and may be measured directly. Alternatively, if embodiments where the first video source 20 and the second video source 22 move relative to each other, the spatial relationship between the first video source 20 and the second video source 22 may be continually measured by a position detecting system. The position detecting system may measure an output $[C_{\rho,\phi}]$ directly, or it may measure and report the first spatial state $[F_{\rho,\phi}]$, the second spatial state $[S_{\rho,\phi}]$. In the latter case, $[C_{\rho,\phi}]$ can be computed as $[C_{\rho,\phi}]$ and $[C_{\rho,\phi}]$ as follows:

$$[C_{\rho,\phi}] = [F_{\rho,\phi}]^* [S_{\rho,\phi}]^{-1} \text{ (indirect computation).}$$

The three-dimensional position of the corner points of the second frame 30, relative to the center of the second frame 30, are constants which may be included in the specification sheets of the second video source 22. There are four (4) such points if the second video source 22 is two-dimensional, and eight (8) such points if the second video source 22 is three-dimensional. For each such corner point, three-dimensional position relative to the first video source 20 may be computed using the formula:

$$c_s = c_f^* [C_{\rho,\phi}],$$

where c_f is the second frame 30 corner point relative to the second video source 22, and c_s is the second frame 30 corner point relative to first video source 20.

If either the first video source 20 or the second video source 22 comprise a video camera, then the field-of-view of the video camera, and the frame, may be given by the manufacturer. The two-dimensional coordinates of the corner points (s_x, s_y) of the second frame 30 in the first frame 28 may be computed as follows:

$$c_{sp} = (c_s^* [P]),$$

$$\text{where } P = \begin{bmatrix} \cos(f) & 0 & 0 & 0 \\ 0 & \cos(f) & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \end{bmatrix},$$

and f=the field of view of the first video source 20.

c_{sp} is a four (4) element homogenous coordinate consisting of $[x_{csp}, y_{csp}, z_{csp}, h_{csp}]$. The two-dimensional coordinates are finally computed as:

$$s_x = x_{csp} / h_{csp}; \text{ and}$$

$$s_y = y_{csp} / h_{csp}.$$

By knowing s_x and s_y , for all the corners of the second frame 30 relative to the first frame 28 standard compositing hardware may be used to overlay and, thereby, spatially registering the first real-time dynamic video stream and the second real-time dynamic video stream to generate the composite real-time dynamic video stream. As such the

spatial registration of the first real-time dynamic video stream and the second real-time dynamic video stream may be performed using information other than an anatomical characteristic and/or a position of the subject (i.e. a person's body), the world, or some other reference coordinate system. Accordingly, the composite real-time dynamic video stream may be generated independently of the position or condition of the subject, the location and/or existence of anatomical features and/or landmarks, and/or the condition or state of the medical procedure site.

The determination whether to directly or indirectly compute the spatial relationship between the first video source 20 and the second video source 22 may depend on an arrangement of components of the system, and a method used to establish the first spatial state of the first video source 20 and the second spatial state of the second video source 22.

FIGS. 4A and 4B are schematic diagrams illustrating alternative exemplary arrangements of components in which the direct computation or the indirect computation for determining the spatial relationship between the first video source 20 and the second video source 22 may be used.

FIG. 4A illustrates an exemplary arrangement in which the direct computation of the spatial relationship between the first video source 20 and the second video source 22 may be used, according to an embodiment of the present invention. An articulated mechanical arm 34 may connect the first video source 20 and the second video source 22. The mechanical arm 34 may be part of and/or extend to an instrument or other structure, which supports and/or allows the use of the mechanical arm 34, and thereby the first video source 20 and the second video source 22. The mechanical arm 34 may provide a rigid connection between the first video source 20 and the second video source 22. In such a case, because the mechanical arm may be rigid, the first spatial state of the first video source 20 and the second spatial state of the second video source 22 may be fixed.

Accordingly, because the first spatial state and the second spatial state may be fixed, the first spatial state and the second spatial state may be programmed or recorded in the controller 12. The controller 12 may then directly compute the spatial relationship between the first video source 20 and the second video source 22 and, therefrom, the composite representation 32. As discussed above, the composite representation 32 represents the spatial registration of the first real-time dynamic video stream and the second real-time dynamic video stream. The controller 12 may then generate the composite real-time dynamic video stream from the composite representation 32.

Alternatively, the mechanical arm 34 may comprise joints 34A, 34B, 34C connecting rigid portions or links 34D, 34E of the mechanical arm 34. The joints 34A, 34B, 34C may include rotary encoders for measuring and encoding the angle of each of the joints 34A, 34B, 34C. By measuring the angle of the joints 34A, 34B, 34C and knowing the length of the links 34D, 34E, the first spatial state $[C_{p,\phi}]$ of the second video source 22, relative to that of the first video source 20 may be determined. The controller 12 may receive $[C_{p,\phi}]$ and, therefrom, compute the composite representation 32. As discussed above, the composite representation 32 represents the spatial registration of the first real-time dynamic video stream and the second real-time dynamic video stream. The controller 12 may generate the composite real-time dynamic video stream from the composite representation. The mechanical arm 34 may be a Faro-arm™ mechanical arms or any similar component that provides the functionality described above.

FIG. 4B illustrates an exemplary arrangement where the indirect computation of the spatial relationship between the first video source 20 and the second video source 22 may be used, according to an embodiment of the present invention.

In FIG. 4B, an intermediary in the form of a positions detecting system comprising a first transmitter 36, a second transmitter 38, and an infrared detection system 40 are shown. The first transmitter 36 and the second transmitter 38 may be in the form of LED's. The infrared detection system 40 may comprise one or more infrared detectors 40A, 40B, 40C. The infrared detectors 40A, 40B, 40C may be located or positioned to be in lines-of-sight of the first transmitter 36 and the second transmitter 38. The lines-of-sight are shown in FIG. 4B by lines emanating from the first transmitter 36 and the second transmitter 38.

The infrared detection system 40 may determine the first spatial state of the first video source 20 and the second spatial state of the second video source 22 by detecting the light emitted from the first transmitter 36 and the second transmitter 38, respectively. The infrared detection system 40 may also determine the intermediary reference related to the position of the infrared detection system 40. The infrared detection system 40 may then send the first spatial state of the first video source 20, represented as $[F_{p,\phi}]$, and the second spatial state of the second video source 22, represented as $[S_{p,\phi}]$, to the controller 12. The controller 12 may receive the first spatial state and the second spatial state, and may compute the spatial relationship $[C_{p,\phi}]$ between the first video source 20 and the second video source 22 using the indirect computation and, therefrom, the composite representation 32. As discussed above, the composite representation 32 represents the spatial registration of the first real-time dynamic video stream and the second real-time dynamic video stream. The controller 12 may then generate the composite real-time dynamic video stream from the composite representation 32.

The infrared detection system 40 may be any type of optoelectronic system for example the Northern Digital Instrument Optotrak™. Alternatively, other position detecting systems may be used such as magnetic, GPS+ compass, inertial, acoustic, or any other equipment for measuring spatial relationship, or relative or absolute displacement and orientation.

FIGS. 5 and 6 are schematic diagrams illustrating exemplary systems in which the exemplary arrangements discussed with respect to FIGS. 4A and 4B may be implemented in medical imaging systems based on the system 10 shown in FIG. 1, according to an embodiment of the present invention. FIGS. 5 and 6 each illustrate systems for generating composite real-time dynamic video streams using medical modalities comprising ultrasonography and endoscopy. Accordingly, FIGS. 5 and 6 comprise additional components and detail than which are shown in system 10 to discuss the present invention with respect to ultrasonography and endoscopy. However, it should be understood that the present invention is not limited to any particular modality, including any particular medical modality.

FIG. 5 is a schematic diagram illustrating a system 10' comprising an endoscope 42 and an ultrasound transducer 44 combined in a compound minimally-invasive instrument 48, according to an embodiment of the present invention. FIG. 5 is provided to illustrate an exemplary system in which the direct computation of the spatial relationship between the first video source 20 and the second video source 22 may be used. The compound minimally-invasive

instrument 48 may be used to provide images of the scene based on multiple medical modalities using a single minimally-invasive instrument.

The compound minimally-invasive instrument 48 may penetrate into the body 46 of the subject, for example the patient, to align with the structure 24 and the region of interest 26 within the structure 24. In this embodiment, the structure 24 may be an organ within the body 46, and the region of interest 26 may be a growth or lesion within the structure 24. A surgeon may use the compound minimally-invasive instrument 48 to provide both an endoscopic and ultrasonographic composite view to accurately target the region of interest 26 for any particular treatment and/or procedure.

The endoscope 42 may be connected, either optically or in some other communicable manner to a first video camera 50. Accordingly, the first video source 20 may be understood to comprise the endoscope 42 and the first video camera 50. The first video camera 50 may capture an image of the structure 24 through the endoscope 42. From the image captured by the first video camera 50, the first video camera 50 may produce a first real-time dynamic video stream of the image and send the first real-time dynamic video stream to the controller 12.

The ultrasound transducer 44 may be communicably connected to a second video camera 52. Accordingly, the second video source 22 may be understood to comprise the ultrasound transducer 44 and the second video camera 52. The ultrasound transducer 44 may detect an image of the region of interest 26 within the structure 24 and communicate the image detected to the second video camera 52. The second video camera 52 may produce a second real-time dynamic video stream representing the image detected by the ultrasound transducer 44, and then send the second real-time dynamic video stream to the controller 12.

Because the compound minimally-invasive instrument 48 comprises both the endoscope 42 and the ultrasound transducer 44, the first spatial state and the second spatial state may be fixed with respect to each other, and, accordingly, the spatial relationship of the first video source 20 and the second video source 22 may be determined by the direct computation discussed above with reference to FIG. 4A. This may be so even if the first video camera 50 and the second video camera 52, as shown in FIG. 5, are located remotely from the compound minimally-invasive instrument 48. In other words, the first video camera 50 and the second video camera 52 may not be included within the compound minimally-invasive instrument 48. As discussed above, the first spatial state and the second spatial state may be determined relative to a particular perspective of the image of the scene that is captured and/or detected. As such the first spatial state may be based on the position and displacement of the endoscope 42, while the second spatial state may be based on the displacement and position of the ultrasound transducer 44.

The first spatial state and the second spatial state may be received by the controller 12. The controller 12 may then determine the spatial relationship between the first video source 20, and the second video source 22 using the direct computation discussed above. Using the spatial relationship, the first real-time dynamic video stream and the second real-time dynamic video stream may be spatially registered to generate the composite representation 32. The composite real-time dynamic video stream may be generated from the composite representation 32. The controller 12 may then send the composite real-time dynamic video stream to the display 18.

FIG. 6 is a schematic diagram illustrating a system 10" comprising a separate endoscope 42 and an ultrasound transducer 44, according to an embodiment of the present invention; in this embodiment, the endoscope 42 comprises a laparoscope, and the ultrasound transducer 44 comprises a laparoscopic ultrasound transducer. FIG. 6 is provided to illustrate an exemplary system in which the direct computation of the spatial relationship between the first video source 20 and the second video source 22 may be used.

Accordingly, in FIG. 6, instead of one minimally-invasive instrument penetrating the body 46, two minimally-invasive instruments are used. The endoscope 42 may align with the structure 24. The ultrasound transducer 44 may extend further into the body 46 and may contact the structure 24 at a point proximal to the region of interest 26. In a similar manner to the system 10', the structure 24 may be an organ within the body 46, and the region of interest 26 may be a blood vessel, growth, or lesion within the structure 24. A surgeon may use the endoscope 42 and the ultrasound transducer 44 to provide a composite view of the structure 24 and the region of interest 26 to accurately target the region of interest 26 point on the structure 24 for any particular treatment and/or procedure.

To provide one of the images of the composite view for the surgeon, the endoscope 42 may be connected, either optically or in some other communicable manner, to a first video camera 50. Accordingly, the first video source 20 may be understood to comprise the endoscope 42 and the first video camera 50. The first video camera 50 may capture an image of the structure 24 through the endoscope 42. From the image captured by the first video camera 50, the first video camera 50 may produce a first real-time dynamic video stream of the image and send the first real-time dynamic video stream to the controller 12.

Additionally, to provide another image of the composite view for the surgeon, the ultrasound transducer 44 may be communicably connected to a second video camera 52. Accordingly, the second video source 22 may be understood to comprise the ultrasound transducer 44 and the second video camera 52. The ultrasound transducer 44 may detect an image of the region of interest 26 within the structure 24 and communicate the image detected to the second video camera 52. The second video camera 52 may produce a second real-time dynamic video stream representing the image detected by the ultrasound transducer 44 and then send the second real-time dynamic video stream to the controller 12.

Because the endoscope 42 and the ultrasound transducer 44 are separate, the first spatial state of the first video source 20 and the second spatial state of the second video source 22 may be determined using the indirect computation discussed above with reference to FIG. 4B. As discussed above, the indirect computation involves the use of an intermediary, such as a positional system. Accordingly, in system 10", an intermediary comprising a first transmitter 36, a second transmitter 38 and an infrared detection system 40 may be included. The first transmitter 36 may be located in association with the endoscope 42, and the second transmitter 38 may be located in association with the ultrasound transducer 44. Associating the first transmitter 36 with the endoscope 42 and the second transmitter 38 with the ultrasound transducer 44 may allow the first video camera 50 to be located remotely from the endoscope 42, and/or the second video camera 52 to be located remotely from the ultrasound transducer 44.

As discussed above with respect to the system 10', the first spatial state and the second spatial state may be determined

with respect to the particular perspectives of the image of the scene that may be captured and/or detected by the first video source 20 and the second video source 22, respectively. As such the first spatial state may be based on the orientation and displacement of the endoscope 42, while the second spatial state may be based on the displacement and orientation of the ultrasound transducer 44. Additionally, in system 10' of FIG. 5, the endoscope 42 and the ultrasound transducer 44 are shown in a co-located arrangement in the compound minimally-invasive instrument 48. As such, the first spatial state of the first video source 20 and the second spatial state of the of the second video source 22 in addition to being fixed may also be very close relationally. Conversely, in the system 10", the orientation and displacement of the endoscope 42 and the ultrasound transducer 44 may be markedly different as shown in FIG. 6, which may result in the first spatial state of the first video source 20 and the second spatial state of the second video source 22 not being close relationally.

The infrared detection system 40 may determine the first spatial state of the first video source 20 and the second spatial state of the second video source 22 by detecting the light emitted from the first transmitter 36 and the second transmitter 38, respectively. The infrared detection system 40 may also determine the intermediary reference related to the position of the infrared detection system 40. The infrared detection system 40 may then send the first spatial state, the second spatial state, and the intermediary reference to the controller 12. The controller 12 may receive the first spatial state, the second spatial state, and the intermediary reference and may compute the spatial relationship between the first video source 20 and the second video source 22 using the indirect computation and, therefrom, the composite representation 32. As discussed above, the composite representation 32 represents the spatial registration of the first real-time dynamic video stream and the second real-time dynamic video stream. The controller 12 may then generate the composite real-time dynamic video stream from the composite representation 32.

For purposes of the present invention, the controller 12 may be understood to comprise devices, components and systems not shown in system 10' and system 10" in FIGS. 5 and 6. For example, the controller 12 may be understood to comprise an ultrasound scanner, which may be a Sonosite MicroMaxx, or similar scanner. Also, the controller 12 may comprise a video capture board, which may be a Foresight Imaging Accustream 170, or similar board. An exemplary video camera suitable for use in the system 10' and system 10" of FIGS. 5 and 6 is the Stryker 988 that has a digital IEEE 1394 output, although other digital and analog cameras may be used. The endoscope may be any single or dual optical path laparoscope, or similar endoscope.

FIGS. 7A, 7B, and 7C are photographic representations illustrating a first frame 54 from the first real-time dynamic video stream, a second frame 56 from the second real-time dynamic video stream, and a composite frame 58 of the composite real-time dynamic video stream generated from the spatial registration of the first real-time dynamic video stream and the second real-time dynamic video stream, according to an embodiment of the present invention. FIGS. 7A, 7B, and 7C are provided to further illustrate an embodiment of the present invention with reference to actual medical modalities, and the manner in which the composite real-time dynamic video stream based on multiple modalities may appear to a surgeon viewing a display.

In FIG. 7A, the first real-time dynamic video stream may be produced based on an endoscopic modality. In FIG. 7B,

the second real-time dynamic video stream may be produced based on medical ultrasonographic modality. In FIG. 7A, the first real-time dynamic video stream shows the structure 24 in the form of an organ of the human body being contacted by an ultrasound transducer 44. FIG. 7B shows the second real-time dynamic video stream is produced using the ultrasound transducer 44 shown in FIG. 7A. In FIG. 7B the region of interest 26, which appears as blood vessels within the structure 24 is shown. In FIG. 7C, the composite real-time dynamic video stream generated shows the first real-time dynamic video stream and the second real-time dynamic video stream spatially registered. The second real-time dynamic video stream is merged with the first real-time dynamic video stream in appropriate alignment. As such the second real-time dynamic video stream is displaced and oriented in a manner as reflects the actual displacement and orientation of the region of interest 26 within the structure 24. In other words, the region of interest 26 is shown in the composite real-time dynamic video stream as it would appear if the surface of the structure 24 were cut away to make the region of interest 26 visible.

FIG. 8 illustrates a diagrammatic representation of what a controller 12 adapted to execute functioning and/or processing described herein. In the exemplary form, the controller may comprise a computer system 60, within which is a set of instructions for causing the controller 12 to perform any one or more of the methodologies discussed herein. The controller may be connected (e.g., networked) to other controllers or devices in a local area network (LAN), an intranet, an extranet, or the Internet. The controller 12 may operate in a client-server network environment, or as a peer controller in a peer-to-peer (or distributed) network environment. While only a single controller is illustrated, the controller 12 shall also be taken to include any collection of controllers and/or devices that individually or jointly execute a set (or multiple sets) of instructions to perform any one or more of the methodologies discussed herein. The controller 12 may be a server, a personal computer, a mobile device, or any other device.

The exemplary computer system 60 includes a processor 62, a main memory 64 (e.g., read-only memory (ROM), flash memory, dynamic random access memory (DRAM) such as synchronous DRAM (SDRAM) or Rambus DRAM (RDRAM), etc.), and a static memory 66 (e.g., flash memory, static random access memory (SRAM), etc.), which may communicate with each other via a bus 68. Alternatively, the processor 62 may be connected to the main memory 64 and/or the static memory 66 directly or via some other connectivity means.

The processor 62 represents one or more general-purpose processing devices such as a microprocessor, central processing unit, or the like. More particularly, the processing device may be complex instruction set computing (CISC) microprocessor, reduced instruction set computing (RISC) microprocessor, very long instruction word (VLIW) microprocessor, or processor implementing other instruction sets, or processors implementing a combination of instruction sets. The processor 62 is configured to execute processing logic 70 for performing the operations and steps discussed herein.

The computer system 60 may further include a network interface device 72. It also may include an input means 74 to receive input (e.g., the first real-time dynamic video stream, the second real-time dynamic video stream, the first spatial state, the second spatial state, and the intermediary reference) and selections to be communicated to the processor 62 when executing instructions. It also may include

an output means 76, including but not limited to the display 18 (e.g., a head-mounted display, a liquid crystal display (LCD), or a cathode ray tube (CRT)), an alphanumeric input device (e.g., a keyboard), and/or a cursor control device (e.g., a mouse).

The computer system 60 may or may not include a data storage device having a computer-readable medium 78 on which is stored one or more sets of instructions 80 (e.g., software) embodying any one or more of the methodologies or functions described herein. The instructions 80 may also reside, completely or at least partially, within the main memory 64 and/or within the processor 62 during execution thereof by the computer system 60, the main memory 64, and the processor 62 also constituting computer-readable media. The instructions 80 may further be transmitted or received over a network via the network interface device 72.

While the computer-readable medium 78 is shown in an exemplary embodiment to be a single medium, the term "computer-readable medium" should be taken to include a single medium or multiple media (e.g., a centralized or distributed database, and/or associated caches and servers) that store the one or more sets of instructions. The term "computer-readable medium" shall also be taken to include any medium that is capable of storing, encoding, or carrying a set of instructions for execution by the controller and that cause the controller to perform any one or more of the methodologies of the present invention. The term "computer-readable medium" shall accordingly be taken to include, but not be limited to, solid-state memories, optical and magnetic media, and carrier wave signals.

Those skilled in the art will recognize improvements and modifications to the preferred embodiments of the present invention. All such improvements and modifications are considered within the scope of the concepts disclosed herein and the claims that follow.

What is claimed is:

1. A method of medical procedure image guidance, comprising the steps of:

- receiving real-time first spatial state data associated with a first medical device;
- obtaining first medical imaging data associated with the first medical device;
- receiving real-time second spatial state data associated with a second medical device that is different from the first medical device;
- obtaining second medical imaging data associated with the second medical device;
- determining, using one or more processors, a spatial relationship between the first medical device and the second medical device based at least in part on the first spatial state data and the second spatial state data; and causing a display device to display composite medical imaging data comprising at least a portion of the first medical imaging data and at least a portion of the second medical imaging data based at least in part on the determined spatial relationship between the first medical device and the second medical device.

2. The method of claim 1, further comprising spatially registering the first medical imaging data with the second medical imaging data based at least on the first spatial state data associated with the first medical device and the second spatial state data associated with the second medical device.

3. The method of claim 1, wherein the first medical device is usable in at least one of laparoscopy, hysteroscopy, thoroscopy, arthroscopy, colonoscopy, bronchoscopy, cystoscopy, proctosigmoidoscopy, esophagogastroduodenoscopy, and colposcopy.

4. The method of claim 1, wherein the first medical device is usable in at least one of ultrasonography, magnetic resonance imaging, x-ray imaging, computed tomography, and optical wavefront imaging.

5. The method of claim 1, wherein the first medical imaging data comprises video.

6. The method of claim 1, wherein the first medical device comprises a two-dimensional modality.

7. The method of claim 1, wherein, the first medical device comprises a three-dimensional modality.

8. The method of claim 1, wherein the second medical device comprises a two-dimensional modality.

9. The method of claim 1, wherein the second medical device comprises a three-dimensional modality.

10. The method of claim 1, wherein the second medical device comprises an invasive medical device.

11. A system for medical procedure image guidance, comprising: an image guidance system, wherein the image guidance system is configured to:

- receive real-time first spatial state data associated with a first medical device;

- obtain first medical imaging data associated with the first medical device;

- receive real-time second spatial state data associated with a second medical device that is different from the first medical device;

- obtain second medical imaging data associated with the second medical device;

- determine a spatial relationship between the first medical device and the second medical device based at least in part on the first spatial state data and the second spatial state data; and

- cause a display device to display composite medical imaging data comprising at least a portion of the first medical imaging data and at least a portion of the second medical imaging data based at least in part on the determined spatial relationship between the first medical device and the second medical device.

12. The system of claim 11, wherein the image guidance system is configured to spatially register the first medical imaging data with the second medical imaging data based at least on the first spatial state data associated with the first medical device and the second spatial state data associated with the second medical device.

13. The system of claim 11, wherein the first medical device comprises a plurality of first modalities.

14. The system of claim 11, wherein the second medical device comprises a plurality of second modalities.

15. The system of claim 11, wherein the first medical device is usable in at least one of ultrasonography, magnetic resonance imaging, x-ray imaging, computed tomography, and optical wavefront imaging.

16. The system of claim 11, wherein the first medical device is usable in at least one of laparoscopy, hysteroscopy, thoroscopy, arthroscopy, colonoscopy, bronchoscopy, cystoscopy, proctosigmoidoscopy, esophagogastroduodenoscopy, and colposcopy.

17. A computer-readable non-transitory storage medium comprising instructions operable to execute on a computer system, said instructions when executing on said computer system cause the computer system to:

- receive real-time first spatial state data associated with a first medical device;

- obtain first medical imaging data associated with the first medical device;

19

receive real-time second spatial state data associated with
a second medical device that is different from the first
medical device;
obtain second medical imaging data associated with the
second medical device; 5
determine a spatial relationship between the first medical
device and the second medical device based at least in
part on the first spatial state data and the second spatial
state data; and
cause a display device to display composite medical 10
imaging data comprising at least a portion of the first
medical imaging data and at least a portion of the
second medical imaging data based at least in part on
the determined spatial relationship between the first
medical device and the second medical device. 15

* * * * *

20

专利名称(译)	使用多种模态提供医疗过程站点的实时动态图像的系统和方法		
公开(公告)号	US9659345	公开(公告)日	2017-05-23
申请号	US13/936951	申请日	2013-07-08
[标]申请(专利权)人(译)	INNEROPTIC TECH		
申请(专利权)人(译)	INNEROPTIC TECHNOLOGY , INC.		
当前申请(专利权)人(译)	INNEROPTIC TECHNOLOGY , INC.		
[标]发明人	RAZZAQUE SHARIF A KELLER KURTIS P STATE ANDREI GREEN CAROLINE K ACKERMAN JEREMY D		
发明人	RAZZAQUE, SHARIF A KELLER, KURTIS P STATE, ANDREI GREEN, CAROLINE K ACKERMAN, JEREMY D		
IPC分类号	H04N7/18 G06T3/00 A61B1/00 A61B1/04 A61B8/12 A61B8/00 A61B8/08 A61B1/313		
CPC分类号	G06T3/0087 A61B1/0005 A61B1/042 A61B8/12 A61B8/463 A61B8/5238 H04N7/181 A61B1/313		
优先权	60/856670 2006-11-06 US 60/834932 2006-08-02 US		
其他公开文献	US20140016848A1		
外部链接	Espacenet USPTO		

摘要(译)

公开了一种从多种模态提供医疗手术部位的复合实时动态图像的系统和方法，所述多种模态连续且立即地描绘医疗手术部位的当前状态和状态，并且相对于每种模态同步且没有不适当的等待时间。可以通过将来自多个模态的多个实时动态视频流空间地注册到彼此来提供复合实时动态图像。空间地将多个实时动态视频流彼此注册可以提供医疗过程站点的连续且直接的描绘，其具有在多个深度处的医疗过程站点处的感兴趣区域的无障碍和详细视图。因此，外科医生或其他医疗从业者可以在他/她执行医疗程序时在医疗过程现场查看感兴趣区域的单个，准确且当前的复合实时动态图像，从而可以正确地并有效实施医疗程序。

