



US007297153B2

(12) **United States Patent**  
**Kieturakis et al.**

(10) **Patent No.:** **US 7,297,153 B2**  
 (45) **Date of Patent:** **\*Nov. 20, 2007**

(54) **APPARATUS AND METHOD FOR  
 DEVELOPING AN ANATOMIC SPACE FOR  
 LAPAROSCOPIC HERNIA REPAIR AND  
 PATCH FOR USE THEREWITH**

(75) Inventors: **Maciej J. Kieturakis**, San Carlos, CA  
 (US); **Kenneth H. Mollenauer**, Santa  
 Clara, CA (US); **Michelle Y. Monfort**,  
 Los Gatos, CA (US); **Helmut L.  
 Kayan**, Redwood City, CA (US)

(73) Assignee: **General Surgical Innovations, Inc.**,  
 North Haven, CT (US)

(\*) Notice: Subject to any disclaimer, the term of this  
 patent is extended or adjusted under 35  
 U.S.C. 154(b) by 88 days.

This patent is subject to a terminal dis-  
 claimer.

(21) Appl. No.: **11/208,672**

(22) Filed: **Aug. 22, 2005**

(65) **Prior Publication Data**

US 2006/0036277 A1 Feb. 16, 2006

**Related U.S. Application Data**

(60) Continuation of application No. 10/117,765, filed on  
 Apr. 5, 2002, now Pat. No. 6,953,467, which is a  
 continuation of application No. 08/861,913, filed on  
 May 22, 1997, now Pat. No. 6,368,337, which is a  
 continuation of application No. 08/483,293, filed on  
 Jun. 7, 1995, now abandoned, which is a division of  
 application No. 08/124,283, filed on Sep. 20, 1993,  
 now Pat. No. 5,836,961, which is a continuation-in-  
 part of application No. 07/893,988, filed on Jun. 2,  
 1992, now Pat. No. 6,312,442.

(51) **Int. Cl.**  
**A61B 17/00** (2006.01)  
**A61B 1/32** (2006.01)  
**A61M 29/00** (2006.01)

(52) **U.S. Cl.** ..... **606/190; 606/192; 600/207**

(58) **Field of Classification Search** ..... None  
 See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

1,213,005 A 1/1917 Pillsbury

(Continued)

**FOREIGN PATENT DOCUMENTS**

DE 2157727 8/1973

(Continued)

**OTHER PUBLICATIONS**

U.S. Appl. No. 10/884,573, Kieturakis, et al. allowed, not yet  
 issued.\*



(Continued)

*Primary Examiner*—Glenn K. Dawson

(57) **ABSTRACT**

An apparatus for creating an anatomic space in tissue in a  
 body comprises an introducer and a sheath. The tubular  
 sheath may surround the introducer, and may have a weak-  
 ened region along its longitudinal axis. A handle may be  
 provided on the sheath. The handle may be adapted to be  
 pulled proximally to separate the weakened region and allow  
 the sheath to be removed from the introducer. The sheath  
 may be secured to the introducer via detents or latches on the  
 handle.

**16 Claims, 18 Drawing Sheets**



| U.S. PATENT DOCUMENTS |         |                   |               |         |                                |
|-----------------------|---------|-------------------|---------------|---------|--------------------------------|
| 2,854,983 A           | 10/1958 | Baskin            | 5,104,383 A   | 4/1992  | Shichman                       |
| 2,936,760 A           | 5/1960  | Gants             | 5,116,318 A   | 5/1992  | Hillstead                      |
| 3,039,468 A           | 6/1962  | Price             | 5,116,357 A   | 5/1992  | Eberbach                       |
| 3,253,594 A           | 5/1966  | Matthews et al.   | 5,122,122 A   | 6/1992  | Allgood                        |
| 3,417,745 A           | 12/1968 | Sheldon           | 5,122,155 A   | 6/1992  | Eberbach                       |
| 3,459,175 A           | 8/1969  | Miller            | 5,137,512 A   | 8/1992  | Burns et al.                   |
| 3,545,443 A           | 12/1970 | Ansari et al.     | 5,141,494 A   | 8/1992  | Danforth et al.                |
| 3,774,596 A           | 11/1973 | Cook              | 5,141,515 A   | 8/1992  | Eberbach                       |
| 3,800,788 A           | 4/1974  | White             | 5,147,302 A   | 9/1992  | Euteneuer et al.               |
| 3,863,639 A           | 2/1975  | Kleveland         | 5,147,316 A   | 9/1992  | Castillenti                    |
| 3,882,852 A           | 5/1975  | Sinnreich         | 5,147,374 A   | 9/1992  | Fernandez                      |
| 3,915,171 A           | 10/1975 | Shermeta          | 5,152,278 A   | 10/1992 | Clayman                        |
| RE29,207 E            | 5/1977  | Boldac et al.     | 5,158,545 A   | 10/1992 | Trudell et al.                 |
| 4,077,412 A           | 3/1978  | Moossun           | 5,159,925 A   | 11/1992 | Neuwirth et al.                |
| 4,083,369 A           | 4/1978  | Sinnreich         | 5,163,949 A   | 11/1992 | Bonutti                        |
| 4,177,814 A           | 12/1979 | Knepshield et al. | 5,176,128 A   | 1/1993  | Andrese                        |
| 4,198,981 A           | 4/1980  | Sinnreich         | 5,176,649 A   | 1/1993  | Wakabayshi                     |
| 4,217,889 A           | 8/1980  | Radovan et al.    | 5,176,692 A   | 1/1993  | Wilk et al.                    |
| 4,243,050 A           | 1/1981  | Littleford        | 5,183,463 A   | 2/1993  | Debbas                         |
| 4,276,874 A           | 7/1981  | Wolvek et al.     | 5,183,465 A   | 2/1993  | Xanthakos et al.               |
| 4,312,353 A           | 1/1982  | Shahbadian        | 5,188,596 A   | 2/1993  | Condon et al.                  |
| 4,345,606 A           | 8/1982  | Littleford        | 5,188,630 A   | 2/1993  | Christoudias                   |
| 4,411,654 A           | 10/1983 | Boarini           | 5,190,541 A   | 3/1993  | Abele et al.                   |
| 4,490,137 A           | 12/1984 | Moukheibir        | 5,195,506 A   | 3/1993  | Hulfish                        |
| 4,496,345 A           | 1/1985  | Hasson            | 5,195,507 A   | 3/1993  | Bilweis                        |
| 4,501,266 A           | 2/1985  | McDaniel          | 5,197,971 A   | 3/1993  | Bonutti                        |
| 4,555,242 A           | 11/1985 | Saudagar          | 5,201,742 A   | 4/1993  | Hasson                         |
| 4,574,806 A           | 3/1986  | McCarthy          | 5,201,752 A   | 4/1993  | Brown et al.                   |
| 4,581,025 A           | 4/1986  | Timmermans        | 5,201,754 A   | 4/1993  | Crittenden et al.              |
| 4,589,868 A           | 5/1986  | Dretler           | 5,209,725 A   | 5/1993  | Roth                           |
| 4,593,682 A           | 6/1986  | Hekele            | 5,215,526 A   | 6/1993  | Deniega et al.                 |
| 4,596,554 A           | 6/1986  | Dastgeer          | 5,220,928 A   | 6/1993  | Oddsens et al.                 |
| 4,596,559 A           | 6/1986  | Fleischhacker     | 5,222,970 A   | 6/1993  | Reeves                         |
| 4,610,662 A           | 9/1986  | Weikl et al.      | 5,226,429 A   | 7/1993  | Kuzmak                         |
| 4,644,936 A           | 2/1987  | Schiff            | 5,226,890 A   | 7/1993  | Ianniruberto et al.            |
| 4,651,717 A           | 3/1987  | Jakubczak         | 5,232,446 A   | 8/1993  | Arney                          |
| 4,654,030 A           | 3/1987  | Moll              | 5,258,026 A   | 11/1993 | Johnson et al.                 |
| 4,685,447 A           | 8/1987  | Iversen et al.    | 5,261,888 A   | 11/1993 | Semm                           |
| 4,706,670 A           | 11/1987 | Andersen et al.   | 5,267,965 A   | 12/1993 | Deniega                        |
| 4,738,666 A           | 4/1988  | Fuqua             | 5,269,753 A   | 12/1993 | Wilk                           |
| 4,754,030 A           | 6/1988  | Kaplan et al.     | 5,284,474 A   | 2/1994  | Adair                          |
| 4,769,038 A           | 9/1988  | Bendavid et al.   | 5,290,249 A   | 3/1994  | Foster et al.                  |
| 4,772,266 A           | 9/1988  | Groshong          | 5,295,994 A   | 3/1994  | Bonutti                        |
| 4,779,611 A           | 10/1988 | Grooters et al.   | 5,300,106 A   | 4/1994  | Dahl et al.                    |
| 4,784,133 A           | 11/1988 | Mackin            | 5,308,327 A   | 5/1994  | Heaven et al.                  |
| 4,793,348 A           | 12/1988 | Palmaz            | 5,309,896 A   | 5/1994  | Moll et al.                    |
| 4,798,205 A           | 1/1989  | Bonomo et al.     | 5,314,443 A   | 5/1994  | Rudnick                        |
| 4,800,901 A           | 1/1989  | Rosenberg         | 5,318,012 A   | 6/1994  | Wilk                           |
| 4,802,479 A           | 2/1989  | Haber et al.      | 5,330,497 A   | 7/1994  | Freitas et al.                 |
| 4,813,429 A           | 3/1989  | Eshel et al.      | 5,331,975 A   | 7/1994  | Bonutti                        |
| 4,840,613 A           | 6/1989  | Balbierz          | 5,338,305 A   | 8/1994  | Plyley et al.                  |
| 4,854,316 A           | 8/1989  | Davis             | 5,342,307 A   | 8/1994  | Euteneuer et al.               |
| 4,861,334 A           | 8/1989  | Nawaz             | 5,346,504 A   | 9/1994  | Ortiz et al.                   |
| 4,865,593 A           | 9/1989  | Ogawa et al.      | 5,359,995 A   | 11/1994 | Sewell, Jr.                    |
| 4,869,717 A           | 9/1989  | Adair             | 5,361,752 A   | 11/1994 | Moll et al.                    |
| 4,875,468 A           | 10/1989 | Krauter et al.    | 5,370,134 A   | 12/1994 | Chin et al.                    |
| 4,888,000 A           | 12/1989 | McQuilkin et al.  | 5,383,889 A   | 1/1995  | Warner et al.                  |
| 4,899,729 A           | 2/1990  | Gill et al.       | 5,391,178 A   | 2/1995  | Yapor                          |
| 4,917,668 A           | 4/1990  | Haindl            | 5,397,311 A   | 3/1995  | Walker et al.                  |
| 4,927,412 A           | 5/1990  | Menasche          | 5,402,772 A   | 4/1995  | Moll et al.                    |
| 4,931,042 A           | 6/1990  | Holmes            | 5,407,433 A   | 4/1995  | Loomas                         |
| 4,932,956 A           | 6/1990  | Reddy et al.      | 5,425,357 A   | 6/1995  | Moll et al.                    |
| 4,955,895 A           | 9/1990  | Sugiyama et al.   | 5,431,173 A   | 7/1995  | Chin et al.                    |
| 4,966,583 A           | 10/1990 | Debbas            | 5,450,843 A   | 9/1995  | Moll et al.                    |
| 4,994,047 A           | 2/1991  | Walker et al.     | 5,454,365 A   | 10/1995 | Bonutti                        |
| 5,002,557 A           | 3/1991  | Hasson            | 5,468,248 A   | 11/1995 | Chin et al.                    |
| 5,009,643 A           | 4/1991  | Reich et al.      | 5,496,345 A * | 3/1996  | Kieturakis et al. .... 606/192 |
| 5,030,206 A           | 7/1991  | Lander            | 5,514,091 A   | 5/1996  | Yoon                           |
| 5,030,227 A           | 7/1991  | Rosenbluth et al. | 5,601,589 A   | 2/1997  | Fogarty et al.                 |
| 5,042,976 A           | 8/1991  | Ishitsu et al.    | 5,607,443 A   | 3/1997  | Kieturakis et al.              |
| 5,074,871 A           | 12/1991 | Groshong          | 5,755,693 A   | 5/1998  | Walker et al.                  |
|                       |         |                   | 5,836,961 A * | 11/1998 | Kieturakis et al. .... 606/190 |
|                       |         |                   | 6,312,442 B1  | 11/2001 | Kieturakis et al.              |

6,368,337 B1 4/2002 Kieturakis et al.

## FOREIGN PATENT DOCUMENTS

|    |               |         |
|----|---------------|---------|
| EP | 512456        | 9/1939  |
| EP | 0249456       | 12/1988 |
| EP | 0512465       | 11/1992 |
| EP | 0573 273 A2   | 12/1993 |
| EP | 0769270 A1    | 4/1997  |
| GB | 20244427      | 4/1983  |
| SU | 594960        | 2/1978  |
| WO | WO 82/03775   | 11/1982 |
| WO | WO 92/06632   | 4/1992  |
| WO | WO 92/06638   | 4/1992  |
| WO | WO 92/19312   | 11/1992 |
| WO | WO 92/21295   | 12/1992 |
| WO | WO 98/40117 A | 9/1998  |

## OTHER PUBLICATIONS

Berci, G. "Laparoscopy in General Surgery"; Endoscopy (Appleton-Century-Crofts, New York, 1976); pp. 382-400.

Cinelli, R. "Inflatable Silastic Bag: A Practical Device That Simplifies Augmentation Mammoplasty"; Division of Plastic Surgery, Dept. of Surgery at the Maimonides Medical Center and Medical Arts Center of New York (Journal of American Society of Plastic & Reconstructive Surgeons, Inc., Oct. 1981) vol. 68; No. 4; pp. 614-615.

Dulucq, J. Treatment of Inguinal Hernias by Installation of a Subperitoneal Prosthetic Patch Using Pre-Peritoneoscopy (With a Video Film), (Translation of French document from Chirurgie, 1992) No. 118; pp. 83-85.

Gazayerli, M.M. "The Gazayerli Endoscopic Retractor Model 1"; (Surgeons Laparoscopy & Endoscopy; 1991) vol. 1; No. 2; pp. 98-100.

Gunning, J.E. "Chapter 2: History of Laparoscopy"; Laparoscopy; (Williams & Wilkins Company, Baltimore, Maryland, 1977) pp. 6-16.

Hayakawa, N. et al. "Laparoscopic Cholecystectomy Using Retraction of the Falciform Ligament"; (Surgical Laparoscopy & Endoscopy; 1991) vol. 1; No. 2; p. 126.

Hodgson, C. et al. "Some Effects of the Peritoneal Insufflation of Carbon Dioxide at Laparoscopy" (Anaesthesia, Jul. 1970) vol. 25; No. 3; pp. 382-390.

Hoffman, H. et al. "Nasal Reconstruction with the Rapidly Expanded Forehead Flap" (Laryngoscope 99, Oct. 1989) pp. 1096-1098.

Kaplan L. et al. "Retroperitoneoscopy in Dogs" (Gastrointestinal Endoscopy, 1979) vol. 25; No. 1; pp. 13-15.

Manders, MD., Ernest K. Expert Report executed Dec. 1, 1997.

Marshall, R. et al. "Circulatory Effects of Carbon Dioxide Insufflation of the Peritoneal Cavity for Laparoscopy" (British Journal of Anaesthesia, 1972) vol. 44; No. 7; pp. 680-684.

Meretyk, S. et al. "Retroperitoneoscopy: Foreign Body Retrieval" (Journal of Urology, Jun. 1992) vol. 147; No. 6; pp. 1608-1611.

Rigg, MD. Bruce M. "Inflatable Device for Intraoperative Use During Augmentation Mammoplasty" (Reconstructive Surgery, May 1982) p. 898.

Sanchez de Badajoz Chamorro et al. "Endoscopic Cervical Anchorage, New Treatment for Stress Incontinence" (Archivos Espafioles de Urologia, 1988) vol. 41; Issue 2; pp. 2-9.

Sanchez de Badajoz et al. "Stress Incontinence: A New Endoscopic Approach" (Urology, Nov. 1990) vol. 36; No. 5; pp. 403-405.

Sasaki, G. "Intraoperative Sustained Limited Expansion (ISLE) as an Immediate Reconstructive Technique" (Clinics in Plastic Surgery, Jul. 1987) vol. 14; No. 3; pp. 563-573.

Sasaki, G. "Intraoperative Expansion as an Immediate Reconstructive Technique" (Facial Plastic Surgery, Jul. 1988) vol. 5; No. 4; pp. 362-378.

Shafik "Extraperitoneal Laparoscopic Lymphadenectomy in Prostatic Cancer: Preliminary Report of a New Approach" (Journal of Endourology, 1992) vol. 6; No. 2; pp. 113-116.

Voeller, M.D. guy R., Expert Report executed Dec. 1, 1997.

Wickham, J. and Miller, R. Percutaneous Renal Surgery (Churchill Livingstone, New York, 1983) pp. 17-44.

Wittmoser, R. "Retroperitoneoscopy: A Preliminary Report" ; Endoscopy (Appleton-Century-Crofts, New York, 1976) pp. 760-761.

Zhila, V. "Surgical Interventions on the Kidneys and Ureters Using a Retroperitoneoscopy"; Translation of Russian Document from Urology Department of the Kiev State Institute for Physician Advancement of the USSR Ministry of Public Health.

Zucker, K. et al. Surgical Laparoscopy (Quality Medical Publishing, Inc., St. Louis, Missouri, 1991) pp. 25-27; pp. 313-322.

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5





FIG. 6






FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 31




FIG. 30




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37








FIG. 38







**FIG. 41**



**FIG. 42**



**FIG. 43**



**FIG. 44**




FIG. 45




FIG. 46




FIG. 48




FIG. 47




FIG. 49A




FIG. 49B




FIG. 49C




FIG. 49D




FIG. 49E




FIG. 49F




FIG. 49G









FIG. 50



1

# APPARATUS AND METHOD FOR DEVELOPING AN ANATOMIC SPACE FOR LAPAROSCOPIC HERNIA REPAIR AND PATCH FOR USE THEREWITH

## CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 10/117,765, filed on Apr. 5, 2002 now U.S. Pat. No. 6,953,467, which is a continuation of U.S. application Ser. No. 08/861,913, filed on May 22, 1997, now U.S. Pat. No. 6,368,337, which is a continuation of U.S. application Ser. No. 08/483,293, filed on Jun. 7, 1995, now abandoned, which is a divisional of U.S. application Ser. No. 08/124,283, filed on Sep. 20, 1993, now U.S. Pat. No. 5,836,961, which is a continuation-in-part of U.S. application Ser. No. 07/893,988, filed on Jun. 2, 1992, now U.S. Pat. No. 6,312,442. The disclosure of each of these prior applications is hereby incorporated by reference in their entirety.

This invention relates to an apparatus and method for developing an anatomic space for laparoscopic hernia repair and a patch for use therewith.

## BACKGROUND OF THE INVENTION

In the past, in developing spaces and potential spaces within a body, blunt dissectors or soft-tipped dissectors have been utilized to create a dissected space which is parallel to the plane in which the dissectors are introduced into the body tissue. This often may be in an undesired plane, which can lead to bleeding which may obscure the field of view and make it difficult to identify the body structures. In utilizing such apparatus and methods, attempts have been made to develop anatomic spaces in the anterior, posterior, or lateral to the peritoneum. The same is true for pleural spaces and other anatomic spaces. Procedures that have been performed in such spaces include varicocele dissection, lymph node dissection, sympathectomy, and hernia repair. In the past, the inguinal hernia repair has principally been accomplished by the use of an open procedure which involves an incision in the groin to expose the defect in the inguinal floor, remove the hernial sac, and subsequently suture the ligaments and fascias together to reinforce the weakness in the abdominal wall. Recently, laparoscopic hernia repairs have been attempted by inserting laparoscopic instruments into the abdominal cavity through the peritoneum and then placing a mesh to cover the hernia defect. Hernia repair using this procedure has a number of disadvantages, principally because the mesh used for hernia repair is in direct contact with the structures in the abdominal cavity, as for example the intestines, so that there is a tendency for adhesions to form in between these structures. Such adhesions are known to be responsible for certain occasionally serious complications. Such a procedure is also undesirable because typically the patch is stapled into the peritoneum, which is a very thin unstable layer covering the inner abdomen. Thus, the stapled patch can tear away from the peritoneum or shift its position. Other laparoscopic approaches involve cutting away the peritoneum and stapling it closed. This is time consuming, however, and involves the risk that important anatomic structures may be inadvertently cut. In addition, such a procedure is undesirable because it requires the use of a general anesthesia. There is therefore a need for a new and improved apparatus and method for developing an anatomic space and particularly for accomplishing hernia repair by laparoscopy.

2

## SUMMARY OF THE INVENTION

In general, it is an object of the present invention to provide an apparatus and method for developing an anatomic space.

Another object of the invention is to provide an apparatus and method in which such an anatomic space is developed by applying perpendicular forces to create the anatomic space at the weakest plane to create a more natural, less traumatic and bloodless region in which to work.

Another object of the invention is to provide an apparatus and method to obtain surgical exposure in the preperitoneal space.

Another object of the invention is to provide an apparatus and method to create a preperitoneal working space utilizing a balloon dissector.

Another object of the present invention is to provide an apparatus and method of the above character for developing an anatomic space for laparoscopic hernia repair through the anatomic space.

Another object of the invention is to provide an apparatus and method for decreasing the time and risk associated with creating a preperitoneal working space.

Another object of the present invention is to provide an apparatus and method of the above character for a minimally invasive procedure.

Another object of the invention is to provide an apparatus and method of the above character which can be accomplished without the use of a general anesthesia.

Another object of the invention is to provide an apparatus and method of the above character which can be accomplished with a spinal or epidural anesthesia.

Another object of the invention is to provide an apparatus and method of the above character which provides substantially reduced medical costs and a greatly reduced patient recovery time.

Another object of the invention is to provide an apparatus of the above character which is relatively simple and compact.

Another object of the invention is to provide an apparatus and method of the above character which can be readily utilized by surgeons.

Another object of the invention is to provide a patch for use in the apparatus which is firmly secured during the hernia repair.

Another object of the invention is to provide a balloon which has a modified asymmetric manta ray configuration to aid in providing the desired configuration for the extraperitoneal working space for hernia repair.

Another object of the invention is to provide a balloon dissection apparatus in which has a balloon cover is detachably secured to the obturator so that the balloon dissection device is relatively rigid to permit the balloon dissection apparatus to be grasped by the handle to operate the same during dissection.

Another object of the invention is to provide a balloon dissection apparatus of the above character in which a precise release mechanism is provided for releasing the balloon cover from the obturator so that the surgeon can be assured that the balloon cover has been released before it is removed to release the balloon.

Another object of the invention is to provide a balloon dissection apparatus of the above character in which the guide rod or obturator remain in place to maintain ready access to the extraperitoneal working space.

Another object of the invention is to provide a balloon dissection apparatus of the above character in which certain

of the parts which are to be moved relative to other parts are color coded to aid the surgeon in use of the apparatus.

Another object of the apparatus is to provide a tubular member which is provided with a tip having an inclined surface.

Another object of the invention is to provide a balloon dissection apparatus which is provided with a blunt tip which has a diameter which is less than the diameter of the cannula tube.

Another object of the invention is to provide a balloon dissection apparatus of the above character in which at least a part of the same can be sterilized and reused.

Additional objects and features of the invention will appear from the following description in which the preferred embodiments are set forth in detail in conjunction with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side elevational view partially in cross-section of a laparoscopic apparatus incorporating the present invention.

FIG. 2 is a cross-sectional view taken along the 2-2 of FIG. 1.

FIG. 3 is a side elevational view partially in cross-section of the tunneling shaft forming a part of the apparatus shown in FIG. 1 after it has been removed from the apparatus shown in FIG. 1.

FIG. 4 is a cross-sectional view taken along the line 4-4 of FIG. 3.

FIG. 5 is an isometric view of the inflatable balloon utilized in the apparatus in FIG. 1 secured to the tunneling rod.

FIG. 6 is a cross-sectional view taken along the line 6-6 of FIG. 5, and showing by dotted lines the manner in which the balloon as it unfolds develops the anatomic space.

FIG. 7 is a partial plan view of a prone human body, showing the lower abdomen showing the manner in which the laparoscopic apparatus of the present invention is utilized for performing a hernia repair through the preperitoneal space.

FIG. 8 is a sagittal view of the lower abdominal cavity of the human being shown in FIG. 7 showing the apparatus of the present invention introduced into the preperitoneal space.

FIG. 9 is a view similar to FIG. 8, but showing the sleeve removed from the apparatus and with the balloon inflated.

FIG. 10 is a sagittal view similar to FIG. 8 showing the balloon deflated and being removed.

FIG. 11 is a sagittal view similar to FIG. 8 showing removal of the tunneling shaft.

FIG. 12 is an isometric view of a patch incorporating the present invention.

FIG. 13 is a side elevational view of the patch shown in FIG. 12.

FIG. 14 is an isometric view showing the patch in FIGS. 12 and 13 in a rolled-up, generally cylindrical configuration.

FIG. 15 is a sagittal view showing the hernia sac of hernia that is to be repaired.

FIG. 16 is a sagittal view showing the introducer through which the rolled-up patch in FIG. 17 has been introduced into the preperitoneal space by an introducer rod.

FIG. 17 is a sagittal view similar to FIG. 16 showing the attachment of the patch to the hernia sac.

FIG. 18 is a sagittal view similar to FIG. 17 showing the dissection of the hernia sac and the unrolling of the patch.

FIG. 19 is a sagittal view showing the patch in place to provide the hernia repair.

FIG. 20 is an isometric view of another embodiment of a balloon with a patch disposed thereon for use with the apparatus of the present invention.

FIG. 21 is a cross-sectional view taken along the line 21-21 of FIG. 20.

FIG. 22 is an enlarged cross-sectional view taken along the line 22-22 of FIG. 23.

FIG. 23 is a sagittal view showing the manner in which the balloon and patch shown in FIG. 20 are disposed in the preperitoneal space.

FIG. 24 is a sagittal view showing the placement of the balloon and the patch of FIG. 20, and the inflation of the balloon in the preperitoneal space.

FIG. 25 is an isometric view of another embodiment of a balloon and patch for use with the apparatus of the present invention.

FIG. 26 is a rolled-up cross-sectional view of the balloon and patch shown in FIG. 25.

FIG. 27 is an isometric view of another embodiment of a patch for use with the apparatus of the present invention.

FIG. 28 is an isometric view of the patch shown in FIG. 27 wrapped in an introducer assembly.

FIG. 29 is a top plan view of another embodiment of laparoscopic apparatus incorporating the present invention.

FIG. 30 is a side elevational view taken along the line 30-30 of FIG. 29.

FIG. 31 is a cross-sectional view taken along the line 31-31 of FIG. 30.

FIG. 32 is a cross-sectional view taken along the line 32-32 of FIG. 30.

FIG. 33 is an enlarged cross-sectional view of the distal extremity of the laparoscopic apparatus shown in FIG. 29.

FIG. 34 is a partial plan view showing the balloon after it has been removed from the laparoscopic apparatus with the obturator tip shifting its position.

FIG. 35 is a plan view of the balloon shown in FIG. 34 as it is being removed from the body of the patient and bringing along with it the obturator tip.

FIG. 36 is a side elevational view of another embodiment of a laparoscopic apparatus incorporating the present invention.

FIG. 37 is a plan view showing the balloon from the apparatus shown in FIG. 36 in an inflated condition and showing the tunneling rod mounted therein being prevented from being advanced beyond the distal extremity of the balloon.

FIG. 38 is a plan view showing the manner in which the balloon is separated from the tunneling rod as it is retracted.

FIG. 39 is an isometric view of a surgical dissector with a cannula incorporating the present invention in an assembled condition.

FIG. 40 is an isometric exploded view of the components of the surgical dissector with cannula shown in FIG. 39.

FIG. 41 is a side elevational view of the assembly shown in FIG. 39.

FIG. 42 is a top plan view looking along the line 42-42 of FIG. 41.

FIG. 43 is a view partly in cross-section taken along the line 43-43 of FIG. 42.

FIG. 44 is a view looking along the line 44-44 of FIG. 41.

FIG. 45 is a partial side elevational view of the assembly shown in FIG. 1 with the clamping mechanism moved to a release position.

FIG. 46 is a view taken along the line 46-46 of FIG. 45.

FIG. 47 is a partial side elevational view of an assembly shown in FIG. 41 with the retaining ring moved to a locked position.

FIG. 48 is a cross-sectional view taken along the line 48-48 of FIG. 47.

FIGS. 49A-49G are cartoons showing use of the surgical dissector shown in FIG. 1 in a laparoscopic hernia procedure.

FIG. 50 is a cross-sectional view taken along the line 50-50 of FIG. 49C.

FIG. 51 is a cross-sectional view taken along the line 51-51 of FIG. 52 showing another embodiment of a balloon dissection apparatus incorporating the present invention.

FIG. 52 is an end elevational view taken along the line 52-52 of FIG. 51.

FIG. 53 is an enlarged cross-sectional view taken along the line 53-53 of FIG. 51.

FIG. 54 is an enlarged cross-sectional view taken along the line 54-54 of FIG. 53.

FIG. 55 is an enlarged cross-sectional view of a portion of the view shown in FIG. 51 showing the latch members moved to permit removal of the guide rod.

#### DETAILED DESCRIPTION OF THE DRAWINGS

In general, the apparatus of the present invention is used for insertion into a body to create an anatomic space. In one embodiment of the invention, the apparatus is comprised of a tubular introducer member having a bore extending therethrough. A tunneling shaft is slidably mounted in the bore and has proximal and distal extremities including a bullet-shaped tip. A rounded tunneling member is mounted on the distal extremity of the tunneling shaft. An inflatable balloon is provided. Means is provided on the balloon for removably securing the balloon to the tunneling shaft. Means is also provided for forming a balloon inflation lumen for inflating the balloon. The balloon is wrapped on the tunneling shaft. A sleeve substantially encloses the balloon and is carried by the tunneling shaft. The sleeve is provided with a weakened region extending longitudinally thereof, permitting the sleeve to be removed whereby the balloon can be unwrapped and inflated so that it lies generally in a plane. The balloon, as it is being inflated, creates forces generally perpendicular to the plane of the balloon to cause pulling apart of the tissue along a natural plane to provide the anatomic space.

More in particular, as shown in the drawings, the apparatus or device 31 for creating such an anatomic space for use in a laparoscopic procedure (see FIG. 1) includes an introducer sleeve or device 32 which consists of a tubular member 33 formed of a suitable material such as plastic which is provided with a bore 34 extending throughout the length thereof. A handle section 36 is mounted on one end of the tubular member 33 and is also formed of a suitable material such as plastic. It is provided with a bore 37 which is in communication with the bore 33. A flapper valve 38 is mounted within the section 36 and is movable between a position in which it closes off the bore 37 and position out of the way of the bore 37 by a finger operated actuator 39 mounted on the exterior of the section 36. A stopcock 41 is mounted on the section 36 and is in communication with the passage 37. A lever 42 is provided for opening and closing the stopcock 41.

A tunneling shaft assembly 46 is slidably mounted in the bores 37 and 34 of the introducer sleeve 32. The tunneling shaft assembly 46 consists of a tunneling shaft 47 formed of a suitable material such as stainless steel, of a suitable length, as for example 18 inches, and a suitable diameter of

approximately 1/8 inch. The tunneling shaft 47 is provided with proximal and distal extremities 48 and 49.

An introducer member 51 is slidably mounted on the tunneling shaft 47 and is formed of a suitable material such as plastic. The introducer member 51 is substantially hollow as shown and is provided with a bore 52 through which the tunneling shaft 47 extends. The introducer member 51 is provided with a substantially hemispherical tip 53 to form a rounded protrusion or first obturator through which the shaft 47 extends. The introducer member 51 has a length such that when it is introduced into the bore 34 of the introducer sleeve 32, it extends out of the distal extremity of the introducer sleeve 32, as shown particularly in FIG. 1. This diameter of the introducer member 51 is sized so that it can be slidably mounted in the bore 34. The other end of the introducer member 51 is provided with a chamfer 54.

A disk-type seal 43 having a central opening is provided in the section 36 in alignment with the bore 37, and is adapted to permit the introduction of the introducer member 51 therethrough.

The section 36 forms one part of a three-piece handle 56 of the laparoscopic apparatus 31 which is sized so that it is adapted to be grasped by the human hand. As can be seen particularly in FIG. 4, the handle 56 is generally rectangular in cross-section. The handle 56 is provided with an intermediate section 57 which has a bore 58 extending therethrough in registration with the bore 37 and has the same general diameter as the bore 37 so that the introducer member 51 can travel therethrough. The sections of the handle 56 can be characterized as having first, second, and third sections in which section 36 is the first section and intermediate section 57 is the second section. A latch is provided for interconnecting the intermediate section 57 to the first section 36, and consists of a pair of oppositely disposed latches 61 pivotally mounted on the pins 62 in the intermediate section 57. Each of the latches 61 is provided with a latch portion 63 adapted to engage a protrusion 64 provided on the end section 36, and is yieldably urged into engagement therewith by a spring 66. Each of the latches is provided with a cam surface 67 which is adapted to be engaged by the chamfer 54 of the introducer member 51 to cam the latch portion 63 out of engagement with the protrusion 64 to release the intermediate section 57 from the first section for a purpose hereinafter described.

The handle 56 also consists of another end section 71, which can also be characterized as the third section, which is secured to the proximal extremity of the tunneling shaft or rod 47. A pair of latches 72 are provided in the end section 71 and are pivotally mounted on pins 73. The latches 72 are provided with latch portions 74 adapted to engage projections 76 provided in the intermediate section 57. Means is provided for yieldably retaining the latches 72 in engagement with the projections 76 and consists of a U-shaped spring 77 mounted within the end section 71 and engaging the latches 72. The latches 72 are provided with knurled portions 72a which extend outwardly and which are adapted to be grasped by the fingers of the hand so that the latch portions 74 can be moved out of engagement with the projections 76 against the force of the spring 77.

The tunneling shaft assembly 46 also includes a tip 79 which is mounted on the distal extremity of the tunneling shaft 47. As shown, the tip 79 is substantially olive-shaped and can also be called a second obturator. It is provided with a rounded hemispherical surface on its distal extremity which has a maximum diameter which is slightly less than the diameter of the bores 34 and 37 so that it can pass through the introducer sleeve 32. The proximal extremity of

the tip **79** is of smaller diameter to provide an annular step **81** in the tip. The proximal extremity of the tip **79** is also hemispherical, as shown. The tip **79** can be formed of a suitable material such as plastic and can be secured to the distal extremity of the tunneling shaft **47** by suitable means such as an adhesive. As hereinafter explained, the tunneling shaft or **47** is movable so that the tip **79** can be brought into engagement with the hemispherical end **53** of the introducer member **51** for a purpose hereinafter described.

The laparoscopic apparatus **31** also includes a balloon assembly **86** which is shown in FIGS. **2**, **5**, and **6**. As shown in FIG. **5**, when the balloon assembly **86** consists of a balloon **87** which in plan, when deflated, has a pear-shaped configuration when viewed in plan. The balloon **87** is preferably formed of a non-elastomeric, medical-grade material of a suitable type such as PVC. Thus, the balloon **87** can be formed of two sheets **88** and **89** of such a material which have their outer margins bonded together by suitable means such as by a heat seal **91** extending around the perimeter of the flat balloon. The balloon **87** is provided with a neck **94** into which a flexible tubular member **96** extends, and is secured therein in a suitable airtight fashion such as by an adhesive. The tubular member **96** is provided with a lumen **97** which is in communication with the interior of the balloon **87** and which can be used for inflating the balloon **87** through a Luer-type fitting **98** mounted on the free end of the tubular member **96**.

Means is provided for removably securing the balloon **87** to the tunneling shaft **47**, and consists of a sleeve **101** formed of the same material as the balloon **87**, and which can be formed integral or separate therefrom and adhered thereto by suitable means such as an adhesive. The sleeve **101** extends longitudinally of the balloon **87** and is disposed generally equidistant from the side margins of the same. The sleeve **101** is provided with a passage **102** extending therethrough which is sized to slidably accommodate the tunneling shaft **47**. Means is provided for permitting separation of the balloon **87** from the tunneling shaft **47** by movement side-wise from the axis of the passage **102** and takes the form of longitudinally spaced apart perforations **103** in the sleeve **101** extending longitudinally the length of the sleeve **101**. The perforations **103** are spaced close enough together to form a weakened region so that the balloon can be readily separated from the tunneling shaft **47** by separating the plastic sleeve **101** by tearing the plastic between the perforations as hereinafter described.

As shown in FIG. **6**, the sleeve **101** is disposed equidistant from the side margins of the balloon **87**, permitting the balloon **87** to be inflated as hereinafter described and as also shown by the dotted lines in FIG. **6**, to be inflated around the shaft **47**. When deflated, the side margins of the balloon **87** can be rolled inwardly toward the shaft **47** as shown by the broken lines in FIG. **6** to permit the same to be folded into a generally cylindrical configuration as shown in FIG. **2**, and to be enclosed within a removable sheath **106** carried by the tunneling shaft **47**. The removable sheath **106** is formed of a relatively thin-walled tubular member **107** of a suitable material such as Teflon which has a weakened region **108** in its wall extending longitudinally the length thereof. This weakened region **108** can take the form of a slit as shown, or can be a series of perforations or slots formed in the wall, or a combination thereof. The proximal extremity of the tubular member **107** is provided with split-apart or separable end portions **107a** and **107b** to which are secured finger rings **109** of a suitable material such as plastic and secured thereto by fasteners **111**.

Operation and use of the laparoscopic apparatus in performing the method for laparoscopic hernia repair through preperitoneal space may now be briefly described as follows. Let it be assumed that the laparoscopic apparatus **31** has been assembled as shown in FIG. **1**. As shown in FIG. **7**, let it be assumed that a human patient **121** is in a prone position and has a hernia **122** in the lower abdominal area which he wishes to have repaired. The patient is prepared in an appropriate manner by administering a suitable anesthesia, as for example a spinal anesthesia, and any other necessary preparation. The surgeon first makes an infraumbilical incision **126** in the skin below the navel or umbilicus **127** and separates the fat **129** and then incises the anterior rectus sheath or fascia **131** in the midline. Care should be taken not to penetrate the peritoneum **132** overlying the abdominal cavity **133** (see FIG. **8**).

After the incision **126** has been made in the manner hereinbefore described, the laparoscopic apparatus **31** is then taken by one hand of the surgeon, grasping the handle **56** and utilizing the other hand to facilitate the insertion of the rounded blunt tip **79** into the incision **126**. The blunt tip **79** is then caused to enter the slit in the fascia **131** and pass anterior to the peritoneum **132**, in between the rectus muscles (laterally) and enters the potential preperitoneal space. The blunt tip **79** is then utilized as a tunneling device by the surgeon using one hand **56** to advance the blunt tip **79** toward the pubic region of the patient while the surgeon places his other hand on the abdomen to feel the apparatus **31** as it is being advanced. The advance of the apparatus **31** is continued until the blunt tip **79** is below the symphysis pubis **137** as shown in FIG. **8**, and preferably is disposed between the symphysis pubis **137** and the bladder **138**.

After the apparatus **31** has been properly positioned as shown in FIG. **8**, the removable sheath **106** is removed by the surgeon using one hand to engage the finger rings **109** which are exterior of the body of the patient and outside of the incision **126**. At the same time, the other hand of the surgeon is utilized to stabilize the portion of the apparatus **31** which is within the preperitoneal space. The sheath **106** can be readily withdrawn since it is formed of Teflon and is split or weakened along its length, by pulling it proximally and away from the longitudinal axis of the tubular member **33**. As the sheath **106** opens and slips off, it exposes the balloon **87** of the balloon assembly **86**. When the sheath **106** is completely removed, a sterile saline solution serving as a balloon inflation medium is introduced into the balloon **87** through the tubular member **96** by connecting a conventional syringe **141** to the Luer fitting **98**. The balloon **87** typically can be inflated to a suitable size by introducing 500 cc or less of normal saline solution into the balloon **87** by pressing on the plunger **142**. As the balloon **87** is inflated, the balloon **87** progressively unwraps with its side margins rolling outwardly from the center while expanding into a plane to cause progressive separation or dissection of tissue (i.e., **131**, **132**) along its weakest points by application of forces generally perpendicular to the plane of the balloon **87** to create the preperitoneal or anatomic space. The balloon **87** expands around the tunneling shaft **47** in the manner shown in broken lines in FIG. **6** to achieve the progressive separation until complete inflation is achieved. The surgeon can sense the filling of the balloon **87** by feeling the abdomen of the patient **121** as the balloon **87** is inflated. The balloon **87** serves to open up the preperitoneal space **136** to provide a bloodless space for the procedures hereinafter to be performed. Since the balloon **87** is formed of a non-elastomeric material, it is a volume-limited balloon to prevent over-expansion. Different sizes of balloons can be utilized for

different patient sizes. With a smaller balloon **87** it is possible to deflate the balloon **87** and then shift the balloon and again reinflate it to obtain the desired bloodless preperitoneal space.

After the desired bloodless anatomic space or pocket is formed, the balloon **87** is deflated by withdrawing the normal saline solution by withdrawal of the plunger **142** of the syringe **141** or via a hospital vacuum aspirator. After the balloon **87** has been deflated, the balloon assembly **86** can be removed by grasping the handle **56** of the laparoscopic apparatus or device **31** with one hand and using the other hand to grasp the tubular member **96** and the proximal extremity of the balloon **87** and to remove the same through the incision **126**, as shown in FIG. 10. As the balloon **87** is being removed, it is progressively separated from the tunneling shaft **47** by causing the sleeve **101** to split apart along the longitudinal perforations **103** provided in the sleeve **101**. This makes it possible to separate the balloon **87** from the tunneling shaft **47** without the necessity of removing the tunneling shaft **47** or the introducer sleeve **32**.

After the balloon assembly **86** has been removed, the introducer sleeve **32** can be advanced distally over the tunneling shaft **47** so it extends well into the preperitoneal space **136** as shown in FIG. 11. The end section **71** of the handle **56** is then removed by depressing the latches **72** by engaging the portions **72a** to disengage the latch portions **74** from the intermediate section **57** of the handle **56**. The third section **71** is then withdrawn proximally as shown in FIG. 11 to bring the olive-shaped tip **79** into engagement with the distal tip of the introducer member **51** to cause both the tip **79** and the introducer member **51** to be withdrawn or retracted. As the introducer member **51** is being withdrawn, its chamfer **54** will strike the cam surfaces **67** of the latches **61** to cause them to disengage from the end piece **36** to carry it along with the introducer member **51** and shown in FIG. 2. Thus, it can be seen that the tunneling shaft assembly **46** can be readily removed merely by one motion of the surgeon's hand. Thereafter, a conventional laparoscope **144** (see FIG. 16) can be introduced through the introducer sleeve **32** to permit the surgeon to view the preperitoneal space **136**.

The dissected preperitoneal space **136** is then insufflated with carbon dioxide through the stopcock **41** to a pressure ranging from 6 to 8 mm of mercury. Thereafter, two additional trocars **146** and **147** are introduced through the abdominal wall into the dissected preperitoneal space **136** in appropriate locations. Thus, as shown in FIG. 7, trocar **146** is introduced into the left side of the abdomen of the patient **121** below the introducer sleeve **32** and the trocar **147** is introduced into the dissected preperitoneal space **136** immediately above the symphysis pubis **137** and directly below the introducer sleeve **32**. As can be appreciated, the locations of the trocars **146** and **147** is generally dictated by the location of the hernia **122** to be repaired.

A patch **151** of the present invention to be utilized in the hernia repair procedure is shown in detail in FIGS. 12, 13, and 14. The patch **151** can be characterized as a hernia patch or graft and is made of a suitable plastic mesh such as a Prolene mesh manufactured by Ethicon, Inc. The patch **151** can be of any desired configuration. For example, it can be generally circular as shown and consists of a disk **152** of a suitable diameter, as for example 2 inches. A tail **153** is secured to the disk substantially in the center thereof, in a suitable manner. For example, as shown, the tail **153** can be provided with split portions **153a** and **153b** which are split apart and offset with respect to each other. The split portions **153a** and **153b** are secured to a smaller reinforcing disk **154**

formed of the same material as disk **152** and secured to the disk **152** by suitable means such as surgical thread (not shown). The tail **153** is formed of the same material as the disk **152** and **154**, or it can be formed of a different material, such as Goretex. It can have a size such that it has a width of approximately 1/2 inch and a length of approximately 1 1/2 inches. As shown particularly in FIG. 14, the side margins of the disk **152** can be rolled inwardly towards the center adjacent the tail **153** to form a cylindrical roll **156** with the tail **153** extending outwardly therefrom. The roll **156** can be maintained in its rolled-up condition by means of sutures **157** disposed adjacent opposite ends of the roll and on opposite sides of the tail **153**.

Referring now to FIGS. 15 and 16, conventional laparoscopic instruments are used to repair the hernia **161** by placement of the patch **151**. First, the laparoscopic instruments are introduced through the introducer device **32** while being observed through laparoscope **144** to dissect the hernia **161**. The hernia neck **162** may be observed as it is entering the internal inguinal ring **163**. The repair procedure starts by dissecting the hernia space **161** from the surrounding tissue (spermatic duct and vessels) (see FIG. 15). The process is facilitated by CO<sub>2</sub> pressure impinging on then neck **162** of the hernia sac **161**. As soon as this dissection is completed, the roll **156** is pushed into the trocar **147** and advanced through the same by suitable means such as a deployment rod **164** (see FIG. 16) to enter the dissected preperitoneal space **136** as shown in FIG. 16. Alternatively, the roll **156** can be placed in a tubular member (not shown) which can be used to position the roll **156** within the trocar **157**. Thereafter, by the deployment rod **164**, the roll **156** can be pushed out of the tubular member in the he dissected preperitoneal space **136**.

The roll **156**, after it is in the preperitoneal space **136**, is then manipulated so that its tail **153** is disposed alongside the neck **162** of the hernia sac **161** as shown in FIG. 17. With reference to FIG. 17, a conventional stapling device **166** is then introduced through the trocar **146** to staple the tail **153** to the neck **162**. These staples **167** serve to divide the neck **162** of the sac **161** into distal and proximal portions **162a** and **162b**. As soon as this stapling operation is completed, the two portions **162a** and **162b** are separated from each other because of the pressure of the insufflation gas to cause the tail **153** of the patch **151** to be pulled upwardly into the inguinal ring to pull with it the disk **152**. The sutures **157** are cut apart to permit the disk **152** to unroll and to be placed across the inguinal ring **163** which created the main weakness in the abdominal wall permitting the hernia which is being repaired to occur. The proximal portion **162b** of the neck **162** is stapled together by staples **173** as shown in FIG. 18. The proximal portion **162** is then permitted to fold back into the desired anatomical location within the abdomen.

Thereafter, while observing the procedure under the laparoscope, the dissected preperitoneal space **136** can be deflated by permitting the carbon dioxide gas to escape to the atmosphere through the stopcock **41** in the introducer device **32** by operation of the stopcock lever arm **42**. As deflation is taking place, the movement of the patch **151** is observed through the laparoscope **144** so that it does not become displaced. When the deflation has been completed, the patch **151** is in a position over the inguinal ring **163** and serves to provide reinforcement to prevent the occurrence of another hernia in that area. The tail **153** is disposed with the inguinal ring **163** and retains the mesh disk **152** so that it surrounds the inguinal ring **163**.

After deflation is complete, the trocars **146** and **147**, as well as the introducer device **32**, can be removed. Small

sutures can then be utilized to close the various small openings which have been made in the abdominal wall so that there will be minimal noticeable scars after healing. The scar in the navel or umbilicus typically is nearly invisible.

It has been found that the use of the laparoscopic apparatus **31** in accomplishing the method as hereinbefore set forth provides a procedure in which the pain after the operation is markedly reduced. This is particularly true since the operation does not involve suturing of any ligaments which typically produces the pain. In addition, the recovery time for the patient is greatly accelerated. In the procedure of the present invention, a patient can return to work within a matter of three to five days, rather than in a number of weeks as in a conventional hernia repair procedure. The procedure also has other advantages. For example, it is not necessary to use a general anesthesia. Another principal advantage of the procedure is that there is no contact of the mesh patch **151** with the intestines of the patient or other intra-abdominal structures, thus greatly reducing the possibility of adhesion formation. In addition, the graft which is formed by the patch **151** is more secure and is positioned in an anatomically correct position. This is because the hernia sac **161** is in exact alignment with the hernia and pulls with it the tail **153** of the graft to ensure that the graft formed by the patch **151** is drawn into the correct position and is maintained in that position to prevent migration. In addition, the graft, by having an additional central disk **154**, ensures that additional reinforcement is provided in the proper location in the center where the weakest region in the abdominal wall has occurred. In addition, by such proper centering, the mesh construction of the patch **151** serves to uniformly reinforce the area surrounding the hernia.

Another embodiment of the present invention is shown in FIGS. **20**, **21**, and **22** with respect to another embodiment of a balloon assembly **181** and another embodiment of a patch or graft **182**. The balloon assembly **181** consists of a balloon **186** formed of two sheets **187** and **188** which are rectangular in shape, as for example square as shown in FIG. **20**. The sheets **187** and **188** are heat-sealed together at their outer margins as indicated by the broken line **189**. A tubular member **191** is provided which has one end sealed into one corner of the balloon **186** as shown in FIG. **20**. The tubular member **191** has a lumen **192** which opens into the interior space **193** of the balloon **186**. The sheets **187** and **188** are formed of a non-elastomeric material of the type hereinbefore described. A Luer fitting **194** is connected to the free end of the tubular member **191** and is utilized for introducing a saline solution into the balloon **186** for inflating the same.

The graft or patch **182** can have a desired configuration, as for example circular as shown in FIG. **20**. It is formed of a non-absorbable synthetic surgical mesh, as for example from polypropylene manufactured by Ethicon Inc. As shown, the mesh patch **182** overlies the sheet **187**.

The balloon assembly **181** already made in Ser. No. 324,519 with the patch **182** thereon can be rolled-up into a roll **196** as shown in FIG. **22** in which the patch or graft **182** is disposed within the roll **196**. The roll **196** can be maintained in the roll configuration by sutures **197** wrapped about the same. As shown in FIG. **23**, the roll **196** can then be introduced through a side trocar **146** and introduced into the dissected preperitoneal space **136** with the tubular member **191** extending through the trocar **146** and having its Luer fitting **194** disposed outside of the trocar **146**. After the roll **196** has been introduced, the sutures **197** can be removed and the balloon **186** can be inflated by introducing a saline solution through the fitting **194** by use of a syringe **199** (see FIG. **24**). Before the saline solution is introduced to inflate

the balloon **186**, the roll **196** is properly positioned so that when it is inflated and begins to unroll, it will unroll in the proper direction so that the graft or patch **182** carried thereby is properly positioned as shown in FIG. **24**. After the roll **196** has been completely unrolled, continued inflation of the balloon **186** moves the patch **182** so that it is pressed against the portion of the fascia through which the hernia has occurred as shown in FIG. **24**. As soon as the graft **182** has been properly positioned, the balloon **186** is deflated. The trocar **146** is then removed, and thereafter the balloon **186** can be withdrawn through the opening in which the trocar was present. Thereafter, the gas utilized for insufflation can be permitted to discharge through another trocar so that the fascia **131** comes into engagement with the peritoneum **132** with the large-area patch **182** held in place therebetween. Thereafter, the trocars can be removed in the manner hereinbefore described to complete the procedure.

Another embodiment of a balloon assembly for deploying a large-area patch or graft **201** through a trocar is shown in FIG. **25**. The large-area graft **201** shown in FIG. **25** is formed of a mesh material of the type hereinbefore described and has a generally oval-shaped configuration conforming to the general shape of the balloon **202** of the balloon assembly **203**. The balloon **202** is constructed of a nonelastomeric material in the manner hereinbefore described. A tubular member **206** is provided for inflating the balloon and has a Luer fitting **207** on the free end thereof. Means is provided for retaining the mesh graft **201** on one side of the balloon and consists of plastic flaps **208** provided on opposite sides of the balloon **202**, and secured thereto by a suitable means such as a heat seal along the broken line **209**. The inner margins of the flaps **208** are free and are adapted to receive the outer margins of the graft **201** as shown particularly in FIG. **25**.

The balloon **202** with the mesh graft **201** thereon can be rolled up into a substantially cylindrical roll **211** by rolling the outer margins of the balloon inwardly on top of the mesh material to provide two rolls **211** and **212** which are brought in adjacent to each other as shown in FIG. **26** with the mesh graft **201** being wrapped up therewith. The two rolls **211** and **212** can then be inserted into a tubular sheath **214**. The sheath **214** can then be introduced through a trocar in a manner hereinbefore described and then pushed out of the sheath **214** into the abdominal cavity. The balloon **202** can then be inflated with a saline solution to cause the two rolls **211** and **212** to unroll in opposite directions and then for the balloon **202** to inflate to move the patch **201** carried thereby into engagement with the portion of the fascia having the hernia therein. Thereafter, the balloon **202** can be deflated, the trocar removed, the balloon removed, and the dissected preperitoneal space deflated so that the large mesh graft **201** is disposed between the fascia and the peritoneum and is retained in position therebetween.

Another embodiment of a graft which can be utilized in connection with the present invention is shown in FIG. **27**. The patch or graft **216** is constructed in a manner similar to the graft or patch **151** shown in FIGS. **12** and **13**, with the exception that it is constructed in a manner so that it can be utilized with a direct hernia rather than an indirect inguinal hernia hereinbefore described. The graft **216** is formed of a sheet of circular mesh in the form of a disk **217** with a reinforcing central disk **218** which has a barbed head **219** secured thereto. The barbed head **219** is formed of a biodegradable material such as polyglycolic acid. The mesh graft **216** can be folded over a deployment rod **221** and introduced into a cylindrical sheath **222** (see FIG. **28**) which is sized so that it can be introduced through a conventional trocar, then

deployed from the sheath **22** by pushing on the deployment rod **221**. After the graft **216** has been deployed into the dissected preperitoneal space **136**, it can be positioned in an appropriate manner so that the barb **219** is positioned so that it is in alignment with the inguinal ring whereby upon deflation of the preperitoneal space **136** the barb **219** will extend through the inguinal ring to serve to retain the graft **201** firmly in place.

Another embodiment of a laparoscopic apparatus incorporating the present invention is laparoscopic apparatus **231** as shown in FIGS. **29** through **32**. The laparoscopic apparatus **231** includes introducer sleeve or device **32** identical to that hereinbefore described. It also includes a tunneling shaft assembly **46** which is provided with a tunneling shaft or rod **47** and a proximal extremity **49** (see FIG. **32**). In the previous embodiment of the laparoscopic apparatus, the tunneling shaft assembly is provided with an olive-shaped or bullet-shaped tip **79** which was secured to the distal extremity **49** of the tunneling shaft **47**. In the present embodiment of the apparatus shown in FIGS. **29** through **32**, the obturator tip **79a** is detachably mounted on the distal extremity **49** of the tunneling rod **47**. The proximal extremity of the tip **79a** is provided with a slot **236** which extends through one side of the proximal extremity into the central portion of the proximal extremity of the tip **79a**. The slot **236** is adapted to receive the rounded extremity **237** provided on the distal extremity **49** of the tunneling rod **47** (see FIG. **32**). A removable sleeve **241** is provided as a part of a laparoscopic apparatus **231**, and is similar in many respects to the removable sleeve or sheath **106** hereinbefore described. The removable sleeve **241** is formed of a suitable material such as Teflon as hereinbefore described and is provided with a tubular member **242** which is provided with a relatively thin wall **243** that has a weakened portion extending longitudinally thereof in the form of a slit **244** (see FIG. **31**). The tubular member **242** is provided with a proximal extremity **246** and a distal extremity **247**. The proximal extremity **246** has a thicker cross-section than the distal extremity **247**, as shown in FIGS. **31** and **32**. The proximal extremity **246** is provided with a recess **248** formed in the wall which is diametrically opposite the slit **244** that serves as a relief region to permit the movable sleeve **241** to be split apart when it is removed from the balloon.

The proximal extremity **246** is provided with wing-like members **251** and **252** which extend diametrically therefrom, spaced 90° apart from the slit **244**. These outstretched wings **251** and **252** serve to help the physician orient the laparoscopic apparatus **231** as it is being utilized. The proximal extremity **246** is also provided with a handle **256** which is formed integral therewith and which extends radially from the tubular member **242**. The handle **256** is provided with a finger hole **257** extending therethrough through which a finger can be inserted to facilitate pulling the removable sleeve **241** off of the balloon as described in connection with the previous embodiment.

As shown in FIG. **33**, the tip **79a** is detachably mounted in the proximal extremity of the removable sleeve **241** so that the tip **79** can serve as a second obturator during introduction of the laparoscopic apparatus **231** as hereinbefore described. Means is provided for securing the detachable tip **79a** to prevent it from becoming separated from the laparoscopic apparatus **231** and for permitting its withdrawal after the laparoscopic procedure is being completed. As shown in FIGS. **33** and **34**, such means consists of a flexible elongate element **261** in the form of a braided string formed of a suitable fabric such as Nylon, which has one end **262** secured in a slot **263** provided on the distal extremity of the

tip **79a** by suitable means such as an adhesive (not shown). The flexible elongate element **261** extends from the distal extremity of the tip **79a** in a recess **264** opening through the external surfaces of the tip **79a**. The proximal extremity of the flexible elongate element **261** can be secured directly to the balloon **87** or, alternatively, it can extend through the perforated sleeve **101** provided in the balloon along the tunneling shaft so that it extends beyond the proximal extremity of the tunneling shaft.

The use of the laparoscopic apparatus **231** in performing a laparoscopic procedure is substantially identical to that hereinbefore described with the exception that when the removable sleeve **241** is removed from the balloon **87**, the removable sleeve can be pushed forwardly to detach the tip **79a** from the tunneling shaft **47**. The removable sleeve **241** then can be pulled rearwardly to separate it from the balloon along the slit **244**. As soon as this occurs, the tip **79** becomes free of the sleeve and begins to rotate in the direction of the arrow **266** shown in FIG. **34**. When the balloon has been inflated and has performed its functions as hereinbefore described and it is now desired to remove the balloon **87**, the balloon **87** can be withdrawn in the manner hereinbefore described, and since the tip **79a** is tethered to the balloon **87** itself or flexible elongate element **261** attached thereto extends out proximally of the balloon **87**, the tip **79a** is withdrawn or can be withdrawn with the balloon **87**.

This laparoscopic apparatus **231** with its detachable obturator tip **79a** will be useful in certain applications of the present invention. With the previous laparoscopic apparatus hereinbefore described, there is a possibility that when the obturator tip **79** is withdrawn, critical structures, as for example small arteries, may be inadvertently incised between the tip **79** and the distal extremity of the tubular member **33** of the introducer device **32**. This possibility is eliminated by having the detachable tip **79a**, which is withdrawn when the balloon is withdrawn.

Still another embodiment of the laparoscopic apparatus incorporating the present invention is shown in FIGS. **36**, **37**, and **38**, in which the laparoscopic apparatus **271** consists of a balloon **272** of the type hereinbefore described, which is provided with a perforated sleeve **273** through which the tunneling rod **47** extends. The distal extremity **274** of the sleeve is closed by an end piece **276**. The balloon **272** is wrapped in the manner hereinbefore described around the tunneling shaft **247**. The tunneling shaft or rod **47** is not provided with a tunneling member or second obturator of the type hereinbefore described but its end is rounded as shown by providing a rounded tip **47a**.

The wrapped balloon **272** is enclosed within a removable sleeve **281** which is similar to those hereinbefore described. It is provided with a tubular member **282** that has a weakened region in the form of a slit **283** extending longitudinally the length thereof. The removable sleeve **281** differs from those hereinbefore described in that rather than being open at the end as in previous embodiments, it is provided with a closed-end, bullet-shaped, or olive-shaped tip **286**. The slit **283** is provided with a curved portion **283a** which extends through the bullet-shaped tip **286** so that the sleeve can be peeled off of the balloon **272** in the manner hereinbefore described by pulling on the handle **288** having a finger hole **289** therein. During the time that the removable sleeve **281** is being peeled off or separated from the balloon **272**, the balloon is held in place by the tunneling rod **47** which engages the end **276** of the perforated sleeve **273**. The balloon **272**, after it is inflated, can be separated from the tunneling rod **47** by pulling on the balloon and causing its distal extremity to lift up and to break apart at the perfora-

tions and peel away from the rounded extremities 47a of the tunneling shaft 47 as shown in FIG. 38. Continued pulling on the balloon 272 will cause it to separate from the tunneling rod 47 so that the balloon 272 can be removed as hereinbefore described. Thus, it can be seen that there has been provided an embodiment of the laparoscopic apparatus of the present invention in which the need for an obturator carried by the distal extremity of the tunneling rod 47 has been eliminated by providing the second obturator as a part of the removable sleeve 281. In all other respects, the operation and use of the laparoscopic apparatus 271 is similar to that hereinbefore described.

From the foregoing, it can be seen that there has been provided an apparatus and method for developing an anatomic space by the use of a wrapped balloon which, as it is inflated, gradually unwraps to tend to form a plane to cause forces to be created perpendicular to the plane for pulling apart tissue along a natural plane to provide an anatomic space, thereby providing a dissection in the weakest plane creating a more natural, less traumatic, and bloodless region in which to perform various medical procedures. Such anatomic spaces can be created in various parts of the human body, for example, in the preperitoneal area to provide a space anterior to the peritoneum for hernia repair and for varicocele dissection. Spaces can also be developed lateral to the peritoneum and spaces posterior to the peritoneum for performing medical procedures such as a sympathectomy and a lymph node dissection.

As hereinbefore explained, the apparatus and method is particularly appropriate for performing laparoscopic hernia repair, permitting the use of grafts and patches which can be used for direct and indirect hernias with minimal pain to the patient and with the patient being able to return to work within a few days.

Another embodiment of a laparoscopic apparatus 301 incorporating the present invention is shown in FIGS. 39-48. The laparoscopic apparatus 301 can also be described as an assembly in the form of a surgical dissector with a cannula which serves as a hand manipulated surgical instrument that can be used during general surgical laparoscopic procedures to dissect the layers of fascia between the skin and the peritoneum as described in conjunction with the previously disclosed embodiments of the invention. The laparoscopic apparatus 301 consists of a cannula 302 with a tunneling device 303 mounted therein. The tunneling device 303 is formed by the combination of an introducer member 307 and the guide rod assembly 306. The laparoscopic apparatus also includes a skin seal assembly 311, a balloon assembly 312, and a balloon cover assembly 316 as shown particularly in FIGS. 39 and 40.

The cannula 302 consists of a cannula tube 321 formed of a rigid plastic having proximal and distal extremities 322 and 323. A flow passage 324 extends from the proximal extremity 322 to the distal extremity 323. A cannula housing or handle 326 is mounted on the proximal extremity by suitable means such by molding it directly thereon. As disclosed in copending application Ser. No. 07/968,201, filed on Oct. 29, 1992, the disclosure of which is hereby incorporated by reference in its entirety, the handle 326 includes first and second valve members (not shown) in which one valve member serves as a duck-bill valve and the other valve member serves as a circular instrument or tool seal. The housing is provided with a Luer-type fitting 327 which is in communication with the interior of the housing outside of the duck-bill valve and is in communication with the passage 324 in the cannula tube 321.

As described in said copending application Ser. No. 07/968,201, filed on Oct. 29, 1992, the cannula 302 is adapted to receive the tunneling device or blunt obturator device 303 which is generally of the type described hereinbefore in the present application. This device 303 consists of the blunt obturator 306 having a blunt tip 331 which is generally olive-shaped as shown (see FIG. 41) and is formed of a suitable material such as plastic. The olive-shaped tip 331 is molded on the distal extremity 332 of a rod or a shaft 333 formed of a suitable material such as stainless steel. The blunt tip 331 is sized so that its outside diameter is slightly less than the inside diameter of the cannula tube 321. The proximal extremity 334 of the rod or shaft 333 has mounted thereon a handle part 336 of a handle assembly 337 which includes a second handle part 338. The handle parts 336 and 338 are adapted to mate with each other and are detachably connected in a manner described in copending application Ser. No. 07/968,201, filed on Oct. 21, 1992 by the use of latch means (not shown) adapted to be actuated by spring-operated latch members 339 disposed on opposite sides of the handle part 336 and adapted to be engaged by the fingers of the hand holding the handle assembly 337. The second handle part 338 forms a part of the introducer device 307 and is mounted on the proximal extremity 341 of a tubular member 342 formed of a suitable material such as plastic. The tubular member 342 is provided with a distal extremity 343 and has a bore 344 extending from the proximal extremity to the distal extremity through an end surface 346 (see FIG. 41) which is inclined at a suitable angle, as for example, approximately 45° proximally from the horizontal axis of the bore 344. The bore 344 is sized so it can slidably receive the shaft 333.

The handle part 338 is provided with latch means (not shown) which is adapted to releasably connect the handle part 338 to the cannula housing 326 and includes latch members 349 disposed on opposite sides of the handle part 338 adapted to be engaged by the fingers of the hand holding the handle assembly 337 to permit the handle part 338 to be separated from the cannula housing 326.

The skin seal assembly 311 generally can be of the type described in copending application Ser. No. 08/124,333, filed on Sep. 20, 1993, and as described therein consists of a screw body 350 formed of a suitable material such as plastic having a helical thread 351 and a scalloped flange 352. A resilient insert 353 is disposed in the screw body 351 and is formed of a suitable resilient material such as silicone. The insert 353 is provided with a bore 354 extending therethrough. A collet 357 having slots 358 therein surrounds the insert 353 and is engaged by a collar 356 movable axially of the screw body 351 and is adapted to move the collet to compress the insert 353 to move the insert between a retaining position for the cannula tube 321 extending through the bore 354 to retain the cannula 302 in a desired longitudinal position with respect to the skin seal assembly 311 and a releasing position in which the cannula 302 can be slidably moved longitudinally inwardly or outwardly with respect to the skin seal 311. The collar 356 is provided with an annular shoulder 359 having circumferentially spaced-apart slots 360 therein which are used for a purpose hereinafter described. As explained in copending application Ser. No. 08/124,333, filed on Sep. 20, 1993, means is provided to restrain rotation of the collar 356 with respect to the collet 357 and includes longitudinally extending keys 355 spaced 180° apart.

The balloon assembly 312 consists of a balloon 361 formed of a non-elastomeric, medical grade plastic material, of a suitable type such as polyurethane. The balloon 361 can

be characterized as having an asymmetric manta ray configuration when viewed in plan and is provided with a forwardly extending rounded protuberance **362** which has a width substantially less than that of the balloon **361**. The balloon **361** consists of two sheets of material which can be identified as a first or upper sheet **363** and a second or lower sheet **364** which have been die cut to the desired configuration with their edges bonded together in a suitable manner such as by means of a heat seal to form a balloon which has a generally flat configuration when deflated as shown in FIG. **40**. The upper or outer surface of the first or upper sheet **363** has been roughened in areas **365** as shown in FIG. **40** on the outwardly extending lobe portions **361a** and **361b** for a purpose hereinafter described. The roughening can be accomplished in any suitable manner such as by embossing the plastic material with a pattern having raised portions therein.

Means is provided for inflating the balloon with a suitable medium, as for example, a liquid such as a saline solution and consists of a flexible tube **366** that extends into the balloon between the two sheets **363** and **364** and forms a fluid-tight seal therewith. The interior of the balloon can be inflated and deflated by introduction of the fluid through the tube **366**. The tube **366** is connected to a Y-adaptor **367** which has one leg of the Y connected to a one-way valve **368** having a Luer fitting and the other leg connected to a tube **369** which is connected to a tapered fitting **371**. A conventional pinch off clamp **372** is mounted on the tube **369**. The tube **366** is adapted to be releasably retained in the slots **360** of the shoulder **359**.

Means is provided for removably securing the balloon **361** to the tunneling rod or shaft **306** and consists of an elongate tubular member or sleeve **376** which extends along the length of the balloon **361** and is disposed on one side of the balloon **361** which can be called the top side generally centrally of the balloon **361**. The tubular member **376** is provided with a passage **377** therein through which the tunneling or guide rod or shaft **333** extends. As hereinbefore explained, this tubular member or sleeve **376** can be formed as a separate member which is bonded to the top sheet **363** or alternatively can be formed integral with the top sheet **363** with two heat seals being provided above and below to form the sleeve **376** with the passage **377** therein. The tubular member **376** can be provided with spaced-apart elongate slits or perforations (not shown) extending along a line **378** in the tubular member **376** to facilitate separation of the balloon from the tunneling rod **333** as hereinafter described. With such a construction, it can be seen that the tunneling rod or blunt dissector or obturator **306** overlies the balloon **361** for advantageous features hereinafter described.

The balloon cover assembly **316** consists of a semi-rigid tube **381** formed of a suitable material such as plastic and is provided with proximal and distal extremities **382** and **383**. It is provided with a bore **384** (see FIG. **42**) which extends from the proximal extremity **382** to the distal extremity **383**. The tube **381** is provided with a weakened region in the form of a partial slit **386** extending from the distal extremity **383** to the proximal extremity **382** of the tube **381** on the bottom side of the tube **381** as viewed in FIG. **40** (also see FIG. **42**). The tube **381** is provided with a proximal end wall **387** which extends at a suitable angle, as for example  $45^\circ$  proximally with respect to the axis of the bore **384**.

The balloon cover assembly **316** also includes a handle **391** which, as shown, can be formed as a separate part and is secured to the proximal extremity **382** of the tube **381** by a metal clip **392**. The handle **391** is provided with a tapered body **393** formed of a suitable material such as plastic which

as shown in FIGS. **42** and **47** is open on the bottom side to make accessible a longitudinally extending recess **394** which is semi-circular in cross-section. A pair of sideways extending wings **396** are formed integral with the body **393** and lie in a plane which is substantially coincident with the axis of the semi-circular recess **394**. As shown, the wings **396** are disposed at the proximal extremity of the body **393**.

An upwardly extending fin **397** is formed on the body **393** substantially equidistant from the wings **396** in a direction generally perpendicular to the plane in which the wings **396** lie. The fin **397** is relatively narrow and is provided with an upper surface **378** having notches **401** and **402** therein. A vertically extending wall **406** is formed as a part of the fin **397** and extends generally in a direction which is perpendicular to the plane of the wings **396**. The wall **406** extends in a direction at right angles to the fin **397** and has a gradually increasing thickness from the top to the bottom ends of the wall (see FIG. **46**). The body **393** is provided with a pair of spaced-apart holes **407** spaced approximately  $90^\circ$  apart and  $45^\circ$  from each side of the fin **397**. An elongate slot **408** is formed in the body **393** and is generally in alignment with the fin **397**. A pair of camming slots **411** are provided on opposite sides of the body **393** in the wings **396** adjacent the distal extremities of the wings adjacent the body. The camming slots **411** are provided with inclined camming surfaces **412**.

The body **393** is provided with a pair of diametrically disposed protrusions **413** which extend into the recess **394** and which are adapted to seat in a pair of diametrically opposed holes **414** provided in the distal extremity of the introducer member **342**.

The balloon cover assembly **316** also includes a clamping member **416** which is provided with a central body **417** and a pair of downwardly extending legs **418** and **419** (see FIG. **43**) which extend downwardly into the camming slots **411**. As shown, the central body **417** is disposed just distal of the fin **397** and is provided with semi-circular guides **421** formed integral with the central body **417** and disposed on opposite sides of the fin **397** in a fulcrum region which is just slightly above the point of commencement of the legs **418** and **419**. The central body **417** is provided with longitudinally extending reinforcing ribs **422** (see FIGS. **43** and **45**). It is also provided with a proximally extending latch portion **426** which extends generally at right angles to the central body **417**. The latch portion **426** is provided with a centrally disposed slot **427** extending substantially the entire length thereof which receives the upper extremity of the fin **397** so that when the clamping member **416** is snapped into place over the body **393**, the latch portion **426** is disposed in the notch **401** and cannot clear the uppermost portion of the fin **397**. The clamping member **416** as hereinafter described is adapted to be moved between positions in which it is disposed within the notch **401** or alternatively in the notch **402**. Laterally extending rounded raised portions **428** are provided on the central body **417** are adapted to be engaged by a finger of the hand when moving the clamping member **416** from the notch **401** to the notch **402**.

Operation and use of the surgical balloon dissection apparatus **301** in performing the method for developing an anatomic space for laparoscopic hernia repair in connection with the apparatus shown in FIGS. **39-48** may now be briefly described as follows in conjunction with the cartoons which are shown in FIG. **49a** through FIG. **49g**. The surgeon in connection with the present method identifies the appropriate fascia layer to be dissected, either by direct visualization of the tissue and/or by manual palpation. Let it be assumed that it is desired to perform a hernia repair on a patient **451**

and that it is desired to create an extraperitoneal working space for performing the surgical repair. The surgeon makes a small incision **452** in the skin of the patient in the umbilicus or slightly lateral of the umbilicus. A retractor (not shown) can then be utilized to open up the incision and to move it laterally to either side to locate the rectus muscles that run longitudinally of the body of the patient on both sides of the umbilicus or navel. As soon as the rectus sheath has been located, the incision is made in the rectus sheath through the incision previously made midway between the two sets of the rectus muscles. The surgeon then grasps the laparoscopic or balloon dissection apparatus **301** by using a hand, as for example, his right hand as shown in FIG. **49A** to grasp the handle assembly **337** to introduce the blunt end **331** into the incision to engage the anterior wall of the posterior rectus sheath. The balloon dissector **301** is then advanced longitudinally of the patient's body generally parallel to the two sets of rectus muscles as shown by the arrow **453** by using the rectus sheath as a guide to pass the blunt tip **331** to cause separation of tissue and to pass over the arcuate line and transversal is fascia to the level of the symphysis pubis. This can be readily accomplished with the balloon dissector **301** because the balloon cover assembly **316** is latched to and generally rigidly connected to the distal extremity of the introducer member **342** of the introducer device **307** by having the protrusions **413** provided on the tubular cover **381** seated within the holes **414** provided on the distal extremity of the introducer member **342**. This provides a rigid assembly of the balloon dissector **301** so it can be operated by the surgeon grasping the handle assembly **337** without the need to have the physician grasp by the other hand an intermediate part of the balloon dissector to cause a desired manipulation and steering of the blunt tip **331** as the dissection of the tissue is accomplished as it is advanced.

The travel of the blunt tip **331** to the level of the symphysis pubis can be readily ascertained by the surgeon who can use his hand to palpate the abdominal region of the patient and thereby feel the blunt tip **331** as it is advanced until the blunt tip **331** strikes the symphysis pubis. This can be readily ascertained by the right hand holding the handle assembly **337** feeling the impact of the tip **331** striking the symphysis pubis **468** (see FIG. **50**) which impact is communicated through the rigid structure of the balloon dissector to the handle assembly **337** where it can be felt by the hand of the surgeon. The balloon dissector **301** is then advanced a small additional amount so that the blunt tip **331** drops below the symphysis pubis **468**.

Thereafter, the balloon cover handle **391** is engaged by the same right hand of the physician as shown in FIG. **49B** and the thumb is used to engage the transverse rounded protrusions **428** by moving the upper extremity of the clamping or latching member **416** proximally to cause the latch portion **426** to move into engagement with the notch **402** carried by the fin **397**. As this is occurring, the legs **418** and **419** carried by the central body **417** are moved from the position shown in FIG. **42** to the position shown in FIG. **47** and in doing so engaging the camming surfaces **412** whereby the portions of the wings **396** secured to the body **393** are cammed outwardly so that the protrusions **413** are moved out of engagement with the holes **414**. The direction of movement of the latch or clamping member **416** is indicated by the arrow **454** in FIG. **49B**. As soon as the handle **391** has been released, the handle **391** is moved proximally with two fingers of the hand grasping the wings **396** to pull them upwardly and proximally to cause the balloon cover assembly **316** to be removed. The balloon **361** is held in place by the tunneling

shaft or rod **336** and exits through the slit **386** provided at the bottom of the tubular cover **381** which serves as a tear away sheath. The balloon inflation tube **366** is retained in one of the slots **360** in the shoulders **359** so that it does not become entangled in the wings **396** as the balloon cover assembly **316** is removed. This exposes the balloon **361** which has its side margins rolled inwardly in rolls **461** with one being rolled in a counterclockwise direction and the other being rolled in a clockwise direction so that they underlie the tunneling rod **333** as shown in FIG. **50**. Also, to provide optimum dissection as hereinafter described before the rolling up occurs the forwardly extending protuberance **362** can be folded inwardly along a fold line **471** and the sidewardly extending lobe portions also can be folded inwardly along fold lines **472**. To inflate the balloon, the pinch off clamp **372** is closed and a conventional 60 cc syringe **476** containing a saline solution is connected to the one-way valve **368**. The syringe **466** is then operated as shown by the arrow **477** to introduce the saline solution from the syringe **476** into the tubular member **366** and into the interior of the balloon **361** to gradually inflate the same. The one-way check valve **368** ensures that saline solution cannot exit therefrom when the syringe **466** is removed. The syringe **476**, after it has been emptied, can be removed and refilled with a saline solution which is introduced into the balloon in the same manner to cause the side margins of the balloon **461** to unwrap in opposite directions as shown in FIG. **50** on opposite sides of the tunneling rod **333** until they become completely unwrapped. Typically, it may take as many as approximately ten syringes of saline solution to cause the balloon **361** to completely unwrap and the move into an inflated condition as shown in FIG. **50**. As the balloon is being filled and unwrapping, it continues to separate or dissect tissue overlying the peritoneum to provide an extraperitoneal working space between the transversalis fascia and the rectus muscles.

As hereinbefore described, the balloon **361** in plan has an asymmetric manta ray-like configuration to provide the desired optimum extraperitoneal working space for the hernia repair. The forwardly extending protrusion **362** provided on the balloon **361** as it is inflated dissects distally from the distal extremity of the blunt tip **331** of the guide rod **333** serves to provide good dissection of tissue in the area of Cooper's ligaments and also to dissect laterally around the inguinal rings. By utilizing an asymmetric manta ray-like construction, it is possible to provide a balloon **361** with its wide side margins or lobe portions **361a** and **361b** which when inflated to cause forward movement of the balloon **361** to dissect downwardly around the inguinal rings and to wedge the balloon **361** in place. The forwardly extending protrusion **362** as it is inflated dissects like a small balloon down to the Cooper's ligament. In this way, it is impossible to obtain an extraperitoneal working space **478** which exposes all the desired anatomy at one time before moving off to the hernia sac and to do the final dissection for the hernia repair. By providing such a large extraperitoneal working space it is unnecessary to manually advance the dissection. The balloon has also been shaped to properly match the anatomy in which the procedure is to be formed so as to reduce to a minimum the amount of manual dissection which may be needed. Since the balloon has a particular shape and is formed of a non-elastomeric material, the dissection will occur in the desired locations which would not necessarily be the case if the balloon were formed of an elastomeric material which generally would have a tendency to follow the path of least resistance. Additional assurance is provided for ensuring that dissection will occur in the desired loca-

tions with the non-elastomeric balloon of the present invention because the balloon is held in place by the tunneling rod 333 underlying the symphysis pubis 468 as shown in FIG. 50. Also, by providing roughened areas 365, these areas frictionally engage overlying tissue so that the lobe portions 361a and 361b can serve as anchors to prevent displacement of the balloon 361 after the balloon 361 as it is being inflated.

After the amount of desired tissue dissection has taken place by inflation of the balloon 361 to provide the extraperitoneal working space, the balloon 361 is deflated by connecting the evacuation fitting 371 into an evacuation port (not shown) of an operating room suction system. The pinch clamp 372 is released to open the tube 369 to permit the saline solution which had been introduced into the balloons 361 to be sucked out to completely deflate the balloon from the inflated condition as shown in FIG. 49C. After the balloon has been deflated, the tubular member 366 can be grasped by the fingers of the hand as shown, and the deflated balloon 361 pulled out through the incision 452 in the direction as shown by the arrow 481 in FIG. 49D. If necessary, the handle assembly 337 can be held by the other hand. The balloon 361, as it is being pulled off, has its sleeve 376 separates from the tunneling or guide rod 331 by breaking through the linear perforations lying along the line 378. The guide rod 331 remains in place to preserve an easy entry into the extraperitoneal space which has been created. The balloon 361 can then be discarded.

After the balloon 361 has been removed, the left hand is used to grasp the lower second handle part 38 with the left hand while the right hand engages the upper or first handle part 336 of the handle assembly 337. The fingers of the right hand then engage the latch members 339 on opposite sides by the fingers of the hand to release the first part 336 from the second part 338 and to permit the left hand to move the second part 338 in the direction of the arrow 482 shown in FIG. 49E. The second part 338 carries with it the cannula 302 attached thereto and the introducer device 307 which extends therethrough with the skin seal assembly 311 mounted on the cannula tube 321. This advancement over the guide rod 333 is continued until the distal extremity 343 of the introducer member 342 has been advanced into the desired position. As soon as this has been accomplished, the skin seal assembly 311 is slidably advanced on the cannula tube 321 until the skin seal approaches the incision 452. The screw body 351 is then rotated by the fingers of the hand engaging the flange 352, and/or to the shoulder 359 to screw it into the incision 452 and to form a gas tight skin seal with the skin of the patient. As soon as a good skin seal has been established, the introducer device 307 is clamped in a fixed position with respect to the skin seal assembly 311 by pushing generally downwardly on the collar 356 to engage the collet 357 to form a friction grip between the elastomeric insert 353 and the cannula tube 321.

After the cannula 302 is in a fixed in position, the blunt obturator 306 can be removed along with the tunneling device or blunt obturator device 303. This is accomplished merely by continuing to pull upwardly on the handle part. 336 with the hand in the direction indicated by the arrow 483 as shown in FIG. 49F. As this pulling motion continues, the blunt tip 331 will engage the distal extremity 343 of the introducer member 342 causing a withdrawal force to be applied to the second handle part 338 to cause it to automatically release from the housing 326. This permits the blunt obturator device 303 to be removed through the cannula tube 321. This is possible because the blunt tip 331 has a diameter which can pass through the interior of the

cannula tube 321 and through the valving provided in the housing 326. In withdrawing the guide rod 333 carrying the obturator tip 331, it can be seen that it continues to be guided by the introducer member 342 and thus will remain centered with respect to the cannula tube 321 to avoid any pinching action at the distal end 323 of the cannula tube 321. As soon as the obturator tip 331 strikes the introducer member 342, the handle part 338 is automatically disengaged from the cannula handle 326. The latch parts 349 are substantially buried within the second handle part 338 so they are relatively inaccessible to the surgeon ensuring that he will operate the latch parts 339 carried by the first handle 336 which helps to ensure that the surgeon remove the handle parts 336 and 338 in two stages.

After this has been accomplished, a source of gas such as carbon dioxide is connected to the stop cock valve 328. The stop cock valve 328 is opened to permit the carbon dioxide to inflate the dissected extraperitoneal working space such as indicated by the dotted lines 476 shown in FIG. 49G. The cannula 302 can then be utilized for introducing instruments of various types into the dissected extraperitoneal working space. The inflation gas cannot escape because of the valving provided in the handle 326 of the cannula 302.

Additional cannulae can be introduced in various positions in the abdomen of the patient through which additional surgical instruments can be introduced for performing the surgical procedure to be performed in the extraperitoneal working space. The remainder of the hernia repair procedure to be accomplished in the extraperitoneal working space is substantially the same as hereinbefore described and therefore will not be described in detail. By way of example, let it be assumed that a hernia sac has been formed in the patient, as for example, by passing down into the scrotum to form a typical indirect hernia. The hernia sac can be pulled out and ligated in a manner hereinbefore described. Thereafter, a piece of mesh as hereinbefore described can be introduced through another site and rolled out over the region through which the sac had previously passed. The mesh can then be stapled in place, as for example along the Cooper's ligament. After the hernia repair has been completed, the extraperitoneal working space can be deflated by opening the stop cock valve 328 and bleeding the CO<sub>2</sub> contained therein to atmosphere to permit the abdominal wall to return to its normal position to help retain the mesh which has been placed in the desired position.

In connection with the formation of the extraperitoneal working space with the apparatus of the present invention, it has been found that it is desirable to have the guide rod 333 be in position in which it overlies the balloon 361, because this helps to ensure that the balloon dissection will occur in appropriate areas because the blunt tip 331 underlying the symphysis pubis is retained in the desired position even during the time that the balloon is unrolling during inflation. Positioning the guide rod 333 in this manner ensures that the balloon 361 will roll out in the opposite directions from the rod and also to help to push the balloon downwardly during inflation.

In order to make the apparatus more user friendly, the parts which are to be moved for operation with respect to other parts have been color coded, as for example they can be colored black with the remaining parts being of another color, such as grey or white. Thus, the clamping or latch member 416 is of a black color because it must be removed to unlatch the balloon cover assembly 316. Similarly, the collar 356 of the skin seal assembly 311 is of a black color because it must be moved to clamp the cannula 302 in a

desired position. Similarly, the latch parts 339 and 349 are of black color because they also must be moved to separate the handle parts.

The wings 396 are provided on the balloon cover 316 in addition to serving as means to facilitate grasping of the balloon cover assembly 316 when it is desired to remove the same, as serve to visually indicate the plane in which the balloon 361 of the balloon dissection apparatus 301 causes dissection. Generally this dissection plane is in a plane which is parallel to the plane in which the wings 396 lie.

As hereinbefore explained, the introducer member 342 is provided with an obturator end surface or tip which is inclined at an angle in a direction away from the normal direction of insertion to inhibit any tendency that the tip 35 might hang up on tissue as it is being advanced through the tissue during dissection.

The sizing of the blunt obturator tip 331 so it is smaller than the inner diameter of the cannula tube 321 helps to ensure that tissue will not become entrapped or pinched between the tip 331 and the cannula tube 321. In addition, as hereinbefore described, the obturator tip 331 is tapered in both directions into a smaller dimension from the center to also minimize the possibility of any tissue being entrapped between the tip 331 and the cannula tube 321 and thereby ensuring that a shearing action will not occur.

In conjunction with the foregoing disclosure, it has been assumed that the balloon dissection apparatus hereinbefore described typically would be disposed of after each use. In the event it is desired to economize and it is desired to reutilize at least certain portions of the balloon dissection apparatus after a use in a laparoscopic procedure, another embodiment of a balloon dilatation apparatus 501 incorporating the present invention is shown in FIGS. 51-55. As shown therein, it consists of a handle assembly 502 similar to the handle assembly 337 hereinbefore described which includes a handle part 503 similar to the handle part 336. Other parts of the balloon dissection apparatus 501 are not shown because they can be identical to those hereinbefore described. The handle part 503 is provided with two sections 506 and 507 which can be fastened together in a suitable manner such as by ultrasonic bonding or an adhesive. Latch members 511 and 512 are provided on opposite sides of the handle part 503 and are provided with finger portions 513 that are adapted to be engaged by fingers of the hand which extend outwardly through recesses 514 in the sections 506 and 507. The latch members 511 and 512 are each provided with a latch 516 which is yieldably urged in an outward direction by a yieldable spring member 517 engaging a downwardly depending lip 518 provided within the sections 506 and 507. The latch members 511 and 512 are pivotally mounted between the sections 506 and 507 by pivot pins 519 formed integrally on the latch members 511 and 512 and extending into bosses 521 provided in the sections 506 and 107 which are formed of a suitable material such as plastic.

First and second inserts 526 and 527 formed of a suitable material such as plastic are mounted in the sections 506 and 507. First and second latch members 531 and 532 formed of a suitable material such as metal are provided which are seated in recesses 533 and 534 provided in the inserts 526 and 527. The latch members 531 and 532 are generally U-shaped and are yieldably urged into engagement with each other to form an elongate slot 536 extending there-through. Upstanding legs 538 formed integral with the inserts 526 and 527 are provided in rectangular spaces 539 in the inserts 526 and 527 so that the upper extremities of the legs 538 can be flexed by movement of the latch members 531 and 532 as shown by dotted lines in FIG. 54.

A guide rod 541 is provided which is similar to the guide rod 333 with the exception that its distal extremity 542 is also provided with an annular recess 533. The distal extremity 542 is provided with a chamfer 544 and a pair of opposed flats 546 which extend through the chamfer 544. The guide rod 541 extends through a hole 551 provided by semicircular recesses formed in the sections 506 and 507 and by a hole 552 formed by semicircular recesses in the inserts 526 and 527. A larger hole 553 formed by semicircular recesses in the inserts 526 and 527 of a larger diameter than the hole 552 is provided which receives a push-button 556 and extends through a hole 557 also formed by semicircular recesses provided in the sections 506 and 507. A dish-shaped or concave recess 558 is provided in the sections 506 and 507 and facilitates engaging the push-button 556 by a finger of the hand.

The pushbutton 556 is provided with a bore 561 which is sized so that it can receive the distal extremity 542 of the guide rod 541. The pushbutton is provided with sideways extending skirts 562 extending 180° with respect to each other and which are provided with distally and inwardly extending camming surfaces 563 which terminate at a tip 564 that is generally V-shaped as shown in FIG. 51. The tip 564 is formed so that it is adapted to enter into the slot 536 formed by the U-shaped members 531 and 532. Thus, when the pushbutton 556 is depressed, the tip 564 will enter the slot 536 in a progressive manner to urge them apart so that the camming surfaces 563 carried thereby engage the U-shaped latch members 531 and 532, in regions just above and below the guide rod 541 so that the guide rod 541 is released by the U-shaped latch members 531 and 532 permitting it to be pulled out of the handle part 503. Release of the guide rod 541 makes it possible to separate the guide rod 541 from the remainder of the balloon dissection apparatus 501 so that the handle assembly 502 and the other parts carried thereby can be separated from the guide rod. Thereafter, the guide rod 541, the balloon 361 and the balloon cover assembly 316 can be disposed of. The other parts of the apparatus can be reutilized after appropriate sterilization. In order to ensure that the other parts survive sterilization, it may be desirable to form the plastic reusable parts of a suitable plastic such as a polysulfone.

In connection with the foregoing, it can be seen that by making minor changes in the construction it is possible to save a great number of parts of the balloon dissection apparatus for reuse after sterilization. Only the parts which are most difficult to clean are disposed of after a one-time use.

From the foregoing it can be seen that there has been provided an apparatus and method which is particularly suitable for developing an anatomic space such as an extraperitoneal working space between the abdominal wall and the peritoneum by dissecting tissue with the use of a non-elastomeric balloon. The balloon dissection apparatus has many features facilitating its use in developing such an anatomic space and for particularly developing an extraperitoneal working space for hernia repair.

What is claimed is:

1. An apparatus for creating an anatomic space comprising:

a tubular member having a bore extending therethrough; a handle including a proximal section, a distal section, and an intermediate section therebetween, said distal section attached to said tubular member and having a bore therein in alignment with said bore in said tubular member;

25

- a tunneling shaft slidably mounted in said bore of said tubular member, said tunneling shaft secured to the proximal section and including a blunt distal end for tunneling through tissue wherein said proximal section is detachable from said intermediate section to permit said tunneling shaft to move longitudinally through the apparatus;
- a deflated balloon attached to said tunneling shaft; and a sheath enclosing said balloon and having a weakened region extending longitudinally thereof permitting said sheath to be removed from said balloon.
2. The apparatus of claim 1, further comprising: an obturator having opposed open ends and defining a passageway therethrough and attached to the intermediate section, said obturator and intermediate section being slidably mounted on said tunneling shaft.
3. The apparatus of claim 2, wherein said blunt distal end has a diameter greater than a diameter of the passageway of said obturator.
4. The apparatus of claim 3, wherein the blunt distal end has diameter less than a diameter of said bore of said tubular member.
5. The apparatus of claim 2, further comprising: a monolithically formed handle attached to a proximal region of said sheath wherein proximal movement of said handle causes the weakened region of the sheath to separate thereby allowing said sheath to be removed from said balloon.
6. The apparatus of claim 5, wherein said handle includes one or more protrusions adapted to be received by one or more complementary recesses in said obturator for releasably securing said handle to said apparatus.
7. The apparatus of claim 1, further comprising: a valve member mounted in said distal section and movable between a first position wherein said bore in said distal section is sealed and a second position wherein said bore in said distal section is open.
8. The apparatus of claim 1, wherein said balloon is releasably attached to the tunneling shaft.
9. The apparatus of claim 8, wherein said balloon includes a sleeve extending along one surface of the balloon wherein said sleeve includes a weakened region.

26

10. The apparatus of claim 9, wherein at least one of said weakened regions includes a plurality of spaced-apart perforations.
11. The apparatus of claim 1 wherein said balloon further includes an interior space and an inflation lumen, said inflation lumen extending from said balloon and in fluid communication with the interior space.
12. An apparatus for creating an anatomic space comprising:  
 a tubular member having a bore extending therethrough;  
 a first handle attached to said tubular member and having a bore therein in alignment with said bore in said tubular member;  
 a tunneling shaft slidably mounted in said bore of said tubular member, said tunneling shaft secured to a second handle and including a blunt distal end for tunneling through tissue wherein said second handle is detachable from said first handle to permit said tunneling shaft to move longitudinally through the apparatus;  
 a deflated balloon attached to said tunneling shaft; and  
 a sheath enclosing said balloon and having a weakened region extending longitudinally thereof permitting said sheath to be removed from said balloon.
13. The apparatus of claim 12, wherein the second handle has a proximal section and an intermediate section, the intermediate section having latches for attachment to the first handle.
14. The apparatus of claim 13, further comprising an introducer member attached to the intermediate section, the introducer member having a bore for receiving the tunneling shaft and the introducer member being received in the tubular member.
15. The apparatus of claim 12, wherein the first handle comprises a cannula housing having a fitting in communication with the bore in the tubular member.
16. The apparatus of claim 15, wherein the cannula housing includes at least one valve member.

\* \* \* \* \*

|                |                                                                                                                                                                                                                          |         |            |
|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|------------|
| 专利名称(译)        | 用于开发用于腹腔镜疝修补的解剖学空间的装置和方法以及与其一起使用的贴片                                                                                                                                                                                      |         |            |
| 公开(公告)号        | <a href="#">US7297153</a>                                                                                                                                                                                                | 公开(公告)日 | 2007-11-20 |
| 申请号            | US11/208672                                                                                                                                                                                                              | 申请日     | 2005-08-22 |
| [标]申请(专利权)人(译) | KIETURAKIS马切伊Ĵ<br>MOLLENAUER KENNETH ^ h<br>蒙福特MICHELLEÿ<br>KAYAN HELMUT大号                                                                                                                                               |         |            |
| 申请(专利权)人(译)    | KIETURAKIS马切伊Ĵ<br>MOLLENAUER KENNETH ^ h<br>蒙福特MICHELLEÿ<br>KAYAN HELMUT大号                                                                                                                                               |         |            |
| 当前申请(专利权)人(译)  | 普外科创新股份有限公司.                                                                                                                                                                                                             |         |            |
| [标]发明人         | KIETURAKIS MACIEJ J<br>MOLLENAUER KENNETH H<br>MONFORT MICHELLE Y<br>KAYAN HELMUT L                                                                                                                                      |         |            |
| 发明人            | KIETURAKIS, MACIEJ J.<br>MOLLENAUER, KENNETH H.<br>MONFORT, MICHELLE Y.<br>KAYAN, HELMUT L.                                                                                                                              |         |            |
| IPC分类号         | A61B17/00 A61B1/32 A61M29/00 A61B1/00 A61B1/303 A61B1/307 A61B1/31 A61B1/313 A61B17/02 A61B17/03 A61B17/32 A61B17/34 A61B18/08 A61B19/00 A61F2/00 A61F2/958 A61M25/06 A61M29/02                                          |         |            |
| CPC分类号         | A61B17/0218 A61M29/02 A61B18/08 A61F2/0063 A61M25/0668 A61M25/1002 A61B17/320016 A61B17/3421 A61B17/3439 A61B19/5212 A61B2017/00557 A61B2017/320044 A61B2017/320048 A61B2019/4868 A61F2002/0072 A61B90/361 A61B2090/0813 |         |            |
| 其他公开文献         | US20060036277A1                                                                                                                                                                                                          |         |            |
| 外部链接           | <a href="#">Espacenet</a> <a href="#">USPTO</a>                                                                                                                                                                          |         |            |

#### 摘要(译)

用于在身体组织中产生解剖学空间的设备包括导引器和护套。管状护套可以围绕导引器，并且可以沿其纵向轴线具有弱化区域。手柄可以设置在护套上。手柄可以适于向近侧拉动以分离弱化区域并允许护套从导引器移除。护套可以通过手柄上的棘爪或闩锁固定到导引器上。

