



US 20150265342A1


(19) **United States**(12) **Patent Application Publication****Long et al.**(10) **Pub. No.: US 2015/0265342 A1**(43) **Pub. Date: Sep. 24, 2015**(54) **ELECTRICAL ABLATION DEVICES****Publication Classification**(71) Applicant: **Ethicon Endo-Surgery, Inc.**, Cincinnati, OH (US)(72) Inventors: **Gary L. Long**, Cincinnati, OH (US); **Ragae M. Ghabrial**, Pittsburgh, PA (US); **David N. Plescia**, Mentor, OH (US); **Omar J. Vakharia**, Cincinnati, OH (US)(51) **Int. Cl.****A61B 18/14** (2006.01)**A61B 18/12** (2006.01)(52) **U.S. Cl.**CPC **A61B 18/1492** (2013.01); **A61B 18/1477** (2013.01); **A61B 18/1206** (2013.01); **A61B 2018/00898** (2013.01)(21) Appl. No.: **14/673,111**(22) Filed: **Mar. 30, 2015****Related U.S. Application Data**

(60) Continuation of application No. 13/602,742, filed on Sep. 4, 2012, now Pat. No. 9,011,431, which is a division of application No. 12/352,375, filed on Jan. 12, 2009, now Pat. No. 8,361,066.

(57)

ABSTRACT

An electrical ablation apparatus comprises first and second electrodes. Each electrode comprises a first end configured to couple an energy source and a second end configured to couple to a tissue treatment region. An energy source is coupled to the first and second electrodes. The energy source is configured to deliver a first series of electrical pulses sufficient to induce cell necrosis by irreversible electroporation and a second series of electrical pulses sufficient to induce cell necrosis by thermal heating, through at least one of the first and second electrodes. The first series of electrical pulses is characterized by a first amplitude, a first pulse length, and a first frequency. The second series of electrical pulses is characterized by a second amplitude, a second pulse length, and a second frequency.






FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 2E




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11






FIG. 12






FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23

ELECTRICAL ABLATION DEVICES

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This non-provisional patent application is a continuation patent application claiming priority under 35 U.S.C. §120 of U.S. patent application Ser. No. 13/602,742, filed Sep. 4, 2012, entitled ELECTRICAL ABLATION DEVICES, now U.S. Patent Application Publication No. 2012/0330306, which is a divisional patent application claiming priority under 35 U.S.C. §121 of U.S. patent application Ser. No. 12/352,375, filed Jan. 12, 2009, entitled ELECTRICAL ABLATION DEVICES, now U.S. Pat. No. 8,361,066, the entire disclosures of which are hereby incorporated by reference herein.

BACKGROUND

[0002] Electrical ablation therapy has been employed in medicine for the treatment of undesirable tissue such as diseased tissue, cancer, malignant and benign tumors, masses, lesions, and other abnormal tissue growths. While conventional apparatuses, systems, and methods for the electrical ablation of undesirable tissue are effective, one drawback with conventional electrical ablation treatment is the resulting permanent damage that may occur to the healthy tissue surrounding the abnormal tissue due primarily to the detrimental thermal effects resulting from exposing the tissue to thermal energy generated by the electrical ablation device. This may be particularly true when exposing the tissue to electric potentials sufficient to cause cell necrosis using high temperature thermal therapies including focused ultrasound ablation, radiofrequency (RF) ablation, or interstitial laser coagulation. Other techniques for tissue ablation include chemical ablation, in which chemical agents are injected into the undesirable tissue to cause ablation as well as surgical excision, cryotherapy, radiation, photodynamic therapy, Moh's micrographic surgery, topical treatments with 5-fluorouracil, laser ablation. Other drawbacks of conventional thermal, chemical, and other ablation therapy are cost, length of recovery, and the extraordinary pain inflicted on the patient.

[0003] Conventional thermal, chemical, and other ablation techniques have been employed for the treatment of a variety of undesirable tissue. Thermal and chemical ablation techniques have been used for the treatment of varicose veins resulting from reflux disease of the greater saphenous vein (GSV), in which the varicose vein is stripped and then is exposed to either chemical or thermal ablation. Other techniques for the treatment of undesirable tissue are more radical. Prostate cancer, for example, may be removed using a prostatectomy, in which the entire or part of prostate gland and surrounding lymph nodes are surgically removed. Like most other forms of cancer, radiation therapy may be used in conjunction with or as an alternate method for the treatment of prostate cancer. Another thermal ablation technique for the treatment of prostate cancer is RF interstitial tumor ablation (RITA) via trans-rectal ultrasound guidance. While these conventional methods for the treatment of prostate cancer are effective, they are not preferred by many surgeons and may result in detrimental thermal effects to healthy tissue surrounding the prostate. Similar thermal ablation techniques may be used for the treatment of basal cell carcinoma (BCC) tissue, a slowly growing cutaneous malignancy derived from the rapidly proliferating basal layer of the epidermis. BCC

tissue in tumors ranging in size from about 5 mm to about 40 mm may be thermally ablated with a pulsed carbon dioxide laser. Nevertheless, carbon dioxide laser ablation is a thermal treatment method and may cause permanent damage to healthy tissue surrounding the BCC tissue. Furthermore, this technique requires costly capital investment in carbon dioxide laser equipment. Undesirable tissue growing inside a body lumen such as the esophagus, large bowel, or in cavities formed in solid tissue such as the breast, for example, can be difficult to destroy using conventional ablation techniques. Surgical removal of undesirable tissue, such as a malignant or benign tumor, from the breast is likely to leave a cavity. Surgical resection of residual intraluminal tissue may remove only a portion of the undesirable tissue cells within a certain margin of healthy tissue. Accordingly, some undesirable tissue is likely to remain within the wall of the cavity due to the limitation of conventional ablation instrument configurations, which may be effective for treating line-of-sight regions of tissue, but may be less effective for treating the residual undesirable tissue.

[0004] Accordingly, there remains a need for improved electrical ablation apparatuses, systems, and methods for the treatment of undesirable tissue found in diseased tissue, cancer, malignant and benign tumors, masses, lesions, and other abnormal tissue growths. There remains a need for minimally invasive treatment of undesirable tissue through the use of irreversible electroporation (IRE) ablation techniques without causing the detrimental thermal effects of conventional thermal ablation techniques.

FIGURES

[0005] The novel features of the various described embodiments are set forth with particularity in the appended claims. The various embodiments, however, both as to organization and methods of operation, together with advantages thereof, may be understood in accordance with the following description taken in conjunction with the accompanying drawings as follows.

[0006] FIG. 1 illustrates one embodiment of an electrical ablation system.

[0007] FIGS. 2A-D illustrate one embodiment of the electrical ablation device in various phases of deployment.

[0008] FIG. 2E illustrates one embodiment of the electrical ablation device comprising multiple needle electrodes.

[0009] FIG. 3 illustrates one embodiment of the electrical ablation system shown in FIGS. 1 and 2A-D in use to treat undesirable tissue located on the surface of the liver.

[0010] FIG. 4 illustrates a detailed view of one embodiment of the electrical ablation system shown in FIG. 3 in use to treat undesirable tissue located on the surface of the liver.

[0011] FIG. 5 is a graphical representation of a series of electrical pulses that may be applied to undesirable tissue to create a first necrotic zone by inducing irreversible electroporation in the tissue and to create a second necrotic zone by inducing thermal effects near the electrode-tissue-interface using the electrical ablation system shown in FIG. 4.

[0012] FIGS. 6, 7, and 8 illustrate one embodiment of an electrical ablation device to treat undesirable tissue within body lumen using electrical energy, where FIG. 6 illustrates a sectioned view of one embodiment of an electrical ablation device, FIG. 7 illustrates an end view of one embodiment of the electrical ablation device shown in FIG. 6, and FIG. 8 illustrates a cross-sectional view of one embodiment of the electrical ablation device shown in FIG. 6.

[0013] FIG. 9 illustrates one embodiment of an electrical ablation system in use to treat non-metastatic prostate cancer in a patient.

[0014] FIG. 10 is a graphical representation of a series of electrical pulses that may be applied to undesirable tissue to induce irreversible electroporation suitable to ablate non-metastatic cancer of the prostate as described in FIG. 9.

[0015] FIG. 11 illustrates one embodiment of the electrical ablation system described FIG. 1 in use to treat basal cell carcinoma (BCC) tissue.

[0016] FIG. 12 is a graphical representation of a series of electrical pulses for treating basal cell carcinoma (BCC) tissue as shown in FIG. 11 with irreversible electroporation energy.

[0017] FIG. 13A illustrates one embodiment of an electrical ablation device, in a collapsed state, the device having a configuration suitable for the treatment of abnormal tissue located in a lumen, abscess, void, or cavity.

[0018] FIG. 13B illustrates one embodiment of the electrical ablation device shown in FIG. 13A, in an inflated state, the device having a configuration suitable for the treatment of abnormal tissue located in a lumen, abscess, void, or cavity.

[0019] FIG. 14 is a cross-sectional view of the electrical ablation device showing a cross-sectional view of the conductive elastomer electrode and the non-conductive catheter shown in FIGS. 13A and 13B.

[0020] FIG. 15 illustrates one embodiment of the electrical ablation device shown in FIG. 13A inserted through the mouth and esophagus to ablate cancerous tissue in the esophagus using electrical pulses.

[0021] FIG. 16 illustrates a distal portion of an endoscope used in conjunction with the electrical ablation device shown in FIG. 13A.

[0022] FIG. 17 illustrates a cross-sectional view of a breast showing a cavity that may be left after a lumpectomy to remove a tumor from the breast.

[0023] FIG. 18 illustrates one embodiment of a catheter inserted into the cavity left in the breast following a lumpectomy procedure as shown in FIG. 17.

[0024] FIG. 19 illustrates an expanded sponge filling the cavity left in the breast following a lumpectomy as shown in FIG. 17.

[0025] FIG. 20 illustrates the expanded sponge intact to fill the cavity left in the breast as shown in FIG. 17 following irreversible electroporation ablation therapy.

[0026] FIG. 21 illustrates a mesh of a finite element model of a sponge inserted in the cavity left in the breast as shown in FIG. 17.

[0027] FIG. 22 is a graphical representation of electric potential and electrical field strength sufficient to induce irreversible electroporation when applied to the sponge located within the breast cavity as shown in FIG. 17.

[0028] FIG. 23 is a graphical representation of electric field strength contours in volts per meter (V/m) developed when electrodes are energized by an energy source.

DESCRIPTION

[0029] Various embodiments are directed to apparatuses, systems, and methods for the electrical ablation treatment of undesirable tissue such as diseased tissue, cancer, malignant and benign tumors, masses, lesions, and other abnormal tissue growths without causing any detrimental thermal effects to surrounding healthy tissue. Numerous specific details are set forth to provide a thorough understanding of the overall

structure, function, manufacture, and use of the embodiments as described in the specification and illustrated in the accompanying drawings. It will be understood by those skilled in the art, however, that the embodiments may be practiced without the specific details. In other instances, well-known operations, components, and elements have not been described in detail so as not to obscure the embodiments described in the specification. Those of ordinary skill in the art will understand that the embodiments described and illustrated herein are non-limiting examples, and thus it can be appreciated that the specific structural and functional details disclosed herein may be representative and do not necessarily limit the scope of the embodiments, the scope of which is defined solely by the appended claims.

[0030] Reference throughout the specification to “various embodiments,” “some embodiments,” “one embodiment,” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment. Thus, appearances of the phrases “in various embodiments,” “in some embodiments,” “in one embodiment,” or “in an embodiment” in places throughout the specification are not necessarily all referring to the same embodiment. Furthermore, the particular features, structures, or characteristics may be combined in any suitable manner in one or more embodiments. Thus, the particular features, structures, or characteristics illustrated or described in connection with one embodiment may be combined, in whole or in part, with the features, structures, or characteristics of one or more other embodiments without limitation.

[0031] It will be appreciated that the terms “proximal” and “distal” may be used throughout the specification with reference to a clinician manipulating one end of an instrument used to treat a patient. The term “proximal” refers to the portion of the instrument closest to the clinician and the term “distal” refers to the portion located furthest from the clinician. It will be further appreciated that for conciseness and clarity, spatial terms such as “vertical,” “horizontal,” “up,” and “down” may be used herein with respect to the illustrated embodiments. However, surgical instruments may be used in many orientations and positions, and these terms are not intended to be limiting and absolute.

[0032] Various embodiments of apparatuses, systems, and methods for the electrical ablation treatment of undesirable tissue such as diseased tissue, cancer, malignant and benign tumors, masses, lesions, and other abnormal tissue growths, are described throughout the specification and illustrated in the accompanying drawings. The electrical ablation devices in accordance with the described embodiments may comprise one or more electrodes configured to be positioned into or proximal to undesirable tissue in a tissue treatment region (e.g., target site, worksite) where there is evidence of abnormal tissue growth, for example. In general, the electrodes comprise an electrically conductive portion (e.g., medical grade stainless steel) and are configured to electrically couple to an energy source. Once the electrodes are positioned into or proximal to the undesirable tissue, an energizing potential is applied to the electrodes to create an electric field to which the undesirable tissue is exposed. The energizing potential (and the resulting electric field) may be characterized by multiple parameters such as frequency, amplitude, pulse width (duration of a pulse or pulse length), and/or polarity. Depending on the diagnostic or therapeutic treatment to be rendered, a particular electrode may be configured either as an anode (+) or

a cathode (−) or may comprise a plurality of electrodes with at least one configured as an anode and at least one other configured as a cathode. Regardless of the initial polar configuration, the polarity of the electrodes may be reversed by reversing the polarity of the output of the energy source.

[0033] In various embodiments, a suitable energy source may comprise an electrical waveform generator, which may be configured to create an electric field that is suitable to create irreversible electroporation in undesirable tissue at various electric field amplitudes and durations. The energy source may be configured to deliver irreversible electroporation pulses in the form of direct-current (DC) and/or alternating-current (AC) voltage potentials (e.g., time-varying voltage potentials) to the electrodes. The irreversible electroporation pulses may be characterized by various parameters such as frequency, amplitude, pulse length, and/or polarity. The undesirable tissue may be ablated by exposure to the electric potential difference across the electrodes.

[0034] In one embodiment, the energy source may comprise a wireless transmitter to deliver energy to the electrodes using wireless energy transfer techniques via one or more remotely positioned antennas. Those skilled in the art will appreciate that wireless energy transfer or wireless power transmission is the process of transmitting electrical energy from an energy source to an electrical load without interconnecting wires. An electrical transformer is the simplest instance of wireless energy transfer. The primary and secondary circuits of a transformer are not directly connected and the transfer of energy takes place by electromagnetic coupling through a process known as mutual induction. Power also may be transferred wirelessly using RF energy. Wireless power transfer technology using RF energy is produced by Powercast, Inc. and can achieve an output of 6 volts for a little over one meter. Other low-power wireless power technology has been proposed such as described in U.S. Pat. No. 6,967,462.

[0035] The apparatuses, systems, and methods in accordance with the described embodiments may be configured for minimally invasive ablation treatment of undesirable tissue through the use of irreversible electroporation to be able to ablate undesirable tissue in a controlled and focused manner without inducing thermally damaging effects to the surrounding healthy tissue. The apparatuses, systems, and methods in accordance with the described embodiments may be configured to ablate undesirable tissue through the use of electroporation or electropermeabilization. More specifically, the apparatuses, systems, and methods in accordance with the described embodiments may be configured to ablate undesirable tissue through the use of irreversible electroporation. Electroporation increases the permeabilization of a cell membrane by exposing the cell to electric pulses. The external electric field (electric potential/per unit length) to which the cell membrane is exposed to significantly increases the electrical conductivity and permeability of the plasma in the cell membrane. The primary parameter affecting the transmembrane potential is the potential difference across the cell membrane. Irreversible electroporation is the application of an electric field of a specific magnitude and duration to a cell membrane such that the permeabilization of the cell membrane cannot be reversed, leading to cell death without inducing a significant amount of heat in the cell membrane. The destabilizing potential forms pores in the cell membrane when the potential across the cell membrane exceeds its dielectric strength causing the cell to die under a process

known as apoptosis and/or necrosis. The application of irreversible electroporation pulses to cells is an effective way for ablating large volumes of undesirable tissue without deleterious thermal effects to the surrounding healthy tissue associated with thermal-inducing ablation treatments. This is because irreversible electroporation destroys cells without heat and thus does not destroy the cellular support structure or regional vasculature. A destabilizing irreversible electroporation pulse, suitable to cause cell death without inducing a significant amount of thermal damage to the surrounding healthy tissue, may have amplitude in the range of about several hundred to about several thousand volts and is generally applied across biological membranes over a distance of about several millimeters, for example, for a relatively long duration. Thus, the undesirable tissue may be ablated in-vivo through the delivery of destabilizing electric fields by quickly creating cell necrosis.

[0036] The apparatuses, systems, and methods for electrical ablation therapy in accordance with the described embodiments may be adapted for use in minimally invasive surgical procedures to access the tissue treatment region in various anatomic locations such as the brain, lungs, breast, liver, gall bladder, pancreas, prostate gland, and various internal body lumen defined by the esophagus, stomach, intestine, colon, arteries, veins, anus, vagina, cervix, fallopian tubes, and the peritoneal cavity, for example, without limitation. Minimally invasive electrical ablation devices may be introduced to the tissue treatment region using a trocar inserted through a small opening formed in the patient's body or through a natural body orifice such as the mouth, anus, or vagina using transluminal access techniques known as Natural Orifice Transluminal Endoscopic Surgery (NOTES)TM. Once the electrical ablation devices (e.g., electrodes) are located into or proximal to the undesirable tissue in the treatment region, electric field potentials can be applied to the undesirable tissue by the energy source. The electrical ablation devices comprise portions that may be inserted into the tissue treatment region percutaneously (e.g., where access to inner organs or other tissue is done via needle-puncture of the skin). Other portions of the electrical ablation devices may be introduced into the tissue treatment region endoscopically (e.g., laparoscopically and/or thoracoscopically) through trocars or working channels of the endoscope, through small incisions, or transcutaneously (e.g., where electric pulses are delivered to the tissue treatment region through the skin).

[0037] FIG. 1 illustrates one embodiment of an electrical ablation system 10. The electrical ablation system 10 may be employed to ablate undesirable tissue such as diseased tissues, cancers, tumors, masses, lesions, abnormal tissue growths inside a patient using electrical energy. The electrical ablation system 10 may be used in conjunction with endoscopic, laparoscopic, thoracoscopic, open surgical procedures via small incisions or keyholes, percutaneous techniques, transcutaneous techniques, and/or external non-invasive techniques, or any combinations thereof without limitation. The electrical ablation system 10 may be configured to be positioned within a natural body orifice of the patient such as the mouth, anus, or vagina and advanced through internal body lumen or cavities such as the esophagus, colon, cervix, urethra, for example, to reach the tissue treatment region. The electrical ablation system 10 also may be configured to be positioned and passed through a small incision or keyhole formed through the skin or abdominal wall of the patient to reach the tissue treatment region using a

trocar. The tissue treatment region may be located in the brain, lungs, breast, liver, gall bladder, pancreas, prostate gland, various internal body lumen defined by the esophagus, stomach, intestine, colon, arteries, veins, anus, vagina, cervix, fallopian tubes, and the peritoneal cavity, for example, without limitation. The electrical ablation system **10** can be configured to treat a number of lesions and osteopathologies comprising metastatic lesions, tumors, fractures, infected sites, inflamed sites. Once positioned into or proximate the tissue treatment region, the electrical ablation system **10** can be actuated (e.g., energized) to ablate the undesirable tissue. In one embodiment, the electrical ablation system **10** may be configured to treat diseased tissue in the gastrointestinal (GI) tract, esophagus, lung, or stomach that may be accessed orally. In another embodiment, the electrical ablation system **10** may be adapted to treat undesirable tissue in the liver or other organs that may be accessible using transluminal access techniques such as, without limitation, NOTES™ techniques, where the electrical ablation devices may be initially introduced through a natural orifice such as the mouth, anus, or vagina and then advanced to the tissue treatment site by puncturing the walls of internal body lumen such as the stomach, intestines, colon, cervix. In various embodiments, the electrical ablation system **10** may be adapted to treat undesirable tissue in the brain, liver, breast, gall bladder, pancreas, or prostate gland, using one or more electrodes positioned percutaneously, transcutaneously, transluminally, minimally invasively, and/or through open surgical techniques, or any combination thereof.

[0038] In one embodiment, the electrical ablation system **10** may be employed in conjunction with a flexible endoscope **12**, as well as a rigid endoscope, laparoscope, or thoracoscope, such as the GIF-100 model available from Olympus Corporation. In one embodiment, the endoscope **12** may be introduced to the tissue treatment region trans-anally through the colon, trans-orally through the esophagus and stomach, trans-vaginally through the cervix, transcutaneously, or via an external incision or keyhole formed in the abdomen in conjunction with a trocar. The electrical ablation system **10** may be inserted and guided into or proximate the tissue treatment region using the endoscope **12**.

[0039] In the embodiment illustrated in FIG. 1, the endoscope **12** comprises an endoscope handle **34** and an elongate relatively flexible shaft **32**. The distal end of the flexible shaft **32** may comprise a light source and a viewing port. Optionally, the flexible shaft **32** may define one or more working channels for receiving various instruments, such as electrical ablation devices, for example, therethrough. Images within the field of view of the viewing port are received by an optical device, such as a camera comprising a charge coupled device (CCD) usually located within the endoscope **12**, and are transmitted to a display monitor (not shown) outside the patient.

[0040] In one embodiment, the electrical ablation system **10** may comprise an electrical ablation device **20**, a plurality of electrical conductors **18**, a handpiece **16** comprising an activation switch **62**, and an energy source **14**, such as an electrical waveform generator, electrically coupled to the activation switch **62** and the electrical ablation device **20**. The electrical ablation device **20** comprises a relatively flexible member or shaft **22** that may be introduced to the tissue treatment region using a variety of known techniques such as

an open incision and a trocar, through one of more of the working channels of the endoscope **12**, percutaneously, or transcutaneously.

[0041] In one embodiment, one or more electrodes (e.g., needle electrodes, balloon electrodes), such as first and second electrodes **24a,b**, extend out from the distal end of the electrical ablation device **20**. In one embodiment, the first electrode **24a** may be configured as the positive electrode and the second electrode **24b** may be configured as the negative electrode. The first electrode **24a** is electrically connected to a first electrical conductor **18a**, or similar electrically conductive lead or wire, which is coupled to the positive terminal of the energy source **14** through the activation switch **62**. The second electrode **24b** is electrically connected to a second electrical conductor **18b**, or similar electrically conductive lead or wire, which is coupled to the negative terminal of the energy source **14** through the activation switch **62**. The electrical conductors **18a,b** are electrically insulated from each other and surrounding structures, except for the electrical connections to the respective electrodes **24a,b**. In various embodiments, the electrical ablation device **20** may be configured to be introduced into or proximate the tissue treatment region using the endoscope **12** (laparoscope or thoracoscope), open surgical procedures, or external and non-invasive medical procedures. The electrodes **24a,b** may be referred to herein as endoscopic or laparoscopic electrodes, although variations thereof may be inserted transcutaneously or percutaneously. As previously discussed, either one or both electrodes **24a,b** may be adapted and configured to slideably move in and out of a cannula, lumen, or channel defined within the flexible shaft **22**.

[0042] Once the electrodes **24a,b** are positioned at the desired location into or proximate the tissue treatment region, the electrodes **24a,b** may be connected to or disconnected from the energy source **14** by actuating or de-actuating the switch **62** on the handpiece **16**. The switch **62** may be operated manually or may be mounted on a foot switch (not shown), for example. The electrodes **24a,b** deliver electric field pulses to the undesirable tissue. The electric field pulses may be characterized based on various parameters such as pulse shape, amplitude, frequency, and duration. The electric field pulses may be sufficient to induce irreversible electroporation in the undesirable tissue. The induced potential depends on a variety of conditions such as tissue type, cell size, and electrical pulse parameters. The primary electrical pulse parameter affecting the transmembrane potential for a specific tissue type is the amplitude of the electric field and pulse length that the tissue is exposed to.

[0043] In one embodiment, a protective sleeve or sheath **26** may be slidably disposed over the flexible shaft **22** and within a handle **28**. In another embodiment, the sheath **26** may be slidably disposed within the flexible shaft **22** and the handle **28**, without limitation. The sheath **26** is slideable and may be located over the electrodes **24a,b** to protect the trocar and prevent accidental piercing when the electrical ablation device **20** is advanced therethrough. Either one or both of the electrodes **24a,b** of the electrical ablation device **20** may be adapted and configured to slideably move in and out of a cannula, lumen, or channel formed within the flexible shaft **22**. The second electrode **24b** may be fixed in place. The second electrode **24b** may provide a pivot about which the first electrode **24a** can be moved in an arc to other points in the tissue treatment region to treat larger portions of the diseased tissue that cannot be treated by fixing the electrodes **24a,b** in

one location. In one embodiment, either one or both of the electrodes **24a,b** may be adapted and configured to slideably move in and out of a working channel formed within a flexible shaft **32** of the flexible endoscope **12** or may be located independently of the flexible endoscope **12**. Various features of the first and second electrodes **24a,b** are described in more detail in FIGS. 2A-D.

[0044] In one embodiment, the first and second electrical conductors **18a,b** may be provided through the handle **28**. In the illustrated embodiment, the first electrode **24a** can be slideably moved in and out of the distal end of the flexible shaft **22** using a slide member **30** to retract and/or advance the first electrode **24a**. In various embodiments either or both electrodes **24a,b** may be coupled to the slide member **30**, or additional slide members, to advance and retract the electrodes **24a,b**, e.g., position the electrodes **24a,b**. In the illustrated embodiment, the first electrical conductor **18a** coupled to the first electrode **24a** is coupled to the slide member **30**. In this manner, the first electrode **24a**, which is slidably movable within the cannula, lumen, or channel defined by the flexible shaft **22**, can advanced and retracted with the slide member **30**.

[0045] In various other embodiments, transducers or sensors **29** may be located in the handle **28** of the electrical ablation device **20** to sense the force with which the electrodes **24a,b** penetrate the tissue in the tissue treatment zone. This feedback information may be useful to determine whether either one or both of the electrodes **24a,b** have been properly inserted in the tissue treatment region. As is particularly well known, cancerous tumor tissue tends to be denser than healthy tissue and thus greater force is required to insert the electrodes **24a,b** therein. The transducers or sensors **29** can provide feedback to the operator, surgeon, or clinician to physically sense when the electrodes **24a,b** are placed within the cancerous tumor. The feedback information provided by the transducers or sensors **29** may be processed and displayed by circuits located either internally or externally to the energy source **14**. The sensor **29** readings may be employed to determine whether the electrodes **24a,b** have been properly located within the cancerous tumor thereby assuring that a suitable margin of error has been achieved in locating the electrodes **24a,b**.

[0046] In one embodiment, the input to the energy source **14** may be connected to a commercial power supply by way of a plug (not shown). The output of the energy source **14** is coupled to the electrodes **24a,b**, which may be energized using the activation switch **62** on the handpiece **16**, or in one embodiment, an activation switch mounted on a foot activated pedal (not shown). The energy source **14** may be configured to produce electrical energy suitable for electrical ablation, as described in more detail below.

[0047] In one embodiment, the electrodes **24a,b** are adapted and configured to electrically couple to the energy source **14** (e.g., generator, waveform generator). Once electrical energy is coupled to the electrodes **24a,b**, an electric field is formed at a distal end of the electrodes **24a,b**. The energy source **14** may be configured to generate electric pulses at a predetermined frequency, amplitude, pulse length, and/or polarity that are suitable to induce irreversible electroporation to ablate substantial volumes of undesirable tissue in the treatment region. For example, the energy source **14** may be configured to deliver DC electric pulses having a predetermined frequency, amplitude, pulse length, and/or polarity suitable to induce irreversible electroporation to

ablate substantial volumes of undesirable tissue in the treatment region. The DC pulses may be positive or negative relative to a particular reference polarity. The polarity of the DC pulses may be reversed or inverted from positive-to-negative or negative-to-positive a predetermined number of times to induce irreversible electroporation to ablate substantial volumes of undesirable tissue in the treatment region.

[0048] In one embodiment, a timing circuit may be coupled to the output of the energy source **14** to generate electric pulses. The timing circuit may comprise one or more suitable switching elements to produce the electric pulses. For example, the energy source **14** may produce a series of *n* electric pulses (where *n* is any positive integer) of sufficient amplitude and duration to induce irreversible electroporation suitable for tissue ablation when the *n* electric pulses are applied to the electrodes **24a,b**. In one embodiment, the electric pulses may have a fixed or variable pulse length, amplitude, and/or frequency.

[0049] The electrical ablation device **20** may be operated either in bipolar or monopolar mode. In bipolar mode, the first electrode **24a** is electrically connected to a first polarity and the second electrode **24b** is electrically connected to the opposite polarity. For example, in monopolar mode, the first electrode **24a** is coupled to a prescribed voltage and the second electrode **24b** is set to ground. In the illustrated embodiment, the energy source **14** may be configured to operate in either the bipolar or monopolar modes with the electrical ablation system **10**. In bipolar mode, the first electrode **24a** is electrically connected to a prescribed voltage of one polarity and the second electrode **24b** is electrically connected to a prescribed voltage of the opposite polarity. When more than two electrodes are used, the polarity of the electrodes may be alternated so that any two adjacent electrodes may have either the same or opposite polarities, for example.

[0050] In monopolar mode, it is not necessary that the patient be grounded with a grounding pad. Since a monopolar energy source **14** is typically constructed to operate upon sensing a ground pad connection to the patient, the negative electrode of the energy source **14** may be coupled to an impedance simulation circuit. In this manner, the impedance circuit simulates a connection to the ground pad and thus is able to activate the energy source **14**. It will be appreciated that in monopolar mode, the impedance circuit can be electrically connected in series with either one of the electrodes **24a,b** that would otherwise be attached to a grounding pad.

[0051] In one embodiment, the energy source **14** may be configured to produce RF waveforms at predetermined frequencies, amplitudes, pulse widths or durations, and/or polarities suitable for electrical ablation of cells in the tissue treatment region. One example of a suitable RF energy source is a commercially available conventional, bipolar/monopolar electrosurgical RF generator such as Model Number ICC 350, available from Erbe, GmbH.

[0052] In one embodiment, the energy source **14** may be configured to produce destabilizing electrical potentials (e.g., fields) suitable to induce irreversible electroporation. The destabilizing electrical potentials may be in the form of bipolar/monopolar DC electric pulses suitable for inducing irreversible electroporation to ablate tissue undesirable tissue with the electrical ablation device **20**. A commercially available energy source suitable for generating irreversible electroporation electric filed pulses in bipolar or monopolar mode is a pulsed DC generator such as Model Number ECM 830, available from BTX Molecular Delivery Systems Boston,

Mass. In bipolar mode, the first electrode **24a** may be electrically coupled to a first polarity and the second electrode **24b** may be electrically coupled to a second (e.g., opposite) polarity of the energy source **14**. Bipolar/monopolar DC electric pulses may be produced at a variety of frequencies, amplitudes, pulse lengths, and/or polarities. Unlike RF ablation systems, however, which require high power and energy levels delivered into the tissue to heat and thermally destroy the tissue, irreversible electroporation requires very little energy input into the tissue to kill the undesirable tissue without the detrimental thermal effects because with irreversible electroporation the cells are destroyed by electric field potentials rather than heat.

[0053] In one embodiment, the energy source **14** may be coupled to the first and second electrodes **24a,b** by either a wired or a wireless connection. In a wired connection, the energy source **14** is coupled to the electrodes **24a,b** by way of the electrical conductors **18a,b**, as shown. In a wireless connection, the electrical conductors **18a,b** may be replaced with a first antenna (not shown) coupled the energy source **14** and a second antenna (not shown) coupled to the electrodes **24a,b**, wherein the second antenna is remotely located from the first antenna. In one embodiment, the energy source may comprise a wireless transmitter to deliver energy to the electrodes using wireless energy transfer techniques via one or more remotely positioned antennas. As previously discussed, wireless energy transfer or wireless power transmission is the process of transmitting electrical energy from the energy source **14** to an electrical load, e.g., the abnormal cells in the tissue treatment region, without using the interconnecting electrical conductors **18a,b**. An electrical transformer is the simplest instance of wireless energy transfer. The primary and secondary circuits of a transformer are not directly connected. The transfer of energy takes place by electromagnetic coupling through a process known as mutual induction. Wireless power transfer technology using RF energy is produced by Powercast, Inc. The Powercast system can achieve a maximum output of 6 volts for a little over one meter. Other low-power wireless power technology has been proposed such as described in U.S. Pat. No. 6,967,462.

[0054] In one embodiment, the energy source **14** may be configured to produce DC electric pulses at frequencies in the range of about 1 Hz to about 10000 Hz, amplitudes in the range of about ± 100 to about ± 3000 VDC, and pulse lengths (e.g., pulse width, pulse duration) in the range of about 1 μ s to about 100 ms. The polarity of the electric potentials coupled to the electrodes **24a,b** may be reversed during the electrical ablation therapy. For example, initially, the DC electric pulses may have a positive polarity and an amplitude in the range of about +100 to about +3000 VDC. Subsequently, the polarity of the DC electric pulses may be reversed such that the amplitude is in the range of about -100 to about -3000 VDC. In one embodiment, the undesirable cells in the tissue treatment region may be electrically ablated with DC pulses suitable to induce irreversible electroporation at frequencies of about 10 Hz to about 100 Hz, amplitudes in the range of about +700 to about +1500 VDC, and pulse lengths of about 10 μ s to about 50 μ s. In another embodiment, the abnormal cells in the tissue treatment region may be electrically ablated with an electrical waveform having an amplitude of about +500 VDC and pulse duration of about 20 ms delivered at a pulse period T or repetition rate, frequency $f=1/T$, of about 10 Hz. It has been

determined that an electric field strength of 1,000V/cm is suitable for destroying living tissue by inducing irreversible electroporation.

[0055] FIGS. 2A-D illustrate one embodiment of the electrical ablation device **20** in various phases of deployment. In the embodiment illustrated in FIGS. 2A-D, the sheath **26** is disposed over the flexible shaft **22**, however, those skilled in the art will appreciate that the sheath **26** may be disposed within the flexible shaft **22**. The electrical ablation device **20** may be used in conjunction with the electrical ablation system **10** shown in FIG. 1. It will be appreciated that other devices and electrode configurations may be employed without limitation. FIG. 2A illustrates an initial phase of deployment wherein the sheath **26** is extended in the direction indicated by arrow **40** to cover the electrodes **24a,b**. The electrodes **24a,b** may have dimensions of about 0.5 mm, about 1 mm, or about 1.5 mm in diameter. It will be appreciated that the dimensions of the electrodes **24a,b** may be anywhere from about 0.5 mm to about 1.5 mm in diameter. The electrical ablation device **20** may be introduced into the tissue treatment region through a trocar, as illustrated in FIG. 3, for example. FIG. 2B illustrates another phase of deployment wherein the sheath **26** is retracted within the handle **28** in the direction indicated by arrow **42**. In this phase of deployment, the first and second electrodes **24a,b** extend through the distal end of the flexible shaft **22** and are ready to be inserted into or proximate the tissue treatment region. The first electrode **24a** may be retracted in direction **42** through a lumen **44** formed in the flexible shaft **22** by holding the handle **28** and pulling on the slide member **30**. FIG. 2C illustrates a transition phase wherein the first electrode **24a** is the process of being retracted in direction **42** by pulling on the slide member **30** handle, for example, in the same direction. FIG. 2D illustrates another phase of deployment wherein the first electrode **24a** is in a fully retracted position. In this phase of deployment the electrical ablation device **20** can be pivotally rotated about an axis **46** defined by the second electrode **24b**. The electrodes **24a,b** are spaced apart by a distance "r." The distance "r" between the electrodes **24a,b** may be 5.0 mm, about 7.5 mm, or about 10 mm. It will be appreciated that the distance "r" between the electrodes **24a,b** may be anywhere from about 5.0 mm to about 10.0 mm. Thus, the electrical ablation device **20** may be rotated in an arc about the pivot formed by the second electrode **24b**, the first electrode **24a** may be placed in a new location in the tissue treatment region within the radius "r." Retracting the first electrode **24a** and pivoting about the second electrode **24b** enables the surgeon or clinician to target and treat a larger tissue treatment region essentially comprising a circular region having a radius "r," which is the distance between the electrodes **24a,b**. Thus, the electrodes **24a,b** may be located in a plurality of positions in and around the tissue treatment region in order to treat much larger regions of tissue. Increasing the electrode **24a,b** diameter and spacing the electrodes **24a,b** further apart enables the generation of an electric field over a much larger tissue regions and thus the ablation of larger volumes of undesirable tissue. In this manner, the operator can treat a larger tissue treatment region comprising cancerous lesions, polyps, or tumors, for example.

[0056] Although the electrical ablation electrodes according to the described embodiments have been described in terms of the particular needle type electrodes **24a,b** as shown and described in FIGS. 1 and 2A-D, those skilled in the art will appreciate that other configurations of electrical ablation

electrodes may be employed for the ablation of undesirable tissue, without limitation. In one embodiment, the electrical ablation device **20** may comprise two or more fixed electrodes that are non-retractable. In another embodiment, the electrical ablation device **20** may comprise two or more retractable electrodes, one embodiment of which is described below with reference to FIG. 2E. In another embodiment, the electrical ablation device **20** may comprise at least one slidable electrode disposed within at least one working channel of the flexible shaft **32** of the endoscope **12**. In another embodiment, the electrical ablation device **20** may comprise at least one electrode may be configured to be inserted into the tissue treatment region transcutaneously or percutaneously. Still in various other embodiments, the electrical ablation device **20** may comprise at least one electrode configured to be introduced to the tissue treatment region transcutaneously or percutaneously and at least one other electrode may be configured to be introduced to the tissue treatment region through at least one working channel of the flexible shaft **32** of the endoscope **12**. The embodiments, however, are not limited in this context.

[0057] FIG. 2E illustrates one embodiment of an electrical ablation device **800** comprising multiple needle electrodes **824m**, where *m* is any positive integer. In the illustrated embodiment, the electrical ablation device **800** comprises four electrodes **824a**, **824b**, **824c**, **824d**. It will be appreciated that in one embodiment, the electrical ablation device **800** also may comprise three needle electrodes **824a**, **824b**, **824c**, without limitation. The electrical ablation device **800** may be used in conjunction with the electrical ablation system **10** shown in FIG. 1. It will be appreciated that other devices and electrode configurations may be employed without limitation. The electrodes **824a-m** each may have dimensions of about 0.5 mm, about 1 mm, or about 1.5 mm in diameter. It will be appreciated that the dimensions of each of the electrodes **824a-m** may be anywhere from about 0.5 mm to about 1.5 mm in diameter. The electrical ablation device **800** may be introduced into the tissue treatment region through a trocar, as subsequently described and illustrated with reference to FIG. 3, for example.

[0058] The electrical ablation device **800** comprises essentially the same components as the electrical ablation device **20** described with reference to FIGS. 2A-D. The electrical ablation device **800** comprises the relatively flexible member or shaft **22**, the protective sheath **26**, and one or more handles **28** to operate either the sheath **26**, the electrodes **824a,b,c,d**, or both. The electrodes **824a,b,c,d** may be individually or simultaneously deployable and/or retractable in the direction indicated by arrow **842**. The electrodes **824a,b,c,d** extend out from the distal end of the electrical ablation device **800**. In one embodiment, the first and second electrodes **824a**, **824b** may be configured as the positive electrode coupled to the anode of the energy source **14** via corresponding first and second electrical conductors **818a**, **818b**, and the third and fourth **824c**, **824d** may be configured as the negative electrode coupled to the cathode of the energy source **14** via corresponding third and fourth electrical conductors **818c**, **818d**, or similar electrically conductive leads or wires, through the activation switch **62**. Once the electrodes **824a,b,c,d** are positioned at the desired location into or proximate the tissue treatment region, the electrodes **824a,b,c,d** may be connected/disconnected from the energy source **14** by actuating/de-actuating the switch **62**.

[0059] As previously discussed with reference to FIGS. 2A-D, as shown in FIG. 2E in one embodiment, the protective sleeve or sheath **26** may be slidably disposed over the flexible shaft **22** and within the handle **28**. In an initial phase of deployment, the sheath **26** is extended in direction **40** to cover the electrodes **824a,b,c,d** to protect the trocar and prevent accidental piercing when the electrical ablation device **800** is advanced therethrough. Once the electrodes **824a,b,c,d** are located into or proximate the tissue treatment region, the sheath **26** is refracted in direction **42** to expose the electrodes **824a,b,c,d**. One or more of the electrodes **824a,b,c,d** of the electrical ablation device **800** may be adapted and configured to slideably move in and out of a cannula, lumen, or channel formed within the flexible shaft **22**. In one embodiment all of the electrodes **824a,b,c,d** are configured to slideably move in and out channels formed within lumens formed within the flexible shaft **22**, referred to for example as the lumen **44** in FIGS. 2A-D, to advance and retract the electrodes **824a,b,c,d** as may be desired by the operator. Nevertheless, in other embodiments, it may be desired to fix all or certain ones of the one or more electrodes **824a,b,c,d** in place.

[0060] The various embodiments of electrodes described in the present specification, e.g., the electrodes **24a,b**, or **824a-m**, may be configured for use with an electrical ablation device (not shown) comprising an elongated flexible shaft to house the needle electrodes **24a,b**, or **824a-m**, for example. The needle electrodes **24a,b**, or **824a-m**, are free to extend past a distal end of the electrical ablation device. The flexible shaft comprises multiple lumen formed therein to slidably receive the needle electrodes **24a,b**, or **824a-m**. A flexible sheath extends longitudinally from a handle portion to the distal end. The handle portion comprises multiple slide members received in respective slots defining respective walls. The slide members are coupled to the respective needle electrodes **24a,b**, or **824a-m**. The slide members are movable to advance and retract the electrode **24a,b**, or **824a-m**. The needle electrodes **24a,b**, or **824a-m**, may be independently movable by way of the respective slide members. The needle electrodes **24a,b**, or **824a-m**, may be deployed independently or simultaneously. An electrical ablation device (not shown) comprising an elongated flexible shaft to house multiple needle electrodes and a suitable handle is described with reference to FIGS. 4-10 in commonly owned U.S. patent application Ser. No. 11/897,676 titled ELECTRICAL ABLATION SURGICAL INSTRUMENTS, filed Aug. 31, 2007, now U.S. Patent Application Publication No. 2009/0062788, the entire disclosure of which is incorporated herein by reference in its entirety.

[0061] It will be appreciated that the electrical ablation devices **20**, **800** described with referenced to FIGS. 2A-E, may be introduced inside a patient endoscopically (as shown in FIG. 15, transcutaneously, percutaneously, through an open incision, through a trocar (as shown in FIG. 3), through a natural orifice (as shown in FIG. 15), or any combination thereof. In one embodiment, the outside diameter of the electrical ablation devices **20**, **800** may be sized to fit within a working channel of an endoscope and in other embodiments the outside diameter of the electrical ablation devices **20**, **800** may be sized to fit within a hollow outer sleeve **620**, or trocar, as shown in FIG. 15, for example. The hollow outer sleeve **620** or trocar is inserted into the upper gastrointestinal tract of a patient and may be sized to also receive a flexible endoscopic portion of an endoscope **622** (e.g., gastroscope), similar to the endoscope **12** described in FIG. 1.

[0062] FIG. 3 illustrates one embodiment of the electrical ablation system 10 shown in FIGS. 1 and 2A-D in use to treat undesirable tissue 48 located on the surface of the liver 50. The undesirable tissue 48 may be representative of a variety of diseased tissues, cancers, tumors, masses, lesions, abnormal tissue growths, for example. In use, the electrical ablation device 20 may be introduced into or proximate the tissue treatment region through a port 52 of a trocar 54. The trocar 54 is introduced into the patient via a small incision 59 formed in the skin 56. The endoscope 12 may be introduced into the patient trans-anally through the colon, trans-orally down the esophagus and through the stomach using transluminal techniques, or through a small incision or keyhole formed through the patient's abdominal wall (e.g., the peritoneal wall). The endoscope 12 may be employed to guide and locate the distal end of the electrical ablation device 20 into or proximate the undesirable tissue 48. Prior to introducing the flexible shaft 22 through the trocar 54, the sheath 26 is slid over the flexible shaft 22 in a direction toward the distal end thereof to cover the electrodes 24a,b (as shown in FIG. 2A) until the distal end of the electrical ablation device 20 reaches the undesirable tissue 48.

[0063] Once the electrical ablation device 20 has been suitably introduced into or proximate the undesirable tissue 48, the sheath 26 is retracted to expose the electrodes 24a,b (as shown in FIG. 2B) to treat the undesirable tissue 48. To ablate the undesirable tissue 48, the operator initially may locate the first electrode 24a at a first position 58a and the second electrode 24b at a second position 60 using endoscopic visualization and maintaining the undesirable tissue 48 within the field of view of the flexible endoscope 12. The first position 58a may be near a perimeter edge of the undesirable tissue 48. Once the electrodes 24a,b are located into or proximate the undesirable tissue 48, the electrodes 24a,b are energized with irreversible electroporation pulses to create a first necrotic zone 65a. For example, once the first and second electrodes 24a,b are located in the desired positions 60 and 58a, the undesirable tissue 48 may be exposed to an electric field generated by energizing the first and second electrodes 24a,b with the energy source 14. The electric field may have a magnitude, frequency, and pulse length suitable to induce irreversible electroporation in the undesirable tissue 48 within the first necrotic zone 65a. The size of the necrotic zone is substantially dependent on the size and separation of the electrodes 24a,b, as previously discussed. The treatment time is defined as the time that the electrodes 24a,b are activated or energized to generate the electric pulses suitable for inducing irreversible electroporation in the undesirable tissue 48.

[0064] This procedure may be repeated to destroy relatively larger portions of the undesirable tissue 48. The position 60 may be taken as a pivot point about which the first electrode 24a may be rotated in an arc of radius "r," the distance between the first and second electrodes 24a,b. Prior to rotating about the second electrode 24b, the first electrode 24a is retracted by pulling on the slide member 30 (FIGS. 1 and 2A-D) in a direction toward the proximal end and rotating the electrical ablation device 20 about the pivot point formed at position 60 by the second electrode 24b. Once the first electrode 24a is rotated to a second position 58b, it is advanced to engage the undesirable tissue 48 at point 58b by pushing on the slide member 30 in a direction towards the distal end. A second necrotic zone 65b is formed upon energizing the first and second electrodes 24a,b. A third necrotic zone 65c is

formed by retracting the first electrode 24a, pivoting about pivot point 60 and rotating the first electrode 24a to a new location, advancing the first electrode 24a into the undesirable tissue 48 and energizing the first and second electrodes 24a,b. This process may be repeated as often as necessary to create any number of necrotic zones 65p, where p is any positive integer, within multiple circular areas of radius "r," for example, that is suitable to ablate the entire undesirable tissue 48 region. At anytime, the surgeon or clinician can reposition the first and second electrodes 24a,b and begin the process anew. In other embodiments, the electrical ablation device 800 comprising multiple needle electrodes 824a-m described with reference to FIG. 2E may be employed to treat the undesirable tissue 48. Those skilled in the art will appreciate that similar techniques may be employed to ablate any other undesirable tissues that may be accessible trans-anally through the colon, and/or orally through the esophagus and the stomach using transluminal access techniques. Therefore, the embodiments are not limited in this context.

[0065] FIG. 4 illustrates a detailed view of one embodiment of the electrical ablation system 10 shown in FIG. 3 in use to treat undesirable tissue 48 located on the surface of the liver 50. The first and second electrodes 24a,b are embedded into or proximate the undesirable tissue 48 on the liver 50. The first and second electrodes 24a,b are energized to deliver one or more electrical pulses of amplitude and length sufficient to induce irreversible electroporation in the undesirable tissue 48 and create the first necrotic zone 65a. Additional electric pulses may be applied to the tissue immediately surrounding the respective electrodes 24a,b to form second, thermal, necrotic zones 63a,b near the electrode-tissue-interface. The duration of an irreversible electroporation energy pulse determines whether the temperature of the tissue 63a,b immediately surrounding the respective electrodes 24a,b raises to a level sufficient to create thermal necrosis. As previously discussed, varying the electrode 24a,b size and spacing can control the size and shape of irreversible electroporation induced necrotic zone 65a. Electric pulse amplitude and length can be varied to control the size and shape of the thermally induced necrotic zones near the tissue-electrode-interface. In other embodiments, the electrical ablation device 800 comprising multiple needle electrodes 824a-m may be used to treat the undesirable tissue 48 located on the surface of the liver 50, for example.

[0066] FIG. 5 is a graphical representation of a series of electrical pulses that may be applied to undesirable tissue to create a first necrotic zone by inducing irreversible electroporation in the tissue and to create a second necrotic zone by inducing thermal effects near the electrode-tissue-interface using the electrical ablation system 10 shown in FIG. 4. Time (t) is shown along the horizontal axis and voltage (VDC) is shown along the vertical axis. Initially the undesirable tissue 48 is exposed to a first series of electrical pulses 70 of a first predetermined amplitude, length, and frequency sufficient to induce the irreversible electroporation necrotic zone 65a. Subsequently, the undesirable tissue near the electrode-tissue-interface is exposed to a second series of electrical pulses 72 of a second predetermined amplitude, length, and frequency sufficient to induce thermal necrotic effects on the tissue and create thermal necrotic zones 63a,b. As shown in FIG. 5, the first series of pulses 70 comprises about 20 to 40 electric pulses having an amplitude of about 1000 VDC, pulse length t_1 of about 10 μ s to about 15 μ s, and a period T_1 (e.g., pulse repetition rate $f_1=1/T_1$) of about 100 μ s ($f_1=10000$ Hz).

The first series of pulses is sufficient to induce irreversible electroporation in the necrotic zone **65a**. The period T_1 is defined as the pulse length t_1 plus the pulse spacing **74**, e.g., the time between a falling edge of a pulse and a rising edge of a subsequent pulse. The second series of pulses **72** may comprise a single pulse or multiple pulses having an amplitude of about 500 VDC, pulse length t_2 of about 10 ms to about 15 ms, and a period T_2 of about 100 ms ($f_2=10$ Hz). The second series of pulses is sufficient to create thermal necrotic zones **63a, b** in the tissue near the electrode-tissue-interface immediately surrounding the respective electrodes **24a, b**. In one embodiment, $f_1=f_2=10$ Hz (i.e., $T_1=T_2=100$ MS).

[0067] In one embodiment, the thermal necrotic zones **63a, b** formed in the tissue immediately surrounding the electrodes **24a, b** at the tissue-electrode-interface are beneficial to stop bleeding in the undesirable tissue **48** as a result of the mechanical trauma resulting from inserting or embedding the electrodes **24a, b** into the undesirable tissue **48** of the liver **50**. Although in general irreversible electroporation induced by electric pulses do not cause thermal necrosis or other detrimental thermal effects, the longer electrical pulses **72** may be applied to the undesirable tissue **48** in succession to thermally seal the tissue immediately surrounding the electrodes **24a, b** at the tissue-electrode-interface. Thus, the technique of applying a combination of a first series of substantially shorter electrical pulses **70** (in the microseconds range) and a second series of substantially longer energy pulses **72** (in the milliseconds range) may be employed for sealing vessels prior to transecting a vessel. Accordingly, the first series of pulses **70** may be applied to a vessel to induce cell necrosis by irreversible electroporation. Then, the second series of pulses **72** may be applied to vessel to create thermal necrotic zones to seal the vessel prior to dissecting the vessel.

[0068] In various embodiments, a series of electrical pulses may be characterized according to the following parameters as may be provided by the energy source **14**, for example. In one embodiment, the energy source **14** may be configured to produce DC electric pulses at frequencies in the range of about 1 Hz to about 10000 Hz, amplitudes in the range of about ± 100 to about ± 3000 VDC, and pulse lengths (e.g., pulse width, pulse duration) in the range of about 1 μ s to about 100 ms. The polarity of the electric potentials coupled to the electrodes **24a, b** may be reversed during the electrical ablation therapy. For example, initially, the DC electric pulses may have a positive polarity and an amplitude in the range of about +100 to about +3000 VDC. Subsequently, the polarity of the DC electric pulses may be reversed such that the amplitude is in the range of about -100 to about -3000 VDC. In one embodiment, the undesirable cells in the tissue treatment region may be electrically ablated with DC pulses suitable to induce irreversible electroporation at frequencies of about 10 Hz to about 100 Hz, amplitudes in the range of about +700 to about +1500 VDC, and pulse lengths of about 10 μ s to about 50 μ s. In another embodiment, the abnormal cells in the tissue treatment region may be electrically ablated with an electrical waveform having an amplitude of about +500 VDC and pulse duration of about 20 ms delivered at a pulse period T or repetition rate, frequency $f=1/T$, of about 10 Hz.

[0069] FIGS. **6**, **7**, and **8** illustrate one embodiment of an electrical ablation device **290** to treat undesirable tissue located within body lumen using electrical energy. FIG. **6** illustrates a sectioned view of one embodiment of the electrical ablation device **290**. FIG. **7** illustrates an end view of the embodiment of the electrical ablation device **290** shown in

FIG. **6**. FIG. **8** illustrates a cross-sectional view of the embodiment of the electrical ablation device **290** shown in FIG. **6**. As previously discussed, reflux disease of the greater saphenous vein (GSV) can result in a varicose vessel **292**, which is illustrated in FIG. **8**. Conventionally, varicose veins have been treated by stripping and then applying either chemical or thermal ablation to internal portions of a lumen defined by the varicose vessel **292**. In the embodiment illustrated in FIGS. **6-8**, the electrical ablation device **290** is configured to couple to the energy source **14** and to be inserted within a lumen defined by the varicose vessel **292**. Once inserted into the varicose vessel **292**, the electrical ablation device **290** may be energized by the energy source **14** to apply high-voltage DC electrical pulses to an inner wall **294** portion of the varicose vessel **292**. High-voltage DC pulses may be used to ablate the undesirable tissue and to subsequently seal the varicose vessel **292**. The embodiment illustrated in FIGS. **6-8**, however, is not limited in this context, and the electrical ablation device **290** may be employed to treat and seal tissue within any inner body lumen using energy in the form of electrical pulses supplied by the energy source **14**.

[0070] Referring to FIGS. **6-8**, the electrical ablation device **290** comprises a probe **296** comprising a cannula, channel, or lumen **300** extending longitudinally therethrough. The distal end **298** of the probe **296** comprises first and second ring electrodes **302a, b** to which a potential difference may be applied by the energy source **14**. The first and second ring electrodes **302a, b** may be coupled to respective positive and negative terminals of the energy source **14** through corresponding first and second electrical conductors **304a, b**. The first and second electrical conductors **304a, b** extend through respective conduits **306a, b** formed within the probe **296** and extend longitudinally therethrough. The first and second electrical conductors **304a, b** may be electrically coupled to the first and second ring electrodes **302a, b** in any suitable manner. The first and second ring electrodes **302a, b** are adapted to receive energy in the form of electrical pulses from the energy source **14**. The electrical pulses generate an electric field suitable for treating, e.g., ablating, the undesirable tissue within a lumen such as the lumen defined by the varicose vessel **292** as shown in FIG. **8**. In one embodiment, once energized by the energy source **14**, the first and second ring electrodes **302a, b** generate an electric field suitable to induce irreversible electroporation in the undesirable tissue. It will be appreciated that a potential difference may be created across the first and second ring electrodes **302a, b** to generate an electric field strength suitable to induce irreversible electroporation in the undesirable tissue. In other embodiments, the probe **296** may comprise one or more electrodes in addition to the first and second ring electrodes **302a, b**.

[0071] The electrical ablation probe **296** has a form factor that is suitable to be inserted within a lumen defined by the varicose vessel **292** and to ablate tissue in the tapered lumen **298** portion of the varicose vessel **292**. The probe **296** engages the inner wall **294** of the varicose vessel **292** in the tapered lumen **298** portion of the varicose vessel **292**. Suction **306** applied at a proximal end of the probe **296** draws a vacuum within the lumen **300** of the probe **296** to collapse the varicose vessel **292** at the distal end **298** of the probe **296**. Once the vessel **292** is collapsed or pulled down by the suction **306**, a first pulse train **302** of high-voltage DC electrical pulses at a first amplitude A_1 (e.g., ~1000V amplitude) and a first pulse length T_1 (e.g., ~50 microseconds) is applied to the first and second ring electrodes **302a, b** by the energy source **14**. The

high-voltage DC pulse train **302** eventually kills the cells within the tapered lumen **298** portion of the varicose vessel **292** by irreversible electroporation. A second pulse train **304** having a lower voltage amplitude A_2 (e.g., ~ 500 VDC) and a second longer pulse length T_2 (e.g., ~ 15 milliseconds) is applied to the first and second ring electrodes **302a,b** of the probe **296** to thermally seal the varicose vessel **292**. As previously discussed, in one embodiment, the polarity of the electrical pulses may be inverted or reversed by the energy source **14** during the ablation or sealing treatment process. In various embodiments, the electrical pulses may be characterized by the parameters in accordance with the output of the energy source **14** as discussed with respect to FIGS. **1** and **5**, for example.

[0072] FIG. **9** illustrates one embodiment of an electrical ablation system **400** in use to treat non-metastatic prostate cancer in a patient. As previously discussed, a radical prostatectomy in which the entire prostate **404** and surrounding lymph nodes are removed is one of the conventional treatments for prostate cancer. Like most other forms of cancer, radiation therapy may be used in conjunction with or as an alternate method for the treatment of prostate cancer. Another thermal ablation technique for the treatment of prostate cancer is RF interstitial tumor ablation (RITA) via trans-rectal ultrasound guidance. While these conventional methods for the treatment of prostate cancer are effective, they are not preferred by many surgeons and may result in detrimental thermal effects to healthy tissue surrounding the prostate. The electrical ablation system **400** in accordance with the described embodiments provides improved electrical ablation of prostate cancer using irreversible electroporation pulses through supplied by an energy source to electrodes positioned into and/or proximate the prostate cancer tissue.

[0073] With reference to FIG. **9**, the electrical ablation system **400** comprises an electrical ablation device **402** comprising at least two electrodes **402a,b**, and the energy source **14**. The electrical ablation system **400** may be adapted for use in conjunction with the electrical ablation system **10** described in FIG. **1**. The electrodes **402a,b** are configured to be positioned within internal body lumens or cavities and, in one embodiment, may be configured for use in conjunction with the flexible endoscope **12** also described in FIG. **1**. The electrodes **402a,b** are configured to couple to the corresponding electrical conductors **18a,b**, the handpiece **16**, the activation switch **62**, and the energy source **14**, as previously discussed in FIG. **1**. The first electrode **402a** comprises a wire or flexible conductive tube that may be introduced through the urethra **406** into the prostate **404** proximally to the bladder **410**. The first electrode **402a** may be located into the prostate **404** using well known fluoroscopy or ultrasonic guidance, for example. The second electrode **402b** comprises a pad and may be introduced into the anus **408** and advanced to a location proximate to the prostate **404**. The first electrode **402a** has a much smaller surface area relative to the trans-anally placed second electrode **402b** pad. The first electrode **402a** may be connected to the positive (+) terminal of the energy source **14** and the second electrode **402b** may be connected to the negative (-) terminal of the energy source **14**. In one embodiment, the energy source **14** may be configured as a high-voltage DC electric pulse generator. The activation switch **62** portion of the handpiece **16**, as shown in FIG. **1**, can be used to energize the electrical ablation system **400** to ablate the non-metastatic cancer in the prostate **404** by irreversible electroporation pulses supplied by the energy source **14** and delivered

through the electrodes **402a,b** as described in FIG. **10** below. In other embodiments, the probe **296** may comprise one or more electrodes in addition to the first and second electrodes **402a,b**.

[0074] FIG. **10** is a graphical representation of a series of electrical pulses **412** that may be applied to undesirable tissue to induce irreversible electroporation suitable to ablate non-metastatic cancer of the prostate **404** as described in FIG. **9**. Time (t) is shown along the horizontal axis and voltage (V) is shown along the vertical axis. A series of electrical pulses **412** having a predetermined amplitude V_o and pulse length t_o sufficient to induce irreversible electroporation may be applied to the prostate **404** through the electrodes **402a,b** to ablate the undesirable cancerous tissue. Multiple electrical pulses **412**, for example, 20 to 40 pulses, of amplitude of about 1500 to about 3000 volts DC (V_o) each having a pulse length t_o of about 10 μs to about 50 μs , and a period (T) of about 10 ms. The electrical pulses **412** having such parameters are sufficient to induce irreversible electroporation to ablate the cancerous tissue in the prostate **404**. The period T (e.g., pulse repetition rate $f=1/T$) may be defined as the pulse length t_o plus 10 μs the length of time between pulses, or the pulse spacing **414**. A conductive fluid may be introduced into the urethra **406** to extend the range of the positive electrode **402a**. In various embodiments, the electrical pulses may be characterized by the parameters in accordance with the output of the energy source **14** as discussed with respect to FIGS. **1** and **5**, for example.

[0075] FIG. **11** illustrates one embodiment of the electrical ablation system **10** described FIG. **1** in use to treat basal cell carcinoma (BCC) tissue. In FIG. **11**, the electrical ablation system **10**, described in FIG. **1**, is shown in use to treat BCC tissue **502**. BCC tissue **502** is a slowly growing cutaneous malignancy derived from a rapidly proliferating basal layer of the epidermis **504**. As previously discussed, conventional treatments for BCC include surgical excision, cryo-therapy, radiation, photodynamic therapy, Moh's micrographic surgery, and topical treatments with 5-fluorouracil. Minimally-invasive methods of treating BCC include laser ablation with a pulsed carbon dioxide laser. Although, the treatment of BCC with a carbon dioxide laser has been shown to be effective on tumors ranging in size from about 5 mm to about 40 mm, carbon dioxide treatment is a thermal method of treating tissue that may cause permanent thermal damage to healthy tissue surrounding the BCC tissue and requires costly capital investment in carbon dioxide laser equipment.

[0076] The electrical ablation device **20** of the electrical ablation system **10** may be used to induce irreversible electroporation suitable to treat undesirable BCC tissue using electrical pulses supplied by the energy source **14**. The first and second electrodes **24a,b** are transcutaneously inserted through the epidermis **504** and embedded into the BCC tissue **502**. The first and second electrodes **24a,b** are separated by a distance "D." The first electrode **24a** is electrically to the positive (+) output of the energy source **14** and the second electrode **24b** is electrically connected to the negative (-) output of the energy source **14**. In one embodiment, the energy source **14** may be a high-voltage DC generator. The energized electrodes **24a,b** generate an electric field inducing irreversible electroporation suitable for ablating the undesirable BCC tissue **502** located between the electrodes **24a,b**. A larger portion of the BCC tissue **502** may be ablated by relocating and re-energizing the first and second electrodes **24a,b** using the technique previously described with

reference to FIG. 3, for example. As previously discussed, varying the electrode **24a,b** size and spacing can control the size and shape of irreversible electroporation induced necrotic zone. Accordingly, as previously discussed, increasing the electrode **24a,b** diameter and spacing between the electrodes **24a,b** enables the generation of an electric field over a much larger tissue regions and thus the ablation of larger volumes of undesirable tissue. In other embodiments, the electrical ablation device **800** comprising multiple needle electrodes **824a-m** may be used to treat the BCC tissue **502**, for example.

[0077] FIG. 12 is a graphical representation of a series of electrical pulses **512** that may be applied to undesirable tissue to induce irreversible electroporation suitable to ablate BCC tissue as described in FIG. 11. Time (t) is shown along the horizontal axis and voltage (V) is shown along the vertical axis. As shown in FIG. 12, a series of electrical pulses **512** having a predetermined amplitude V_o and pulse length t_o sufficient to induce irreversible electroporation may be applied to the BCC tissue **502** to ablate the undesirable cancerous tissue. About 20 to about 40 pulses **512** of with an amplitude of about 1500 to about 3000 VDC (V_o), a pulse length t_o of about 10 μ s to about 50 μ s, a period T (the pulse length t_o plus the pulse spacing **54**) of about 10 ms may be suitable for inducing irreversible electroporation to ablate the undesirable BCC tissue **502** in the region D between the electrodes **24a,b**. Multiple placements of the electrode **24a,b** in rapid succession and the application of additional pulses **512** can be used to ablate larger portions of the BCC tissue **502**, as previously discussed in FIG. 3. As previously discussed, varying the electrode **24a,b** size and spacing can control the size and shape of irreversible electroporation induced necrotic zone. Accordingly, increasing the electrode **24a,b** diameter and spacing the electrodes **24a,b** further apart (e.g., greater than "D") enables the generation of an electric field over a much larger tissue regions and thus the ablation of larger volumes of undesirable tissue. Injecting a conductive fluid into the BCC tissue **502** is another technique to increase the size and shape of the irreversible electroporation induced necrotic zone and extend the range of the positive electrode **24a**, for example. In various embodiments, the electrical pulses may be characterized by the parameters in accordance with the output of the energy source **14** as discussed with respect to FIGS. 1 and 5, for example.

[0078] FIG. 13A illustrates one embodiment of an electrical ablation device **600** in a collapsed state. The electrical ablation device **600** has a configuration suitable for the treatment of undesirable tissue located in a lumen, abscess, void, or cavity. Although other electrode configurations may be effective for treating line-of-sight regions of tissue, such electrodes may not be as effective at treating tissue within a cavity. To overcome these limitations, the electrical ablation device **600** comprises an electrode configured to inflate and expand into the cavity to make contact with tissue along the inner wall of the cavity. The electrical ablation device **600** comprises an elongate tubular body extending from a proximal end to a distal end. In one embodiment, the electrical ablation device **600** may comprise a conductive elastomer electrode **602** portion (e.g., balloon, tip) and a non-conductive catheter **604** portion, which may be formed of a non-electrically conductive (e.g., electrically insulative) elastomeric material. The electrical ablation device **600** may be referred to as a balloon catheter, balloon probe, or balloon-tipped catheter, for example, without limitation. In one embodiment, the inflat-

able portion of the conductive elastomer electrode **602** may be formed of an electrically conductive elastomer suitable for coupling to the energy source **14** via an electrically conductive terminal **610** and a first electrically conductive wire **608a**. Once inflated, the elastomeric properties of the conductive elastomer electrode **602** conform to the internal walls of the cavity. Upon energizing, the conductive elastomer electrode **602** delivers electrical pulses to the tissue within the internal walls of the cavity to induce irreversible electroporation.

[0079] In one embodiment, the electrical ablation device **600** may be fabricated using a concurrent injection process such that the conductive elastomer electrode **602** portion and the non-conductive catheter **604** portion are formally integrally. In another embodiment, the electrical ablation device **600** may be fabricated by manufacturing the conductive elastomer electrode **602** and the non-conductive catheter **604** separately and then joining the two components using any suitable joining method such as, for example, bolting, screwing, welding, crimping, gluing, bonding, brazing, soldering, press fitting, riveting, heat shrinking, heat welding, ultrasonic welding, or any other suitable method.

[0080] FIG. 13B illustrates one embodiment of the electrical ablation device **600** shown in FIG. 13A in an inflated state. As previously discussed, in an inflated state the conductive elastomer electrode **602** may be employed for ablating cancerous tumors growing within internal body lumens such as the esophagus or the large bowel, or in cavities remaining when cancerous tumors are removed from solid tissue, such as the breast. Although surgical resection of tumors in solid tissue can include a margin of healthy tissue, cancer cells may remain in the tissue within the cavity. The conductive elastomer electrode **602** may be inserted in the cavity, inflated, and energized by the energy source **14** to expose the tissue within the cavity to electrical pulses suitable to induce irreversible electroporation to ablate any cancer cells remaining within the cavity.

[0081] FIG. 14 is a cross-sectional view of the electrical ablation device **600** showing a cross-sectional view of the conductive elastomer electrode **602** and the non-conductive catheter **604** shown in FIGS. 13A and 13B. The conductive elastomer electrode **602** may be coupled to a first end **606** of the electrically conductive wire **608a**. The wire **608a** may be located through the non-conductive catheter **604** and the first end **606** electrically connected (e.g., bonded, soldered, brazed) to the conductive elastomer electrode **602** through the electrically conductive terminal **610**. In one embodiment, the non-conductive catheter **604** may be extruded with an embedded strip of conductive material serving as the electrically conductive terminal **610**. The wire **608a** may be electrically connected to one end of the electrically conductive terminal **610**. In one embodiment, the electrical ablation device **600** may be configured to couple to one terminal of the energy source **14** via a second end of the electrically conductive wire **608a**. A return electrode **612** (e.g., in the form of a pad or needle electrode) is coupled to a second electrically conductive wire **608b**, which is coupled to another terminal of the energy source **14**. The return electrode **612** may be orientated proximal to the conductive elastomer electrode **602** of the electrical ablation device **600** (e.g., the balloon catheter). When irreversible electroporation energy pulses are applied to the conductive elastomer electrode **602** of the electrical ablation device **600**, the tissue between the conductive elastomer portion **602** and the return electrode **608b** is ablated, e.g., destroyed by the pulsed irreversible electroporation

energy. In other embodiments, the return electrode 612 may comprise multiple electrodes, for example.

[0082] In one embodiment, the conductive elastomer electrode 602 may be fabricated from or may comprise an electrically conductive material suitable for conducting electrical energy from the energy source 14 to the internal cavity sufficient to induce irreversible electroporation to the tissue within the cavity. The electrically conductive elastomer material is similar to conductive elastomers used as gasket material for electronic enclosures used for shielding electronic devices from electromagnetic interference (EMI). Conductive elastomers may be formed by infiltrating an elastomeric matrix with electrically conductive filler materials such as silver, gold, copper, or aluminum, to produce a hybrid material having the elastic properties of the elastomeric matrix and the electrically conductive properties of the metallic filler materials (some materials may have volume resistivity values as low as 0.004 Ω -cm, for example). The conductive elastomer may be formed as thin sheets, catheters, and balloons suitable for medical applications. In one embodiment, the conductive elastomer electrode 602 may be fabricated from medical grade polyurethane material comprising at least one electrically conductive coating on an outer surface thereof. In another embodiment, the conductive elastomer electrode 602 may be made from an electrically conductive material. In yet another embodiment, the conductive elastomer electrode 602 may be made from an electrically insulative material, such as the medical grade polyurethane, and inflated with a conductive fluid (e.g., saline) to form the electrically conductive portion of the conductive elastomer electrode 602.

[0083] In one embodiment the conductive elastomer electrode 602 may be coupled to the anode (+) electrode of the energy source 14 and in another embodiment the conductive elastomer electrode 602 may be coupled to the cathode (−) electrode of the energy source 14. It will be appreciated that the polarity of the conductive elastomer electrode 602 may be reversed by reversing the output polarity of the energy source 14. In one embodiment, the conductive elastomer electrode 602 may be coupled to either the anode (+) or the cathode (−) of the energy source 14. For example, the conductive elastomer electrode 602 may be coupled to the cathode (+) of the energy source 14 relative to a ground plane cathode (−) in contact with the patient and coupled to the negative terminal of the energy source 14.

[0084] FIG. 15 illustrates one embodiment of the electrical ablation device shown in FIG. 13A inserted through the mouth and esophagus to ablate cancerous tissue in the esophagus using electrical pulses. As shown in FIG. 15, a hollow outer sleeve 620 or trocar is inserted into the upper gastrointestinal tract of a patient and receives a flexible endoscopic portion of an endoscope 622 (e.g., gastroscope), similar to the endoscope 12 described in FIG. 1. A variety of different types of endoscopes are known and, therefore, their specific construction and operation will not be discussed in great detail herein. In various embodiments, the flexible endoscopic portion 620 may be fabricated from nylon or high-density polyethylene plastic, for example. FIG. 15 illustrates, in general form, one embodiment of the electrical ablation device 600 that can be inserted through a natural orifice such as the mouth 626 and advanced through a cavity or lumen such as the esophagus 628, e.g., esophageal cavity, to apply electrical pulses sufficient to induce irreversible electroporation to ablate the undesirable cancerous tissue 630 located in the esophagus 628.

[0085] FIG. 16 illustrates the distal portion 624 of the endoscope 622 shown in FIG. 15. As shown in FIG. 16, the electrical ablation device 600 is advanced through the distal end 624 of the endoscope 622. In various embodiments, the endoscope 622 can serve to define various tool-receiving passages 628, or “working channels,” that extend from the natural orifice 626 to the surgical site. In addition, the endoscope 622 comprises a viewing port 630. The endoscope 622 may be used for viewing the surgical site within the patient’s body. Various cameras and/or lighting apparatuses may be inserted into the viewing port 630 of the endoscope 622 to provide the surgeon with a view of the surgical site.

[0086] With reference now to FIGS. 15 and 16, the electrical ablation device 600 is one of the tools or surgical instruments that can be accommodated in the tool-receiving passage 628 of the endoscope 622. The conductive elastomer electrode 602 (e.g., balloon, tip) and the non-conductive catheter 604 are configured to communicate with at least one pressurized air source 634 and a vacuum source 632 to respectively inflate and deflate the conductive elastomer electrode 602. In one embodiment, a vacuum/air tube 636 can be sized to receive other surgical instruments therein. In various embodiments, the endoscope 622 may comprise a video camera that communicates with a video display unit 638 that can be viewed by the surgeon during the operation. In addition, the endoscope 622 may further comprise a fluid-supply lumen therethrough that is coupled to an inflation fluid such as a water source 640, saline solution, and/or any other suitable inflation fluid and/or an air supply lumen that is coupled to the air source 642. In various embodiments, the fluid-supply lumen, e.g., the inflation fluid line, may be coupled to conventional inline valves (not shown) to control the flow of inflation fluid. For example, a proximal end of the inline valve may be removably coupled to a conventional inflation syringe. The fluid-supply lumen defines an inflation lumen that fluidically communicates with the interior of the conductive elastomer electrode 602 (e.g., the balloon electrode) via an aperture (not shown). The fluid-supply lumen provides a fluid communication path for inflating the conductive elastomer electrode 602 with a conductive fluid. The fluid may be either saline or air or other suitable electrically conductive inflation fluid. As previously discussed, the conductive elastomer electrode 602 is coupled to the energy source 14 to deliver electrical pulses to the esophageal cavity. The transcutaneous electrode 612 is also coupled to the energy source 14 through electrically conductive wire 608b.

[0087] In use, the electrical ablation device 600 may be introduced into a natural orifice such as the mouth 626 and advanced into a lumen, abscess, void, or cavity such as the esophagus 628, as shown in FIG. 15. In the illustrated embodiment, the conductive elastomer electrode 602 is inserted through the working channel 628 of the endoscope 622 and into the lumen or cavity defined by the esophagus 628 and the return electrode 612 is inserted transcutaneously and is located proximate to the cancerous tissue 630. Once located within the esophagus 628, the conductive elastomer electrode 602 may be inflated using either the water source 640 or the air source 642. The water source 640 may supply a conductive solution (e.g., saline solution) to enhance the conductivity of the conductive elastomer electrode 602 and to enhance the contact area between the conductive elastomer electrode 602 and the inner wall of the esophageal cavity 628 including the cancerous tissue 630. Once inflated, the conductive elastomer electrode 602 is energized by the energy source 14 with a

number of high-voltage DC electrical pulses to cause necrosis of the undesirable cancerous tissue 630 between the conductive elastomer electrode 602 and the return electrode 612. In this example, the high-voltage DC electrical pulses generate an electric field in a concentric zone around the esophageal cavity 628. The electric field has a sufficient magnitude and pulse length to induce irreversible electroporation in the undesirable cancerous tissue 630. The depth of the necrotic zone depends on the amplitude of the applied electric field, the pulse length, the number of pulses, and the repetition rate or frequency of the pulses. In various embodiments, the electrical pulses may be characterized by the parameters in accordance with the output of the energy source 14 as discussed with respect to FIGS. 1 and 5, for example.

[0088] FIGS. 17-20 illustrate a method of treating residual undesirable tissue within cavities formed in the solid tissue after removal of a mass of undesirable tissue. FIG. 17 illustrates a cross-sectional view of a breast 702 showing a cavity 700 that may be left after a lumpectomy to remove a tumor from the breast 702. In tumors that grow in solid tissue, the rate of recurrence of undesirable tissue depends on the margin of healthy tissue relative to the undesirable tissue that is removed. Accordingly, to minimize the recurrence of the tumor once the undesirable tissue is removed from the breast 702, the residual tissue in the cavity 700 should be ablated. The residual tissue may be ablated using the techniques previously described in FIGS. 13-16 above or the techniques described in FIGS. 18-20 below.

[0089] FIG. 18 illustrates one embodiment of a catheter 704 inserted into the cavity 700 left in the breast 702 after a lumpectomy procedure. A distal end 706 of the catheter 704 comprises a compressed sponge 708 or any suitable type of expandable foam material. A sleeve 710 slidably disposed over the catheter 704 and the sponge 708 contains the sponge 708 until it is ready to expand into the cavity 700. When the sleeve 710 is retracted in the direction indicated by arrow 712, the sponge 708 may be expanded into the cavity 700 by pumping saline into the sponge 708 through the catheter 704. An electrode 714 is inserted through the catheter 704 and into the sponge 708 such that the electrode 714 is in electrical communication with the sponge 708. The electrode 714 may be coupled to the positive terminal of the energy source 14, for example.

[0090] FIG. 19 illustrates an expanded sponge filling the cavity 700 left in the breast 702 following a lumpectomy as shown in FIG. 17. As shown in FIG. 19, the sponge 708 has been soaked with saline solution and has expanded to fill the cavity 700 upon removal of the sleeve 710. Multiple wire electrodes 714 may be embedded in the saline soaked sponge 708. Each of these wire electrodes 714 may be coupled to the positive terminal of the energy source 14. The body or outer portion of the breast 702 may be electrically grounded through one or more large surface area electrodes 716a,b. It will be appreciated that in other embodiments that either a single surface area electrode or more than two surface area electrodes may be employed, without limitation. The negative electrodes 716a,b are connected to the negative terminal of the energy source 14. The sponge 708 and the residual tissue within the cavity 700 are exposed to a series of electric pulses (e.g., high-voltage DC electric pulses) suitable for inducing irreversible electroporation. The high-voltage DC electric pulses in the form graphically illustrated in FIG. 5, 10, or 12 generate an electric field sufficient to cause apoptosis/necrosis in a zone extending beyond the edge of the cavity

700, for example. In various embodiments, the electrical pulses may be characterized by the parameters in accordance with the output of the energy source 14 as discussed with respect to FIGS. 1 and 5, for example.

[0091] FIG. 20 illustrates the expanded sponge 708 intact to fill the cavity 700 left in the breast 702 as shown in FIG. 17 following irreversible electroporation ablation therapy. After the irreversible electroporation ablation treatment is completed, the positive electrode 714 is removed from the cavity 700 and the negative electrodes 716a,b are removed from the breast 702. The sponge 708, however, may be left inside to fill the cavity 700.

[0092] FIG. 21 illustrates a mesh of a finite element model 709 of a sponge inserted in the cavity 700 left in the breast 702 as shown in FIG. 17. The horizontal and the vertical axes represent distance in meters (m) with the center defined at (0,0). As shown in FIG. 21, the mesh of the finite element model 709 is a two-dimensional representation of the sponge similar to the sponge 708 inserted in the cavity 700 of the breast 702 previously described in FIGS. 17-20, for example.

[0093] FIG. 22 is a graphical representation of electric potential and electrical field strength sufficient to induce irreversible electroporation when applied to the sponge 708 located within the breast cavity 700 as shown in FIG. 17. The horizontal and the vertical axes represent distance in meters (m) with the center defined at (0,0). As shown in FIG. 22, electric field strength in Volts/meter (V/m) is represented by electric field lines 718 shown as concentric contours or circles extending from an outer perimeter of the sponge 708 to a point in space 726 where the electric field strength is at a minimum. A scale 722 to the right of the graph represents electric field strength in V/m. Electric potential 720 in Volts (V) applied to the sponge 708 within the cavity 700 is represented by the shaded zones 720. A vertical scale 724 shown to the right of the electric field strength scale 722 represents electric potential in V with the minimum potential at the bottom and the maximum potential at the top. The electrical field lines 718a,b just outside the outer perimeter of the sponge 708 are representative of an electric field potential 720a of about 1400 to about 2000 V sufficient to cause cell necrosis by irreversible electroporation.

[0094] FIG. 23 is a graphical representation of electric field strength contours in volts per meter (V/m) developed when electrodes are energized by an energy source. The horizontal and the vertical axes represent distance in meters (m) with the center defined at (0,0). FIG. 23 illustrates a graph 730 of electric field strength contours developed when the electrodes 24a,b are inserted into the sponge 708 and energized by the energy source 14, as described in FIGS. 17-22. A vertical scale 732 shown to the right of the graph 730 represents the electric field strength in a range from a minimum of about 50,000V/m (bottom) to a maximum of about 100,000V/m (top). Irreversible electroporation energy in this range of electric field strength (e.g., about 50,000V/m to about 100,000V/m) are suitable for efficient and effective treatment of medical conditions that require the ablation of undesirable tissue from a localized region (i.e., in the case of the treatment of cancer). With reference to the embodiment described in FIGS. 17-22, needle-probes or electrodes 24a,b are inserted into the sponge 708. As shown in the graph 730, electric field strength contours 734, 736 represent the maximum electric field strength (e.g., about 80,000 to about 100,000V/m) in a region proximate to the location where the needle electrodes 24a,b are inserted into the sponge 708. Electric field strength contour

738 represents electric field strength of about 50,000V/m. In regions outside the sponge 708, the electric field strength peaks at contour 742 to about 100,000V/m and then tapers off with distance to about 80,000V/m at contour 744 to about 50,000V/m at contour 746. It will be appreciated that other electric field strength contours may be developed to render effective irreversible electroporation ablation therapy. Accordingly, the embodiments described herein should not be limited in this context.

[0095] The embodiments of the electrical ablation devices described herein may be introduced inside a patient using minimally invasive or open surgical techniques. In some instances it may be advantageous to introduce the electrical ablation devices inside the patient using a combination of minimally invasive and open surgical techniques. Minimally invasive techniques provide more accurate and effective access to the treatment region for diagnostic and treatment procedures. To reach internal treatment regions within the patient, the electrical ablation devices described herein may be inserted through natural openings of the body such as the mouth, anus, and/or vagina, for example. Minimally invasive procedures performed by the introduction of various medical devices into the patient through a natural opening of the patient are known in the art as NOTES™ procedures. Surgical devices, such as an electrical ablation devices, may be introduced to the treatment region through the working channels of the endoscope to perform key surgical activities (KSA), including, for example, electrical ablation of tissues using irreversible electroporation energy. Some portions of the electrical ablation devices may be introduced to the tissue treatment region percutaneously or through small-keyhole-incisions.

[0096] Endoscopic minimally invasive surgical and diagnostic medical procedures are used to evaluate and treat internal organs by inserting a small tube into the body. The endoscope may have a rigid or a flexible tube. A flexible endoscope may be introduced either through a natural body opening (e.g., mouth, anus, and/or vagina). A rigid endoscope may be introduced via trocar through a relatively small-keyhole-incision (usually 0.5-1.5 cm). The endoscope can be used to observe surface conditions of internal organs, including abnormal or diseased tissue such as lesions and other surface conditions and capture images for visual inspection and photography. The endoscope may be adapted and configured with working channels for introducing medical instruments to the treatment region for taking biopsies, retrieving foreign objects, and/or performing surgical procedures.

[0097] Once an electrical ablation device is inserted in the human body internal organs may be reached using trans-organ or transluminal surgical procedures. The electrical ablation device may be advanced to the treatment site using endoscopic transluminal access techniques to perforate a lumen, and then, advance the electrical ablation device and the endoscope into the peritoneal cavity. Transluminal access procedures for perforating a lumen wall, inserting, and advancing an endoscope therethrough, and pneumoperitoneum devices for insufflating the peritoneal cavity and closing or suturing the perforated lumen wall are well known. During a transluminal access procedure, a puncture must be formed in the stomach wall or in the gastrointestinal tract to access the peritoneal cavity. One device often used to form such a puncture is a needle knife which is inserted through the working channel of the endoscope, and which utilizes energy to penetrate through the tissue. A guidewire is then fed

through the endoscope and is passed through the puncture in the stomach wall and into the peritoneal cavity. The needle knife is removed, leaving the guidewire as a placeholder. A balloon catheter is then passed over the guidewire and through the working channel of the endoscope to position the balloon within the opening in the stomach wall. The balloon can then be inflated to increase the size of the opening, thereby enabling the endoscope to push against the rear of the balloon and to be feed through the opening and into the peritoneal cavity. Once the endoscope is positioned within the peritoneal cavity, numerous procedures can be performed through the working channel of the endoscope.

[0098] The endoscope may be connected to a video camera (single chip or multiple chips) and may be attached to a fiber-optic cable system connected to a “cold” light source (halogen or xenon), to illuminate the operative field. The video camera provides a direct line-of-sight view of the treatment region. The abdomen is usually insufflated with carbon dioxide (CO₂) gas to create a working and viewing space. The abdomen is essentially blown up like a balloon (insufflated), elevating the abdominal wall above the internal organs like a dome. CO₂ gas is used because it is common to the human body and can be removed by the respiratory system if it is absorbed through tissue.

[0099] Once the electrical ablation devices are located at the target site, the diseased tissue may be electrically ablated or destroyed using the various embodiments of electrodes discussed herein. The placement and location of the electrodes can be important for effective and efficient electrical ablation therapy. For example, the electrodes may be positioned proximal to a treatment region (e.g., target site or worksite) either endoscopically or transcutaneously (percutaneously). In some implementations, it may be necessary to introduce the electrodes inside the patient using a combination of endoscopic, transcutaneous, and/or open techniques. The electrodes may be introduced to the tissue treatment region through a working channel of the endoscope, an over-tube, or a trocar and, in some implementations, may be introduced through percutaneously or through small-keyhole-incisions.

[0100] Preferably, the various embodiments of the devices described herein will be processed before surgery. First, a new or used instrument is obtained and if necessary cleaned. The instrument can then be sterilized. In one sterilization technique, the instrument is placed in a closed and sealed container, such as a plastic or TYVEK® bag. The container and instrument are then placed in a field of radiation that can penetrate the container, such as gamma radiation, x-rays, or high-energy electrons. The radiation kills bacteria on the instrument and in the container. The sterilized instrument can then be stored in the sterile container. The sealed container keeps the instrument sterile until it is opened in the medical facility.

[0101] It is preferred that the device is sterilized. This can be done by any number of ways known to those skilled in the art including beta or gamma radiation, ethylene oxide, steam.

[0102] Although the various embodiments of the devices have been described herein in connection with certain disclosed embodiments, many modifications and variations to those embodiments may be implemented. For example, different types of end effectors may be employed. Also, where materials are disclosed for certain components, other materi-

als may be used. The foregoing description and following claims are intended to cover all such modification and variations.

[0103] Any patent, publication, or other disclosure material, in whole or in part, that is said to be incorporated by reference herein is incorporated herein only to the extent that the incorporated materials does not conflict with existing definitions, statements, or other disclosure material set forth in this disclosure. As such, and to the extent necessary, the disclosure as explicitly set forth herein supersedes any conflicting material incorporated herein by reference. Any material, or portion thereof, that is said to be incorporated by reference herein, but which conflicts with existing definitions, statements, or other disclosure material set forth herein will only be incorporated to the extent that no conflict arises between that incorporated material and the existing disclosure material.

1-5. (canceled)

6. An electrical ablation apparatus, comprising:

an elongated tubular body made of an electrically conductive material, the elongated tubular body comprising:

an arcuate closed distal end configured for entry into a first natural orifice of a body;

an open proximal end; and

a first electrode received in the open proximal end of the elongated tubular body, the first electrode electrically coupled to the elongated tubular body;

a second electrode, located external to the elongated tubular body, the second electrode configured for entry into the body; and

an energy source having a first conductive terminal in electrical communication with the first electrode and a second conductive terminal in electrical communication with the second electrode, the energy source configured to deliver a first series of electrical pulses sufficient to induce cell necrosis by irreversible electroporation across the first electrode and the second electrode,

wherein the first series of electrical pulses are characterized by a first amplitude, a first pulse length, and a first frequency.

7. The apparatus of claim 6, wherein the elongated tubular body is dimensioned for insertion into a channel of an endoscope, thoracoscope, or laparoscope.

8. The apparatus of claim 6, wherein the elongated tubular body is further configured for entry into a lung of the body.

9. The apparatus of claim 6, wherein the second electrode is configured for entry into a second natural orifice of the body.

10. The apparatus of claim 6, wherein the second electrode is configured for transcutaneous entry into the body.

11. The apparatus of claim 6, wherein a distal end of the second electrode is configured to be placed proximate to a distal end of the first electrode independent of a placement of the distal end of the first electrode.

12. A method for using an electrical ablation apparatus, comprising:

inserting an elongated tubular body made of an electrically conductive material comprising an arcuate closed distal end and a first electrode received in an open proximal end of the elongated tubular body into a first natural orifice of a body, wherein the first electrode is electrically coupled to the elongated tubular body;

inserting a second electrode, located external to the elongated tubular body, into the body;

electrically contacting a first conductive terminal of an energy source with the first electrode, and electrically contacting a second conductive terminal of the energy source with the second electrode; and

delivering, by the energy source, a first series of electrical pulses sufficient to induce cell necrosis by irreversible electroporation across the first electrode and the second electrode,

wherein the first series of electrical pulses are characterized by a first amplitude, a first pulse length, and a first frequency.

13. The method of claim 12, wherein inserting an elongated tubular body into a first natural orifice of a body comprises inserting the elongated tubular body through the first natural orifice of the body into a lung of the body.

14. The method of claim 12, wherein inserting the second electrode into the body comprises inserting the second electrode into a second natural orifice of the body.

15. The method of claim 12, wherein inserting the second electrode into the body comprises inserting the second electrode transcutaneously into the body.

16. The method of claim 12, further comprising placing a distal end of the second electrode proximate to a distal end of the first electrode independent of a placement of the distal end of the first electrode.

17. An electrical ablation system, comprising:

an elongated tubular body made of an electrically conductive material, the elongated tubular body comprising:

an arcuate closed distal end configured for entry into a first natural orifice of a body;

an open proximal end; and

a first electrode received in the open proximal end of the elongated tubular body, the first electrode electrically coupled to the elongated tubular body;

a visualization device configured to visualize an internal compartment of the body and configured to receive the elongated tubular body;

a second electrode, located external to the elongated tubular body, the second electrode configured for entry into the body; and

an energy source having a first conductive terminal in electrical communication with the first electrode and a second conductive terminal in electrical communication with the second electrode, the energy source configured to deliver a first series of electrical pulses sufficient to induce cell necrosis by irreversible electroporation across the first electrode and the second electrode;

wherein the first series of electrical pulses are characterized by a first amplitude, a first pulse length, and a first frequency.

18. The system of claim 17, wherein visualization device comprises an endoscope, a thoracoscope, or a laparoscope.

19. The system of claim 17, wherein visualization device comprises a plurality of working channels.

20. The system of claim 17, wherein the visualization device further comprises a viewing port.

21. The system of claim 17, wherein the second electrode further comprises a conductive portion in electrical communication with a distal end of the second electrode.

22. The system of claim 21, wherein the conductive portion is a sharpened portion.

23. The system of claim 21, wherein the conductive portion is a pad.

24. The system of claim **21**, further comprising a handpiece comprising an activation switch in electrical communication with the energy source.

* * * * *

专利名称(译)	电消融装置		
公开(公告)号	US20150265342A1	公开(公告)日	2015-09-24
申请号	US14/673111	申请日	2015-03-30
[标]申请(专利权)人(译)	伊西康内外科公司		
申请(专利权)人(译)	爱惜康内镜手术，INC.		
当前申请(专利权)人(译)	ETHICON LLC		
[标]发明人	LONG GARY L GHABRIAL RAGAE M PLESCIA DAVID N VAKHARIA OMAR J		
发明人	LONG, GARY L. GHABRIAL, RAGAE M. PLESCIA, DAVID N. VAKHARIA, OMAR J.		
IPC分类号	A61B18/14 A61B18/12		
CPC分类号	A61B18/1492 A61B18/1477 A61B18/1206 A61B2018/1425 A61B2018/00482 A61B2018/00577 A61B2018/00613 A61B2018/00898 A61B2018/00214 A61B2018/00547 A61B2018/124		
其他公开文献	US10004558		
外部链接	Espacenet USPTO		

摘要(译)

电消融设备包括第一和第二电极。每个电极包括配置成耦合能量源的第一端和配置成耦合到组织治疗区域的第二端。能量源耦合到第一和第二电极。能量源配置成通过第一和第二电极中的至少一个输送足以通过不可逆电穿孔诱导细胞坏死的第一系列电脉冲和足以通过热加热诱导细胞坏死的第二系列电脉冲。第一系列电脉冲的特征在于第一幅度，第一脉冲长度和第一频率。第二系列电脉冲的特征在于第二幅度，第二脉冲长度和第二频率。

