



US009289115B2

(12) **United States Patent**
Dang et al.

(10) **Patent No.:** **US 9,289,115 B2**
(45) **Date of Patent:** **Mar. 22, 2016**

(54) **NATURAL ORIFICE SURGERY SYSTEM**

(71) Applicants: **Kevin K. Dang**, Garden Grove, CA (US); **Jeremy J. Albrecht**, Rancho Santa Margarita, CA (US); **Blaze Brown**, Rancho Santa Margarita, CA (US); **Adam Hoke**, Columbia City, IN (US); **Adeeb Saiduddin**, Irvine, CA (US); **Gary M. Johnson**, Rancho Santa Margarita, CA (US); **Jacob J. Filek**, Rancho Santa Margarita, CA (US)

(72) Inventors: **Kevin K. Dang**, Garden Grove, CA (US); **Jeremy J. Albrecht**, Rancho Santa Margarita, CA (US); **Blaze Brown**, Rancho Santa Margarita, CA (US); **Adam Hoke**, Columbia City, IN (US); **Adeeb Saiduddin**, Irvine, CA (US); **Gary M. Johnson**, Rancho Santa Margarita, CA (US); **Jacob J. Filek**, Rancho Santa Margarita, CA (US)

(73) Assignee: **Applied Medical Resources Corporation**, Rancho Santa Margarita, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 200 days.

(21) Appl. No.: **13/865,854**

(22) Filed: **Apr. 18, 2013**

(65) **Prior Publication Data**

US 2013/0245381 A1 Sep. 19, 2013

Related U.S. Application Data

(63) Continuation-in-part of application No. 61/636,492, filed on Apr. 20, 2012.

(60) Provisional application No. 13/250,398, filed on Sep. 30, 2011, provisional application No. 61/389,091, filed on Oct. 1, 2010, provisional application No. 61/485,321, filed on May 12, 2011.

(51) **Int. Cl.**

A61B 1/32 (2006.01)
A61B 17/02 (2006.01)
A61B 17/34 (2006.01)
A61B 17/00 (2006.01)

(52) **U.S. Cl.**

CPC *A61B 1/32* (2013.01); *A61B 17/0218* (2013.01); *A61B 17/0293* (2013.01); *A61B 17/3421* (2013.01); *A61B 17/3423* (2013.01); *A61B 17/3431* (2013.01); *A61B 2017/00557* (2013.01); *A61B 2017/345* (2013.01); *A61B 2017/347* (2013.01); *A61B 2017/3419* (2013.01); *A61B 2017/3443* (2013.01); *A61B 2017/3452* (2013.01); *A61B 2017/3466* (2013.01); *A61B 2017/3482* (2013.01); *A61B 2017/3492* (2013.01)


(58) **Field of Classification Search**

CPC .. *A61B 1/32*; *A61B 17/0218*; *A61B 17/3421*; *A61B 17/3431*
USPC 600/201-246
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

558,364 A	4/1896	Doolittle
1,157,202 A	10/1915	Bates et al.
1,598,284 A	8/1926	Kinney
1,690,995 A	11/1928	Pratt
1,180,466 A	6/1931	Deutsch
1,810,466 A	6/1931	Deutsch
2,219,564 A	10/1940	Reyniers
2,305,289 A	12/1942	Coburg
2,478,586 A	8/1949	Krapp
2,669,991 A	2/1954	Curutchet
2,695,608 A	11/1954	Gibbon
2,812,758 A	11/1957	Blumenschein
2,835,253 A	5/1958	Borgeson
2,853,075 A	9/1958	Hoffman et al.
3,039,468 A	6/1962	Price
3,057,350 A	10/1962	Cowley
3,111,943 A	11/1963	Orndorff
3,195,934 A	7/1965	Parrish
3,244,169 A	4/1966	Baxter
3,253,594 A	5/1966	Matthews et al.
3,313,299 A	4/1967	Spademan
3,329,390 A	7/1967	Hulsey



US 9,289,115 B2

Page 2

3,332,417 A	7/1967	Blanford et al.	4,553,537 A	11/1985	Rosenberg
3,347,226 A	10/1967	Harrower	4,555,242 A	11/1985	Saudagar
3,347,227 A	10/1967	Harrower	4,556,996 A	12/1985	Wallace
3,397,692 A	8/1968	Creager, Jr. et al.	4,601,710 A	7/1986	Moll
3,402,710 A	9/1968	Paleschuck	4,610,665 A	9/1986	Matsumoto et al.
3,416,520 A	12/1968	Creager, Jr.	4,626,245 A	12/1986	Weinstein
3,447,533 A	6/1969	Spicer	4,634,424 A	1/1987	O'Boyle
3,522,800 A	8/1970	Lesser	4,634,432 A	1/1987	Kocak
3,523,534 A	8/1970	Nolan	4,644,951 A	2/1987	Bays
3,570,475 A	3/1971	Weinstein	4,649,904 A	3/1987	Krauter
3,656,485 A	4/1972	Robertson	4,653,476 A	3/1987	Bonnet
3,685,786 A	8/1972	Woodson	4,654,030 A	3/1987	Moll et al.
3,717,151 A	2/1973	Collett	4,655,752 A	4/1987	Honkanen et al.
3,717,883 A	2/1973	Mosher	4,673,393 A	6/1987	Suzuki et al.
3,729,006 A	4/1973	Wilder et al.	4,673,394 A	6/1987	Fenton
3,729,027 A	4/1973	Bare	4,691,942 A	9/1987	Ford
3,782,370 A	1/1974	McDonald	4,714,749 A	12/1987	Hughes et al.
3,797,478 A	3/1974	Walsh et al.	4,738,666 A	4/1988	Fuqua
3,799,166 A	3/1974	Marsan	4,755,170 A	7/1988	Golden
3,807,393 A	4/1974	McDonald	4,760,933 A	8/1988	Christner et al.
3,828,764 A	8/1974	Jones	4,776,843 A	10/1988	Martinez et al.
3,831,583 A	8/1974	Edmunds et al.	4,777,943 A	10/1988	Chvapil
3,841,332 A	10/1974	Treacle	4,784,646 A	11/1988	Feingold
3,850,172 A	11/1974	Cazalis	4,796,629 A	1/1989	Grayzel
3,853,126 A	12/1974	Schulte	4,798,594 A	1/1989	Hillstead
3,853,127 A	12/1974	Spademan	4,802,694 A	2/1989	Vargo
3,856,021 A	12/1974	McIntosh	4,808,168 A	2/1989	Warring
3,860,274 A	1/1975	Ledstrom et al.	4,809,679 A	3/1989	Shimonaka et al.
3,861,416 A	1/1975	Wichterle	4,828,554 A	5/1989	Griffin
3,907,389 A	9/1975	Cox et al.	4,842,931 A	6/1989	Zook
3,915,171 A	10/1975	Shermeta	4,848,575 A	7/1989	Nakamura et al.
3,965,890 A	6/1976	Gauthier	4,856,502 A	8/1989	Ersfeld et al.
3,970,089 A	7/1976	Saice	4,863,430 A	9/1989	Klyce et al.
3,996,623 A	12/1976	Kaster	4,863,438 A	9/1989	Gauderer et al.
4,000,739 A	1/1977	Stevens	4,889,107 A	12/1989	Kaufman
4,016,884 A	4/1977	Kwan-Gett	4,895,565 A	1/1990	Hillstead
4,024,872 A	5/1977	Muldoon	4,897,081 A	1/1990	Poirier
4,030,500 A	6/1977	Ronnquist	4,903,710 A	2/1990	Jessamine et al.
4,043,328 A	8/1977	Cawood, Jr. et al.	4,911,974 A	3/1990	Shimizu et al.
4,069,913 A	1/1978	Harrigan	4,915,132 A	4/1990	Hodge et al.
4,083,370 A	4/1978	Taylor	4,926,882 A	5/1990	Lawrence
4,096,853 A	6/1978	Weigand	4,929,235 A	5/1990	Merry et al.
4,112,932 A	9/1978	Chiulli	4,944,732 A	7/1990	Russo
4,117,847 A	10/1978	Clayton	4,950,222 A	8/1990	Scott et al.
4,130,113 A	12/1978	Graham	4,950,223 A	8/1990	Silvanov
4,177,814 A	12/1979	Knepshield et al.	4,984,564 A	1/1991	Yuen
4,183,357 A	1/1980	Bentley et al.	4,991,593 A	2/1991	LeVahn
4,187,849 A	2/1980	Stim	4,998,538 A	3/1991	Charowsky et al.
4,188,945 A	2/1980	Wenander	5,000,745 A	3/1991	Guest et al.
4,217,664 A	8/1980	Faso	5,009,224 A	4/1991	Cole
4,222,126 A	9/1980	Boretos et al.	5,015,228 A	5/1991	Columbus et al.
4,228,792 A	10/1980	Rhys-Davies	5,019,101 A	5/1991	Purkait et al.
4,239,036 A	12/1980	Krieger	5,026,366 A	6/1991	Leckrone
4,240,411 A	12/1980	Hosono	5,037,379 A	8/1991	Clayman et al.
4,253,201 A	3/1981	Ross et al.	5,041,095 A	8/1991	Littrell
4,254,973 A	3/1981	Benjamin	5,045,070 A	9/1991	Grodecki et al.
4,306,562 A	12/1981	Osborne	D320,658 S	10/1991	Quigley et al.
4,321,915 A	3/1982	Leighton	5,071,411 A	12/1991	Hillstead
4,331,138 A	5/1982	Jessen	5,073,169 A	12/1991	Raiken
4,338,934 A	7/1982	Spademan	5,074,878 A	12/1991	Bark et al.
4,338,937 A	7/1982	Lerman	5,082,005 A	1/1992	Erdley
4,367,728 A	1/1983	Mutke	5,086,763 A	2/1992	Hathman
4,369,284 A	1/1983	Chen	5,092,846 A	3/1992	Nishijima et al.
4,399,816 A	8/1983	Spangler	5,104,389 A	4/1992	Deem
4,402,683 A	9/1983	Kopman	5,125,396 A	6/1992	Ray
4,411,659 A	10/1983	Jensen et al.	5,125,897 A	6/1992	Quinn et al.
4,421,296 A	12/1983	Stephens	5,127,626 A	7/1992	Hilal et al.
4,424,833 A	1/1984	Spector et al.	5,129,885 A	7/1992	Green et al.
4,428,364 A	1/1984	Bartolo	5,141,498 A	8/1992	Christian
4,430,081 A	2/1984	Timmermans	5,149,327 A	9/1992	Oshiyama
4,434,791 A	3/1984	Darnell	5,156,617 A	10/1992	Reid
4,436,519 A	3/1984	O'Neill	5,158,553 A	10/1992	Berry et al.
4,454,873 A	6/1984	Laufenberg et al.	5,159,921 A	11/1992	Hoover
4,473,067 A	9/1984	Schiff	5,161,773 A	11/1992	Tower
4,475,548 A	10/1984	Muto	5,167,636 A	12/1992	Clement
4,485,490 A	12/1984	Akers et al.	5,167,637 A	12/1992	Okada et al.
4,488,877 A	12/1984	Klein	5,176,648 A	1/1993	Holmes et al.
4,543,088 A	9/1985	Bootman et al.	5,176,662 A	1/1993	Bartholomew et al.
4,550,713 A	11/1985	Hyman	5,176,697 A	1/1993	Hasson et al.

US 9,289,115 B2

Page 3

5,178,162 A	1/1993	Bose	5,411,483 A	5/1995	Loomas
5,180,365 A	1/1993	Ensminger et al.	5,413,571 A	5/1995	Katsaros et al.
5,183,471 A	2/1993	Wilk	5,423,848 A	6/1995	Washizuka et al.
5,188,595 A	2/1993	Jacobi	5,429,609 A	7/1995	Yoon
5,188,607 A	2/1993	Wu	5,431,676 A	7/1995	Dubrul et al.
5,192,301 A	3/1993	Kamiya et al.	5,437,683 A	8/1995	Neumann et al.
5,197,955 A	3/1993	Stephens et al.	5,439,455 A	8/1995	Kieturakis et al.
5,207,656 A	5/1993	Kranys	5,441,486 A	8/1995	Yoon
5,209,737 A	5/1993	Ritchart et al.	5,443,452 A	8/1995	Hart et al.
5,211,370 A	5/1993	Powers	5,456,284 A	10/1995	Ryan et al.
5,211,633 A	5/1993	Stouder, Jr.	5,460,170 A	10/1995	Hammerslag
5,213,114 A	5/1993	Bailey, Jr.	5,460,616 A	10/1995	Weinstein et al.
5,226,890 A	7/1993	Ianniruberto et al.	5,468,248 A	11/1995	Chin et al.
5,234,455 A	8/1993	Mulhollan	5,476,475 A	12/1995	Gadberry
5,241,968 A	9/1993	Slater	5,480,410 A	1/1996	Cuschieri et al.
5,242,400 A	9/1993	Blake, III et al.	5,486,426 A	1/1996	McGee et al.
5,242,409 A	9/1993	Buelna	5,490,843 A	2/1996	Hildwein et al.
5,242,412 A	9/1993	Blake, III et al.	5,492,304 A	2/1996	Smith et al.
5,242,415 A	9/1993	Kantrowitz et al.	5,496,280 A	3/1996	Vandenbroek et al.
5,248,304 A	9/1993	Vigdorchik et al.	5,503,112 A	4/1996	Luhman et al.
5,256,150 A	10/1993	Quiachon et al.	5,507,758 A	4/1996	Thomason et al.
5,257,973 A	11/1993	Villasuso	5,508,334 A	4/1996	Chen
5,257,975 A	11/1993	Foshee	5,511,564 A	4/1996	Wilk
5,259,366 A	11/1993	Reydel et al.	5,514,109 A	5/1996	Mollenauer et al.
5,261,883 A	11/1993	Hood et al.	5,514,133 A	5/1996	Golub et al.
5,262,468 A	11/1993	Chen	5,514,153 A	5/1996	Bonutti
5,263,922 A	11/1993	Sova et al.	5,518,278 A	5/1996	Sampson
5,269,763 A	12/1993	Boehmer et al.	5,520,632 A	5/1996	Leveen
5,269,772 A	12/1993	Wilk	5,522,791 A	6/1996	Leyva
5,273,449 A	12/1993	Mattis et al.	5,522,824 A	6/1996	Ashby
5,273,545 A	12/1993	Hunt et al.	5,524,644 A	6/1996	Crook
D343,236 S	1/1994	Quigley et al.	5,526,536 A	6/1996	Cartmill
5,279,575 A	1/1994	Sugarbaker	5,531,758 A	7/1996	Uschold et al.
5,290,310 A	3/1994	Makower et al.	5,538,509 A	7/1996	Dunlap et al.
D346,022 S	4/1994	Quigley et al.	5,540,648 A	7/1996	Yoon
5,299,582 A	4/1994	Potts	5,540,711 A	7/1996	Kieturakis et al.
5,300,034 A	4/1994	Behnke	5,545,150 A	8/1996	Danks et al.
5,300,035 A	4/1994	Clement	5,545,179 A	8/1996	Williamson, IV
5,300,036 A	4/1994	Mueller et al.	5,549,563 A	8/1996	Kronner
5,308,336 A	5/1994	Hart et al.	5,549,637 A	8/1996	Crainich
5,309,896 A	5/1994	Moll et al.	5,554,124 A	9/1996	Alvarado
5,312,391 A	5/1994	Wilk	5,562,632 A	10/1996	Davila et al.
5,314,417 A	5/1994	Stephens et al.	5,562,677 A	10/1996	Hildwein et al.
5,316,541 A	5/1994	Fischer	5,562,688 A	10/1996	Riza
5,320,611 A	6/1994	Bonutti et al.	5,571,115 A	11/1996	Nicholas
5,330,437 A	7/1994	Durman	5,571,137 A	11/1996	Marlow et al.
5,330,486 A	7/1994	Wilk	5,575,799 A	11/1996	Bolanos et al.
5,330,497 A	7/1994	Freitas et al.	5,577,993 A	11/1996	Zhu et al.
5,331,975 A	7/1994	Bonutti	5,578,048 A	11/1996	Pasqualucci et al.
5,334,143 A	8/1994	Carroll	5,580,344 A	12/1996	Hasson
5,334,646 A	8/1994	Chen	5,584,850 A	12/1996	Hart et al.
5,336,192 A	8/1994	Palestrant	5,601,579 A	2/1997	Semertzides
5,336,708 A	8/1994	Chen	5,601,581 A	2/1997	Fogarty et al.
5,338,313 A	8/1994	Mollenauer et al.	5,603,702 A	2/1997	Smith et al.
5,342,315 A	8/1994	Rowe et al.	5,607,443 A	3/1997	Kieturakis et al.
5,342,385 A	8/1994	Norelli et al.	5,620,415 A	4/1997	Lucey et al.
5,350,364 A	9/1994	Stephens et al.	5,620,420 A	4/1997	Kriesel
5,353,786 A	10/1994	Wilk	5,628,732 A	5/1997	Antoon, Jr. et al.
5,354,280 A	10/1994	Haber et al.	5,632,284 A	5/1997	Graether
5,360,417 A	11/1994	Gravener et al.	5,632,979 A	5/1997	Goldberg et al.
5,364,345 A	11/1994	Lowery et al.	5,634,911 A	6/1997	Hermann et al.
5,364,372 A	11/1994	Danks et al.	5,634,936 A	6/1997	Linden et al.
5,366,446 A	11/1994	Tal et al.	5,634,937 A	6/1997	Mollenauer et al.
5,366,478 A	11/1994	Brinkerhoff et al.	5,636,645 A	6/1997	Ou
5,368,545 A	11/1994	Schaller et al.	5,640,977 A	6/1997	Leahy et al.
5,375,588 A	12/1994	Yoon	5,643,301 A	7/1997	Mollenauer
5,380,288 A	1/1995	Hart et al.	5,649,550 A	7/1997	Crook
5,383,861 A	1/1995	Hempel et al.	5,651,771 A	7/1997	Tangherlini et al.
5,385,552 A	1/1995	Haber et al.	5,653,705 A	8/1997	de la Torre et al.
5,385,553 A	1/1995	Hart et al.	5,657,963 A	8/1997	Hinchliffe et al.
5,385,560 A	1/1995	Wulf	5,658,272 A	8/1997	Hasson
5,389,080 A	2/1995	Yoon	5,658,306 A	8/1997	Kieturakis
5,389,081 A	2/1995	Castro	5,662,615 A	9/1997	Blake, III
5,391,153 A	2/1995	Haber et al.	5,672,168 A	9/1997	de la Torre et al.
5,391,156 A	2/1995	Hildwein et al.	5,681,341 A	10/1997	Lunsford et al.
5,395,367 A	3/1995	Wilk	5,683,378 A	11/1997	Christy
5,403,264 A	4/1995	Wohlers et al.	5,685,854 A	11/1997	Green et al.
5,403,336 A	4/1995	Kieturakis et al.	5,685,857 A	11/1997	Negus et al.
5,407,433 A	4/1995	Loomas	5,697,914 A	12/1997	Brimhall

US 9,289,115 B2

Page 4

5,707,703 A	1/1998	Rothrum et al.	5,997,515 A	12/1999	de la Torre et al.
5,709,664 A	1/1998	Vandenbroek et al.	6,004,303 A	12/1999	Peterson
5,713,858 A	2/1998	Heruth et al.	6,010,494 A	1/2000	Schafer et al.
5,713,869 A	2/1998	Morejon	6,017,355 A	1/2000	Hessel et al.
5,720,730 A	2/1998	Blake, III	6,018,094 A	1/2000	Fox
5,725,536 A	3/1998	Oberlin et al.	6,024,736 A	2/2000	de la Torre et al.
5,728,103 A	3/1998	Picha et al.	6,025,067 A	2/2000	Fay
5,730,748 A	3/1998	Fogarty et al.	6,033,426 A	3/2000	Kaji
5,735,791 A	4/1998	Alexander et al.	6,033,428 A	3/2000	Sardella
5,738,628 A	4/1998	Sierocuk et al.	6,035,559 A	3/2000	Freed et al.
5,741,234 A	4/1998	Aboul-Hosn	6,042,573 A	3/2000	Lucey
5,741,298 A	4/1998	MacLeod	6,045,535 A	4/2000	Ben Nun
5,743,884 A	4/1998	Hasson et al.	6,048,309 A	4/2000	Flom et al.
5,749,882 A	5/1998	Hart et al.	6,050,871 A	4/2000	Chen
5,755,660 A	5/1998	Tyagi	6,053,934 A	4/2000	Andrews et al.
5,760,117 A	6/1998	Chen	6,059,816 A	5/2000	Moenning
5,769,783 A	6/1998	Fowler	6,066,117 A	5/2000	Fox et al.
5,782,812 A	7/1998	Hart et al.	6,068,639 A	5/2000	Fogarty et al.
5,782,817 A	7/1998	Franzel et al.	6,076,560 A	6/2000	Stahle et al.
5,782,859 A	7/1998	Nicholas et al.	6,077,288 A	6/2000	Shimomura
5,788,676 A	8/1998	Yoon	6,086,603 A	7/2000	Termin et al.
5,792,119 A	8/1998	Marx	6,090,043 A	7/2000	Austin et al.
5,795,290 A	8/1998	Bridges	6,099,506 A	8/2000	Macoviak et al.
5,803,919 A	9/1998	Hart et al.	6,110,154 A	8/2000	Shimomura et al.
5,803,921 A	9/1998	Bonadio	6,123,689 A	9/2000	To et al.
5,803,923 A	9/1998	Singh-Derewa et al.	6,142,935 A	11/2000	Flom et al.
5,807,350 A	9/1998	Diaz	6,142,936 A	11/2000	Beane et al.
5,810,712 A	9/1998	Dunn	6,149,642 A	11/2000	Gerhart et al.
5,810,721 A	9/1998	Mueller et al.	6,150,608 A	11/2000	Wambeke et al.
5,813,409 A	9/1998	Leahy et al.	6,159,182 A	12/2000	Davis
5,814,026 A	9/1998	Yoon	6,162,172 A	12/2000	Cosgrove et al.
5,817,062 A	10/1998	Flom et al.	6,162,196 A	12/2000	Hart et al.
5,819,375 A	10/1998	Kastner	6,162,206 A	12/2000	Bindokas
5,820,555 A	10/1998	Watkins, III et al.	6,163,949 A	12/2000	Neuenschwander
5,820,600 A	10/1998	Carlson et al.	6,164,279 A	12/2000	Tweedle
5,830,191 A	11/1998	Hildwein et al.	6,171,282 B1	1/2001	Ragsdale
5,832,925 A	11/1998	Rothrum	6,183,486 B1	2/2001	Snow et al.
5,836,871 A	11/1998	Wallace et al.	6,197,002 B1	3/2001	Peterson
5,841,298 A	11/1998	Huang	6,217,555 B1	4/2001	Hart et al.
5,842,971 A	12/1998	Yoon	6,217,590 B1	4/2001	Levinson
5,848,992 A	12/1998	Hart et al.	6,224,612 B1	5/2001	Bates et al.
5,853,395 A	12/1998	Crook et al.	6,228,063 B1	5/2001	Aboul-Hosn
5,853,417 A	12/1998	Fogarty et al.	6,238,373 B1	5/2001	de la Torre et al.
5,857,461 A	1/1999	Levitsky et al.	6,241,768 B1	6/2001	Agarwal et al.
5,860,995 A	1/1999	Berkelaar	6,254,533 B1	7/2001	Fadem et al.
5,865,728 A	2/1999	Moll et al.	6,254,534 B1	7/2001	Butler et al.
5,865,729 A	2/1999	Meehan et al.	6,258,065 B1	7/2001	Dennis et al.
5,865,807 A	2/1999	Blake, III	6,264,604 B1	7/2001	Kieturakis et al.
5,865,817 A	2/1999	Moenning et al.	6,267,751 B1	7/2001	Mangosong
5,871,474 A	2/1999	Hermann et al.	6,276,661 B1	8/2001	Laird
5,876,413 A	3/1999	Fogarty et al.	6,287,280 B1	9/2001	Lampropoulos et al.
5,879,368 A	3/1999	Hoskin et al.	6,315,770 B1	11/2001	de la Torre et al.
5,882,344 A	3/1999	Stouder, Jr.	6,319,246 B1	11/2001	de la Torre et al.
5,884,639 A	3/1999	Chen	6,322,541 B2	11/2001	West
5,894,843 A	4/1999	Benetti et al.	6,325,384 B1	12/2001	Berry, Sr. et al.
5,895,377 A	4/1999	Smith et al.	6,346,074 B1	2/2002	Roth
5,899,208 A	5/1999	Bonadio	6,371,968 B1	4/2002	Kogasaka et al.
5,899,913 A	5/1999	Fogarty et al.	6,382,211 B1	5/2002	Crook
5,904,703 A	5/1999	Gilson	6,383,162 B1	5/2002	Sugarbaker
5,906,577 A	5/1999	Beane et al.	6,391,043 B1	5/2002	Moll et al.
5,913,847 A	6/1999	Yoon	6,413,244 B1	7/2002	Bestetti et al.
5,916,198 A	6/1999	Dillow	6,413,458 B1	7/2002	Pearce
5,916,232 A	6/1999	Hart	6,420,475 B1	7/2002	Chen
5,919,476 A	7/1999	Fischer et al.	6,423,036 B1	7/2002	Van Huizen
5,931,832 A	8/1999	Jensen	6,440,061 B1	8/2002	Wenner et al.
5,947,922 A	9/1999	MacLeod	6,440,063 B1	8/2002	Beane et al.
5,951,467 A	9/1999	Picha et al.	6,443,957 B1	9/2002	Addis
5,951,588 A	9/1999	Moenning	6,447,489 B1 *	9/2002	Peterson 604/264
5,957,888 A	9/1999	Hinchliffe	6,450,983 B1	9/2002	Rambo
5,957,913 A	9/1999	de la Torre et al.	6,454,783 B1	9/2002	Piskun
5,962,572 A	10/1999	Chen	6,464,686 B1	10/2002	O'Hara et al.
5,964,781 A	10/1999	Mollenauer et al.	6,468,292 B1	10/2002	Mollenauer et al.
5,976,174 A	11/1999	Ruiz	6,482,181 B1	11/2002	Racenet et al.
5,989,232 A	11/1999	Yoon	6,485,435 B1	11/2002	Bakal
5,989,233 A	11/1999	Yoon	6,485,467 B1	11/2002	Crook et al.
5,989,266 A	11/1999	Foster	6,488,620 B1	12/2002	Segermark et al.
5,993,471 A	11/1999	Riza et al.	6,488,692 B1	12/2002	Spence et al.
5,993,485 A	11/1999	Beckers	6,494,893 B2	12/2002	Dubrul et al.
5,994,450 A	11/1999	Pearce	6,527,787 B1	3/2003	Fogarty et al.

US 9,289,115 B2

Page 5

6,533,734	B1	3/2003	Corley, III et al.	7,100,614	B2	9/2006	Stevens et al.
6,551,270	B1	4/2003	Bimbo et al.	7,101,353	B2	9/2006	Lui et al.
6,551,276	B1	4/2003	Mann et al.	7,105,009	B2	9/2006	Johnson
6,551,344	B2	4/2003	Thill	7,105,607	B2	9/2006	Chen
6,552,109	B1	4/2003	Chen	7,112,185	B2	9/2006	Hart et al.
6,554,793	B1	4/2003	Pauker et al.	7,118,528	B1	10/2006	Piskun
6,558,371	B2	5/2003	Dorn	7,134,929	B2	11/2006	Chen
6,569,120	B1	5/2003	Green	7,153,261	B2	12/2006	Wenchell
6,578,577	B2	6/2003	Bonadio et al.	7,163,510	B2	1/2007	Kahle et al.
6,579,281	B2	6/2003	Palmer et al.	7,192,436	B2	3/2007	Sing et al.
6,582,364	B2	6/2003	Butler et al.	7,193,002	B2	3/2007	Chen
6,589,167	B1	7/2003	Shimomura et al.	7,195,590	B2	3/2007	Butler et al.
6,589,211	B1	7/2003	MacLeod	7,214,185	B1	5/2007	Rosney et al.
6,607,504	B2	8/2003	Haarala et al.	7,217,277	B2	5/2007	Parihar et al.
6,613,952	B2	9/2003	Rambo	7,222,380	B2	5/2007	Chen
6,623,426	B2	9/2003	Bonadio et al.	7,223,257	B2	5/2007	Shubayev et al.
6,627,275	B1	9/2003	Chen	7,223,278	B2	5/2007	Davison et al.
6,663,598	B1	12/2003	Carrillo et al.	7,226,484	B2	6/2007	Chen
6,669,674	B1	12/2003	Macoviac et al.	7,235,062	B2	6/2007	Brustad
6,676,639	B1	1/2004	Ternström	7,235,084	B2	6/2007	Skakoon et al.
6,702,787	B2	3/2004	Racenet et al.	7,238,154	B2	7/2007	Ewers et al.
6,705,989	B2	3/2004	Cuschieri et al.	7,244,244	B2	7/2007	Racenet et al.
6,706,050	B1	3/2004	Giannadakis	7,276,075	B1	10/2007	Callas et al.
6,714,298	B2	3/2004	Ryer	7,290,367	B2	11/2007	Chen
6,716,201	B2	4/2004	Blanco	7,294,103	B2	11/2007	Bertolero et al.
6,723,044	B2	4/2004	Pulford et al.	7,297,106	B2	11/2007	Yamada et al.
6,723,088	B2	4/2004	Gaskill, III et al.	7,300,399	B2	11/2007	Bonadio et al.
6,725,080	B2	4/2004	Melkent et al.	7,316,699	B2	1/2008	McFarlane
6,793,621	B2	9/2004	Butler et al.	7,331,940	B2	2/2008	Sommerich
6,794,440	B2	9/2004	Chen	7,338,473	B2	3/2008	Campbell et al.
6,796,940	B2	9/2004	Bonadio et al.	7,344,546	B2	3/2008	Wulfinan et al.
6,797,765	B2	9/2004	Pearce	7,344,547	B2	3/2008	Piskun
6,800,084	B2	10/2004	Davison et al.	7,344,568	B2	3/2008	Chen
6,811,546	B1	11/2004	Callas et al.	7,377,898	B2	5/2008	Ewers et al.
6,814,078	B2	11/2004	Crook	7,390,317	B2	6/2008	Taylor et al.
6,814,700	B1	11/2004	Mueller et al.	7,393,322	B2	7/2008	Wenchell
6,817,974	B2	11/2004	Cooper et al.	7,412,977	B2	8/2008	Fields et al.
6,830,578	B2	12/2004	O'Heeron et al.	7,445,597	B2	11/2008	Butler et al.
6,837,893	B2	1/2005	Miller	7,473,221	B2	1/2009	Ewers et al.
6,840,946	B2	1/2005	Fogarty et al.	7,481,765	B2	1/2009	Ewers et al.
6,840,951	B2	1/2005	de la Torre et al.	7,537,564	B2	5/2009	Bonadio et al.
6,846,287	B2	1/2005	Bonadio et al.	7,540,839	B2	6/2009	Butler et al.
6,860,463	B2	3/2005	Hartley	7,559,893	B2	7/2009	Bonadio et al.
6,863,674	B2	3/2005	Kasahara et al.	7,578,832	B2	8/2009	Johnson
6,866,861	B1	3/2005	Luhman	7,645,232	B2	1/2010	Shluzas
6,867,253	B1	3/2005	Chen	7,650,887	B2	1/2010	Nguyen et al.
6,869,393	B2	3/2005	Butler	7,661,164	B2	2/2010	Chen
6,878,110	B2	4/2005	Yang et al.	7,704,207	B2	4/2010	Albrecht et al.
6,884,253	B1	4/2005	McFarlane	7,717,847	B2	5/2010	Smith
6,890,295	B2	5/2005	Michels et al.	7,727,146	B2	6/2010	Albrecht et al.
6,895,965	B2	5/2005	Scarberry et al.	7,727,255	B2	6/2010	Taylor et al.
6,902,541	B2	6/2005	McNally et al.	7,736,306	B2	6/2010	Brustad et al.
6,902,569	B2	6/2005	Parmer et al.	7,749,415	B2	7/2010	Brustad et al.
6,908,430	B2	6/2005	Caldwell et al.	7,753,901	B2	7/2010	Piskun et al.
6,909,220	B2	6/2005	Chen	7,758,500	B2	7/2010	Boyd et al.
6,913,609	B2	7/2005	Yencho et al.	7,766,824	B2	8/2010	Jensen et al.
6,916,310	B2	7/2005	Sommerich	7,811,251	B2	10/2010	Wenchell et al.
6,916,331	B2	7/2005	Mollenauer et al.	7,815,567	B2	10/2010	Albrecht et al.
6,929,637	B2	8/2005	Gonzalez et al.	7,837,612	B2	11/2010	Gill et al.
6,936,037	B2	8/2005	Bubb et al.	7,841,765	B2	11/2010	Keller
6,939,296	B2	9/2005	Ewers et al.	7,850,667	B2	12/2010	Gresham
6,945,932	B1	9/2005	Caldwell et al.	7,867,164	B2	1/2011	Butler et al.
6,958,037	B2	10/2005	Ewers et al.	7,878,974	B2	2/2011	Brustad et al.
6,972,026	B1	12/2005	Caldwell et al.	7,896,889	B2	3/2011	Mazzocchi et al.
6,979,324	B2	12/2005	Bybordi et al.	7,909,760	B2	3/2011	Albrecht et al.
6,991,602	B2	1/2006	Nakazawa et al.	7,930,782	B2	4/2011	Chen
6,997,909	B2	2/2006	Goldberg	8,137,267	B2 *	3/2012	Shelton et al. 600/203
7,001,397	B2	2/2006	Davison et al.	2001/0037053	A1	11/2001	Bonadio et al.
7,008,377	B2	3/2006	Beane et al.	2001/0047188	A1	11/2001	Bonadio et al.
7,014,628	B2	3/2006	Bousquet	2002/0002324	A1	1/2002	McManus
7,033,319	B2	4/2006	Pulford et al.	2002/0010389	A1	1/2002	Butler et al.
7,052,454	B2	5/2006	Taylor	2002/0013542	A1	1/2002	Bonadio et al.
7,056,304	B2	6/2006	Bacher et al.	2002/0016607	A1	2/2002	Bonadio et al.
7,056,321	B2	6/2006	Pagliuca et al.	2002/0026230	A1	2/2002	Moll et al.
7,067,583	B2	6/2006	Chen	2002/0038077	A1	3/2002	de la Torre et al.
7,077,852	B2	7/2006	Fogarty et al.	2002/0072762	A1	6/2002	Bonadio et al.
7,081,089	B2	7/2006	Bonadio et al.	2002/0111536	A1	8/2002	Cuschieri et al.
7,083,626	B2	8/2006	Hart et al.	2003/0004253	A1	1/2003	Chen
7,093,599	B2	8/2006	Chen	2003/0028179	A1	2/2003	Piskun

2003/0040711	A1	2/2003	Racenet et al.	2006/0161049	A1	7/2006	Beane et al.
2003/0078478	A1	4/2003	Bonadio et al.	2006/0161050	A1	7/2006	Butler et al.
2003/0139756	A1	7/2003	Brustad	2006/0241651	A1	10/2006	Wilk
2003/0167040	A1	9/2003	Bacher et al.	2006/0247498	A1	11/2006	Bonadio et al.
2003/0187376	A1	10/2003	Rambo	2006/0247499	A1	11/2006	Butler et al.
2003/0192553	A1	10/2003	Rambo	2006/0247500	A1	11/2006	Voegele et al.
2003/0225392	A1	12/2003	McMichael et al.	2006/0247516	A1	11/2006	Hess et al.
2003/0236505	A1	12/2003	Bonadio et al.	2006/0247586	A1	11/2006	Voegele et al.
2003/0236549	A1	12/2003	Bonadio et al.	2006/0247673	A1	11/2006	Voegele et al.
2004/0015185	A1	1/2004	Ewers et al.	2006/0247678	A1	11/2006	Weisenburgh, II et al.
2004/0024363	A1	2/2004	Goldberg	2006/0258899	A1	11/2006	Gill et al.
2004/0049099	A1	3/2004	Ewers et al.	2006/0264706	A1	11/2006	Piskun
2004/0049100	A1	3/2004	Butler	2006/0270911	A1	11/2006	Voegele et al.
2004/0054353	A1	3/2004	Taylor	2007/0004968	A1	1/2007	Bonadio et al.
2004/0063833	A1	4/2004	Chen	2007/0049966	A1	3/2007	Bonadio et al.
2004/0068232	A1	4/2004	Hart et al.	2007/0088202	A1	4/2007	Albrecht et al.
2004/0070187	A1	4/2004	Chen	2007/0088204	A1	4/2007	Albrecht
2004/0072942	A1	4/2004	Chen	2007/0093695	A1	4/2007	Bonadio et al.
2004/0073090	A1	4/2004	Butler	2007/0118175	A1	5/2007	Butler et al.
2004/0092795	A1	5/2004	Bonadio et al.	2007/0149859	A1	6/2007	Albrecht
2004/0092796	A1	5/2004	Butler et al.	2007/0151566	A1	7/2007	Kahle et al.
2004/0093018	A1	5/2004	Johnson	2007/0156023	A1	7/2007	Frasier et al.
2004/0097793	A1	5/2004	Butler et al.	2007/0185387	A1	8/2007	Albrecht et al.
2004/0106942	A1	6/2004	Taylor et al.	2007/0203398	A1	8/2007	Bonadio et al.
2004/0111061	A1	6/2004	Curran	2007/0208312	A1	9/2007	Norton et al.
2004/0127772	A1	7/2004	Ewers et al.	2007/0255219	A1	11/2007	Vaugh et al.
2004/0138529	A1	7/2004	Wiltshire et al.	2007/0270752	A1	11/2007	Labombard
2004/0143158	A1	7/2004	Hart et al.	2007/0299387	A1	12/2007	Williams et al.
2004/0154624	A1	8/2004	Bonadio et al.	2008/0027476	A1	1/2008	Piskun
2004/0167559	A1	8/2004	Taylor et al.	2008/0048011	A1	2/2008	Weller
2004/0173218	A1	9/2004	Yamada et al.	2008/0097162	A1	4/2008	Bonadio et al.
2004/0215063	A1	10/2004	Bonadio et al.	2008/0097163	A1	4/2008	Butler et al.
2004/0230161	A1	11/2004	Zeiner	2008/0200767	A1	8/2008	Ewers et al.
2004/0243144	A1	12/2004	Bonadio et al.	2008/0255519	A1	10/2008	Piskun et al.
2004/0249248	A1	12/2004	Bonadio et al.	2008/0281161	A1	11/2008	Albrecht et al.
2004/0254426	A1	12/2004	Wenchell	2008/0281162	A1	11/2008	Albrecht et al.
2004/0260244	A1	12/2004	Piechowicz et al.	2009/0012477	A1	1/2009	Norton et al.
2004/0267096	A1	12/2004	Caldwell et al.	2009/0036745	A1	2/2009	Bonadio et al.
2005/0020884	A1	1/2005	Hart et al.	2009/0069837	A1	3/2009	Bonadio et al.
2005/0033246	A1	2/2005	Ahlberg et al.	2009/0093683	A1	4/2009	Richard et al.
2005/0059865	A1	3/2005	Kahle et al.	2009/0093752	A1	4/2009	Richard et al.
2005/0065475	A1	3/2005	Hart et al.	2009/0131754	A1	5/2009	Ewers et al.
2005/0065543	A1	3/2005	Kahle et al.	2009/0137879	A1	5/2009	Ewers et al.
2005/0080319	A1	4/2005	Dinkler, II et al.	2009/0149714	A1	6/2009	Bonadio
2005/0090713	A1	4/2005	Gonzales et al.	2009/0182279	A1	7/2009	Wenchell et al.
2005/0090716	A1	4/2005	Bonadio et al.	2009/0182282	A1	7/2009	Okihiisa
2005/0090717	A1	4/2005	Bonadio et al.	2009/0187079	A1	7/2009	Albrecht et al.
2005/0096695	A1	5/2005	Olich	2009/0227843	A1	9/2009	Smith et al.
2005/0131349	A1	6/2005	Albrecht et al.	2009/0259110	A1 *	10/2009	Bastia et al. 600/235
2005/0148823	A1	7/2005	Vaugh et al.	2009/0292176	A1	11/2009	Bonadio et al.
2005/0155611	A1	7/2005	Vaugh et al.	2009/0326330	A1	12/2009	Bonadio et al.
2005/0159647	A1	7/2005	Hart et al.	2010/0063362	A1	3/2010	Bonadio et al.
2005/0192483	A1	9/2005	Bonadio et al.	2010/0063364	A1	3/2010	Bonadio et al.
2005/0192598	A1	9/2005	Johnson et al.	2010/0081880	A1	4/2010	Widenhouse et al.
2005/0197537	A1	9/2005	Bonadio et al.	2010/0081881	A1	4/2010	Murray et al.
2005/0203346	A1	9/2005	Bonadio et al.	2010/0081995	A1	4/2010	Widenhouse et al.
2005/0209510	A1	9/2005	Bonadio et al.	2010/0100043	A1	4/2010	Racenet
2005/0222582	A1	10/2005	Wenchell	2010/0113882	A1	5/2010	Widenhouse et al.
2005/0240082	A1	10/2005	Bonadio et al.	2010/0217087	A1	8/2010	Bonadio et al.
2005/0241647	A1	11/2005	Nguyen	2010/0228091	A1	9/2010	Widenhouse et al.
2005/0251124	A1	11/2005	Zvuloni et al.	2010/0228092	A1	9/2010	Ortiz et al.
2005/0261720	A1	11/2005	Caldwell et al.	2010/0228094	A1	9/2010	Ortiz et al.
2005/0267419	A1	12/2005	Smith	2010/0240960	A1	9/2010	Richard
2005/0277946	A1	12/2005	Greenhalgh	2010/0249523	A1	9/2010	Spiegel et al.
2005/0283050	A1	12/2005	Gundlapalli et al.	2010/0249524	A1	9/2010	Ransden et al.
2005/0288558	A1	12/2005	Ewers et al.	2010/0249525	A1	9/2010	Shelton, IV et al.
2005/0288634	A1	12/2005	O'Heeron et al.	2010/0249694	A1	9/2010	Choi et al.
2006/0020164	A1	1/2006	Butler et al.	2010/0261972	A1	10/2010	Widenhouse et al.
2006/0020241	A1	1/2006	Piskun et al.	2010/0261975	A1	10/2010	Huey et al.
2006/0030755	A1	2/2006	Ewers et al.	2010/0286484	A1	11/2010	Stellon et al.
2006/0041270	A1	2/2006	Lenker	2010/0298646	A1	11/2010	Stellon et al.
2006/0047284	A1	3/2006	Gresham	2010/0312063	A1 *	12/2010	Hess et al. 600/204
2006/0047293	A1	3/2006	Haberland et al.	2010/0312066	A1 *	12/2010	Cropper et al. 600/207
2006/0052669	A1	3/2006	Hart	2011/0009704	A1 *	1/2011	Marczyk et al. 600/207
2006/0084842	A1	4/2006	Hart et al.	2011/0021877	A1	1/2011	Fortier et al.
2006/0106402	A1	5/2006	McLucas	2011/0028891	A1	2/2011	Okoniewski
2006/0129165	A1	6/2006	Edoga et al.	2011/0034935	A1 *	2/2011	Kleyman 606/108
2006/0149137	A1	7/2006	Pingleton et al.	2011/0034946	A1	2/2011	Kleyman
2006/0149306	A1	7/2006	Hart et al.	2011/0034947	A1	2/2011	Kleyman

2011/0071462	A1	3/2011	Ewers et al.	
2011/0071463	A1	3/2011	Ewers et al.	
2011/0118552	A1*	5/2011	Fischvogt	600/206
2012/0095297	A1	4/2012	Dang et al.	

FOREIGN PATENT DOCUMENTS

DE	26 05 148	A1	8/1977
DE	33 36 279	C2	1/1986
DE	37 39 532		12/1988
DE	37 37 121		5/1989
DE	296 00 939		6/1996
DE	19828009		12/1999
EP	0 113 520		7/1984
EP	0 142 262		5/1985
EP	0 517 248		12/1992
EP	0 537 768		4/1993
EP	0 807 416		11/1997
EP	0 849 517		6/1998
EP	0950376		10/1999
EP	1 118 657		7/2001
EP	1 125 552		8/2001
EP	1 312 318		5/2003
EP	1 407 715		4/2004
EP	2 044 889		4/2009
EP	2 272 450	A2	1/2011
EP	2 340 792		7/2011
FR	1456623		9/1966
GB	1151993		5/1969
GB	1355611		6/1974
GB	1372491		10/1974
GB	1379772		1/1975
GB	1400808		7/1975
GB	1407023		9/1975
GB	1482857		8/1977
GB	1496696		12/1977
GB	2071502		9/1981
GB	2255019		10/1992
GB	2275420		8/1994
GB	2298906		9/1996
IE	930649		9/1993
IE	930650		9/1993
IE	S940150		2/1994
IE	S940613		8/1994
IE	S940960		12/1994
IE	S950055		1/1995
IE	S950266		4/1995
IE	S75368		8/1997
IE	S960196		8/1997
IE	S970810		11/1997
IE	991010		7/2000
IE	990218		11/2000
IE	990219		11/2000
IE	990220		11/2000
IE	990660		2/2001
IE	990795		3/2001
JP	10-108868		4/1998
JP	11-290327		10/1999
JP	2001-61850		3/2001
JP	2002-28163		1/2002
JP	02003 235879	A	8/2003
JP	2004-195037		7/2004
SU	1342485		1/1997
WO	WO 86/06272		11/1986
WO	WO 86/06316		11/1986
WO	WO 92/11880		7/1992
WO	WO 92/21292		12/1992
WO	WO 93/05740		4/1993
WO	WO 93/14801		8/1993
WO	WO 94/04067		3/1994
WO	WO 94/22357		10/1994
WO	WO 95/05207		2/1995
WO	WO 95/07056		3/1995
WO	WO 95/22289		8/1995
WO	WO 95/24864		9/1995
WO	WO 95/27445		10/1995
WO	WO 95/27468		10/1995
WO	WO 96/36283		11/1996
WO	WO 97/11642		4/1997

WO	WO 97/32514	9/1997
WO	WO 97/32515	9/1997
WO	WO 97/42889	11/1997
WO	WO 98/19853	5/1998
WO	WO 98/35614	8/1998
WO	WO 98/48724	11/1998
WO	WO 99/03416	1/1999
WO	WO 99/15068	4/1999
WO	WO 99/16368	4/1999
WO	WO 99/22804	5/1999
WO	WO 99/25268	5/1999
WO	WO 99/29250	6/1999
WO	WO 00/32116	6/2000
WO	WO 00/32117	6/2000
WO	WO 00/32119	6/2000
WO	WO 00/32120	6/2000
WO	WO 00/35356	6/2000
WO	WO 00/54675	9/2000
WO	WO 00/54676	9/2000
WO	WO 00/54677	9/2000
WO	WO 01/08563	2/2001
WO	WO 01/08581	2/2001
WO	WO 01/26558	4/2001
WO	WO 01/26559	4/2001
WO	WO 01/45568	6/2001
WO	WO 01/45568	6/2001
WO	WO 01/49363	7/2001
WO	WO 01/91652	12/2001
WO	WO 02/07611	1/2002
WO	WO 02/17800	3/2002
WO	WO 02/34108	5/2002
WO	WO 03/011153	2/2003
WO	WO 03/011551	2/2003
WO	WO 03/026512	4/2003
WO	WO 03/032819	4/2003
WO	WO 03/034908	5/2003
WO	WO 03/061480	7/2003
WO	WO 03/077726	9/2003
WO	WO 03/103548	12/2003
WO	WO 2004/026153	4/2004
WO	WO 2004/030547	4/2004
WO	WO 2004/075730	9/2004
WO	WO 2004/075741	9/2004
WO	WO 2004/075930	9/2004
WO	WO 2005/009257	2/2005
WO	WO 2005/034766	4/2005
WO	WO 2005/089661	9/2005
WO	WO 2006/040748	4/2006
WO	WO 2006/059318	6/2006
WO	WO 2006/100658	9/2006
WO	WO 2007/044849	4/2007
WO	WO 2008/015566	2/2008
WO	WO 2008/093313	8/2008
WO	WO 2008/121294	10/2008
WO	WO 2010/045253	4/2010
WO	WO 2010/082722	7/2010
WO	WO 2010/104259	9/2010

OTHER PUBLICATIONS

The International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US2011/054266, titled "Natural Orifice Surgery System", dated Apr. 2, 2013.

European Patent Office, The International Search Report and Written Opinion for International Application No. PCT/US2013/037213, titled "Natural Orifice Surgery System" dated Jul. 3, 2013.

U.S. Appl. No. 10/381,220; filed Mar. 20, 2003; Title: Surgical Access Apparatus and Method, now USPN 7,473,221 issued Jan. 6, 2009.

U.S. Appl. No. 10/436,522; filed May 13, 2003; Title: Laparoscopic Illumination Apparatus and Method, now USPN 6,939,296 issued Sep. 6, 2005.

U.S. Appl. No. 10/399,209; filed Aug. 22, 2003; Title: Wound Retraction Apparatus and Method, now USPN 6,958,037 issued Oct. 25, 2005.

- U.S. Appl. No. 11/218,412; filed Sep. 1, 2005; Title: Wound Retraction Apparatus and Method, now USPN 7,238,154 issued Jul. 3, 2007.
- U.S. Appl. No. 10/399,057; filed Apr. 11, 2003; Title: Sealed Surgical Access Device, now USPN 7,052,454 issued May 30, 2006.
- U.S. Appl. No. 10/666,579; filed Sep. 17, 2003; Title: Surgical Instrument Access Device, now USPN 7,163,510 issued Jan. 16, 2007.
- U.S. Appl. No. 10/052,297; filed Jan. 18, 2002; Title: Hand Access Port Device, now USPN 6,908,430 issued Jun. 21, 2005.
- U.S. Appl. No. 08/015,765; filed Feb. 10, 1993; Title: Gas-Tight Seal Accommodating Surgical Instruments With a Wide Range of Diameters, now USPN 5,407,433 issued Apr. 18, 1995.
- U.S. Appl. No. 08/040,373; filed Mar. 30, 1993; Title: Gas-Tight Seal Accommodating Surgical Instruments With a Wide Range of Diameters, now USPN 5,411,483 issued May 2, 1995.
- U.S. Appl. No. 10/902,756; filed Jul. 29, 2004; Title: Hand Access Port Device, now abandoned.
- U.S. Appl. No. 10/802,125; filed Mar. 15, 2004; Title: Surgical Guide Valve, now abandoned.
- U.S. Appl. No. 10/516,198; filed Nov. 30, 2004; Title: Wound Retractor, now USPN 7,650,887 issued Jan. 26, 2010.
- U.S. Appl. No. 10/927,551; filed Aug. 25, 2004; Title: Surgical Access System, now abandoned.
- U.S. Appl. No. 11/244,647; filed Oct. 5, 2005; Title: Surgical Access Apparatus and Method, now USPN 7,481,765 issued Jan. 27, 2009.
- U.S. Appl. No. 11/548,746; filed Oct. 12, 2006; Title: Method of Making a Hand Access Laparoscopic Device, now USPN 7,749,415 issued Jul. 6, 2010.
- U.S. Appl. No. 11/548,765; filed Oct. 12, 2006; Title: Split Hoop Wound Retractor, now USPN 7,815,567 issued Oct. 26, 2010.
- U.S. Appl. No. 11/548,767; filed Oct. 12, 2006; Title: Circular Surgical Retractor now USPN 7,704,207 issued Apr. 27, 2010.
- U.S. Appl. No. 11/548,781; filed Oct. 12, 2006; Title: Wound Retractor With Gel Cap, now USPN 7,727,146 issued Jun. 1, 2010.
- U.S. Appl. No. 11/548,955; filed Oct. 12, 2006; Title: Hand Access Laparoscopic Device, now USPN 7,736,306 issued Jun. 15, 2010.
- U.S. Appl. No. 11/755,305; filed May 30, 2007; Title: Wound Retraction Apparatus and Method, now USPN 7,377,898 issued May 27, 2008.
- U.S. Appl. No. 11/548,758; filed Oct. 12, 2007; Title: Split Hoop Wound Retractor With Gel Pad, now USPN 7,909,760 issued Mar. 22, 2011.
- U.S. Appl. No. 12/693,242; filed Jan. 1, 2010; Title: Wound Retractor, now USPN 7,913,697 issued Mar. 29, 2011.
- U.S. Appl. No. 12/768,328; filed Apr. 27, 2010; Title: Circular Surgical Retractor, now USPN 7,892,172 issued Feb. 22, 2011.
- U.S. Appl. No. 12/791,666; filed Jun. 1, 2010; Title: Wound Retractor With Gel Cap, now USPN 7,883,461 issued Feb. 8, 2011.
- U.S. Appl. No. 12/815,986; filed Jun. 15, 2010; Title: Hand Access Laparoscopic Device, now USPN 7,878,974 issued Feb. 1, 2011.
- U.S. Appl. No. 10/695,295; filed Oct. 28, 2003; Title: Surgical Gel Seal.
- U.S. Appl. No. 11/132,741; filed May 18, 2005; Title: Gas-Tight Seal Accommodating Surgical Instruments With a Wide Range of Diameters.
- U.S. Appl. No. 11/245,709; filed Oct. 7, 2005; Title: Surgical Access System.
- U.S. Appl. No. 11/330,661; filed Jan. 12, 2006; Title: Sealed Surgical Access Device.
- U.S. Appl. No. 11/564,409; filed Nov. 29, 2006; Title: Surgical Instrument Access Device.
- U.S. Appl. No. 12/108,400; filed Apr. 23, 2008; Title: Wound Retraction Apparatus and Method.
- U.S. Appl. No. 12/119,371; filed May 12, 2008; Title: Surgical Retractor With Gel Pad.
- U.S. Appl. No. 12/119,414; filed May 12, 2008; Title: Surgical Retractor.
- U.S. Appl. No. 12/358,080; filed Jan. 22, 2009; Title: Surgical Instrument Access Device.
- U.S. Appl. No. 12/360,634; filed Jan. 27, 2009; Title: Surgical Access Apparatus and Method.
- U.S. Appl. No. 12/360,710; filed Jan. 27, 2009; Title: Surgical Access Apparatus and Method.
- U.S. Appl. No. 12/578,422; filed Oct. 13, 2009; Title: Single Port Access System.
- U.S. Appl. No. 12/905,932; filed Oct. 15, 2010; Title: Split Hoop Wound Retractor.
- U.S. Appl. No. 12/960,449; filed Dec. 3, 2010; Title: Surgical Access Apparatus and Method.
- U.S. Appl. No. 12/960,458; filed Dec. 3, 2010; Title: Surgical Access Apparatus and Method.
- U.S. Appl. No. 13/006,727; filed Jan. 14, 2011; Title: Hand Access Laparoscopic Device.
- U.S. Appl. No. 13/008,728; filed Jan. 18, 2011; Title: Wound Retractor With Gel Cap.
- U.S. Appl. No. 13/023,334; filed Feb. 8, 2011; Title: Circular Surgical Retractor.
- U.S. Appl. No. 13/031,892; filed Feb. 22, 2011; Title: Wound Retractor.
- U.S. Appl. No. 13/050,042; filed Mar. 17, 2011; Title: Split Hoop Wound Retractor With Gel Pad.
- U.S. Appl. No. 10/446,365; filed May 28, 2003; Title: Screw-Type Seal With Inflatable Membrane.
- U.S. Appl. No. 12/004,439; filed Dec. 20, 2007; Title: Skin Seal.
- U.S. Appl. No. 12/004,441; filed Dec. 20, 2007; Title: Screw-Type Skin Seal With Inflatable Membrane.
- U.S. Appl. No. 12/607,667; filed Oct. 28, 2009; Title: Screw-Type Skin Seal With Inflatable Membrane.
- U.S. Appl. No. 10/965,217; filed Oct. 15, 2004; Title: Surgical Sealing Device.
- U.S. Appl. No. 10/981,730; filed Nov. 5, 2004; Title: Surgical Sealing Device.
- U.S. Appl. No. 11/246,909; filed Oct. 11, 2005; Title: Instrument Access Device.
- U.S. Appl. No. 11/291,089; filed Dec. 1, 2005; Title: A Surgical Sealing Device.
- U.S. Appl. No. 11/486,383; filed Jul. 14, 2006; Title: Wound Retractor.
- U.S. Appl. No. 11/785,752; filed Apr. 19, 2007; Title: Instrument Access Device.
- U.S. Appl. No. 12/244,024; filed Oct. 2, 2008; Title: Seal Anchor for Use in Surgical Procedures.
- U.S. Appl. No. 12/578,832; filed Oct. 14, 2009; Title: Flexible Access Device for Use in Surgical Procedure.
- U.S. Appl. No. 12/706,043; filed Feb. 16, 2010; Title: Flexible Port Seal.
- U.S. Appl. No. 12/719,341; filed Mar. 8, 2010; Title: Foam Port and Introducer Assembly.
- U.S. Appl. No. 10/895,546; filed Jul. 21, 2004; Title: Laparoscopic Instrument and Cannula Assembly and Related Surgical Method.
- U.S. Appl. No. 10/913,565; filed Aug. 5, 2004; Title: Surgical Device With Tack-Free Gel and Method of Manufacture.
- Dexterity Protractor Instruction Manual by Dexterity Surgical, Inc., dated 1999.
- European Patent Office, European Search Report for European Application No. EP 10 18 4681, entitled "Wound Retraction Apparatus and Method", dated Nov. 22, 2010.
- European Patent Office, European Search Report for European Application No. EP 10 18 4608, entitled "Wound Retraction Apparatus and Method", dated Nov. 22, 2010.
- European Patent Office, European Search Report for European Application No. EP 10 18 4648, entitled "Wound Retraction Apparatus and Method", dated Nov. 22, 2010.
- European Patent Office, European Search Report for European Application No. EP 10 18 4731, entitled "Wound Retraction Apparatus and Method", dated Nov. 22, 2010.
- European Patent Office, European Search Report for European Application No. EP 10 18 4661, entitled "Wound Retraction Apparatus and Method", dated Nov. 22, 2010.
- European Patent Office, European Search Report for European Application No. EP 10 18 4677, entitled "Wound Retraction Apparatus and Method", dated Nov. 22, 2010.
- European Patent Office, European Search Report for European Application No. EP 10 18 9325, entitled "Split Hoop Wound Retractor", dated Dec. 14, 2010.

- European Patent Office, European Search Report for European Application No. EP 10 18 9327, entitled "Split Hoop Wound Retractor", dated Dec. 14, 2010.
- European Patent Office, European Search Report for European Application No. EP 10 18 9328, entitled "Split Hoop Wound Retractor", dated Dec. 15, 2010.
- European Patent Office, European Search Report for European Application No. EP 04 00 2888, entitled "Hand Access Port Device", dated Sep. 10, 2004.
- European Patent Office, European Search Report for European Application No. EP 04 00 2889, entitled "Hand Access Port Device", dated Sep. 13, 2004.
- European Patent Office, International Search Report and The Written Opinion of the International Searching Authority for International Application No. PCT/US2006/040154, mailed Jan. 30, 2007.
- European Patent Office, International Search Report and The Written Opinion of the International Searching Authority for International Application No. PCT/US2006/040073, mailed Jan. 26, 2007.
- European Patent Office, International Search Report and The Written Opinion of the International Searching Authority for International Application No. PCT/US2006/039905, mailed Jan. 17, 2007.
- European Patent Office, International Search Report and The Written Opinion of the International Searching Authority for International Application No. PCT/US2006/039883, mailed Jan. 31, 2007.
- European Patent Office, International Search Report and The Written Opinion of the International Searching Authority for International Application No. PCT/US2006/039800, mailed Apr. 16, 2007.
- European Patent Office, International Search Report and The Written Opinion of the International Searching Authority for International Application No. PCT/US2006/039799, mailed Mar. 27, 2007.
- European Patent Office, European Search Report for European Application No. EP 08253236 dated Feb. 10, 2009.
- Horigame, et al., Silicone Rumen Cannula with a Soft Cylindrical Part and a Hard Flange, *Journal of Dairy Science*, Nov. 1989, vol. 72, No. 11, pp. 3230-3232.
- Horigame, et al., Technical Note: Development of Duodenal Cannula for Sheep, *Journal of Animal Science*, Apr. 1992, vol. 70, Issue 4, pp. 1216-1219.
- International Searching Authority/US, International Search Report and the Written Opinion of the International Searching Authority for International Application No. PCT/US04/05484, mailed on Nov. 12, 2004.
- International Searching Authority/US, International Search Report and the Written Opinion of the International Searching Authority for International Application No. PCT/US01/29682, mailed on Jun. 14, 2002.
- McSweeney, Cannulation of the Rumen in Cattle and Buffaloes, *Australian Veterinary Journal*, Aug. 1989, vol. 66, No. 8, pp. 266-268.
- Neil Sheehan, Supplemental Expert Report of Neil Sheehan, Re: U.S. Pat. No. 5,741,298, United States District Court for the Central District of California, Civil Action No. SACV 03-1322 JVS, Aug. 9, 2005.
- Office Action in co-pending U.S. Appl. No. 12/360,634, dated Jan. 24, 2011 in 12 pages.
- Office Action in co-pending U.S. Appl. No. 12/360,710, dated Jan. 24, 2011 in 12 pages.
- Technical Note: Development of Duodenal Cannula for Sheep, Faculty of Agriculture and School of Medicine Tohoku University, Sendai 981, Japan, dated 1992.
- The International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US2004/028250, dated Aug. 29, 2006.
- The International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US2006/039799, dated Apr. 16, 2008.
- The International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US2006/039800 dated Apr. 16, 2008.
- Yamazaki, et al., Diurnal Changes in the Composition of Abomasal Digesta in Fasted and Fed Sheep, *The Tohoku Journal of Agricultural Research*, Mar. 1987, vol. 37, No. 34, pp. 49-58.
- Kagaya, Laparoscopic cholecystectomy via two ports, using the "Twin-Port" system, *J. Hepatobiliary Pancreat Surg* (2001) 8:76-80, dated Feb. 20, 2001.
- Declaration of John R. Brustad dated Dec. 10, 2009, submitted in U.S. Appl. No. 11/548,955, including Appendices A-D regarding product sales brochures and production drawings from 2001 and 2005.
- International Search Report and Written Opinion for PCT/IE2005/000113, mailed on Feb. 22, 2006.
- International Searching Authority-US, International Search Report and Written Opinion of the International Searching Authority for International Application No. PCT/US04/25511, mailed Nov. 7, 2007.
- International Bureau of WIPO, International Report on Patentability for International Application No. PCT/US04/25511, mailed Dec. 6, 2007.
- International Search Report and Written Opinion for PCT/IE2007/000050 mailed on Aug. 13, 2007.
- The International Searching Authority, The International Search Report and Written Opinion of the International Searching Authority for International Application No. PCT/US08/63445, mailed Sep. 29, 2008.
- The International Searching Authority, The International Search Report and Written Opinion of the International Searching Authority for International Application No. PCT/US08/063463 mailed Sep. 10, 2008.
- The International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US2008/063463, entitled "Surgical Retractor", dated Nov. 17, 2009.
- The International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US08/63445, entitled "Surgical Retractor with Gel Pad", dated Nov. 17, 2009.
- International Searching Authority—European Patent Office, The International Search Report and Written Opinion for International Application No. PCT/US2011/054266, mailed Feb. 9, 2012.
- European Patent Office, European Search Report for European Patent No. 11172709.5, dated Aug. 16, 2011.
- European Patent Office, European Search Report for European Patent No. 11172706.1, dated Aug. 16, 2011.
- European Patent Office, European Search Report for European Patent No. 12151288, dated Feb. 10, 2012.
- European Patent Office, European Search Report for European Patent No. 08755332, dated Apr. 18, 2012.
- European Patent Office, Supplementary European Search Report for European Patent Application No. 08755322, dated Apr. 18, 2012.
- European Patent Office, Supplementary European Search Report for European Patent Application No. 08755336, dated Jun. 15, 2012.
- Harold W. Harrower, M.D., Isolation of Incisions into Body Cavities, *The American Journal of Surgery*, vol. 116, pp. 824-826, Dec. 1968.
- International Searching Authority—European Patent Office, The International Search Report and Written Opinion for International Application No. PCT/US2012/60997, mailed Mar. 7, 2013.
- The International Bureau of WIPO, International Preliminary Report on Patentability for Application No. PCT/US2013/037213, titled "Natural Orifice Surgery System" dated Oct. 21, 2014.

* cited by examiner

Primary Examiner — Christopher Beccia
(74) *Attorney, Agent, or Firm* — Cynthia A. Bonner

(57)

ABSTRACT

Embodiments of a surgical access port system that comprises a retractor that is adapted for being coupled to a cap and that is particularly useful in natural orifice surgery are described. The retractor comprises an outer ring, wherein the outer ring is configured to be disposed proximate the natural orifice of the patient and substantially surround the orifice; a tubular body; a funnel segment extending between and coupling the outer ring and the tubular body, wherein the funnel segment provides a diametric reduction between the relatively large

diameter of the outer ring and the relatively smaller diameter of the tubular body, which is sized to fit within a natural orifice with minimal distention of the orifice; and an inflatable member disposed around the distal end of the tubular body, the inflatable member sized and configured to fit snugly around

the tubular body in the deflated condition and to expand against the wall of the natural orifice in the inflated state to thereby stabilize and retain the retractor within the orifice.

14 Claims, 46 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3









FIG. 4


**FIG. 5**


**FIG. 6A**



**FIG. 6B**



**FIG. 6C**


**FIG. 6D**

**FIG. 6E**

**FIG. 6F**





**FIG. 7A**








FIG. 7B

**FIG. 7C**

**FIG. 7D**

**FIG. 7E**

**FIG. 7F**





FIG. 7H







FIG. 7K





FIG. 7L









FIG. 7M

**FIG. 8A**

**FIG. 8B**

**FIG. 8C**

**FIG. 8D**

**FIG. 9A**




**FIG. 9B**

FIG. 9C








FIG. 10B






FIG. 11A













FIG. 11D





**FIG. 11F**








**FIG. 13**

**FIG. 14A**





**FIG. 16A****FIG. 16B**

**FIG. 17A****FIG. 17B**

NATURAL ORIFICE SURGERY SYSTEM

CROSS REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. Provisional Application Ser. No. 61/636,492, entitled "NATURAL ORIFICE MICROSURGERY SYSTEM," filed Apr. 20, 2012 and is a continuation-in-part of U.S. application Ser. No. 13/250,398, entitled "NATURAL ORIFICE MICROSURGERY SYSTEM," filed Sep. 30, 2011, which claims the benefit of U.S. Provisional Application Ser. No. 61/389,091 entitled "TRANSANAL ENDOSCOPIC MICROSURGERY SYSTEM," filed Oct. 1, 2010 and U.S. Provisional Application Ser. No. 61/485,321, entitled "TRANSANAL ENDOSCOPIC MICROSURGERY SYSTEM," filed May 12, 2011. The above-referenced applications are hereby incorporated by reference herein in their entirety.

BACKGROUND

1. Technical Field

This application is generally directed to surgical devices, and more particularly, to a retractor adapted for use with a cap, that is useful in natural orifice single-port surgical procedures.

2. Description of the Related Art

Access devices are commonly used in surgery to facilitate the introduction of various surgical instruments into natural biological vessels, conduits, orifices, cavities, and other interior regions of the body. These access devices include, for example, devices that facilitate the introduction of a needle into a vessel, and trocars that facilitate the introduction of laparoscopic instruments into the abdomen of the body.

Some of these access devices are introduced into regions that include a fluid or gas under pressure. In the case of a needle access device, the pressure may be from a liquid, such as blood. In the case of a trocar, the pressure may be from a gas, such as an insufflation gas. In either case, it is desirable to provide for the introduction of the surgical instrument into the cavity without permitting the escape of the pressurized fluid or gas.

In the case of trocars, a cannula at the distal end of the trocar is typically connected to a seal housing at the proximal end of the trocar. Together the cannula and housing form a working channel through which various instruments can be inserted to access the cavity. Seal mechanisms are commonly disposed in the housing and include a septum valve that seals the working channel when an instrument is in place, and a zero closure valve that seals the working channel when the instrument is removed.

Current surgical access ports allow for single instrument access through each port, or allow for multiple instrument access through a rigid cannula. Some devices, such as transanal endoscopic microsurgery (TEMS) units require that the device be attached to the surgical table to support the weight of the device, as well as to locate the position of the device respective to the patient. These devices do not provide flexibility to the surgeon in selecting instrument size, and they restrict instrument movement with their rigid cannulas. Additionally, surgeons are performing laparoscopic surgical procedures through a single or a limited number of access ports. The procedures may be performed through a single two (2) centimeter incision at the umbilicus, or in certain cases, transvaginally or trans-anally. What is needed is a system that meets the needs of these new procedures, facilitating more flexible movement of laparoscopic instruments through a

single or limited number of ports while preventing the escape of pressured fluids or gasses and permitting large specimen removal.

SUMMARY OF THE INVENTION

The invention is directed to a surgical access port system that comprises a retractor that is adapted for being coupled to a cap and that is particularly useful in natural orifice surgery. The retractor comprises an outer ring, wherein the outer ring is configured to be disposed proximate the natural orifice of the patient and substantially surround the orifice; a tubular body; a funnel segment extending between and coupling the outer ring and the tubular body, wherein the funnel segment provides a diametric reduction between the relatively large diameter of the outer ring and the relatively smaller diameter of the tubular body, which is sized to fit within a natural orifice with minimal distention of the orifice; and an inflatable member disposed around the distal end of the tubular body, the inflatable member sized and configured to fit snugly around the tubular body in the deflated condition and to expand against the wall of the natural orifice in the inflated state to thereby stabilize and retain the retractor within the orifice.

In one aspect, the tubular body comprises a substantially flexible material, such as a KRATON® material, a PELLETHANE® material or a silicone rubber material. In another aspect, the tubular body comprises a more rigid material, such as polycarbonate. The tubular body defines a generally cylindrical passage large enough to accommodate at least one laparoscopic instrument there through, and preferably is sufficiently large such that two or more surgical instruments positioned there through can be translated or pivoted relative to one another. In one aspect, the tubular body comprises one or more coatings, such as an antimicrobial coating. In one aspect, the tubular body has an adjustable length, where, for example, it comprises interlocking sections or perforations. In another aspect, the tubular body has opening or windows along the length of the body, to provide access by surgical instruments to the body cavity or orifice.

In one aspect, the funnel segment comprises an inner surface that can provide a bearing surface for an obturator used to advance to the retractor into a body cavity. The funnel segment can have a substantially linear taper between the relatively large diameter of the outer ring and the relatively smaller diameter of the tubular body. In one aspect, the funnel segment has a curved profile between the relatively large diameter and the relatively smaller diameter.

In one aspect, the tubular body can be formed from a relatively flexible material and the funnel segment and the outer ring from a relatively rigid material. The surgical access port system can further comprise an obturator.

In one aspect, the surgical access port system further comprises a removable cap, wherein the cap is adapted to sealingly engage the outer ring. In one aspect, the cap has a sealable access surface, such as a gel pad, and can include at least one fluid or gas port. In one aspect, the surgical access port system further comprises at least one trocar access device, wherein the trocar access device is adapted to be positioned through the sealable access surface. The trocar access device preferably contains at least one sealing valve, such as a septum seal or duck bill valve. In one aspect, the trocar access device has a low profile.

These and other features and advantages of the invention will become more apparent with a discussion of embodiments in reference to the associated drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side view of a patient in surgery illustrating an embodiment of the access device positioned on the abdomen and in use.

FIG. 2 is a cross-sectional side view illustrating an embodiment of the access device, with the wound retractor retracting the vagina of a patient, and the gel cap sealing the opening of the wound retractor.

FIG. 3 is a front view illustrating an embodiment of the access device deployed and in use at the mouth of the patient.

FIG. 4 is a top view illustrated a patient in the prone position with an embodiment of the access device deployed and in use at the anus of the patient.

FIG. 5 is a perspective view of an embodiment of an access device comprising a cap and a retractor.

FIG. 6A is a side view of an embodiment of a natural orifice retractor. FIG. 6B is a top view of the natural orifice retractor of FIG. 6A. FIG. 6C is a partial cut away of the natural orifice retractor of FIG. 6A.

FIG. 6D is a side view of another embodiment of a natural orifice retractor. FIG. 6E is a top view of the natural orifice retractor of FIG. 6D. FIG. 6F is a perspective view of the natural orifice retractor of FIG. 6A.

FIG. 6G is a perspective view of an obturator adapted to facilitate introduction of a natural orifice retractor into a body orifice such as an anus. FIG. 6H is a side view of the obturator of FIG. 6G.

FIG. 6I is a perspective view of an obturator having a straight shaft piece, adapted to facilitate introduction of a natural orifice retractor into a body orifice such as an anus. FIG. 6J is a perspective view of a retractor disposed on the obturator of FIG. 6I.

FIG. 7A is a partial side cross section of the natural orifice retractor of FIG. 6A with a gel cap coupled therewith to form one embodiment of natural orifice access device.

FIG. 7B is a side cross section of the natural orifice retractor of FIG. 6D.

FIG. 7C is a perspective view of a natural orifice retractor formed from sections and having cut-out portions or windows in the tubular body of the retractor. FIG. 7D is a cutaway view of the retractor of FIG. 7C showing the slidable engagement of the sections. FIG. 7E is a cutaway view of the retractor of FIG. 7C showing the snap-lock mechanism securing the sections together.

FIG. 7F is a perspective view and a side view of an alternative embodiment of a retractor having cut-out portions or windows in the tubular body of the retractor.

FIG. 7G is a perspective view of an alternative embodiment of a retractor having an inflatable member. FIG. 7H shows a close-up view of the inflatable member. FIG. 7I is a top-down perspective view of a retractor showing the check valve port of inflating the inflatable member. FIG. 7J is a cutaway side view showing the check valve and channel disposed in the tubular body of the retractor. FIG. 7K is a side view of a retractor showing the channel disposed between the check valve and the inflatable member.

FIG. 7L is a perspective view of an obturator, modified with an indent to provide clearance for the inflation port shown in FIGS. 7J and 7K and adapted to facilitate introduction of a natural orifice retractor into a body orifice such as an anus.

FIG. 7M is a perspective view and a side view of a perforated natural orifice retractor.

FIG. 8A is a side view of the natural orifice access device of FIG. 7A. FIG. 8B is a top view of the natural orifice access device illustrated in FIG. 7A. FIG. 8C is a perspective view of the natural orifice access device illustrated in FIG. 7A.

FIG. 8D is a perspective view of the natural orifice retractor of FIG. 6D with a gel cap therewith to form one embodiment of natural orifice access device.

FIG. 9A is a perspective view of an embodiment of a natural orifice access device including a cap having a plurality of trocars extending there through. FIG. 9B is a perspective view of another embodiment of a natural orifice access device including a cap having a plurality of trocars extending there through.

FIG. 9C is an exploded view of an embodiment of a trocar access device and optional obturator, which is a component of some embodiments of the access device system.

FIG. 10A is a top perspective view of an embodiment of a gel cap. FIG. 10B is a bottom view of an embodiment of a cap ring.

FIG. 11A is a top view of an embodiment of a gel cap comprising a plurality of access ports embedded in the gel pad. FIG. 11B is a top perspective view of the gel cap illustrated in FIG. 11A. FIG. 11C is a bottom perspective view of the gel cap illustrated in FIG. 11A.

FIG. 11D is a top perspective view of the gel cap illustrated in FIG. 11A with instruments inserted through two of the access ports. FIG. 11E is a bottom perspective view of the gel cap and instruments illustrated in FIG. 11D. FIG. 11F is a side view of the gel cap and instruments illustrated in FIG. 11D.

FIG. 11G is a top perspective view of an embodiment of gel cap comprising a fixed camera or laparoscope port.

FIG. 12 is a cutaway perspective view of an embodiment of an access device system comprising a gel cap that snap fits to a retractor.

FIG. 13 is an exploded view of an embodiment of a trocar.

FIGS. 14A and 14B are side views of an embodiment of a trocar comprising a fixation cannula in an insertion configuration and a fixation configuration, respectively.

FIG. 15 is a side view of another embodiment of a trocar comprising a fixation cannula.

FIG. 16A is a side view of another embodiment of a trocar comprising a fixation cannula. FIG. 16B is a perspective view of an embodiment of a bolster suitable for use with the trocar illustrated in FIG. 16A.

FIG. 17A is a side view of another embodiment of a trocar comprising a fixation cannula. FIG. 17B is a perspective view of an embodiment of a bolster suitable for use with the trocar illustrated in FIG. 17A.

Similar components have similar reference numbers throughout.

DETAILED DESCRIPTION OF CERTAIN EMBODIMENTS

Embodiments of a surgical instrument access device system are useful, for example, for single incision, single port, and/or limited port laparoscopic surgical procedures, for example, abdominal (FIG. 1), transvaginal (FIG. 2), transoral (FIG. 3), and transanal (FIG. 4) procedures. Various surgical instrument access devices are described in U.S. Patent Application Publication No. 2009/0187079, entitled "SURGICAL INSTRUMENT ACCESS DEVICE," filed Jan. 22, 2009, and U.S. Pat. No. 7,727,146, entitled "WOUND RETRACTOR WITH GEL CAP," both of which are incorporated by reference in their entireties herein.

FIG. 5 illustrates a perspective view of an embodiment of an access device system 5000 comprising a retractor 5100 and a cap 5500, which is useful in single port and/or limited port procedures. The retractor or surgical wound retractor 5100 is placed and/or positioned into, across, and/or through a surgical incision and/or body orifice to enlarge, reshape, and/or

isolate the incision or body orifice. The cap 5500 provides an artificial body wall through which instruments access the interior of a patient's body, for example, a body cavity. The components of the access device 5000 comprise any suitable biologically compatible materials.

Two embodiments of natural orifice access ports or retractors 6100, 7100 sharing certain similarities are illustrated in FIGS. 6-9. One embodiment of retractor 6100 is illustrated in FIGS. 6A-6C, 7A, 8A-8C, and 9A. Another embodiment of retractor 7100 is illustrated in FIGS. 6D-6F, 7B, 8D, and 9B.

The embodiment of the natural orifice access port or retractor 6100 illustrated in a side view in FIG. 6A can be adapted for use in a transanal surgical procedure. The retractor 6100 comprises an inner or distal ring 6110, an outer or proximal ring 6120, a tubular body 6130, and a funnel segment 6140 extending between and coupling the inner ring 6110 and the outer ring 6120. The tubular body 6130 comprises a relatively flexible material such as a KRATON® material or a silicone rubber material, which is substantially cylindrical in the illustrated embodiment. In other embodiments, the tubular body 6130 has another shape, for example, an oval cross section. Some embodiments of the tubular body 6130 comprise one or more coatings that provide additional functionality, for example, an anti-microbial coating.

Embodiments of the inner ring 6110 are sufficiently flexible and compliant to be compressed and/or deformed for insertion into a body orifice such as a patient's anus during a transanal surgical procedure. When subsequently released within an associated body cavity, the inner ring 6110 substantially returns to its original shape or footprint. In some embodiments, the inner ring 6110 assumes a substantially circular shape in a relaxed state, for example, when released within a body cavity. In other embodiments, the inner ring 6110 has another shape in the relaxed state, for example, an oval. The inner ring 6110 assumes a different shape when compressed for insertion through an incision or body orifice, for example, a substantially oval shape, a generally linear shape, a tear-drop shape, or another suitable shape. Those skilled in the art will recognize that in other embodiments, the inner ring 6110 in the relaxed state has a shape other than round, for example, oval, elliptical, or D-shaped. In other embodiments, the inner ring 6110 is substantially rigid, that is, non-compliant under the ordinary conditions under which it is used. In some embodiments, the inner ring extends outward from the surface of the tubular body, as shown, for example, in FIG. 6A, to thereby aid in retaining the retractor in the body cavity after it is deployed.

Embodiments of the inner ring 6110 can comprise a generally circular cross section. In other embodiments, the inner ring 6110 comprises another cross-sectional shape, for example, at least one of oval or elliptical, tear-drop shaped, and D-shaped. For example, in embodiments illustrated in FIGS. 6D-6F, the inner ring 7110 can have a cross-sectional shape that is substantially flush with the tubular body 7130 of the retractor 7100 as further described herein. Those skilled in the art will understand that other cross sections are used in other embodiments. As further discussed herein with respect to the flexion region of the inner ring 6110, some embodiments of the inner ring 6110 comprise at least one notch and/or weak spot, which facilitate folding or deforming the inner ring 6110, thereby facilitating insertion and/or removal of the inner ring 6110.

Returning to FIG. 6A, the outer ring 6120 is proximal the funnel section 6140. In the illustrated embodiment, the outer ring 6120 has a substantially circular footprint. As further discussed herein, the outer ring 6120 can be sized and configured to sealingly couple to a cap or other access device

thereon. In some embodiments, one or more suture points 6160 can be disposed on the retractor 6110 adjacent the outer ring 6120.

With reference to FIG. 6B, a top view of retractor 6100 is illustrated. In the illustrated embodiment, outer ring 6120 has a generally circular profile. Additionally, in the illustrated embodiment, two suture points 6160 are generally diametrically opposed relative to the generally circular profile of the outer ring 6120. In other embodiments, the retractor can include more or fewer than two suture points disposed of various locations relative to the outer ring 6120.

With continued reference to FIG. 6B, the tubular body 6130 has a generally circular profile defining a generally cylindrical passage 6150. The generally cylindrical passage 6150 is desirably large enough to accommodate more than one laparoscopic instrument there through such that a single natural orifice access device can be used to provide access for multiple surgical instruments in a body cavity. Moreover, generally cylindrical passage 6150 is desirably large enough such that multiple surgical instruments positioned there through can be translated or pivoted relative to one another, allowing a surgeon to manipulate the instruments as desired during a surgical procedure. The generally cylindrical passage extends between a proximal end 6152 of the retractor 6100 adjacent the outer ring 6120 to a distal end 6154 of the retractor 6100 adjacent the inner ring 6110 (FIG. 6A).

With continued reference to FIG. 6B, in the illustrated embodiment, the funnel segment 6140 provides a diametric reduction between the relatively large diameter of the outer ring 6120, which is sized and configured to be removably coupled to an access device such as a cap, and the relatively smaller diameter of the passage 6150, which is sized to fit within a natural orifice with minimal distention of the orifice. The funnel segment 6140 has an inner surface 6142 which can provide a bearing surface for an obturator used to advance to the retractor 6100 into a body cavity. In some embodiments, the funnel segment 6140 can have a substantially linear taper between the relatively large diameter and the relatively smaller diameter such that the inner surface 6142 is a frusto-conical segment. In other embodiments, the funnel segment 6140 can have a curved profile between the relatively large diameter and the relatively smaller diameter.

In some embodiments, a natural orifice access system can include a retractor 6100 and an optional obturator 6400 (FIG. 6G-6H). The obturator can have a proximal bearing surface 6410 sized and configured to bear against the inner surface 6142 of the funnel segment 6140 and a distal dilation surface 6420 sized and configured to expand a natural orifice for passage of the retractor 6100. Thus, during insertion of the retractor 6100 into a natural orifice, the dilation surface 6420 expands a pathway to a surgical site in a body cavity while the obturator bears on the inner surface 6142 of the funnel segment 6140 to advance the retractor 6100 into position in the surgical site. Furthermore, in some embodiments, the obturator can have a handle 6430 at a proximal end thereof adapted to facilitate selective twisting or rotation of the obturator about a longitudinal axis thereof during insertion.

It can be desirable that the outer ring 6120 is relatively stiff compared with the relatively flexible tubular body 6130 of the retractor 6100 so that the outer ring 6120 can sealingly engage an access device such as a cap. With reference to FIG. 6C, a perspective view of the retractor is illustrated with a partial cutaway of the outer ring 6120. In the illustrated embodiment, the outer ring 6120 includes an annular groove 6122 formed therein in which a reinforcing member 6124 is disposed. In some embodiments, the reinforcing member 6124 can comprise a metallic member such as a wire formed into a ring

shape. For example, in some embodiments the reinforcing member **6124** can comprise a stainless steel ring positioned within the groove **6122** during manufacture of the retractor **6100**. In other embodiments, the reinforcing member **6124** can comprise an injectable nonmetallic member. For example, in some embodiments, a glass filled polymer or polycarbonate material can be injected into the groove **6122** during manufacture of the retractor **6100**.

While the illustrated embodiments of retractor **6100** include a reinforcing member to enhance the rigidity of the outer ring **6120**, in other embodiments, the retractor **6100** can be formed in a multiple-shot molding process. For example, in some embodiments, an inner segment of the retractor defined by the tubular body **6130** and the inner ring **6110** is formed in one molding operation from a flexible material, and an outer segment of the retractor **6100** defined by the funnel segment **6140** and the outer ring **6120** is formed in another molding operation from a relatively rigid material such as a polycarbonate material or other suitable material. One embodiment of retractor **7100** formed in a multiple-shot molding process is illustrated in FIGS. **6D-F**, **7B**, **8D**, and **9B**.

With continued reference to FIG. **6C**, the illustrated embodiment includes a continuous generally annular groove. In other embodiments, a plurality of noncontiguous recesses can each receive one of a plurality of reinforcing members. Moreover, in some embodiments, the outer ring can include two or more concentric generally annular grooves, which each receive a corresponding reinforcing member.

With reference to FIG. **7A**, a cross-sectional view of a natural orifice access device including a retractor **6100** and a removable cap **6200** is shown. In the illustrated embodiment, the tubular body **6130** is formed of a flexible material having a predetermined fixed length **L**, inner diameter **D**, and wall thickness **T**. The fixed length **L**, inner diameter **D**, and wall thickness **T** are selected to accommodate the anatomy of a natural orifice, such as the anal orifice of a majority of patients. It is contemplated that the retractor **6100** can be scaled to different sizes for patients of different ages. Furthermore, in some embodiments, it is contemplated that the retractor can include a telescopic tubular body such that the tubular body can be selectively positioned at a variety of lengths depending on patient anatomy and the location of the surgical site within the body cavity. Desirably, the wall thickness **T** and material of the tubular body **6130** are selected such that the tubular body **6130** is resilient enough to maintain the passage **6150** there through when positioned in the natural orifice. Moreover, desirably, the inner diameter, **D** is sufficiently large to accommodate multiple surgical instruments. For example, in embodiments of the retractor **6100** adapted for use in a TEMS procedure, the inner diameter **D** and thickness **T** can be sized such that an outer diameter of the retractor can be between approximately 30 mm and 70 mm, desirably between approximately 35 mm and 50 mm, and in one embodiment approximately 40 mm. Additionally, desirably, the fixed length **L** is sufficiently long such that the inner ring **6110** can be positioned at a surgical site within a body cavity and the outer ring **6120** can be positioned outside the natural orifice. In some embodiments, the fixed length **L** is of a length such that the device has an overall length between the proximal end **6152** and the distal end **6154** of between approximately 10 mm and approximately 100 mm, desirably between approximately 20 mm and 80 mm, more desirably between approximately 30 mm and 60 mm, and in one embodiment, approximately 40 mm.

With continued reference to FIG. **7A**, in some embodiments, the annular groove **6122** can be open to an inner surface of the outer ring **6120**. Thus, the retractor **6100** can be

formed of a flexible material in a single molding operation with the annular groove **6122** having an opening, and the reinforcing member **6124** can be subsequently inserted into the upper groove **6122**.

With continued reference to FIG. **7A**, in some embodiments, the retractor **6100** can include a flexion region between the tubular body **6130** and the inner ring **6110**, such as an undercut **6170**. Advantageously, the flexion region can allow the inner ring **6110** to flex or rotate relative to the tubular body **6130** during insertion such that the inner ring **6110** presents a relatively small outer diameter in an insertion configuration and a relatively larger outer diameter in an undisturbed configuration.

In other embodiments, shown in FIG. **7G**, the inner ring can comprise an inflatable member **6132** such as an annular balloon coupled to a gas or fluid source that can be selectively inflated and deflated between a deflated, relatively small diameter state for insertion and removal, and an inflated, relatively high diameter state for retention in a body cavity. An inflation port **6134**, for example a check valve, affixed to the funnel portion **6140** of the retractor, is connected to the inflatable member **6132** through a channel **6136** within the wall of the tubular body **6130**. Fluid or gas introduced through the inflation port flows through the channel into the inflatable member to thereby inflate the member.

The channel **6136** runs through the tubular body, generally parallel to the longitudinal axis of the tubular body, with a proximal opening interacting with the inflation port **6134** and a distal opening **6139** into outer surface of the tubular body at the inflatable member. In one aspect, the inflation port **6134** may include a normally closed check valve having a spring-loaded plunger. In a further aspect, the check valve may include a Luer lock. It is contemplated that other inflation ports that are well known in the art may be used.

In this embodiment, the tubular body **6130** is preferably comprised of a relatively rigid material, such as a polycarbonate. The tubular body has an inflatable member at the distal end that may be created by heat shrinking polyolefin tubing around the outside of the tubular body. The distal end of the body/tubing assembly is then heated for approximately 30 to 40 seconds, and then placed inside a mold and injected with air to give the inflatable member an annular balloon shape as seen in FIG. **7H**, or any other desired shape, depending on the configuration of the mold. The inflatable member **6132** should have sufficient impermeability properties to substantially prevent inflation gas or fluid from permeating through a wall of the inflatable member.

In one embodiment, the inflatable member **6132** may include a substantially toroid shape upon inflation. In another embodiment, the inflatable member may include a disc shape upon inflation. In another embodiment, the inflatable member **6132** may be a fluted balloon. Other shapes suitable for particular natural orifices will be appreciated by one skilled in the art.

In use, the inflatable member may be inflated after the retractor is disposed within the natural orifice by inserting a syringe into the valve **6134** located at the proximal end **6138** of the channel within the tubular body (see FIG. **7I**). As shown in FIGS. **7J** and **7K**, the port leads into the channel **6136**, which allows the fluid or gas from the syringe to travel to the inflatable member **6132**. In this embodiment, the optional obturator **6400** may be modified with an indent **6139** to provide clearance for the inflation port, as shown in FIG. **7L**.

With reference to FIG. **8A**, a side view of a natural orifice access device having a cap **6200** removably coupled to a retractor **6100** is illustrated. In the illustrated embodiment, the cap **6200** comprises a sealable access surface **6210** such as

a gel pad surface as described in further detail herein. In certain embodiments, the cap 6200 can also comprise at least one gas or fluid port 6220, 6230. In the illustrated embodiment, the cap 6200 comprises two gas or fluid ports 6220, 6230, such that one port can be used for gas insufflation and the other port can be used for ventilation for example when electrosurgery is performed through the access device. In certain embodiments, at least one of the gas or fluid ports 6220, 6230 comprises a valve such as a stopcock valve to selectively control the flow of fluid there through.

With reference to FIG. 8B, a top view of the natural orifice access device is illustrated. The sealable access surface 6210 can be encircled by and restrained by an annular frame 6240 such as a split ring having a clamp 6250. The clamp 6250 can be movable between an open configuration in which the cap 6200 is selectively removable from the retractor 6100 and a clamped configuration in which the cap 6200 can be secured to the retractor 6100. For example, the annular frame 6240 can be positioned peripherally around the outer ring 6120 with the clamp 6250 in the open configuration and the clamp moved to the clamped configuration to sealingly fix the cap 6200 to the retractor 6100. Accordingly, the cap 6200 can be easily removed during a surgical procedure to facilitate removal of excised tissue from a surgical site through the retractor 6100.

With reference to FIG. 8C, a perspective view of the natural orifice access device is illustrated. In the illustrated embodiment, the clamp 6250 can have a distal flange 6252 positioned to interface with the outer ring 6120 of the retractor when the clamp is in the clamped configuration. As illustrated, the clamp 6250 engages a distal surface of the outer ring 6120 of the retractor 6100. In some embodiments, the annular frame 6240 can further comprise at least one distal flange sized and positioned to interface with a retractor. In the illustrated embodiment, the annular frame 6240 comprises a distal flange 6260 positioned to engage a distal surface of the outer ring 6120 of the retractor. As illustrated, the flange 6260 is generally diametrically opposed to the distal flange of the clamp 6250. In other embodiments, the annular frame 6240 can include more than one distal flange positioned substantially equally spaced about the periphery of the annular frame 6240 or spaced irregularly about the periphery of the annular frame.

With reference to FIG. 9A, another embodiment of natural orifice access device is illustrated with a cap 6300 removably coupled to a retractor 6100 such as that described above with respect to FIGS. 6A-6C, 7A, 8A-8C, and 9A. In the illustrated embodiment, the cap 6300 includes multiple trocar access devices 6310 positioned through an access surface 6320 thereof. Advantageously, the multiple trocar access devices 6310 allow for easy placement and manipulation of multiple laparoscopic instruments in a surgical site through a single natural orifice.

In some embodiments, the inner ring 6110 and the outer ring 6120 independently have different footprint shapes and/or footprint diameters. For example, in the embodiment illustrated in the embodiment of retractor 7100 illustrated in FIGS. 6D-F, 7B, 8D, and 9B, the inner ring 7110 can be substantially flush with the tubular body 7130 while the outer ring 7120 can be an annular member having a generally circular cross-section. An inner ring 6110 with a larger diameter permits a greater retraction force, but is more difficult to insert and remove from a body cavity.

With reference to FIGS. 6D-6F, in some embodiments, a natural orifice access port or retractor 7100 can be adapted for use in a transanal endoscopic microsurgery (TEMS) procedure. The retractor 7100 comprises an inner or distal ring

7110, an outer or proximal ring 7120, a tubular body 7130, and a funnel segment 7140 extending between and coupling the inner ring 7110 and the outer ring 7120. The tubular body 7130 comprises a relatively flexible material such as a KRA-TON® material or a silicone rubber material, which is substantially cylindrical in the illustrated embodiment. In other embodiments, the tubular body 7130 has another shape, for example, an oval cross section. Some embodiments of the tubular body 7130 comprise one or more coatings that provide additional functionality, for example, an anti-microbial coating.

In the illustrated embodiment, the inner ring 7110 is substantially flush with a distal end of the tubular body 7130 such that the retractor 7100 has a generally tubular configuration extending distally of the funnel segment 7140 to the distal end. Embodiments of the inner ring 7110 are sufficiently flexible and compliant to be compressed and/or deformed for insertion into a body orifice such as a patient's anus during a transanal surgical procedure. When subsequently released within an associated body cavity, the inner ring 7110 substantially returns to its original shape or footprint. In some embodiments, the inner ring 7110 assumes a substantially circular shape substantially flush with the generally cylindrical tubular body 7130 in a relaxed state, for example, when released within a body cavity. In other embodiments, the inner ring 7110 has another shape in the relaxed state, for example, an oval. The inner ring 7110 assumes a different shape when compressed for insertion through an incision or body orifice, for example, a substantially oval shape, a generally linear shape, a tear-drop shape, or another suitable shape. In other embodiments, the inner ring 7110 is substantially rigid, that is, non-compliant under the ordinary conditions under which it is used.

With continued reference to FIGS. 6D-6F, in some embodiments, the inner ring 7110 can be shaped and configured to facilitate insertion through a natural orifice. For example, in the illustrated embodiment, the inner ring 7110 can include a radiused edge to facilitate atraumatic entry through a natural orifice. In other embodiments, the inner ring 7110 can include a beveled edge to facilitate entry through a natural orifice. Furthermore, in the illustrated embodiment, the inner ring 7110 can be formed at an angle transverse to a longitudinal axis defined by the tubular body 7130. Advantageously, such an angled inner ring 7110 can facilitate insertion of the retractor 7100 through a natural orifice. In other embodiments, the inner ring 7110 can be substantially perpendicular to the longitudinal axis defined by the tubular body.

With continued reference to FIGS. 6D-6F, the outer ring 7120 is proximal the funnel section 7140. In the illustrated embodiment, the outer ring 7120 has a substantially circular footprint. As further discussed herein, the outer ring 7120 can be sized and configured to sealingly couple to a cap or other access device thereon. In some embodiments, as discussed above with reference to the embodiments of FIGS. 6A-6C, one or more suture points can be disposed on the retractor 7100 adjacent the outer ring 7120.

With continued reference to FIGS. 6D-6F, the tubular body 7130 can have a generally circular profile defining a generally cylindrical passage 7150. The generally cylindrical passage 7150 is desirably large enough to accommodate more than one laparoscopic instrument there through such that a single natural orifice access device can be used to provide access for multiple surgical instruments in a body cavity. Moreover, generally cylindrical passage 7150 is desirably large enough such that multiple surgical instruments positioned there through can be translated or pivoted relative to one another,

allowing a surgeon to manipulate the instruments as desired during a surgical procedure. The generally cylindrical passage extends between a proximal end **7152** of the retractor **7100** adjacent the outer ring **7120** to a distal end **7154** of the retractor **7100** adjacent the inner ring **7110** (FIG. 6D).

With reference to FIG. 6D, in the illustrated embodiment, the funnel segment **7140** provides a diametric reduction between the relatively large diameter of the outer ring **7120**, which is sized and configured to be removably coupled to an access device such as a cap, and the relatively smaller diameter of the passage **7150**, which is sized to fit within a natural orifice with minimal distention of the orifice. The funnel segment **7140** has an inner surface **7142** which can provide a bearing surface for an obturator used to advance to the retractor **7100** into a body cavity. In some embodiments, the funnel segment **7140** can have a substantially linear taper between the relatively large diameter and the relatively smaller diameter such that the inner surface **7142** is a frusto-conical segment. In other embodiments, the funnel segment **7140** can have a curved profile between the relatively large diameter and the relatively smaller diameter.

In some embodiments, a natural orifice access system can include a retractor **7100** and an optional obturator, such as described above with reference to FIG. 6G. The obturator can have a proximal bearing surface **6410** sized and configured to bear against the inner surface **7142** of the funnel segment **7140** and a distal dilation surface **6420** sized and configured to expand a natural orifice for passage of the retractor **7100**. Thus, during insertion of the retractor **7100** into a natural orifice, the dilation surface expands a pathway to a surgical site in a body cavity while the obturator bears on the inner surface **7142** of the funnel segment **7140** to advance the retractor **7100** into position in the surgical site. Furthermore, in some embodiments, the obturator can have a handle **6430** at a proximal end thereof adapted to facilitate selective twisting or rotation of the obturator about a longitudinal axis thereof during insertion.

In an alternative embodiment, shown in FIG. 6I, the obturator **6405** includes a straight shaft piece **6425** between the distal dilation surface **6420** and the proximal bearing surface **6410** that facilitates dilation of the natural orifice prior to inserting the retractor. It can then be combined with the retractor **7100** to help ease insertion, as shown in FIG. 6J.

With reference to FIG. 7B, it can be desirable that the outer ring **7120** is relatively stiff compared with the relatively flexible tubular body **7130** of the retractor **7100** so that the outer ring **7120** can sealingly engage an access device such as a cap. In the illustrated embodiment, the retractor **7100** is formed in a multiple-shot molding process. For example, in the illustrated embodiment, an inner segment of the retractor **7100** defined by the tubular body **7130** and the inner ring **7110** is formed in one molding operation from a flexible material, and an outer segment of the retractor **7100** defined by the funnel segment **7140** and the outer ring **7120** is formed in another molding operation from a relatively rigid material such as a polycarbonate material or other suitable material.

In other embodiments, a multiple-shot molding process can be varied such that the resulting inner and outer segments are different from those of the illustrated embodiment. For example, in certain embodiments, the inner segment can include the tubular body **7130**, the inner ring **7110**, and a portion of the funnel segment **7140**, while the outer segment can include a portion of the funnel segment **7140** and the outer ring **7120**. In certain other embodiments, the inner segment can include the inner ring **7110** and a portion of the tubular

body **7130**, while the outer segment can include a portion of the tubular body **7130**, the funnel segment **7140**, and the outer ring **7120**.

With reference to FIGS. 6D and 7B, a retractor **7100** formed in a multiple-shot molding process can include one or more retention members **7160** on the inner segment and the outer segment to maintain the position of the inner segment relative to the outer segment. For example, in some embodiments, a distal end of the outer segment can include one or more protrusions **7162** extending radially outwardly from the funnel segment **7140** and one or more recesses **7164** recessed radially inwardly from the funnel segment **7140** at an interface region of the inner segment and the outer segment of the retractor **7100**. In the illustrated embodiment, the distal end of the outer segment includes a plurality of protrusions **7162** alternating with a plurality of recesses **7164** there between. Moreover, in some embodiments, the outer segment can include an annular groove **7170** formed in the funnel segment **7140** at an interface region of the inner segment and the outer segment of the retractor **7100**. The inner segment of the retractor **7100** can include an annular member **7166** disposed within and matingly engaging the groove **7170** to maintain the position of the inner segment relative to the outer segment.

With reference to FIG. 7B, a cross-sectional view of retractor **7100** is shown. In the illustrated embodiment, the tubular body **7130** is formed of a flexible material having a predetermined fixed length **L2**, inner diameter **D2**, and wall thickness **T2**. The fixed length **L2**, inner diameter **D2**, and wall thickness **T2** are selected to accommodate the anatomy of a natural orifice, such as the anal orifice of a majority of patients. It is contemplated that the retractor **7100** can be scaled to different sizes for patients of different ages. Furthermore, in some embodiments, it is contemplated that the retractor can include a telescopic tubular body such that the tubular body can be selectively positioned at a variety of lengths depending on patient anatomy and the location of the surgical site within the body cavity. Desirably, the wall thickness **T2** and material of the tubular body **7130** are selected such that the tubular body **7130** is resilient enough to maintain the passage **7150** there through when positioned in the natural orifice. Moreover, desirably, the inner diameter, **D2** is sufficiently large to accommodate multiple surgical instruments. For example, in embodiments of the retractor **7100** adapted for use in a transanal surgical procedure, the inner diameter **D2** and thickness **T2** can be sized such that an outer diameter of the retractor can be between approximately 30 mm and 70 mm, desirably between approximately 35 mm and 50 mm, and in one embodiment approximately 40 mm. Additionally, desirably, the fixed length **L2** is sufficiently long such that the inner ring **7110** can be positioned at a surgical site within a body cavity and the outer ring **7120** can be positioned outside the natural orifice. In some embodiments, the fixed length **L2** is of a length such that the device has an overall length between the proximal end **7152** and the distal end **7154** of between approximately 100 mm and approximately 200 mm, desirably between approximately 120 mm and 180 mm, more desirably between approximately 140 mm and 160 mm, and in one embodiment, approximately 150 mm.

With reference to FIG. 8D, a perspective view of a natural orifice access device having a cap **6200** substantially similar to that described with respect to FIGS. 8A-8C removably coupled to a retractor **7100** is illustrated. In the illustrated embodiment, the cap **6200** comprises a sealable access surface **6210** such as a gel pad surface as described in further detail herein. In certain embodiments, the cap **6200** can also comprise at least one gas or fluid port **6220**, **6230**. In the illustrated embodiment, the cap **6200** comprises two gas or

fluid ports **6220**, **6230**, such that one port can be used for gas insufflation and the other port can be used for ventilation for example when electrosurgery is performed through the access device. In certain embodiments, at least one of the gas or fluid ports **6220**, **6230** comprises a valve such as a stopcock valve to selectively control the flow of fluid there through.

With continued reference to FIG. 8D, a top view of the natural orifice access device is illustrated. The sealable access surface **6210** can be encircled by and restrained by an annular frame **6240** such as a split ring having a clamp **6250**. The clamp **6250** can be movable between an open configuration in which the cap **6200** is selectively removable from the retractor **7100** and a clamped configuration in which the cap **6200** can be secured to the retractor **7100**. For example, the annular frame **6240** can be positioned peripherally around the outer ring **7120** with the clamp **6250** in the open configuration and the clamp moved to the clamped configuration to sealingly fix the cap **6200** to the retractor **7100**. Accordingly, the cap **6200** can be easily removed during a surgical procedure to facilitate removal of excised tissue from a surgical site through the retractor **7100**.

With reference to FIG. 9B, another embodiment of natural orifice access device is illustrated can include a cap **6300** substantially similar to that described above with reference to FIG. 9A removably coupled to a retractor **7100** such as that described above with respect to FIGS. 6D-F, 7B, and 8D. The cap **6300** can include multiple trocar access devices **6310** positioned through an access surface **6320** thereof. Advantageously, the multiple trocar access devices **6310** allow for easy placement and manipulation of multiple laparoscopic instruments in a surgical site through a single natural orifice.

As discussed herein, the retractors shown in FIGS. 7A and 7B can include a telescopic tubular body such that the tubular body can be selectively positioned at a variety of lengths depending on patient anatomy and the location of the surgical site within the body cavity. In another embodiment, illustrated in FIG. 7C, the tubular body may be formed in sections of varying length that slidably engage and snap lock together to provide a variety of lengths, depending of the number and size of the sections selected and assembled. With reference to FIG. 7C, a perspective view of a retractor **6500** is shown having three sections: an outer ring section **6510**, an inner ring section **6520**, and an intermediate section **6530** disposed between the other two sections. The three sections are held together by a snap lock mechanism **6540**. Each section terminates at the distal end with an annular groove **6550** that slidably engages with the proximal end **6560** of the next section, best shown in the cross section view of FIG. 7D. The snap lock mechanism is shown in cross-section in FIG. 7E. The tubular body of the embodiment shown in FIG. 7C-E is preferably formed from a relatively stiff material, such as a polycarbonate.

Optionally, as shown in FIG. 7C-7F, the tubular body of the retractor can include cut-out portions or windows **6570**, to provide access to regions of the anatomy that would otherwise be obscured by the tubular body while the retractor is in place. Thus, the retractor can be inserted into the body orifice or incision to provide retraction and to protect the lining of the body cavity, and then manipulated to align the window(s) to the sites of interest in the body cavity for access by surgical instruments.

As will be appreciated, such cut-out portions may be provided in retractors having tubular bodies of both rigid and flexible construction, as well as tubular bodies formed as a single piece or in sections. FIG. 7M shows an example of a flexible tubular body of a retractor, both in side view and in perspective view, wherein the tubular body contains perfora-

tions **6580**. The tubular body can be cut or torn at the perforations to vary the length of the tubular body and/or to incorporate cut-out portions into the tubular body. The tubular body of the embodiment shown in FIG. 7M is preferably formed from a relatively flexible material, such as KRA-TON® or PELLETHANE®.

In the illustrated embodiments of FIGS. 9A and 9B, the trocar access devices **6310** have a relatively low profile, that is, protrude minimally above the access surface **6320** and/or below the distal surface of the cap **6300**. Accordingly, the trocar access devices **6310** are shorter than a length of a typical trocar and comprise a seal assembly positioned above the access surface **6320** and a cannula extending through the gel pad of the cap **6300**. The reduced length of the trocar access devices **6310** allows increased angular or pivotal motion for instruments extending there through, and also permits the use of curved and/or angled instruments.

FIG. 9C is an exploded view of an embodiment of a trocar access device **6310** and optional obturator **6600**, which is a component of some embodiments of the access device system. In the illustrated embodiment, the obturator **6600** comprises a pointed, puncture tip **6610**.

The trocar access device **6310** comprises a proximal end, a distal end, and a longitudinal axis. The trocar access device **6310** comprises a cannula **6620** extending along the longitudinal axis. A trocar seal **6630** is disposed at the proximal end of the cannula **6620**, contained within a housing **6640**. A retainer **6650** is disposed at the distal end or tip of the cannula **6620**.

The cannula **6620** comprises a tubular body dimensioned to accommodate an instrument or instruments received there through. In the illustrated embodiment, the cannula **6620** is a substantially cylindrical tube, and extends through the cap **6300** in use. In the illustrated embodiment, the cannula **6620** is comparatively short because the cannula need only traverse the cap **6300** (FIG. 9A-B), which has a known and consistent thickness, rather than a body wall. Accordingly, some embodiments of the cannula **6620** are not more than about 2-times longer, about 1.5-times longer, about 1.2-times longer, or about 1.1-times longer than the thickness of the gel pad. In some embodiments, the cannula **6620** is less than about 20 mm, about 10 mm, or about 5 mm longer than the thickness of the gel pad. In some embodiments, the cannula **6620** is about as long as the gel pad is thick. In other embodiments, the cannula **6620** has a different length, for example, a length typical for a cannula used for traversing a body wall. Shorter length cannula permit increased angular degrees of freedom for instruments passing there through. Embodiments of shorter cannula also accommodate curved instruments. The cannula **6620** comprises any suitable biocompatible material. In some embodiments, the cannula **6620** comprises a flexible material.

The illustrated trocar seal **6630** comprises an instrument or septum seal **6660** and a zero seal **6670**. Optionally, a shield **6680** may be disposed within the instrument seal **6660**. The instrument seal **6660** seals instruments passing there through, thereby maintaining pressurization in a body cavity such as pneumoperitoneum or pneumorectum. The zero seal **6670** provides a seal when no instrument passes through the trocar seal **6630**. The instrument seal **6660** and zero seal **6670** are received in a housing **6640** disposed at the proximal end of the cannula **6620** and secured therein by a seal cover **6690**.

The retainer **6650** is disposed at or near the distal end of the cannula **6620**. In some embodiments, the retainer **6650** and cannula **6630** are integrated, while in other embodiments, the retainer **6650** and cannula **6630** are not integrated. In the illustrated embodiment, the proximal end of the retainer **6650**

comprises a flange **6655** that is generally flat and perpendicular to the longitudinal axis, while the distal end is tapered, narrowing toward the distal end of the cannula **6620**. The flange **6655** reduces the likelihood of accidental or inadvertent removal of the trocar access device **6310** from the cap. Some embodiments of the proximal face of the flange **6655** comprise additional anchoring features, for example, at least one of barbs, spikes, ridges, texturing, and the like, which are configured to penetrate or bite into a distal face of the cap **6300**. In some embodiments, a diameter of the flange **6655** is from about 1.2 to about 2.5 times wider, or from about 1.5 to about 2.0 times wider than an outer diameter of the cannula **6630**. Some embodiments of the trocar access device **6310** are 5-mm trocars, in which the outer diameter of the cannula **6620** is from about 7 mm to about 8 mm.

The tapered end of the retainer **6650** facilitates insertion of the trocar access device **6310** through the cap, either by itself, or when assembled with the obturator **6600** extending there through. For example, in some embodiments, the retainer **6650** is inserted through a preformed opening in the cap **6300**.

In some embodiments in which the retainer **6650** and cannula **6620** are not integrated, that is, are separate components, the retainer **6650** is secured to the cannula **6620** after the cannula **6620** is inserted through the cap. In some embodiments, the cannula **6620** and retainer **6650** are secured mechanically, for example, using latches, screw threads, clips, lock rings, ratchets, and the like. In some embodiments, the cannula **6620** and retainer **6650** are secured adhesively. In some embodiments, the position of the retainer **6650** is adjustable, for example, to accommodate caps of different thicknesses. In some embodiments, the cannula **6620** and/or retainer **6650** is secured to the cap, for example, adhesively.

An embodiment of a procedure for retracting a body orifice is described with reference to the embodiments of the retractor **6100** illustrated in FIGS. 6A-6C, 7A, 8A-8C, and 9A, and the embodiments of retractor **7100** illustrated in FIGS. 6D-6F, 7B, 8D, and 9B, although the procedure is applicable to all of the embodiments of the retractor disclosed herein. In use, the surgical wound retractor **6100**, **7100** is inserted into a body orifice, such as the vagina (FIG. 2), mouth (FIG. 3) or anus (FIG. 4). The inner ring **6110**, **7110** is folded or compressed into an oval or other suitable shape and urged through the incision or body orifice into an associated body cavity. Once the inner ring **6110**, **7110** is fully disposed within the associated body cavity, it is allowed to resume its original, relaxed shape, for example, substantially circular, oval, or other original shape. In some embodiments, the inner ring **6110** is then pulled upward against the inner surface of the body cavity, for example, by pulling the outer ring **6120** upward. An outer surface of the tubular body **6130**, **7130** retracts the natural orifice.

As illustrated in FIG. 5, some embodiments of the access device **5000** comprise a cap, cover, or lid **5500** coupled to the outer ring of the retractor **5100**, which seals the retractor **5100**, for example, for maintaining pressurization within a body cavity such as pneumoperitoneum or pneumorectum. In some embodiments, lid **5500** is removable, for example to provide access into the body cavity. Some embodiments of the lid **5500** comprise a transparent or translucent portion, thereby allowing a user to view into the body cavity without removing the lid **5500**. As will be described below, one embodiment of a lid **5500** is a gel cap. In some embodiments, a cross-sectional shape of the outer ring **6120** (FIG. 6A), **7120** (FIG. 6D) of the retractor is selected to reduce or prevent the lid **5500** from partial and/or incorrect coupling to the outer ring **6110** (FIG. 6A), **7120** (FIG. 6D) of the wound retractor. Such cross-sectional shapes include oval and rectangular, or

any other suitable cross-sectional shape that provides the desired functionality, for example, hexagonal, octagonal, and the like. Additionally, depending on the use and on surgeon preference, in some embodiments, each of the inner ring **6110**, **7110** and outer ring **6120**, **7120** of the wound retractor includes independently variable design configurations. For example, embodiments of the inner ring **6110**, **7110** and/or the outer ring **6120**, **7120** are rigid or flexible, and have footprints, cross-sectional shapes, and/or dimensions dependent on the intended use, for example, circular or oval footprints, diameters dependent on incision or orifice dimensions, or cross-sectional dimensions dependent on retraction force. In some embodiments, the inner ring **6100** may extend radially out from the tubular body **6130** when deployed, stabilizing the retractor within the body orifice (FIG. 7A). In other embodiments, the inner ring **7110** may be flush with the tubular body **7130**, as where, for example, the length L2 of the tubular body is sufficient to stabilize the retractor within the body orifice (FIG. 7B).

FIG. 10A illustrates in perspective an embodiment of a cap or cover **10500**, which is a surgical access device that seals the opening between the body cavity and the area outside the body cavity while providing access into the body cavity from outside the body cavity. More particularly, the illustrated cap **10500** releasably and sealingly couples to the outer ring **6120** (FIG. 6A), **7120** (FIG. 6D) of the wound retractor. The cap **10500** comprises a cap ring **10510** dimensioned and configured for coupling to the outer ring **6120**, **7120** of the wound retractor and a pad **10530** coupled to the cap ring **10510**. Embodiments of the cap **10500** provide an artificial body wall with consistent properties compared with a natural body wall, for example, thickness, compliance, rigidity, uniformity, and the like.

The illustrated cap or cover **10500** is substantially circular. In other embodiments, the gel cap **10500** has another shape or footprint, for example, oval, elliptical, parabolic, square, rectangular, or another suitable curved or polygonal shape. In some embodiments, the outer ring **6120**, **7120** of the retractor and cap ring **10510** of the cap have the same general shape or footprint. In other embodiments, the outer ring **6120**, **7120** of the retractor and cap ring **10501** of the cap have substantially different shapes, for example, a generally circular outer ring **6120**, **7120** and an oval cap ring **10510**. In these embodiments, the outer ring **6120**, **7120** is distorted or reshaped for coupling to the cap ring **10510**, for example, by compressing opposed sides of the outer ring **6120**, **7120**. Non-circular shapes are useful, for example, for procedures in which space is limited. As discussed above, retracting a long, straight incision using an oval or elongated retractor requires less force than a similar procedure using a circular retractor.

In some embodiments, the pad **10530** comprises a gel. In such embodiments, the pad **10530** is referred to as a "gel pad" and the cap **10500** is referred to as a "gel cap". Descriptions of gel pads and gel caps generally apply to embodiments in which the pad **10530** does not comprise gel unless otherwise specified. In some embodiments, the gel pad **10530** does not comprise any preformed access channels there through, for example, for instrument access. Instruments may be inserted directly through the gel pad **10530**, puncturing the gel pad **10530**, and thereby creating access channels or portions in the gel pad **10530**. Each access portion forms an instrument seal in the presence of an instrument inserted there through and a zero seal in the absence of an instrument inserted there through. The gel provides a gas tight seal around a variety of shapes and sizes of instruments inserted there through. Some embodiments of the gel pad **10530** also provide trocar access directly there through, which also provide instrument access

into the body cavity. Embodiments of the gel pad **10530** have a working diameter of from about 40 mm to about 120 mm, which is the diameter of a portion of the gel pad **10530** through which instruments and/or trocars may be inserted. Embodiments of the gel cap **10500** are typically from about 10 mm to 50 mm wider than the working diameter.

Accordingly, embodiments of the gel cap **10500** maintain pressurization within a body cavity such as pneumoperitoneum or pneumorectum during multiple instrument exchanges and substantially prevent unintentional loss of pressurization. Embodiments of the gel cap **10500** also provide substantially continuous access and visibility during surgery. Embodiments of the gel cap **10500** have a small profile for use in procedures with limited surgical space.

In some embodiments, the gel is an ultragel, which is characterized by an ultimate elongation greater than about 1000 percent and a durometer less than about 5 Shore A. Some embodiments of the ultragel comprising KRATON® and mineral oil exhibit an ultimate elongation exceeding about 1500 percent and improved sealing properties, for example, sealing with instruments of a wider size range than other seal materials. In some embodiments, the seals comprising ultragels also form zero seals when the instrument is removed therefrom. Accordingly, in some embodiments of seals comprising ultragels, a single seal is acts as both the instrument seal as well as the zero seal.

Some embodiments of the cap ring **10510** comprise a substantially cylindrical ring comprising a proximal portion, a distal portion, and a longitudinal axis extending from the proximal portion to distal portions. In other embodiments, the cap ring **10510** has another shape or footprint, for example, oval. As best seen in FIG. **10B**, which is a bottom view of a cap ring **10510**, in the illustrated embodiment, the proximal portion of the cap ring **10510** comprises a plurality of apertures **10512** distributed about the periphery thereof. The apertures **10512** extend through a wall **10514** at the proximal portion of the cap ring. In other embodiments, the apertures **10512** are disposed in at least one member extending either longitudinally inward or longitudinally outward from the wall **10514** of the cap ring. The gel pad **10530** is disposed at the proximal portion of the cap ring **10510** in the illustrated embodiment, with portions of the gel pad **10530** extending through the apertures **10512**, thereby creating an interlocking structure between the cap ring **10510** and the gel pad **10530**, mechanically locking the cap ring **10510** and the gel pad **10530** together.

The distal portion of the cap ring **10510** is substantially cylindrical in the illustrated embodiment, and is dimensioned and configured to receive the outer ring **6120** (FIG. **6A**), **7120** (FIG. **6D**) of the wound retractor. The cap ring **10510** comprises a latch mechanism **10516** that removably couples the cap ring **10510** to the outer ring **6120**, **7120**. Those skilled in the art will understand that other mechanisms are also useful for coupling the cap ring **10510** to the outer ring **6120**, **7120** of the wound retractor, for example, protruding lips, levers, clips, latches, tongues, grooves, screw threads, bayonet mounts, screws, friction fittings, compression fitting, snap caps, and the like. In the illustrated embodiment, when the outer ring **6120**, **7120** of the wound retractor is received in the distal portion of the cap ring **10510**, the outer ring **6120**, **7120** of the wound retractor contacts and embeds within a portion of the gel pad **10530** disposed at the distal portion of the cap ring **10510**, thereby displacing a portion of the gel, and forming a seal between the gel pad **10530**, and the outer ring **6120**, **7120** and tubular body **6130**, **7130** of the wound retractor. Thus, the distal portion of the gel pad **10530** is in juxtaposi-

tion with the incision or body orifice. In other embodiments, the cap ring **10510** is permanently coupled or fixed to the outer ring **6120**, **7120**.

The cap ring **10510** in some embodiments comprises a polymer. Examples of suitable polymers include, at least one of polyethylene (PE), low density polyethylene (LDPE), high density polyethylene (HDPE), ultra high molecular weight polyethylene (UHMWPE), polycarbonate, thermoplastic elastomers (DYNAFLEX®, GLS Corp.; KRATON®, Kraton Polymers), polyphenylene oxide (PPO), polystyrene, and the like. The polymer component of the cap ring is fabricated by any suitable method, including injection molding, melt casting, blow molding, and the like.

Some embodiments of a process in which the gel pad **10530** is cast in the cap ring **10510** are include steps performed at temperatures above about 130° C. over several hours, for example, from about three (3) to about four (4) hours. Accordingly, in some of these embodiments, the cap ring **10510** does not deform under these conditions.

Some embodiments of the gel pad **10530** comprise an elastomeric gel. Examples of such gels are described in U.S. patent application Ser. No. 10/381,220, filed Mar. 20, 2003, the disclosure of which is hereby incorporated by reference as if set forth in full herein. Embodiments of the gel are prepared by mixing at least one triblock copolymer with a solvent that dissolves the midblocks of the triblock copolymer. The mixture is typically a slurry. The endblocks typically comprise a thermoplastic material, such as styrene, while the midblocks typically comprise a thermoset elastomer such as, ethylene/butylene, isoprene, or butadiene. Examples of the triblock copolymer include styrene-ethylene/butylene-styrene (SEBS), styrene-isoprene-styrene (SIS), and styrene-butadiene-styrene (SBS). In some embodiments, the solvent is an oil, for example, mineral oil. Upon heating a mixture or slurry of the triblock copolymer, the midblocks dissolve in the mineral oil, thereby forming a network of the insoluble endblocks. The resulting network has enhanced elastomeric properties compared with the parent copolymer. In some embodiments, the triblock copolymer used is KRATON® G1651, which has a styrene to rubber ratio of 33/67. Once formed, the gel is substantially permanent and, by the nature of the endblocks, processable as a thermoplastic elastomer henceforward. The mixture or slurry has a minimum temperature at which it becomes a gel, which is referred to as the minimum gelling temperature (MGT). This temperature typically corresponds to the glass transition temperature of the thermoplastic endblock plus a few degrees. For example, the MGT for a mixture of KRATON® G1651 and mineral oil is about 120° C. When the slurry reaches the MGT and the transformation to a gel state takes place, the gel becomes more transparent, thereby providing a visual endpoint confirming the complete transformation of the slurry to the gel state, whereupon the gel may be cooled. Some embodiments of the gel comprise a diblock copolymer, either instead of or in addition to the triblock copolymer. Embodiments of the diblock copolymer comprise a thermoplastic first endblock, for example, styrene, and a thermoset elastomeric second endblock, for example, ethylene/butylene, isoprene, or butadiene. An example of a suitable diblock copolymer is styrene-ethylene/butylene (SEB).

For a given mass of slurry to form a complete gel, the entire mass of the slurry is heated to or above the MGT and held at or above the MGT for a sufficient time for the end blocks to form a network or matrix of interconnections. The slurry will continue to form a gel at temperatures between the MGT and temperatures at which the components of the slurry/gel begin to decompose and/or oxidize. For example, when the slurry/

gel is heated at temperatures above 250° C., the mineral oil in the slurry/gel will begin to be volatile and oxidize. Oxidizing may cause the gel to turn brown and become oily.

The speed at which a given volume of slurry forms a gel depends on the speed with which the entire mass of slurry reaches the MGT. Also, at temperatures higher than the MGT, the end block networks distribute and form more rapidly, thereby speeding the gel formation.

The various base gel formulas may also be mixed or alloyed with one another to provide gels with a variety of intermediate properties. For example, KRATON® G1701X is a mixture of seventy percent (70%) SEB and thirty percent (30%) SEBS, with an overall styrene to rubber ratio of 28/72. Those skilled in the art will appreciate that an almost unlimited number of combinations, alloys, and styrene to rubber ratios can be formulated, each providing and embodiment exhibiting one or more advantages, for example, low durometer, high elongation, and good tear strength.

Some embodiments of the gel material further comprise a polymer that, with a foaming agent, improves the sealing properties of the gel, for example, silicone, soft urethanes, and even harder plastics. Examples of suitable silicones include those used for electronic encapsulation. Examples of suitable harder plastics include polyvinylchloride (PVC), isoprene, KRATON® neat, and other KRATON®/oil mixtures. In the KRATON®/oil mixture, suitable oils include vegetable oils, petroleum oils, and silicone oils, as well as mineral oil.

Some embodiments of the gel comprise one or more additives that provide one or more desirable properties, for example, at least one of enhanced lubricity, improved appearance, and wound protection. Additives are incorporated directly into the gel and/or applied as a surface treatment. In some embodiments, other compounds are added to the gel to modify its physical properties and/or to assist in subsequent modification of the surface by providing bonding sites and/or surface charges. Additionally, oil-based colorants are added to the slurry to create gels of different colors in some embodiments.

Some embodiments of the gel pad **10530** comprise a layer of polyethylene on at least one surface. Polyethylene is dissolved in mineral oil and the solution applied to one or more surfaces of the gel pad **10530**. The mineral oil does not evaporate, but instead, absorbs into the gel pad over time, leaving behind the polyethylene as a layer on the surface of the gel pad.

In some embodiments, the triblock copolymer/solvent mixture/slurry used to manufacture the gel pad **10530** comprises about ninety percent (90%) by weight of mineral oil and about ten percent (10%) by weight of KRATON® G1651. From a thermodynamic standpoint, this mixture behaves similarly to mineral oil. Because mineral oil has a relatively high heat capacity, transforming 0.45 kg (1 pound) of the slurry into a homogenous gel at about 130° C. may take from about three (3) to about four (4) hours. Once formed, the gel can be cooled as quickly as practicable with no apparent deleterious effects on the gel. In some embodiments, the gel is cooled by cold-water immersion. In other embodiments, the gel is air-cooled. Those skilled in the art will recognize that other cooling techniques are used in other embodiments.

Certain properties of the KRATON®/oil gel will vary with the weight ratio of the components. In general, a higher proportion of mineral oil results in a softer gel, while a higher proportion of KRATON® results in a firmer gel. A too-soft gel exhibits excessive tenting or doming of the gel cap **10500** during surgery when a patient's body cavity is insufflated. Some embodiments of gels that are too soft also do provide an adequate instrument seal and/or zero seal. The gel should be

sufficiently soft to provide an adequate seal both in the presence of an instrument and in the absence of an instrument, however.

On prolonged or extended sitting or standing, the copolymer, such as KRATON®, and the solvent, such as mineral oil, in the slurry may separate. The slurry may be mixed to greater homogeneity, for example, with a high shear mixer. Mixing the slurry may introduce or add air to the slurry, however. To remove air from the slurry, the slurry may be degassed. In some embodiments, the slurry is degassed under a vacuum, for example, within a vacuum chamber. In some embodiments, the applied vacuum is about 0.79 meters (about 29.9 inches) of mercury, or about one (1) atmosphere. Optionally, stirring or mixing the slurry under vacuum facilitates removal of the air. During degassing under vacuum, the slurry typically expands, then bubbles, and then reduces in volume. The vacuum is typically discontinued when the bubbling substantially ceases. Degassing the slurry in a vacuum chamber reduces the volume of the slurry by about ten percent (10%). Degassing the slurry also reduces oxidation of the finished gel in some embodiments.

Degassing the slurry tends to result in a firmer gel. A gel made from a degassed slurry comprising about 91.6% by weight of mineral oil and about 8.4% by weight of KRATON® G1651, an eleven-to-one ratio, has about the same firmness as a gel made from a slurry that is not degassed and that comprises about ninety percent (90%) by weight of mineral oil and about ten percent (10%) by weight of KRATON® G1651, a nine-to-one ratio.

Because mineral oil typically has a lower density than KRATON®, the two components will separate after mixing, with the less dense mineral oil rising to the top of the container. This phase separation typically occurs when transforming a static slurry into a gel over several hours. Consequently, the resulting gel is non-homogeneous, with a higher concentration of mineral oil at the top and a lower concentration at the bottom. The speed of separation is a function of the depth or head height of the slurry being heated. Factors relevant to the relative homogeneity of the gel include the mass of slurry, the head height, the temperature at which the gel sets, and the speed at which the energy is transferred to the gel.

The gel pad **10530** or gel cap **10500** are gamma sterilized in some embodiments, which is relatively and/or comparatively simpler to qualify compared with other sterilization process, for example, versus ethylene oxide. Gamma sterilization can cause large bubbles to form in the gel pad, however, which are cosmetic and/or aesthetic issues in the sterilized devices. Because bubbles typically comprise greater than ninety-nine percent (99%) room air, the dissolved air is advantageously removed from the slurry prior to transforming the slurry into a gel. For example, the slurry may be degassed under vacuum, as described above, then gelled by heating. Some bubbles may still form in the gel during gamma sterilization, but typically disappear over a period of from about twenty-four (24) hours to about seventy-two (72) hours. Typically, mineral oil at room temperature has about ten percent (10%) dissolved gas. As discussed above, removing air from the gel makes the gel firmer. This effect is counterbalanced by a softening of the gel by the gamma radiation during gamma sterilization, however.

In some embodiments in which the gel pad **10530** is gamma sterilized, the gel comprises about ninety percent (90%) mineral oil by weight and about ten percent (10%) KRATON® by weight. As stated above, degassing the slurry makes the gel firmer. The counteracting softening by the gamma radiation, however, results in a gel with substantially

the same firmness as a gel comprising about ninety percent (90%) mineral oil by weight and about ten percent (10%) KRATON® by weight that is not degassed and gamma sterilized.

In some embodiments, the gel pad **10530** is coupled to, attached to, faulted with, or integrated with the cap ring **10510** to provide a gas-tight seal between the cap ring **10510** and the tubular body **6130** (FIG. 6A), **7130** (FIG. 6D). The gel pad **10530** covers and seals the entire opening in the cap ring **10510**, as well as covering substantially the entire wound or orifice opening. As stated above, the gel pad **10530** provides a gas tight seal around a variety of shapes and sizes of instruments inserted there through.

Embodiments in which a gel pad support structure of the cap ring **10510** comprises a thermoplastic elastomer, for example, DYNAFLEX® or KRATON®, and the gel pad **10530** comprises a similar thermoplastic elastomer, for example, KRATON®, exhibit improved adhesion between the gel pad **10530** and the cap ring **10510**. The polystyrene component of KRATON® in the gel pad **10530** improves adhesion with polyphenylene oxide (PPO), polystyrene, and other similar polymers.

In some embodiments of cap rings **10510** comprising polycarbonate, the polycarbonate component of the cap ring **10510** does not bond with the gel pad **10530** at 130° C., which is a typical manufacturing temperature for a gel pad **10530** comprising KRATON®. Raising the temperature to about 150° C. for a few minutes during casting, however, bonds the gel pad **10530** to the cap ring **10510**. It is believed that heating the gel pad **10530** and cap ring **10510** to a temperature at which both the polystyrene component of the gel and the polycarbonate are simultaneously above their melt points allows bonds to form there between. In other embodiments, the uncured gel and the cap ring **10510** are heated to near or at the glass transition temperature of the polycarbonate in the cap ring **10510**, thereby bonding the gel pad **10530** to the cap ring **10510**.

In some embodiments, the gel comprises mineral oil and the cap ring **10510** comprises a polymer that dissolves in mineral oil under the manufacturing conditions, for example, polyethylene (PE), low density polyethylene (LDPE), high density polyethylene (HDPE), and ultra high molecular weight polyethylene (UHMWPE). Using polyethylene (PE) as an example, PE has a higher molecular weight than mineral oil and dissolves in mineral oil at the temperatures used to cast the gel pad **10530**. As such, as a portion of the PE in the cap ring **10510** dissolves in the mineral oil in the gel pad **10530** at the processing temperatures, for example, above about 130° C., a bond between the PE in the cap ring **10510** and gel pad **10530** is formed.

In an embodiment of a method for manufacturing a gel cap, the cap ring **10510** is placed into a mold that together with the cap ring **10510** includes a negative space in the desired shape of the gel pad and uncured gel is added to the mold. Sufficient uncured gel is then added to the mold to cover and fill the apertures **10512**. The uncured gel flows through, fills, and remains within the apertures. Also, in some embodiments, the mold is filled with sufficient uncured gel to extend into the distal portion of the cap ring **10510**. After the gel cures, the gel in the apertures connects and couples the gel on a first side of each aperture **10512** to the gel on a second side of the aperture, thereby mechanically locking the gel pad **10530** to the cap ring **10510**.

Some embodiments include another method for coupling the gel pad **10530** to the cap ring **10510**, either in addition to or instead of the mechanical interlocking discussed above. Such methods are useful, for example, for coupling sepa-

ately formed gel pads or gel slugs **10530** and cap rings **10510**. Some embodiments use a glue or adhesive to couple the gel pad **10530** to the cap ring **10510**, for example, cyanoacrylate (SUPERGLUE® or KRAZY GLUE®). The glue is believed to bond to either the rubber or the styrene component of the triblock copolymer with a bond is frequently stronger than the gel material itself. Some embodiments use solvent welding in which a solvent dissolves a plastic in the cap ring **10510** and the polystyrene in the gel pad **10530**. The solvent is applied to the gel pad **10530** and cap ring **10510** by any suitable method, for example, by spraying and/or by dipping. In effect, the solvent melts both the plastic of the cap ring **10510** as well as the polystyrene in the gel pad **10530**, thereby forming a bond between the two, which remains after the solvent evaporates.

In an embodiment for manufacturing a gel cap **10500**, the gel pad **10530** is cast into the cap ring **10510** to form the gel cap **10500**. The cap ring **10510** is positioned in or placed into a mold cavity of a casting mold. Embodiments of the mold cavity include support for the annular walls of the cap ring **10510**. Embodiments of the mold comprise a material with sufficient heat dissipation properties, for example, at least one of aluminum, copper, and brass. Those skilled in the art will recognize that other mold materials with lower heat dissipation properties will produce acceptable parts in some embodiments. Furthermore, some embodiments of the mold comprise active cooling elements, for examples, channels through which coolants are pumped.

The mold cavity and cap ring **10510** assembly is then filled with a desired amount of the triblock copolymer/mineral oil slurry such that the slurry contacts the cap ring **10510**. In some embodiments, the slurry is preheated, for example, to about 52° C. (125° F.), which facilitates a complete filling of the mold cavity by the slurry, thereby reducing the probability of voids in the gel. Preheating the slurry to a temperature below the MGT reduces the viscosity of the slurry and allows the slurry to flow more easily. As stated above, some embodiments of the slurry are degassed in a vacuum before casting. In some embodiments, the slurry is also degassed after it is filled in the mold cavity to remove any air that may have been introduced during the filling of the mold cavity, as well as to facilitate flow of the slurry into voids in the mold. The mold, cap ring, and slurry are heated, for example, in an oven, until the slurry reaches a temperature of about 150° C. As stated above, the slurry turns into gel at about 120° C.; however, at about 150° C., the gel bonds to a polycarbonate cap ring **10510**. Depending on the material used in the cap ring **10510**, bonding may take place at a temperature other than about 150° C. In embodiments in which the cap ring **10510** is comprises a material with a lower melting point than the MGT, for example 120° C., the gel pad **10530** is molded separately as a gel slug, which is then bonded to the cap ring **10510** as discussed above.

When the transformation of the slurry into a gel is complete, for example, when the temperature of the gel pad reaches about 150° C., the gel cap **10500** is cooled, for example, by air-cooling, cold-water immersion, or another suitable method. At 150° C. the gel pad **10530** is soft and easily distorted. Distortions in the gel pad **10530** present during cooling would be set after cooling. Accordingly, in some embodiments, the gel cap **10500** is cooled within the mold, thereby reducing the likelihood of distorting the gel pad **10530**. Factors affecting the cooling time include the size and configuration of the mold, the quantity of gel, temperature and quantity of cooling medium, the properties of the cooling medium, and the mold material. As an example, the cooling time for a particular gel cap **10500** may be about two (2) hours

for air cooling and about fifteen (15) minutes for water cooling. Whether cooling with air or water, the final properties of the gel are substantially the same. The gel cap **10500** is typically cooled to about ambient room temperature, but may be cooled to a lower temperature if desired. At about 0° C., the gel hardens, which is useful, for example, in secondary operations such as when coupling separately manufactured gel pads **10530** and cap rings **10510**. The gel cap **10500** may be removed from the mold at any time after the gel has set.

When removed from the mold, the gel pad **10530** typically has a tacky surface. Coating the gel pad **10530** with a powder, such as cornstarch, substantially reduces or eliminates the tackiness of the cured gel pad **10530**.

As stated above, in some embodiments, the gel pad **10530** is molded separately from the cap ring **10510**, and coupled to the cap ring **10510** in a secondary operation, for example, bonding. In some embodiments, the gel pad **10530** is molded as a gel slug with an outer perimeter smaller than the perimeter of the inner cylindrical wall of the cap ring **10510** and a height greater than the height of the cap ring **10510**. Because the gel pad **10530** is molded separate from the cap ring **10510**, the slurry need only be heated to the MGT, for example, about 120° C., to complete the transformation of the slurry into a gel, whereupon the gel becomes substantially transparent. As discussed above, the gel slug may be cooled, for example, to about 0° C., then placed within the inner cylindrical wall of the cap ring **10510**.

In some embodiments, the gel slug is coupled to the cap ring **10510** through compression molding, in which the gel slug is compressed longitudinally, thereby expanding the outer perimeter of the gel slug and compressing the gel slug against the inner cylindrical wall of the cap ring **10510**. The compressed gel slug and cap ring **10510** are then heated to a sufficient temperature for the polystyrene in the gel and the polymer of the cap ring **10510** to form bonds there between. Molding the gel slug separately from the cap ring **10510** followed by heat bonding the gel slug to the cap ring is especially useful in embodiments in which the cap ring **10510** comprises a material with a melting temperature lower than the MGT of the gel. In such situations, the gel slug can be molded separately and heat bonded to the cap ring **10510** without melting the cap ring **10510**.

An embodiment of a method for retracting an incision or body orifice using the retractor **6100**, **7100** is discussed in detail above. The method results in the outer ring **6120**, **7120** of the retractor substantially in contact with the exterior surface of the body wall. The gel cap **10510** is then coupled to the outer ring **6120**, **7120** of the retractor, thereby sealing the opening between the body cavity and the area outside the body cavity and allowing the surgeon to insufflate the body cavity.

As discussed above, embodiments of the gel cap **10500** comprise no preformed access channels in the gel pad **10530**. In use, instruments may be inserted directly through the gel pad **10530**, thereby creating access channels through the gel pad **10530**. Each access channel created in the gel cap forms an instrument seal in the presence of an instrument passing there through because the gel provides a gas tight seal around a variety of shapes and sizes of instruments. When the instrument is removed from the gel pad **10530**, the channel created in the gel pad by the instrument closes to form a zero seal.

Some embodiments of the cap use access devices such as trocars inserted through the gel pad **10530** for instrument access, in particular, where an access channel experiences repeated instrument manipulation, for example, insertion, removal, advancement, retraction, rotation and/or other

manipulation. Each trocar inserted through the gel pad **10530** permits repeated introduction, removal, and/or manipulation of instruments there through.

In some embodiments, the gel cap **10500** initially comprises no access channels, and the surgeon is at liberty to determine the placement of instruments there through. Moreover, the surgeon has unlimited flexibility in the placement and repositioning of ports within the area of the gel cap **10500**, as well as the option of selecting different trocar sizes for different clinical procedures. Being detachable, the gel cap **10500** allows for the removal of large specimens. Once removed, the gel cap **10500** can be re-coupled to the outer ring **6120**, **7120** of the retractor, thereby restoring the seal and allow the surgeon to re-insufflate the body cavity.

Moreover, embodiments of the gel are deformable without losing physical integrity, and while maintaining substantially gas tight instrument seals with any instruments extending there through, as well as gas tight zero seals for any access channels without any instruments extending there through. Accordingly, embodiments of the gel cap **10500** permit both translational or positional, and angular or pivotal "float" or degrees of freedom for the instruments passing through the gel pad **10530**. This float permits instrument motion both relative to the cap ring **10510** as well as relative to other instruments. In contrast, other single or limited port systems do not exhibit one or both translational or angular float for instruments.

FIG. 11A is a top view of an embodiment of a gel cap **11500** comprising a plurality of access ports, seals, or sealing valves disposed in the gel pad. FIG. 11B is a perspective top view of the gel cap **11500** mounted on a retractor. FIG. 11C is a perspective bottom view of the gel cap **11500** mounted on a retractor. The gel cap **11500** comprises a cap ring **11510** and a gel pad **11530**, which are generally similar to the cap ring and gel pad of the embodiment described above.

The gel cap **11500** further comprises a plurality of access ports **11540**, at least a portion of which is disposed within or embedded within the gel pad **11530**. In the illustrated embodiment, the access ports **11540** have a low profile, that is, do not protrude or protrude minimally above the proximal surface of the gel pad **11530** and/or below the distal surface of the gel pad **11530**. Accordingly, the lengths of the access ports **11540** are similar to the thickness of the gel pad **11530**, which is shorter than a length of a typical trocar inserted in the gel pad **11530**, which comprises a seal assembly positioned above the gel pad **10530**, and a cannula extending through the gel pad **11530**. The reduced length of the access port **11540** allows increased angular or pivotal motion for instruments extending there through, and also permits the use of curved and/or angled instruments. In the illustrated embodiment, the access ports **11540** are substantially permanent or non-removable under the conditions under which the gel cap **11500** is used. Trocars can also be inserted through the gel pad **11530** if additional ports are desired.

Each port **11540** comprises longitudinal axis extending from a proximal side to a distal side of the gel pad **11530**, a first seal **11542** disposed at the proximal side of the gel pad **11530**, and a second seal **11544** disposed distal to the first seal **11542**. A sight of each of the ports or seals **11540** has an aperture through the gel pad **11530** and coincides with the longitudinal axis. In the illustrated embodiment, the first seal **11542** forms an instrument seal with an instrument extending there through and the second seal **11544** forms a zero seal in the absence of an instrument extending there through.

In the illustrated embodiment, the first seal **11542** comprises a septum seal. Each septum seal comprises an aperture **11546** there through that is slightly smaller than a cross-

section of the smallest instrument to be inserted there through. The aperture **11546** of the septum seal is substantially aligned with the aperture through the gel pad and the longitudinal axis of the port **11540**. When an instrument is inserted through the aperture **11546** of the septum seal, the aperture **11546** expands and engages the outer surface of the instrument, thereby forming a seal therewith. The septum seal comprises an elastomeric material that biases the aperture against an instrument is inserted there through. Those skilled in the art will understand that other types of instrument seals are used in other embodiments.

In the illustrated embodiment, the second seal **11544** comprises a double-duckbill valve, which functions as a zero-closure seal that provides a zero seal in the absence of an instrument inserted there through. Those skilled in the art will understand that the second seal comprises another type of seal, for example, a duckbill valve, a flap valve, and the like. The double-duckbill valve comprises an elastomeric material. In some embodiments, each of the first seal **11542** and the second seal **11544** independently comprise an elastomeric material, for example, at least one of rubber, synthetic rubber, silicone, ethylene propylene diene monomer (EPDM), ethylene-propylene copolymer (EP rubber), polyisoprene, polybutadiene, polyurethane, styrene-butadiene, ethylene vinyl acetate (EVA), polychloroprene (NEOPRENE®), perfluoroelastomer (KALREZ®), and the like.

Thus, during use, the septum seal provides an instrument seal in the presence of an instrument inserted there through, and the duckbill valve provides a zero seal in the absence of an instrument inserted there through. The illustrated embodiment comprises ports or seals **11540** in the gel pad of different sizes. Each size of port **11540** sealing accommodates a different range of instrument sizes inserted there through. The size of a port is typically given as the diameter of the largest instrument that the port will accommodate, for example, 5 mm, 11 mm, or 12 mm. FIGS. **11D**, **11E**, and **11F** are a perspective top view, a perspective bottom view, and a side view of a thinner instrument **11550a** and a thicker instrument **11550b** inserted through a smaller port **11540a** and a larger port **11540b**, respectively, of the embodiment of the gel cap **11500** illustrated in FIGS. **11A-11C**.

FIG. **11G** is a top perspective view of an embodiment of a gel cap **11500** further comprising a fixed port position, for example, for a camera or a laparoscope. The fixed port **11560** comprises a lock mechanism **11562** that maintaining the position of a camera or laparoscope inserted there through. In some embodiments, one of the ports **11540** further comprises a stopcock and/or gas fitting used as a gas inlet and/or outlet port for insufflating, depressurizing, and/or venting the body cavity of gas. In some embodiments, a gas inlet/outlet port is disposed on the cap ring **11510**.

FIG. **12** is a cutaway perspective view of an embodiment of an access device system **12000** comprising retractor **12100** and a cap or cover **12500**, which are similar to embodiments of retractors and gel caps described above. The retractor **12100** comprises an inner ring **12110**, an outer ring **12120**, and a sleeve **12130** extending between the inner ring **12110** and the outer ring **12120**. In the illustrated embodiment, the cap **12500** is a gel cap comprising a proximal side, a distal side, a cap ring **12510**, and a gel pad **12530**. In the illustrated embodiment, the cap ring **12510** comprises a tubular ring dimensioned to receive the outer ring **12120** of the retractor therewithin. The distal side of the cap ring **12510** comprises an annular slot **12520**, which is sufficiently radially deformable for the outer ring **12120** to reversibly pass there through.

Accordingly, the illustrated embodiment of the cap ring **12510** secures the cap **12500** to the outer ring **12120** with a snap or friction fit.

FIG. **13** is an exploded view of an embodiment of a trocar **13800** and optional obturator **13900**, which is a component of some embodiments of the access device system. In the illustrated embodiment, the obturator **13900** comprises a pointed, puncture tip **13910**. In embodiments in which the trocar **13800** and obturator **13900** are inserted through a gel pad **10530** rather than a body wall, potential damage to underlying tissue by contact with the tip **13910** is reduced because the gel pad **10530** serves as an artificial body wall that is spaced from the underlying tissue as discussed above. In other embodiments, the obturator tip **13910** has another shape, for example, blunt and/or bladeless, which, for example, reduces the likelihood of damage to other components of the access system, for example, a retraction sheath of a retractor.

The trocar **13800** comprises a proximal end, a distal end, and a longitudinal axis. The trocar **13800** comprises a cannula **13810** extending along the longitudinal axis. A trocar seal **13820** is disposed at the proximal end of the cannula **13810**. A retainer **13830** is disposed at the distal end or tip of the cannula **13810**. In the illustrated embodiment, the distal end or tip of the cannula **13810** is not angled. Other embodiments comprise an angled distal end or tip of the cannula **13810**. The illustrated embodiment of the trocar **13800** does not comprise an insufflation gas inlet. Consequently, the trocar **13800** is typically used in procedures in which a body cavity is not insufflated, or in which insufflation is provided through another device. Other embodiments of trocars are disclosed in U.S. patent application Ser. No. 11/677,994, filed Feb. 22, 2007, the disclosure of which is incorporated by reference.

The cannula **13810** comprises an elongate, tubular cannula body **13812** dimensioned to accommodate an instrument or instruments received there through. In the illustrated embodiment, the cannula body **13812** is a substantially cylindrical tube, and extends through the gel pad **10530** in use. In the illustrated embodiment, the cannula body **13812** extends from the proximal end of the cannula **13810** to which the trocar seal **13820** is coupled, and which has a larger outer diameter than the cannula body **13812**.

In some embodiments, the cannula **13810** is comparatively short because the cannula body **13812** need only traverse the gel pad **10530** (FIG. **10A**), which has a known and consistent thickness, rather than a body wall. Accordingly, some embodiments of the cannula body **13812** are not more than about 2-times longer, about 1.5-times longer, about 1.2-times longer, or about 1.1-times longer than the thickness of the gel pad. In some embodiments, the cannula body **13812** is less than about 20 mm, about 10 mm, or about 5 mm longer than the thickness of the gel pad. In some embodiments, the cannula body **13812** is about as long as the gel pad is thick. In other embodiments, the cannula body **13812** has a different length, for example, a length typical for a cannula used for traversing a body wall. Shorter length cannula bodies permit increased angular degrees of freedom for instruments passing there through. Embodiments of shorter cannula bodies also accommodate curved instruments. The cannula **13810** comprises any suitable biocompatible material. In some embodiments, the cannula **13810** comprises a flexible material.

The illustrated trocar seal **13820** comprises an instrument or septum seal **13822** and a zero seal **13824**. The instrument seal **13822** seals instruments passing there through, thereby maintaining pressurization in a body cavity such as pneumoperitoneum or pneumorectum. The zero seal **13824** provides a seal when no instrument passes through the trocar seal **13820**. The instrument seal **13822** and zero seal **13824** are

received in a housing **13826** disposed at the proximal end of the cannula **13810** and secured therein by a seal cover **13828**.

The retainer **13830** is disposed at or near the distal end of the cannula **13810**. In the illustrated embodiment, the distal end of the cannula **13810** is generally perpendicular to the longitudinal axis thereof, or not angled. Other embodiments comprise an angled distal end or tip. In some embodiments, the retainer **13830** and cannula **13810** are integrated, while in other embodiments, the retainer **13830** and cannula **13810** are not integrated. In the illustrated embodiment, the proximal end of the retainer **13830** comprises a flange **13832** that is generally flat and perpendicular to the longitudinal axis, while the distal end is tapered, narrowing toward the distal end of the cannula **13810**. The flange **13832** reduces the likelihood of accidental or inadvertent removal of the trocar **13800** from the gel pad. Some embodiments of the proximal face of the flange **13832** comprise additional anchoring features, for example, at least one of barbs, spikes, ridges, texturing, and the like, which are configured to penetrate or bite into a distal face of the gel pad **10530**. In some embodiments, a diameter of the flange **13832** is from about 1.5 to about 2.5 times wider, or from about 2 to about 2.2 times wider than an outer diameter of the cannula body **13812**. Some embodiments of the trocar **13800** are 5-mm trocars, in which the outer diameter of the cannula body **13812** is from about 7 mm to about 8 mm.

The tapered end of the retainer **13830** facilitates insertion of the trocar **13800** through the gel pad, either by itself, or when assembled with the obturator **13900** extending there through. For example, in some embodiments, the retainer **13830** is inserted through a preformed opening in the gel pad **10530**. Because embodiments of the gel material of the gel pad **10530** have high elongation values, as discussed above, the retainer **13830** is insertable through a relatively small opening in the gel pad **10530**, yet resists inadvertent removal, as discussed above.

In some embodiments in which the retainer **13830** and cannula **13810** are not integrated, that is, are separate components, the retainer **13830** is secured to the cannula **13810** after the cannula **13810** is inserted through the gel pad. In some embodiments, the cannula **13810** and retainer **13830** are secured mechanically, for example, using latches, screw threads, clips, lock rings, ratchets, and the like. In some embodiments, the cannula **13810** and retainer **13830** are secured adhesively. In some embodiments, the position of the retainer **13830** is adjustable, for example, to accommodate gel pads of different thicknesses. In some embodiments, the cannula **13810** and/or retainer **13830** is secured to the gel pad, for example, adhesively.

FIG. **14A** is a side view of another embodiment of a trocar **14800** that is suitable as a component of a single-port surgical access system described above, for example, comprising a gel pad **10530** and retractor. Some embodiments of the access system comprise a plurality of trocars **14800**. The trocar **14800** is generally similar to the trocar **13800** described above, and comprises a cannula **14810**, a trocar seal assembly **14820**, and a retainer **14830**, which are generally similar to the corresponding features described above. The illustrated embodiment of the trocar **14800** further comprises a bolster **14840** and a locking component **14850**. The illustrated embodiment of the cannula **14810** is also referred to as a "fixation cannula" as will become apparent from the discussion below.

In the illustrated embodiment, the bolster **14840** comprises a torus or doughnut. A cannula body **14812** extends through an opening in the bolster **14840**. A diameter of the opening of the bolster **14840** is sufficiently larger than an outer diameter

of the cannula body **14812** to permit free movement along the cannula body **14812**. The illustrated embodiment of the bolster **14840** comprises a deformable material, for example, a polymer resin and/or elastomer, as will be described in greater detail below. Examples of suitable materials include rubber, natural rubber, synthetic rubber, polyisoprene, styrene-butadiene rubber, silicone rubber, ethylene-propylene copolymer, ethylene-propylene-diene monomer rubber, polybutadiene, polychloroprene, polyurethane, and the like. Some embodiments of the bolster **14840** comprise a lubricious layer or coating in an area or region that contacts the cannula **14810**, which facilitates movement along the cannula **14810**.

An outer diameter of some embodiments of the bolster **14840** is from about 0.8 to about 2 times, or from about 1 to about 1.5 times a diameter of a flange **14832** of the retainer **14830**. A thickness of the bolster is from about 3 mm (0.12 inch) to about 10 mm (0.4 inch), or from about 4 mm (0.16 inch) to about 6 mm (0.24 inch). In some embodiments, a distal face **14844** of the bolster is concave, thereby providing additional clamping or fixation force on the gel pad **10530**, as well as conforming to gel pads **10530** with different and/or non-uniform thicknesses. The particular dimensions of the bolster **14830** are selected based on the properties of the bolster material and the gel material, and the dimensions of the cannula body **14812**, the locking component **14850**, and the gel pad **10530**.

The locking component **14850** is disposed on the cannula body **14812** proximal of the retainer **14830**, and comprises a lip **14852** proximal of an enlarged section **14854**. The lip **14852** extends radially from the cannula body **14812** with a diameter greater than the diameter of the opening of the bolster **14840**. The elastomeric material of the bolster **14840** permits the bolster **14840** to be urged over and past the lip **14852**. In the illustrated embodiment, the lip **14852** comprises a ratchet dimensioned to facilitate the bolster **14840** sliding distally and to resist the bolster **14840** from sliding proximally. Also, in the illustrated embodiment, the lip **14852** is a continuous structure encircling the cannula body **14812**. In other embodiments, the lip **14852** comprises a plurality of structures disposed around the cannula body **14812**.

The enlarged section **14854** is generally cylindrical with a diameter that is about the same as or slightly larger than the diameter of the opening in the bolster **14840**, thereby frictionally engaging the bolster **14840** thereto. In the illustrated embodiment, the enlarged section **14854** is longer than a thickness of the bolster **14840**. In the illustrated embodiment, the enlarged section **14854** does not extend to or contact the flange **14832** of the retainer **14830**, thereby not reducing a surface area of a proximal face thereof, and thereby improving the removal resistance thereof. In other embodiments, the enlarged section **14854** extends to the retainer **14830**. Other embodiments do not comprise an enlarged section.

A distance between a distal end of the lip **14852** and a proximal face of the flange **14832** is equal to or slightly less than a sum of a thickness of the bolster **14840** and the gel pad **10530**. In some embodiments, the gel pad is from about 5 mm (about 0.4 inch) to about 30 mm (about 1.2 inch) thick, or from about 13 mm (about 0.5 inch) to about 25 mm (about 1 inch) thick.

The trocar **14800** has at least two configurations: a first or insertion configuration illustrated in FIG. **14A**, and a second or fixation configuration illustrated in FIG. **14B**.

In an embodiment of a method for using the trocar **14800**, the trocar **14800** is placed in the insertion configuration in which the bolster **14840** is first positioned on the cannula body **14812**. The trocar **14800** is placed in the artificial body

wall either before the artificial body wall is coupled to a patient's body and/or after coupling thereto.

In the embodiment illustrated in FIG. 14A, the bolster 14840 is positioned at the proximal end of the cannula body 14812, where the bolster 14840 frictionally engages a distal portion of a cannula bell 14814, which is an enlarged portion at the proximal end of the cannula 14810 to which the seal assembly 14820 couples.

The distal end of the trocar 14800 is positioned on, then the retainer 14830 inserted through an artificial body wall, for example, a gel pad 10530. In some embodiments, an obturator 13900 (FIG. 13) is first inserted through the seal assembly 14820 at the proximal end of the trocar with the tip 13910 extending from the distal end thereof before this step. In other embodiments, an opening is first made in the artificial body wall using another instrument. In other embodiments, the distal end of the trocar 14800 is forced through the artificial body wall, generating an opening in the process.

The trocar 14800 is then converted into the fixation configuration illustrated in FIG. 14B by sliding the bolster 14840 down the cannula body 14812, and over the lip 14852 onto the enlarged section 14852. In the illustrated configuration, the artificial body wall is captured and compressed between the flange 14830 of the retainer and the bolster 14840. The lip 14852 locks the bolster 14840 in place, preventing it from moving proximally, thereby fixing or locking the trocar 14800 to the artificial body wall.

In the fixation configuration, the trocar 14800 fixed relative to a local portion of the artificial body wall to which it is engaged. As discussed above, however, embodiments of artificial body walls exhibit high elongations. Accordingly, the trocar 14800 is translatable and/or pivotable relative to an original position and orientation by deforming the artificial body wall.

In embodiments using an obturator 13910, the obturator is withdrawn. The trocar 14800 serves as an access port for one or more instruments during a surgical procedure.

If desired, the trocar 14800 is removed from the artificial body wall, for example, by first disengaging the bolster 14840 from the locking component 14850, then pulling the retainer 14830 from the artificial body wall. In some embodiments, the trocar 14800 and artificial body wall are not disengaged and are disposed of as a unit. In some embodiments, the bolster 14840 is not disengagable from the locking component 14850.

FIG. 15 is a side view of another embodiment of a retention trocar 15000, which is generally similar to the embodiment illustrated in FIGS. 14A and 14B and described above. The trocar 15000 comprises an elongate, tubular cannula 15810 comprising a proximal end, a distal end, and a cannula body 15812; a seal assembly 15820 coupled to the proximal end of the cannula 15810; a retainer 15830 disposed at the distal end of the cannula 15810; a bolster 14840 through which the cannula body 15812 extends; and a locking component 15850 disposed on the cannula body proximal of the retainer 15830.

In the illustrated embodiment, the locking component 15850 comprises an enlarged section 15854 on which are disposed screw threads 15852. The bolster 15840 comprises matching threads. Consequently, the bolster 15840 is threadably engagable to the locking component 15850. The threading also permits adjusting the relative positions of the bolster 15840 and a flange 15832 of the retainer in the fixation configuration of the trocar 15800, thereby permitting fixation to an artificial body wall with a non-uniform thickness and/or to artificial body walls of different thicknesses.

FIG. 16A is a side view of another embodiment of a trocar 16800. FIG. 16B is a perspective view of an embodiment of a

bolster 16840 usable with the trocar 16800. The combination of the trocar 16800 and bolster 16840 are generally similar to the embodiments of trocars illustrated in FIGS. 14A, 14B, and 15. The trocar 16800 comprises an elongate, tubular fixation cannula 16810 comprising a proximal end, a distal end, and a cannula body 16812; a seal assembly 16820 coupled to the proximal end of the cannula 16810; a retainer 16830 disposed at the distal end of the cannula 16810; and a locking component 16850 disposed on the cannula body proximal of the retainer 16830.

In the illustrated embodiment, the locking component 16850 comprises an enlarged section 16854 comprising a plurality of annular rings 16852 extending radially from the cannula body 16812, which define a plurality of annular slots 16856. In the illustrated embodiment, a proximal edge of each ring 16856 is beveled; however, some embodiments do not comprise a beveled edge.

FIG. 16B illustrates an embodiment of a bolster 16840 in the form of a clip comprising a flattened body 16842 comprising a cut-out 16844 comprising a semicircular portion. The cut-out 16844 is dimensioned to engage the slots 16856. A thickness of the body 16842 at the cut-out 16844 is also dimensioned to engage the slots 16856. The bolster 16840 comprises a grip 16846 extending vertically from the body 16842, which provides a user grip for installing and/or adjusting the bolster 16840. In other embodiments, the cut-out 16844 has another shape, for example, polygonal, rectangular, a portion of a hexagon, and the like.

In use, the retainer 16830 of the trocar is inserted through an artificial body wall as discussed above, and fixed therein by engaging the bolster 16840 in a slot 16856 providing a desired fixation force. The degree of fixation is adjustable by selecting a different slot.

In some embodiments, the bolster cut-out 16844 engages a plurality of slots, thereby providing additional stability in the fixation configuration. Other embodiments comprise a bolster through with the cannula body 16812 extends, similar to the embodiments discussed above. In some of these embodiments, the locking component 16850 serves as a ratchet. The bolster comprises one or more pawls, which are optionally disengagable, thereby enhancing adjustability.

FIG. 17A illustrates a side view of an embodiment of a trocar 17800 comprising a fixation cannula and FIG. 17B is a perspective view of an embodiment of a bolster. The embodiments illustrated in FIGS. 17A and 17B are generally similar to the embodiments of trocars illustrated in FIGS. 14A-16B and described above.

The trocar 17800 comprises an elongate, tubular fixation cannula 17810 comprising a proximal end, a distal end, and a cannula body 17812; a seal assembly 17820 coupled to the proximal end of the cannula 17810; a retainer 17830 disposed on the cannula body 17812; and a locking component 17850 disposed at the distal end of the cannula 17810. The illustrated embodiment of the trocar 17800 is similar to the embodiment illustrated in FIG. 16A with the positions of the retainer 17830 and the locking component 17850 reversed. In the illustrated embodiment, a flange 17832 of the retainer faces distally.

The locking component 17850 comprises an enlarged section 17854 comprising a plurality of annular rings 17852 extending radially from the cannula body 17812, which define a plurality of annular slots 17856.

FIG. 17B illustrates an embodiment of a bolster 17840 in the form of a clip comprising a flattened body 17842 comprising a cut-out 17844 comprising a semicircular portion. The cut-out 17844 is dimensioned to engage slots 17856 in the locking component. A thickness of the body 17842 at the

31

cut-out **17844** is also dimensioned to engage the slots **17856**. The illustrated embodiment of the bolster does not comprise a grip; however, other embodiments comprise a grip.

In some embodiments for using the embodiment of the trocar **17800**, the cannula **17810** is fixed to an artificial body wall before the artificial body wall is coupled to a patient's body. For example, in some embodiments, one or more trocars **17800** are fixed on a gel pad **10530** (FIG. 10A) of a gel cap **10500** before the gel cap **10500** is coupled to a retractor **6100**, **7100** (FIGS. 6A-F).

While certain embodiments have been particularly shown and described with reference to exemplary embodiments thereof, it will be understood by those of ordinary skill in the art that various changes in form and details may be made therein without departing from the spirit and scope thereof as defined by the following claims.

What is claimed is:

1. A surgical access port system adapted for performing laparoscopic surgical procedures at a natural orifice comprising:

an outer ring, wherein the outer ring is configured to be disposed proximate the natural orifice of the patient and substantially surround the orifice;

a tubular body having a proximal end, a distal end, a longitudinal axis and a fixed length and diameter adapted to accommodate the anatomy of the natural orifice, wherein the tubular body defines a generally cylindrical passage large enough to accommodate at least two laparoscopic instruments there through;

a funnel segment extending between and coupling the outer ring and the proximal end of the tubular body, wherein the funnel segment provides a diametric reduction between the relatively large diameter of the outer ring and the relatively smaller diameter of the tubular body, which is sized to fit within a natural orifice with minimal distention of the orifice;

a removable gel cap, wherein the gel cap comprises a gel pad and a cap ring coupled with the gel pad, wherein the cap ring is engagable with the outer ring;

a trocar comprising a tubular cannula body having a proximal end, a distal end, a longitudinal axis extending from the proximal end to the distal end, and a cannula wall defining a cannula lumen, a seal assembly coupled to the proximal end of the cannula body, and a retainer extending from the distal end of the cannula body, wherein the tubular cannula body is disposed through the gel pad at

32

a site selected by the user to capture the gel pad between the retainer and the seal assembly;

an inflation port disposed within the funnel segment;

an inflatable member circumferentially disposed around the distal end of the tubular body; and

a channel connecting the inflatable member to the inflation port;

wherein the inflatable member is configured upon to expand upon inflation circumferentially outward from the distal end of tubular body to engage the wall of the natural orifice and to thereby secure the tubular body within the natural orifice.

2. The surgical access port system of claim 1, wherein the tubular body comprises a substantially flexible material.

3. The surgical access port system of claim 2, wherein the flexible material is selected from the group consisting of a KRATON® material, a PELLETHANE® material and a silicone rubber material.

4. The surgical access port system of claim 1, wherein the tubular body comprises a polycarbonate.

5. The surgical access port system of claim 1, wherein the tubular body comprises one or more coatings.

6. The surgical access port system of claim 1, wherein the coating comprises an anti-microbial coating.

7. The surgical access port system of claim 1, wherein the tubular body comprises two or more interlocking sections.

8. The surgical access port system of claim 1, wherein the tubular body comprises at least one perforation.

9. The surgical access port system of claim 1, wherein the funnel segment comprises an inner surface that can provide a bearing surface for an obturator used to advance to the retractor into a body cavity.

10. The surgical access port system of claim 1, wherein the funnel segment has a substantially linear taper between the relatively large diameter and the relatively smaller diameter.

11. The surgical access port system of claim 1, wherein the funnel segment has a curved profile between the relatively large diameter and the relatively smaller diameter.

12. The surgical access port system of claim 1, further comprising an obturator.

13. The surgical access port system of claim 1, wherein the tubular body is formed from a relatively flexible material and the funnel segment and the outer ring are formed from a relatively rigid material.

14. The surgical access port system of claim 1, wherein the cap comprises at least one gas port.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 9,289,115 B2
APPLICATION NO. : 13/865854
DATED : March 22, 2016
INVENTOR(S) : Kevin K. Dang et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Specification

- Column 1, line 9: Please change "U.S. application" to --U.S. Application--.
- Column 18, line 21: Please change "U.S. patent application" to --U.S. Patent Application--.
- Column 21, line 6: Please change "faulted" to --formed--.
- Column 25, line 27: Please add a --.-- after the word like.
- Column 26, line 31: Please change "U.S. patent application" to --U.S. Patent Application--.

Signed and Sealed this
Twenty-eighth Day of June, 2016



Michelle K. Lee
Director of the United States Patent and Trademark Office

专利名称(译)	自然口腔手术系统		
公开(公告)号	US9289115	公开(公告)日	2016-03-22
申请号	US13/865854	申请日	2013-04-18
[标]申请(专利权)人(译)	党KEVIN ALBRECHT JEREMY BROWN BLAZE HOKE ADAM SAIDUDDIN ADEEB JOHNSON GARY中号 JACOB J		
申请(专利权)人(译)	党 , KEVIN K. ALBRECHT , JEREMY J. BROWN , BLAZE HOKE , ADAM SAIDUDDIN , ADEEB JOHNSON , GARY M. FILEK , JACOB J.		
当前申请(专利权)人(译)	应用医疗资源CORPORATION		
[标]发明人	DANG KEVIN K ALBRECHT JEREMY J BROWN BLAZE HOKE ADAM SAIDUDDIN ADEEB JOHNSON GARY M FILEK JACOB J		
发明人	DANG, KEVIN K. ALBRECHT, JEREMY J. BROWN, BLAZE HOKE, ADAM SAIDUDDIN, ADEEB JOHNSON, GARY M. FILEK, JACOB J.		
IPC分类号	A61B1/32 A61B17/34 A61B17/02 A61B17/00		
CPC分类号	A61B1/32 A61B17/0218 A61B17/0293 A61B17/3421 A61B17/3423 A61B17/3431 A61B2017/00557 A61B2017/345 A61B2017/347 A61B2017/3419 A61B2017/3443 A61B2017/3452 A61B2017/3466 A61B2017/3482 A61B2017/3492 A61B2017/00889 A61B2017/00907 A61B2017/0225 A61B2017/3429 A61B2017/3445 A61B2017/3486		
优先权	61/485321 2011-05-12 US 61/389091 2010-10-01 US		
其他公开文献	US20130245381A1		
外部链接	Espacenet USPTO		
摘要(译)			

描述了包括牵开器的外科进入端口系统的实施例，该牵开器适于联接到帽并且在自然孔口手术中特别有用。牵开器包括外环，其中外环构造靠近患者的自然孔口并且基本上围绕孔口;管状体;在外环和管状体之间延伸并连接的漏斗段，其中漏斗段在外环的相对大直径和管状体的相对较小直径之间提供直径减小，其尺寸适合于自然的孔口膨胀最小的孔口;以及围绕管状主体的远端设置的可充气构件，该可充气构件的尺寸和构造适于在收缩状态下紧密地配合在管状主体周围并且在膨胀状态下抵靠自然孔的壁膨胀，从而稳定和保持孔内的牵开器。

