



US009498245B2

(12) **United States Patent**
Voegelé et al.

(10) **Patent No.:** **US 9,498,245 B2**
(45) **Date of Patent:** **Nov. 22, 2016**

(54) **ULTRASONIC SURGICAL INSTRUMENTS**

(71) Applicant: **Ethicon Endo-Surgery, Inc.**,
Cincinnati, OH (US)

(72) Inventors: **Aaron C. Voegelé**, Loveland, OH (US);
Scott A. Nield, Hamilton, OH (US);
Foster B. Stulen, Mason, OH (US);
Shan Wan, Mason, OH (US)

(73) Assignee: **Ethicon Endo-Surgery, LLC**,
Guaynabo, PR (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 59 days.

(21) Appl. No.: **14/270,722**

(22) Filed: **May 6, 2014**

(65) **Prior Publication Data**

US 2014/0243864 A1 Aug. 28, 2014

Related U.S. Application Data

(63) Continuation of application No. 13/717,084, filed on
Dec. 17, 2012, now Pat. No. 8,754,570, which is a
(Continued)

(51) **Int. Cl.**
H01L 41/09 (2006.01)
A61B 17/32 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61B 17/320068** (2013.01); **A61B 8/4209**
(2013.01); **A61B 8/4494** (2013.01); **A61B**
2017/0023 (2013.01); **A61B 2017/00402**
(2013.01); **A61B 2017/320072** (2013.01);
A61B 2017/320076 (2013.01); **A61B**
2017/320088 (2013.01); **H01L 41/0906**

(2013.01); *Y10T 29/42* (2015.01); *Y10T*
29/49005 (2015.01); *Y10T 29/49155* (2015.01)

(58) **Field of Classification Search**
CPC **A61B 17/320068**; **A61B 2017/00402**
USPC **310/334**; **606/169**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

969,528 A 9/1910 Disbrow
1,570,025 A 1/1926 Young
(Continued)

FOREIGN PATENT DOCUMENTS

AU 2003241752 A1 9/2003
CN 1634601 A 7/2005
(Continued)

OTHER PUBLICATIONS

International Preliminary Report on Patentability for PCT/US2010/
039290, Jan. 4, 2012 (7 pages).


(Continued)

Primary Examiner — J. San Martin

(57) **ABSTRACT**

In one general aspect, various embodiments are directed to an ultrasonic surgical instrument that comprises a transducer configured to produce vibrations along a longitudinal axis at a predetermined frequency. In various embodiments, an ultrasonic blade extends along the longitudinal axis and is coupled to the transducer. In various embodiments, the ultrasonic blade includes a body having a proximal end and a distal end, wherein the distal end is movable relative to the longitudinal axis by the vibrations produced by the transducer.

10 Claims, 39 Drawing Sheets



Related U.S. Application Data

continuation of application No. 12/490,906, filed on
Jun. 24, 2009, now Pat. No. 8,334,635.

(51) **Int. Cl.**

A61B 8/00 (2006.01)
A61B 17/00 (2006.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

1,813,902 A	7/1931	Bovie	4,836,186 A	6/1989	Scholz
2,704,333 A	3/1955	Calosi et al.	4,838,853 A	6/1989	Parisi
2,736,960 A	3/1956	Armstrong	4,844,064 A	7/1989	Thimsen et al.
2,849,788 A	9/1958	Creek	4,850,354 A	7/1989	McGurk-Burleson et al.
2,874,470 A	2/1959	Richards	4,852,578 A	8/1989	Companion et al.
2,990,616 A	7/1961	Balamuth et al.	4,865,159 A	9/1989	Jamison
RE25,033 E	8/1961	Balamuth et al.	4,867,157 A	9/1989	McGurk-Burleson et al.
3,015,961 A	1/1962	Roney	4,878,493 A	11/1989	Pasternak et al.
3,053,124 A	9/1962	Balamuth et al.	4,881,550 A	11/1989	Kothe
3,082,805 A	3/1963	Royce	4,896,009 A	1/1990	Pawlowski
3,432,691 A	3/1969	Shoh	4,903,696 A	2/1990	Stasz et al.
3,489,930 A	1/1970	Shoh	4,915,643 A	4/1990	Samejima et al.
3,513,848 A	5/1970	Winston et al.	4,922,902 A	5/1990	Wuchinich et al.
3,526,219 A	9/1970	Balamuth	4,965,532 A	10/1990	Sakurai
3,554,198 A	1/1971	Tatoian et al.	4,979,952 A	12/1990	Kubota et al.
3,614,484 A	10/1971	Shoh	4,981,756 A	1/1991	Rhandhawa
3,616,375 A	10/1971	Inoue	5,013,956 A	5/1991	Kurozumi et al.
3,629,726 A	12/1971	Popescu	5,015,227 A	5/1991	Broadwin et al.
3,636,943 A	1/1972	Balamuth	5,026,387 A	6/1991	Thomas
3,668,486 A	6/1972	Silver	5,042,707 A	8/1991	Taheri
3,702,948 A	11/1972	Balamuth	5,084,052 A	1/1992	Jacobs
3,776,238 A	12/1973	Peyman et al.	5,105,117 A	4/1992	Yamaguchi
3,805,787 A	4/1974	Banko	5,109,819 A	5/1992	Custer et al.
3,809,977 A	5/1974	Balamuth et al.	5,112,300 A	5/1992	Ureche
3,830,098 A	8/1974	Antonevich	5,123,903 A	6/1992	Quaid et al.
3,854,737 A	12/1974	Gilliam, Sr.	5,126,618 A	6/1992	Takahashi et al.
3,862,630 A	1/1975	Balamuth	D327,872 S	7/1992	McMills et al.
3,875,945 A	4/1975	Friedman	5,162,044 A	11/1992	Gahn et al.
3,900,823 A	8/1975	Sokal et al.	5,163,421 A	11/1992	Bernstein et al.
3,918,442 A	11/1975	Nikolaev et al.	5,163,537 A	11/1992	Radev
3,924,335 A	12/1975	Balamuth et al.	5,167,725 A	12/1992	Clark et al.
3,946,738 A	3/1976	Newton et al.	5,174,276 A	12/1992	Crockard
3,955,859 A	5/1976	Stella et al.	D332,660 S	1/1993	Rawson et al.
3,956,826 A	5/1976	Perdreux, Jr.	5,176,677 A	1/1993	Wuchinich
4,012,647 A	3/1977	Balamuth et al.	5,176,695 A	1/1993	Dulebohn
4,074,719 A	2/1978	Semm	5,184,605 A	2/1993	Grzeszykowski
4,156,187 A	5/1979	Murry et al.	5,188,102 A	2/1993	Idemoto et al.
4,167,944 A	9/1979	Banko	D334,173 S	3/1993	Liu et al.
4,188,927 A	2/1980	Harris	5,209,719 A	5/1993	Baruch et al.
4,200,106 A	4/1980	Douvas et al.	5,213,569 A	5/1993	Davis
4,203,444 A	5/1980	Bonnell et al.	5,214,339 A	5/1993	Naito
4,300,083 A	11/1981	Heiges	5,218,529 A	6/1993	Meyer et al.
4,302,728 A	11/1981	Nakamura	5,221,282 A	6/1993	Wuchinich
4,306,570 A	12/1981	Matthews	5,226,909 A	7/1993	Evans et al.
4,445,063 A	4/1984	Smith	5,226,910 A	7/1993	Kajiyama et al.
4,491,132 A	1/1985	Aikins	5,241,236 A	8/1993	Sasaki et al.
4,504,264 A	3/1985	Kelman	5,241,968 A	9/1993	Slater
4,512,344 A	4/1985	Barber	5,242,460 A	9/1993	Klein et al.
4,526,571 A	7/1985	Wuchinich	5,254,129 A	10/1993	Alexander
4,574,615 A	3/1986	Bower et al.	5,257,988 A	11/1993	L'Esperance, Jr.
4,617,927 A	10/1986	Manes	5,261,922 A	11/1993	Hood
4,633,119 A	12/1986	Thompson	5,263,957 A	11/1993	Davison
4,634,420 A	1/1987	Spinosa et al.	5,264,925 A	11/1993	Shipp et al.
4,640,279 A	2/1987	Beard	5,275,166 A	1/1994	Vaitekunas et al.
4,641,053 A	2/1987	Takeda	5,275,609 A	1/1994	Pingleton et al.
4,646,738 A	3/1987	Trott	5,282,800 A	2/1994	Foshee et al.
4,646,756 A	3/1987	Watmough et al.	5,282,817 A	2/1994	Hoogetboom et al.
4,649,919 A	3/1987	Thimsen et al.	5,285,795 A	2/1994	Ryan et al.
4,662,068 A	5/1987	Polonsky	5,304,115 A	4/1994	Pflueger et al.
4,674,502 A	6/1987	Imonti	D347,474 S	5/1994	Olson
4,708,127 A	11/1987	Abdelghani	5,312,023 A	5/1994	Green et al.
4,712,722 A	12/1987	Hood et al.	5,312,425 A	5/1994	Evans et al.
4,819,635 A	4/1989	Shapiro	5,322,055 A	6/1994	Davison et al.
4,827,911 A	5/1989	Broadwin et al.	5,324,299 A	6/1994	Davison et al.
4,832,683 A	5/1989	Idemoto et al.	5,326,013 A	7/1994	Green et al.
			5,326,342 A	7/1994	Pflueger et al.
			5,344,420 A	9/1994	Hilal et al.
			5,345,937 A	9/1994	Middleman et al.
			5,346,502 A	9/1994	Estabrook et al.
			5,353,474 A	10/1994	Good et al.
			5,357,164 A	10/1994	Imabayashi et al.
			5,357,423 A	10/1994	Weaver et al.
			5,359,994 A	11/1994	Krauter et al.
			5,366,466 A	11/1994	Christian et al.
			5,371,429 A	12/1994	Manna
			5,374,813 A	12/1994	Shipp
			D354,564 S	1/1995	Medema
			5,381,067 A	1/1995	Greenstein et al.
			5,387,215 A	2/1995	Fisher

(56)

References Cited

U.S. PATENT DOCUMENTS

5,389,098 A	2/1995	Tsuruta et al.	5,873,882 A	2/1999	Straub et al.
5,394,187 A	2/1995	Shipp	5,878,193 A	3/1999	Wang et al.
5,403,312 A	4/1995	Yates et al.	5,879,364 A	3/1999	Bromfield et al.
5,403,334 A	4/1995	Evans et al.	5,883,615 A	3/1999	Fago et al.
5,408,268 A	4/1995	Shipp	5,893,835 A	4/1999	Witt et al.
D358,887 S	5/1995	Feinberg	5,897,523 A	4/1999	Wright et al.
5,411,481 A	5/1995	Allen et al.	5,897,569 A	4/1999	Kellogg et al.
5,419,761 A	5/1995	Narayanan et al.	5,904,681 A	5/1999	West, Jr.
5,421,829 A	6/1995	Olichney et al.	5,906,627 A	5/1999	Spaulding
5,423,844 A	6/1995	Miller	5,906,628 A	5/1999	Miyawaki et al.
5,438,997 A	8/1995	Sieben et al.	5,911,699 A	6/1999	Anis et al.
5,445,639 A	8/1995	Kuslich et al.	5,916,229 A	6/1999	Evans
5,449,370 A	9/1995	Vaitekunas	5,935,143 A	8/1999	Hood
5,451,220 A	9/1995	Ciervo	5,935,144 A	8/1999	Estabrook
5,456,684 A	10/1995	Schmidt et al.	5,938,633 A	8/1999	Beaupre
5,471,988 A	12/1995	Fujio et al.	5,944,718 A	8/1999	Austin et al.
5,478,003 A	12/1995	Green et al.	5,944,737 A	8/1999	Tsonton et al.
5,483,501 A	1/1996	Park et al.	5,947,984 A	9/1999	Whipple
5,486,162 A	1/1996	Brumbach	5,954,736 A	9/1999	Bishop et al.
5,490,860 A	2/1996	Middle et al.	5,954,746 A	9/1999	Holthaus et al.
5,500,216 A	3/1996	Julian et al.	5,957,882 A	9/1999	Nita et al.
5,501,654 A	3/1996	Failla et al.	5,957,943 A	9/1999	Vaitekunas
5,505,693 A	4/1996	Mackool	5,968,007 A	10/1999	Simon et al.
5,507,738 A	4/1996	Ciervo	5,968,060 A	10/1999	Kellogg
5,527,331 A	6/1996	Kresch et al.	5,974,342 A	10/1999	Petrofsky
5,540,693 A	7/1996	Fisher	D416,089 S	11/1999	Barton et al.
5,558,671 A	9/1996	Yates	5,980,510 A	11/1999	Tsonton et al.
5,562,609 A	10/1996	Brumbach	5,980,546 A	11/1999	Hood
5,562,610 A	10/1996	Brumbach	5,989,274 A	11/1999	Davison et al.
5,573,424 A	11/1996	Poppe	5,989,275 A	11/1999	Estabrook et al.
5,577,654 A	11/1996	Bishop	5,993,465 A	11/1999	Shipp et al.
5,591,187 A	1/1997	Dekel	5,993,972 A	11/1999	Reich et al.
5,593,414 A	1/1997	Shipp et al.	5,994,855 A	11/1999	Lundell et al.
5,601,601 A	2/1997	Tal et al.	6,024,741 A	2/2000	Williamson, IV et al.
5,603,773 A	2/1997	Campbell	6,024,750 A	2/2000	Mastri et al.
5,607,436 A	3/1997	Pratt et al.	6,027,515 A	2/2000	Cimino
5,618,304 A	4/1997	Hart et al.	6,031,526 A	2/2000	Shipp
5,618,492 A	4/1997	Auten et al.	6,033,375 A	3/2000	Brumbach
5,620,447 A	4/1997	Smith et al.	6,033,399 A	3/2000	Gines
5,626,595 A	5/1997	Sklar et al.	6,036,667 A	3/2000	Manna et al.
5,628,760 A	5/1997	Knoepfler	6,036,707 A	3/2000	Spaulding
5,630,420 A	5/1997	Vaitekunas	6,048,224 A	4/2000	Kay
D381,077 S	7/1997	Hunt	6,050,943 A	4/2000	Slayton et al.
5,651,780 A	7/1997	Jackson et al.	6,051,010 A	4/2000	DiMatteo et al.
5,653,713 A	8/1997	Michelson	6,056,735 A	5/2000	Okada et al.
5,669,922 A	9/1997	Hood	6,063,098 A	5/2000	Houser et al.
5,674,235 A	10/1997	Parisi	6,066,132 A	5/2000	Chen et al.
5,678,568 A	10/1997	Uchikubo et al.	6,066,151 A	5/2000	Miyawaki et al.
5,690,269 A	11/1997	Bolanos et al.	6,068,627 A	5/2000	Orszulak et al.
5,694,936 A	12/1997	Fujimoto et al.	6,068,647 A	5/2000	Witt et al.
5,704,534 A	1/1998	Huitema et al.	6,077,285 A	6/2000	Boukhny
5,711,472 A	1/1998	Bryan	6,083,191 A	7/2000	Rose
5,713,896 A	2/1998	Nardella	6,086,584 A	7/2000	Miller
5,717,306 A	2/1998	Shipp	6,090,120 A	7/2000	Wright et al.
5,728,130 A	3/1998	Ishikawa et al.	6,096,033 A	8/2000	Tu et al.
5,730,752 A	3/1998	Alden et al.	6,099,542 A	8/2000	Cohn et al.
5,733,074 A	3/1998	Stöck et al.	6,109,500 A	8/2000	Alli et al.
5,741,226 A	4/1998	Strukel et al.	6,110,127 A	8/2000	Suzuki
5,766,164 A	6/1998	Mueller et al.	6,113,594 A	9/2000	Savage
5,792,135 A	8/1998	Madhani et al.	6,117,152 A	9/2000	Huitema
5,792,138 A	8/1998	Shipp	6,126,629 A	10/2000	Perkins
5,792,165 A	8/1998	Klieman et al.	6,129,735 A	10/2000	Okada et al.
5,808,396 A	9/1998	Boukhny	6,132,368 A	10/2000	Cooper
5,810,859 A	9/1998	DiMatteo et al.	6,132,448 A	10/2000	Perez et al.
5,817,084 A	10/1998	Jensen	6,139,320 A	10/2000	Hahn
5,817,119 A	10/1998	Klieman et al.	6,139,561 A	10/2000	Shibata et al.
5,827,323 A	10/1998	Klieman et al.	6,142,615 A	11/2000	Qiu et al.
5,828,160 A	10/1998	Sugishita	6,142,994 A	11/2000	Swanson et al.
5,833,696 A	11/1998	Whitfield et al.	6,147,560 A	11/2000	Erhage et al.
5,836,897 A	11/1998	Sakurai et al.	6,152,902 A	11/2000	Christian et al.
5,836,957 A	11/1998	Schulz et al.	6,159,160 A	12/2000	Hsei et al.
5,843,109 A	12/1998	Mehta et al.	6,159,175 A	12/2000	Strukel et al.
5,851,212 A	12/1998	Zirps et al.	6,162,194 A	12/2000	Shipp
5,858,018 A	1/1999	Shipp et al.	6,165,150 A	12/2000	Banko
5,873,873 A	2/1999	Smith et al.	6,174,310 B1	1/2001	Kirwan, Jr.
			6,179,853 B1	1/2001	Sachse et al.
			6,183,426 B1	2/2001	Akisada et al.
			6,204,592 B1	3/2001	Hur
			6,205,855 B1	3/2001	Pfeiffer

(56)

References Cited

U.S. PATENT DOCUMENTS

6,206,844	B1	3/2001	Reichel et al.	6,537,291	B2	3/2003	Friedman et al.
6,210,403	B1	4/2001	Klicek	6,543,452	B1	4/2003	Lavigne
6,214,023	B1	4/2001	Whipple et al.	6,543,456	B1	4/2003	Freeman
6,228,080	B1	5/2001	Gines	6,544,260	B1	4/2003	Markel et al.
6,231,565	B1	5/2001	Tovey et al.	6,558,376	B2	5/2003	Bishop
6,233,476	B1	5/2001	Strommer et al.	6,561,983	B2	5/2003	Cronin et al.
6,238,366	B1	5/2001	Savage et al.	6,572,563	B2	6/2003	Ouchi
6,245,065	B1	6/2001	Panescu et al.	6,572,632	B2	6/2003	Zisterer et al.
6,252,110	B1	6/2001	Uemura et al.	6,575,969	B1	6/2003	Rittman, III et al.
D444,365	S	7/2001	Bass et al.	6,582,451	B1	6/2003	Marucci et al.
D445,092	S	7/2001	Lee	D477,408	S	7/2003	Bromley
D445,764	S	7/2001	Lee	6,588,277	B2	7/2003	Giordano et al.
6,254,623	B1	7/2001	Haibel, Jr. et al.	6,589,200	B1	7/2003	Schwemberger et al.
6,257,241	B1	7/2001	Wampler	6,589,239	B2	7/2003	Khandkar et al.
6,258,034	B1	7/2001	Hanafy	6,607,540	B1	8/2003	Shipp
6,267,761	B1	7/2001	Ryan	6,610,059	B1	8/2003	West, Jr.
6,270,831	B2	8/2001	Kumar et al.	6,616,450	B2	9/2003	Mossle et al.
6,273,852	B1	8/2001	Lehe et al.	6,619,529	B2	9/2003	Green et al.
6,274,963	B1	8/2001	Estabrook et al.	6,623,500	B1	9/2003	Cook et al.
6,277,115	B1	8/2001	Saadat	6,623,501	B2	9/2003	Heller et al.
6,278,218	B1	8/2001	Madan et al.	6,626,848	B2	9/2003	Neuenfeldt
6,280,407	B1	8/2001	Manna et al.	6,626,926	B2	9/2003	Friedman et al.
6,283,981	B1	9/2001	Beaupre	6,633,234	B2	10/2003	Wiener et al.
6,287,344	B1	9/2001	Wampler et al.	6,644,532	B2	11/2003	Green et al.
6,290,575	B1	9/2001	Shipp	6,652,539	B2	11/2003	Shipp et al.
6,306,157	B1	10/2001	Shchervinsky	6,652,545	B2	11/2003	Shipp et al.
6,309,400	B2	10/2001	Beaupre	6,656,132	B1	12/2003	Ouchi
6,319,221	B1	11/2001	Savage et al.	6,656,177	B2	12/2003	Truckai et al.
6,325,795	B1	12/2001	Lindemann et al.	6,660,017	B2	12/2003	Beaupre
6,325,799	B1	12/2001	Goble	6,662,127	B2	12/2003	Wiener et al.
6,325,811	B1	12/2001	Messerly	6,663,941	B2	12/2003	Brown et al.
6,328,751	B1	12/2001	Beaupre	6,666,860	B1	12/2003	Takahashi
6,338,657	B1	1/2002	Harper et al.	6,666,875	B1	12/2003	Sakurai et al.
6,340,352	B1	1/2002	Okada et al.	6,669,690	B1	12/2003	Okada et al.
6,350,269	B1	2/2002	Shipp et al.	6,669,710	B2	12/2003	Moutafis et al.
6,352,532	B1	3/2002	Kramer et al.	6,676,660	B2	1/2004	Wampler et al.
6,364,888	B1	4/2002	Niemeyer et al.	6,678,621	B2	1/2004	Wiener et al.
6,379,320	B1	4/2002	Lafon et al.	6,679,875	B2	1/2004	Honda et al.
D457,958	S	5/2002	Dycus et al.	6,679,899	B2	1/2004	Wiener et al.
6,383,194	B1	5/2002	Pothula	6,682,544	B2	1/2004	Mastri et al.
6,387,109	B1	5/2002	Davison et al.	6,685,701	B2	2/2004	Orszulak et al.
6,388,657	B1	5/2002	Natoli	6,685,703	B2	2/2004	Pearson et al.
6,391,042	B1	5/2002	Cimino	6,689,145	B2	2/2004	Lee et al.
6,398,779	B1	6/2002	Buyse et al.	6,689,146	B1	2/2004	Himes
6,402,743	B1	6/2002	Orszulak et al.	6,716,215	B1	4/2004	David et al.
6,402,748	B1	6/2002	Schoenman et al.	6,719,776	B2	4/2004	Baxter et al.
6,405,733	B1	6/2002	Fogarty et al.	D490,059	S	5/2004	Conway et al.
6,416,486	B1	7/2002	Wampler	6,731,047	B2	5/2004	Kauf et al.
6,423,073	B2	7/2002	Bowman	6,733,506	B1	5/2004	McDevitt et al.
6,423,082	B1	7/2002	Houser et al.	6,739,872	B1	5/2004	Turri
6,428,539	B1	8/2002	Baxter et al.	D491,666	S	6/2004	Kimmell et al.
6,432,118	B1	8/2002	Messerly	6,743,245	B2	6/2004	Lobdell
6,436,114	B1	8/2002	Novak et al.	6,746,284	B1	6/2004	Spink, Jr.
6,436,115	B1	8/2002	Beaupre	6,752,815	B2	6/2004	Beaupre
6,440,062	B1	8/2002	Ouchi	6,755,825	B2	6/2004	Shoenman et al.
6,443,968	B1	9/2002	Holthaus et al.	6,761,698	B2	7/2004	Shibata et al.
6,443,969	B1	9/2002	Novak et al.	6,762,535	B2	7/2004	Take et al.
6,449,006	B1	9/2002	Shipp	6,770,072	B1	8/2004	Truckai et al.
6,454,781	B1	9/2002	Witt et al.	6,773,409	B2	8/2004	Truckai et al.
6,454,782	B1	9/2002	Schwemberger	6,773,443	B2	8/2004	Truwit et al.
6,458,142	B1	10/2002	Faller et al.	6,773,444	B2	8/2004	Messerly
6,480,796	B2	11/2002	Wiener	6,778,023	B2	8/2004	Christensen
6,485,490	B2	11/2002	Wampler et al.	6,783,524	B2	8/2004	Anderson et al.
6,491,708	B2	12/2002	Madan et al.	6,786,382	B1	9/2004	Hoffman
6,497,715	B2	12/2002	Satou	6,786,383	B2	9/2004	Stegelman
6,500,176	B1	12/2002	Truckai et al.	6,790,173	B2	9/2004	Saadat et al.
6,500,188	B2	12/2002	Harper et al.	6,790,216	B1	9/2004	Ishikawa
6,500,312	B2	12/2002	Wedekamp	6,796,981	B2	9/2004	Wham et al.
6,506,208	B2	1/2003	Hunt et al.	D496,997	S	10/2004	Dycus et al.
6,511,493	B1	1/2003	Moutafis et al.	6,802,843	B2	10/2004	Truckai et al.
6,514,267	B2	2/2003	Jewett	6,809,508	B2	10/2004	Donofrio
6,524,251	B2	2/2003	Rabiner et al.	6,810,281	B2	10/2004	Brock et al.
6,524,316	B1	2/2003	Nicholson et al.	6,827,712	B2	12/2004	Tovey et al.
6,527,736	B1	3/2003	Attinger et al.	6,828,712	B2	12/2004	Battaglin et al.
6,533,784	B2	3/2003	Truckai et al.	6,835,082	B2	12/2004	Gonnering
				6,849,073	B2	2/2005	Hoey et al.
				6,863,676	B2	3/2005	Lee et al.
				6,869,439	B2	3/2005	White et al.
				6,875,220	B2	4/2005	Du et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,877,647	B2	4/2005	Green et al.	7,169,144	B2	1/2007	Hoey et al.
6,882,439	B2	4/2005	Ishijima	7,169,146	B2	1/2007	Truckai et al.
6,887,209	B2	5/2005	Kadziauskas et al.	7,179,254	B2	2/2007	Pendekanti et al.
6,887,252	B1	5/2005	Okada et al.	7,179,271	B2	2/2007	Friedman et al.
6,899,685	B2	5/2005	Kernode et al.	7,186,253	B2	3/2007	Truckai et al.
6,905,497	B2	6/2005	Truckai et al.	7,189,233	B2	3/2007	Truckai et al.
6,908,472	B2	6/2005	Wiener et al.	D541,418	S	4/2007	Schechter et al.
6,913,579	B2	7/2005	Truckai et al.	7,204,820	B2	4/2007	Akahoshi
6,915,623	B2	7/2005	Dey et al.	7,207,997	B2	4/2007	Shipp et al.
6,923,804	B2	8/2005	Eggers et al.	7,210,881	B2	5/2007	Greenberg
6,926,712	B2	8/2005	Phan	7,211,079	B2	5/2007	Treat
6,926,716	B2	8/2005	Baker et al.	7,217,128	B2	5/2007	Atkin et al.
6,929,632	B2	8/2005	Nita et al.	7,217,269	B2	5/2007	El-Galley et al.
6,929,644	B2	8/2005	Truckai et al.	7,220,951	B2	5/2007	Truckai et al.
6,933,656	B2	8/2005	Matsushita et al.	7,223,229	B2	5/2007	Inman et al.
D509,589	S	9/2005	Wells	7,229,455	B2	6/2007	Sakurai et al.
6,942,660	B2	9/2005	Pantera et al.	7,235,071	B2	6/2007	Gonnering
6,942,677	B2	9/2005	Nita et al.	7,244,262	B2	7/2007	Wiener et al.
6,945,981	B2	9/2005	Donofrio et al.	7,269,873	B2	9/2007	Brewer et al.
6,946,779	B2	9/2005	Birgel	7,273,483	B2	9/2007	Wiener et al.
6,948,503	B2	9/2005	Refior et al.	D552,241	S	10/2007	Bromley et al.
D511,145	S	11/2005	Donofrio et al.	7,282,048	B2	10/2007	Goble et al.
6,974,450	B2	12/2005	Weber et al.	7,285,895	B2	10/2007	Beaupré
6,976,844	B2	12/2005	Hickok et al.	7,300,431	B2	11/2007	Dubrovsky
6,976,969	B2	12/2005	Messerly	7,300,435	B2	11/2007	Wham et al.
6,977,495	B2	12/2005	Donofrio	7,300,446	B2	11/2007	Beaupre
6,979,332	B2	12/2005	Adams	7,303,531	B2	12/2007	Lee et al.
6,981,628	B2	1/2006	Wales	7,303,557	B2	12/2007	Wham et al.
6,984,220	B2	1/2006	Wuchinich	7,309,849	B2	12/2007	Truckai et al.
6,994,708	B2	2/2006	Manzo	7,311,706	B2	12/2007	Schoenman et al.
7,001,335	B2	2/2006	Adachi et al.	7,311,709	B2	12/2007	Truckai et al.
7,011,657	B2	3/2006	Truckai et al.	7,317,955	B2	1/2008	McGreevy
7,014,638	B2	3/2006	Michelson	7,318,831	B2	1/2008	Alvarez et al.
7,033,357	B2	4/2006	Baxter et al.	7,326,236	B2	2/2008	Andreas et al.
7,037,306	B2	5/2006	Podany	7,331,410	B2	2/2008	Yong et al.
7,041,083	B2	5/2006	Chu et al.	7,335,165	B2	2/2008	Truwit et al.
7,041,088	B2	5/2006	Nawrocki et al.	7,335,997	B2	2/2008	Wiener
7,041,102	B2	5/2006	Truckai et al.	7,337,010	B2	2/2008	Howard et al.
7,044,949	B2	5/2006	Orszulak et al.	7,353,068	B2	4/2008	Tanaka et al.
7,066,893	B2	6/2006	Hibner et al.	7,354,440	B2	4/2008	Truckai et al.
7,066,895	B2	6/2006	Podany	7,364,577	B2	4/2008	Wham et al.
7,070,597	B2	7/2006	Truckai et al.	RE40,388	E	6/2008	Gines
7,074,218	B2	7/2006	Washington et al.	7,380,695	B2	6/2008	Doll et al.
7,074,219	B2	7/2006	Levine et al.	7,380,696	B2	6/2008	Shelton, IV et al.
7,077,039	B2	7/2006	Gass et al.	7,381,209	B2	6/2008	Truckai et al.
7,077,845	B2	7/2006	Hacker et al.	7,390,317	B2	6/2008	Taylor et al.
7,077,853	B2	7/2006	Kramer et al.	7,404,508	B2	7/2008	Smith et al.
7,083,619	B2	8/2006	Truckai et al.	7,408,288	B2	8/2008	Hara
7,087,054	B2	8/2006	Truckai et al.	7,416,101	B2	8/2008	Shelton, IV et al.
7,090,672	B2	8/2006	Underwood et al.	7,416,437	B2	8/2008	Sartor et al.
7,101,371	B2	9/2006	Dycus et al.	D576,725	S	9/2008	Shumer et al.
7,101,378	B2	9/2006	Salameh et al.	7,419,490	B2	9/2008	Falkenstein et al.
7,104,834	B2	9/2006	Robinson et al.	7,422,139	B2	9/2008	Shelton, IV et al.
7,108,695	B2	9/2006	Witt et al.	7,422,463	B2	9/2008	Kuo
7,111,769	B2	9/2006	Wales et al.	D578,643	S	10/2008	Shumer et al.
7,112,201	B2	9/2006	Truckai et al.	D578,644	S	10/2008	Shumer et al.
D531,311	S	10/2006	Guerra et al.	D578,645	S	10/2008	Shumer et al.
7,117,034	B2	10/2006	Kronberg	7,431,704	B2	10/2008	Babaev
7,118,564	B2	10/2006	Ritchie et al.	7,441,684	B2	10/2008	Shelton, IV et al.
7,124,932	B2	10/2006	Isaacson et al.	7,455,208	B2	11/2008	Wales et al.
7,125,409	B2	10/2006	Truckai et al.	7,462,181	B2	12/2008	Kraft et al.
7,128,720	B2	10/2006	Podany	7,464,846	B2	12/2008	Shelton, IV et al.
7,131,860	B2	11/2006	Sartor et al.	7,472,815	B2	1/2009	Shelton, IV et al.
7,135,018	B2	11/2006	Ryan et al.	7,473,263	B2	1/2009	Johnston et al.
7,135,030	B2	11/2006	Schwemberger et al.	7,479,148	B2	1/2009	Beaupre
7,137,980	B2	11/2006	Buyse et al.	7,479,160	B2	1/2009	Branch et al.
7,144,403	B2	12/2006	Booth	7,481,775	B2	1/2009	Weikel, Jr. et al.
7,153,315	B2	12/2006	Miller	7,488,285	B2	2/2009	Honda et al.
D536,093	S	1/2007	Nakajima et al.	7,494,468	B2	2/2009	Rabiner et al.
7,156,189	B1	1/2007	Bar-Cohen et al.	7,503,893	B2	3/2009	Kucklick
7,156,853	B2	1/2007	Muratsu	7,503,895	B2	3/2009	Rabiner et al.
7,157,058	B2	1/2007	Marhasin et al.	7,506,790	B2	3/2009	Shelton, IV
7,159,750	B2	1/2007	Racenet et al.	7,506,791	B2	3/2009	Omaitis et al.
7,160,299	B2	1/2007	Baily	7,524,320	B2	4/2009	Tierney et al.
7,163,548	B2	1/2007	Stulen et al.	7,530,986	B2	5/2009	Beaupre et al.
				7,534,243	B1	5/2009	Chin et al.
				D594,983	S	6/2009	Price et al.
				7,540,871	B2	6/2009	Gonnering
				7,544,200	B2	6/2009	Houser

(56)

References Cited

U.S. PATENT DOCUMENTS

7,549,564	B2	6/2009	Boudreaux	D638,540	S	5/2011	Ijiri et al.
7,559,450	B2	7/2009	Wales et al.	7,951,165	B2	5/2011	Golden et al.
7,567,012	B2	7/2009	Namikawa	7,959,050	B2	6/2011	Smith et al.
7,572,266	B2	8/2009	Young et al.	7,959,626	B2	6/2011	Hong et al.
7,578,820	B2	8/2009	Moore et al.	7,972,329	B2	7/2011	Refior et al.
7,582,095	B2	9/2009	Shipp et al.	7,976,544	B2	7/2011	McClurken et al.
7,585,181	B2	9/2009	Olsen	7,981,050	B2	7/2011	Ritchart et al.
7,588,176	B2	9/2009	Timm et al.	7,998,157	B2	8/2011	Culp et al.
7,601,119	B2	10/2009	Shahinian	8,038,693	B2	10/2011	Allen
7,621,930	B2	11/2009	Houser	8,057,498	B2	11/2011	Robertson
7,641,653	B2	1/2010	Dalla Betta et al.	8,058,771	B2	11/2011	Giordano et al.
7,654,431	B2	2/2010	Hueil et al.	8,061,014	B2	11/2011	Smith et al.
7,659,833	B2	2/2010	Warner et al.	8,070,711	B2	12/2011	Bassinger et al.
7,665,647	B2	2/2010	Shelton, IV et al.	8,070,762	B2	12/2011	Escudero et al.
7,670,334	B2	3/2010	Hueil et al.	8,075,558	B2	12/2011	Truckai et al.
7,670,338	B2	3/2010	Albrecht et al.	8,089,197	B2	1/2012	Rinner et al.
7,674,263	B2	3/2010	Ryan	8,097,012	B2	1/2012	Kagarise
7,678,069	B1	3/2010	Baker et al.	8,105,323	B2	1/2012	Buyse et al.
7,678,125	B2	3/2010	Shipp	8,142,461	B2	3/2012	Houser et al.
7,686,770	B2	3/2010	Cohen	8,152,825	B2	4/2012	Madan et al.
7,686,826	B2	3/2010	Lee et al.	8,157,145	B2	4/2012	Shelton, IV et al.
7,688,028	B2	3/2010	Phillips et al.	8,161,977	B2	4/2012	Shelton, IV et al.
7,691,098	B2	4/2010	Wallace et al.	8,162,966	B2	4/2012	Connor et al.
7,699,846	B2	4/2010	Ryan	8,172,846	B2	5/2012	Brunnett et al.
7,713,202	B2	5/2010	Boukhny et al.	8,172,870	B2	5/2012	Shipp
7,714,481	B2	5/2010	Sakai	8,177,800	B2	5/2012	Spitz et al.
D618,797	S	6/2010	Price et al.	8,182,502	B2	5/2012	Stulen et al.
7,726,537	B2	6/2010	Olson et al.	D661,801	S	6/2012	Price et al.
7,738,969	B2	6/2010	Bleich	D661,802	S	6/2012	Price et al.
7,740,594	B2	6/2010	Hibner	D661,803	S	6/2012	Price et al.
7,751,115	B2	7/2010	Song	D661,804	S	6/2012	Price et al.
D621,503	S	8/2010	Otten et al.	8,197,502	B2	6/2012	Smith et al.
7,766,210	B2	8/2010	Shelton, IV et al.	8,226,675	B2	7/2012	Houser et al.
7,766,693	B2	8/2010	Sartor et al.	8,236,019	B2	8/2012	Houser
7,770,774	B2	8/2010	Mastri et al.	8,236,020	B2	8/2012	Smith et al.
7,770,775	B2	8/2010	Shelton, IV et al.	8,246,575	B2	8/2012	Viola
7,771,444	B2	8/2010	Patel et al.	8,246,615	B2	8/2012	Behnke
7,775,972	B2	8/2010	Brock et al.	8,252,012	B2	8/2012	Stulen
7,778,733	B2	8/2010	Nowlin et al.	8,253,303	B2	8/2012	Giordano et al.
7,780,054	B2	8/2010	Wales	8,257,377	B2	9/2012	Wiener et al.
7,780,593	B2	8/2010	Ueno et al.	8,257,387	B2	9/2012	Cunningham
7,780,651	B2	8/2010	Madhani et al.	8,273,087	B2	9/2012	Kimura et al.
7,780,659	B2	8/2010	Okada et al.	D669,992	S	10/2012	Schafer et al.
7,784,662	B2	8/2010	Wales et al.	D669,993	S	10/2012	Merchant et al.
7,796,969	B2	9/2010	Kelly et al.	8,286,846	B2	10/2012	Smith et al.
7,798,386	B2	9/2010	Schall et al.	8,287,485	B2	10/2012	Kimura et al.
7,799,020	B2	9/2010	Shores et al.	8,287,528	B2	10/2012	Wham et al.
7,799,045	B2	9/2010	Masuda	8,287,532	B2	10/2012	Carroll et al.
7,803,152	B2	9/2010	Honda et al.	8,303,576	B2	11/2012	Brock
7,806,891	B2	10/2010	Nowlin et al.	8,319,400	B2	11/2012	Houser et al.
7,810,693	B2	10/2010	Broehl et al.	8,323,302	B2	12/2012	Robertson et al.
7,819,819	B2	10/2010	Quick et al.	8,333,778	B2	12/2012	Smith et al.
D627,066	S	11/2010	Romero	8,333,779	B2	12/2012	Smith et al.
7,824,401	B2	11/2010	Manzo et al.	8,334,468	B2	12/2012	Palmer et al.
7,832,611	B2	11/2010	Boyden et al.	8,334,635	B2	12/2012	Voegele et al.
7,834,484	B2	11/2010	Sartor	8,337,407	B2	12/2012	Quistgaard et al.
7,837,699	B2	11/2010	Yamada et al.	8,338,726	B2	12/2012	Palmer et al.
7,845,537	B2	12/2010	Shelton, IV et al.	8,344,596	B2	1/2013	Nield et al.
7,846,155	B2	12/2010	Houser et al.	8,348,967	B2	1/2013	Stulen
7,846,161	B2	12/2010	Dumbauld et al.	8,357,103	B2	1/2013	Mark et al.
7,854,735	B2	12/2010	Houser et al.	8,372,099	B2	2/2013	Deville et al.
D631,155	S	1/2011	Peine et al.	8,372,101	B2	2/2013	Smith et al.
7,861,906	B2	1/2011	Doll et al.	8,372,102	B2	2/2013	Stulen et al.
7,862,560	B2	1/2011	Marion	8,374,670	B2	2/2013	Selkee
7,876,030	B2	1/2011	Taki et al.	8,377,059	B2	2/2013	Deville et al.
D631,965	S	2/2011	Price et al.	8,377,085	B2	2/2013	Smith et al.
7,878,991	B2	2/2011	Babaev	8,382,782	B2	2/2013	Robertson et al.
7,879,033	B2	2/2011	Sartor et al.	8,403,948	B2	3/2013	Deville et al.
7,892,606	B2	2/2011	Thies et al.	8,403,949	B2	3/2013	Palmer et al.
7,901,400	B2	3/2011	Wham et al.	8,403,950	B2	3/2013	Palmer et al.
7,901,423	B2	3/2011	Stulen et al.	8,418,349	B2	4/2013	Smith et al.
7,905,881	B2	3/2011	Masuda et al.	8,419,757	B2	4/2013	Smith et al.
7,922,061	B2	4/2011	Shelton, IV et al.	8,419,758	B2	4/2013	Smith et al.
7,922,651	B2	4/2011	Yamada et al.	8,419,759	B2	4/2013	Dietz
D637,288	S	5/2011	Houghton	8,425,545	B2	4/2013	Smith et al.
				8,430,898	B2	4/2013	Wiener et al.
				8,435,257	B2	5/2013	Smith et al.
				8,439,912	B2	5/2013	Cunningham et al.
				8,439,939	B2	5/2013	Deville et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,444,637 B2	5/2013	Podmore et al.	2004/0097912 A1	5/2004	Gonnering
8,444,662 B2	5/2013	Palmer et al.	2004/0097919 A1	5/2004	Wellman et al.
8,461,744 B2	6/2013	Wiener et al.	2004/0097996 A1	5/2004	Rabiner et al.
8,469,981 B2	6/2013	Robertson et al.	2004/0116952 A1	6/2004	Sakurai et al.
8,479,969 B2	7/2013	Shelton, IV	2004/0147934 A1	7/2004	Kiester
8,485,413 B2	7/2013	Scheib et al.	2004/0167508 A1	8/2004	Wham et al.
8,486,057 B2	7/2013	Behnke, II	2004/0176686 A1	9/2004	Hare et al.
8,486,096 B2	7/2013	Robertson et al.	2004/0199193 A1	10/2004	Hayashi et al.
8,491,578 B2	7/2013	Manwaring et al.	2004/0204728 A1	10/2004	Haefner
D687,549 S	8/2013	Johnson et al.	2004/0243147 A1	12/2004	Lipow
8,512,365 B2	8/2013	Wiener et al.	2004/0260300 A1	12/2004	Gorensek et al.
8,523,889 B2	9/2013	Stulen et al.	2005/0021018 A1	1/2005	Anderson et al.
8,531,064 B2	9/2013	Robertson et al.	2005/0021065 A1	1/2005	Yamada et al.
8,535,340 B2	9/2013	Allen	2005/0033337 A1	2/2005	Muir et al.
8,535,341 B2	9/2013	Allen	2005/0049546 A1	3/2005	Messerly et al.
8,546,996 B2	10/2013	Messerly et al.	2005/0070800 A1	3/2005	Takahashi
8,546,999 B2	10/2013	Houser et al.	2005/0096683 A1	5/2005	Ellins et al.
8,573,461 B2	11/2013	Shelton, IV et al.	2005/0099824 A1	5/2005	Dowling et al.
8,573,465 B2	11/2013	Shelton, IV	2005/0103819 A1	5/2005	Racenet et al.
8,579,928 B2	11/2013	Robertson et al.	2005/0143769 A1	6/2005	White et al.
8,591,506 B2	11/2013	Wham et al.	2005/0149108 A1	7/2005	Cox
8,591,536 B2	11/2013	Robertson	2005/0165345 A1	7/2005	Laufer et al.
D695,407 S	12/2013	Price et al.	2005/0177184 A1	8/2005	Easley
D696,631 S	12/2013	Price et al.	2005/0182339 A1	8/2005	Lee et al.
8,602,288 B2	12/2013	Shelton, IV et al.	2005/0188743 A1	9/2005	Land
8,616,431 B2	12/2013	Timm et al.	2005/0192610 A1	9/2005	Houser et al.
8,623,027 B2	1/2014	Price et al.	2005/0209620 A1	9/2005	Du et al.
8,650,728 B2	2/2014	Wan et al.	2005/0234484 A1	10/2005	Houser et al.
8,652,155 B2	2/2014	Houser et al.	2005/0249667 A1	11/2005	Tuszynski et al.
8,659,208 B1	2/2014	Rose et al.	2005/0256405 A1	11/2005	Makin et al.
8,663,220 B2	3/2014	Wiener et al.	2005/0261581 A1	11/2005	Hughes et al.
8,690,582 B2	4/2014	Rohrbach et al.	2005/0261588 A1	11/2005	Makin et al.
8,696,366 B2	4/2014	Chen et al.	2005/0273090 A1	12/2005	Nieman et al.
8,704,425 B2	4/2014	Giordano et al.	2005/0288659 A1	12/2005	Kimura et al.
8,709,031 B2	4/2014	Stulen	2006/0030797 A1	2/2006	Zhou et al.
8,749,116 B2	6/2014	Messerly et al.	2006/0058825 A1	3/2006	Ogura et al.
8,754,570 B2	6/2014	Voegele et al.	2006/0063130 A1	3/2006	Hayman et al.
8,764,735 B2	7/2014	Coe et al.	2006/0066181 A1	3/2006	Bromfield et al.
8,773,001 B2	7/2014	Wiener et al.	2006/0079879 A1	4/2006	Faller et al.
8,779,648 B2	7/2014	Giordano et al.	2006/0084963 A1	4/2006	Messerly
2001/0025173 A1	9/2001	Ritchie et al.	2006/0095046 A1	5/2006	Trieu et al.
2001/0025183 A1	9/2001	Shahidi et al.	2006/0190034 A1	8/2006	Nishizawa et al.
2001/0025184 A1	9/2001	Messerly	2006/0206100 A1	9/2006	Eskridge et al.
2001/0031950 A1	10/2001	Ryan	2006/0206115 A1	9/2006	Schomer et al.
2001/0039419 A1	11/2001	Francischelli et al.	2006/0211943 A1	9/2006	Beaupre
2002/0002377 A1	1/2002	Cimino	2006/0217729 A1	9/2006	Eskridge et al.
2002/0019649 A1	2/2002	Sikora et al.	2006/0235306 A1	10/2006	Cotter et al.
2002/0022836 A1	2/2002	Goble et al.	2006/0253050 A1	11/2006	Yoshimine et al.
2002/0029055 A1	3/2002	Bonutti	2006/0264809 A1	11/2006	Hansmann et al.
2002/0049551 A1	4/2002	Friedman et al.	2007/0016235 A1	1/2007	Tanaka et al.
2002/0052617 A1	5/2002	Anis et al.	2007/0016236 A1	1/2007	Beaupre
2002/0077550 A1	6/2002	Rabiner et al.	2007/0055228 A1	3/2007	Berg et al.
2002/0077645 A1*	6/2002	Wiener	2007/0056596 A1	3/2007	Fanney et al.
		A61B 17/320068	2007/0060915 A1	3/2007	Kucklick
		606/169	2007/0060935 A1	3/2007	Schwardt et al.
			2007/0063618 A1	3/2007	Bromfield
			2007/0074584 A1	4/2007	Talarico et al.
			2007/0106317 A1	5/2007	Shelton, IV et al.
			2007/0129716 A1	6/2007	Daw et al.
			2007/0130771 A1	6/2007	Ehlert et al.
			2007/0131034 A1	6/2007	Ehlert et al.
			2007/0149881 A1	6/2007	Rabin
			2007/0162050 A1	7/2007	Sartor
			2007/0166663 A1	7/2007	Telles et al.
			2007/0173803 A1	7/2007	Wham et al.
			2007/0173813 A1	7/2007	Odom
			2007/0173872 A1	7/2007	Neuenfeldt
			2007/0175949 A1	8/2007	Shelton, IV et al.
			2007/0185380 A1	8/2007	Kucklick
			2007/0191712 A1	8/2007	Messerly et al.
			2007/0219481 A1	9/2007	Babaev
			2007/0239028 A1	10/2007	Houser et al.
			2007/0239101 A1	10/2007	Kellogg
			2007/0249941 A1	10/2007	Salehi et al.
			2007/0260234 A1	11/2007	McCullagh et al.
			2007/0265560 A1	11/2007	Soltani et al.
			2007/0275348 A1	11/2007	Lemon
			2007/0282332 A1*	12/2007	Witt
					A61B 17/320092
					606/50

(56)

References Cited

U.S. PATENT DOCUMENTS

2007/0282335	A1	12/2007	Young et al.	2010/0298743	A1	11/2010	Nield et al.
2007/0287933	A1	12/2007	Phan et al.	2010/0298851	A1	11/2010	Nield
2008/0009848	A1	1/2008	Paraschiv et al.	2011/0004233	A1	1/2011	Muir et al.
2008/0051812	A1	2/2008	Schmitz et al.	2011/0009850	A1	1/2011	Main et al.
2008/0058585	A1	3/2008	Novak et al.	2011/0015627	A1	1/2011	Dinardo et al.
2008/0058775	A1	3/2008	Darian et al.	2011/0077648	A1	3/2011	Lee et al.
2008/0058845	A1	3/2008	Shimizu et al.	2011/0082486	A1	4/2011	Messerly et al.
2008/0082039	A1	4/2008	Babaev	2011/0087212	A1	4/2011	Aldridge et al.
2008/0082098	A1	4/2008	Tanaka et al.	2011/0087213	A1	4/2011	Messerly et al.
2008/0114364	A1	5/2008	Goldin et al.	2011/0087214	A1	4/2011	Giordano et al.
2008/0125768	A1	5/2008	Tahara et al.	2011/0087215	A1	4/2011	Aldridge et al.
2008/0140158	A1	6/2008	Hamel et al.	2011/0087216	A1	4/2011	Aldridge et al.
2008/0171938	A1	7/2008	Masuda et al.	2011/0087217	A1	4/2011	Yates et al.
2008/0172051	A1	7/2008	Masuda et al.	2011/0087218	A1	4/2011	Boudreaux et al.
2008/0177268	A1	7/2008	Daum et al.	2011/0087256	A1	4/2011	Wiener et al.
2008/0188878	A1	8/2008	Young	2011/0112526	A1	5/2011	Fritz et al.
2008/0200940	A1	8/2008	Eichmann et al.	2011/0144806	A1	6/2011	Sandhu et al.
2008/0208231	A1	8/2008	Ota et al.	2011/0196398	A1	8/2011	Robertson et al.
2008/0214967	A1	9/2008	Aranyi et al.	2011/0196399	A1	8/2011	Robertson et al.
2008/0234709	A1	9/2008	Houser	2011/0196404	A1	8/2011	Dietz et al.
2008/0234710	A1	9/2008	Neurohr et al.	2011/0224689	A1	9/2011	Larkin et al.
2008/0243106	A1	10/2008	Coe et al.	2011/0238065	A1	9/2011	Hunt et al.
2008/0245371	A1	10/2008	Gruber	2011/0257650	A1	10/2011	Deville et al.
2008/0249553	A1	10/2008	Gruber et al.	2011/0270126	A1	11/2011	Gunday et al.
2008/0255423	A1	10/2008	Kondo et al.	2011/0290853	A1	12/2011	Shelton, IV et al.
2008/0262490	A1	10/2008	Williams	2011/0290856	A1	12/2011	Shelton, IV et al.
2008/0281200	A1	11/2008	Voic et al.	2012/0004655	A1	1/2012	Kim et al.
2008/0281315	A1	11/2008	Gines	2012/0022525	A1	1/2012	Dietz et al.
2008/0281322	A1	11/2008	Sherman et al.	2012/0022530	A1	1/2012	Woodruff et al.
2008/0287948	A1	11/2008	Newton et al.	2012/0059289	A1	3/2012	Nield et al.
2009/0023985	A1	1/2009	Ewers	2012/0065628	A1	3/2012	Naito
2009/0030437	A1	1/2009	Houser et al.	2012/0071863	A1	3/2012	Lee et al.
2009/0030439	A1	1/2009	Stulen	2012/0078139	A1	3/2012	Aldridge et al.
2009/0036914	A1	2/2009	Houser	2012/0078243	A1	3/2012	Worrell et al.
2009/0048537	A1	2/2009	Lydon et al.	2012/0078244	A1	3/2012	Worrell et al.
2009/0054886	A1	2/2009	Yachi et al.	2012/0078247	A1	3/2012	Worrell et al.
2009/0054894	A1	2/2009	Yachi	2012/0078278	A1	3/2012	Bales, Jr. et al.
2009/0076506	A1	3/2009	Baker	2012/0080332	A1	4/2012	Shelton, IV et al.
2009/0082716	A1	3/2009	Akahoshi	2012/0083783	A1	4/2012	Davison et al.
2009/0112229	A1	4/2009	Omori et al.	2012/0083784	A1	4/2012	Davison et al.
2009/0118751	A1	5/2009	Wiener et al.	2012/0116379	A1	5/2012	Yates et al.
2009/0118802	A1	5/2009	Mioduski et al.	2012/0116391	A1	5/2012	Houser et al.
2009/0138006	A1	5/2009	Bales et al.	2012/0116395	A1	5/2012	Madan et al.
2009/0143799	A1	6/2009	Smith et al.	2012/0130256	A1	5/2012	Buyse et al.
2009/0143800	A1	6/2009	Deville et al.	2012/0130365	A1	5/2012	McLawhorn
2009/0143806	A1	6/2009	Witt et al.	2012/0136354	A1	5/2012	Rupp
2009/0149801	A1	6/2009	Crandall et al.	2012/0138660	A1	6/2012	Shelton, IV
2009/0207923	A1	8/2009	Dress	2012/0143211	A1	6/2012	Kishi
2009/0223033	A1	9/2009	Houser	2012/0150170	A1	6/2012	Buyse et al.
2009/0254077	A1	10/2009	Craig	2012/0165816	A1	6/2012	Kersten et al.
2009/0270853	A1	10/2009	Yachi et al.	2012/0172873	A1	7/2012	Artale et al.
2009/0270899	A1	10/2009	Carusillo et al.	2012/0172904	A1	7/2012	Muir et al.
2009/0275940	A1	11/2009	Malackowski et al.	2012/0177005	A1	7/2012	Liang et al.
2009/0318945	A1	12/2009	Yoshimine et al.	2012/0184946	A1	7/2012	Price et al.
2009/0327715	A1	12/2009	Smith et al.	2012/0199630	A1	8/2012	Shelton, IV
2010/0004508	A1	1/2010	Naito et al.	2012/0199632	A1	8/2012	Spivey et al.
2010/0016785	A1	1/2010	Takuma	2012/0203247	A1	8/2012	Shelton, IV et al.
2010/0016852	A1	1/2010	Manzo et al.	2012/0209289	A1	8/2012	Duque et al.
2010/0022825	A1	1/2010	Yoshie	2012/0209303	A1	8/2012	Frankhouser et al.
2010/0030233	A1	2/2010	Whitman et al.	2012/0210223	A1	8/2012	Eppolito
2010/0030248	A1	2/2010	Palmer et al.	2012/0245582	A1	9/2012	Kimball et al.
2010/0036370	A1	2/2010	Mirel et al.	2012/0259353	A1	10/2012	Houser et al.
2010/0042077	A1	2/2010	Okada	2012/0265196	A1	10/2012	Turner et al.
2010/0049180	A1	2/2010	Wells et al.	2012/0269676	A1	10/2012	Houser et al.
2010/0069940	A1*	3/2010	Miller	2012/0310262	A1	12/2012	Messerly et al.
			A61B 17/320068	2012/0330307	A1	12/2012	Ladtow et al.
			606/169	2013/0012957	A1	1/2013	Shelton, IV et al.
2010/0158307	A1	6/2010	Kubota et al.	2013/0012970	A1	1/2013	Houser
2010/0187283	A1	7/2010	Crainich et al.	2013/0030433	A1	1/2013	Heard
2010/0222714	A1	9/2010	Muir et al.	2013/0035680	A1	2/2013	Ben-Haim et al.
2010/0228264	A1	9/2010	Robinson et al.	2013/0053840	A1	2/2013	Krapohl et al.
2010/0234906	A1	9/2010	Koh	2013/0072856	A1	3/2013	Frankhouser et al.
2010/0262134	A1	10/2010	Jensen et al.	2013/0072857	A1	3/2013	Frankhouser et al.
2010/0274160	A1	10/2010	Yachi et al.	2013/0079762	A1	3/2013	Twomey et al.
2010/0280407	A1	11/2010	Polster	2013/0103023	A1	4/2013	Monson et al.
2010/0292691	A1	11/2010	Brogna	2013/0103024	A1	4/2013	Monson et al.
				2013/0110145	A1	5/2013	Weitzman
				2013/0123776	A1	5/2013	Monson et al.
				2013/0123777	A1	5/2013	Monson et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2013/0123782 A1 5/2013 Trees et al.
 2013/0123822 A1 5/2013 Wellman et al.
 2013/0131660 A1 5/2013 Monson et al.
 2013/0165929 A1 6/2013 Muir et al.
 2013/0211397 A1 8/2013 Parihar et al.
 2013/0217967 A1 8/2013 Mohr et al.
 2013/0226207 A1 8/2013 Stulen et al.
 2013/0226208 A1 8/2013 Wiener et al.
 2013/0245659 A1 9/2013 Robertson et al.
 2013/0267975 A1 10/2013 Timm et al.
 2013/0274734 A1 10/2013 Maass et al.
 2013/0282003 A1 10/2013 Messerly et al.
 2013/0282039 A1 10/2013 Wiener et al.
 2013/0285758 A1 10/2013 Aldridge et al.
 2013/0289591 A1 10/2013 Boudreaux et al.
 2013/0296908 A1 11/2013 Schulte et al.
 2013/0338661 A1 12/2013 Behnke, II
 2013/0345689 A1 12/2013 Ruddenklau et al.
 2013/0345733 A1 12/2013 Robertson et al.
 2014/0005640 A1 1/2014 Shelton, IV et al.
 2014/0005653 A1 1/2014 Shelton, IV et al.
 2014/0005654 A1 1/2014 Batross et al.
 2014/0005656 A1 1/2014 Mucilli et al.
 2014/0005661 A1 1/2014 Shelton, IV et al.
 2014/0005662 A1 1/2014 Shelton, IV et al.
 2014/0005667 A1 1/2014 Stulen et al.
 2014/0005668 A1 1/2014 Rhee et al.
 2014/0005676 A1 1/2014 Shelton, IV et al.
 2014/0005680 A1 1/2014 Shelton, IV et al.
 2014/0005681 A1 1/2014 Gee et al.
 2014/0005682 A1 1/2014 Worrell et al.
 2014/0005701 A1 1/2014 Olson et al.
 2014/0005702 A1 1/2014 Timm et al.
 2014/0005703 A1 1/2014 Stulen et al.
 2014/0005704 A1 1/2014 Vakharia et al.
 2014/0005705 A1 1/2014 Weir et al.
 2014/0005708 A1 1/2014 Shelton, IV et al.
 2014/0005718 A1 1/2014 Shelton, IV et al.
 2014/0058427 A1 2/2014 Robertson
 2014/0066962 A1 3/2014 Robertson et al.
 2014/0087569 A1 3/2014 Lee
 2014/0114327 A1 4/2014 Boudreaux et al.
 2014/0114334 A1 4/2014 Olson et al.
 2014/0155921 A1 6/2014 Price et al.
 2014/0180280 A1 6/2014 Sigmon, Jr.

FOREIGN PATENT DOCUMENTS

CN 1640365 A 7/2005
 CN 1694649 A 11/2005
 CN 1922563 A 2/2007
 CN 1951333 A 4/2007
 CN 101040799 A 9/2007
 CN 101467917 A 1/2009
 DE 9210327 U1 11/1992
 DE 4323585 A1 1/1995
 DE 19608716 C1 4/1997
 DE 20021619 U1 3/2001
 DE 10042606 A1 8/2001
 EP 0171967 A2 2/1986
 EP 1839599 A1 10/1987
 EP 0443256 A1 8/1991
 EP 0456470 A1 11/1991
 EP 0598976 A2 1/1994
 EP 0677275 A2 3/1995
 EP 0482195 B1 1/1996
 EP 0695535 A1 2/1996
 EP 0741996 A2 11/1996
 EP 0612570 B1 6/1997
 EP 1108394 A2 6/2001
 EP 0908148 B1 1/2002
 EP 1229515 A2 8/2002
 EP 1285634 A1 2/2003
 EP 0908155 B1 6/2003
 EP 0705570 B1 4/2004

EP 0765637 B1 7/2004
 EP 0870473 B1 9/2005
 EP 0624346 B1 11/2005
 EP 1594209 A1 11/2005
 EP 1199044 B1 12/2005
 EP 1609428 A1 12/2005
 EP 1199043 B1 3/2006
 EP 1433425 B1 6/2006
 EP 1704824 A1 9/2006
 EP 1749479 A1 2/2007
 EP 1815950 A1 8/2007
 EP 1844720 A1 10/2007
 EP 1862133 A1 12/2007
 EP 1199045 B1 6/2008
 EP 1972264 A1 9/2008
 EP 1974771 A1 10/2008
 EP 1435852 B1 12/2008
 EP 1498082 B1 12/2008
 EP 1707131 B1 12/2008
 EP 1997438 A2 12/2008
 EP 2014218 A2 1/2009
 EP 2042112 A2 4/2009
 EP 1832259 B1 6/2009
 EP 2074959 A1 7/2009
 EP 2111813 A1 10/2009
 EP 2200145 A1 6/2010
 EP 1214913 B1 7/2010
 EP 2238938 A1 10/2010
 EP 2298154 A2 3/2011
 EP 1510178 B1 6/2011
 EP 2305144 A1 6/2011
 EP 2335630 A1 6/2011
 EP 2361562 A1 8/2011
 EP 2365608 A2 9/2011
 EP 2316359 B1 3/2013
 EP 1616529 B1 9/2013
 GB 2032221 A 4/1980
 GB 2379878 B 11/2004
 GB 2447767 B 8/2011
 JP S 50-100891 12/1973
 JP S 59-68513 10/1982
 JP 62-221343 A 9/1987
 JP S 62-227343 10/1987
 JP 62-292153 A 12/1987
 JP 63-109386 A 5/1988
 JP 63-315049 A 12/1988
 JP H 01-151452 A 6/1989
 JP H 01-198540 A 8/1989
 JP 02-71510 U 5/1990
 JP 2-286149 A 11/1990
 JP H 02-292193 A 12/1990
 JP 04-25707 U 2/1992
 JP 4-30508 U 3/1992
 JP 05-095955 A 4/1993
 JP H 06-070938 A 3/1994
 JP 6-104503 A 4/1994
 JP 6-507081 A 8/1994
 JP H 7-508910 A 10/1995
 JP 7-308323 A 11/1995
 JP 8-24266 A 1/1996
 JP 8-275951 A 10/1996
 JP H 08-336545 A 12/1996
 JP H 09-503146 A 3/1997
 JP H 09-135553 A 5/1997
 JP 10-295700 A 11/1998
 JP H 11-501543 A 2/1999
 JP H 11-128238 5/1999
 JP H 11-192235 A 7/1999
 JP 11-253451 A 9/1999
 JP 2000-041991 A 2/2000
 JP 2000-070279 A 3/2000
 JP 2000-210299 A 8/2000
 JP 2000-287987 A 10/2000
 JP 2001-502216 A 2/2001
 JP 2003612 A 6/2001
 JP 2001-309925 A 11/2001
 JP 2002-186901 A 7/2002
 JP 2002-204808 A 7/2002
 JP 2002-263579 A 9/2002

(56)

References Cited

FOREIGN PATENT DOCUMENTS

JP	2002-330977	A	11/2002
JP	2002-542690	A	12/2002
JP	2003-000612	A	1/2003
JP	2003-010201		1/2003
JP	2003-510158	A	3/2003
JP	2003-126110	A	5/2003
JP	2003-310627	A	5/2003
JP	2003-530921	A	10/2003
JP	2003-339730	A	12/2003
JP	2004-147701	A	5/2004
JP	2005027026	A	1/2005
JP	2005-066316	A	3/2005
JP	2005-074088	A	3/2005
JP	2005-534451	A	11/2005
JP	2006-6410	A	1/2006
JP	2006-116194	A	5/2006
JP	2006-158525	A	6/2006
JP	2006-218296	A	8/2006
JP	2006217716	A	8/2006
JP	2006-288431	A	10/2006
JP	2007-050181	A	3/2007
JP	2007-229454	A	9/2007
JP	2007-527747	A	10/2007
JP	2008-508065	A	3/2008
JP	2008-119250	A	5/2008
JP	2009-511206	A	3/2009
JP	4262923	B2	5/2009
JP	2009-523567	A	6/2009
JP	2010-514923	A	5/2010
JP	5208761	B2	6/2013
WO	WO 92/22259	A2	12/1992
WO	WO 93/14708	A1	8/1993
WO	WO 93/16646		9/1993
WO	WO 93/20877		10/1993
WO	WO 94/21183	A1	9/1994
WO	WO 95/09572	A1	4/1995
WO	WO 96/30885	A1	10/1996
WO	WO 98/26739	A1	6/1998
WO	WO 98/35621	A1	8/1998
WO	WO 98/37815	A1	9/1998
WO	WO 99/52489		10/1999
WO	WO 01/54590	A1	8/2001
WO	WO 01/67970	A1	9/2001
WO	WO 01/95810	A2	12/2001
WO	WO 02/062241	A1	8/2002
WO	WO 2004/012615	A1	2/2004
WO	WO 2004/026104	A2	4/2004
WO	WO 2004/032754	A2	4/2004
WO	WO 2004/032762	A1	4/2004
WO	WO 2004/032763	A2	4/2004
WO	WO 2004/037095	A2	5/2004
WO	WO 2004/098426	A1	11/2004
WO	WO 2004/112618	A2	12/2004
WO	WO 2005/122917	A1	12/2005
WO	WO 2006/012797	A1	2/2006
WO	WO 2006/042210	A2	4/2006
WO	WO 2006/058223	A2	6/2006
WO	WO 2006/063199	A2	6/2006
WO	WO 2006/083988	A1	8/2006
WO	WO 2006/119139	A2	11/2006
WO	WO 2006/119376		11/2006
WO	WO 2006/129465	A1	12/2006
WO	WO 2007/008703	A2	1/2007
WO	WO 2007/008710	A2	1/2007
WO	WO 2007/040818	A1	4/2007
WO	WO 2007/047380	A2	4/2007
WO	WO 2007/047531	A2	4/2007
WO	WO 2007/056590	A1	5/2007
WO	WO 2007/087272	A2	8/2007
WO	WO 2007/143665	A2	12/2007
WO	WO 2008/016886	A2	2/2008
WO	WO 2008/042021	A1	4/2008
WO	WO 2008/049084	A2	4/2008
WO	WO 2008/130793	A1	10/2008
WO	WO 2009/018406	A2	2/2009

WO	WO 2009/027065	A1	3/2009
WO	WO 2009/046234	A2	4/2009
WO	WO 2009/120992	A2	10/2009
WO	WO 2010/068783	A1	6/2010
WO	WO 2011/008672	A2	1/2011
WO	WO 2011/052939	A2	5/2011
WO	WO 2011/144911	A1	11/2011
WO	WO 2012/061722	A2	5/2012
WO	WO 2012/135705	A1	10/2012
WO	WO 2013/018934	A1	2/2013
WO	WO 2013/062978	A2	5/2013

OTHER PUBLICATIONS

Partial International Search Report for PCT/US2010/039290, Oct. 4, 2010 (2 pages).

International Search Report for PCT/US2010/039290, Jan. 17, 2011 (7 pages).

AST Products, Inc., "Principles of Video Contact Angle Analysis," 20 pages, (2006).

Covidien 501(k) Summary Sonication, dated Feb. 24, 2011 (7 pages).

Technology Overview, printed from www.harmonicscalpel.com, Internet site, website accessed on Jun. 13, 2007, (3 pages).

Sheritt et al., "Novel Horn Designs for Ultrasonic/Sonic Cleaning Welding, Soldering, Cutting and Drilling," Proc. SPIE Smart Structures Conference, vol. 4701, Paper No. 34, San Diego, CA, pp. 353-360, Mar. 2002.

Lim et al., "A Review of Mechanism Used in Laparoscopic Surgical Instruments," Mechanism and Machine Theory, vol. 38, pp. 1133-1147, (2003).

Gooch et al., "Recommended Infection-Control Practices for Dentistry, 1993," Published: May 28, 1993; [retrieved on Aug. 23, 2008]. Retrieved from the internet: URL: <http://wonder.cdc.gov/wonder/prevguid/p0000191/p0000191.asp> (15 pages).

Huston et al., "Magnetic and Magnetostrictive Properties of Cube Textured Nickel for Magnetostrictive Transducer Applications," IEEE Transactions on Magnetics, vol. 9(4), pp. 636-640 (Dec. 1973).

Incropera et al., "Fundamentals of Heat and Mass Transfer", Wiley, New York (1990). (Book—not attached).

F. A. Duck, "Optical Properties of Tissue Including Ultraviolet and Infrared Radiation," pp. 43-71 in *Physical Properties of Tissue* (1990).

Orr et al., "Overview of Bioheat Transfer," pp. 367-384 in *Optical-Thermal Response of Laser-Irradiated Tissue*, A. J. Welch and M. J. C. van Gemert, eds., Plenum, New York (1995).

Campbell et al., "Thermal Imaging in Surgery," p. 19-3, in *Medical Infrared Imaging*, N. A. Diakides and J. D. Bronzino, Eds. (2008).

Sullivan, "Cost-Constrained Selection of Strand Diameter and Number in a Litz-Wire Transformer Winding," IEEE Transactions on Power Electronics, vol. 16, No. 2, Mar. 2001, pp. 281-288.

Sullivan, "Optimal Choice for Number of Strands in a Litz-Wire Transformer Winding," IEEE Transactions on Power Electronics, vol. 14, No. 2, Mar. 1999, pp. 283-291.

Graff, K.F., "Elastic Wave Propagation in a Curved Sonic Transmission Line," IEEE Transactions on Sonics and Ultrasonics, SU-17(1), 1-6 (1970).

Makarov, S. N., Ochmann, M., Desinger, K., "The longitudinal vibration response of a curved fiber used for laser ultrasound surgical therapy," Journal of the Acoustical Society of America 102, 1191-1199 (1997).

Morley, L. S. D., "Elastic Waves in a Naturally Curved Rod," Quarterly Journal of Mechanics and Applied Mathematics, 14: 155-172 (1961).

Walsh, S. J., White, R. G., "Vibrational Power Transmission in Curved Beams," Journal of Sound and Vibration, 233(3), 455-488 (2000).

<http://www.apicalinstr.com/generators.htm>.

<http://www.dotmed.com/listing/electrosurgical-unit/ethicon/ultrasonic-g110-1466724>.

<http://www.ethicon.com/gb-en/healthcare-professionals/products/engineering-devices/capital/ge...>

(56)

References Cited

OTHER PUBLICATIONS

[http://www.4-traders.com/Johnson-Johnson-4832/news/Johnson-Johnson-Ethicon-E . . .](http://www.4-traders.com/Johnson-Johnson-4832/news/Johnson-Johnson-Ethicon-E...)

<http://www.medicalexpo.com/medical-manufacturer/electrosurgical-generator-6951.html>.

http://www.megadyne.com/es_generator.php.

<http://www.valleylab.com/product/es/generators/index.html>.

U.S. Appl. No. 14/136,836, filed Dec. 20, 2013.

U.S. Appl. No. 13/804,205, filed Mar. 14, 2013.

U.S. Appl. No. 13/843,295, filed Mar. 15, 2013.

U.S. Appl. No. 13/833,706, filed Mar. 15, 2013.

U.S. Appl. No. 14/057,682, filed Oct. 18, 2013.

* cited by examiner




Fig. 1





Fig. 1A







Fig.3






Fig.5





Fig. 6



706




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig.14




Fig.15





Fig.16

*Fig.16A*




Fig. 17





Fig. 18

*Fig. 19*




Fig. 20




Fig. 21




Fig. 22A




Fig. 22B




Fig. 23A





Fig. 23B

*Fig.24*





Fig. 25

*Fig.26*




Fig.27




Fig. 28




Fig. 29




Fig. 30




Fig. 31






Fig. 32






Fig.35




Fig.36




Fig.37







Fig.38

*Fig.39*

*Fig. 40**Fig. 41*




Fig.42




Fig.43




Fig. 44




Fig. 45




Fig.46




Fig. 47




Fig. 48




Fig. 49




Fig. 50




Fig. 51

ULTRASONIC SURGICAL INSTRUMENTS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation application under 35 U.S.C. §120 of U.S. patent application Ser. No. 13/717,084, now U.S. Patent Application Publication No. 2013/0178882, entitled ULTRASONIC SURGICAL INSTRUMENTS COMPRISING TRANSDUCER ARRANGEMENTS, filed on Dec. 17, 2012, which issued as U.S. Pat. No. 8,754,570 on Jun. 17, 2014, which is a continuation application under 35 U.S.C. §120 of U.S. patent application Ser. No. 12/490,906, now U.S. Patent Application Publication No. 2010/0331869, entitled TRANSDUCER ARRANGEMENTS FOR ULTRASONIC SURGICAL INSTRUMENTS, filed on Jun. 24, 2009, which issued as U.S. Pat. No. 8,334,635 on Dec. 18, 2012, both of which are hereby incorporated by reference herein in their respective entireties.

BACKGROUND

The present invention relates, in general, to ultrasonic surgical instruments. Ultrasonic instruments, including both hollow core and solid core instruments, are used for the safe and effective treatment of many medical conditions. Ultrasonic instruments, and particularly solid core ultrasonic instruments, are advantageous because they may be used to cut and/or coagulate organic tissue using energy in the form of mechanical vibrations transmitted to a surgical end effector at ultrasonic frequencies. Ultrasonic vibrations, when transmitted to organic tissue at suitable energy levels and using a suitable end effector, may be used to cut, dissect, elevate or cauterize tissue or to separate muscle tissue from bone. Ultrasonic instruments utilizing solid core technology are particularly advantageous because of the amount of ultrasonic energy that may be transmitted from the ultrasonic transducer, through a waveguide, and to the surgical end effector. Such instruments may be used for open procedures or minimally invasive procedures, such as endoscopic or laparoscopic procedures, wherein the end effector is passed through a trocar to reach the surgical site.

Activating or exciting the end effector (e.g., cutting blade) of such instruments at ultrasonic frequencies induces longitudinal vibratory movement that generates localized heat within adjacent tissue. Because of the nature of ultrasonic instruments, a particular ultrasonically actuated end effector may be designed to perform numerous functions, including, for example, cutting and coagulation. Ultrasonic vibration is induced in the surgical end effector by electrically exciting a transducer, for example. The transducer may be constructed of one or more piezoelectric or magnetostrictive elements in the instrument hand piece. Vibrations generated by the transducer are transmitted to the surgical end effector via an ultrasonic waveguide extending from the transducer to the surgical end effector. The waveguide and end effector are designed to resonate at the same frequency as the transducer. Therefore, when an end effector is attached to a transducer, the overall system frequency is the same frequency as the transducer itself.

The amplitude of the longitudinal ultrasonic vibration at the tip, d , of the end effector behaves as a simple sinusoid at the resonant frequency as given by:

$$d=A \sin(\omega t)$$

where:

ω =the radian frequency which equals 2π times the cyclic frequency, f ; and

A =the zero-to-peak amplitude.

- 5 The longitudinal excursion of the end effector tip is defined as the peak-to-peak (p-t-p) amplitude, which is just twice the amplitude of the sine wave or $2A$. Often, the end effector can comprise a blade which, owing to the longitudinal excursion, can cut and/or coagulate tissue. U.S. Pat. No. 6,283,981, which issued on Sep. 4, 2001 and is entitled METHOD OF BALANCING ASYMMETRIC ULTRASONIC SURGICAL BLADES; U.S. Pat. No. 6,309,400, which issued on Oct. 30, 2001 and is entitled CURVED ULTRASONIC BLADE HAVING A TRAPEZOIDAL CROSS SECTION; and U.S. Pat. No. 6,436,115, which issued on Aug. 20, 2002 and is entitled BALANCED ULTRASONIC BLADE INCLUDING A PLURALITY OF BALANCE ASYMMETRIES, the entire disclosures of which are hereby incorporated by reference herein, disclose various ultrasonic surgical instruments.

SUMMARY

In one general aspect, various embodiments are directed to an ultrasonic surgical instrument that comprises a transducer configured to produce vibrations along a longitudinal axis at a predetermined frequency. In various embodiments, an ultrasonic blade extends along the longitudinal axis and is coupled to the transducer. In various embodiments, the ultrasonic blade includes a body having a proximal end and a distal end, wherein the distal end is movable relative to the longitudinal axis by the vibrations produced by the transducer.

FIGURES

The features of various embodiments are set forth with particularity in the appended claims. The various embodiments, however, both as to organization and methods of operation, together with further objects and advantages thereof, may best be understood by reference to the following description, taken in conjunction with the accompanying drawings as follows.

FIG. 1 illustrates an embodiment of an ultrasonic surgical instrument system.

FIG. 1A illustrates an embodiment of an ultrasonic surgical instrument system depicting a handle comprising a switch.

FIG. 2 illustrates an embodiment of a connection union/joint for an ultrasonic instrument.

FIG. 3 is a schematic of an end effector and a wave guide of an ultrasonic surgical instrument and a representative longitudinal strain pattern and longitudinal stress pattern developed within the wave guide and end effector.

FIG. 4 is a schematic of a transducer of an ultrasonic surgical instrument and a representative longitudinal strain pattern and longitudinal stress pattern developed within the transducer.

FIG. 5 is a schematic of the end effector and wave guide illustrated in FIG. 3 and a representative longitudinal displacement pattern developed within the wave guide and end effector.

FIG. 6 is a schematic of the transducer illustrated in FIG. 4 and a representative longitudinal displacement pattern developed within the transducer.

FIG. 7 is a schematic of a transducer of an ultrasonic surgical instrument in accordance with at least one embodi-

ment and a representative longitudinal strain pattern and a representative longitudinal stress pattern developed within the transducer.

FIG. 8 illustrates an embodiment of a transducer comprising piezoelectric elements having different thicknesses.

FIG. 9 illustrates a second embodiment of a transducer comprising piezoelectric elements having different thicknesses.

FIG. 10 illustrates a third embodiment of a transducer comprising piezoelectric elements having different thicknesses.

FIG. 11 illustrates a fourth embodiment of a transducer comprising piezoelectric elements having different thicknesses.

FIG. 12 illustrates a fifth embodiment of a transducer comprising piezoelectric elements having different thicknesses.

FIG. 13 illustrates a sixth embodiment of a transducer comprising piezoelectric elements having different thicknesses.

FIG. 14 is a schematic of the work profiles that can be produced by the transducer of FIG. 8 and the transducer of FIG. 11.

FIG. 15 illustrates an embodiment of a transducer comprising piezoelectric elements having different diameters.

FIG. 16 illustrates a second embodiment of a transducer comprising piezoelectric elements having different diameters.

FIG. 16A illustrates a third embodiment of a transducer comprising piezoelectric elements having different diameters.

FIG. 17 illustrates an embodiment of a transducer comprising piezoelectric elements and deflectable straps configured to cool the piezoelectric elements.

FIG. 18 illustrates the deflectable straps of FIG. 17 being deflected by vibrations produced by the piezoelectric elements.

FIG. 19 illustrates an embodiment of a transducer comprising piezoelectric elements, deflectable straps configured to cool the piezoelectric elements, and a plurality of masses mounted to the deflectable straps.

FIG. 20 illustrates an embodiment of a wave guide, an end effector, a sheath, and flexible membranes mounted to the wave guide and the sheath configured to displace air surrounding the wave guide and end effector when the wave guide and end effector are vibrated.

FIG. 21 is an end view of the arrangement of FIG. 20.

FIG. 22A illustrates an embodiment of a transducer having a first arrangement of piezoelectric elements.

FIG. 22B illustrates the transducer of FIG. 22A having a second arrangement of piezoelectric elements.

FIG. 23A illustrates an embodiment of a transducer having a first arrangement of piezoelectric elements.

FIG. 23B illustrates the transducer of FIG. 23A having a second arrangement of piezoelectric elements.

FIG. 24 illustrates an embodiment of a transducer movably adjustable relative to a wave guide.

FIG. 25 illustrates a kit for an ultrasonic surgical instrument comprising a plurality of wave guides and end effectors.

FIG. 26 illustrates an embodiment of an ultrasonic surgical instrument.

FIG. 27 illustrates a handle of an ultrasonic surgical instrument and a proximal portion of a wave guide, wherein the handle comprises a flexible housing.

FIG. 28 illustrates the handle of FIG. 27 in a flexed condition.

FIG. 29 illustrates an end view of the handle of FIG. 27 in an unflexed condition.

FIG. 30 illustrates an end view of the handle of FIG. 27 in a flexed condition.

FIG. 31 illustrates an embodiment of a surgical instrument comprising a plurality of transducers.

FIG. 32 illustrates a second embodiment of a surgical instrument comprising a plurality of transducers.

FIG. 33 illustrates an embodiment of an integral wave guide and end effector.

FIG. 34 illustrates an embodiment of a transducer comprising piezoelectric elements assembled directly to a wave guide.

FIG. 35 illustrates an embodiment of a piezoelectric element and electrodes mounted thereto, wherein the electrodes comprise tabs extending therefrom.

FIG. 36 illustrates a transducer stack comprising a plurality of the piezoelectric elements of FIG. 35.

FIG. 37 illustrates an embodiment of a piezoelectric element and electrodes mounted thereto.

FIG. 38 illustrates a transducer stack comprising a plurality of the piezoelectric elements of FIG. 37.

FIG. 39 illustrates an end view of a transducer stack comprising piezoelectric elements, electrodes positioned intermediate the piezoelectric elements, and connecting electrodes operably connecting the intermediate electrodes.

FIG. 40 illustrates a transducer stack comprising a plurality of piezoelectric elements having a plurality of notches therein and connecting electrodes extending through the notches.

FIG. 41 illustrates an end view of the transducer stack of FIG. 40.

FIG. 42 illustrates a transducer stack comprising a plurality of piezoelectric elements having a plurality of flat surfaces and a plurality of connecting electrodes.

FIG. 43 illustrates an end view of the transducer stack of FIG. 42.

FIG. 44 illustrates a transducer stack comprising a plurality of piezoelectric elements having a plurality of indexing features configured to assure the proper alignment of the piezoelectric elements.

FIG. 45 is a schematic illustrating how the indexing features of the piezoelectric elements of FIG. 44 can prevent misalignment between the piezoelectric elements.

FIG. 46 illustrates an embodiment of a transducer stack and an enclosure surrounding the transducer stack.

FIG. 47 illustrates the enclosure of FIG. 46 in a ruptured condition and a material at least partially surrounding the transducer stack.

FIG. 48 illustrates a second embodiment of a transducer stack and an enclosure surrounding the transducer stack.

FIG. 49 is partially-sectioned plan view of a clamp coagulator depicting a clamp arm assembly in an open position.

FIG. 50 is partially-sectioned plan view of a clamp coagulator of FIG. 49 depicting the clamp arm assembly in a closed position.

FIG. 51 is a perspective view of the clamp are assembly of FIG. 49 depicting a clamp arm comprising a tissue pad.

DESCRIPTION

Before explaining various embodiments in detail, it should be noted that such embodiments are not limited in their application or use to the details of construction and arrangement of parts illustrated in the accompanying drawings and description. The illustrative embodiments may be

implemented or incorporated in other embodiments, variations and modifications, and may be practiced or carried out in various ways. For example, the surgical instruments disclosed below are illustrative only and not meant to limit the scope or application thereof. Furthermore, unless otherwise indicated, the terms and expressions employed herein have been chosen for the purpose of describing the illustrative embodiments for the convenience of the reader and are not to limit the scope thereof.

Certain exemplary embodiments will now be described to provide an overall understanding of the principles of the structure, function, manufacture, and use of the devices and methods disclosed herein. One or more examples of these embodiments are illustrated in the accompanying drawings. Those of ordinary skill in the art will understand that the devices and methods specifically described herein and illustrated in the accompanying drawings are non-limiting exemplary embodiments and that the scope of the various embodiments is defined solely by the claims. The features illustrated or described in connection with one exemplary embodiment may be combined with the features of other embodiments. Such modifications and variations are intended to be included within the scope of the claims.

Various embodiments described herein relate, in general, to ultrasonic surgical instruments and blades for use therewith. Examples of ultrasonic surgical instruments and blades are disclosed in U.S. Pat. Nos. 5,322,055; 5,954,736; 6,309,400; 6,278,218; 6,283,981; and 6,325,811, wherein the entire disclosures of which are incorporated by reference herein. Also incorporated by reference in its entirety is commonly-owned U.S. patent application Ser. No. 11/726,625, now Patent Publication No. 2008/0234710, entitled ULTRASONIC SURGICAL INSTRUMENTS, filed on Mar. 22, 2007. The disclosures of the following commonly-owned United States patent applications are incorporated herein by reference in their entirety:

(1) U.S. patent application Ser. No. 12/490,906, now U.S. Pat. No. 8,334,635, entitled TRANSDUCER ARRANGEMENTS FOR ULTRASONIC SURGICAL INSTRUMENTS, filed on Jun. 24, 2009;

(2) U.S. patent application Ser. No. 12/490,922, now U.S. Pat. No. 8,650,728, entitled ULTRASONIC SURGICAL INSTRUMENTS, filed on Jun. 24, 2009;

(3) U.S. patent application Ser. No. 12/490,933, now U.S. Pat. No. 8,344,596, entitled TRANSDUCER ARRANGEMENTS FOR ULTRASONIC SURGICAL INSTRUMENTS, filed on Jun. 24, 2009;

(4) U.S. patent application Ser. No. 12/490,948, now U.S. Pat. No. 8,319,400, entitled ULTRASONIC SURGICAL INSTRUMENTS, filed on Jun. 24, 2009; and

(5) U.S. patent application Ser. No. 13/555,523, now U.S. Pat. No. 8,546,999, entitled ULTRASONIC SURGICAL INSTRUMENTS, filed on Jun. 23, 2012.

An ultrasonic instrument and blade according to various embodiments can be of particular benefit, among others, in orthopedic procedures where it is desirable to remove cortical bone and/or tissue while controlling bleeding. Due to its cutting and coagulation characteristics, a blade of an ultrasonic surgical instrument may be useful for general soft tissue cutting and coagulation. In certain circumstances, a blade according to various embodiments may be useful to simultaneously cut and hemostatically seal or cauterize tissue. A blade may be straight or curved, and useful for either open or laparoscopic applications. A blade according to various embodiments may be useful in spine surgery, especially to assist in posterior access in removing muscle from bone.

FIG. 1 illustrates one embodiment of an ultrasonic system 10. One embodiment of the ultrasonic system 10 comprises an ultrasonic signal generator 12 coupled to an ultrasonic transducer 14, a hand piece assembly 60 comprising a hand piece housing 16, and an end effector 50. The ultrasonic transducer 14, which is known as a "Langevin stack", generally includes a transduction portion 18, a first resonator or end-bell 20, and a second resonator or fore-bell 22, and ancillary components. In various embodiments, the ultrasonic transducer 14 is preferably an integral number of one-half system wavelengths ($n\lambda/2$) in length as will be described in more detail below. An acoustic assembly 24 can include the ultrasonic transducer 14, a mount 26, a velocity transformer 28, and a surface 30.

It will be appreciated that the terms "proximal" and "distal" are used herein with reference to a clinician gripping the hand piece assembly 60. Thus, the end effector 50 is distal with respect to the more proximal hand piece assembly 60. It will be further appreciated that, for convenience and clarity, spatial terms such as "top" and "bottom" also are used herein with respect to the clinician gripping the hand piece assembly 60. However, surgical instruments are used in many orientations and positions, and these terms are not intended to be limiting and absolute.

The distal end of the end-bell 20 is connected to the proximal end of the transduction portion 18, and the proximal end of the fore-bell 22 is connected to the distal end of the transduction portion 18. The fore-bell 22 and the end-bell 20 have a length determined by a number of variables, including the thickness of the transduction portion 18, the density and modulus of elasticity of the material used to manufacture the end-bell 20 and the fore-bell 22, and the resonant frequency of the ultrasonic transducer 14. The fore-bell 22 may be tapered inwardly from its proximal end to its distal end to amplify the ultrasonic vibration amplitude of the velocity transformer 28, or, alternately, fore-bell 22 may have no amplification.

Referring again to FIG. 1, end-bell 20 can include a threaded member extending therefrom which can be configured to be threadably engaged with a threaded aperture in fore-bell 22. In various embodiments, piezoelectric elements, such as piezoelectric elements 32, for example, can be compressed between end-bell 20 and fore-bell 22 when end-bell 20 and fore-bell 22 are assembled together. Piezoelectric elements 32 may be fabricated from any suitable material, such as, for example, lead zirconate-titanate, lead meta-niobate, lead titanate, and/or any suitable piezoelectric crystal material, for example.

In various embodiments, as discussed in greater detail below, transducer 14 can further comprise electrodes, such as positive electrodes 34 and negative electrodes 36, for example, which can be configured to create a voltage potential across one or more piezoelectric elements 32. Each of the positive electrodes 34, negative electrodes 36, and the piezoelectric elements 32 can comprise a bore extending through the center which can be configured to receive the threaded member of end-bell 20. In various embodiments, the positive and negative electrodes 34 and 36 are electrically coupled to wires 38 and 40, respectively, wherein the wires 38 and 40 can be encased within a cable 42 and electrically connectable to the ultrasonic signal generator 12 of the ultrasonic system 10.

In various embodiments, the ultrasonic transducer 14 of the acoustic assembly 24 converts the electrical signal from the ultrasonic signal generator 12 into mechanical energy that results in primarily longitudinal vibratory motion of the ultrasonic transducer 24 and the end effector 50 at ultrasonic

frequencies. A suitable generator is available as model number GEN01, from Ethicon Endo-Surgery, Inc., Cincinnati, Ohio. When the acoustic assembly 24 is energized, a vibratory motion standing wave is generated through the acoustic assembly 24. A suitable vibrational frequency range may be about 20 Hz to 120 kHz and a well-suited vibrational frequency range may be about 30-70 kHz and one example operational vibrational frequency may be approximately 55.5 kHz.

The amplitude of the vibratory motion at any point along the acoustic assembly 24 may depend upon the location along the acoustic assembly 24 at which the vibratory motion is measured. A minimum or zero crossing in the vibratory motion standing wave is generally referred to as a node (i.e., where motion is usually minimal), and an absolute value maximum or peak in the standing wave is generally referred to as an anti-node (i.e., where motion is usually maximal). The distance between an anti-node and its nearest node is one-quarter wavelength ($\lambda/4$).

As outlined above, the wires 38 and 40 transmit an electrical signal from the ultrasonic signal generator 12 to the positive electrodes 34 and the negative electrodes 36. The piezoelectric elements 32 are energized by the electrical signal supplied from the ultrasonic signal generator 12 in response to a foot switch 44, for example, to produce an acoustic standing wave in the acoustic assembly 24. The electrical signal causes disturbances in the piezoelectric elements 32 in the form of repeated small displacements resulting in large compression forces within the material. The repeated small displacements cause the piezoelectric elements 32 to expand and contract in a continuous manner along the axis of the voltage gradient, producing longitudinal waves of ultrasonic energy.

In various embodiments, the ultrasonic energy produced by transducer 14 can be transmitted through the acoustic assembly 24 to the end effector 50 via an ultrasonic transmission waveguide 46. In order for the acoustic assembly 24 to deliver energy to the end effector 50, the components of the acoustic assembly 24 are acoustically coupled to the end effector 50. For example, the distal end of the ultrasonic transducer 14 may be acoustically coupled at the surface 30 to the proximal end of the ultrasonic transmission waveguide 46 by a threaded connection such as a stud 48.

The components of the acoustic assembly 24 can be acoustically tuned such that the length of any assembly is an integral number of one-half wavelengths ($n\lambda/2$), where the wavelength λ is the wavelength of a pre-selected or operating longitudinal vibration drive frequency f_d of the acoustic assembly 24, and where n is any positive integer. It is also contemplated that the acoustic assembly 24 may incorporate any suitable arrangement of acoustic elements.

The ultrasonic end effector 50 may have a length substantially equal to an integral multiple of one-half system wavelengths ($\lambda/2$). A distal end 52 of the ultrasonic end effector 50 may be disposed at, or at least near, an antinode in order to provide the maximum, or at least nearly maximum, longitudinal excursion of the distal end. When the transducer assembly is energized, in various embodiments, the distal end 52 of the ultrasonic end effector 50 may be configured to move in the range of, for example, approximately 10 to 500 microns peak-to-peak and preferably in the range of approximately 30 to 150 microns at a predetermined vibrational frequency.

As outlined above, the ultrasonic end effector 50 may be coupled to the ultrasonic transmission waveguide 46. In various embodiments, the ultrasonic end effector 50 and the ultrasonic transmission guide 46 as illustrated are formed as

a single unit construction from a material suitable for transmission of ultrasonic energy such as, for example, Ti6Al4V (an alloy of titanium including aluminum and vanadium), aluminum, stainless steel, and/or any other suitable material. Alternately, the ultrasonic end effector 50 may be separable (and of differing composition) from the ultrasonic transmission waveguide 46, and coupled by, for example, a stud, weld, glue, quick connect, or other suitable known methods. The ultrasonic transmission waveguide 46 may have a length substantially equal to an integral number of one-half system wavelengths ($\lambda/2$), for example. The ultrasonic transmission waveguide 46 may be preferably fabricated from a solid core shaft constructed out of material that propagates ultrasonic energy efficiently, such as titanium alloy (i.e., Ti6Al4V) or an aluminum alloy, for example.

In various embodiments, referring to FIG. 2, the ultrasonic transmission waveguide 46 can comprise a longitudinally projecting attachment post 54 at a proximal end to couple to the surface 30 of the acoustic assembly by a threaded connection such as the stud 48. The distal end of the ultrasonic transmission waveguide 46 may be coupled to the proximal end of the end effector 50 by an internal threaded connection, for example, preferably at or near an antinode. It is contemplated that the end effector 50 may be attached to the ultrasonic transmission waveguide 46 by any suitable means, such as a welded joint or the like, for example. Although the end effector 50 may be detachable from the ultrasonic transmission waveguide 46, it is also contemplated that the end effector 50 and the ultrasonic transmission waveguide 46 may be formed as a single unitary piece.

In various embodiments, further to the above, FIG. 2 illustrates one embodiment of a connection union/joint 70 for an ultrasonic instrument. The connection union/joint 70 may be formed between the attachment post 54 of the ultrasonic transmission waveguide 46 and the surface 30 of the velocity transformer 28 at the distal end of the acoustic assembly 24. The proximal end of the attachment post 54 comprises a female threaded substantially cylindrical recess 66 to receive a portion of the threaded stud 48 therein. The distal end of the velocity transformer 28 also may comprise a female threaded substantially cylindrical recess 68 to receive a portion of the threaded stud 48. The recesses 66, 68 are substantially circumferentially and longitudinally aligned.

In the embodiment illustrated in FIG. 1, the ultrasonic transmission waveguide 46 comprises a plurality of stabilizing silicone rings or compliant supports 56 positioned at, or at least near, a plurality of nodes. The silicone rings 56 can dampen undesirable vibration and isolate the ultrasonic energy from a sheath 58 at least partially surrounding waveguide 46, thereby assuring the flow of ultrasonic energy in a longitudinal direction to the distal end 52 of the end effector 50 with maximum efficiency.

As shown in FIG. 1, the sheath 58 can be coupled to the distal end of the handpiece assembly 60. The sheath 58 generally includes an adapter or nose cone 62 and an elongated tubular member 64. The tubular member 64 is attached to and/or extends from the adapter 62 and has an opening extending longitudinally therethrough. In various embodiments, the sheath 58 may be threaded or snapped onto the distal end of the housing 16. In at least one embodiment, the ultrasonic transmission waveguide 46 extends through the opening of the tubular member 64 and the silicone rings 56 can contact the sidewalls of the opening and isolate the ultrasonic transmission waveguide 46

therein. In various embodiments, the adapter **62** of the sheath **58** is preferably constructed from Ultem®, for example, and the tubular member **64** is fabricated from stainless steel, for example. In at least one embodiment, the ultrasonic transmission waveguide **46** may have polymeric material, for example, surrounding it in order to isolate it from outside contact.

In various embodiments, as described above, a surgical instrument can comprise a transducer configured to produce longitudinal vibrations, an end effector and/or wave guide operably coupled to the transducer, and other various acoustic assembly components which operably connect, and/or support, the transducer, wave guide, and/or end effector. In certain embodiments, as also described above, the transducer can produce vibrations which can be transmitted to the end effector, wherein the vibrations can drive the transducer, the wave guide, the end effector, and/or the other various components of the acoustic assembly at, or near, a resonant frequency. In resonance, a longitudinal strain pattern, or longitudinal stress pattern, can develop within the transducer, the wave guide, and/or the end effector, for example. In various embodiments, referring now to FIGS. **3** and **4**, such a longitudinal strain pattern, or longitudinal stress pattern, can cause the longitudinal strain, or longitudinal stress, to vary along the length of the transducer, wave guide, and/or end effector, in a sinusoidal, or at least substantially sinusoidal, manner. In at least one embodiment, for example, the longitudinal strain pattern can have maximum peaks and zero points, wherein the strain values can vary in a non-linear manner between such peaks and zero points.

In various circumstances, further to the above, the longitudinal strain, or longitudinal stress, at any given location within wave guide **146** and/or end effector **150**, for example, can be pulsed between various strain, or stress, states. Referring to FIGS. **3** and **4**, for example, the longitudinal strain within wave guide **146** at Point A can be cycled between a tensile, or positive, ϵ_{max} and a compressive, or negative, ϵ_{max} , when a cyclical voltage is supplied to the piezoelectric elements **132** of transducer **114**, for example, and especially when the system substantially comprising wave guide **146**, end effector **150**, and transducer **114** is vibrated at or near its resonant frequency. In various circumstances, the absolute values of the compressive and tensile maximum longitudinal strains can be equal, or at least substantially equal. Correspondingly, the longitudinal stress within wave guide **146** at Point A can be cycled between a tensile, or positive, σ_{max} and a compressive, or negative, σ_{max} , wherein the absolute values of the compressive and tensile maximum longitudinal stresses can be equal, or at least substantially equal. Similarly, referring to FIG. **4**, the longitudinal strain within transducer **114** at Point B can be cycled between a tensile ϵ_{max} and a compressive ϵ_{max} and the longitudinal stress can be cycled between a tensile σ_{max} and a compressive σ_{max} .

In various embodiments, as outlined above, the longitudinal strain, or longitudinal stress, within any given point within wave guide **146** and/or end effector **150** can be cycled between two values, the absolute values of which can be substantially the same. In such embodiments, the range of longitudinal strain, or longitudinal stress, incurred at a location can be evaluated as a peak-to-peak value, i.e., ϵ_{ptp} or σ_{ptp} , respectively. In at least one embodiment, although not illustrated, the voltage supplied to piezoelectric elements **132** of transducer **114** can be rectified such that the voltage is cycled between zero and a maximum voltage or, alternatively, between zero and a minimum voltage wherein, as a result, the longitudinal strain profile can be cycled between

zero and a maximum compressive strain or, alternatively, between zero and a maximum tensile strain. In any event, referring again to the longitudinal stress and longitudinal strain patterns depicted in FIG. **3**, the stress pattern is illustrated as overlapping the strain pattern. In various circumstances, however, the longitudinal stress and longitudinal strain within any given point in wave guide **146** and/or end effector **150** will not have the same magnitude. Rather, the magnitude of the stress, measured in psi, for example, may be larger, and most likely substantially larger, than the magnitude of the strain, measured in an in/in unitless dimension. In various circumstances, the stress (σ) and strain (ϵ) values can be linearly proportional and can be related by the relationship:

$$\sigma = E * \epsilon$$

wherein E comprises the modulus of elasticity of the material of the wave guide **146** and/or end effector **150**, for example, at a particular point.

In various embodiments, a longitudinal strain pattern, or longitudinal stress pattern, within transducer **116**, wave guide **146** and/or end effector **150**, as depicted in FIGS. **3** and **4**, for example, can comprise one or more zero-strain, or one or more zero-stress, points. In conjunction with FIGS. **5** and **6**, the zero-strain and zero-stress points within transducer **116**, wave guide **146**, and end effector **150** can coincide with the anti-nodes of the standing wave of vibrations within transducer **116**, wave guide **146**, and end effector **150**, wherein the anti-nodes are represented by Points AN. As the reader will recall, referring to FIGS. **5** and **6**, the anti-nodes of a standing wave of longitudinal vibrations can correspond with the maximum longitudinal vibrational displacement, i.e., δ_{max} and/or $-\delta_{max}$, for example, of the standing wave of vibrations. Furthermore, the maximum-strain and maximum-stress points within transducer **116**, wave guide **146**, and end effector **150** can coincide with the nodes of the standing wave of vibrations which are represented by points N. As the reader will also recall, referring to FIGS. **5** and **6**, the nodes of a standing wave of longitudinal vibrations can correspond with the zero longitudinal displacement points of the standing wave of vibrations. As illustrated in FIG. **3**, referring to the discussion above, Point A is at or near a node N. As also illustrated in FIG. **3**, the distal end **152** of end effector **150** is positioned at or near an antinode AN and, similarly, the proximal end of wave guide **146** is also positioned at an antinode AN. As discussed above, certain advantages can be obtained by assuring that the distal end **152** of end effector **150** is positioned at, or near, an antinode, wherein at least one such advantage can include capitalizing on the maximum longitudinal vibration displacement realized at an antinode, for example. Certain other advantages can be obtained by assuring that the proximal end of wave guide **146** is positioned at, or near, an antinode, wherein at least one such advantage can include capitalizing on the longitudinal zero strain, or longitudinal zero stress, point realized at an antinode. Similar to the above, the proximal end of wave guide **146** can comprise a connection or union joint, such as the connection joint **70** illustrated in FIG. **2**, for example, and, by placing this connection joint at or near an antinode, the joint may be exposed to little, if any, longitudinal stress or longitudinal strain induced by the standing wave of vibrations.

As described above, a voltage, or power, source can be operably coupled with one or more of the piezoelectric elements of a transducer, wherein a voltage potential applied to each of the piezoelectric elements can cause the piezo-

electric elements to expand and contract, or vibrate, in a longitudinal direction. As also described above, the voltage potential can be cyclical and, in various embodiments, the voltage potential can be cycled at a frequency which is the same as, or nearly the same as, the resonant frequency of the system of components comprising transducer 116, wave guide 146, and end effector 150, for example. In various embodiments, however, certain of the piezoelectric elements within the transducer may contribute more to the standing wave of longitudinal vibrations than other piezoelectric elements within the transducer. More particularly, a longitudinal strain profile may develop within a transducer wherein the strain profile may control, or limit, the longitudinal displacements that some of the piezoelectric elements can contribute to the standing wave of vibrations, especially when the system is being vibrated at or near its resonant frequency.

Referring now to FIG. 7, piezoelectric elements 232a, which are positioned closer to node N than the other piezoelectric elements of transducer 214, can be subjected to a larger strain, or stress, than the other piezoelectric elements of transducer 214. In various embodiments, the strain within a piezoelectric element can determine the amount of current that can flow, or be drawn through, the piezoelectric element. In certain embodiments, the strain and the current can be linearly proportional while, in other embodiments, the strain and the current can be geometrically proportional. As piezoelectric elements 232a are positioned closest to the node within transducer 214, and thus exposed to the highest strain, piezoelectric elements 232a may be able to draw more current from the power source than the other piezoelectric elements which are positioned further away from the node and exposed to lesser strains. The larger currents flowing through piezoelectric elements 232a, for example, can cause piezoelectric elements 232a to have larger longitudinal vibrations and contribute larger displacements to the standing wave of vibrations within transducer 214, and an end effector attached thereto, than the other piezoelectric elements of transducer 214 which are positioned further away from the node. In certain embodiments, the current drawn by a piezoelectric element and the longitudinal displacement of the piezoelectric element can be linearly proportional while, in other embodiments, the current and the longitudinal displacement can be geometrically proportional.

By way of example, further to the above, piezoelectric elements 232a are closer to node N than piezoelectric elements 232b and, as illustrated in FIG. 7, piezoelectric elements 232b may be subjected to less strain than piezoelectric elements 232a. As a result, in accordance with the above, piezoelectric elements 232b may draw less current than piezoelectric elements 232a. Furthermore, as the power consumed by a piezoelectric element can be defined by the product of the current flowing through the piezoelectric element and the voltage potential applied across the piezoelectric element, piezoelectric elements 232b may consume less power than piezoelectric elements 232a. Such a relationship may be especially true in embodiments in which the voltage potential across piezoelectric elements 232a and 232b is the same, or at least substantially the same. Correspondingly, piezoelectric elements 232c may draw less current and consume less power than piezoelectric elements 232b and, similarly, piezoelectric elements 232d may draw less current and consume less power than piezoelectric elements 232c.

Further to the above, piezoelectric elements which draw larger currents and consume larger quantities of power can

perform larger quantities of work. More particularly, such piezoelectric elements can create larger longitudinal displacements and/or generate larger longitudinal forces when they are vibrated and, as the work produced by a piezoelectric element can be proportional to the product of the forces and the displacements that are generated by the piezoelectric element, such piezoelectric elements can output more work. As a result of the above, piezoelectric elements which are positioned closer to a node may produce more work than piezoelectric elements which are positioned further away from the node. This may be especially true in embodiments where the piezoelectric elements of a transducer are comprised of the same material and are substantially the same size. In various embodiments, however, piezoelectric elements which consume larger quantities of power and perform larger quantities of work can generate larger quantities of heat. In at least one embodiment, as a result, the piezoelectric elements positioned closest to the node may produce more heat than piezoelectric elements which are positioned further away from the node. In various circumstances, the flow of heat away from the piezoelectric elements positioned closest to the node may be inhibited as such piezoelectric elements may be positioned intermediate adjacent piezoelectric elements which may reduce the flow of air there-around. In certain circumstances, larger quantities of heat can have a negative impact on the performance of various piezoelectric elements. For example, larger quantities of heat can produce pyroelectricity within one or more of the piezoelectric elements which can counteract the voltage potential applied thereto and/or possibly reduce the life of the piezoelectric elements.

In various embodiments, further to the above, a transducer can comprise several different piezoelectric elements, wherein the piezoelectric elements can be selected in order to equalize, or at least better distribute, the work performed by the piezoelectric elements of the transducer. In certain embodiments, piezoelectric elements positioned further away from a node may produce the same work as piezoelectric elements positioned closer to the node. In certain other embodiments, piezoelectric elements positioned further away from a node may not produce the same work as piezoelectric elements positioned closer to the node, but they may produce approximately 90%, approximately 80%, approximately 70%, approximately 60%, approximately 50%, approximately 40%, and/or approximately 30% of the work produced by piezoelectric elements positioned closer to the node. In at least one embodiment, the different piezoelectric elements can be comprised of materials which have different strain constants (d_{33}), wherein the strain constant of a material can be expressed as the ratio of the strain (ϵ) produced within a material divided by the electric field (E) experienced by the piezoelectric element. In at least one such embodiment, referring again to FIG. 7, for example, piezoelectric elements 232a can be comprised of a first material having a first strain constant and piezoelectric elements 232b can be comprised of a second material having a second strain constant, for example. In various embodiments, the first strain constant can be higher than the second strain constant. Generally, the current needed by a piezoelectric element to produce a certain amount of work can be inversely proportional to the strain constant of the piezoelectric element and, thus, selecting a material for a piezoelectric element which has a higher strain constant can reduce the current that the piezoelectric element will draw and, correspondingly, reduce the heat that the piezoelectric element will produce. Correspondingly, selecting a material for a piezoelectric element which has a lower strain constant

can increase the current required to produce a certain amount of work, and thus increase the heat that the piezoelectric element will produce.

Further to the above, the work produced by the piezoelectric elements of a transducer can be balanced, or at least more evenly balanced, by utilizing piezoelectric elements comprised of a material having a higher strain constant closer to a node and utilizing piezoelectric elements comprised of a material having a lower strain constant further away from the node. In various embodiments, piezoelectric elements **232a** can be comprised of a first material having a first strain constant, piezoelectric elements **232b** can be comprised of a second material having a second strain constant, piezoelectric elements **232c** can be comprised of a third material having a third strain constant, and piezoelectric elements **232d** can be comprised of a fourth material having a fourth strain constant, wherein, in at least one embodiment, the first strain constant can be larger than the second strain constant, the second strain constant can be larger than the third strain constant, and the third strain constant can be larger than the fourth strain constant. In various embodiments, the strain constants of the piezoelectric elements can range between approximately $100 \text{ e}^{-12} \text{ m/V}$ and approximately $600 \text{ e}^{-12} \text{ m/V}$, and/or between approximately $150 \text{ e}^{-12} \text{ m/V}$ and approximately $500 \text{ e}^{-12} \text{ m/V}$, and/or between approximately $150 \text{ e}^{-12} \text{ m/V}$ and approximately $350 \text{ e}^{-12} \text{ m/V}$, for example. In any event, owing to the selection of materials for the piezoelectric elements, referring again to FIG. 7, piezoelectric elements **232b** may produce the same quantity of work as, or at least a large fraction of, the work produced by piezoelectric elements **232a**, for example, and, similarly, piezoelectric elements **232c** may produce the same quantity of work as, or at least a large fraction of, the work produced by piezoelectric elements **232b**, for example. Likewise, piezoelectric elements **232d** may produce the same quantity of work as, or at least a large fraction of, the work produced by piezoelectric elements **232c**.

In various embodiments, as a result of the above, the heat generated by the piezoelectric elements of a transducer can be balanced, or at least more evenly balanced, such that the heat is generated evenly, or at least more evenly, throughout the transducer. Such embodiments can prevent, or at least reduce the possibility of, an undesirable quantity of heat from being generated and/or retained within a single, or centralized, location within the transducer, for example. In certain circumstances, as a result of the above, piezoelectric elements **232b** may generate the same quantity of heat as, or at least a large fraction of, the heat generated by piezoelectric elements **232a**, for example, and, similarly, piezoelectric elements **232c** may generate the same quantity of heat as, or at least a large fraction of, the heat generated by piezoelectric elements **232b**, for example. Likewise, piezoelectric elements **232d** may generate the same quantity of heat as, or at least a large fraction of, the heat generated by piezoelectric elements **232c**. In at least one such embodiment, the heat generated and/or retained by the piezoelectric elements can be evenly distributed, or at least more evenly distributed, within the transducer **214**. In various embodiments, the additional heat generated and/or retained within piezoelectric elements **232d**, for example, can be more easily drawn into distal end member **222** and/or proximal end member **220**, for example, such that the heat can be more easily dissipated from transducer **214**. In certain embodiments, end members **220** and **222** can comprise heat sinks which can draw heat away from the piezoelectric elements, wherein, in at least one embodiment, end members **220** and **222** can be

comprised of metal, for example. In such embodiments, the possibility of the piezoelectric elements becoming overheated can be reduced.

In various alternative embodiments, it may be desirable to utilize piezoelectric elements comprised of a material having a lower strain constant closer to a node and piezoelectric elements comprised of a material having a higher strain constant further away from the node. In various embodiments, piezoelectric elements **232a** can be comprised of a first material having a first strain constant, piezoelectric elements **232b** can be comprised of a second material having a second strain constant, piezoelectric elements **232c** can be comprised of a third material having a third strain constant, and piezoelectric elements **232d** can be comprised of a fourth material having a fourth strain constant, wherein, in at least one embodiment, the first strain constant can be smaller than the second strain constant, the second strain constant can be smaller than the third strain constant, and the third strain constant can be smaller than the fourth strain constant.

In certain embodiments, further to the above, the heat generated by the piezoelectric elements of a transducer can be balanced, or at least more evenly balanced, by utilizing materials having different dielectric dissipation or dampening properties. In various circumstances, the dielectric dissipation of a material can be expressed as the measure of the loss-rate of power of a mode of oscillation in a dissipative system. Stated another way, in certain circumstances, the dielectric dissipation of a material can represent the energy dissipation, or losses, that can occur within a vibrating piezoelectric element, and/or transducer, wherein such dissipation, or losses, can result in heat generation. In any event, in various embodiments, different materials can be utilized which have larger and/or smaller dissipative or dampening qualities, wherein materials having smaller dissipative or dampening qualities may generate less heat, for example. In at least one embodiment, piezoelectric elements comprised of materials having smaller dissipative qualities can be positioned closer to a node whereas piezoelectric elements comprised of materials having larger dissipative qualities can be positioned further away from a node. In various embodiments, the dielectric dissipation factor of the piezoelectric materials of a transducer can range between approximately 0.002 and approximately 0.01, for example.

In certain embodiments, further to the above, the work generated by the piezoelectric elements of a transducer can be balanced, or at least more evenly balanced, by utilizing materials having different dielectric constants. In various embodiments, piezoelectric elements comprised of materials having a lower dielectric constant may be able to produce more work than piezoelectric elements having a higher dielectric constant. In at least one embodiment, as a result, piezoelectric elements **232a** can be comprised of a first material having a first dielectric constant, piezoelectric elements **232b** can be comprised of a second material having a second dielectric constant, piezoelectric elements **232c** can be comprised of a third material having a third dielectric constant, and piezoelectric elements **232d** can be comprised of a fourth material having a fourth dielectric constant, wherein, in at least one embodiment, the first dielectric constant can be larger than the second dielectric constant, the second dielectric constant can be larger than the third dielectric constant, and the third dielectric constant can be larger than the fourth dielectric constant. In various embodiments, further to the above, the relative dielectric constants of the piezoelectric materials can range between approximately 900 and approximately 1200, for example, wherein

the relative dielectric constant of a material (ϵ_r) can be defined as the static permittivity of the material (ϵ_s) divided by the permittivity constant (ϵ_0). In any event, owing to the selection of materials for the piezoelectric elements, referring again to FIG. 7, piezoelectric elements **232b** may produce the same quantity of work as, or at least a large fraction of, the work produced by piezoelectric elements **232a**, for example, and, similarly, piezoelectric elements **232c** may produce the same quantity of work as, or at least a large fraction of, the work produced by piezoelectric elements **232b**, for example. Likewise, piezoelectric elements **232d** may produce the same quantity of work as, or at least a large fraction of, the work produced by piezoelectric elements **232c**.

In certain embodiments, further to the above, the work generated by the piezoelectric elements of a transducer can be balanced, or at least more evenly balanced, by utilizing materials having different voltage sensitivities. In various embodiments, piezoelectric elements comprised of materials having a higher voltage sensitivity may be able to produce more work than piezoelectric elements having a lower voltage sensitivity. In at least one embodiment, as a result, piezoelectric elements **232a** can be comprised of a first material having a first voltage sensitivity, piezoelectric elements **232b** can be comprised of a second material having a second voltage sensitivity, piezoelectric elements **232c** can be comprised of a third material having a third voltage sensitivity, and piezoelectric elements **232d** can be comprised of a fourth material having a fourth voltage sensitivity, wherein, in at least one embodiment, the first voltage sensitivity can be smaller than the second voltage sensitivity, the second voltage sensitivity can be smaller than the third voltage sensitivity, and the third voltage sensitivity can be smaller than the fourth voltage sensitivity. In various embodiments, the voltage sensitivity of a piezoelectric material can be defined as the responsiveness, or change in shape, of the material to a voltage potential, wherein piezoelectric materials having a higher voltage sensitivity may require less voltage to produce larger displacements within the material. In any event, owing to the selection of materials for the piezoelectric elements, referring again to FIG. 7, piezoelectric elements **232b** may produce the same quantity of work as, or at least a large fraction of, the work produced by piezoelectric elements **232a**, for example, and, similarly, piezoelectric elements **232c** may produce the same quantity of work as, or at least a large fraction of, the work produced by piezoelectric elements **232b**, for example. Likewise, piezoelectric elements **232d** may produce the same quantity of work as, or at least a large fraction of, the work produced by piezoelectric elements **232c**.

As discussed above, referring again to FIG. 7, the piezoelectric elements of a transducer which are positioned closer to a node may generate and/or retain more heat than the piezoelectric elements of a transducer which are positioned further away from a node. As also discussed above, the materials of the piezoelectric elements can be selected such that the heat produced and/or retained by the piezoelectric elements can be leveled, or at least better leveled, across the transducer. In various circumstances, however, heat generation and/or retention may be centralized within the piezoelectric elements near the node. In various embodiments, as discussed in greater detail below, the piezoelectric elements of a transducer can be comprised of different materials having different Curie temperatures (T_c). The Curie temperature of piezoelectric materials can be described as the temperature above which a piezoelectric material may lose its polarization and piezoelectric characteristics. In various

circumstances, as a result, it may be desirable that the temperatures of the piezoelectric materials do not exceed their Curie temperatures.

In various embodiments, especially in embodiments where there is a large thermal gradient in the transducer between the piezoelectric elements **232a** at the center, or node, of the transducer stack and the piezoelectric elements **232d** at the ends, or antinodes, of the transducer stack, the piezoelectric elements positioned closer to the node can be comprised of a material having a higher Curie temperature than the Curie temperature of the piezoelectric elements positioned further away from the node. In at least one embodiment, piezoelectric elements **232a** can be comprised of a first material having a first Curie temperature, piezoelectric elements **232b** can be comprised of a second material having a second Curie temperature, piezoelectric elements **232c** can be comprised of a third material having a third Curie temperature, and piezoelectric elements **232d** can be comprised of a fourth material having a fourth Curie temperature, wherein, in at least one embodiment, the first Curie temperature can be larger than the second Curie temperature, the second Curie temperature can be larger than the third Curie temperature, and the third Curie temperature can be larger than the fourth Curie temperature. In at least one such embodiment, for example, piezoelectric elements **232a** and/or **232b**, for example, can be comprised of (K, Na)NbO₃, which is commonly-referred to as sodium potassium niobate or "KNN" and has a Curie temperature of approximately 410° C. Further to the above, piezoelectric elements **232a** and/or **232b** can be comprised of Bi₄Ti₃O₁₂, which is commonly-referred to as "BTO" and has a Curie temperature of approximately 280° C., and/or (Bi, Na)TiO₃—(Bi, K)TiO₃—(Ba, Sr)TiO₃, which is commonly-referred to as "BNBK" and has a Curie temperature of approximately 675° C., and/or any suitable high T_c lead-free piezoelectric material, for example. In addition to the above, piezoelectric elements **232c** and/or **232d**, for example, can be comprised of BaTiO₃, which is commonly-referred to as barium titanate and has a Curie temperature of approximately 110° C., and/or any suitable low T_c lead-free piezoelectric material, for example. In at least one embodiment, piezoelectric elements **232a** can be comprised of BNBK (T_c =675° C.), piezoelectric elements **232b** can be comprised of KNN (T_c =410° C.), piezoelectric elements **232c** can be comprised of BTO (T_c =280° C.), and piezoelectric elements **232d** may be comprised of barium titanate (T_c =110° C.), for example. Although such arrangements may be useful in various circumstances, each of the piezoelectric elements within a transducer stack can be comprised of one or more of any of the materials mentioned herein.

In various embodiments, further to the above, the first piezoelectric elements **232a** having a first Curie temperature can draw a first current, the second piezoelectric elements **232b** having a second Curie temperature can draw a second current, wherein the first current can be larger in magnitude than the second current. Owing to a higher first Curie temperature, the first, or higher, current may not detrimentally overheat the first piezoelectric elements **232a** and, similarly, the second, or lower, current may not detrimentally overheat the second piezoelectric elements **232b**. In at least one such embodiment, the third piezoelectric elements **232c** can draw a third current which has a lower magnitude than the second current and, in addition, the fourth piezoelectric elements **232d** can draw a fourth current which has a lower magnitude than the third current.

In various embodiments, referring now to FIGS. 8-13, piezoelectric elements having different thicknesses can be

utilized to distribute the work produced by, and the current drawn by, the piezoelectric elements of a transducer. Referring to FIG. 8, transducer 314a, for example, can comprise four piezoelectric elements 332 having a first thickness and four piezoelectric elements 333 having a second thickness, for example, wherein the second thickness is larger than the first thickness. In such embodiments, piezoelectric elements 332 and 333 can be arranged such that the work produced by the piezoelectric elements can generate a work profile as illustrated in FIG. 14. Referring to FIGS. 8 and 14, the thicker piezoelectric elements 333 are positioned closer to node N than the thinner piezoelectric elements 332 wherein, owing to the arrangement of piezoelectric elements 332 and 333 and the longitudinal stress profile $\epsilon(l)$ generated within the transducer, the work produced by the piezoelectric elements may not be distributed evenly across the piezoelectric elements. In fact, referring to FIG. 14, the work produced by the transducer may be heavily concentrated in the large piezoelectric elements 333 positioned proximate to the node N. Correspondingly, the thinner piezoelectric elements 332 of transducer 314 may produce far less work than piezoelectric elements 333 as they are positioned further away from node N and closer to antinodes AN and, as a result, are subjected to less longitudinal strain.

In various embodiments, referring now to transducers 314b, 314c, 314e, and 314f illustrated in FIGS. 9, 10, 12, and 13, respectively, piezoelectric elements 332 and 333 can be stacked in different arrangements, wherein the different arrangements can produce different work profiles. In various embodiments, further to the above, the piezoelectric elements of a transducer can be arranged such that the work profile produced by the piezoelectric elements is level across the transducer, or at least more closely approximating a level work profile than the work profile produced by transducer 314a, for example. In at least one embodiment, referring now to FIG. 11, transducer 314d, similar to the above, can comprise four piezoelectric elements 332 and four piezoelectric elements 333, for example. In such embodiments, piezoelectric elements 332 and 333 of transducer 314d can be arranged such that the work produced by the piezoelectric elements may generate a work profile as illustrated in FIG. 14. More particularly, referring to FIGS. 11 and 14, the thinner piezoelectric elements 332 of transducer 314d are positioned closer to node N than the thicker piezoelectric elements 333 wherein, owing to the arrangement of piezoelectric elements 332 and 333, the work produced by the piezoelectric elements of transducer 314d may be more evenly distributed across the piezoelectric elements. By way of comparison, the large concentration, or peak, of work centralized around node N that may be produced by transducer 314a may be noticeably larger than the less-pronounced concentration of work centralized around node N that may be produced by transducer 314d. Furthermore, by way of comparison, the thicker piezoelectric elements 333 positioned at the ends of the transducer stack of transducer 314d may produce more work than the thinner piezoelectric elements 332 positioned at the ends of the transducer stack of transducer 314a, thereby further leveling the work profile of transducer 314d.

While it is possible that the work profiles illustrated in FIG. 14 may represent the actual work profiles of various transducers, such work profiles have been provided for the purposes of demonstration and discussion. Various other work profiles may be possible. Referring to FIG. 14, the reader will note that the horizontal axis is marked with the numbers 1-8 which represent the eight piezoelectric elements of the exemplary embodiments of transducers 314a

and 314d, for example. More particularly, the number 1 may represent the first, or most proximal, piezoelectric element, the number 2 may represent the second, or second-most proximal, piezoelectric element, and so forth. The reader will also note that the vertical axis is marked with percentage values. Such percentage values represent the current that a particular piezoelectric element may draw as compared to the total current drawn by the transducer. For example, the first piezoelectric element of transducer 314a may draw approximately 10.5% of the total current drawn by transducer 314a while the first piezoelectric element of transducer 314d may draw approximately 11.5% of the total current drawn by transducer 314d. In various embodiments, in view of the above, if the percentages of current drawn by each piezoelectric element of transducer 314a were summed, the result should total 100%. Similarly, the percentages of the current drawn by each piezoelectric element of transducer 314d, when summed, should also total 100%.

In various embodiments, as outlined above, the longitudinal strain profile produced by the standing wave of vibrations within a transducer can be sinusoidal, wherein the longitudinal strain can vary in a non-linear or geometric manner between first and second values. In certain embodiments, referring once again to FIG. 8, the strain profile $\epsilon(l)$ within transducer 314a can be represented by a half-sine wave extending between two antinodes AN of the standing wave of vibrations, for example, although other embodiments are envisioned in which any suitable number of antinodes can be located within a transducer. Alternatively, embodiments are envisioned in which no antinodes are located within a transducer. In any event, as also outlined above, the maximum longitudinal strain of the strain profile $\epsilon(l)$ can occur at the node N of the standing wave of vibrations, wherein the piezoelectric elements positioned closest to node N, such as piezoelectric elements 333₃ and 333₄ of transducer 314a, for example, can be subjected to the most longitudinal strain. For example, referring to FIG. 8, piezoelectric elements 333₃ and 333₄ are positioned just to the left of, or proximal with respect to, node N, wherein the element 333₄ is subjected to a longitudinal strain ϵ_4 and the element 333₃ is subjected to a longitudinal strain ϵ_3 , wherein strain ϵ_4 is less than ϵ_{max} and wherein strain ϵ_3 is less than strain ϵ_4 . For the purposes of this example, longitudinal strain ϵ_4 can represent the average strain across piezoelectric element 333₄ and longitudinal strain ϵ_3 can represent the average strain across piezoelectric element 333₃. Correspondingly, referring again to FIG. 8, longitudinal strain ϵ_3 and longitudinal strain ϵ_4 are illustrated as occurring in the center of the piezoelectric elements 333₃ and 333₄, respectively. In any event, further to the above, strain ϵ_3 and strain ϵ_4 may allow piezoelectric elements 333₃ and 333₄ to contribute larger quantities of work than the piezoelectric elements 332₂ and 332₁ positioned proximally with respect to piezoelectric elements 333₃ and 333₄, wherein piezoelectric elements 332₂ and 332₁ are subjected to longitudinal strain ϵ_2 and longitudinal strain ϵ_1 , respectively. Similar to the above, strains ϵ_2 and ϵ_1 can represent the average longitudinal strains experienced across piezoelectric elements 332₂ and 332₁, for example.

Further to the above, referring again to FIG. 8, longitudinal strain ϵ_2 is less than longitudinal strain ϵ_3 and, in addition, longitudinal strain ϵ_1 is less than strain ϵ_2 and significantly less than strain ϵ_4 . Such a relationship is due to the sinusoidal nature, or shape, of the strain profile $\epsilon(l)$. Owing to such a shape, more particularly, the longitudinal strain induced within the transducer can decrease in a geometric, or non-linear, manner with respect to node N and,

as a result, the strain profile within the transducer can experience larger changes in longitudinal strain at locations further away from node N, and/or locations closer to an antinode AN. As a result, piezoelectric elements positioned further away from the node N may be subjected to significantly less longitudinal strain and may be less capable of producing larger quantities of work. In order to better balance the work distribution of the piezoelectric elements of a transducer, referring once again to FIG. 11, the piezoelectric elements can be arranged such that the differences in average longitudinal strain experienced across the piezoelectric elements can be reduced. In at least one comparative example, referring to FIGS. 8 and 11, the piezoelectric elements of transducer 314d can be arranged such that the distance B11 between the node N and the center of piezoelectric element 333₁ of transducer 314d is less than the distance A11 between the node N and the center of piezoelectric element 332₁ of transducer 314a. Owing to the fact that distance B11 is shorter than distance A11, the average longitudinal strain experienced within, and the work produced by, piezoelectric element 333₁ of transducer 314d may be greater than the average strain experienced within, and the work produced by, piezoelectric element 332₁ of transducer 314a. Owing to the increase in work that piezoelectric element 333₁ of transducer 314d can provide, the difference in work produced by piezoelectric element 333₁ and piezoelectric element 332₄ of transducer 314d can be less than the difference in work produced by piezoelectric elements 332₁ and piezoelectric element 333₄ of transducer 314a, for example.

Further to the above, referring again to FIGS. 8 and 11, the distance B12 between the node N and the center of piezoelectric element 333₂ of transducer 314d is less than the distance A12 between the node N and the center of piezoelectric element 332₂ of transducer 314a. Owing to the fact that distance B12 is shorter than distance A12, similar to the above, the average strain experienced within, and work produced by, piezoelectric element 333₂ of transducer 314d may be greater than the average strain experienced within, and the work produced by, piezoelectric element 332₂ of transducer 314a. Owing to the increase in work that piezoelectric element 333₂ of transducer 314d can provide, similar to the above, the difference in work produced by piezoelectric element 333₂ and piezoelectric element 332₄ of transducer 314d can be less than the difference in work produced by piezoelectric elements 332₂ and piezoelectric element 333₄ of transducer 314a, for example. Similarly, distance B13 can be shorter than distance A13 with regard to the third piezoelectric element and, in addition, distance B14 can be shorter than distance A14 with regard to the fourth piezoelectric element, i.e., the element positioned closest to node N. As illustrated in FIGS. 8 and 11, the other piezoelectric elements of transducers 314a and 314d, i.e., elements 333₅, 333₆, 332₇, and 332₈ of transducer 314a and elements 332₅, 332₆, 333₇, and 333₈ of transducer 314d, can be arranged in a corresponding, or mirror-image, manner, wherein the above-provided discussion is adaptable with respect to these elements with regard to node N and the second, or opposite, antinode AN. In any event, referring once again to FIG. 14, the work produced by the piezoelectric elements across the transducer can be leveled, or at least more closely leveled, by arranging the piezoelectric elements such that the average strain that each element is subjected to is the same, or closer to being same.

In various embodiments, further to the above, piezoelectric elements which are subjected to larger average longitudinal strains can produce larger amplitudes of longitudinal

vibrations, especially in thicker piezoelectric elements, i.e., piezoelectric elements which are thicker in the longitudinal direction. In various circumstances, the longitudinal strain of a piezoelectric element can be defined as the change in thickness (Δt) of the piezoelectric element divided by its original, or unenergized, thickness (t_0) and, when the longitudinal strain within the piezoelectric element is dictated by the generated strain field within a resonating transducer, the utilization of thicker piezoelectric elements may demand that larger longitudinal displacements occur within the piezoelectric elements in order for the relative ratio of ($\Delta t/t_0$) to be maintained. Stated another way, for a given longitudinal strain value, a larger (t_0) may dictate a larger Δt and, correspondingly, a smaller (t_0) may dictate a smaller Δt . As outlined above, referring again to FIG. 11, the thicker piezoelectric elements 333 of transducer 314d are positioned further away from node N than piezoelectric elements 332 and, although the thicker elements 333 may be subjected to a smaller average strains than the thinner elements 332, the thickness of piezoelectric elements 333 may compensate for the smaller average strains and may still provide sufficient longitudinal displacements, or vibrations, and produce sufficient quantities of work such that the work profile produced by transducer 314d is level, or at least closer to being level. Although not illustrated, various piezoelectric elements can be used within a transducer wherein the piezoelectric elements can have a variety of different thicknesses, and wherein, in certain embodiments, a transducer can comprise piezoelectric elements having three or more different thicknesses. In certain embodiments, also not illustrated, a transducer can comprise piezoelectric elements wherein the thickest piezoelectric elements are positioned on the ends of the transducer stack, the thinnest piezoelectric elements are positioned in the middle of the stack, and piezoelectric elements having an intermediate thickness are positioned therebetween such that the thicknesses of these piezoelectric elements are arranged in a descending order towards the middle of the stack, for example.

Further to the above, referring again to FIGS. 8-13, the piezoelectric elements of a transducer can have the same, or at least substantially the same, width, height, and/or diameter. In certain other embodiments, referring now to FIG. 15, a transducer, such as transducer 414, for example, can comprise piezoelectric elements having different widths, heights, and/or diameters. More particularly, in at least one embodiment, transducer 414 can comprise first piezoelectric elements 432a having a first diameter, second piezoelectric elements 432b having a second diameter, third piezoelectric elements 432c having a third diameter, and fourth piezoelectric elements 432d having a fourth diameter. In such embodiments, the first, second, third, and/or fourth piezoelectric elements can have different capacitances owing to their different diameters. More particularly, as discussed above, each piezoelectric element can comprise electrodes placed on the opposite sides of the piezoelectric element in order to generate a voltage, or electric, potential across the element, wherein, owing to the directly proportional relationship between the surface area of the electrodes and the potential capacitance of a piezoelectric element, piezoelectric elements having larger diameters can comprise electrodes having larger surface areas and, thus, can generate larger capacitances within the larger piezoelectric elements. In various circumstances, the directly proportional relationship between the surface area of the electrodes and the capacitance of the piezoelectric element can be linear, or at least substantially linear, although embodiments having a geometric relationship are contemplated. Furthermore,

owing to the directly proportional relationship between the capacitance of a piezoelectric element and the current flowing through the piezoelectric element, the larger piezoelectric elements having larger capacitances can draw larger currents and, thus, perform larger quantities of work. In various circumstances, the directly proportional relationship between the capacitance and the current flowing through the piezoelectric element can be linear, or at least substantially linear, although embodiments having a geometric relationship are contemplated. In certain circumstances, the capacitance of a piezoelectric element can be represented by the relationship provided below:

$$C=(K*\epsilon_0*A)/t$$

wherein K represents the dielectric constant of the piezoelectric element material, wherein ϵ_0 represents the permittivity of air, wherein A represents the surface area of the electrodes, and wherein t represents the thickness of the piezoelectric element between the electrodes.

Referring once again to FIG. 15, the diameter of piezoelectric elements 432a of transducer 414 can be constant, or at least substantially constant, across the thickness thereof. Similarly, the diameters of piezoelectric elements 432b, 432c, and/or 432d can be constant, or at least substantially constant, across the thicknesses thereof. In at least one embodiment, such piezoelectric elements can comprise first and second electrodes which are positioned on opposite sides thereof which have the same, or at least substantially the same, diameter. In various alternative embodiments, the diameter of one or more piezoelectric elements of a transducer may not be constant across the thickness thereof. In at least one such embodiment, referring now to FIG. 16, transducer 514 can comprise a piezoelectric element 532a, for example, which can comprise a first diameter 531 and a second diameter 535, wherein the second diameter 535 can be larger than the first diameter 531. As illustrated in FIG. 16, the diameter of piezoelectric element 532a can decrease between the larger second diameter 535 and the smaller first diameter 531. In various embodiments, the diameter of piezoelectric element 532a can decrease in a linear, or an at least substantially linear, manner, although other changes in diameter are contemplated, such as non-linear or geometric decreases, for example.

Further to the above, first and second electrodes can be attached to the sides of piezoelectric elements 532a, wherein the first electrode can have the same diameter, or at least substantially the same diameter, as first diameter 531, and wherein the second electrode can have the same diameter, or at least substantially the same diameter, as second diameter 535. Owing to the different diameters and/or areas, A, of the first and second electrodes, in various embodiments, the capacitance, C, of piezoelectric element 532a can be such that the work produced by piezoelectric element 532a is consistent with a desired work profile. In certain embodiments, transducer 514 can further comprise piezoelectric elements 532b, 532c, and/or 532d, wherein the diameters of these piezoelectric elements can also decrease between first and second diameters. In at least one embodiment, referring again to FIG. 16, the diameters of the piezoelectric elements of transducer 514 can decrease at a constant, or at least substantially constant, rate between the largest diameters of piezoelectric elements 532d and the smallest diameters of piezoelectric elements 532a. In various embodiments, referring now to FIG. 16A, the diameters of the piezoelectric elements of transducer 2714 can increase at a constant, or at least substantially constant, rate between the smallest diameters of piezoelectric elements 2732d and the largest diam-

eters of piezoelectric elements 2732a. Although not illustrated, other embodiments are envisioned in which the diameters of the piezoelectric elements increase and/or decrease in a non-linear manner and/or have any other suitable profile. In any event, similar to the above, the larger and smaller diameters of piezoelectric elements 532a, 532b, 532c, and/or 532d can be arranged such the capacitances, C, of the piezoelectric elements result in a desired work profile. More particularly, as outlined above, larger electrodes can be associated with the larger diameters of the piezoelectric elements as compared to the smaller electrodes associated with the smaller diameters, wherein the larger electrodes can be positioned closer to an antinode AN and, as a result, can provide for a more even distribution of work across the work profile. In various other embodiments, referring again to FIG. 16A, the largest diameters of piezoelectric elements 2732a, 2732b, 2732c, and 2732d can be positioned closer to a node so as to capitalize on larger strain values within the strain profile.

In various embodiments, as outlined above, the piezoelectric elements of a transducer can generate heat, wherein, in some circumstances, excessive heat may affect the performance of the piezoelectric elements. In certain embodiments, a transducer can comprise a pump. Referring to FIGS. 17 and 18, transducer 614 can comprise one or more straps, or ribbons, 617 which can be configured to pump air around one or more piezoelectric elements 632 of transducer 614 when transducer 614 is actuated as also outlined above. In at least one such embodiment, piezoelectric elements 632 can be positioned intermediate end-bell 620 and fore-bell 622, wherein, although not illustrated in FIG. 17, end-bell 620 and fore-bell 622 can be fastened together so as to capture and/or compress piezoelectric elements 632 therebetween. In certain circumstances, one or more straps 617 can be mounted to end-bell 620 and fore-bell 622 wherein, in at least one embodiment, straps 617 can be mounted to end-bell 620 and fore-bell 622 after end-bell 620 and fore-bell 622 have been bolted together. In at least one embodiment, transducer 614 can comprise four straps 617 which can be welded, and/or otherwise suitably fastened, to end-bell 620 and fore-bell 622, wherein the straps 617 can be positioned equidistantly, or at least substantially equidistantly, around the perimeter of the transducer. Although straps 617 are illustrated as being rectangular and having a constant thickness, straps 617 can have any suitable shape and/or a non-constant thickness. In various embodiments, referring to FIG. 17, gaps 637 can be defined between straps 617 and piezoelectric elements 632 such that, when straps 617 deflect, as described in greater detail below, straps 617 do not contact piezoelectric elements 632.

In various circumstances, referring to FIG. 18, the vibrations produced by piezoelectric elements 632 can cause straps 617 to vibrate and deflect. The deflections of straps 617 can displace the air surrounding straps 617, such as the air located intermediate straps 617 and piezoelectric elements 632, for example, and cause the air to flow over the piezoelectric elements. In various circumstances, the air flowing over the piezoelectric elements 632 can be, at least initially, cooler than the piezoelectric elements 632 such that the air can absorb heat from the piezoelectric elements 632. In certain embodiments, the transducer 614 can be positioned within a handle of a surgical instrument, wherein the handle can include one or more air vents which can allow the warmed air to be exhausted from the handle and allow cooler air to enter the handle and further cool the piezoelectric elements 632. In certain embodiments, a fan having one or more fan blades can be positioned within the handle in order

to assist in moving the cooler air around the piezoelectric elements and/or move the heated air out of the handle. In various embodiments, referring again to FIG. 18, straps 617 can be configured to vibrate or deflect in one or more directions. In at least one embodiment, straps 617 can be configured to deflect in a direction which is transverse to longitudinal axis 699 such that straps 617 pump air in a radial, or at least substantially radial, direction over the piezoelectric elements. In certain embodiments, straps 617 can be configured to deflect in directions which are perpendicular, parallel, and/or skew with respect to longitudinal axis 699. In certain embodiments, straps 617 can be configured to produce a laminar flow of air over piezoelectric elements 632, and/or a turbulent flow of air, depending on the geometry and the surface conditions of the piezoelectric elements. In various embodiments, straps 617 can be comprised of metal, such as copper or brass, for example, wherein straps 617 can be configured to conduct heat between end-bell 620 and fore-bell 622. In at least one such embodiment, heat can flow from one end of transducer 614 to the other end such that the heat stored within transducer 614 can be spread evenly, or at least substantially evenly, throughout transducer 614.

In various embodiments, as outlined above, the piezoelectric elements 626 of transducer 614 can generate longitudinal vibrations which can cause straps, or ribbons, 617 to vibrate and deflect. In certain circumstances, piezoelectric elements 626, for example, can generate vibrations which are transverse or perpendicular to longitudinal axis 699, for example, which can cause straps 617 to vibrate and deflect. In such circumstances, fairly large deflections of straps 617 can occur. In certain embodiments, however, straps 617 may not deflect a sufficient amount to produce a desired air flow. In at least one embodiment, referring now to FIG. 19, one or more weights, or masses, 739 can be mounted to one or more straps 717 which can be configured to cause an eccentricity, or imbalance, within straps 717. Owing to such an imbalance, the vibrations produced by the piezoelectric elements 732 of transducer 714 can be amplified, at least initially, to create larger deflections within straps 717. Stated another way, masses 739 can "kick-off" the deflections of straps 717. In various circumstances, the additional weight of the masses can cause larger deflections of straps 717 throughout the duration in which transducer 714 is operated. In at least one embodiment, masses 739 can comprise, or at least approximate, point masses which do not stiffen, or at least substantially stiffen, straps 717. In any event, each strap 717 can include one or more masses mounted thereto or, in certain other embodiments, some straps 717 can include one or more masses mounted thereto while some straps 717 may not have any straps mounted thereto at all. In certain embodiments, masses 739 can be welded to straps 717 and, in various embodiments, masses 739 can be adhered to and/or fastened to straps 717.

In various embodiments, as outlined above, an ultrasonic surgical instrument can comprise a cable configured to supply current to the transducer of the surgical instrument. In certain embodiments, the cable can be configured to conduct heat away from the transducer and/or a handpiece of the surgical instrument in which the transducer is positioned. In at least one embodiment, the cable can comprise several layers. For example, in at least one such embodiment, a cable can comprise an inner core, an outer core, a first insulative layer positioned intermediate the inner core and the outer core, a second insulative layer surrounding the second insulative layer, and an outer insulative layer. The

inner core and the outer core can be configured to conduct current to and from the transducer, wherein the first and second insulative layers can be configured to prevent current from leaking therefrom. The thermally conductive material can be configured to draw heat out of the transducer, and/or handpiece, and conduct the heat out of the surgical instrument. In certain circumstances, the conductive material can act as a heat sink and, in at least one embodiment, the conductive material can be comprised of aluminum. In any event, the outer insulative layer can be configured to protect a surgeon, for example, from touching the hot conductive material during use.

In various embodiments, as discussed above, the vibrations produced by a transducer of an ultrasonic instrument can be transmitted to a wave guide, such as wave guide 46, for example, and an end effector, such as end effector 50, for example. Owing to such vibrations, especially when the wave guide and end effector are driven at resonance, the wave guide and end effector may generate and store heat, especially at the nodes of the standing wave of vibrations. In some circumstances, such localized heat generation may be useful. In various circumstances, however, it may be desirable to distribute the heat generated within the wave guide and/or end effector such that the heat is not localized, or at least less localized, in one or more locations. In various embodiments, referring to FIGS. 20 and 21, a surgical instrument can comprise a wave guide 846, an end effector 850, and a sheath, such as 841, for example, which can be configured to surround, or at least partially surround, a portion of wave guide 846 and end effector 850. In certain embodiments, a surgical instrument can comprise a pump configured to move air along a wave guide and/or end effector. In at least one embodiment, the surgical instrument can further include one or more membranes, or diaphragms, extending between sheath 841 and wave guide 846, and/or between sheath 841 and end effector 850. In at least one such embodiment, the surgical instrument can comprise membranes 843 mounted to sheath 841 and wave guide 846, wherein, when wave guide 846 is subjected to vibrations, as outlined above, membranes 843 can move, or pump, air along wave guide 846 and/or end effector 850. More particularly, in at least one embodiment, the center portions 845 of membranes 843 can be affixed to wave guide 846, for example, such that, when wave guide 846 is subjected to longitudinal vibrations, the central portions 845 of membranes 843 can undergo longitudinal excursions while the outer portions 847 of membranes can remain stationary, or at least substantially stationary, as they can be affixed to sheath 841.

Owing to the longitudinal excursions of central portions 845, air positioned intermediate sheath 841 and wave guide 846, for example, can be moved longitudinally along wave guide 846 such that the air can absorb heat generated by and stored within wave guide 846, for example. In certain embodiments, the membranes can produce a laminar and/or turbulent flow of air across the surface of wave guide 846 and end effector 850. In various embodiments, one or more membranes 843 can be positioned at the antinodes of the standing wave of vibrations such that the larger longitudinal displacements of wave guide 846, which occur at the antinodes, can be utilized to produce larger displacements of membranes 843 and larger flows of air. In at least one such embodiment, a membrane can be positioned at each antinode that occurs within a wave guide and an end effector. In various embodiments, the membranes may only be placed at the antinodes while, in other embodiments, several membranes may be positioned in a region surrounding an anti-

node, for example. In any event, the membranes can further comprise one or more apertures, slots, perforations, and/or openings **849** which can be configured to allow air to flow through the membranes **843**, for example. In various embodiments, the membranes can comprise any suitable quantity of apertures, for example, such as one or more apertures, four or more apertures, and/or ten or more apertures, for example. In at least one embodiment, the apertures of one membrane **843**, for example, can be aligned with the apertures of adjacent membranes **843**. In various embodiments, the outer portions **847** of membranes **843** can be adhered to, and/or otherwise suitably attached to, sheath **841** while the inner portions **845** of membranes **843** can be adhered to, and/or otherwise suitably attached to, wave guide **846**. In certain embodiments, the inner portions **845** can comprise a hole which can allow membranes **843** to be slid onto and positioned on wave guide **846**. In various embodiments, membranes **843** can be comprised of a polymer material, for example, wherein the material can be thin enough to permit at least a portion of the membrane to move longitudinally while thick enough to withstand repeated movements thereof.

In various circumstances, as outlined above, the piezoelectric elements of a transducer positioned closer to a node may be required to perform larger quantities of work and may be subjected to higher temperatures than piezoelectric elements positioned further away from the node. In such circumstances, the piezoelectric elements closest to the node may degrade, and lose their ability to perform a certain amount of work, at a faster rate than the piezoelectric elements positioned further away from the node. When such degradation has occurred in the past, the transducer was discarded. In various embodiments described herein, the transducer can be disassembled after it has been used such that the piezoelectric elements of the transducer can be rearranged. In at least one embodiment, referring to FIG. 22A, a transducer **914** can comprise piezoelectric elements **932a**, **932b**, **932c**, and **932d** wherein, in at least the arrangement illustrated in FIG. 22A, piezoelectric elements **932a** are positioned closest to the node N and piezoelectric elements **932d** are positioned closest to the antinodes AN. After transducer **914** has been used, it may be likely that piezoelectric elements **932a** will have degraded more than piezoelectric elements **932b**, **932c**, and **932d**. In certain embodiments, as a result, piezoelectric elements **932a** can be shuffled to the ends of the transducer stack and piezoelectric elements **932b**, **932c**, and **932d** can be moved inwardly as illustrated in FIG. 22B. Thereafter, in such embodiments, piezoelectric elements **932b** may perform larger quantities of work than piezoelectric elements **932a** would have. After transducer **914** has been used once again, transducer **914** can be disassembled such that piezoelectric elements **932b** can be shuffled to the ends of the stack, or furthest away from the node, and piezoelectric elements **932c**, and **932d** can be moved inwardly, or closer to the node. While this particular sequence of reshuffling the piezoelectric elements may be useful, any other suitable sequence may be used.

In various embodiments, further to the above, a transducer can be assembled utilizing several piezoelectric elements which have been used more than once or have undergone different duty cycles. In at least one embodiment, referring to FIG. 23A, transducer **1014**, for example, can be assembled using first piezoelectric elements **1032a** which have undergone a first amount of duty cycles, if any, second piezoelectric elements **1032b** which have undergone a second amount of duty cycles, third piezoelectric elements **1032c** which have undergone a third amount of duty cycles,

and fourth piezoelectric elements **1032d** which have undergone a fourth amount of duty cycles. In at least one such embodiment, the first amount of duty cycles can be zero, or at less than the second amount of duty cycles, the second amount of duty cycles can be less than the third amount of duty cycles, and the third amount of duty cycles can be less than the fourth amount of duty cycles. In certain circumstances, as a result, the fourth piezoelectric elements **1032d** may be more degraded, or less capable of producing work, than the third piezoelectric elements **1032c**, the third piezoelectric elements **1032c** can be more degraded than the second piezoelectric elements **1032b**, and the second piezoelectric elements **1032b** can be more degraded than the first piezoelectric elements **1032a**. In such embodiments, the piezoelectric elements having less duty cycles can be positioned closer to a node such that the less-degraded piezoelectric elements can more efficiently contribute to the standing wave of longitudinal vibrations and generate greater quantities of work. Stated another way, further to the above, the largest longitudinal displacements, or vibrations, produced by a transducer are generated by piezoelectric elements positioned at or near a node of the standing wave, wherein the less-degraded piezoelectric elements positioned at or near the node can better capitalize on their position.

After a transducer assembled in accordance with above, such as transducer **1014**, for example, has been used, each of the piezoelectric elements, i.e., elements **1032a**, **1032b**, **1032c**, and **1032d**, of the transducer will have undergone additional duty cycles and may have become further degraded. In at least one embodiment, as a result, the piezoelectric elements **1032d**, which have undergone the most duty cycles at this point, can be removed from the transducer stack. The other remaining piezoelectric elements, i.e., elements **1032a**, **1032b**, and **1032c** can be shifted outwardly within the transducer stack, or repositioned within the transducer stack such that they are positioned further away from the node. In at least one such embodiment, referring now to FIG. 23B, new piezoelectric elements, such as elements **1032e**, for example, can be positioned at or nearest to the node. In various embodiments, piezoelectric elements **1032e** may have undergone no duty cycles, or may have undergone less duty cycles than piezoelectric elements **1032a**, for example. In any event, the transducer can be reassembled and used once again. Thereafter, the transducer can be disassembled once again and new, or at least less-used, piezoelectric elements can be inserted into the stack. Although the insertion of new, or at least less-used, elements into the transducer stack may typically correspond with the removal of a corresponding quantity of piezoelectric elements from the transducer stack, embodiments are envisioned in which new elements can be added to the transducer stack, thereby increasing the total quantity of piezoelectric elements within the stack. Furthermore, although pairs of new, or at least less-used, piezoelectric elements can be replaced within the transducer at a given time, embodiments are envisioned where only one piezoelectric element, or more than two piezoelectric elements, are replaced at a given time.

In various alternative embodiments, further to the above, the piezoelectric elements having more duty cycles within a transducer can be positioned at or nearest to a node while the piezoelectric elements having fewer duty cycles can be positioned further away from the node. In certain embodiments, as the piezoelectric elements having fewer duty cycles may be positioned closer to the antinodes, such piezoelectric elements may be capable of leveling, or at least better leveling, the work produced by the piezoelectric

elements. More particularly, as discussed in great detail above, the piezoelectric elements positioned closer to the antinodes of a standing wave of vibrations may undergo less stress and strain and, thus, have less capacity to draw current and produce work and, by having the new, or less-degraded, piezoelectric elements positioned near the antinodes, such piezoelectric elements may be able to compensate for the lesser stress and strain and provide a greater quantity of work than older, or more-degraded, piezoelectric elements would have provided. Similarly, by using the older, or more-degraded, piezoelectric elements closer to the node, such elements may produce a flatter work profile than new, or less-degraded, piezoelectric elements would have provided. In various embodiments, a flatter work profile can be produced which can be beneficial in various circumstances as outlined herein.

As discussed in great detail above, an ultrasonic instrument can comprise a transducer, a wave guide, and an end effector, wherein the transducer can be configured to produce vibrations which causes a system, or assembly, comprising the transducer, the wave guide, and the end effector to vibrate at a resonant frequency. As also discussed above, the resonant frequency of such an assembly may be affected by various mounting or connecting members, for example. In any event, the assembly may be designed to have a particular resonant frequency, such as approximately 55,000 kHz, for example. Owing to various manufacturing differences, however, each assembly may have a slightly different resonant frequency and, as a result, each assembly may be tested in order to find its resonant frequency. If it is determined that the natural frequency of the assembly needs to be adjusted, the end of the wave guide and/or end effector may be ground in order to adjust their length and, as a result, adjust the resonant frequency of the assembly. Although such an assembly process may be useful for its intended purpose, the process may be time consuming and/or may not provide adequate adjustability of the assembly. For example, in the event that too much length is ground off of a wave guide, for example, the wave guide must typically be thrown out and the adjustment process must be repeated with a new wave guide.

In various embodiments, referring now to FIG. 24, an ultrasonic instrument can comprise a transducer 1114, a wave guide 1146, and an end effector 1150 which can collectively comprise an assembly having a resonant frequency, wherein wave guide 1146 can be mounted to transducer 1114 such that transducer 1114 can be adjusted relative to wave guide 1146. More particularly, in at least one embodiment, transducer 1114 can comprise a threaded aperture 1115 which can be configured to threadably receive a threaded end 1151 of wave guide 1146 such that wave guide 1146 can be rotated relative to transducer 1114 in order to move wave guide 1146 and end effector 1150 along axis 1199. For example, wave guide 1146 can be rotated in a clockwise direction in order to move the distal end 1152 of end effector 1150 distally with respect to, or away from, transducer 1114. Correspondingly, wave guide 1146 can be rotated in a counter-clockwise direction in order to move distal end 1152 of end effector 1150 proximally, or toward, transducer 1114. In certain embodiments, threaded aperture 1115 can extend between the proximal end of end-bell 1120 and the distal end of fore-bell 1122. In various circumstances, as a result of the above, the length "L" between transducer 1114 and the distal tip 1152 of end effector 1150 can be adjusted in order to tune the resonant frequency of the assembly such that it matches a desired resonant frequency. In at least one embodiment, length "L" can be adjusted such

that the distal tip 1152 of end effector 1150 is positioned at, or near, an antinode of the standing wave of longitudinal vibrations and/or such that the center of the transducer stack of piezoelectric elements 1132 is positioned at, or near, a node of the standing wave of longitudinal vibrations.

In any event, once wave guide 1146, end effector 1150, and transducer 1114 have been suitably positioned relative to one another, wave guide 1146 can be immovably affixed to transducer 1114, for example. In at least one embodiment, wave guide 1146 can be welded to end-bell 1120 and/or fore-bell 1122. In certain embodiments, although not illustrated, the assembly can further comprise a connector which can be configured to operably and releasably couple wave guide 1146 to transducer 1114. In at least one such embodiment, the assembly can further comprise one or more compression collars which can be threadably engaged onto end-bell 1120 and/or fore-bell 1122 so as to compress end-bell 1120 and/or fore-bell 1122 against wave guide 1146 and create a friction fit therebetween. In such embodiments, the compression collars can be uncoupled from end-bell 1120 and/or fore-bell 1122 such that the relative position of wave guide 1146 and transducer 1114 can be adjusted once again. In various embodiments, although not illustrated, an ultrasonic assembly can comprise a transducer and a wave guide, and/or end effector, wherein at least a portion of the wave guide can be press-fit into a hole within the transducer. In at least one such embodiment, the position of the wave guide within the transducer hole can be adjusted with sufficient axial force applied thereto even though the wave guide may be immovable relative to the transducer during the course of the ordinary operation of the surgical instrument.

In various embodiments, also not illustrated, an ultrasonic instrument can comprise a transducer having an aperture and, in addition, a wave guide, or end effector, configured to be inserted into the aperture, wherein a thermal interference fit can be created between the wave guide and the sidewalls of the transducer aperture, for example. More particularly, in at least one such embodiment, the transducer aperture and the wave guide can be configured such that the wave guide cannot be inserted into the transducer aperture when the transducer and the wave guide are at the same temperature, or at least substantially the same temperature, although the transducer can be heated such that the aperture expands, and/or the wave guide can be cooled such that it contracts, so that the wave guide can be inserted into the transducer aperture. Owing to such temperature differences, sufficient clearance can exist between the wave guide and the side walls of the transducer aperture such that the position of the wave guide relative to the transducer can be adjusted. After the transducer has been sufficiently cooled, and/or after the wave guide has been sufficiently warmed, an interference fit may exist between the wave guide and the sidewalls of the transducer aperture. Such an interference fit can be referred to as a thermal interference fit. In any event, if it is determined that the position of the wave guide needs to be readjusted, the transducer can be heated and/or the wave guide can be cooled once again in order to permit the wave guide to be moved relative to the transducer once again.

In various embodiments, the length and mass of an assembly comprising a transducer, wave guide, and/or end effector can dictate the resonant frequency of the assembly. In various circumstances, the length of the assembly can be selected such that the resonant frequency of the assembly is within a range of frequencies that a voltage or current source can supply to the transducer. In certain embodiments, a given transducer, wave guide, and/or end effector may be

required to be used together and, in the event that a different length wave guide or different end effector is needed, a different surgical instrument altogether may be required. In various alternative embodiments, referring now to FIG. 25, a surgical instrument kit can comprise a handpiece comprising a transducer and two or more wave guides and/or two or more end effectors which can be assembled to the transducer in order to allow a surgical instrument to be adapted to have various lengths and/or have various uses. More particularly, in at least one embodiment, a kit can comprise a transducer 1214, an integral first wave guide 1246a and first end effector 1250a, and an integral second wave guide 1246b and second end effector 1250b, wherein, in at least one such embodiment, a surgeon can selectively assemble the integral first wave guide 1246a and first end effector 1250a, and/or the integral second wave guide 1246b and second end effector 1250b, to transducer 1214 such that the surgical instrument can have different lengths, for example. In various embodiments, the length and mass of the integral first wave guide 1246a and end effector 1250a can be such that, when they are attached to transducer 1214, the voltage and/or current source can supply power to the transducer 1214 at a first resonant frequency and, similarly, the length and mass of the integral second wave guide 1246b and end effector 1250b can be such that, when they are attached to transducer 1214, the voltage and/or current source can supply power to the transducer 1214 at a second, or different, resonant frequency. In certain embodiments, the first and second resonant frequencies can be the same, or at least substantially the same. In various embodiments, the transducer 1214 can comprise a threaded aperture 1268 and the wave guides 1246a and 1246b can each comprise a threaded stud 1248 which can be threadably inserted into the threaded aperture 1268. In certain embodiments, integral wave guide 1246a and end effector 1250a can comprise a first length which is an integer multiple of one-half of the wavelength of the standing wave of vibrations, i.e., $(n*\lambda)/2$, at the resonant frequency of the assembly. Similarly, in at least one embodiment, the integral wave guide 1246b and end effector 1250b can comprise a second length which is an integer multiple of one-half of the wavelength of the standing wave of vibrations at the resonant frequency of the assembly, i.e., $(m*\lambda)/2$, wherein m can be less than n, for example. In various embodiments, the lengths of the wave guides and end effectors can be configured such that the tips 1252a and 1252b of the assemblies, and/or the threaded studs 1248, are positioned at or near an antinode of the standing wave of vibrations.

In various embodiments, further to the above, an ultrasonic instrument may comprise a transducer, a wave guide, and an end effector, wherein the ultrasonic instrument may further comprise a housing at least partially surrounding the transducer and a sheath at least partially surrounding the wave guide and/or end effector. In at least one embodiment, referring to FIG. 26, ultrasonic surgical instrument 1310 can comprise a transducer 1314, a housing 1316 encompassing transducer 1314, a wave guide 1346, a sheath 1341 encompassing wave guide 1346, and an end effector 1350. In certain embodiments, surgical instrument 1310 can further comprise one or more stabilizing supports 1356 which can be configured to support wave guide 1346 and/or end effector 1350 within sheath 1341. In at least one such embodiment, sheath 1341 can comprise a handle portion and/or can be configured to be grasped, or gripped, by a surgeon such that the surgeon can accurately manipulate surgical instrument 1310 and, in particular, accurately manipulate distal end 1352 of end effector 1350. In at least

one embodiment, at least a portion of the outer surface of sheath 1341 can comprise a roughened and/or textured surface. In certain embodiments, the outer surface of sheath 1341 can comprise a round, or at least substantially round, cross-section having a diameter of approximately 5 millimeters, approximately 10 millimeters, approximately 15 millimeters, and/or a diameter between approximately 4 millimeters and approximately 16 millimeters.

In any event, supports 1356 can be sufficiently rigid to transfer forces between sheath 1341 and wave guide 1346 and yet can be sufficiently compliant to permit relative movement between wave guide 1346 and sheath 1341. In certain embodiments, supports 1356 can also dampen vibrations transmitted between wave guide 1346 and sheath 1341, for example. In various embodiments, supports 1356 can be positioned at or near the nodes of the standing wave of longitudinal vibrations, although supports 1356 can be positioned at any suitable location. Supports 1356 positioned at or near the nodes of the longitudinal standing wave of vibrations may undergo smaller displacements and, thus, smaller vibrations may be transmitted to sheath 1341, for example. In any event, transducer housing 1316 can be mounted to sheath 1341 wherein, in various embodiments, housing 1316 can be adhered to, fastened to, and/or otherwise suitably affixed to sheath 1341. In various embodiments, housing 1316 can be mounted to sheath 1341 such that housing 1316 is not in direct contact with transducer 1314. In at least one such embodiment, transducer 1314 and housing 1316 can move, or float, relative to one another. In at least one embodiment, referring again to FIG. 26, surgical instrument 1310 can further comprise one or more compliant supports, such as support 1353, for example, positioned intermediate housing 1316 and sheath 1341, wherein support 1353 can be configured to dampen vibrations transmitted between sheath 1341 and housing 1316. In certain embodiments, support 1353 can comprise an o-ring compressed between sheath 1341 and housing 1316. Owing to such an arrangement, in at least one embodiment, the connection between transducer housing 1316 and sheath 1341 can occur at any suitable location along the length of surgical instrument 1310 with little or no regard to whether such a location is at a node and/or antinode of the standing wave of longitudinal vibrations.

In various embodiments, further to the above, a transducer housing, such as transducer housing 1316, for example, can be comprised of a rigid, or at least substantially rigid material, such as plastic, for example. In certain embodiments, a transducer housing can be sufficiently flexible such that it can be deflected, or elastically deformed, between a first configuration, in which the transducer housing does not contact, or at least substantially contact, a transducer positioned therein, and a second position in which the transducer housing contacts the transducer. In at least one embodiment, referring now to FIGS. 27-30, an ultrasonic surgical instrument can comprise a transducer 1414, a transducer housing 1416 at least partially surrounding transducer 1414, and a wave guide 1446 which can be operably coupled with transducer 1414. Similar to the above, although not illustrated in FIGS. 27-30, the surgical instrument can further comprise a sheath at least partially surrounding wave guide 1446, wherein at least a portion of housing 1416 can be mounted to the sheath, for example. In certain embodiments, referring to FIG. 28, a surgeon, or other clinician, can grasp housing 1416 in order to apply a gripping force thereto and deflect it inwardly toward transducer 1414 such that housing 1416 can engage at least a portion of transducer 1414, such as a gripping portion. In such circumstances, the surgeon or

clinician can hold transducer **1414** in position via housing **1416** while they mount wave guide **1446** to transducer **1414**. More particularly, in at least one embodiment, transducer **1414** can comprise a distal end, or gripping portion, **1422**, for example, having one or more flat surfaces, or at least substantially flat surfaces, **1421** which can be easily gripped by the surgeon or clinician while a proximal end of wave guide **1446** is threadably inserted into the transducer, as outlined above. In such circumstances, referring again to FIG. **28**, the surgeon or clinician may be able to rotate, or torque, transducer **1414** in a first direction and/or rotate, or torque, wave guide **1446** in a second, or opposite direction, until wave guide **1446** and transducer **1414** are suitably secured together. In other various embodiments, a transducer may comprise grippable features which can allow the surgeon to insert a wave guide into the transducer in an axial, or longitudinal, direction, for example. In any event, in at least one embodiment, the gripping portion **1422**, for example, can be located at an anti-node of the standing wave of longitudinal vibrations.

In various embodiments, once the wave guide has been mounted to the transducer, the surgeon or clinician can release housing **1416** such that housing **1416** sufficiently expands and is no longer in contact with transducer **1414**. In various embodiments, the housing **1416** can be sufficiently resilient such that it returns to its original shape. Owing to the above, in certain embodiments, the transducer housing may not contact the transducer and, as a result, may not impede or affect the standing wave of vibrations created by the transducer during use. In the event that the surgeon or clinician seeks to detach wave guide **1446** from transducer **1414**, they may grip housing **1416** once again and rotate, or torque, the wave guide and transducer in opposite directions. In various embodiments, although not illustrated, a portion of a handle can comprise one or more inwardly extending interlocking features which, when the handle is compressed inwardly towards a transducer, can be configured to engage corresponding interlocking features on the transducer. Such embodiments can provide a keyed arrangement which can facilitate holding the transducer in position when a wave guide or end effector is mounted thereto, for example. Although not illustrated, various alternative embodiments are envisioned in which a flexible housing is mounted to the transducer at least one location, but is flexible inwardly to connect a wave guide or end effector to the transducer as outlined herein.

In various embodiments, as outlined above, the power produced by a transducer of an ultrasonic surgical instrument, and/or the magnitude of the vibrations produced by the transducer, can be proportional the voltage potential applied across the piezoelectric elements of the transducer, for example. While increasing the voltage applied to the piezoelectric elements can increase the power output of the transducer, such a power increase can be met with an undesirable increase in temperatures as outlined above. In certain embodiments, referring now to FIG. **31**, a surgical instrument can comprise a wave guide **1546**, an end effector **1550**, a first transducer **1514a**, and a second transducer **1514b**, wherein wave guide **1546** can be mounted to first transducer **1514a**, and wherein first transducer **1514a** can be mounted to second transducer **1514b**. In at least one embodiment, similar to the above, one of transducer **1514a** and transducer **1514b** can comprise a threaded aperture, such as aperture **1568**, for example, and the other of transducer **1514a** and transducer **1514b** can comprise a threaded post, such as post **1548**, for example, wherein threaded post **1548**

and threaded aperture **1568** can be configured to securely fasten first transducer **1514a** and second transducer **1514b** together.

In various embodiments, further to the above, the power of an ultrasonic instrument can be increased by the selective attachment of second transducer **1514b** to first transducer **1514a**, for example. In at least one embodiment, a kit can be provided to a surgeon including a handle, a first transducer, a second transducer, and a wave guide and/or end effector, wherein, if the surgeon desires the surgical instrument to have a first, or lower, power, the surgeon, or other clinician, can insert the first transducer **1514a** into the handle and assemble the first transducer **1514a** to the wave guide and/or end effector without assembling the second transducer **1514b** to the instrument. In certain embodiments, the first transducer **1514a** may already be inserted into the handle and may already be operably engaged with the wave guide and/or end effector when the surgeon or other clinician receives the kit. In either event, if the surgeon desires that the surgical instrument should have a second, or larger, power, the surgeon can selectively attach the second transducer **1514b** to the first transducer **1514a**, wave guide, and/or end effector. Similar to the above, in certain embodiments, the second transducer **1514b** may already be preassembled to the first transducer **1514a** when the surgeon or other clinician receives the kit.

In various embodiments, further to the above, a kit for a surgical instrument can comprise more than two transducers. In at least one embodiment, for example, the kit may comprise a first transducer configured to supply a first quantity of power, a second transducer configured to supply a second quantity of power, and a third transducer configured to supply a third quantity of power, for example. In certain embodiments, a kit may have more than three transducers and, in some embodiments, some of the transducers within the kit can be configured to supply the same, or at least substantially the same, quantity of power. In any event, the surgeon or other clinician can select from the provided transducers in order to arrive at a desired quantity of power that will be supplied to the surgical instrument. In at least one such embodiment, more than two transducers can be assembled together in order to deliver power to the wave guide. In various embodiments, referring again to FIG. **31**, the transducers can be affixed to one another in a series arrangement wherein the total deliverable power of the surgical instrument can be determined by summing the deliverable power of each transducer.

In various embodiments, further to the above, an ultrasonic surgical instrument comprising two or more transducers operably coupled to a wave guide and/or end effector of the surgical instrument can be configured such that the transducers produce standing waves of vibrations which overlap, or at least substantially overlap, with one another. In at least one embodiment, a surgical instrument can comprise a first transducer which produces a first standing wave of vibrations within a wave guide and, in addition, a second transducer which produces a second standing wave of vibrations within the wave guide, wherein the nodes and antinodes of the first and second standing waves of vibrations can be coincident, or at least nearly coincident with one another. In at least one such embodiment, the first and second standing waves of vibrations can supplement each other such that the displacements produced by the standing waves are superimposed onto one another and have an additive effect.

In certain embodiments, referring now to FIG. **32**, two or more transducers can be mounted to a wave guide and/or end

effector of an ultrasonic surgical instrument in a parallel arrangement. More particularly, in at least one embodiment, an ultrasonic surgical instrument can comprise a wave guide **1646**, an end effector **1650**, a first transducer **1614a**, and a second transducer **1614b**, wherein transducers **1614a** and **1614b** can both be mounted to a common mounting portion of wave guide **1646**. In certain embodiments, similar to the above, the transducers and the wave guide can comprise co-operating threaded apertures and posts which can be utilized to secure the transducers to the wave guide. Also similar to the above, the standing waves of longitudinal vibrations produced by transducers **1614a** and **1614b** can supplement each other such that the displacements produced by the standing waves are superimposed onto one another and have an additive effect. In various embodiments, although not illustrated, an ultrasonic surgical instrument can comprise transducers which can be operably engaged with a wave guide and/or end effector in both parallel and series arrangements. For example, first and second transducers can be directly mounted to a wave guide in parallel with one another, wherein a third transducer can be mounted to the first transducer such that it is in series with the first transducer, and wherein a fourth transducer can be mounted to the second transducer such that it is in series with the second transducer, for example.

In various embodiments, further to the above, the first and second transducers of a surgical instrument can be configured such that the center of each of the piezoelectric stacks of the first and second transducers are positioned at, or near, a node of the standing wave of vibrations. In other various embodiments, the first and second transducers of a surgical instrument can be configured such that the center of the piezoelectric stack of the first transducer is positioned at, or near, a node and such that the center of the piezoelectric stack of the second transducer is positioned closer to an antinode. In such embodiments, further to the above, the first piezoelectric stack may be able to contribute more work, and may generate more heat, than the second piezoelectric stack. In at least one such embodiment, as a result, the piezoelectric elements within the first transducer can be different than the piezoelectric elements within the second transducer. More particularly, the piezoelectric elements of the first transducer, i.e., the transducer positioned closer to a node, can be comprised of a material, or materials, which have a higher strain constant, for example, than the materials of the piezoelectric elements of the second transducer. In various embodiments, the piezoelectric elements of the first transducer can be comprised of a material having a higher Curie temperature, for example, than the material of the piezoelectric elements of the second transducer. In certain embodiments, the piezoelectric elements of the first transducer can comprise piezoelectric elements which have undergone a higher, or lower, quantity of duty cycles than the piezoelectric elements of the second transducer.

In various embodiments, an ultrasonic surgical instrument can comprise a wave guide and/or end effector, a first transducer, and a second transducer, wherein the first and second transducers can be operably engaged with the wave guide and/or end effector as outlined above. In at least one embodiment, the first transducer and the second transducer can each be selectively actuatable. In at least one such embodiment, the surgical instrument can comprise a handle which can comprise one or more switches which can be configured to selectively actuate the first and second transducers positioned therein. Referring to FIG. 1A, a switch **43** is positioned on the hand piece assembly **60**. For example, a switch can be moved from an off position to a first position

in order to actuate the first transducer, to a second position to actuate the second transducer, and/or to a third position to actuate the first transducer and the second transducer. In certain other embodiments, a handle can comprise a first switch configured to selectively actuate the first transducer and, in addition, a second switch configured to selectively actuate the second transducer. In such embodiments, the surgeon can select the power to be supplied to the wave guide and/or end effector. In various alternative embodiments, a surgical instrument can comprise three or more transducers which can be selectively actuated.

In various embodiments, as outlined above, a transducer can comprise a fore-bell, an end-bell, and one or more piezoelectric elements compressed, or clamped, between the fore-bell and end-bell. Often, the fore-bell and/or end-bell can include a shaft configured to be positioned within apertures in the piezoelectric elements in order to align the piezoelectric elements with each other. Once the transducer has been assembled, in various embodiments, the wave guide and/or end effector can be operably mounted to the transducer. In various other embodiments described herein, an ultrasonic surgical instrument can comprise a wave guide, an end effector, and one or more piezoelectric elements which can be mounted directly to the wave guide and/or end effector. In at least one embodiment, referring to FIG. 33, a surgical instrument can comprise an end effector **1750** and an integral alignment post, or shaft, **1722**, wherein piezoelectric elements having apertures therein can be aligned with post **1722** such that the piezoelectric elements can be slid along post **1722** until they abut shoulder **1746**. In various embodiments, referring now to FIG. 34, an ultrasonic surgical instrument can comprise an end effector **1850**, a wave guide **1846**, and piezoelectric elements **1832**, wherein elements **1832** can be slid along shaft **1822** until they are stacked against wave guide **1846**. Thereafter, an end member, such as end member **1820**, for example, can be engaged with alignment shaft **1822** and utilized to secure piezoelectric elements **1832** between end member **1820** and wave guide **1846**. In at least one such embodiment, alignment shaft **1822** can comprise a threaded end and, in addition, end member **1820** can comprise a threaded aperture, wherein the threaded aperture can be configured to threadably receive the threaded end of alignment shaft **1822**.

In various embodiments, as outlined above, a voltage potential may be applied to the piezoelectric elements of a transducer to contract and expand the piezoelectric elements and generate vibrations. As also outlined above, such a voltage potential may be cycled between two values, such as between minimum and maximum values, for example. In various embodiments, the piezoelectric elements can be poled such that the voltage potential can affect the piezoelectric elements. More particularly, the piezoelectric elements can undergo a poling process such that a net electric, or magnetic, dipole is stored within each piezoelectric element, wherein the voltage potential can interact with the magnetic dipole and cause the piezoelectric element to vibrate. During a poling process, electrodes can be applied to the opposite sides of a piezoelectric element such that a large electric field can be applied across the piezoelectric element in order to arrange the domains within the piezoelectric material and create a net magnetic dipole within the piezoelectric element. In at least one embodiment, the electrodes may be screen-printed onto the electrodes, wherein one or more stencils can be aligned with the sides of the piezoelectric element, and wherein a roller having conductive ink thereon can be rolled across the stencil such that the conductive ink is selectively applied to the piezo-

electric element. In certain embodiments, a mesh material can be applied to the surface of the piezoelectric element, wherein the conductive ink can be pressed through the mesh, or woven, material which is not covered by a masking portion of the stencil.

In various embodiments, the electrodes utilized to pole the piezoelectric elements, as outlined above, may be ground off of, and/or otherwise removed from, the piezoelectric elements such that a second set of electrodes can be positioned intermediate the various piezoelectric elements of a transducer stack, wherein the second set of electrodes can generate the voltage potential used during the operation of the surgical instrument. In other various embodiments, a second set of electrodes can be applied to the piezoelectric elements utilizing a physical vapor deposition process (PVD), wherein certain conductive materials, such as metals, for example, can be evaporated in a low pressure environment such that the conductive materials can be deposited onto the piezoelectric elements. In certain embodiments, a stencil, or mask, can be placed over the surfaces of the piezoelectric elements such that the conductive materials can be selectively deposited on the piezoelectric elements.

In various embodiments, the electrodes utilized to pole the piezoelectric elements can also be utilized to apply voltage potentials to the piezoelectric elements during use. In at least one embodiment, the electrodes can be pad-printed onto the piezoelectric elements. In at least one such embodiment, a conductive ink can be placed, or poured, onto a printing plate, wherein the surface of the ink can become tacky after being exposed to air, for example. Thereafter, a transfer pad can be pressed onto the ink such that the tacky portion of the ink adheres to transfer pad, the transfer pad can be positioned over a piezoelectric element, and the transfer pad can be pressed onto the piezoelectric element such that the ink adheres to the piezoelectric element. In such embodiments, the printing plate can have various reliefs or contours which can define the areas of the printing plate which can store the conductive ink and, correspondingly, can define the respective areas on the piezoelectric element in which the conductive ink will be applied. In various embodiments, the conductive ink can comprise a fluid, silver, and/or carbon, for example.

In various embodiments, further to the above, one or more electrodes can be adhered to a piezoelectric element. In at least one embodiment, referring now to FIG. 35, a transducer can comprise one or more piezoelectric elements 1932, wherein each piezoelectric element 1932 can comprise a core, or disc, 1931, a positive electrode 1934, and a negative electrode 1936, for example. In at least one such embodiment, the positive electrode 1934 and/or the negative electrode 1936 can be adhered to the core 1931 utilizing a conductive adhesive. In use, as a result, a voltage source can be operably coupled to the positive electrode 1934 and negative electrode 1936 such that a voltage potential can be created between the positive and negative electrodes, as outlined above. When the piezoelectric elements 1932 are assembled into a transducer stack, such as transducer stack 1914 (FIG. 36), for example, the piezoelectric elements 1932 can be arranged such that their positive and/or negative electrodes are aligned with one another. For example, the negative electrode 1936 of piezoelectric element 1932a can be positioned against the negative electrode 1936 of piezoelectric element 1932b and, similarly, the positive electrode 1934 of piezoelectric element 1932b can be positioned against the positive electrode 1934 of piezoelectric element 1932c, for example. Owing to contact between adjacent

negative electrodes 1936, and/or owing to contact between adjacent positive electrodes 1934, the polarization of one of the negative electrodes 1934, or positive electrodes 1936, may polarize an adjacent electrode.

In various embodiments, further to the above, each electrode can comprise a body, which is adhered to piezoelectric element core 1931, and a tab, or portion, 1935 which can be configured to extend outwardly from the electrode body and/or core 1931. In at least one such embodiment, the piezoelectric element core 1931 of a piezoelectric element can comprise an outer profile, wherein tabs, or portions, 1935 can extend outwardly with respect to the outer profile of core 1931. In certain embodiments, the tabs 1935 of adjacent piezoelectric elements 1932 can be connected to one another. In at least one such embodiment, conductive clips, connectors, and/or connecting electrodes, for example, can be utilized to couple the tabs 1935 of adjacent piezoelectric elements 1932 such that the adjacent negative electrodes 1936, or adjacent positive electrodes 1934, can be in electrical communication with one another and have the same, or an at least substantially similar, voltage potential. In at least one embodiment, a clip 1933 can connect adjacent tabs 1935, wherein, in at least one embodiment, clip 1933 can comprise a spring which can bias the clip from an open configuration into a closed configuration, for example. In certain embodiments, as described in greater detail further below, the cores 1931, for example, of various piezoelectric elements can comprise alignment features which can be configured to assure that adjacent piezoelectric elements can be assembled to each other in only one way, or a limited number of ways. In at least one such embodiment, the alignment features can be configured such that the tabs 1935 of the electrodes are aligned, or at least substantially aligned, with one another when the alignment features of piezoelectric elements are aligned, or at least substantially aligned, with one another.

In various embodiments, referring now to FIGS. 37 and 38, a transducer stack 2014 can comprise a plurality of piezoelectric elements, such as elements 2032, for example, wherein each element 2032 can comprise a negative electrode 2034 and a positive electrode 2036. In certain embodiments, the transducer stack 2014 can further comprise one or more first connecting electrodes 2033a which can operably connect a plurality of negative electrodes 2034 and, in addition, one or more second connecting electrodes 2033b which can operably connect a plurality of positive electrodes 2036. More particularly, in at least one embodiment, first connecting electrode 2033a can be connected to the tabs 2035 associated with negative electrodes 2034 in order to polarize each of the negative electrodes 2034 with the same, or at least substantially the same, voltage potential and, in addition, second connecting electrode 2033b can be connected to the tabs 2035 associated with the positive electrodes 2036 in order to polarize each of the positive electrodes 2036 with the same, or at least substantially the same, voltage potential. In various embodiments, the connecting electrodes can comprise a brass or copper strip or material, for example, wherein first connecting electrode 2033a can be welded or soldered to negative electrodes 2034 and, similarly, second connecting electrode 2033b can be welded or soldered to positive electrodes 2036. In some embodiments, the connecting electrodes can comprise insulated wires, and/or any other suitable conductor. In certain embodiments, although not illustrated, the connecting electrodes can comprise one or more clips or clamp elements which can be operably engaged with the tabs 2035, for example. In any event, further to the above, the first con-

necting electrode **2033a** can be operably coupled with the negative terminal of a battery **2029**, and/or any other suitable power source, and the second connecting electrode **2033b** can be operably coupled with the positive terminal of the battery **2029**, for example.

In various embodiments, referring to FIG. **39**, the connecting electrodes **2133** of a transducer stack **2114** can be positioned radially outwardly with respect to the outside diameter (OD), or outer profile, of the piezoelectric elements **2132**. In various circumstances, various radial gaps can exist between the outside diameter (OD), or outer profile, of the piezoelectric elements **2132** and the transducer housing **2116** in order to accommodate the connecting electrodes **2133**. Such gaps, however, can represent lost power capacity of the piezoelectric elements. More particularly, as discussed above, piezoelectric elements having larger diameters, for example, have the capacity for producing larger quantities of work and, as the above-described gaps can represent a loss in the diameter, or size, of the piezoelectric elements, the gaps can reduce the power capacity of the piezoelectric elements. In certain circumstances, however, some amount of gap, G, between the piezoelectric elements **2132** and the transducer housing **2116** may be desired in order to accommodate the radial expansion, or Poisson's expansion, of the piezoelectric elements **2132**, especially when the piezoelectric elements are subjected to longitudinal contraction.

In various embodiments, now referring to FIGS. **40** and **41**, a transducer stack **2214** can comprise a plurality of piezoelectric elements **2232**, positive polarizing electrodes **2236** and/or negative polarizing electrodes **2234** positioned intermediate the piezoelectric elements **2232**, and one or more connecting electrodes **2213** operably connecting the negative electrodes **2234** and/or operably connecting the positive electrodes **2236**. In at least one embodiment, referring to FIG. **41**, each piezoelectric element **2232** can comprise an outside diameter, or outer profile, and one or more grooves, notches, or slots, **2239** therein, wherein notches **2239** can be configured to have a connecting electrode **2213** positioned therein. More particularly, in at least one embodiment, each notch **2239** can be sized and configured to receive a connecting electrode **2213** such that there is a clearance fit between the connecting electrode **2213** and the sidewalls of the notches **2239**, for example. In at least one such embodiment, each notch **2239** can have a width which is wider than the width "W" of a connecting electrode **2213** and a depth which is deeper than the height "L" of a connecting electrode **2213**, for example. In at least one embodiment, the width W can be approximately 2 mm and the height L can be approximately 0.6 mm. In various embodiments, connecting electrodes **2213** and notches **2239** can be configured such that the connecting electrodes **2213** do not extend above, or outwardly with respect to, the outer profile of the piezoelectric elements **2232**. In any event, owing to notches **2239**, referring to FIG. **41**, the largest outer diameter ($OD=2r+2L$), or outer profile, of the piezoelectric elements **2232** can be larger than the largest outer diameter ($OD=2r$), or outer profile, of the piezoelectric elements **2132** and, as a result, piezoelectric elements **2232** may be capable of generating more power than piezoelectric elements **2132**, for example. In certain embodiments, the diameter of piezoelectric elements **2232** ($OD=2r+2L$) can have a diameter of approximately 8 mm, approximately 10 mm, approximately 12 mm, approximately 14 mm, and/or

power increase between approximately 13% and approximately 53%, for example, as compared to piezoelectric elements **2132**.

In various embodiments, further to the above, the connecting electrodes **2213** of transducer stack **2214**, for example, can operably connect one or more negative polarizing electrodes **2234** and/or one or more positive polarizing electrodes **2236** with a power source. For example, referring again to FIG. **40**, a connecting electrode **2213** can connect a first positive electrode **2236** and a second positive electrode **2236** with the positive terminal of a battery, for example, wherein the connecting electrode **2213** can comprise a bridge which spans, and is not operably engaged with, a negative electrode **2234** positioned intermediate the first and second positive electrodes **2236**. On the other side of the transducer stack, for example, another connecting electrode **2213** can operably connect the second positive electrode **2236** with a third positive electrode **2236**, wherein, similar to the above, the connecting electrode **2213** can comprise a bridge which spans, and is not operably engaged with, another negative electrode **2234** positioned intermediate the second and third positive electrodes **2236**. In various embodiments, such a pattern can be repeated in order to operably connect all of the positive electrodes **2236** within transducer stack **2214** with one another and the positive terminal of a power source. As can be seen in FIG. **41**, the piezoelectric elements **2232** can comprise notches **2239** on the opposite sides thereof in order to accommodate the arrangement of connecting electrodes described above, although other arrangements are possible. Similar to the above, a connecting electrode can be configured to connect a first negative electrode **2234** and a second negative electrode **2234** with the negative terminal of a battery, for example, wherein the connecting electrode **2213** can comprise a bridge which spans, and is not operably engaged with, a positive electrode **2236** positioned intermediate the first and second negative electrodes **2234**. On the other side of the transducer stack, for example, another connecting electrode **2213** can operably connect the second negative electrode **2234** with a third negative electrode **2234**, wherein, similar to the above, the connecting electrode **2213** can comprise a bridge which spans, and is not operably engaged with, another positive electrode **2236** positioned intermediate the second and third negative electrodes **2234**.

In various embodiments, referring now to FIGS. **42** and **43**, a transducer stack **2314** can comprise a plurality of piezoelectric elements **2332**, positive electrodes **2336** and/or negative electrodes **2334** positioned intermediate the piezoelectric elements **2332**, and one or more connecting electrodes **2313** operably connecting the negative electrodes **2334** and/or operably connecting the positive electrodes **2336**. In at least one embodiment, piezoelectric elements **2332** can comprise one or more flat surfaces **2339** which can be configured to accommodate connecting electrodes **2313** yet permit the average diameter of the piezoelectric elements **2332** to be increased as compared to the average diameters of piezoelectric elements **2132**. More particularly, referring to FIG. **43**, the diameters of various circular portions of each piezoelectric element **2332**, i.e., the portions intermediate flats **2339**, can be increased such that the outer diameter of the piezoelectric element ($OD=2r+2L$) is the same distance, or at least substantially the same distance, as a diameter defined by connecting electrodes **2313**. In at least one such embodiment, such intermediate portions can add to the overall size, or area, of each piezoelectric element **2332** and, thus, add to the quantity of work that the piezoelectric elements can produce. In certain embodiments, similar to the

above, various portions of piezoelectric elements **2332** can have a diameter of approximately 8 mm, approximately 10 mm, approximately 12 mm, approximately 14 mm, and/or approximately 16 mm, for example, wherein, in certain embodiments, such piezoelectric elements can provide a power increase between approximately 11% and approximately 42%, for example, as compared to piezoelectric elements **2132**. In various embodiments, flats **2339** can be machined into the piezoelectric element, for example.

In various embodiments, as outlined above, the piezoelectric elements of a transducer can undergo a poling process such that a net dipole can be established within the piezoelectric element. In at least one embodiment, such a net dipole can comprise a positive charge (+), a negative charge (-), and a net dipole moment vector defined between the negative charge and the positive charge. In certain embodiments, referring now to FIGS. **44** and **45**, the positive charge (+) of a piezoelectric element, such as piezoelectric elements **2432**, for example, can be positioned on one side of the piezoelectric element while the negative charge (-) can be positioned on the opposite side of the piezoelectric element. In at least one such embodiment, each piezoelectric element **2432** can comprise one or more indicia which can indicate the direction of the net dipole moment vector. For example, piezoelectric elements **2432** can comprise an arrow **2433** formed on the side thereof, wherein the arrow **2433** can point in a direction toward the positive charge and away from the negative charge. In at least one embodiment, arrow **2433** can be ground, pressed, and/or etched, for example, into the side of the piezoelectric element while, in other embodiments, arrow **2433** can be integrally formed with the piezoelectric element when the piezoelectric element is manufactured, for example. In various embodiments, the arrow **2433** can extend from and/or be recessed within the side of the piezoelectric element. In certain embodiments, the arrows **2433** can be painted and/or otherwise suitably applied to the piezoelectric elements. In any event, piezoelectric elements having at least one indicium can allow a person assembling a transducer to readily recognize the polarity of the piezoelectric elements and, as a result, quickly and reliably, arrange the piezoelectric elements such that their poles are properly aligned with one another. In various embodiments, the indicia of a first piezoelectric element can be aligned with the indicia of a second piezoelectric element in order to align the dipole moment vector of the first element with the dipole moment vector of the second element.

In addition to or in lieu of the above, piezoelectric elements can comprise one or more indexing features which can be configured to assure that adjacent piezoelectric elements are properly aligned with one another. For example, referring again to FIGS. **44** and **45**, piezoelectric elements **2432** can comprise one or more recesses, or grooves, **2437** and one or more projections **2439**, wherein projections **2439** can be configured to be seated within recesses **2437** when piezoelectric elements **2432** are properly aligned with one another. More particularly, in at least one embodiment, projections **2439** can be seated within recesses **2437** only when piezoelectric elements are aligned along a common axis **2499** and the polarity of the piezoelectric elements **2432** are aligned such the positive charge (+) on one side of an element is aligned with the positive charge of an adjacent element and/or the negative charge (-) on the other side of the element is aligned with the negative charge of adjacent element. Absent a suitable alignment between the indexing features, referring to FIG. **45**, the piezoelectric elements **2432** may not be properly seated with

one another and a person, or machine, assembling a transducer may be able to quickly detect the misalignment. In various embodiments, various piezoelectric elements, such as elements **2432**, for example, can be configured such they can be assembled in pairs and such that the outwardly-facing surfaces of the piezoelectric elements are flat and parallel with one another, or at least substantially flat and substantially parallel with one another, wherein, referring again to FIG. **44**, the negative charges of the elements can be adjacent to the flat surfaces, and wherein various mated pairs of the piezoelectric elements can be stacked on top of one another with the flat surfaces and negative charges aligned with each other. In at least one such embodiment, the net dipole moment vectors of the piezoelectric elements can be perpendicular, or at least substantially perpendicular, with respect to the outwardly-facing flat surfaces of the piezoelectric elements

In various circumstances, as outlined above, the piezoelectric elements of a transducer may, for whatever reason, lose their ability, or at least a portion of their ability, to generate sufficient vibrations to vibrate the end effector of an ultrasonic surgical instrument. Once a transducer has exceeded its useful life, the transducer is often disposed of. In various circumstances, the piezoelectric elements of such transducers, for example, may be at least partially comprised of lead and/or other certain materials. In various embodiments described herein, a transducer, and/or surgical instrument, may comprise means in which to encapsulate or contain the piezoelectric elements of the transducer when it is desired to dispose of the transducer. In various embodiments, referring now to FIG. **46**, a transducer assembly, such as transducer assembly **2514**, for example, can comprise a transducer stack **2518** comprising an end-bell **2520**, a fore-bell **2522**, one or more piezoelectric elements **2532** positioned intermediate end-bell **2520** and fore-bell **2522**, for example, and an enclosure which is configured to at least partially enclose the transducer stack **2518**. In at least one embodiment, the enclosure may surround the entire piezoelectric element stack **2518** such that only a portion of the fore-bell **2522** extends through the enclosure in order to allow a wave guide and/or end effector to be operably engaged with the transducer stack **2518**.

In various embodiments, further to the above, transducer assembly **2514** can comprise an enclosure **2561** which can have a first compartment **2563** and a second compartment **2565**, wherein the transducer stack **2518** can be positioned within the first compartment **2563** and a material **2567** can be positioned within the second compartment **2565**. Before disposing of the transducer assembly **2514**, in at least one embodiment, the second compartment **2565** can be ruptured such that the material **2567** can flow from the first compartment **2563** into the second compartment **2565** and at least partially surround transducer stack **2518**, as illustrated in FIG. **47**. In at least one such embodiment, referring to FIG. **46**, a sidewall **2569** can be configured to separate the first compartment **2563** and the second compartment **2565**, wherein the sidewall **2569** can be configured to rupture in at least one location. In various embodiments, sidewall **2569**, for example, can comprise one or more score marks, or weak points, for example, which can determine the locations in which the sidewall **2569** may be most likely to rupture. In certain embodiments, the enclosure **2561** can be configured such that a person can use their hand to squeeze the enclosure **2561** and burst the sidewall **2569** separating first compartment **2563** and second compartment **1265**. In various embodiments, the enclosure **2561** can be configured such the material **2567** cannot thereafter escape, or at least

substantially escape, from enclosure **2561**. In at least one such embodiment, the enclosure **2561** can be sealed, or at least substantially sealed, to fore-bell **2522**, for example, such that the material **2567** cannot flow, or at least substantially flow, between enclosure **2561** and the portion of fore-bell **2522** which extends out of enclosure **2561**.

In various embodiments, referring now to FIG. **48**, a transducer assembly **2614** can comprise an enclosure **2661** comprising at least one valve which can be opened to place a first compartment **2665** in fluid communication with a second compartment **2663**. More particularly, in at least one embodiment, the enclosure **2661** can comprise a sidewall **2669** and one or more valves **2671**, for example, which can be selectively opened to permit material **2667** to flow from first compartment **2665** into second compartment **2663**. In at least one such embodiment, especially in embodiments where material **2667** is a fluid, valves **2671** can be configured to pop open when subjected to sufficient fluid pressure generated within material **2667** when the enclosure **2661** is compressed. In various embodiments, material **2667** can be fluidic when it is positioned within the first compartment **2665** and when it initially surrounds transducer stack **2618**. In certain embodiments, however, the material **2667** can be configured to harden after it has entered into first compartment **2665**. In at least one such embodiment, first compartment **2665** can be air-tight and, when the material **2667** enters into the second compartment **2663**, the material **2667** can be exposed to air, for example, which can cause it to harden. In any event, whether or not the material remains fluidic or hardens, the material can encapsulate, or at least partially encapsulate, certain materials within the transducer stack to further reduce the possibility of such materials from escaping from the enclosure.

A clamp arm assembly **300** is depicted in FIGS. **49-51**. Referring primarily to FIG. **51**, the clamp arm assembly **300** comprises a clamp arm **202** and a tissue pad **208**. The clamp arm **202** has tissue pad **208** attached thereto for squeezing tissue between the ultrasonic blade **88** and clamp arm assembly **300**. Serrations **210** are formed in the clamping surfaces of the tissue pad **208** and extend perpendicular to the axis of an ultrasonic blade **88** to allow tissue to be grasped, manipulated, coagulated and cut without slipping between the clamp arm **202** and the ultrasonic blade **88**. The clamp arm **202** is pivotally mounted to rotate in the direction of arrow **122** in FIG. **49** when a pivoting handle portion **136** is moved in the direction indicated by the arrow **121** in FIG. **49**. By advancing the pivoting handle portion **136** toward an instrument housing, the clamp arm **202** is pivoted into a closed position (FIG. **50**). Retracting the pivoting handle portion **136** away from the instrument housing pivots the clamp arm **202** into an open position (FIG. **49**).

The devices disclosed herein can be designed to be disposed of after a single use, or they can be designed to be used multiple times. In either case, however, the device can be reconditioned for reuse after at least one use. Reconditioning can include any combination of the steps of disassembly of the device, followed by cleaning or replacement of particular pieces, and subsequent reassembly. In particular, the device can be disassembled, and any number of the particular pieces or parts of the device can be selectively replaced or removed in any combination. Upon cleaning and/or replacement of particular parts, the device can be reassembled for subsequent use either at a reconditioning facility, or by a surgical team immediately prior to a surgical procedure. Those skilled in the art will appreciate that reconditioning of a device can utilize a variety of techniques for disassembly, cleaning/replacement, and reassembly. Use

of such techniques, and the resulting reconditioned device, are all within the scope of the present application.

Preferably, the various embodiments described herein will be processed before surgery. First, a new or used instrument is obtained and if necessary cleaned. The instrument can then be sterilized. In one sterilization technique, the instrument is placed in a closed and sealed container, such as a plastic or TYVEK bag. The container and instrument are then placed in a field of radiation that can penetrate the container, such as gamma radiation, x-rays, or high-energy electrons. The radiation kills bacteria on the instrument and in the container. The sterilized instrument can then be stored in the sterile container. The sealed container keeps the instrument sterile until it is opened in the medical facility. Sterilization can also be done by any number of ways known to those skilled in the art including beta or gamma radiation, ethylene oxide, and/or steam.

In various embodiments, an ultrasonic surgical instrument can be supplied to a surgeon with a wave guide and/or end effector already operably coupled with a transducer of the surgical instrument. In at least one such embodiment, the surgeon, or other clinician, can remove the ultrasonic surgical instrument from a sterilized package, plug the ultrasonic instrument into a generator, as outlined above, and use the ultrasonic instrument during a surgical procedure. Such a system can obviate the need for a surgeon, or other clinician, to assemble a wave guide and/or end effector to the ultrasonic surgical instrument. After the ultrasonic surgical instrument has been used, the surgeon, or other clinician, can place the ultrasonic instrument into a sealable package, wherein the package can be transported to a sterilization facility. At the sterilization facility, the ultrasonic instrument can be disinfected, wherein any expended parts can be discarded and replaced while any reusable parts can be sterilized and used once again. Thereafter, the ultrasonic instrument can be reassembled, tested, placed into a sterile package, and/or sterilized after being placed into a package. Once sterilized, the reprocessed ultrasonic surgical instrument can be used once again.

Although various embodiments have been described herein, many modifications and variations to those embodiments may be implemented. For example, different types of end effectors may be employed. Also, where materials are disclosed for certain components, other materials may be used. The foregoing description and following claims are intended to cover all such modification and variations.

Any patent, publication, or other disclosure material, in whole or in part, that is said to be incorporated by reference herein is incorporated herein only to the extent that the incorporated materials does not conflict with existing definitions, statements, or other disclosure material set forth in this disclosure. As such, and to the extent necessary, the disclosure as explicitly set forth herein supersedes any conflicting material incorporated herein by reference. Any material, or portion thereof, that is said to be incorporated by reference herein, but which conflicts with existing definitions, statements, or other disclosure material set forth herein will only be incorporated to the extent that no conflict arises between that incorporated material and the existing disclosure material.

What is claimed is:

1. An ultrasonic surgical instrument, comprising:
 - a handle comprising a pivoting handle portion;
 - an end effector configured to treat tissue, wherein said end effector comprises a clamp arm comprising a tissue pad, and wherein said pivoting handle portion is con-

43

figured to move said clamp arm between an open position and a closed position;
 a waveguide extending to said end effector;
 a battery; and
 a vibration generating system selectively operable in a plurality of energizing operating states, wherein said plurality of energizing operating states consists of:
 a first operating state in which a first power is supplied to said end effector; and
 a second operating state in which a second power is supplied to said end effector, wherein said first power is different than said second power; and
 wherein said vibration generating system comprises:
 a transducer selectively attachable to said handle; and
 a switch configured to operably switch said vibration generating system between said first operating state and said second operating state, wherein said switch is positioned on said handle.

2. The ultrasonic surgical instrument of claim 1, wherein said first operating state comprises a maximum power mode, and wherein said second operating state comprises a minimum power mode.

3. The ultrasonic surgical instrument of claim 1, wherein said first power is less than said second power.

4. The ultrasonic surgical instrument of claim 1, wherein said switch is further configured to operably switch said vibration generating system between said plurality of energizing operating states and a non-energizing operating state.

5. The ultrasonic surgical instrument of claim 1, wherein said end effector comprises an ultrasonic blade configured to dissect tissue.

6. A laparoscopic dissection device, comprising:
 a handle comprising a pivoting handle portion;
 an end effector, comprising:
 a blade configured to dissect tissue; and
 a clamp arm comprising a tissue pad, wherein said pivoting handle portion is configured to move said clamp arm between an open position and a closed position;
 a waveguide extending to said end effector;
 a battery; and
 a dual-mode energy delivery system selectively operable in a plurality of active operating states, wherein said plurality of active operating states consists of:

44

a first operating state in which a maximum power is supplied to said end effector; and
 a second operating state in which a minimum power is supplied to said end effector; and
 wherein said dual-mode energy delivery system comprises:
 a selectively-attachable transducer; and
 a switch configured to operably switch said dual-mode energy delivery system between said first operating state and said second operating state, wherein said switch is positioned on said handle.

7. The laparoscopic dissection device of claim 6, wherein said switch is further configured to operably switch said dual-mode energy delivery system between said plurality of active operating states and an inactive operating state.

8. An ultrasonic surgical device, comprising:
 a handle comprising a pivoting handle portion;
 an end effector, wherein said end effector comprises a clamp arm comprising a tissue pad, wherein said pivoting handle portion is configured to move said clamp arm between an open position and a closed position;
 a waveguide extending to said end effector;
 a battery; and
 a two-stage energy delivery system selectively operable in a plurality of active operational conditions, wherein said plurality of active operational conditions comprises:
 a first operational condition in which a maximum power is supplied to said end effector; and
 a second operational condition in which a minimum power is supplied to said end effector; and
 wherein said two-stage energy delivery system comprises:
 a transducer selectively attachable to said handle; and
 a switch configured to operably switch said two-stage energy delivery system between said first operational condition and said second operational condition, wherein said switch is positioned on said handle.

9. The ultrasonic surgical device of claim 8, wherein said end effector comprises a blade configured to dissect tissue.

10. The ultrasonic surgical device of claim 8, wherein said switch is further configured to operably switch said two-stage energy delivery system between said plurality of active operational conditions and an inactive operational condition.

* * * * *

