



US007540839B2

(12) **United States Patent**  
**Butler et al.**

(10) **Patent No.:** **US 7,540,839 B2**  
(45) **Date of Patent:** **\*Jun. 2, 2009**

(54) **WOUND RETRACTOR**

(75) Inventors: **John Butler**, Blackrock (IE); **Frank Bonadio**, Bray (IE); **Michael Mulhall**, Monkstown (IE); **Ronan Bernard McManus**, Bray (IE)

(73) Assignee: **Atropos Limited**, Bray, Co Wicklow (IE)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 805 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **10/635,017**

(22) Filed: **Aug. 6, 2003**

(65) **Prior Publication Data**

US 2004/0073090 A1 Apr. 15, 2004

**Related U.S. Application Data**

(63) Continuation-in-part of application No. 10/374,523, filed on Feb. 27, 2003, now Pat. No. 7,445,597, which is a continuation of application No. 09/849,341, filed on May 7, 2001, now Pat. No. 6,582,364, which is a continuation of application No. 09/688,138, filed on Oct. 16, 2000, now Pat. No. 6,254,534.

(60) Provisional application No. 60/401,023, filed on Aug. 6, 2002.

(30) **Foreign Application Priority Data**

Oct. 14, 1999 (IE) ..... 990861  
Dec. 16, 1999 (IE) ..... 991053  
Feb. 18, 2000 (EP) ..... 00650010

(51) **Int. Cl.**  
**A61B 1/32** (2006.01)

(52) **U.S. Cl.** ..... **600/208**

(58) **Field of Classification Search** ..... 600/204-210  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

1,157,202 A	10/1915	McLeland
1,598,284 A	8/1926	Kinney
1,810,466 A	6/1931	Deutsch
2,219,564 A	10/1940	Reyniers
2,305,289 A	12/1942	Coburg
2,695,608 A	11/1954	Gibbon
2,835,253 A	5/1958	Borgeson
2,853,075 A	10/1958	Hoffman
3,039,468 A	6/1962	Price
3,111,943 A	11/1963	Orndorff
3,244,169 A	4/1966	Baxter
3,253,594 A	5/1966	Matthews et al.
3,313,299 A	4/1967	Spademan

(Continued)

**FOREIGN PATENT DOCUMENTS**

DE 37 39 532 12/1988

(Continued)


*Primary Examiner*—Anu Ramana

(74) *Attorney, Agent, or Firm*—Finnegan, Henderson, Farabow, Garrett & Dunner L.L.P.

(57) **ABSTRACT**

A surgical wound retractor comprises a retracting member for insertion into a wound opening and a proximal member for location externally of a wound opening. A clamp is used to clamp the retracting member to the proximal member.

**23 Claims, 33 Drawing Sheets**



U.S. PATENT DOCUMENTS					
3,332,417 A	7/1967	Blanford et al.	4,863,438 A	9/1989	Gauderer
3,347,226 A	10/1967	Harrower	4,889,107 A	12/1989	Kaufman
3,347,227 A	10/1967	Harrower	4,895,565 A	1/1990	Hillstead
3,397,692 A	8/1968	Creager, Jr. et al.	4,897,081 A	1/1990	Poirier
3,402,710 A	9/1968	Paleschuck	4,903,710 A	2/1990	Jessamine et al.
3,447,533 A	6/1969	Spicer	4,950,222 A	8/1990	Scott et al.
3,522,800 A	8/1970	Lesser	4,950,223 A	8/1990	Trimark
3,523,534 A	8/1970	Nolan	4,984,564 A	1/1991	Yuen
3,570,475 A	3/1971	Weinstein	4,991,593 A	2/1991	LeVahn
3,656,485 A	4/1972	Robertson	4,998,538 A	3/1991	Charowsky et al.
3,685,786 A	8/1972	Woodson	5,015,228 A	5/1991	Columbus et al.
3,717,151 A	2/1973	Collett	5,019,101 A	5/1991	Purkait
3,729,006 A	4/1973	Wilder et al.	5,041,095 A	8/1991	Littrell
3,782,370 A	1/1974	McDonald	5,045,070 A	9/1991	Grodecki et al.
3,797,478 A	3/1974	Walsh et al.	D320,658 S	10/1991	Quigley et al.
3,807,393 A	4/1974	McDonald	5,071,411 A	12/1991	Hillstead
3,828,764 A	8/1974	Jones	5,074,878 A	12/1991	Bark et al.
3,841,332 A	10/1974	Treacle	5,082,005 A	1/1992	Kaldany
3,853,126 A	12/1974	Schulte	5,092,846 A	3/1992	Nishijima
3,853,127 A	12/1974	Spademan	5,125,897 A	6/1992	Quinn et al.
3,856,021 A	12/1974	McIntosh	5,141,498 A	8/1992	Christian
3,907,389 A	9/1975	Cox et al.	5,149,327 A	9/1992	Oshiyama
3,915,171 A	10/1975	Shermeta	5,158,553 A	10/1992	Berry et al.
3,965,890 A	6/1976	Gauthier	5,159,921 A	11/1992	Hoover
3,996,623 A	12/1976	Kaster	5,161,773 A	11/1992	Tower
4,000,739 A	1/1977	Stevens	5,167,636 A	12/1992	Clement
4,016,884 A	4/1977	Kwan-Gett	5,178,162 A	1/1993	Bose
4,024,872 A	5/1977	Muldoon	5,188,595 A	2/1993	Jacobi
4,030,500 A	6/1977	Ronnquist	5,192,301 A	3/1993	Kamiya et al.
4,083,370 A	4/1978	Taylor	5,207,656 A	5/1993	Kranys
4,096,853 A	6/1978	Weigand	5,209,737 A	5/1993	Richartt
4,130,113 A	12/1978	Graham	5,211,370 A	5/1993	Powers
4,177,814 A	12/1979	Knepshield	5,211,633 A	5/1993	Strouder
4,188,945 A	2/1980	Wenander	5,213,114 A	5/1993	Bailey, Jr.
4,217,664 A	8/1980	Faso	5,234,455 A	8/1993	Mulhollan
4,228,792 A	10/1980	Rhys-Davies	5,242,409 A	9/1993	Buelna
4,239,036 A	12/1980	Krieger	5,248,304 A	9/1993	Vigdorchik et al.
4,240,411 A	12/1980	Hosono	5,263,922 A	11/1993	Sova et al.
4,253,201 A	3/1981	Ross et al.	5,269,763 A	12/1993	Boehmer
4,306,562 A	12/1981	Osborne	D343,236 S	1/1994	Quigley et al.
4,321,915 A	3/1982	Leighton	5,279,575 A	1/1994	Sugarbaker
4,331,138 A	5/1982	Jessen	D346,022 S	4/1994	Quigley et al.
4,338,934 A	7/1982	Spademan	5,299,582 A	4/1994	Potts
4,338,937 A	7/1982	Lehrman	5,300,036 A	4/1994	Mueller
4,367,728 A	1/1983	Mutke	5,308,336 A	5/1994	Hart et al.
4,399,816 A	8/1983	Spangler	5,309,896 A	5/1994	Moll et al.
4,411,659 A	10/1983	Jensen et al.	5,316,541 A	5/1994	Fischer
4,421,296 A	12/1983	Stephens	5,320,611 A	6/1994	Bonutti
4,424,833 A	1/1984	Spector	5,330,437 A	7/1994	Durman
4,428,364 A	1/1984	Bartolo	5,330,497 A	7/1994	Freitas
4,430,081 A	2/1984	Timmermans	5,336,192 A	8/1994	Palestrant
4,434,791 A	3/1984	Darnell	5,342,385 A	8/1994	Norelli et al.
4,436,519 A	3/1984	O'Neill	5,350,364 A	9/1994	Stephens et al.
4,485,490 A	12/1984	Akers et al.	5,364,345 A	11/1994	Lowery et al.
4,488,877 A	12/1984	Klein	5,366,478 A	11/1994	Brinkerhoff et al.
4,543,088 A	9/1985	Bootman	5,368,545 A	11/1994	Schaller et al.
4,550,713 A	11/1985	Hyman	5,383,861 A	1/1995	Hempel
4,553,537 A	11/1985	Rosenberg	5,385,553 A	1/1995	Hart et al.
4,601,710 A	7/1986	Moll	5,391,156 A	2/1995	Hildwein et al.
4,610,665 A	9/1986	Matsumoto	5,403,264 A	4/1995	Wohlrs
4,626,245 A	12/1986	Weinstein	5,407,433 A	4/1995	Loomas
4,634,424 A	1/1987	O'Boyle	5,423,848 A	6/1995	Washizuka et al.
4,649,904 A	3/1987	Krauter	5,429,609 A	7/1995	Yoon
4,654,030 A	3/1987	Moll et al.	5,431,676 A	7/1995	Durbal
4,673,393 A	6/1987	Suzuki et al.	5,443,452 A	8/1995	Hart et al.
4,673,394 A	6/1987	Fenton	5,456,284 A	10/1995	Ryan
4,755,170 A	7/1988	Golden	5,476,475 A	12/1995	Gadberry
4,777,943 A	10/1988	Chvapil	5,480,410 A	1/1996	Cuschieri et al.
4,784,646 A	11/1988	Feingold	5,496,280 A	3/1996	Vandenbroeck
4,798,594 A	1/1989	Hillstead	5,503,112 A	4/1996	Luhman
4,809,679 A	3/1989	Shimonaka	5,514,109 A	5/1996	Mollenauer et al.
			5,514,133 A	5/1996	Golub et al.
			5,520,632 A	5/1996	Leveen

# US 7,540,839 B2

Page 3

5,522,791 A	6/1996	Leyva	6,162,206 A	12/2000	Bindokas
5,522,824 A	6/1996	Ashby	6,163,949 A	12/2000	Neuenschwander
5,524,644 A	6/1996	Crook	6,164,279 A	12/2000	Tweedle
5,526,536 A	6/1996	Cartmill	6,171,282 B1	1/2001	Ragsdale
5,545,179 A	8/1996	Williamson, IV	6,183,486 B1	2/2001	Snow et al.
5,562,632 A	10/1996	Davila	6,238,373 B1	5/2001	de la Torre et al.
5,562,688 A	10/1996	Riza	6,254,533 B1	7/2001	Fadem et al.
5,584,850 A	12/1996	Hart et al.	6,254,534 B1	7/2001	Butler et al.
5,601,579 A	2/1997	Semertzides	6,258,065 B1	7/2001	Dennis
5,620,415 A	4/1997	Lucey	6,315,770 B1	11/2001	de la Torre et al.
5,632,979 A	5/1997	Goldberg	6,319,246 B1	11/2001	de la Torre et al.
5,634,911 A	6/1997	Hermann et al.	6,322,541 B2	11/2001	West
5,634,936 A	6/1997	Linden	6,346,074 B1	2/2002	Roth
5,634,937 A	6/1997	Mollenauer et al.	6,382,211 B1	5/2002	Crook
5,636,645 A	6/1997	Ou	6,420,475 B1	7/2002	Chen
5,640,977 A	6/1997	Leahy et al.	6,440,063 B1	8/2002	Beane
5,649,550 A	7/1997	Crook	6,450,983 B1	9/2002	Rambo
5,653,705 A	8/1997	de la Torre et al.	6,454,783 B1	9/2002	Piskun
5,657,963 A	8/1997	Hinchliffe	6,485,435 B1	11/2002	Bakal
5,658,272 A	8/1997	Hasson	6,533,734 B1	3/2003	Corley, III et al.
5,658,306 A	8/1997	Kieturakis	6,554,793 B1	4/2003	Pauker
5,672,168 A	9/1997	de la Torre et al.	6,578,577 B2	6/2003	Bonadio et al.
5,685,854 A	11/1997	Green	6,582,364 B2	6/2003	Butler et al.
5,707,703 A	1/1998	Rothrum et al.	6,589,167 B1	7/2003	Shimonmura
5,709,664 A	1/1998	Vandenbroeck	6,589,211 B1	7/2003	MacLeod
5,720,730 A	2/1998	Blake, III	6,607,504 B2	8/2003	Haarala
5,738,628 A	4/1998	Sierocuk et al.	6,613,952 B2	9/2003	Rambo
5,741,234 A	4/1998	Aboul-Hosn	6,623,426 B2	9/2003	Bonadio et al.
5,741,298 A	4/1998	MacLeod	6,706,050 B1	3/2004	Giannadakis
5,749,882 A	5/1998	Hart et al.	6,714,298 B2	3/2004	Ryer
5,755,660 A	5/1998	Tyagi	6,723,044 B2	4/2004	Pulford
5,769,783 A	6/1998	Fowler	6,796,940 B2	9/2004	Bonadio et al.
5,782,812 A	7/1998	Hart et al.	6,797,765 B2	9/2004	Pearce
5,795,290 A	8/1998	Bridges	6,814,078 B2	11/2004	Crook
5,803,919 A	9/1998	Hart et al.	6,814,700 B1	11/2004	Mueller et al.
5,803,921 A	9/1998	Bonadio	6,840,951 B2	1/2005	de la Torre et al.
5,807,350 A	9/1998	Diaz	6,846,287 B2	1/2005	Bonadio et al.
5,810,721 A	9/1998	Mueller et al.	6,866,861 B1	3/2005	Luhman
5,813,409 A	9/1998	Leahy et al.	6,884,253 B1	4/2005	McFarlane
5,814,026 A	9/1998	Yoon	6,902,541 B2	6/2005	Zevox
5,817,062 A	10/1998	Flom	6,908,430 B2	6/2005	Caldwell
5,820,555 A	10/1998	Mueller	6,916,331 B2	7/2005	Mollenauer et al.
5,832,925 A	11/1998	Rothrum	6,936,037 B2	8/2005	Bubb
5,853,395 A	12/1998	Crook et al.	6,939,296 B2	9/2005	Ewers
5,871,474 A	2/1999	Hermann et al.	6,945,932 B1	9/2005	Caldwell et al.
5,882,344 A	3/1999	Strouder	6,958,037 B2	10/2005	Ewers
5,899,208 A	5/1999	Bonadio	6,979,324 B2	12/2005	Bybordi
5,904,703 A	5/1999	Beane	7,008,377 B2	3/2006	Beane
5,906,577 A	5/1999	Beane et al.	7,052,454 B2	5/2006	Taylor
5,916,232 A	6/1999	Hart	7,081,089 B2	7/2006	Bonadio et al.
5,947,922 A	9/1999	MacLeod	7,195,590 B2	3/2007	Butler et al.
5,951,467 A	9/1999	Picha et al.	2001/0037053 A1	11/2001	Bonadio et al.
5,957,913 A	9/1999	de la Torre et al.	2001/0039430 A1	11/2001	Dubrul et al.
5,964,781 A	10/1999	Mollenauer et al.	2002/0038077 A1	3/2002	de la Torre et al.
5,993,485 A	11/1999	Beckers	2003/0139756 A1	7/2003	Brustad
5,994,450 A	11/1999	Pearce	2003/0187376 A1	10/2003	Rambo
5,997,515 A	12/1999	de la Torre et al.	2003/0192553 A1	10/2003	Rambo
6,024,736 A	2/2000	de la Torre et al.	2003/0225392 A1	12/2003	McMichael
6,025,067 A	2/2000	Fay	2004/0024363 A1	2/2004	Goldberg
6,033,426 A	3/2000	Kaji	2004/0049100 A1	3/2004	Butler et al.
6,033,428 A	3/2000	Sardella	2004/0073090 A1	4/2004	Butler et al.
6,042,573 A	3/2000	Lucey	2004/0092796 A1	5/2004	Butler et al.
6,048,309 A	4/2000	Flom et al.	2004/0093018 A1	5/2004	Johnson
6,059,816 A	5/2000	Moenning	2004/0106942 A1	6/2004	Taylor
6,077,288 A	6/2000	Shimomura et al.	2004/0143158 A1	7/2004	Hart et al.
6,110,154 A	8/2000	Shimomura et al.	2004/0215063 A1	10/2004	Bonadio et al.
6,123,689 A	9/2000	To	2005/0020884 A1	1/2005	Heart et al.
6,142,935 A	11/2000	Flom et al.	2005/0033246 A1	2/2005	Ahlberg
6,142,936 A	11/2000	Beane et al.	2005/0059865 A1	3/2005	Kahle
6,150,608 A	11/2000	Wambeke	2005/0065543 A1	3/2005	Kahle
6,159,182 A	12/2000	Davis	2005/0090713 A1	4/2005	Gonzales et al.
6,162,172 A	12/2000	Cosgrove et al.	2005/0090716 A1	4/2005	Bonadio et al.
6,162,196 A	12/2000	Hart et al.	2005/0090717 A1	4/2005	Bonadio et al.

2005/0131349	A1	6/2005	Albrecht	WO	WO 86/06272	11/1986
2005/0148823	A1	7/2005	Vaugh et al.	WO	WO 92/11880	7/1992
2005/0159647	A1	7/2005	Hart et al.	WO	WO 92/21292	12/1992
2005/0192598	A1	9/2005	Johnson	WO	WO 93/05740	4/1993
2005/0240082	A1	10/2005	Bonadio et al.	WO	WO 95/05207	2/1995
2005/0241647	A1	11/2005	Nguyen	WO	WO 95/07056	3/1995
2005/0277946	A1	12/2005	Greenhalgh	WO	WO 95/22289	8/1995
2005/0288558	A1	12/2005	Ewers	WO	WO 95/24864	9/1995
2005/0288634	A1	12/2005	O'Herron	WO	WO 95/27445	10/1995
2006/0041270	A1	2/2006	Lenker	WO	WO 95/27468	10/1995
2006/0047284	A1	3/2006	Gresham	WO	WO 96/36283	11/1996
2006/0106402	A1	5/2006	McLucas	WO	WO 97/32514	9/1997
2006/0149306	A1	7/2006	Hart et al.	WO	WO 97/32515	9/1997
2006/0247498	A1	11/2006	Bonadio et al.	WO	WO 98/35614	8/1998

## FOREIGN PATENT DOCUMENTS

DE	37 37 121	5/1989	WO	WO 98/48724	11/1998
DE	296 00 939	6/1998	WO	WO 99/03416	1/1999
EP	0142262	5/1985	WO	WO 99/25268	5/1999
EP	0537768	4/1993	WO	WO 99/29250	6/1999
EP	0950376	10/1999	WO	WO 00/32116	6/2000
EP	1118657	7/2001	WO	WO 00/32117	6/2000
FR	1456623	9/1966	WO	WO 00/32119	6/2000
GB	1151993	5/1969	WO	WO 00/32120	6/2000
GB	1355611	6/1974	WO	WO 00/35356	6/2000
GB	1372491	10/1974	WO	WO 00/54675	9/2000
GB	1379772	1/1975	WO	WO 00/54676	9/2000
GB	1400808	7/1975	WO	WO 00/54677	9/2000
GB	1407023	9/1975	WO	WO 01/08563	2/2001
GB	1496696	12/1977	WO	WO 01/08581	2/2001
GB	2071502	9/1981	WO	WO 01/26558	4/2001
GB	2255019	10/1992	WO	WO 01/91652	12/2001
GB	2275420	8/1994	WO	WO 02/34108 A2	5/2002
JP	10-108868	4/1998	WO	WO 03/026512 A1	4/2003
JP	11-290327	10/1999	WO	WO 03/034908 A3	5/2003
JP	2001-61850	3/2001	WO	WO 03/061480 A1	7/2003
JP	2004-195037	7/2004	WO	WO 03/103548 A1	12/2003
RU	SU 1342485	1/1997	WO	WO 2004/026153 A1	4/2004
			WO	WO 2004/030547 A	4/2004
			WO	WO 2005/009257 A2	2/2005






Fig.1

*Fig. 2*






Fig. 4










Fig. 5




















Fig. 14






Fig. 16






Fig. 17




Fig. 19




Fig. 18





Fig. 20









Fig. 22









Fig. 31










Fig. 33













Fig. 36








*Fig. 42*



*Fig. 43*











Fig. 49



**WOUND RETRACTOR**

This application is a Continuation-In-Part of U.S. application Ser. No. 10/374,523, filed on Feb. 27, 2003 now U.S. Pat. No. 7,445,597 which is a Continuation of application Ser. No. 09/849,341, filed on May 7, 2001, now U.S. Pat. No. 6,582,364, which is a Continuation of application Ser. No. 09/688,138, filed Oct. 16, 2000, now U.S. Pat. No. 6,254,534, all of which are incorporated herein by reference. This application claims the priority to Ireland application No. 990861, filed on Oct. 14, 1999, Ireland application No. 991053, filed on Dec. 16, 1999, European application No. 00650010, filed on Feb. 18, 2000, and also claims the benefit of U.S. Provisional Application No. 60/401,023, filed on Aug. 6, 2002, all of which are incorporated herein by reference.

**INTRODUCTION**

The invention relates to a retractor. In particular the invention relates to a retractor for retracting the margins of an incision or a natural bodily orifice to provide maximum exposure of an organ or body structures for examination and/or access for surgical procedures, while also providing protection for the exposed sides of the incised tissue.

Various retractors are known. However in general known retractors are difficult and cumbersome to use, and/or are relatively expensive. In addition known retractors are limited to use with a particular size of incision and a particular patient anatomy.

This invention is directed towards providing an improved wound retractor which will overcome at least some of these problems, and in addition provide a means of wound protection during a surgical procedure.

**STATEMENTS OF INVENTION**

According to the invention there is provided a surgical wound retractor comprising:

- a retracting member for insertion into a wound opening;
- a proximal member for location externally of a wound opening; and
- a clamp for clamping the retracting member to the proximal member.

In one embodiment of the invention the proximal member is movable relative to the retracting member to shorten the axial extent of the retracting member for lateral retraction of a wound opening.

The clamp may be configured to clamp the retracting member to a proximal surface of the proximal member. The clamp may be configured to clamp the retracting member to a distal surface of the proximal member.

In one case the clamp comprises at least one clip. Preferably the clamp comprises two or more clips spaced around the proximal member. Ideally the clips are equi-spaced around the proximal member. The location of the clip on the proximal member may be adjustable.

In a preferred embodiment the proximal member comprises at least one protrusion, and the clip is configured to clamp the retracting member to the proximal member at the protrusion. Ideally the clip is configured to clamp the retracting member from the outer side of the proximal member.

The clip may be substantially "C"-shaped. Ideally the clip is a bulldog clip.

In another case the clip comprises a first clip part and a second clip part. The first clip part is preferably an outer clip part and the second clip part is preferably an inner clip part. The first clip part may be configured to overlap the second clip

part to enclose a portion of the proximal member. The clip may be configured for assembly of the first clip part and the second clip part together. Ideally the clip is configured for snap-fit assembly of the first clip part and the second clip part together.

In one embodiment the proximal member comprises an annular ring means. Preferably the annular ring means comprises a ring over which the retracting member may be led.

In another preferred case the annular ring means comprises an inner ring and an outer ring between which the retracting member may be led. Ideally the inner ring defines a projection for location in a complementary recess of the outer ring with the retracting member located therebetween.

The inner ring may be a relatively loose fit in the recess of the outer ring. The inner ring may be a relatively tight fit in the recess of the outer ring to grip the retracting member therebetween.

In another embodiment at least portion of one of the rings is movable from a rest position in which the retracting member is substantially clamped between the rings to a release position in which at least portion of the retracting member is movable relative to the rings. In one case only portion of the retracting member is movable relative to the rings in the release position.

The outer ring may comprise a plurality of interconnected segments which are independently movable to facilitate localised release of the retracting member for adjusting the retraction force applied at a wound opening. Preferably the ring or segment thereof is manually manipulable between the clamped rest position and the release position.

In a further embodiment of the invention the proximal member comprises one or more anchor formations to which the retracting member may be attached on retraction of a wound opening.

A surface of the proximal member which engages with the retracting member may be of a material with a low coefficient of friction. Preferably the surface is of polytetrafluoroethylene.

An inner wound engaging portion of the retracting member preferably comprises a sleeve for lining a wound opening. Ideally a proximal portion of the retracting member comprises a sleeve extension of the inner wound engaging portion of the retracting member. Most preferably the sleeve is generally cylindrical.

Desirably the retracting member comprises a proximal reinforcing means. The proximal reinforcing means may comprise a ring.

In a further preferred case the retractor comprises a distal member coupled to a distal end of the retracting member for insertion into a wound opening. Ideally the distal member is of a resilient material. Most preferably the distal member comprises an O-ring.

The retractor may comprise a platform for attachment of another device to the retractor. In one case the platform is provided by the proximal member. In another case the platform is provided by the clamp.

In another aspect the invention provides a surgical wound retractor comprising:

- a retracting member movable from an insertion configuration to a retracting configuration to retract laterally a wound opening; and

means for clamping the retracting member in the retracting configuration to maintain a wound opening retracted.

In a preferred embodiment the means for clamping comprises a clamp for clamping the retracting member to a proximal member located externally of the wound opening.

The invention also provides in a further aspect a surgical wound retractor comprising:

a distal anchoring member for insertion into a wound opening;

a connecting means having an inner wound engaging portion and an outer portion, the wound engaging portion being mounted to the distal anchoring member, the connecting means having an insertion configuration in which the inner wound engaging portion has a reduced radial dimension and a retracting configuration;

an external guide means for the outer portion of the connecting means;

the external guide means being movable relative to the connecting means to shorten the axial extent of the connecting means and thereby bias the wound engaging portion of the connecting means into the retracting configuration to retract the wound opening laterally; and

a clamp for clamping the connecting means to the external guide means to maintain retraction of the opening.

According to another aspect of the invention there is provided a method of retracting a wound opening, the method comprising the steps of:

inserting a retracting member into a wound opening;

locating a proximal member externally of the wound opening;

moving at least part of the retracting member laterally to retract the wound opening; and

clamping the retracting member to the proximal member to maintain the wound opening retracted.

In one embodiment of the invention the retracting member is clamped to the proximal member at one or more locations around the proximal member.

The method may comprise the step of adjusting the location of clamping of the retracting member to the proximal member.

In one case at least part of the retracting member is moved laterally by moving the proximal member relative to the retracting member to shorten the axial extent of the retracting member. Ideally the proximal member is moved relative to the retracting member by gripping the retracting member and pulling the retracting member relative to the proximal member.

In a further aspect of the invention, there is provided a method for retracting a wound opening using a surgical wound retractor comprising a distal anchoring member, a connecting means having a wound engaging portion mounted to the distal anchoring member and an outer portion, an external guide means for the outer portion of the connecting means and a clamp; the method comprising the steps of:

positioning the distal anchoring member to be retained inside a wound opening with the connecting means extending outwardly therefrom through the opening;

moving the external guide means relative to the outer portion of the connecting means to shorten the axial extent of the connecting means and thereby bias the wound engaging portion into a retracting configuration to retract the wound opening; and

clamping the connecting means to the external anchoring means to maintain retraction of the wound opening.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be more clearly understood from the following description thereof given by way of example only with reference to the accompanying drawings, in which:

FIG. 1 is an exploded view of a wound retractor according to the invention;

FIG. 2 is a perspective view of the retractor of FIG. 1 assembled;

FIG. 3 is a side cross sectional view of the assembled retractor of FIG. 2;

FIG. 4 is a perspective view of an unretracted wound opening;

FIG. 5 is a perspective view illustrating insertion of part of the retractor of FIG. 2 into the wound opening;

FIG. 6 is a side cross sectional view of the retractor of FIG. 2 after insertion;

FIG. 7 is a plan view of the retractor of FIG. 2 after insertion;

FIGS. 8(a) and 8(b) are side cross sectional views illustrating lateral retraction of the wound opening using the retractor of FIG. 2;

FIG. 9 is a side cross sectional view of the retractor of FIG. 2 after lateral retraction of the wound opening;

FIG. 10 is a plan view of the retractor of FIG. 2 after lateral retraction of the wound opening;

FIG. 11 is a plan view of a part of a guide means of the retractor of FIG. 2;

FIG. 12 is a side view of the part of FIG. 11;

FIG. 13 is a cross sectional view along the line A-A in FIG. 11;

FIG. 14 is a perspective view of a clip according to the invention;

FIG. 15 is a cross-sectional, side view illustrating lateral retraction of a wound opening using the retractor of FIG. 2;

FIG. 16 is a cross-sectional, side view of the clip of FIG. 14 mounted to the retractor of FIG. 15;

FIG. 17 is a plan view of the clip of FIG. 14 mounted to the retractor of FIG. 15;

FIG. 18 is a cross-sectional, side view of four of the clips of FIG. 14 mounted to another wound retractor according to the invention;

FIG. 19 is a plan view of four of the clips of FIG. 14 mounted to the retractor of FIG. 18;

FIGS. 20 and 21 are views similar to FIGS. 18 and 19 of another wound retractor according to the invention;

FIG. 22 is a plan view illustrating retraction of a wound opening using the retractor of FIGS. 20 and 21 and two of the clips of FIG. 14;

FIG. 23 is a plan view of the retractor of FIG. 2 and another clip according to the invention;

FIG. 24 is a view along line IV-IV in FIG. 23;

FIG. 25 is an enlarged, cross-sectional, side view of the retractor of FIG. 2 and the clip of FIG. 23;

FIG. 26 is a perspective view of the retractor of FIG. 2 and the clip of FIG. 23;

FIGS. 27 to 30 are views similar to FIGS. 23 to 26 of the clip of FIG. 23 mounted to the retractor of FIG. 2;

FIG. 31 is a cross sectional view of part of another wound retractor according to the invention;

FIG. 32 is a cross sectional view of the retractor of FIG. 31, in use;

FIG. 33 is an exploded view of parts of another wound retractor according to the invention;

FIG. 34 is a perspective view of the wound retractor of FIG. 33 assembled;

FIGS. 35 and 36 are perspective cut-away views of the retractor of FIG. 34 in different positions;

FIG. 37 is a schematic plan view illustrating manipulation of a part of the retractor of FIGS. 34 to 36;

FIG. 38 is a side cross sectional view of the retractor part in the configuration of FIG. 37;

FIG. 39 is a schematic plan view of the retractor part in a release position;

FIG. 40 is a side cross sectional view of the retractor part in the configuration of FIG. 39;

FIG. 41 is a perspective view of a hand access device for use with a wound retractor according to the invention;

FIG. 42 is a side cross sectional view of the retractor of FIG. 2 with the hand access device of FIG. 41 in position;

FIG. 43 is a perspective view of a drape for use with a wound retractor according to the invention;

FIG. 44 is a side cross sectional view of the retractor of FIG. 2 with the drape of FIG. 43 in position;

FIG. 45 is a perspective view of a form retaining device in a pliable state for use with a wound retractor according to the invention;

FIG. 46 is a perspective view of the form retaining device of FIG. 45 in a stiff state;

FIG. 47 is a side cross sectional view of the retractor of FIG. 2 with the stiffened form retaining device of FIG. 46 in position;

FIG. 48 is an exploded view of the form retaining device of FIG. 45 and a clamp;

FIG. 49 is a side view of the form retaining device of FIG. 45 and the clamp of FIG. 48; and

FIG. 50 is a side cross sectional view of the retractor of FIG. 2 with the form retaining device of FIG. 45 and the clamp of FIG. 48 in position.

#### DETAILED DESCRIPTION

Referring to FIGS. 1 to 13 there is illustrated a wound retractor 101 according to the invention, which in the case illustrated is used to retract the margins of a wound such as an abdominal wound opening 103, as illustrated in FIG. 4.

The retractor 101 comprises a distal anchoring member, in this case in the form of a resilient inner O-ring 105, for insertion into the wound opening 103, and a connecting means, in this case in the form of an elastomeric sleeve 106 which is substantially cylindrical. The sleeve 106 has an inner wound engaging portion and an outer portion, and the wound engaging portion is attached to the inner O-ring 105. The sleeve 106 has an insertion configuration in which the inner wound engaging portion has a reduced radial dimension and a retracting configuration to retract the wound opening 103 laterally.

An external guide means is provided for the outer portion of the sleeve 106, and in this case the guide means comprises an inner ring part 110 and an outer ring part 111 between which the sleeve 106 is led. The retractor 101 includes external anchoring means for anchoring the sleeve 106 to maintain retraction of the wound opening 103, and in this case the anchoring means is provided by a plurality of anchor formations 120 on the outer surface of the outer ring part 111 (FIG. 2), the formations 120 extending radially outwardly to define hooks.

The outer ring part 111 is of the same annular shape as the inner ring part 110 but has a larger diameter and a recess 116. The inner ring part 110 is of a relatively stiff material and mates with the outer ring part 111 in the recess 116 to slidably retain the sleeve 106 therebetween, as illustrated in FIG. 3. In this case the ring parts 110, 111 are a relatively loose fit to facilitate movement of the ring parts 110, 111 relative to the sleeve 106 to shorten the axial extent of the sleeve 106 and thereby bias the wound engaging portion into the retracting configuration to retract the wound opening 103 laterally.

The ring parts 110, 111 are of a material with a low coefficient of friction such as Polytetrafluoroethylene (PTFE). PTFE is a tough, non-resilient material of moderate tensile strength and with excellent lubricity.

The retractor 101 also includes a proximal reinforcing means for engagement with the anchor formations 120, and in this case the reinforcing means is provided by a resilient outer O-ring 109 of a material which is flexible relative to the inner O-ring 105. The outer O-ring 109 is attached to the proximal end of the sleeve 106, the rings 105, 109 helping to maintain the open shape of the sleeve 106 at its extremities (FIG. 2).

In use the inner O-ring 105 and the sleeve 106 are squeezed into the insertion configuration for insertion of the inner O-ring 105 into the wound opening 103 (FIG. 5). The inner O-ring 105 is of a polymeric material which facilitates scrunching up of the inner O-ring 105 into a low-profile, elongate shape, as illustrated in FIG. 5, to facilitate ease of use. On release of the inner O-ring 105, the resilient O-ring 105 returns to its normal O-shape overlapping an inner edge of the wound opening 103 to safely anchor the retractor 101 in the wound, as illustrated in FIG. 6. As may be seen from FIGS. 6 and 7, after insertion of the inner O-ring 105, the wound opening 103 is substantially closed and the sleeve 106 is in a wrinkled compressed configuration.

The sleeve 106 is then pulled while pushing the ring parts 110, 111 against the tissue surrounding the wound opening 103, as illustrated in FIG. 8(a), to shorten the axial extent of the sleeve 106 and thereby bias the wound engaging portion into the retracting configuration to retract laterally the right-hand side (as viewed in FIG. 8(a)) of the wound opening 103. The right-hand side of the outer O-ring 109 is hooked around the formations 120 to maintain the right-hand side of the wound opening 103 retracted (FIG. 8(b)). The left-hand side of the sleeve 106 is then pulled while pushing the ring parts 110, 111 to retract laterally the left-hand side of the wound opening 103, as illustrated in FIG. 8(b). The left-hand side of the outer O-ring 109 is then hooked around the formations 120 to maintain the entire wound opening 103 fully retracted, as illustrated in FIGS. 9 and 10.

The separate formations 120 and the configuration of the wound retractor 101 generally allow the sleeve 106 to be readily manipulated locally as illustrated in FIGS. 8(a) and 8(b) to provide an optimised retraction force. Thus, the manipulation is not simply limited to a single vertical axis but can be carried out in several different directions by pulling of the sleeve 106, and localised hooking of the outer O-ring 109 to the appropriate formation 120. In this way the retractor 101 can be tailored to a particular application.

The recess 116 against which the sleeve 106 is slidably retained by the inner ring part 110 is C-shaped with an extended upper lip 117, as may be seen in FIG. 13. The upper lip 117 maintains the inner ring part 110 safely within the recess 116 regardless of the pulling direction or tensile pulling force exerted on the sleeve 106.

It is preferable to pull the sleeve 106 in a non-vertical direction and to perform localised hooking of the outer O-ring 109, and the extended upper lip 117 encourages non-vertical pulling of the sleeve 106.

The elastomeric sleeve 106 lines the side of the retracted wound opening 103, as illustrated in FIG. 9, and thus acts both as a means of wound retraction and wound protection.

The surgical wound retractor is of simple construction, is easy to use and can be manufactured inexpensively to provide a disposable unit.

A single wound retractor according to the invention may be used for a wide range of incision sizes and to achieve a range of different localised retraction forces which are required to accommodate the incision, the patient anatomy and the surgical procedure to be performed.

FIG. 14 illustrates a clip 300, in this case a bulldog clip, for clamping the sleeve 106 to the outer ring part 111. In this



manner the clip 300 may be used to assist anchoring of the sleeve 106 in a retracted configuration and thereby maintain the wound opening 103 retracted.

The clip 300 is substantially "C"-shaped, and has an inwardly protruding shoulder 301 at the end of one arm of the C (FIG. 14).

In use, the inner O-ring 105 and the sleeve 106 are inserted into the wound opening 103, the right-hand side (as viewed in FIGS. 15 to 17) of the sleeve 106 is pulled to retract the right-hand side of the wound opening 103, and the right-hand side of the outer O-ring 109 is hooked around the formations 120 to maintain the right-hand side of the wound opening 103 retracted, in a manner similar to that described previously with reference to FIGS. 4 to 8(b).

The clip 300 is then mounted to the ring parts 110, 111 to clamp the sleeve 106 to the proximal surface of the outer ring part 111, as illustrated in FIGS. 16 and 17. In this way the clip 300 assists in ensuring the right-hand side of the wound opening 103 remains retracted.

The shoulder 301 assists in securing the clip 300 in position mounted to the outer ring part 111.

The left-hand side of the O-ring 109 is then pulled to retract the left-hand side of the wound opening 103, and the left-hand side of the O-ring 109 is hooked around the formations 120 to maintain the left-hand side of the wound opening 103 retracted, in a manner similar to that described previously with reference to FIGS. 8(b) to 10.

Further clips 300 may be mounted to the ring parts 110, 111 to assist in anchoring the wound opening 103 in the fully retracted configuration.

It will be appreciated that the clips 300 may be mounted to the ring parts 110, 111 at any suitable points around the circumference of the ring parts 110, 111. In particular it is not essential that the clip 300 be mounted to the outer ring part 111 at the anchor formation 120.

Because the clips 300 are separate components from the ring parts 110, 111, this provides an operator with enhanced operational freedom. In particular the retraction force applied to particular points of the wound opening 103 may be tailored by a suitable selection of the number and location of the clips 300.

In FIGS. 18 and 19 there is illustrated another wound retractor 310 according to the invention, which is similar to the wound retractor 101 of FIGS. 1 to 13, and similar elements in FIGS. 18 and 19 are assigned the same reference numerals.

In the case of the wound retractor 310, the outer ring part 111 has no anchor formations. The outer surface of the outer ring part 111 is smooth, as illustrated in FIG. 18.

In use the outer O-ring 109 is pulled over the outer ring part 111, and the clips 300 are mounted to the ring parts 110, 111 to clamp the sleeve 106 to the proximal surface of the outer ring part 111. In this case the clips 300 provide the only means of anchoring the sleeve 106 to maintain the wound opening 103 in the retracted configuration, as illustrated in FIG. 19.

Four clips 300 are illustrated in FIGS. 18 and 19 mounted to the ring parts 110, 111 equi-spaced around the circumference of the ring parts 110, 111. However it will be appreciated that any suitable number of clips 300 may be mounted to the ring parts 110, 111 at any suitable points around the circumference of the ring parts 110, 111 to achieve the desired anchoring of the sleeve 106.

FIGS. 20 to 22 illustrate a further wound retractor 320 according to the invention, which is similar to the wound retractor 310 of FIGS. 18 and 19, and similar elements in FIGS. 20 to 22 are assigned the same reference numerals.

In the case of the wound retractor 320, the external guide means comprises the inner ring part 110 only. There is no outer ring part provided in this case, as illustrated in FIG. 20.

In use the outer O-ring 109 is pulled over the ring part 110, and the clips 300 are mounted to the ring part 110 to clamp the sleeve 106 to the proximal surface of the ring part 110. The clips 300 provide the only means of anchoring the sleeve 106 to maintain the wound opening 103 in the retracted configuration, as illustrated in FIG. 21.

Any suitable number of clips 300 may be mounted to the ring part 110 at any suitable points around the circumference of the ring part 110 to achieve the desired anchoring of the sleeve 106.

As illustrated in FIG. 22 the number and location of the clips 300 may be selected by the operator to achieve a desired retraction force at a particular point of the wound opening 103.

It will be appreciated that the clip 300 is suitable for use with a variety of different wound retractors. In certain cases, the clip 300 provides assistance to other means of anchoring the sleeve 106 to maintain the wound opening 103 retracted. In other cases, the clip 300 provides the only means of anchoring the sleeve 106 to maintain the wound opening 103 retracted.

Referring now to FIGS. 23 to 30, there is illustrated another clip for clamping the sleeve 106 to the outer ring part 110.

In this case, the clamping clip comprises an outer clip part 330 and an inner clip part 331, the clip parts 330, 331 being substantially "C"-shaped. The outer clip part 330 is configured to overlap the inner clip part 331 so that the ring parts 110, 111 are completely enclosed within the clip when the sleeve 106 is clamped to the outer ring part 110 (FIGS. 28 and 29).

The outer clip part 330 has two inwardly protruding fingers 332 for reception in two co-operating recesses 333 in the inner clip part 331 for snap-fit assembly of the clip parts 330, 331 together.

In use, the inner O-ring 105 and the sleeve 106 are inserted into the wound opening 103, the sleeve 106 is pulled to retract the wound opening 103, and the outer O-ring is pulled over the outer ring part 111.

The clip parts 330, 331 are then mounted to the ring parts 110, 111 and snap-fitted together with the inner clip part 331 along the interior of the ring parts 110, 111 and the outer clip part 330 along the exterior of the ring parts 110, 111.

The inner clip part 331 clamps the sleeve 106 to both the proximal surface of the outer ring part 111 and to the distal surface of the outer ring part 111 (FIG. 29). In this way the clip anchors the sleeve 106 to maintain the wound opening 103 retracted.

The snap-fit assembly of the ring parts 110, 111 together assists in maintaining the position of the inner clip part 331 clamping the sleeve 106 to the outer ring part 111.

It will be appreciated that any suitable number of clips may be mounted to the ring parts 110, 111 at any suitable points around the circumference of the ring parts 110, 111 to achieve the desired anchoring of the sleeve 106.

As illustrated in FIGS. 28 and 29, the outer O-ring is not hooked around the formations 120 on the outer ring part 111. When the clip parts 330, 331 are mounted to the ring parts 110, 111, the outer O-ring 109 remains outside of the assembled clip which encloses the ring parts 110, 111.

In FIGS. 23 to 30, the clip is illustrated in use with the wound retractor 101 described previously with reference to FIGS. 1 to 13. It will be appreciated however that the clip is

also suitable for use with other wound retractors, such as the wound retractor **310** of FIGS. **18** and **19**, or the wound retractor **320** of FIGS. **20** to **22**.

In the retractor of FIGS. **1** to **10** the sleeve **106** is a relatively tight fit between the outer and inner guide ring parts **110, 111**. It is also possible to configure the outer and inner ring parts **110, 111** so that the inner ring part **110** is a relatively looser fit in the outer part **111**. In this case the guide means comprises an outer ring part or other annular shape within which slides a second component. The second component is of the same annular shape as the outer ring part but with a lesser diameter and has an exterior compartmental recess designed so that the outer ring part fits loosely around the second component and both can easily slide relative to each other. The components fit loosely together so that an elastomeric sleeve can fit in the gap between them and slide therein. Such an arrangement is illustrated in FIGS. **31** and **32**. On pulling of a local area of the sleeve **106** as indicated in FIG. **32** the inner ring part **110** moves to the opposite side clamping the sleeve **106** at that opposite side while allowing local manipulation of the gripped section of sleeve **106** allowing the local retraction force at the gripped side to be optimised prior to anchoring of the sleeve **106** at that side. This procedure may be repeated at other local regions of the sleeve **106**.

Referring to FIGS. **33** to **40** there is illustrated another wound retractor **150** according to the invention which is similar to the wound retractor **101** described with reference to FIGS. **1** to **13** and like parts are assigned the same reference numerals in FIGS. **33** to **40**.

In this case the guide means comprises the inner ring part **110** and an outer PTFE ring part **151** configured so that the outer ring part **151** engages the inner ring part **110** at a plurality of discrete points circumferentially spaced around the outer ring part **151** to clamp the sleeve **106** between the inner and outer ring parts **110, 151** at each discrete point. The outer ring part **151** comprises a plurality of interconnected segments **155** circumferentially spaced around the outer ring part **151** which press on the inner ring part **110** to clamp the sleeve **106** and are independently movable to facilitate localised release of the sleeve **106** for adjustment of the retraction force.

Cut-out T-slots **156** are provided between the segments **155** and a main body **158** of the outer ring part **151**, and handles **160** project radially outwardly of the main body **158** of the outer ring part **151** intermediate the segments **155**.

In use, adjacent handles **160** are manually gripped as illustrated in FIG. **37** to apply a release force in the direction of arrows A which in turn pulls the local segment **155** in the direction of arrow B from a rest position clamping the sleeve **106** (FIGS. **37** and **38**) to a release position (FIGS. **39** and **40**) in which the sleeve **106** is readily pulled and manipulated locally. By releasing the clamp between the inner ring part **110** and the segment **155** the elastomeric sleeve **106** is readily slid from one position to another. This arrangement is particularly advantageous to facilitate local manipulation of the retraction force.

In general, the wound retractor **150** according to the invention is employed by inserting the inner O-ring **105** into a wound opening **103** and pulling the sleeve **106** so that the inner O-ring **105** lies flat against the interior anatomical surface. The inner O-ring **105** anchors the retractor **150** in the wound and prevents the elastomeric sleeve **106** from slipping out of the wound opening **103**. The guide means clamp is then released by squeezing handles **160** and the ring parts **110, 151** are slid down the elastomeric sleeve **106** until they come into contact with the exterior anatomical surface. Retraction is achieved by pulling the sleeve **106** to shorten the distance

between the inner O-ring **105** and the ring parts **110, 151** and thereby displace the elastomeric sleeve **106** laterally and with it the margins of the wound opening **103**. The elastomeric sleeve **106** is anchored to maintain retraction of the wound opening **103** by releasing the handles **160** of the outer ring part **151** to clamp the sleeve **106**.

The wound retractors according to the invention also provide a platform on which a wide range of devices may be mounted. In one case the platform is provided by an inner projection part of the inner ring part **110** on which a ring part **171** with a complementary recess **172** may be easily fitted somewhat in the manner of a snap-type engagement. Various devices may be provided with such a ring part **171**. For example, as illustrated in FIGS. **41** and **42** the device may be a hand access device **175** for use in laparoscopic surgery. Alternatively the device may be a drape **180** (FIGS. **43** and **44**) or a form retaining device **185** which is manipulated to the form of, for example, an organ **187** to be held back and from which air is then evacuated along an evacuation line **186** to retain the desired organ holding configuration (FIGS. **45** to **47**).

The platform may alternatively be provided by a clamp **200** as illustrated in FIGS. **48** to **50**. The clamp **200** comprises an upper jaw **201**, a lower jaw **202**, a clip **203** and an arm **204**.

The clamp **200** is assembled by screwing the clip **203** to the base of the lower jaw **202**, sliding the upper jaw **201** over the lower jaw **202** to engage the male projecting parts **208** within the corresponding female recesses **209** and extending the arm **204** through the open mouth **207** between the upper and lower jaws **201, 202**. A plurality of teeth **205** are provided on the arm **204**, the teeth **205** being sized to project upwardly through a recess **206** in the upper jaw **201** when the arm **204** is within the open mouth **207**. The teeth **205**, as shown more clearly in FIG. **49**, are shaped such that the arm **204** may be pulled back through the open mouth **207** in a ratchet-type arrangement but cannot be pushed forward again. A suitable material for the clamp components **201, 202, 203, 204** is spring steel.

Various devices may be attached to the free end of the arm **204**, such as the form retaining device **185**, as illustrated in FIG. **48**. In use, the clip **203** is securely fixed to the wound retractor **101** by a snap-fit arrangement with the form retaining device **185** extending into the wound opening **103**, as illustrated in FIG. **50**. The form retaining device **185** is then ratcheted laterally across the wound opening **103** to retract, for example, an internal organ **220**. The ratchet configuration of the clamp **200** and the rigidity of the form retaining device **185** ensure that the internal organ **220** is securely maintained in a desired position.

It will be appreciated that any of the embodiments of the wound retractor according to the invention and/or the clips for clamping the sleeve may be used as a platform on which to mount other devices for use in various surgical procedures. Such devices may include: a capping device to cover the incision site or orifice; a hand-access device to allow the surgical procedure to be converted from an open procedure into a hand-assisted laparoscopic procedure; an instrument port for the insertion of instruments; a trocar for use in laparoscopic surgery; an internal organ retractor to assist in the displacement of internal structures from the operative field; or an illuminating means to deliver illumination to an area shaded from the theatre lights. It will be clear to those skilled in the art that the enhancements are not limited to the brief list mentioned here.

The wound retractor may be constructed in other annular shapes. For example the distal and proximal rings attached to the elastomeric sleeve may be oval or elliptical instead of circular.

## 11

The retractor may be used to retract and protect the margins of a natural bodily orifice such as the anus or vagina, or can be used to retract and protect the edges of a man-made stoma such as is created for tracheostomy or following gastrointestinal surgery.

The invention is not limited to the embodiments hereinbefore described which may be varied in both construction and detail.

The invention claimed is:

1. A wound retractor device, comprising:
  - a longitudinal axis;
  - a distal ring;
  - a proximal assembly including a first member having a radially inner portion and a radially outer portion, and a second member having a radially inner portion and a radially outer portion, the second member including a plurality of interconnected segments which are independently movable to facilitate localized release of the sleeve; and
  - a wound retracting sleeve extending at least between the distal ring and the proximal assembly and slidably received between the radially outer portion of the first member and the radially inner portion of the second member.
2. A wound retractor as claimed in claim 1, wherein the sleeve is a generally cylindrical sleeve.
3. A wound retractor as claimed in claim 1, further including a securing portion configured to fix the sleeve at a desired axial length between the distal ring and the proximal assembly.
4. A wound retractor as claimed in claim 3, wherein the securing portion includes formations on the second member configured to receive a portion of the sleeve.
5. A wound retractor as claimed in claim 1, wherein at least a portion of the first member is located within a recess of the second member.
6. A wound retractor as claimed in claim 1, wherein the segments are manually manipulable between a clamped rest position and a release position.
7. A wound retractor as claimed in claim 1, wherein the distal ring is of resilient material.
8. A wound retractor as claimed in claim 1, wherein the distal ring is an O-ring.
9. A wound retractor as claimed in claim 1, wherein at least a portion of the proximal assembly includes a material with a low coefficient of friction.
10. A wound retractor as claimed in claim 9, said material with a low coefficient of friction is polytetrafluoroethylene.
11. A wound retractor as claimed in claim 1, further including a sealing device coupled to the proximal assembly so as to allow the wound retractor to be used in laparoscopic surgery.

## 12

12. A wound retractor as claimed in claim 11, wherein the sealing device includes a hand access device that extends across a central opening provided by the retractor.

13. A wound retractor as claimed in claim 1, further including a capping device coupled to the proximal assembly, the capping device extending across a central opening provided by the retractor.

14. A wound retractor as claimed in claim 1, wherein the first member includes a ring having a circular cross-section.

15. A wound retractor as claimed in claim 14, wherein the second member includes a ring shape.

16. A wound retractor as claimed in claim 1, wherein the radially outer portion of the first member is curved.

17. A wound retractor as claimed in claim 1, wherein the sleeve is fixed to the distal ring.

18. A wound retractor as claimed in claim 1, further including a clamp to assist in securing the sleeve to the proximal assembly.

19. A wound retractor device, comprising:

a longitudinal axis;

a distal ring;

a proximal assembly including a first member having a radially outer portion, and a second member having a radially inner portion, the radially outer portion of the first member being located at least partially within a recess in the radially inner portion; and

a generally cylindrical wound retracting sleeve extending at least between the distal ring and the proximal assembly, through the proximal assembly between the radially outer portion of the first member and the radially inner portion of the second member, and proximally beyond the proximal assembly, a portion of the sleeve extending proximally beyond the proximal assembly forming a gripping portion for pulling the sleeve to shorten an axial length of the sleeve located between the distal ring and the proximal assembly.

20. A wound retractor as claimed in claim 19, wherein the distal ring is of resilient material.

21. A wound retractor as claimed in claim 19, wherein at least a portion of the proximal assembly includes polytetrafluoroethylene.

22. A wound retractor as claimed in claim 19, further including a sealing device coupled to the proximal assembly so as to allow the wound retractor to be used in laparoscopic surgery.

23. The wound retractor as claimed in claim 22, wherein the sealing device is coupled to the proximal assembly via a snap-type engagement.

\* \* \* \* \*

专利名称(译)	伤口牵开器		
公开(公告)号	<a href="#">US7540839</a>	公开(公告)日	2009-06-02
申请号	US10/635017	申请日	2003-08-06
[标]申请(专利权)人(译)	约翰·巴特勒 BONADIO FR 马尔霍尔MICHAEL 麦克马纳斯RONAN BERNARD		
申请(专利权)人(译)	约翰·巴特勒 BONADIO FRANK 马尔霍尔MICHAEL 麦克马纳斯RONAN BERNARD		
当前申请(专利权)人(译)	阿特洛波斯有限公司		
[标]发明人	BUTLER JOHN BONADIO FRANK MULHALL MICHAEL MCMANUS RONAN BERNARD		
发明人	BUTLER, JOHN BONADIO, FRANK MULHALL, MICHAEL MCMANUS, RONAN BERNARD		
IPC分类号	A61B1/32 A61B17/00 A61B17/02 A61B17/34		
CPC分类号	A61B17/0293 A61B17/3423 A61B17/3431 A61B2017/00265 A61B2017/00557		
优先权	19990861 1999-10-14 IE 19991053 1999-12-16 IE 2000650010 2000-02-18 EP 60/401023 2002-08-06 US		
其他公开文献	US20040073090A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

#### 摘要(译)

手术伤口牵开器包括用于插入伤口开口的缩回构件和用于位于伤口开口外部的近端构件。夹子用于将缩回构件夹紧到近端构件。

