



US010278688B2

(12) United States Patent
Bonadio et al.(10) Patent No.: US 10,278,688 B2
(45) Date of Patent: May 7, 2019

(54) WOUND RETRCTOR DEVICE

(71) Applicant: Atropos Limited, County Wicklow (IE)

(72) Inventors: Frank Bonadio, County Wicklow (IE); John Butler, County Mayo (IE); Trevor Vaugh, County Offaly (IE); Shane J. MacNally, County Wicklow (IE); Alan Reid, Dublin (IE)

(73) Assignee: Atropos Limited, County Wicklow (IE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: 15/610,012

(22) Filed: May 31, 2017

(65) Prior Publication Data

US 2017/0325801 A1 Nov. 16, 2017

Related U.S. Application Data

(63) Continuation of application No. 14/753,796, filed on Jun. 29, 2015, now Pat. No. 9,700,296, which is a (Continued)

(51) Int. Cl.

A61B 17/02 (2006.01)

A61B 17/34 (2006.01)

(Continued)

(52) U.S. Cl.

CPC A61B 17/0293 (2013.01); A61B 1/32 (2013.01); A61B 17/3423 (2013.01); (Continued)

(58) Field of Classification Search

CPC A61B 17/3423; A61B 17/3431; A61B 17/0218; A61B 17/0469; A61B 17/0293

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

1,157,202 A 10/1915 McLeland

1,598,284 A 8/1926 Kinney

(Continued)

FOREIGN PATENT DOCUMENTS

DE 37 39 532 12/1988

DE 37 37 121 5/1989

(Continued)

OTHER PUBLICATIONS

Kagaya, "Laparoscopic cholecystectomy via two ports, using the "Twin-Port" system", J. Hepatobiliary Pancreat Surg (2001) 8:76-80.


Primary Examiner — Anu Ramana

(74) Attorney, Agent, or Firm — Bookoff McAndrews, PLLC

(57) ABSTRACT

A wound protector and retractor device 1 comprises a sleeve 2, a distal member provided by a distal ring 3 of resilient material and a proximal member provided by a proximal ring 4. The sleeve 2 is led around the ring 3 and is free to move axially relative to the distal ring 3 somewhat in the manner of a pulley. The proximal ring 4 is fixed to the sleeve 2, in this case at the proximal inner end thereof. The sleeve 2 terminates in a handle or gripping portion which is reinforced by a gripping ring 15. The sleeve extends from the proximal ring 4 and the distal ring 3 is contained between inner and outer layers 2a, 2b of the sleeve 2. The resilient distal ring 3 is scrunched up and inserted through the incision 6. The sleeve 2 is then pulled upwardly. On pulling of the sleeve 2 upwardly the outer layer 2b is pulled up while the inner layer 2a is drawn around the proximal ring 3. This results in shortening the axial extent between the proximal ring 4 and the distal ring 3, tensioning the sleeve and applying a retraction force to the margins of the incision 6. As the incision is being retracted the margins are also protected by the sleeve. On retraction, an access port is provided, for example for a surgeon to insert his hand and/or an instrument to perform a procedure. The device may be used as a retractor in open surgery or as a base for a valve/seal to allow it to be used in hand assisted laparoscopic surgery or for instrument access or hand access generally.

20 Claims, 52 Drawing Sheets



Related U.S. Application Data

continuation of application No. 13/655,286, filed on Oct. 12, 2012, now Pat. No. 9,095,300, which is a continuation of application No. 12/426,438, filed on Apr. 20, 2009, now Pat. No. 8,317,691, which is a continuation of application No. 10/678,653, filed on Oct. 6, 2003, now Pat. No. 7,559,893.

- (60) Provisional application No. 60/415,780, filed on Oct. 4, 2002, provisional application No. 60/428,215, filed on Nov. 22, 2002, provisional application No. 60/490,909, filed on Jul. 30, 2003.

(51) Int. Cl.

A61B 1/32 (2006.01)
A61B 17/00 (2006.01)

(52) U.S. Cl.

CPC *A61B 17/3439* (2013.01); *A61B 17/3462* (2013.01); *A61B 17/3498* (2013.01); *A61B 17/3431* (2013.01); *A61B 2017/00557* (2013.01); *A61B 2017/0212* (2013.01); *A61B 2017/0225* (2013.01); *A61B 2017/3443* (2013.01); *A61B 2017/3482* (2013.01); *A61B 2017/3484* (2013.01); *A61B 2017/3492* (2013.01)

(56) References Cited**U.S. PATENT DOCUMENTS**

1,810,466 A	6/1931	Deutsch	4,083,370 A	4/1978	Taylor
2,219,564 A	10/1940	Reyniers	4,096,853 A	6/1978	Weigand
2,305,289 A	12/1942	Coburg	4,112,932 A	9/1978	Chiulli
2,695,608 A	11/1954	Gibbon	4,130,113 A	12/1978	Graham
2,835,253 A	5/1958	Borgeson	4,177,814 A	12/1979	Knepshield
2,853,075 A	10/1958	Hoffman	4,188,945 A	2/1980	Wenander
3,039,468 A	6/1962	Price	4,217,664 A	8/1980	Faso
3,111,943 A	11/1963	Orndorff	4,228,792 A	10/1980	Rhys-Davies
3,244,169 A	4/1966	Baxter	4,239,036 A	12/1980	Krieger
3,253,594 A	5/1966	Matthews et al.	4,240,411 A	12/1980	Hosono
3,313,299 A	4/1967	Spademan	4,253,201 A	3/1981	Ross et al.
3,329,390 A	7/1967	Hulsey	4,306,562 A	12/1981	Osborne
3,332,417 A	7/1967	Blanford et al.	4,321,915 A	3/1982	Leighton
3,347,226 A	10/1967	Harrower	4,331,138 A	5/1982	Jessen
3,347,227 A	10/1967	Harrower	4,338,934 A	7/1982	Spademan
3,397,692 A	8/1968	Creager, Jr. et al.	4,338,937 A	7/1982	Lehrman
3,402,710 A	9/1968	Paleschuck	4,367,728 A	1/1983	Mutke
3,447,533 A	6/1969	Spicer	4,399,816 A	8/1983	Spangler
3,522,800 A	8/1970	Lesser	4,411,659 A	10/1983	Jensen et al.
3,523,534 A	8/1970	Nolan	4,421,296 A	12/1983	Stephens
3,570,475 A	3/1971	Weinstein	4,424,833 A	1/1984	Spector
3,592,198 A	7/1971	Evans	4,428,364 A	1/1984	Bartolo
3,656,485 A	4/1972	Robertson	4,430,081 A	2/1984	Timmermans
3,685,786 A	8/1972	Woodson	4,434,791 A	3/1984	Darnell
3,717,151 A	2/1973	Collett	4,436,519 A	3/1984	O'Neill
3,729,006 A	4/1973	Wilder et al.	4,485,490 A	12/1984	Akers et al.
3,782,370 A	1/1974	McDonald	4,488,877 A	12/1984	Klein
3,797,478 A	3/1974	Walsh et al.	4,543,088 A	9/1985	Bootman
3,807,393 A	4/1974	McDonald	4,550,713 A	11/1985	Hyman
3,828,764 A	8/1974	Jones	4,553,537 A	11/1985	Rosenberg
3,841,332 A	10/1974	Treacle	4,601,710 A	7/1986	Moll
3,853,126 A	12/1974	Schulte	4,610,665 A	9/1986	Matsumoto
3,853,127 A	12/1974	Spademan	4,626,245 A	12/1986	Weinstein
3,856,021 A	12/1974	Macintosh	4,634,424 A	1/1987	O'Boyle
3,907,389 A	9/1975	Cox et al.	4,649,904 A	3/1987	Krauter
3,915,171 A	10/1975	Shermeta	4,654,030 A	3/1987	Moll et al.
3,965,890 A	6/1976	Gauthier	4,673,393 A	6/1987	Suzuki et al.
3,996,623 A	12/1976	Kaster	4,673,394 A	6/1987	Fenton
3,998,217 A	12/1976	Trumbull et al.	4,755,170 A	7/1988	Golden
4,000,739 A	1/1977	Stevens	4,776,843 A	10/1988	Martinez et al.
4,016,884 A	4/1977	Kwan-Gett	4,777,943 A	10/1988	Chvapil
4,024,872 A	5/1977	Muldoon	4,784,646 A	11/1988	Feingold
4,030,500 A	6/1977	Ronnquist	4,798,594 A	1/1989	Hillstead
			4,809,679 A	3/1989	Shimonaka
			4,863,438 A	9/1989	Gauderer
			4,889,107 A	12/1989	Kaufman
			4,895,565 A	1/1990	Hillstead
			4,897,081 A	1/1990	Poirier
			4,903,710 A	2/1990	Jessamine et al.
			4,950,222 A	8/1990	Scott et al.
			4,950,223 A	8/1990	Silvanov
			4,984,564 A	1/1991	Yuen
			4,991,593 A	2/1991	LeVahn
			4,998,538 A	3/1991	Charowsky et al.
			5,002,557 A	3/1991	Hasson
			5,015,228 A	5/1991	Columbus et al.
			5,019,101 A	5/1991	Purkait
			5,026,366 A	6/1991	Leckrone
			5,041,095 A	8/1991	Littrell
			5,045,070 A	9/1991	Grodecki et al.
			D320,658 S	10/1991	Quigley et al.
			5,071,411 A	12/1991	Hillstead
			5,074,878 A	12/1991	Bark et al.
			5,082,005 A	1/1992	Kaldany
			5,086,763 A	2/1992	Hathman
			5,092,846 A	3/1992	Nishijima
			5,125,897 A	6/1992	Quinn et al.
			5,129,885 A	7/1992	Green et al.
			5,141,498 A	8/1992	Christian
			5,149,327 A	9/1992	Oshiyama
			5,156,617 A	10/1992	Reid
			5,158,553 A	10/1992	Berry et al.
			5,159,921 A	11/1992	Hoover
			5,161,773 A	11/1992	Tower
			5,167,636 A	12/1992	Clement
			5,178,162 A	1/1993	Bose
			5,188,595 A	2/1993	Jacobi
			5,192,301 A	3/1993	Kamiya et al.
			5,197,955 A	3/1993	Stephens et al.

US 10,278,688 B2

Page 3

(56)	References Cited					
U.S. PATENT DOCUMENTS						
5,207,656 A	5/1993	Kranys	5,707,703 A	1/1998	Rothrum et al.	
5,209,737 A	5/1993	Richartt	5,709,664 A	1/1998	Vandenbroeck	
5,211,370 A	5/1993	Powers	5,720,730 A	2/1998	Blake, III	
5,211,633 A	5/1993	Strouder	5,738,628 A	4/1998	Sierocuk et al.	
5,213,114 A	5/1993	Bailey, Jr.	5,741,234 A	4/1998	Aboul-Hosn	
5,234,455 A	8/1993	Mulholland	5,741,298 A	4/1998	MacLeod	
5,242,409 A	9/1993	Buelna	5,743,884 A	4/1998	Hasson et al.	
5,248,304 A	9/1993	Vigdorchik et al.	5,749,882 A	5/1998	Hart et al.	
5,261,883 A	11/1993	Hood et al.	5,755,660 A	5/1998	Tyagi	
5,263,922 A	11/1993	Sova et al.	5,769,783 A	6/1998	Fowler	
5,269,763 A	12/1993	Boehmer	5,769,794 A	6/1998	Conlan et al.	
5,269,772 A	12/1993	Wilk	5,782,812 A	7/1998	Hart et al.	
D343,236 S	1/1994	Quigley et al.	5,795,290 A	8/1998	Bridges	
5,279,575 A	1/1994	Sugarbaker	5,803,919 A	9/1998	Hart et al.	
D346,022 S	4/1994	Quigley et al.	5,803,921 A	9/1998	Bonadio	
5,299,582 A	4/1994	Potts	5,807,350 A	9/1998	Diaz	
5,300,036 A	4/1994	Mueller	5,810,721 A	9/1998	Mueller et al.	
5,308,336 A	5/1994	Hart et al.	5,813,409 A	9/1998	Leahy et al.	
5,309,896 A	5/1994	Moll et al.	5,814,026 A	9/1998	Yoon	
5,316,541 A	5/1994	Fischer	5,817,062 A	10/1998	Flom	
5,320,611 A	6/1994	Bonutti	5,820,555 A	10/1998	Mueller	
5,330,437 A	7/1994	Durman	5,832,925 A	11/1998	Rothrum	
5,330,497 A	7/1994	Freitas	5,848,992 A	12/1998	Hart et al.	
5,334,143 A	8/1994	Carroll	5,853,395 A	12/1998	Crook et al.	
5,336,192 A	8/1994	Palestrant	5,865,728 A	2/1999	Moll et al.	
5,342,315 A	8/1994	Rowe et al.	5,871,474 A	2/1999	Hermann et al.	
5,342,385 A	8/1994	Norelli et al.	5,882,344 A	3/1999	Strouder	
5,350,364 A	9/1994	Stephens et al.	5,899,208 A	5/1999	Bonadio	
5,364,345 A	11/1994	Lowery et al.	5,904,703 A	5/1999	Gilson	
5,366,478 A	11/1994	Brinkerhoff et al.	5,906,577 A	5/1999	Beane et al.	
5,368,545 A	11/1994	Schaller et al.	5,916,232 A	6/1999	Hart	
5,383,861 A	1/1995	Hempel	5,947,922 A	9/1999	MacLeod	
5,385,553 A	1/1995	Hart et al.	5,951,467 A	9/1999	Picha et al.	
5,391,153 A	2/1995	Haber et al.	5,957,913 A	9/1999	de la Torre et al.	
5,391,156 A	2/1995	Hildwein et al.	5,964,781 A	10/1999	Mollenauer et al.	
5,395,367 A	3/1995	Wilk	5,993,485 A	11/1999	Beckers	
5,403,264 A	4/1995	Wohlers	5,994,450 A	11/1999	Pearce	
5,407,433 A	4/1995	Loomas	5,997,515 A	12/1999	de la Torre et al.	
5,423,848 A	6/1995	Washizuka et al.	6,024,736 A	2/2000	de la Torre et al.	
5,429,609 A	7/1995	Yoon	6,025,067 A	2/2000	Fay	
5,431,676 A	7/1995	Durbal	6,033,426 A	3/2000	Kaji	
5,443,452 A	8/1995	Hart et al.	6,033,428 A	3/2000	Sardella	
5,456,284 A	10/1995	Ryan	6,036,685 A	3/2000	Mueller	
5,476,475 A	12/1995	Gadberry	6,042,573 A	3/2000	Lucey	
5,480,410 A	1/1996	Cuschieri et al.	6,048,309 A	4/2000	Flom et al.	
5,496,280 A	3/1996	Vandenbroeck	6,059,816 A	5/2000	Moenning	
5,503,112 A	4/1996	Luhman	6,077,288 A	6/2000	Shimomura et al.	
5,514,109 A	5/1996	Mollenauer et al.	6,099,506 A	8/2000	Macoviak et al.	
5,514,133 A	5/1996	Golub et al.	6,110,154 A	8/2000	Shimomura et al.	
5,520,632 A	5/1996	Leveen	6,123,689 A	9/2000	To	
5,522,791 A	6/1996	Leyva	6,142,935 A	11/2000	Flom et al.	
5,522,824 A	6/1996	Ashby	6,142,936 A	11/2000	Beane et al.	
5,524,644 A	6/1996	Crook	6,149,642 A	11/2000	Gerhart et al.	
5,526,536 A	6/1996	Cartmill	6,150,608 A	11/2000	Wambeke	
5,545,179 A	8/1996	Williamson, IV	6,159,182 A	12/2000	Davis	
5,562,632 A	10/1996	Davila	6,162,172 A	12/2000	Cosgrove et al.	
5,562,688 A	10/1996	Riza	6,162,196 A	12/2000	Hart et al.	
5,577,993 A	11/1996	Zhu et al.	6,162,206 A	12/2000	Bindokas	
5,582,577 A	12/1996	Lund et al.	6,163,949 A	12/2000	Neuenschwander	
5,584,850 A	12/1996	Hart et al.	6,164,279 A	12/2000	Tweedle	
5,601,579 A	2/1997	Semertzides	6,171,282 B1	1/2001	Ragsdale	
5,620,415 A	4/1997	Lucey	6,183,486 B1	2/2001	Snow et al.	
5,632,979 A	5/1997	Goldberg	6,238,373 B1	5/2001	de la Torre et al.	
5,634,911 A	6/1997	Hermann et al.	6,254,533 B1	7/2001	Fadem et al.	
5,634,936 A	6/1997	Linden	6,254,534 B1	7/2001	Butler et al.	
5,634,937 A	6/1997	Mollenauer et al.	6,258,065 B1	7/2001	Dennis	
5,636,645 A	6/1997	Ou	6,315,770 B1	11/2001	de la Torre et al.	
5,640,977 A	6/1997	Leahy et al.	6,319,246 B1	11/2001	de la Torre et al.	
5,649,550 A	7/1997	Crook	6,322,541 B2	11/2001	West	
5,653,705 A	8/1997	de la Torre et al.	6,328,730 B1	12/2001	Harkrider, Jr.	
5,657,963 A	8/1997	Hinchliffe	6,346,074 B1	2/2002	Roth	
5,658,272 A	8/1997	Hasson	6,382,211 B1	5/2002	Crook	
5,658,306 A	8/1997	Kieturakis	6,420,475 B1	7/2002	Chen	
5,672,168 A	9/1997	de la Torre et al.	6,440,063 B1	8/2002	Beane	
5,685,854 A	11/1997	Green	6,450,983 B1	9/2002	Rambo	
			6,454,783 B1	9/2002	Piskun	
			6,458,077 B1	10/2002	Boebel et al.	
			6,464,686 B1	10/2002	O'Hara et al.	
			6,485,435 B1	11/2002	Bakal	

(56)	References Cited					
U.S. PATENT DOCUMENTS						
6,485,467 B1	11/2002	Crook et al.	9,078,695 B2	7/2015	Hess et al.	
6,488,620 B1	12/2002	Segermark et al.	9,095,300 B2	8/2015	Bonadio et al.	
6,533,734 B1	3/2003	Corley, III et al.	9,131,835 B2	9/2015	Widenhouse et al.	
6,551,270 B1	4/2003	Bimbo et al.	9,271,753 B2	3/2016	Butler et al.	
6,554,793 B1	4/2003	Pauker	9,277,908 B2	3/2016	Butler et al.	
6,569,119 B1	5/2003	Haberland et al.	2001/0037053 A1	11/2001	Bonadio et al.	
6,578,577 B2	6/2003	Bonadio et al.	2001/0039430 A1	11/2001	Dubrul et al.	
6,582,364 B2	6/2003	Butler et al.	2001/0047188 A1	11/2001	Bonadio et al.	
6,589,167 B1	7/2003	Shimonmura	2002/0002324 A1	1/2002	McManus	
6,589,211 B1	7/2003	MacLeod	2002/0010389 A1	1/2002	Butler et al.	
6,607,504 B2	8/2003	Haarala	2002/0038077 A1	3/2002	de la Torre et al.	
6,613,952 B2	9/2003	Rambo	2002/0072762 A1	6/2002	Bonadio et al.	
6,623,426 B2	9/2003	Bonadio et al.	2002/0111536 A1	8/2002	Cuschieri et al.	
6,702,787 B2	3/2004	Racenet et al.	2003/0028179 A1	2/2003	Piskun	
6,706,050 B1	3/2004	Giannadakis	2003/0078478 A1	4/2003	Bonadio et al.	
6,714,298 B2	3/2004	Ryer	2003/0236549 A1	12/2003	Bonadio et al.	
6,723,044 B2	4/2004	Pulford	2004/0015185 A1	1/2004	Ewers et al.	
6,793,621 B2	9/2004	Butler et al.	2004/0024363 A1	2/2004	Goldberg	
6,796,940 B2	9/2004	Bonadio et al.	2004/0049099 A1	3/2004	Ewers et al.	
6,797,765 B2	9/2004	Pearce	2004/0049100 A1	3/2004	Butler	
6,814,078 B2	11/2004	Crook	2004/0068232 A1	4/2004	Hart et al.	
6,814,700 B1	11/2004	Mueller et al.	2004/0073090 A1	4/2004	Butler	
6,840,951 B2	1/2005	de la Torre et al.	2004/0092795 A1	5/2004	Bonadio et al.	
6,846,287 B2	1/2005	Bonadio et al.	2004/0092796 A1	5/2004	Butler et al.	
6,860,463 B2	3/2005	Hartley	2004/0093018 A1	5/2004	Johnson	
6,866,861 B1	3/2005	Luhman	2004/0097793 A1	5/2004	Butler et al.	
6,884,253 B1	4/2005	McFarlane	2004/0106942 A1	6/2004	Taylor	
6,902,541 B2	6/2005	McNally et al.	2004/0143158 A1	7/2004	Hart et al.	
6,908,430 B2	6/2005	Caldwell	2004/0154624 A1	8/2004	Bonadio et al.	
6,916,331 B2	7/2005	Mollenauer et al.	2004/0215063 A1	10/2004	Bonadio et al.	
6,936,037 B2	8/2005	Bubb	2004/0230161 A1	11/2004	Zeiner	
6,939,296 B2	9/2005	Ewers	2004/0249248 A1	12/2004	Bonadio et al.	
6,945,932 B1	9/2005	Caldwell et al.	2004/0260244 A1	12/2004	Piechowicz et al.	
6,958,037 B2	10/2005	Ewers	2005/0020884 A1	1/2005	Heart et al.	
6,979,324 B2	12/2005	Bybordi	2005/0033246 A1	2/2005	Ahlberg	
7,008,377 B2	3/2006	Beane	2005/0059865 A1	3/2005	Kahle	
7,052,454 B2	5/2006	Taylor	2005/0065475 A1	3/2005	Hart et al.	
7,081,089 B2	7/2006	Bonadio et al.	2005/0065543 A1	3/2005	Kahle	
7,083,626 B2	8/2006	Hart et al.	2005/0090713 A1	4/2005	Gozales	
7,112,185 B2	9/2006	Hart et al.	2005/0090716 A1	4/2005	Bonadio et al.	
7,118,528 B1	10/2006	Piskun	2005/0090717 A1	4/2005	Bonadio et al.	
7,153,319 B1	12/2006	Haberland et al.	2005/0131349 A1	6/2005	Albrecht	
7,195,590 B2	3/2007	Butler et al.	2005/0137609 A1	6/2005	Guiraudon	
7,297,106 B2	11/2007	Yamada et al.	2005/0148823 A1	7/2005	Vaugh et al.	
7,300,399 B2	11/2007	Bonadio et al.	2005/0155611 A1	7/2005	Vaugh et al.	
7,344,547 B2	3/2008	Piskun	2005/0159647 A1	7/2005	Hart et al.	
7,445,597 B2	11/2008	Butler et al.	2005/0192483 A1	9/2005	Bonadio et al.	
7,537,564 B2	5/2009	Bonadio et al.	2005/0192598 A1	9/2005	Johnson	
7,540,839 B2	6/2009	Butler et al.	2005/0197537 A1	9/2005	Bonadio et al.	
7,559,893 B2	7/2009	Bonadio et al.	2005/0203346 A1	9/2005	Bonadio et al.	
7,749,415 B2	7/2010	Brustad et al.	2005/0209510 A1	9/2005	Bonadio et al.	
7,753,901 B2	7/2010	Piskun et al.	2005/0222582 A1	10/2005	Wenchell	
7,837,612 B2	11/2010	Gill et al.	2005/0240082 A1	10/2005	Bonadio et al.	
7,867,164 B2	1/2011	Butler et al.	2005/0241647 A1	11/2005	Nguyen	
7,909,760 B2	3/2011	Albrecht et al.	2005/0267419 A1	12/2005	Smith	
7,998,068 B2	8/2011	Bonadio et al.	2005/0277946 A1	12/2005	Greenhalgh	
8,012,088 B2	9/2011	Butler et al.	2005/0288558 A1	12/2005	Ewers	
8,021,296 B2	9/2011	Bonadio et al.	2005/0288634 A1	12/2005	O'Herron	
8,157,817 B2	4/2012	Bonadio et al.	2006/0020164 A1	1/2006	Butler et al.	
8,187,178 B2	5/2012	Bonadio et al.	2006/0020241 A1	1/2006	Piskun et al.	
8,317,691 B2	11/2012	Bonadio et al.	2006/0030755 A1	2/2006	Ewers et al.	
8,343,047 B2	1/2013	Albrecht et al.	2006/0041270 A1	2/2006	Lenker	
8,375,955 B2	2/2013	Desai et al.	2006/0047284 A1	3/2006	Gresham	
8,475,490 B2	7/2013	Hess et al.	2006/0047293 A1	3/2006	Haberland et al.	
8,485,970 B2	7/2013	Widenhouse et al.	2006/0106402 A1	5/2006	McLucas	
8,518,024 B2	8/2013	Williams et al.	2006/0149137 A1	7/2006	Pingleton et al.	
8,657,740 B2	2/2014	Bonadio et al.	2006/0149306 A1	7/2006	Hart et al.	
8,734,336 B2	5/2014	Bonadio et al.	2006/0161050 A1	7/2006	Butler et al.	
8,740,785 B2	6/2014	Butler et al.	2006/0241651 A1	10/2006	Wilk	
8,752,553 B2	6/2014	Bonadio et al.	2006/0247498 A1	11/2006	Bonadio et al.	
8,876,708 B1	11/2014	Piskun et al.	2006/0247499 A1	11/2006	Butler et al.	
8,888,693 B2	11/2014	Bonadio et al.	2006/0247500 A1	11/2006	Voegele et al.	
8,961,406 B2	2/2015	Ortiz et al.	2006/0247516 A1	11/2006	Hess et al.	
8,961,407 B2	2/2015	Widenhouse et al.	2006/0258899 A1	11/2006	Gill et al.	
8,986,202 B2	3/2015	Butler et al.	2006/0264706 A1	11/2006	Piskun	

(56)	References Cited					
U.S. PATENT DOCUMENTS						
2007/0004968 A1	1/2007	Bonadio et al.	EP	1118657	7/2001	
2007/0049966 A1	3/2007	Bonadio et al.	EP	1312318	5/2003	
2007/0093695 A1	4/2007	Bonadio et al.	EP	1593348	11/2005	
2007/0118175 A1	5/2007	Butler et al.	EP	2168511	3/2010	
2007/0185387 A1	8/2007	Albrecht et al.	EP	2238932	10/2010	
2007/0203398 A1	8/2007	Bonadio et al.	FR	1456623	9/1966	
2007/0255219 A1	11/2007	Vaugh et al.	GB	1151993	5/1969	
2007/0287889 A1	12/2007	Mohr	GB	1355611	6/1974	
2007/0299387 A1	12/2007	Williams et al.	GB	1372491	10/1974	
2008/0027476 A1	1/2008	Piskun	GB	1379772	1/1975	
2008/0097162 A1	4/2008	Bonadio et al.	GB	1400808	7/1975	
2008/0097163 A1	4/2008	Butler et al.	GB	1407023	9/1975	
2008/0255519 A1	10/2008	Piskun et al.	JP	1496696	12/1977	
2008/0281161 A1	11/2008	Albrecht et al.	JP	2071502	9/1981	
2008/0281162 A1	11/2008	Albrecht et al.	JP	2255019	10/1992	
2009/0012477 A1	1/2009	Norton et al.	JP	2275420	8/1994	
2009/0036745 A1	2/2009	Bonadio et al.	JP	10-108868	4/1998	
2009/0069837 A1	3/2009	Bonadio et al.	JP	11-290327	10/1999	
2009/0093683 A1	4/2009	Richard et al.	JP	2001-61850	3/2001	
2009/0149714 A1	6/2009	Bonadio	JP	2002-28163	1/2002	
2009/0187079 A1	7/2009	Albrecht et al.	JP	2004-509659	4/2004	
2009/0221966 A1	9/2009	Richard	JP	2004-195037	7/2004	
2009/0292176 A1	11/2009	Bonadio et al.	JP	2011-98138	5/2011	
2009/0326330 A1	12/2009	Bonadio et al.	RU	1342485	1/1997	
2010/0057121 A1	3/2010	Piskun et al.	WO	WO 86/06272	11/1986	
2010/0063362 A1	3/2010	Bonadio et al.	WO	WO 92/11880	7/1992	
2010/0063364 A1	3/2010	Bonadio et al.	WO	WO 92/21292	12/1992	
2010/0081880 A1	4/2010	Widenhouse et al.	WO	WO 93/05740	4/1993	
2010/0081881 A1	4/2010	Murray et al.	WO	WO 95/05207	2/1995	
2010/0113886 A1	5/2010	Piskun et al.	WO	WO 95/07056	3/1995	
2010/0204548 A1	8/2010	Bonadio et al.	WO	WO 95/22289	8/1995	
2010/0217087 A1	8/2010	Bonadio et al.	WO	WO 95/24864	9/1995	
2010/0222643 A1	9/2010	Piskun et al.	WO	WO 95/27445	10/1995	
2010/0261972 A1	10/2010	Widenhouse et al.	WO	WO 95/27468	10/1995	
2010/0262080 A1	10/2010	Widenhouse et al.	WO	WO 96/36283	11/1996	
2010/0274091 A1	10/2010	Rothstein et al.	WO	WO 97/32514	9/1997	
2010/0274093 A1	10/2010	Shelton, IV	WO	WO 97/32515	9/1997	
2010/0280326 A1	11/2010	Hess et al.	WO	WO 98/35614	8/1998	
2011/0011410 A1	1/2011	Desai et al.	WO	WO 98/48724	11/1998	
2011/0071359 A1	3/2011	Bonadio et al.	WO	WO 99/03416	1/1999	
2011/0092778 A1	4/2011	Butler et al.	WO	WO 99/25268	5/1999	
2011/0270195 A1	11/2011	Piskun	WO	WO 99/29250	6/1999	
2012/0016394 A1	1/2012	Bonadio et al.	WO	WO 00/32116	6/2000	
2012/0022333 A1	1/2012	Main et al.	WO	WO 00/32117	6/2000	
2012/0029297 A1	2/2012	Bonadio et al.	WO	WO 00/32119	6/2000	
2012/0095297 A1	4/2012	Dang et al.	WO	WO 00/32120	6/2000	
2012/0116172 A1	5/2012	Butler et al.	WO	WO 00/35356	6/2000	
2012/0123214 A1	5/2012	Bonadio et al.	WO	WO 00/54675	9/2000	
2013/0041231 A1	2/2013	Bonadio et al.	WO	WO 00/54676	9/2000	
2013/0060093 A1	3/2013	Bonadio et al.	WO	WO 00/54677	9/2000	
2013/0116509 A1	5/2013	Bonadio et al.	WO	WO 01/08563	2/2001	
2013/0245373 A1	9/2013	Okoniewski	WO	WO 01/08581	2/2001	
2014/0107425 A1	4/2014	Bonadio et al.	WO	WO 01/26558	4/2001	
2014/0303443 A1	10/2014	Bonadio et al.	WO	WO 01/91652	12/2001	
2014/0323809 A1	10/2014	Bonadio et al.	WO	WO 01/91653	12/2001	
2015/0148611 A1	5/2015	Bonadio et al.	WO	WO 02/17800 A2	3/2002	
2015/0272563 A1	10/2015	Butler et al.	WO	WO 02/34108 A2	5/2002	
2015/0335353 A1	11/2015	Windenhouse et al.	WO	WO 03/026512 A1	4/2003	
2016/0022257 A1	1/2016	Bonadio et al.	WO	WO 03/034908 A3	5/2003	
2017/0325798 A1	11/2017	Prior	WO	WO 03/061480 A1	7/2003	
FOREIGN PATENT DOCUMENTS						
DE	296 00 939	6/1998	WO	WO 03/103548 A1	12/2003	
EP	0113520	7/1984	WO	WO 04/026153 A1	4/2004	
EP	0142262	5/1985	WO	WO 04/030547 A1	4/2004	
EP	0537768	4/1993	WO	WO 05/009257 A2	2/2005	
EP	0950376	10/1999	WO	WO 05/034766 A2	4/2005	
			WO	WO 05/089661	9/2005	
			WO	WO 06/040748 A1	4/2006	
			WO	WO 06/059318	8/2006	
			WO	WO 08/121294 A1	10/2008	
			WO	WO 09/035663 A2	3/2009	
			WO	WO 14/4233 A1	9/2014	
			WO	WO 2017/048512 A1	3/2017	




FIG. 4




FIG. 3




FIG. 1




FIG. 6




FIG. 5




FIG. 2




FIG. 8




FIG. 7




FIG. 10





FIG. 9

**FIG. 11**




FIG. 12




FIG. 13





FIG. 14

**FIG. 15**




FIG. 16




FIG. 17




FIG. 18




FIG. 19





FIG. 20

**FIG. 21**




FIG. 22




FIG. 25






FIG. 23






FIG. 27







FIG. 28

**FIG. 29**

**FIG. 30**

**FIG. 31**




FIG. 32




FIG. 33




FIG. 34






FIG. 35

**FIG. 36**

**FIG. 37**





FIG. 38

**FIG. 39**




FIG. 40




FIG. 41B




FIG. 41A




FIG. 41D




FIG. 41C




FIG. 43




FIG. 42




FIG. 45




FIG. 44




FIG. 47




FIG. 46




FIG. 49




FIG. 48







FIG. 50

**FIG. 51**






FIG. 55




FIG. 54




FIG. 57




FIG. 56




FIG. 59






FIG. 58









FIG. 62



**FIG. 65**




FIG. 66




FIG. 68






FIG. 67






FIG. 72




FIG. 71

WOUND RETRCTOR DEVICE

This application is a Continuation of U.S. application Ser. No. 14/753,796, file Jun. 29, 2015, which is a Continuation of U.S. application Ser. No. 13/655,286, filed Oct. 18, 2012, now U.S. Pat. No. 9,095,300, which is a Continuation of U.S. application Ser. No. 12/426,438, file Apr. 20, 2009, now U.S. Pat. No. 8,317,691, which is a Continuation of U.S. application Ser. No. 10/678,653, filed Oct. 6, 2003, now U.S. Pat. No. 7,559,893, which claims benefits of priority of U.S. Provisional Application Nos. 60/415,780, filed Oct. 4, 2002, 60/428,215, filed Nov. 22, 2002, and 60/490,909, filed Jul. 30, 2003. All of the above-listed applications are incorporated herein by reference in their entireties.

INTRODUCTION

The invention relates to a retractor. In particular the invention relates to a retractor for retracting the margins of an incision or a natural bodily orifice to provide maximum exposure of an organ or body structures for examination and/or access for surgical procedures, while also providing protection for the exposed sides of the incised tissue.

Various retractors are known. Some known retractors are difficult and cumbersome to use, and/or are relatively expensive. In addition, some known retractors are limited to use with a particular size of incision and a particular patient anatomy.

This invention is directed towards providing an improved wound retractor which will overcome at least some of these problems, and in addition provide a means of wound protection during a surgical procedure.

STATEMENTS OF INVENTION

According to the invention there is provided a wound protector and retractor device comprising:

- a longitudinal axis;
- a distal member;
- a proximal member; and
- a sleeve extending at least between the distal member and the proximal member,

the sleeve having a proximal gripping portion for pulling the sleeve upwardly to shorten an axial extent located

between the distal member and the proximal member.

In the device, on release of the gripping portion the shortened axial extent between the distal member and the proximal member is substantially maintained without a requirement for an additional locking device.

In one embodiment the proximal gripping portion is provided at a proximal end portion of the sleeve. The gripping portion may be reinforced by a reinforcing arrangement such as a gripping ring. The gripping ring may be mounted to the sleeve.

In one embodiment the sleeve is fixed to the proximal member at a first end portion and is movable over the proximal member at a second end portion. The sleeve may be axially slidable over the proximal member at the second end portion.

In another embodiment the second end portion of the sleeve is slidably received over a portion of the proximal member to allow relative movement between the sleeve and the proximal member to shorten the axial extent of the sleeve located between the distal member and the proximal member. The portion of the proximal member that slidably receives the sleeve may include an outer portion of the

proximal member. The second end portion of the sleeve may be biased against the proximal member.

In one embodiment the proximal member is located within the sleeve.

The proximal member may form a part of a securing arrangement configured to substantially fix the axial extent of the sleeve located between the distal member and the proximal member at a desired length.

The sleeve may extend from the proximal member, around the distal member, and has a return section outside of the proximal member, the return section providing the proximal gripping portion.

In one embodiment the distal member comprises a distal ring which may be an O-ring.

The distal ring may be formed of an elastomeric material.

In one embodiment the proximal member comprises a proximal ring which may be an O-ring.

The proximal ring may be relatively rigid with respect to the distal ring.

In one embodiment the sleeve is of a pliable material.

The wound protector and retractor device may comprise a guide member for a proximal portion of the sleeve.

The sleeve may extend between the guide member and the proximal member.

The guide member may comprise a receiver for the proximal member. For example, the guide member may have an inwardly facing recess defining a receiver for the proximal member. In one case the proximal member comprises a proximal ring and the recess has a shape which is complementary to that of the proximal ring, for example the recess may be substantially C-shaped in transverse cross section.

In another embodiment a lock may be provided for locking the guide member to the proximal member. The guide member may be engagable with the proximal member to provide the lock.

In some cases the guide member may be an interference fit with the proximal member.

In one embodiment, on retraction of an incision the sleeve defines an excess sleeve portion extending between the proximal member and the gripping portion.

The excess sleeve portion may be removed. Alternatively the excess sleeve portion is inserted through the retractor and in this case may define an organ retainer.

Alternatively the excess sleeve portion is configured to form a seal such as a forearm seal or an instrument seal.

The seal may comprise an iris valve.

In one embodiment the device comprises a guide member for a proximal portion of the sleeve and the excess sleeve material is mounted to the guide member. The excess sleeve material together with the guide member may define a chamber. The chamber may have an inflation port. In one case, on inflation, the chamber defines a seal for an object such as a surgeon's forearm or an instrument shaft.

In one embodiment the device comprises a first proximal mounting member and a second proximal mounting member between which at least portion of a sleeve extends. The first and second mounting members may be movable relative to one another.

The mounting members may be movable axially relative to one another and/or the mounting members are rotationally movable relative to one another.

In one arrangement the mounting members are movable relative to one another to configure at least portion of the proximal portion of the sleeve to form a seal. The mounting members may be movable to twist the sleeve to form an iris.

In one embodiment the device comprises a biassing member for biassing the seal into a desired configuration such as a closed configuration.

The biassing member may be a spring such as a coil spring.

In one embodiment the device further comprises a lock for locking the first and second mounting members together.

The second mounting member may be engagable with the first mounting member to provide the lock. The lock may be provided by snap fitting engagement between the mounting members. Alternatively one mounting member is an interference fit with the other mounting member to provide the lock.

In one case the sleeve which extends between the mounting members is a proximal portion of the retracting sleeve.

In another case the sleeve which extends between the mounting members is a connecting sleeve which is separate from the retracting sleeve.

The first mounting member may comprise a ring member.

The second mounting member may comprise a ring member.

In one embodiment the wound protector and retractor device further includes a valve. The valve may be attached to the retractor device.

In one case the valve is attached to the proximal portion of the sleeve.

In another case a connector is provided between the device and the valve. The connector may comprise a connector sleeve. The connector sleeve may be of substantially fixed length.

In one embodiment a flexible joint is provided between the valve and the device.

In another embodiment a malleable joint is provided between the valve and the device. In this case the valve may be offset with respect to the longitudinal axis of the wound retractor.

In one embodiment the malleable joint is provided by a malleable connecting sleeve section. The malleable connecting sleeve section may be of corrugated configuration.

In one embodiment the valve is a lip seal.

Alternatively the valve is an iris seal.

The valve may be a forearm seal or an instrument seal.

In one embodiment the device comprises a release arrangement for releasing the device from a retracting configuration. The release arrangement may comprise a pulling device. The pulling device may be coupled to the distal member. The pulling device may comprise a pull cord or a ribbon.

In another aspect the invention provides a wound protector and retractor device comprising:

a longitudinal axis;

a distal member;

a proximal member; and

a sleeve extending at least between the distal member and the proximal member,

the sleeve, on retraction of an incision, defining an excess sleeve portion extending proximally from the proximal member.

In one embodiment the excess sleeve portion is configured to form a seal such as a forearm seal or an instrument seal. The seal may comprise an iris valve.

In a further aspect the invention provides a wound protector and retractor device comprising:

a longitudinal axis;

a distal member;

a proximal member; and

a sleeve extending at least between the distal member and the proximal member,

the device further comprising a first proximal mounting member and a second proximal mounting member between which at least portion of a sleeve extends.

The first and second mounting members may be movable relative to one another. The mounting members may be movable axially relative to one another and/or the mounting members are rotationally movable relative to one another. In one case the mounting members are movable relative to one another to configure at least portion of the proximal portion of the sleeve to form a seal. The mounting members may be movable to twist the sleeve to form an iris. The device may comprise a biassing member for biassing the seal into a desired configuration such as a closed configuration.

In another aspect the invention provides a surgical device comprising a wound retractor, a valve and a connector between the wound protector and the valve, the wound retractor comprising:

a longitudinal axis;

a distal member;

a proximal member; and

a sleeve extending at least between the distal member and the proximal member.

The connector may comprise a connector sleeve which may be of substantially fixed length. The connector may comprise a flexible joint between the valve and the retractor. Alternatively the connector comprises a malleable joint between the valve and the retractor. The valve may be offset with respect to the longitudinal axis of the wound retractor. The malleable joint is provided by a malleable connecting sleeve section. The malleable connecting sleeve sections may be of corrugated configuration.

In another aspect the invention provides a method for retracting an incision comprising the steps of:

making an incision in a patient;

providing a wound retractor comprising a longitudinal axis, a distal member, a proximal member, and a sleeve extending at least between the distal member and the proximal member, the sleeve having a proximal gripping portion;

inserting the distal member through the incision such that the sleeve extends through the incision and the proximal member is located outside of the incision; gripping the gripping portion of the sleeve and pulling the sleeve upwardly to shorten an axial extent of the sleeve located between the distal member and the proximal member.

In one embodiment, on release of the gripping portion the shortened axial extent of the sleeve between the distal member and the proximal member is substantially maintained.

The sleeve may be fixed to the proximal member at a first end portion and extending over the proximal member at a second end portion, and the method comprises moving the sleeve over the proximal member as the sleeve is pulled upwardly to shorten the axial extent of the sleeve located between the distal member and the proximal member. The method may comprise the step of moving the sleeve relative to the proximal member including sliding a portion of the sleeve against a radially outer portion of the proximal member.

In one embodiment a portion of the sleeve located between the distal member and the proximal member includes two material layers. The sleeve may be wrapped around the distal member to form the two material layers.

The method may comprise sealing the wound retractor, for example by attaching a seal to the wound retractor, by releaseably mounting a seal to the wound retractor. A seal may be mounted a proximal end of the wound retractor. A seal may be mounted to a proximal end of the sleeve.

In one case the retractor comprises a mounting member and the seal is attached to the mounting member.

In one embodiment the seal is attached to the proximal end of the wound retractor using a connector.

The connector may be a connecting sleeve. The connector may be at least partially of a flexible material. Alternatively the connector is at least partially of a malleable material and the method may comprise the step of manipulating the connector into a desired configuration. In one case the desired configuration is a configuration in which the seal is offset from the longitudinal axis of the wound retractor.

In one embodiment the method comprises pulling the sleeve upwardly to provide an excess sleeve portion extending proximally of the wound retractor. In one case the method comprises the step of cutting away the excess sleeve portion. In another case the method comprises the step of inserting the excess sleeve portion through the retractor. The excess sleeve material may be inserted through the retractor providing an organ retainer.

In another case the method comprises the step of manipulating the excess sleeve portion to provide a seal.

In one embodiment the retractor comprises a proximal mounting member and the excess sleeve portion is attached to the mounting member.

In another embodiment the excess sleeve portion forms, with the mounting member, a chamber. The chamber may have an inflation port and the method comprises inflating the chamber to provide a seal.

The seal may be a lip seal or an iris seal.

In one embodiment the wound retractor is sealed with a forearm seal.

In another embodiment the wound retractor is sealed with an instrument seal.

In one case the incision is of a size to receive an instrument, when retracted.

In another case the incision is of a size to receive a forearm, when retracted.

In a further case the incision is of a size to provide a site for open surgery, when retracted.

According to the invention there is provided a medical device comprising:

a retractor member comprising a distal portion for insertion through an incision made in a patient, and a proximal portion for extending from the incision and outside of the patient;

a distal member associated with the distal portion of the retractor member;

a proximal member associated with the proximal portion of the retractor member;

the retractor member being axially movable relative to the distal member to draw the proximal and distal members towards one another thereby shortening the axial extent of the retractor member between the proximal and distal members.

In one embodiment the retractor member comprises a sleeve member. The sleeve member preferably extends around the distal member.

In one embodiment the distal member is a ring member such as a resilient ring member, for example, an O-ring.

In one embodiment the proximal member is connected to the retractor member. The proximal member may be a ring member.

In one embodiment the sleeve member is of a pliable material.

In one arrangement the sleeve extends from the proximal member, around the distal member and has a return section outside of the proximal member.

The return section may have a handle member such as a ring member.

In one embodiment the device comprises a guide member.

The retractor member may extend between the guide member and the proximal member.

The guide member may comprise a receiver for the proximal member.

The guide member may comprise a guide ring-receiving member.

The sleeve return section may be configured to provide an integral valve member. In this case the sleeve return section may be twisted to provide an iris valve.

In another embodiment the sleeve return section is mounted to the guide member.

The sleeve return section may be extended into the opening defined by the sleeve member.

The device may comprise a lock for locking the guide member to the proximal member. Typically the guide member is engagable with the proximal member to provide the lock.

The guide member may be an interference fit with the proximal member.

In one embodiment of the invention the device includes a valve, such as an iris-type valve.

In one embodiment the device comprises a biassing member for biassing the valve into a desired position such as the closed position.

In one arrangement the device comprises a guide member located proximally of the proximal member and a biassing means is provided between the proximal member and the guide member. The biassing means may comprise a spring such as a coil spring.

In one embodiment a sleeve member extends between the proximal member and the guide member and the biassing means is located around the sleeve. The sleeve member may be an extension of the retractor member.

In one embodiment the device comprises a release member for releasing the device from an incision. The release member may comprise an elongate member such as a pull ribbon or string extending from a distal end of the device.

The release member may extend from the distal member.

In one embodiment the valve is located or locatable proximal of the proximal member. A pliable material may be provided between the valve and the proximal member. The pliable material may comprise a proximal extension of the retractor member.

In one embodiment the pliable material comprises a sleeve section.

In another embodiment the valve is a lip seal.

The invention also provides a method for retracting an incision comprising the steps of:

providing a device comprising a retractor member having a distal portion and a proximal portion, a distal member associated with the distal portion and a proximal portion associated with the proximal portion;

inserting the distal member and the distal portion of the retractor member through an incision made in a patient; and pulling the retractor member axially relative to the distal member to draw the proximal and distal members towards one another thereby shortening the axial extent of the retractor member between the proximal and distal members and retracting the incision.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be more clearly understood from the following description of some embodiments thereof, given by way of example only, with reference to the accompanying drawings, in which:

FIG. 1 is a perspective view of a retractor according to the invention;

FIG. 2 is a cross sectional view of the device of FIG. 1;

FIGS. 3 and 4 are perspective views illustrating the formation of the device of FIGS. 1 and 2;

FIGS. 5 and 6 are cross sectional views of FIGS. 3 and 4 respectively;

FIGS. 7 and 8 are perspective views illustrating the use of the device;

FIGS. 9 and 10 are cross sectional views illustrating the method of use of the device;

FIG. 11 is a cross sectional view of another device according to the invention in a configuration ready for use;

FIG. 12 is a perspective view of the device of FIG. 11 with a distal portion inserted through an incision;

FIG. 13 is a cross sectional view of the device of FIG. 11 with a distal portion inserted through an incision;

FIG. 14 is a cross sectional view of the device of FIG. 11 in use with an incision retracted;

FIG. 15 is a perspective view of the device in the configuration of FIG. 14;

FIG. 16 is a perspective view of the device in situ with an excess sleeve portion being removed;

FIG. 17 is a cross sectional view of the device in situ with an excess sleeve portion extending back into the incision;

FIG. 18 is a perspective view of the device in situ with a excess sleeve portion being twisted;

FIG. 19 is a perspective view similar to FIG. 18 with the excess sleeve portion further twisted to provide an iris valve;

FIG. 20 is a cross sectional view of another device according to the invention in situ;

FIG. 21 is a cross sectional view of the device of FIG. 20 with an excess sleeve portion mounted to a guide member;

FIG. 22 is a cross sectional view of the device of FIG. 21 with the excess sleeve portion inflated to provide an integral everting access part;

FIG. 23 is a perspective view of another retractor according to the invention incorporating a release device;

FIG. 24 is a cross sectional view of the retractor of FIG. 23;

FIG. 25 is a perspective view illustrating the formation of the device of FIG. 23;

FIG. 26 is a cross sectional view of the device in the configuration of FIG. 25;

FIG. 27 is a cross sectional view of the retractor of FIGS. 23 to 26, in use;

FIG. 28 is a cross sectional view of the retractor of FIGS. 23 to 27 illustrating the operation of a release device;

FIG. 29 is a perspective view of another device according to the invention in an insertion configuration;

FIG. 30 is a perspective view of the device of FIG. 29 in position in an incision;

FIG. 31 is another perspective view of the device of FIG. 30 in another configuration;

FIG. 32 is another view of the device of FIG. 31 with an outer portion severed and a valve being formed;

FIG. 33 is a view of the device of FIG. 32 with the valve closed;

FIG. 34 is a perspective view of another device similar to the device of FIGS. 29 to 33 with a valve closed;

FIG. 35 is a cross sectional view of the device of FIG. 34;

FIG. 36 is a perspective view of another device similar to the device of FIGS. 29 to 33 incorporating a biasing means in an inserted configuration;

FIG. 37 is another perspective view of the device of FIG. 36 in a retracting configuration;

FIG. 38 is a perspective view of the device of FIG. 37 in another configuration and excess sleeve being removed;

FIG. 39 is a perspective view of the device of FIG. 38 with a valve closed;

FIG. 40 is a perspective view of the device of FIG. 39 with a valve partially open;

FIGS. 41A and 41B are perspective views of the device of FIG. 39;

FIGS. 41C and 41D are perspective views of the device of FIG. 39 with an object inserted through the valve;

FIG. 42 is a perspective view of another device according to the invention;

FIG. 43 is a cross sectional view of the device of FIG. 42 in position in an incision;

FIG. 44 is a cross sectional view of the device of FIG. 43 with an object extending therethrough;

FIG. 45 is a cross sectional view similar to FIG. 44 with an object offset from a longitudinal axis of the device;

FIG. 46 is a cross sectional view of another device according to the invention on insertion into an incision;

FIG. 47 is a cross sectional view of the device of FIG. 46 with an incision retracted;

FIGS. 48 and 49 are cross sectional views of the device of FIG. 47 showing the formation of an iris valve;

FIG. 50 is a cross sectional view of another access port;

FIG. 51 is a cross sectional view of the port of FIG. 50 with an instrument in position;

FIGS. 52 to 55 are cross sectional views of another access port;

FIGS. 56 and 57 are cross sectional views of a further access port;

FIGS. 58 and 59 are cross sectional views of another access port;

FIGS. 60 to 62 are cross sectional views of a further access port;

FIGS. 63 to 66 are cross sectional views of another access port;

FIGS. 67 to 72 are cross sectional views of another access port of the invention.

DETAILED DESCRIPTION

Referring to the drawings, and initially to FIGS. 1 to 10 thereof there is illustrated a device 1 comprising a retractor member provided by a sleeve 2, a distal member provided by a distal ring 3 of resilient material such as an O-ring and a proximal member provided by a proximal ring 4 which may also be an O-ring.

The sleeve 2 is of any suitable material such as of pliable plastics film material and comprises a distal portion 5 for insertion through an incision 6, in this case made in a patient's abdomen 7, and a proximal portion 8 for extending from the incision 6 and outside of the patient.

In this case the distal ring 3 is not fixed to the sleeve 2 but rather the sleeve is led around the ring 3 and is free to move axially relative to the distal ring 3 somewhat in the manner of a pulley. The proximal ring 4 is fixed to the sleeve 2, in this case at the proximal inner end thereof. The sleeve 2 terminates in a handle or gripping portion which in this case is reinforced by a gripping ring 15.

To configure the retractor device according to the invention a sleeve 2 is first provided with the gripping ring 15

fixed at one end and the proximal ring 4 fixed at the other end [FIGS. 3, 5]. The distal ring 3 is then placed over the sleeve 2 as illustrated in FIGS. 4 and 6. The gripping ring 15 is then used to manipulate the sleeve 2 so that the sleeve 2 is folded back on itself into the configuration of FIGS. 1 and 2 in which the gripping ring 15 is uppermost. The sleeve extends from the proximal ring 4 and the distal ring 3 is contained between inner and outer layers 2a, 2b of the sleeve 2. The device is now ready for use.

The resilient distal ring 3 is scrunched up and inserted through the incision 6 with the distal end 5 of the sleeve 2 as illustrated in FIG. 4. The sleeve 2 is then pulled upwardly in the direction of the arrows A in FIGS. 8 to 10. On pulling of the sleeve 2 upwardly the outer layer 2b is pulled up while the inner layer 2a is drawn around the proximal ring 3. This results in shortening the axial extent between the proximal ring 4 and the distal ring 3, tensioning the sleeve and applying a retraction force to the margins of the incision 6. The system appears to be self locking because when tension is applied to the sleeve 2 and the pulling force is released the rings 3, 4 remain in position with a retraction force applied. Frictional engagement between the layers of the sleeve in this configuration may contribute to this self locking.

As the incision is being retracted the margins are also protected by the sleeve. On retraction, an access port is provided, for example for a surgeon to insert his hand and/or an instrument to perform a procedure. The device may be used as a retractor in open surgery or as a base for a valve/seal to allow it to be used in hand assisted laparoscopic surgery or for instrument or hand access generally.

Excess sleeve portion 20 outside the incision may, for example, be cut-away.

The retractor is suitable for a range of incision sizes and is easily manufactured. It is also relatively easy to manipulate, in use. It not only retracts but also protects the incision.

Referring now to FIGS. 11 to 19 there is illustrated another device 50 according to the invention which is similar to the device described above with reference to FIGS. 1 to 10 and like parts are assigned the same reference numerals. In this case the device comprises a guide member 51 for the proximal ring 4. The guide member 51 is in the form of an annular ring member with an inwardly facing C-shaped groove 52 which is sized to accommodate the ring 4 as illustrated. The outer layer of the sleeve 2 is interposed between the ring 4 and the guide 51 to further control the pulling of the sleeve and thereby further controlling the application of the retraction force. The guide 51 also assists in stabilising the proximal ring 4. The use of the device 50 is illustrated in FIGS. 12 to 15 is similar to that described above.

Any suitable guide such as the ring 51 may be used to assist in retaining/stabilising the proximal ring 4 in a desired position during pulling up of the sleeve to retract the incision. The guide may be located proximal of the ring 4.

The guide member provides a monitoring member to which devices such as valves may be attached.

Referring to FIG. 16, it will be noted that in one case the excess sleeve portion 20 may be cut-away.

Referring to FIG. 17, in this case the excess sleeve portion is inverted 60 into the incision. In this configuration it may act as an organ retractor, or provide the surgeon with an open tunnel to work in.

Referring to FIGS. 18 and 19 in this case the excess sleeve portion is twisted to form an iris diaphragm valve 65.

In the embodiment illustrated in FIGS. 20 to 22 a device 70 according to the invention has an integral seal/valve 71. The device 70 is similar to that described above with

reference to FIGS. 11 to 19 and like parts are assigned the same reference numerals. In this case the guide member 50 has an outer groove 75 to receive the gripping ring 15 as illustrated in FIG. 21. The excess sleeve portion 20 is folded out and down and the gripping ring 15 is engaged in the groove 75 to provide an air tight seal. In this configuration the excess sleeve may be inflated through an inflation port 76 [FIG. 22] to provide an integral access valve 71. The valve may be used to sealingly engage a hand, instrument or the like passing therethrough. The inflated sleeve portion defining the valve is evertable on passing an object therethrough.

Referring to FIGS. 23 to 28 there is illustrated another retractor 80 according to the invention which is similar to the retractors described above and like parts are assigned the same reference numerals. In this case the retractor 80 has a release mechanism which in this case is provided by a release cord or ribbon 81 which is coupled at one end 82 to the inner ring 3 and terminates in an outer free end 83 which may be grasped by a user. The ribbon 81, on assembly, is led through the gap between the proximal ring 4 and the outer guide member 51 so that it is positioned between the ring 4 and the guide member. The ribbon 81 facilitates release of the self locked sleeve in the in-use configuration sited in an incision. Pulling on the ribbon 81 pulls on the inner ring 3, allowing the ring 3 to be released from the inner wall of the incision to thereby release the device. The flexibility of the ring 3 facilitates this movement.

The advantage of this arrangement is that a user can readily release the device from its self locked retracting configuration.

Referring to FIGS. 29 to 33 there is illustrated another device 90 according to the invention in which parts similar to those of the devices described above are assigned the same reference numerals. In this case the device 90 has a lower guide ring 51 for the proximal ring 4 and an outer guide assembly provided by an upper guide ring 91 and a second proximal ring 92 between which the sleeve 2 is led. In all relevant embodiments the upper guide such as the ring 91 may provide a second mounting member located proximally of the first guide member such as the ring 51 which also provides a mounting member. The device is used to first retract an incision as described above. During this phase the outer guide assembly is conveniently external of the guide member 51 and proximal ring 4. Indeed, it may be completely detached from the sleeve 2 and subsequently coupled to the sleeve 2 at an appropriate stage such as when the incision is retracted as illustrated in FIG. 30. The outer guide assembly is then moved downwardly towards the incision as illustrated in FIG. 31. This may be achieved while pulling the sleeve 2 upwardly. When the guide assembly is adjacent to the guide member 51 excess sleeve length may be severed as illustrated in FIG. 32. By twisting the guide assembly relative to the guide member 51 the sleeve 2 is twisted, closing down the lumen of the sleeve 2 and forming an iris type access valve 95 as illustrated in FIG. 33. In this way a sealed access port is provided for hand and/or instrument access through the incision.

It will be appreciated that while reference has been made to an incision made by a surgeon the devices of the invention may be applied for retraction of any opening such as a body opening.

Referring to FIGS. 34 and 35 there is illustrated another retractor device 100 according to the invention which is similar to the device of FIGS. 29 to 33 and like parts are assigned the same reference numerals. In this case a releasable lock is provided to maintain the access valve 95 closed. For interlocking, in this instance the upper guide ring 91 is

an interference fit with the lower guide ring 51. Various other locking arrangements may be used such as a screw threaded or bayonet type engagement, magnets, clips and the like.

Referring to FIGS. 36 to 41D there is illustrated another retractor device 110 according to the invention which is similar to the device of FIGS. 29 to 33 and like parts are assigned the same reference numerals. In this case the device incorporates a biassing means to bias an integral valve into a closed position. The biassing means is in this case provided by a coil spring 111 which is located around the sleeve between the guide rings 51, 91. In use, the device is used in a similar manner to the device of FIGS. 29 to 33 except that on movement of the upper guide ring 91 downwardly the spring 111 also moves downwardly towards the lower guide ring 51, initially into the position illustrated in FIG. 38. Excess sleeve material may be removed at this stage. The spring 111 is tensioned as the upper ring 91 is rotated while pushing the upper ring 91 downwardly. The sleeve material between the two rings 51, 91 is twisted, forming an iris type valve 112 as illustrated in FIG. 39. To open the valve 112 to pass an object such as an instrument, hand, arm or the like therethrough a downward force may be applied to push the upper ring 91 towards the lower ring 51 against the biassing of the spring. This configuration is illustrated in FIG. 40. When the object is inserted the upper ring member 91 is released, allowing the valve to close around the object. The operation of the device 110 will be readily apparent from FIGS. 41A to 41D. In FIG. 41A the valve 112 is illustrated in a closed resting configuration. FIG. 41B shows the application of a downward force to open the valve 112. An object such as an instrument 113 is shown inserted through the open valve 112 in FIG. 41C. In FIG. 41D the downward pressure on the upper ring 91 is released allowing the valve 112 to close around the object 113.

Referring now to FIGS. 42 to 45 there is illustrated another device 120 according to the invention which has some aspects similar to the device of FIGS. 11 to 18 and like parts are assigned the same reference numerals. In this case the device has a lip seal 121. The lip seal 121 is provided by a membrane with a central aperture 122 through which an object 123 such as an instrument is passed. The lip seal 121 is located on the sleeve 2 proximally of the guide ring 51 such that a proximal flexible sleeve section 125 is provided. This sleeve section 125 is very useful in facilitating offset movements of the object 123 as illustrated in FIG. 45. The sleeve section 125 accommodates movement of the object 123 whilst maintaining sealing engagement between the lip seal 121 and the object 123. It will be appreciated that this feature, as with several other features described above may be utilised in association with other constructions of wound protector/retractors and access parts generally other than those illustrated in the drawings.

Referring to FIGS. 46 to 48 there is illustrated another device 130 according to the invention which has some features similar to those of FIGS. 11 to 15, like parts being assigned the same reference numerals. In this case the sleeve has a proximal section external of the wound when the device is in the retracting configuration. This proximal sleeve section comprises a first portion 131 extending from the guide ring 51 and a second portion 132 extending from the first portion 131. The second portion 132 is defined between two spaced-apart iris rings 134, 135. It will be noted that the iris rings 134, 135 have engagement features such as projections and grooves for interengagement on assembly. The iris ring 134 also has an engagement element, in this case provided by a groove 137 for engagement on assembly

with a corresponding engagement element of the guide ring 51 which in this case is provided by a projection 138.

The device is fitted as described above to retract an incision, leaving the first and second sleeve portions 131, 132 extending proximally. The first sleeve portion 131 is redundant and can be removed or scrunched up on assembly of the first iris ring 134 to the guide ring 138 as illustrated in FIG. 48. The second or upper iris ring 135 is then rotated to twist the sleeve section 132 to form an iris-type seal as illustrated in FIG. 49. The iris ring 135 is engaged with the iris ring 134 as illustrated to maintain the valve closed.

In some of the embodiments described above a valve 829 is mounted directly to a retractor base 811. It is possible to provide a flexible coupling between the retractor 811 and the valve 829. For example, as illustrated in FIGS. 93 and 94 such a flexible coupling is provided by a length of flexible sleeve 830 extending between the retractor 811 and the valve 829. The flexible sleeve 830 may be formed by excess retractor sleeve material attached to the valve 829.

In a further embodiment of the invention as illustrated in FIGS. 52 to 57 a valve 860 may be coupled to the retractor 811 in such a way as to facilitate a flexible joint therebetween. For example, a fixed length sleeve 862 may extend between an outer proximal ring 863 of the retractor 811 and the valve 860. Excess sleeve material 864 from the retractor 811 may pass up through the valve 860. The valve 860 may be pushed down and the excess sleeve pulled up to firmly lock the base retractor 811 in the incision. Excess sleeve material 864 may be cut-away and removed, if desired. The flexible sleeve 864 allows the instrument to tilt as illustrated in FIG. 57 without compromising the valve seal to the shaft of the instrument/object 814.

As illustrated in FIGS. 58 and 59 a spring 867 may be provided between the valve 860 and the retractor proximal ring 863 for more controlled flexibility.

Referring now to FIGS. 60 to 62 another modular system is illustrated in which a valve 870 is releasably mounted to a retractor 811. The retractor 811 may have a proximal ring 871 with a recess 872 to receive the valve 870. An instrument shaft 814 can readily pass through the valve 870 and retractor 811. At least a section 873 of the shaft 814 can be bent or steered almost immediately distal of the retractor.

Referring now to FIGS. 63 to 66 any suitable valve 880 may be coupled to a retractor 811 using excess sleeve material 881 from the retractor 811. The valve 880 may be pulled upwardly to deploy the base retractor 811. The excess sleeve material 881 provides a flexible neck which facilitates easy introduction of objects such as an instrument 883, even one having a bent shaft (FIG. 119). As illustrated in FIG. 120 such an arrangement also facilitates additional instrument reach by allowing the valve 880 to be moved closer to the base retractor 811.

Referring to FIGS. 67 to 72 there is illustrated another access port comprising a wound protector and retractor device 811 and a valve 900. The valve 900 is connected to an outer guide ring 901 of the retractor device 811 by a sleeve 902 which in this case is of malleable material of corrugated configuration somewhat in the manner of the bendable hinge portion of a bendable drinking straw. The sleeve 902 may be pre-shaped to be offset from the longitudinal axis of the retractor to facilitate ease of insertion of an instrument or the like. The corrugated sleeve 902 may be compressed as illustrated in FIG. 68 to provide a low profile to facilitate outlining any of excess retractor sleeve as illustrated in FIGS. 69 and 70. Thereafter, the corrugated sleeve 902 can be extended/elongated and is readily manipulated into a desired configuration. Because the sleeve 902 is

13

malleable it will retain a desired bent shape, even when the abdomen is pressurised. Any excess retractor sleeve material 905 may be cut-away as illustrated or used as described above.

In this context the term "malleable" is used to denote an element which is capable of being manipulated into a desired position and/or orientation, and which retains this manipulated position and/or orientation under the typical stresses and strains applied when used for an intended purpose with a patient, for example during partial insertion 10 of a laparoscopic instrument.

The access ports of the invention can be used in a number of ways. In one method the retractor is used as described above, the distal inner ring being inserted into an incision, the outer ring being slid to controllably radially expand the 15 incision. The retractor may then be locked in position. If necessary, the outer ring can be moved further downwardly to create a larger incision.

In some arrangements an instrument may be bent manually outside the body and the bent instrument is delivered 20 through the access port to readily access the operative site.

In a further embodiment an instrument is inserted into the access port and the surgeon uses the abdominal wall itself to bend the instrument and then insert the bent section further into the abdomen.

In all cases the sleeve may be gripped by gripping a valve or other element mounted thereto.

The access ports of the invention have at least some of the following advantages:

Controlled Radial Expansion

1. Greater access using smaller incision
2. Can vary incision size as need be (e.g. specimen removal during lap colo.)

Greater Sealing Capabilities

1. No gas leakage from the wound margins
2. Cannot be inadvertently pulled out of the incision
3. Will seal any incision and never require secondary sealing method (suture, Hasson port, etc.)

Eliminate Intra-Abdominal Profile

1. Gives back more working space in the abdomen (critical in pelvic surgery)
2. Perineal access for operations such as Radical Prostatectomy.

Protection of Wound from Infection and Cancer Seeding

1. Tight seal with no "chimney stack" effect
2. Upon removal all areas of potential contamination are isolated from the incision

Reduced Extra-Abdominal Profile

1. Will increase the effective working length of an instrument
2. Greater working area outside the abdomen

Increase the Freedom of Movement of Conventional Laparoscopic Instruments

The invention is not limited to the embodiments hereinbefore described, with reference to the accompanying drawings, which may be varied in construction and detail.

The invention claimed is:

1. A surgical device, comprising:
a wound retractor, comprising:

a distal ring,
a proximal ring, and

a wound retracting sleeve extending at least between the distal ring and the proximal ring, wherein the wound retractor is for retracting a wound opening via shortening of an axial extent of the wound retracting sleeve that extends between the distal ring and the proximal ring, and wherein the proximal ring and the

14

wound retracting sleeve are separate elements that are engaged such that positioning of a proximal portion of the wound retracting sleeve relative to the proximal ring is adjustable to shorten the axial extent of the wound retracting sleeve; and

a sealing assembly coupled to the wound retractor, wherein the sealing assembly comprises:

an access sleeve having a proximal end, the access sleeve extending proximally from the proximal ring to the proximal end, and

a valve member at the proximal end of the access sleeve, the valve member being movable between a first position and a second position, wherein at least a proximal end of the valve member is:

a first distance from a proximal end of the proximal ring in the first position, and

a second distance from the proximal end of the proximal ring in the second position, the first distance being greater than the second distance, and

wherein material forming the access sleeve inherently biases the valve member toward moving from the first position to the second position.

2. The surgical device of claim 1, wherein a central longitudinal axis of the valve member is aligned with a central longitudinal axis of the wound retractor when the valve member is in the first position.

3. The surgical device of claim 1, wherein a central longitudinal axis of the valve member is tilted relative to a central longitudinal axis of the wound retractor when the valve member is in the second position, and an angle between the central longitudinal axes increases as the valve member moves from the first position to the second position.

4. The surgical device of claim 1, wherein a width of the access sleeve tapers as the access sleeve extends proximally from the proximal ring to the proximal end.

5. The surgical device of claim 1, wherein at least a portion of the valve member extends proximally beyond a proximalmost portion of the access sleeve.

6. The surgical device of claim 1, wherein spring material forming the access sleeve provides the inherent biasing to cause the access sleeve to spring back toward the first position from the second position.

7. The surgical device of claim 1, wherein the wound retracting sleeve is slidably coupled to the proximal ring.

8. The surgical device of claim 1, wherein a distalmost end of the valve member is distal to a proximalmost end of the access sleeve.

9. A surgical device, comprising:

a wound retractor, comprising:

a distal ring,

a proximal ring, and

a wound retracting sleeve extending at least between the distal ring and the proximal ring, wherein the wound retractor is for retracting a wound opening via shortening of an axial extent of the wound retracting sleeve that extends between the distal ring and the proximal ring, and wherein the proximal ring and the wound retracting sleeve are separate elements that are engaged such that positioning of a proximal portion of the wound retracting sleeve relative to the proximal ring is adjustable to shorten the axial extent of the wound retracting sleeve; and

a sealing assembly coupled to the wound retractor, wherein the sealing assembly comprises:

15

an access sleeve having a proximal end, the access sleeve extending proximally from the proximal ring to the proximal end, and
 a valve member at the proximal end of the access sleeve, the valve member being movable between a first position and a second position, wherein a central longitudinal axis of the valve member is more tilted relative to a central longitudinal axis of the wound retractor in the second position than in the first position, and wherein material forming the access sleeve is inherently biased to return the valve member to the first position upon removal of a force acting to deform the access sleeve and place the valve member in the second position.

10. The surgical device of claim 9, wherein spring material forming the access sleeve provides the inherent biasing to cause the access sleeve to spring back to the first position from the second position upon removal of the force.

11. The surgical device of claim 9, wherein the central longitudinal axes of the valve member and the wound retractor are aligned when the valve member is in the first position.

12. The surgical device of claim 9, wherein a lateral portion of the access sleeve buckles as the valve member moves from the first position to the second position.

13. The surgical device of claim 12, wherein the lateral portion becomes straight as the valve member moves from the second position to the first position.

14. The surgical device of claim 9, wherein a first portion of the access sleeve has a first width, and a second portion of the access sleeve has a second width, and wherein the first width is wider than the second width.

15. A surgical device, comprising:
 a wound retractor, comprising:

a distal ring,
 a proximal ring, and
 a wound retracting sleeve extending at least between the distal ring and the proximal ring, wherein the wound retractor is for retracting a wound opening via shortening of an axial extent of the wound retracting

16

sleeve that extends between the distal ring and the proximal ring, and wherein the proximal ring and the wound retracting sleeve are separate elements that are engaged such that positioning of a proximal portion of the wound retracting sleeve relative to the proximal ring is adjustable to shorten the axial extent of the wound retracting sleeve; and
 a sealing assembly coupled to the wound retractor, wherein:

the sealing assembly comprises an access sleeve having a proximal end, the access sleeve extending proximally from the proximal ring to the proximal end, such that the proximal end is separated from the proximal ring by a distance, and the access sleeve including a wall extending between the proximal ring and the proximal end, and

material forming the wall is resilient, such that the access sleeve is biased by the resilience of the material to move from a contracted configuration to an extended configuration upon removal of a force deforming the access sleeve into the contracted configuration.

16. The surgical device of claim 15, wherein the wall includes spring material that provides the resiliency for causing the access sleeve to spring back into the extended configuration from the contracted configuration.

17. The surgical device of claim 15, wherein the access sleeve tapers.

18. The surgical device of claim 15, wherein the access sleeve is tilted, relative to a central longitudinal axis of the wound retractor, in the contracted configuration.

19. The surgical device of claim 15, wherein central longitudinal axes of the access sleeve and the wound retractor are aligned when the access sleeve is in the extended configuration.

20. The surgical device of claim 15, wherein in the extended configuration, a lateral portion of the wall is straight as the lateral portion extends from the proximal ring to the proximal end.

* * * * *

专利名称(译)	伤口牵开器装置		
公开(公告)号	US10278688	公开(公告)日	2019-05-07
申请号	US15/610012	申请日	2017-05-31
[标]申请(专利权)人(译)	阿特波斯有限公司		
申请(专利权)人(译)	阿特洛波斯有限公司		
当前申请(专利权)人(译)	阿特洛波斯有限公司		
[标]发明人	BONADIO FRANK BUTLER JOHN VAUGH TREVOR MACNALLY SHANE J REID ALAN		
发明人	BONADIO, FRANK BUTLER, JOHN VAUGH, TREVOR MACNALLY, SHANE J. REID, ALAN		
IPC分类号	A61B17/02 A61B17/34 A61B1/32 A61B17/00		
CPC分类号	A61B17/0293 A61B1/32 A61B17/3423 A61B17/3439 A61B17/3462 A61B17/3498 A61B2017/3492 A61B2017/00557 A61B2017/0212 A61B2017/0225 A61B2017/3443 A61B2017/3482 A61B2017/3484 A61B17/3431		
优先权	60/415780 2002-10-04 US 60/428215 2002-11-22 US 60/490909 2003-07-30 US		
其他公开文献	US20170325801A1		
外部链接	Espacenet		

摘要(译)

伤口保护器和牵开器装置1包括套管2，由弹性材料的远端环3提供的远端构件和由近端环4提供的近端构件。套筒2围绕环3引导并且可以以滑轮的方式稍微相对于远端环3轴向移动。近端环4固定到套管2，在这种情况下在其近端内端。套筒2终止于手柄或抓握部分，该抓握部分由抓握环15加强。套筒从近端环4延伸，并且远端环3包含在套筒2的内层和外层2—个，2b之间。将弹性远端环3碾碎并插入切口6。然后将套筒2向上拉。在向上拉套筒2时，向上拉外层2b，同时围绕近端环3拉动内层2—种。这导致缩短近端环4和远端环3之间的轴向范围，张紧套管并向切口边缘6施加缩回力。当切口缩回时，边缘也受到套筒的保护。在缩回时，提供进入端口，例如用于外科医生插入他的手和/或器械以执行手术。该装置可用作开放手术中的牵开器或用作瓣膜/密封件的基部，以允许其用于手助腹腔镜手术或一般用于器械进入或手动进入。

