



US 20070038227A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2007/0038227 A1**

Massicotte et al.

(43) **Pub. Date:** **Feb. 15, 2007**

(54) **METHOD AND DEVICE FOR EXTRACTING
OBJECTS FROM THE BODY**

Publication Classification

(76) Inventors: **J. Mathieu Massicotte**, North Reading, MA (US); **Peter J. Massicott**, Boston, MA (US)

(51) **Int. Cl.**
A61B 17/22 (2006.01)

(52) **U.S. Cl.** **606/127**

Correspondence Address:
Gauthier & Connors LLP
Suite 2300
225 Franklin Street
Boston, MA 02110 (US)

(57) **ABSTRACT**


(21) Appl. No.: **11/503,617**

(22) Filed: **Aug. 14, 2006**

A device for extracting objects from the body, such as urinary stones, using a low pressure inflatable toroidal balloon that serves to engulf the object during extraction while dilating and protecting the passageway. The balloon loads onto an ureteroscope prior to insertion, rather than through the ureteroscope as do existing balloons. The toroidal balloon is a simple and unique device that may be applied external to the extracting telescope and does not interfere with existing methods for stone manipulation such as laser lithotripsy, irrigation and basket extraction in the case of urinary stone manipulation.

Related U.S. Application Data

(60) Provisional application No. 60/708,124, filed on Aug. 12, 2005.






FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5









FIGURE 6








Figure 9a




Figure 9b




Figure 9c





Figure 10






Figure 11e

Figure 11f

METHOD AND DEVICE FOR EXTRACTING OBJECTS FROM THE BODY

RELATED APPLICATION

[0001] This application claims priority to U.S. provisional application 60/708,124 filed Aug. 12, 2005, which is incorporated in its entirety herein by reference.

BACKGROUND OF THE INVENTION

[0002] 1. Field of Invention

[0003] This invention relates generally to medical devices, more particularly to devices for removal of stone, foreign bodies and the like from the body.

[0004] 2. Discussion of Prior Art

[0005] Existing techniques for extraction of stones from the body such as in the case of stones lodged in the urinary collecting system and in the biliary tree can be cumbersome, inefficient and risky with respect to complications. For example, the extraction of urinary stones often requires cystoscopic balloon dilation of the distal ureter using a high pressure balloon to increase the capacity of the ureter in order to allow decreased resistance with passage of the ureteroscope and extraction of the stone or its fragments. This high pressure balloon requires a costly pressure gauge and can be traumatic to the ureter placing the ureter at risk for stricture formation. After dilation, an ureteroscope is inserted and lithotripsy performed if the stone is too large for extraction. The stone is then engaged under direct vision with a basket or similar device and then withdrawn into the bladder where the stone is then considered passed. This technique requires that the stone be of sufficiently diminutive size (which is usually not the case with a lodged stone) or that the stone be fragmented with a device such as a laser which in itself carries the risk of injury to the ureter. Furthermore, extraction of a stone engaged in a wire basket carries the risk of frictional damage to the ureteral mucosa and wall, the risk of a retained basket engaged with stone requiring tertiary referral or open surgery, or the risk of catastrophic avulsion injury of the ureter.

[0006] The above time consuming, costly and risky standard techniques begs for the development of a device which will provide a less cumbersome, safer, more efficient and less costly technique to treat the extremely common problem of urinary stone disease. Other inventors have attempted to address this vexing task.

[0007] Hardwick, U.S. Pat. No. 4,469,100, proposed a device in which the stone is drawn into the balloon by intussusception, protecting the ureteral walls from the friction with stone extraction. The deficiencies of this idea include the blind passage of the device to the stone (i.e.: not under direct visualization as with the standard technique), dependence upon suction to engage a stone which has an irregular surface not amenable to suction seal for traction, and, most significantly, the device's construction where the balloon is attached to the catheter near its proximal and distal ends. The result of the latter construction is that, while the stone achieves sanctuary within the confines of the balloon's wall during intussusception, the external surface of the balloon is withdrawn in direct opposition to the ureteral wall when extracting the stone which places the ureter at risk for injury.

[0008] Another inventor who attempts to solve the existing problems with stone extraction is Drettler, U.S. Pat. No. 4,927,426. Here a catheter-like device is used which allows a laser fiber for lithotripsy but suffers the same deficiencies as Hardwick's device. U.S. Pat. Nos. 4,243,040 and 4,295,464, likewise, suffer similar problems.

[0009] Current techniques for biliary stone extraction also can be cumbersome, inefficient and risky for complication. Gallstones may become lodged in the biliary tree, often at the sphincter of Oddi which may result in biliary colic and cholangitis or pancreatitis. Many surgical devices and techniques exist for treatment of these stones confined to the biliary tree and unable to pass to the duodenum. Access to and extraction of biliary stones often require balloon dilation or sphincterotomy at the duodenal papilla which carries the risk of bleeding and perforation. The stone is then engaged with a basket, such as Cook's The Web™ Extraction Basket which risks, as with a urinary stone, injury of the biliary ductal system and retention of the basket.

[0010] Another technique for stone extraction uses a balloon such as that described by Karpeil, et al., U.S. Pat. No. 6,692,484 B1, where the sphincter is dilated and a second balloon is used to push the stone through into the duodenum. Similar balloons, such as the Cook Endoscopy Tri-Ex® Triple Lumen Extraction Balloon, often requires sphincterotomy. These balloons in general work well but do not directly control the stone as with a basket which can sometimes leave the stone wedged between the balloon and ductal wall.

[0011] Whatever the precise merits, features, and advantages of the above cited references, none of them achieves or fulfills the purposes of the present invention.

SUMMARY OF THE INVENTION

[0012] The device consists of a balloon, inflated and deflated through a small catheter, which is applied to the outside of a ureteroscope (or inserted through a separate guide when used in a separate application) which inverts to safely guide the removal of a stone, surgical specimen, foreign body or organ. As the object is drawn through the balloon, there is significantly less friction and therefore less risk for injury to surrounding tissue.

[0013] The present invention's toroidal balloon is activated via inflation. The unwanted object is manipulated with existing techniques and then drawn into the balloon, inverting the balloon. With extraction, the object is drawn internally through the balloon, protecting the tissue from the object. The balloon is taken down from the inside and does not require the sliding of the external balloon surface against the tissue. This allows a low friction extraction since only the two opposing inner balloon surfaces are sliding against each other. Since friction is minimized and the anatomy protected from the object, larger objects may be extracted without the need for dilation or fragmentation of the object. It is thus a highly efficient safety device for removing objects from the body.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] FIG. 1 illustrates an exemplary embodiment of the present invention's toroidal balloon used to remove an object that is lodged, for example, between the walls of the ureter.

[0015] FIG. 2 illustrates one embodiment of the present invention's toroidal balloon device for attachment to a scope.

[0016] FIG. 3 illustrates such an example, wherein an attachment is configured without the inflation catheter, wherein the coupling attachment inserts directly into a channel of a scope for inflation.

[0017] FIG. 4 illustrates another embodiment wherein the present invention's toroidal balloon comprises a luer lock connector, valve, an inflation/deflation port, a toroidal balloon, a coupling attachment to the catheter, and a catheter containing wire to open a basket.

[0018] FIG. 5 illustrates scenarios wherein the basket is closed, open, and open with balloon being inflated.

[0019] FIG. 6 illustrates a first design to apply the present invention's balloon to the end of the scope.

[0020] FIGS. 7a-c illustrate another design to apply the present invention's balloon to the end of the scope.

[0021] FIGS. 8a-c illustrate yet another design to apply the present invention's balloon to the end of the scope.

[0022] FIG. 9a illustrates the present invention's balloon having the scope being advanced to the stone.

[0023] FIG. 10 illustrates how the stone is withdrawn with minimal friction based on the teaching of the present invention as illustrated and described according to FIG. 1.

[0024] FIG. 11a-f illustrate the technique of how the present invention's device can be used as a balloon instrument.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0025] While this invention is illustrated and described in a preferred embodiment, the device may be produced in many different configurations, forms and materials. There is depicted in the drawings, and will herein be described in detail, a preferred embodiment of the invention, with the understanding that the present disclosure is to be considered as an exemplification of the principles of the invention and the associated functional specifications for its construction and is not intended to limit the invention to the embodiment illustrated. Those skilled in the art will envision many other possible variations within the scope of the present invention.

[0026] The present invention provides for a toroidal balloon used in the extraction of objects from the body. FIG. 1 illustrates an exemplary embodiment of the present invention's toroidal balloon used to remove an object 102 that is lodged, for example, between the walls of the ureter. The inflated toroidal balloon is taken down internally, wherein the external balloon surface does not move relative to the ureter (i.e., there is no sliding of the external balloon surface against ureter). The inflated toroidal balloon inverts with minimal friction during extraction. Object 102 is drawn internally through the balloon. Reference points 104, 106, 108, and 110 are shown to illustrate how the balloon is taken down internally. The method illustrated in FIG. 1 teaches the low friction extraction of object 102 with the sliding of the two opposing inner balloon surfaces, allowing for the safe removal of a stone, surgical specimen, foreign body or

organ. Inflation of balloon is preferable as it minimizes friction between the ureteroscope/basket/stone complex with extraction.

[0027] It should be noted that the only significant force with the extraction described in FIG. 1 is a radial force involved with the low friction extraction, wherein the force distribution similar to that of a wedge splitting wood. Also, since the stone itself dilates the ureter (just enough for stone passage, no more), there are no overdilation problems. Hence, the present invention's toroidal balloon minimizes ureteral dilation injury.

[0028] FIG. 2 illustrates one embodiment of the present invention's toroidal balloon device for attachment to a scope. The device as per the embodiment of FIG. 2 comprises luer lock connector 201, valve 202, inflation/deflation catheter 203, toroidal balloon 204, coupling attachment 205 and, optionally, a sheath 205 along catheter to guide insertion of scope.

[0029] Connector 201 is a conventional luer lock threaded to receive a conventional syringe in an air/watertight connection. It should be noted that a no pressure gauge is required for low pressure balloon for most applications. The Luer lock connection may be part of a locking valve 202 to control inflation or deflation. The valve is then connected to a catheter 203 which on the opposite end is connected with the toroidal balloon 204. The catheter 203 provides a conduit for the fluid such as saline, or a biocompatible lubricant used for inflation of the balloon. Catheter 203 is sufficient long to allow extracorporeal inflation of balloon 204 (e.g., approximately 20-50 cm in length). The flexible catheter 203, constructed of polyethylene or other appropriate material, runs through the inner opening in the balloon 204, attaching at the leading end of the balloon only. Inflation/deflation catheter 203 provides a conduit for fluid such as saline or other biocompatible lubricant used for in/deflation of balloon. The proximal end of the inflation/deflation catheter 203 attaches to syringe, distal to balloon and is sufficiently long to allow extracorporeal inflation (e.g., 20-50 cm in length). The inflation/deflation catheter 203 attaches at balloon's leading edge and runs internal to balloon, external to scope, and is made of polyethylene or other material. Further, the inflation/deflation catheter 203 may not be necessary with specialized endoscope (i.e., if balloon attaches directly to scope channel)

[0030] In one embodiment, the inflation/deflation catheter 203 has a non-cylindrical construction for low-profile.

[0031] Balloon 204 may be constructed of an expandable material such as latex rubber, silicone or other medical grade material/elastomer. Balloon 204 may have a lubricious coating to facilitate insertion into the ureter. Balloon 204 may be coated with a biologically active substance such as an alpha-blocker or smooth muscle relaxant. Balloon 204 may have reinforcements in the wall to maintain shape and pressure. Dilatation of the ureter is only a minor role of the balloon so construction with a high tension substance is unnecessary. A purpose of inflation is to minimize friction between the ureteroscope/basket/stone complex with extraction. Balloon 204 achieves this low friction extraction with the sliding of the two opposing inner balloon surfaces. In one non-limiting example, the length of the balloon is 2 to about 20 cm long. The length depends upon the distance from the stone to just beyond the ureteral orifice, as determined by the Urologist.

[0032] Attachment 205 of the catheter to the balloon may be of plastic or metal (alloy) and be shaped to allow simultaneous filling (or emptying) of the balloon 204 and fixation of the balloon/catheter device to the distal end of the endoscope such as a ureteroscope. Existing ureteroscopes vary in construction so the construction of the attachment will be specific to the ureteroscope. The attachment will also be formulated to allow loading of the balloon over the ureteroscope.

[0033] Attachment 205 attaches inflation/deflation catheter 203 to balloon 204 and attaches the device to a telescope. Attachment 205 facilitates loading of balloon 204 onto the telescope and facilitates insertion of the scope into ureteral orifice (e.g., may be, tapered/curved at the leading edge). Attachment 205 could also help seal the balloon closed in manufacturing process. Attachment 205, in one non-limiting example, is made using plastic or metal (alloy).

[0034] Attachment 205 may be constructed for a water-tight attachment to endoscope channel for inflation. FIG. 3 illustrates such an example, wherein attachment 205 is configured without inflation catheter wherein the coupling attachment 205 inserts directly into a channel of a scope for inflation.

[0035] The toroidal balloon device may also be fashioned with dimensions and materials for other applications such as removal of gall stones, foreign bodies, surgical specimens, etc. The device is of simple construction, of low cost and disposable.

[0036] The balloon is attached to the extraction device at just one level at the distal aspect, so the stone can both be drawn via intussusception into the protective confines of the inner surface and also drawn out the entire length of the balloon and out of the patient via intussusception. The device in Hardwick's patent (U.S. Pat. No. 4,469,100) intussuscepts slightly to cover the stone but is not a toroidal balloon since it is attached both distally and proximally. Hardwick's double attachment may allow minimal inversion of the balloon to cover the stone before the balloon is pulled out, but intussusception of the balloon is not the mechanism by which a stone is extracted. The ability to invert our entire balloon is the important and unique benefit of our device.

[0037] During stone extraction using Hardwick's doubly attached balloon, after a short length of intussusception, the outer surface of his balloon must be dragged across the surface of the ureter during extraction. It seems doubtful that the friction and other physical forces would allow extraction of an inflated balloon through a tight tube such as the ureter. There is no balloon in common use which is withdrawn in the ureter while inflated.

[0038] The present invention's 204 balloon is taken down internally with minimal friction. By contrast, Hardwick's balloon is extracted by sliding the external balloon wall against the ureteral wall. In our balloon, the only walls that slide against each other are the two internal surfaces of the balloon, wetted by the fluid used to inflate the balloon. Unlike Hardwick's balloon, the outside wall of our balloon remains stationary with respect to the ureteral wall until it inverts during the extraction.

[0039] Another important difference is that the present invention's balloon facilitates existing techniques for stone extraction. The present invention's device is added external

to the ureteroscope without affecting existing techniques for stone manipulation and adds safety and efficiency to the process of stone extraction. Ureteral stones are addressed, fragmented if necessary and engaged per routine with existing devices (ureteroscopes, laser fibers and wire baskets, respectively). Urologists won't need to learn a new technique for stone manipulation. They'll need only to inflate the sleeve (balloon) for extraction. Hardwick device's, in contrast to our balloon, replaces the ureteroscope and depends upon suction to grasp the stone. This requires blind passage of the device, not under safe direct visualization as with ours, to the level of the stone, which would be difficult and risky. The ability to grasp a jagged stone by suction is suspect. In addition, suction would engage the ureteral wall.

[0040] FIG. 4 illustrates another embodiment wherein the present invention's toroidal balloon is used as an instrument, wherein the setup comprises a luer lock connector 401, valve 402, inflation/deflation port 403, toroidal balloon 404, coupling attachment to the catheter 405, and catheter containing wire to open basket 406. The principle of functionality is similar to that of what is outlined in FIG. 1. FIG. 5 illustrates scenarios wherein the basket is closed, open, and open with balloon being inflated.

[0041] FIG. 6 illustrates a first design to apply the present invention's balloon to the end of the scope. In this example, the balloon is constructed over a tube matching the external conformation of the scope 601. The length of the balloon is at least the distance from the stone to uretral orifice.

[0042] FIGS. 7a-c illustrate another design to apply the present invention's balloon to the end of the scope. As shown in FIG. 7a, the balloon is pre-rolled and attached to the end of the scope 701 and, as shown in FIGS. 7b-c, the pre-rolled balloon is then unrolled, like a condom, onto the telescope. As mentioned previously, the length of the balloon is at least the distance from the stone to uretral orifice.

[0043] FIGS. 8a-c illustrate yet another design to apply the present invention's balloon to the end of the scope. As shown in FIG. 8a, the balloon is inflated before application to the scope 801. As shown in FIG. 8b, the inflated balloon is attached to the end of the scope 801 and, then, rolled back over the scope 801. As shown in FIG. 8c, the balloon is then deflated and is ready for insertion into the patient.

[0044] FIG. 9a illustrates the present invention's balloon having the scope being advanced to stone 901. The stone is then fragmented with a laser, if necessary, and is engaged within basket 902 as shown in FIG. 9b. In FIG. 9c, the toroidal balloon is then inflated. FIG. 10 illustrates how the stone 901 is withdrawn with minimal friction based on the teaching of the present invention as illustrated and described according to FIG. 1.

[0045] FIG. 11a-f illustrate the technique of how the present invention's device can be used as a balloon instrument. According to FIG. 11a, basket 1102 is inserted into the scope. According to FIG. 11b, the basket 1105 is advanced into the duct and opened. According to FIG. 11c, the stone 1106 is engaged in basket 1105. Next, as shown in FIG. 11d, the balloon is inflated. FIG. 11e depicts an example wherein the balloon is inflated within the duct with the stone engaged in the basket. FIG. 11f illustrates how the stone is withdrawn with minimal friction based on the teaching of the present invention as illustrated and described according to FIG. 1.

[0046] The present invention can be used in the extraction of various objects, including, but not limited to: percutaneous stone extraction (PCNL), bladder stones, urethral stones, tracheal foreign bodies, rectal foreign bodies, surgical specimens, endotracheal tubes, or virtually in any endoscopic procedure.

[0047] Therefore, the present invention provides a toroidal balloon of a simple construction and has a low-cost of manufacturing. Further, the present invention's toroidal balloon provides for a low risk of device failure. The present invention's device may be a disposable toroidal balloon. The present invention's device may also be fashioned with dimensions and materials for other applications such as removal of gall stones, foreign bodies, surgical specimens, etc.

[0048] The present invention allows for the development of specialized ureteroscopes, such as a smaller scope with a balloon attachment for stone basketing and extraction only. Further, the present invention's toroidal balloon is applicable to multiple medical and veterinary specialties and body systems.

CONCLUSION

[0049] A system and method has been shown in the above embodiments for the effective implementation of a method and device for extracting objects from the body. While various preferred embodiments have been shown and described, it will be understood that there is no intent to limit the invention by such disclosure, but rather, it is intended to cover all modifications and alternate constructions falling within the spirit and scope of the invention, as defined in the appended claims. For example, the present invention should not be limited by size, materials, or specific manufacturing techniques.

1. An expandable toroidal balloon used to remove a foreign object comprising:

an internal balloon surface contacting a foreign object;
an external balloon surface contacting a biological wall;
said foreign object being drawn internally through said expandable toroidal balloon via an inversion of said internal balloon surface and external balloon surface, said inversion safely guiding the removal of said foreign object without sliding of said external balloon surface against said biological wall.

2. An expandable toroidal balloon as per claim 1, wherein said expandable toroidal balloon has a lubricious coating.

3. An expandable toroidal balloon as per claim 1, wherein said expandable toroidal balloon is coated with a biologically active substance.

4. An expandable toroidal balloon as per claim 3, wherein said biologically active substance is any of, or a combination of, the following: an alpha-blocker or smooth muscle relaxant.

5. An expandable toroidal balloon as per claim 1, wherein said toroidal balloon is attached to a scope.

6. An expandable toroidal balloon as per claim 5, wherein said toroidal balloon is constructed over a tube matching an external configuration of said scope.

7. An expandable toroidal balloon as per claim 5, wherein said toroidal balloon is pre-rolled, attached to an end of said scope, unrolled onto said scope, prior to internally drawing said foreign object.

8. An expandable toroidal balloon as per claim 5, wherein said toroidal balloon is inflated, rolled back over said scope, and deflated prior to internally drawing said foreign object.

9. An expandable toroidal balloon as per claim 1, wherein said toroidal balloon is part of a medical balloon instrument.

10. An expandable toroidal balloon as per claim 1, wherein said balloon is made of any of the following materials: latex rubber, silicone, or elastomer.

11. An expandable toroidal balloon as per claim 1, wherein said foreign object is any of the following: percutaneous stone, bladder stone, urethral stone, tracheal foreign body, rectal foreign body, surgical specimen, or endotracheal tubes.

12. A method to remove a foreign object comprising:
inflating a toroidal balloon having an internal balloon surface and an external balloon surface;
inserting said toroidal balloon into a tract wherein said external balloon surface contacts a biological wall of said tract;
drawing a foreign object into said internal balloon surface; and

inverting said internal balloon surface and external balloon surface to draw said foreign object internally through said expandable toroidal balloon, said inversion safely guiding the removal of said foreign object without sliding of said external balloon surface against said biological wall.

13. A method to remove a foreign object, as per claim 12, wherein said expandable toroidal balloon has a lubricious coating.

14. A method to remove a foreign object, as per claim 12, wherein said expandable toroidal balloon is coated with a biologically active substance.

15. A method to remove a foreign object, as per claim 12, wherein said biologically active substance is any of, or a combination of, the following: an alpha-blocker or smooth muscle relaxant.

16. A method to remove a foreign object, as per claim 12, wherein said toroidal balloon is attached to a scope.

17. A method to remove a foreign object, as per claim 16, wherein said toroidal balloon is constructed over a tube matching an external configuration of said scope.

18. A method to remove a foreign object, as per claim 16, wherein said toroidal balloon is pre-rolled, attached to an end of said scope, unrolled onto said scope, prior to internally drawing said foreign object.

19. A method to remove a foreign object, as per claim 16, wherein said toroidal balloon is inflated, rolled back over said scope, and deflated prior to internally drawing said foreign object.

20. A method to remove a foreign object, as per claim 12, wherein said toroidal balloon is part of a medical balloon instrument.

21. A method to remove a foreign object, as per claim 12, wherein said balloon is made of any of the following materials: latex rubber, silicone, or elastomer.

22. A method to remove a foreign object, as per claim 12, wherein said foreign object is any of the following: percutaneous stone, bladder stone, urethral stone, tracheal foreign body, rectal foreign body, surgical specimen, or endotracheal tubes.

专利名称(译)	用于从身体提取物体的方法和装置		
公开(公告)号	US20070038227A1	公开(公告)日	2007-02-15
申请号	US11/503617	申请日	2006-08-14
[标]申请(专利权)人(译)	MASSICOTTE缩略词 MASSICOTT PETER J		
申请(专利权)人(译)	MASSICOTTE缩略词 MASSICOTT PETER J		
当前申请(专利权)人(译)	MASSICOTTE缩略词 MASSICOTT PETER J		
[标]发明人	MASSICOTTE J MATHIEU MASSICOTT PETER J		
发明人	MASSICOTTE, J. MATHIEU MASSICOTT, PETER J.		
IPC分类号	A61B17/22 A61F2/958		
CPC分类号	A61B17/22032 A61B17/221 A61B17/3421 A61B2017/3435 A61B17/3431 A61B2017/2212 A61B17/3423		
优先权	60/708124 2005-08-12 US		
其他公开文献	US8343170		
外部链接	Espacenet USPTO		

摘要(译)

一种用于从身体中提取物体的装置，例如尿石，使用低压可充气环形气球，其用于在提取期间吞噬物体同时扩张和保护通道。在插入之前，球囊加载到输尿管镜上，而不是像现有的球囊一样通过输尿管镜。环形气球是一种简单而独特的装置，可以应用在提取望远镜的外部，并且不会干扰现有的石头操纵方法，例如在尿石操纵的情况下进行激光碎石，灌慨和筐提取。

