

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
14 April 2011 (14.04.2011)(10) International Publication Number
WO 2011/044338 A2

(51) International Patent Classification:

A61B 18/12 (2006.01) *B06B 1/02* (2006.01)

(21) International Application Number:

PCT/US2010/051787

(22) International Filing Date:

7 October 2010 (07.10.2010)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/250,217	9 October 2009 (09.10.2009)	US
12/896,384	1 October 2010 (01.10.2010)	US
12/896,470	1 October 2010 (01.10.2010)	US
12/896,479	1 October 2010 (01.10.2010)	US
12/896,451	1 October 2010 (01.10.2010)	US
12/896,360	1 October 2010 (01.10.2010)	US
12/896,467	1 October 2010 (01.10.2010)	US
12/896,345	1 October 2010 (01.10.2010)	US

(71) Applicant (for all designated States except US):

ETHICON ENDO-SURGERY, INC. [US/US]; 4545 Creek Road, Cincinnati, OH 45242 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **WEINER, Eitan, T.** [US/US]; 9519 Croton Drive, Cincinnati, OH 45242 (US). **ALDRIDGE, Jeffrey, L.** [US/US]; 106 W. Concord Drive, Lebanon, OH 45036 (US). **NOYES, Brian, T.** [US/US]; 3719 Wild Cherry Way, Mason, OH 45040(US). **MESSERLY, Jeffrey, D.** [US/US]; 2181 Telegraph Court, Cincinnati, OH 45244 (US). **GIORDANO, James, R.** [US/US]; 5647 Chestnutview Lane, Milford, OH 45150 (US). **BEETEL, Robert, J.** [US/US]; 13438 Skyline Boulevard, Redwood City, CA 94062 (US). **PRICE, Nathan, J.** [US/US]; 11217 N. Trigger Road, Dunlap, IL 61525 (US). **STULEN, Foster, B.** [US/US]; 6245 Bridgewater Court, Mason, OH 45040 (US). **MILLER, Matthew, C.** [US/US]; 3524 Zumstein Avenue, Cincinnati, OH 45040 (US). **WILEY, Jeffrey, P.** [US/US]; 5585 Autumn Wynd Lane, Milford, OH 45150 (US). **PRICE, Daniel, W.** [US/US]; 185 Overlook Drive, Loveland, OH 45140 (US). **KOCH, Robert, L.** [US/US]; 2515 Bymeside Avenue, Cincinnati, OH 45239 (US). **BROTZ, Joseph, A.** [US/US]; 4321 Stoney Ridge Trail, Oshkosh, WI 54904 (US). **HEIN, John, E.** [US/US]; 2185 Willow Hill Drive, Neenah, WI 54956 (US). **VOEGELE, Aaron, C.** [US/US]; 143 Shoemaker Drive, Loveland, OH 45140 (US). **ABBOTT, Daniel, J.** [US/US]; 5944 Marsh Circle, Loveland, OH 45140 (US). **KILLINGER, Scott, B.** [US/US]; 3671 Nantucket Drive, Loveland, OH 45140 (US). **DAVISON, Mark, A.** [US/US]; 5791 Grazing Court, Mason, OH 45040 (US). **YATES, David, C.** [US/US]; 7534 Galway Court, West Chester, OH 45069 (US). **MONSON, Gavin, M.** [US/US]; 5966 Reily Millville Road, Oxford, OH 45056 (US).

[Continued on next page]

(54) Title: SURGICAL GENERATOR FOR ULTRASONIC AND ELECTROSURGICAL DEVICES




FIG. 1

(57) Abstract: A surgical generator that may produce a drive signal or signals of particular voltages, currents, and frequencies, e.g. 55,500 cycles per second (Hz). The drive signal or signals may be provided to an ultrasonic surgical device, and specifically to a transducer. In one embodiment, the generator may be configured to produce a drive signal of a particular voltage, current, and/or frequency output signal that can be stepped with high resolution, accuracy, and repeatability. Additionally, the surgical generator may generate a drive signal or signals with output power sufficient to perform bipolar electrosurgery using radio frequency (RF) energy. The drive signal may be provided, for example, to electrodes of the electrosurgical device. Accordingly, the generator may be configured for therapeutic purposes by applying electrical signals to an ultrasonic transducer or electrical energy to the tissue sufficient for treating the tissue (e.g., cutting, coagulation, cauterization, tissue welding, etc.).



(74) **Agents:** JOHNSON, Philip, S. et al.; Johnson & Johnson, One Johnson & Johnson Plaza, New Brunswick, NJ 08933 (US).

(81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ,

TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to the identity of the inventor (Rule 4.17(i))
- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))

Published:

- without international search report and to be republished upon receipt of that report (Rule 48.2(g))

SURGICAL GENERATOR FOR ULTRASONIC AND ELECTROSURGICAL DEVICES

CROSS REFERENCE TO RELATED APPLICATION

[0001] This application claims the benefit under Title 35, United States Code § 119(e), of U.S. Provisional Patent Application Ser. No. 61/250,217, filed October 9, 2009 and entitled A DUAL BIPOLAR AND ULTRASONIC GENERATOR FOR ELECTRO-SURGICAL INSTRUMENTS, which is hereby incorporated by reference in its entirety.

[0002] The present application is related to the following, concurrently-filed U.S. Patent Applications, which are incorporated herein by reference in their entirety:

(1) U.S. Patent Application Serial No.12/896,351 entitled DEVICES AND TECHNIQUES FOR CUTTING AND COAGULATING TISSUE, Attorney Docket No. END6427USCIP1/080591CIP;

(2) U.S. Patent Application Serial No.12/896,360 entitled SURGICAL GENERATOR FOR ULTRASONIC AND ELECTROSURGICAL DEVICES, Attorney Docket No. END6673USNP/100558

(3) U.S. Patent Application Serial No.12/896,479 entitled SURGICAL GENERATOR FOR ULTRASONIC AND ELECTROSURGICAL DEVICES, Attorney Docket No. END6673USNP1/100557;

(4) U.S. Patent Application Serial No.12/869,345, entitled SURGICAL GENERATOR FOR ULTRASONIC AND ELECTROSURGICAL DEVICES, Attorney Docket No. END6673USNP2/100559;

(5) U.S. Patent Application Serial No.12/896,384 entitled SURGICAL GENERATOR FOR ULTRASONIC AND ELECTROSURGICAL DEVICES, Attorney Docket No. END6673USNP3/100560;

(6) U.S. Patent Application Serial No.12/896,467, entitled SURGICAL GENERATOR FOR ULTRASONIC AND ELECTROSURGICAL DEVICES, Attorney Docket No. END6673USNP4/100562;

(7) U.S. Patent Application Serial No.12/896,451 entitled SURGICAL GENERATOR FOR ULTRASONIC AND ELECTROSURGICAL DEVICES, Attorney Docket No. END6673USNP5/100563; and

(8) U.S. Patent Application Serial No.12/896,470 entitled SURGICAL GENERATOR FOR ULTRASONIC AND ELECTROSURGICAL DEVICES, Attorney Docket No. END6673USNP6/100564.

BACKGROUND

[0003] Various embodiments are directed to surgical devices, and generators for supplying energy to surgical devices, for use in open or minimally invasive surgical environments.

[0004] Ultrasonic surgical devices, such as ultrasonic scalpels, are finding increasingly widespread applications in surgical procedures by virtue of their unique performance characteristics. Depending upon specific device configurations and operational parameters, ultrasonic surgical devices can provide substantially simultaneous transection of tissue and homeostasis by coagulation, desirably minimizing patient trauma. An ultrasonic surgical device may comprise a handpiece containing an ultrasonic transducer, and an instrument coupled to the ultrasonic transducer having a distally-mounted end effector (e.g., a blade tip) to cut and seal tissue. In some cases, the instrument may be permanently affixed to the handpiece. In other cases, the instrument may be detachable from the handpiece, as in the case of a disposable instrument or an instrument that is interchangeable between different handpieces. The end effector transmits ultrasonic energy to tissue brought into contact with the end effector to realize cutting and sealing action. Ultrasonic surgical devices of this nature can be configured for open surgical use, laparoscopic, or endoscopic surgical procedures including robotic-assisted procedures.

[0005] Ultrasonic energy cuts and coagulates tissue using temperatures lower than those used in electrosurgical procedures and can be transmitted to the end effector by an ultrasonic generator in communication with the handpiece. Vibrating at high frequencies (e.g., 55,500 times per second), the ultrasonic blade denatures protein in the tissue to form a sticky coagulum. Pressure exerted on tissue by the blade surface collapses blood vessels and allows the coagulum to form a haemostatic seal. A surgeon can control the cutting speed and coagulation by the force applied to the tissue by the end effector, the time over which the force is applied and the selected excursion level of the end effector.

[0006] The ultrasonic transducer may be modeled as an equivalent circuit comprising first branch having a static capacitance and a second "motional" branch having a serially connected inductance, resistance and capacitance that define the electromechanical properties of a resonator. Known ultrasonic generators may include a tuning inductor for tuning out the static capacitance at a resonant frequency so that substantially all of generator's drive signal current flows into the motional branch. Accordingly, by using a tuning inductor, the generator's

drive signal current represents the motional branch current, and the generator is thus able to control its drive signal to maintain the ultrasonic transducer's resonant frequency. The tuning inductor may also transform the phase impedance plot of the ultrasonic transducer to improve the generator's frequency lock capabilities. However, the tuning inductor must be matched with the specific static capacitance of an ultrasonic transducer at the operational resonance frequency. In other words, a different ultrasonic transducer having a different static capacitance requires a different tuning inductor.

[0007] Additionally, in some ultrasonic generator architectures, the generator's drive signal exhibits asymmetrical harmonic distortion that complicates impedance magnitude and phase measurements. For example, the accuracy of impedance phase measurements may be reduced due to harmonic distortion in the current and voltage signals.

[0008] Moreover, electromagnetic interference in noisy environments decreases the ability of the generator to maintain lock on the ultrasonic transducer's resonant frequency, increasing the likelihood of invalid control algorithm inputs.

[0009] Electrosurgical devices for applying electrical energy to tissue in order to treat and/or destroy the tissue are also finding increasingly widespread applications in surgical procedures. An electrosurgical device may comprise a handpiece and an instrument having a distally-mounted end effector (e.g., one or more electrodes). The end effector can be positioned against the tissue such that electrical current is introduced into the tissue. Electrosurgical devices can be configured for bipolar or monopolar operation. During bipolar operation, current is introduced into and returned from the tissue by active and return electrodes, respectively, of the end effector. During monopolar operation, current is introduced into the tissue by an active electrode of the end effector and returned through a return electrode (e.g., a grounding pad) separately located on a patient's body. Heat generated by the current flow through the tissue may form haemostatic seals within the tissue and/or between tissues and thus may be particularly useful for sealing blood vessels, for example. The end effector of an electrosurgical device may also comprise a cutting member that is movable relative to the tissue and the electrodes to transect the tissue.

[0010] Electrical energy applied by an electrosurgical device can be transmitted to the instrument by a generator in communication with the handpiece. The electrical energy may be in the form of radio frequency ("RF") energy. RF energy is a form of electrical energy that may be in the frequency range of 300 kHz to 1 MHz. During its operation, an electrosurgical device can transmit low frequency RF energy through tissue, which causes ionic agitation, or friction, in effect resistive heating, thereby increasing the temperature of the tissue. Because a sharp

boundary may be created between the affected tissue and the surrounding tissue, surgeons can operate with a high level of precision and control, without sacrificing un-targeted adjacent tissue. The low operating temperatures of RF energy may be useful for removing, shrinking, or sculpting soft tissue while simultaneously sealing blood vessels. RF energy may work particularly well on connective tissue, which is primarily comprised of collagen and shrinks when contacted by heat.

[0011] Due to their unique drive signal, sensing and feedback needs, ultrasonic and electrosurgical devices have generally required different generators. Additionally, in cases where the instrument is disposable or interchangeable with a handpiece, ultrasonic and electrosurgical generators are limited in their ability to recognize the particular instrument configuration being used and to optimize control and diagnostic processes accordingly. Moreover, capacitive coupling between the non-isolated and patient-isolated circuits of the generator, especially in cases where higher voltages and frequencies are used, may result in exposure of a patient to unacceptable levels of leakage current.

SUMMARY

[0012] Various embodiments of a generator to communicate a drive signal to a surgical device are disclosed. In one embodiment, the generator may comprise a power amplifier to receive a time-varying drive signal waveform. The drive signal waveform may be generated by a digital-to-analog conversion of at least a portion of a plurality of drive signal waveform samples. An output of the power amplifier may be for generating a drive signal. The drive signal may comprise one of: a first drive signal to be communicated to an ultrasonic surgical device, a second drive signal to be communicated to an electrosurgical device. The generator may also comprise a sampling circuit to generate samples of current and voltage of the drive signal when the drive signal is communicated to the surgical device. Generation of the samples may be synchronized with the digital-to-analog conversion of the drive signal waveform samples such that, for each digital-to-analog conversion of a drive signal waveform sample, the sampling circuit generates a corresponding set of current and voltage samples. The generator may also comprise at least one device programmed to, for each drive signal waveform sample and corresponding set of current and voltage samples, store the current and voltage samples in a memory of the at least one device to associate the stored samples with the drive signal waveform sample. The at least one device may also be programmed to, when the drive signal comprises the first drive signal: determine a motional branch current sample of the ultrasonic surgical device based on the stored current and voltage samples, compare the motional branch

current sample to a target sample selected from a plurality of target samples that define a target waveform, the target sample selected based on the drive signal waveform sample, determine an amplitude error between the target sample and the motional branch current sample, and modify the drive signal waveform sample such that an amplitude error determined between the target sample and a subsequent motional branch current sample based on current and voltage samples associated with the modified drive signal waveform sample is reduced.

[0013] In one embodiment, the generator may comprise a memory and a device coupled to the memory to receive for each of a plurality of drive signal waveform samples used to synthesize the drive signal, a corresponding set of current and voltage samples of the drive signal. For each drive signal waveform sample and corresponding set of current and voltage samples, the device may store the samples in a memory of the device to associate the stored samples with the drive signal waveform sample. Also, for each drive signal waveform sample and corresponding set of current and voltage samples, the device may, when the drive signal comprises a first drive signal to be communicated to an ultrasonic surgical device, determine a motional branch current sample of the ultrasonic surgical device based on the stored samples, compare the motional branch current sample to a target sample selected from a plurality of target samples that define a target waveform, the target sample selected based on the drive signal waveform sample, determine an amplitude error between the target sample and the motional branch current sample, and modify the drive signal waveform sample such that an amplitude error determined between the target sample and a subsequent motional branch current sample based on current and voltage samples associated with the modified drive signal waveform sample is reduced.

[0014] Embodiments of a method for determining motional branch current in an ultrasonic transducer of an ultrasonic surgical device over multiple frequencies of a transducer drive signal are also disclosed. In one embodiment, the method may comprise, at each of a plurality of frequencies of the transducer drive signal, oversampling a current and voltage of the transducer drive signal, receiving, by a processor, the current and voltage samples, and determining, by the processor, the motional branch current based on the current and voltage samples, a static capacitance of the ultrasonic transducer and the frequency of the transducer drive signal.

[0015] Embodiments of a method for controlling a waveform shape of a motional branch current in an ultrasonic transducer of a surgical device are also disclosed. In one embodiment, the method may comprise generating a transducer drive signal by selectively recalling, using a direct digital synthesis (DDS) algorithm, drive signal waveform samples stored in a look-up table

(LUT), generating samples of current and voltage of the transducer drive signal when the transducer drive signal is communicated to the surgical device, determining samples of the motional branch current based on the current and voltage samples, a static capacitance of the ultrasonic transducer and a frequency of the transducer drive signal, comparing each sample of the motional branch current to a respective target sample of a target waveform to determine an error amplitude, and modifying the drive signal waveform samples stored in the LUT such that an amplitude error between subsequent samples of the motional branch current and respective target samples is reduced.

[0016] In accordance with various embodiments, a surgical generator for providing a drive signal to a surgical device may comprise a first transformer and a second transformer. The first transformer may comprise a first primary winding and a first secondary winding. The second transformer may comprise a second primary winding and a second secondary winding. The surgical generator may further comprise a generator circuit to generate the drive signal. The generator circuit may be electrically coupled to the first primary winding to provide the drive signal across the first primary winding. The surgical generator may also comprise a patient-side circuit electrically isolated from the generator circuit. The patient-side circuit may be electrically coupled to the first secondary winding. Further, the patient-side circuit may comprise first and second output lines to provide the drive signal to the surgical device. In addition, the surgical generator may comprise a capacitor. The capacitor and the second secondary winding may be electrically coupled in series between the first output line and ground.

[0017] Also, in accordance with various embodiments, a surgical generator for providing a drive signal to a surgical device may comprise a first transformer, a patient-side circuit, and a capacitor. The first transformer may comprise a primary winding, a first secondary winding, and a second secondary winding. A polarity of the first secondary winding relative to the primary winding may be opposite the polarity of the second secondary winding. The generator circuit may generate the drive signal and may be electrically coupled to the first primary winding to provide the drive signal across the first primary winding. The patient-side circuit may be electrically isolated from the generator circuit and may be electrically coupled to the first secondary winding. Also, the patient-side circuit may comprise first and second output lines to provide the drive signal to the surgical device. The capacitor and second secondary winding may be electrically coupled in series between the first output line and ground.

[0018] Additionally, in accordance with various embodiments, a surgical generator for providing a drive signal to a surgical device may comprise, a first transformer, a generator circuit, a patient-side circuit and a capacitor. The first transformer may comprise a primary

winding and a secondary winding. The generator circuit may generate the drive signal and may be electrically coupled to the first primary winding to provide the drive signal across the first primary winding. The patient-side circuit may be electrically isolated from the generator circuit and may be electrically coupled to the secondary winding. Further, the patient-side circuit may comprise first and second output lines to provide the drive signal to the surgical device. The capacitor may be electrically coupled to the primary winding and to the first output line.

[0019] In accordance with various embodiments, a surgical generator for providing a drive signal to a surgical device may comprise a first transformer, a generator circuit, a patient-side circuit, as well as first, second and third capacitors. The first transformer may comprise a primary winding and a secondary winding. The generator circuit may generate the drive signal and may be electrically coupled to the first primary winding to provide the drive signal across the first primary winding. The patient-side circuit may be electrically isolated from the generator circuit and may be electrically coupled to the secondary winding. Further, the patient-side circuit may comprise first and second output lines to provide the drive signal to the surgical device. A first electrode of the first capacitor may be electrically coupled to the primary winding. A first electrode of the second capacitor may be electrically coupled to the first output line and a second electrode of the second capacitor may be electrically coupled to a second electrode of the first capacitor. A first electrode of the third capacitor may be electrically coupled to the second electrode of the first capacitor and the second electrode of the second capacitor. A second electrode of the third capacitor may be electrically coupled to ground.

[0020] Various embodiments of surgical device control circuits are also disclosed. In one embodiment, the control circuit may comprise a first circuit portion comprising at least one first switch. The first circuit portion may communicate with a surgical generator over a conductor pair. The control circuit may also comprise a second circuit portion comprising a data circuit element. The data circuit element may be disposed in an instrument of the surgical device and transmit or receive data. The data circuit element may implement data communications with the surgical generator over at least one conductor of the conductor pair.

[0021] In one embodiment, the control circuit may comprise a first circuit portion comprising at least one first switch. The first circuit portion may communicate with a surgical generator over a conductor pair. The control circuit may also comprise a second circuit portion comprising a data circuit element. The data circuit element may be disposed in an instrument of the surgical device and transmit or receive data. The data circuit element may implement data communications with the surgical generator over at least one conductor of the conductor pair. The first circuit portion may receive a first interrogation signal transmitted from the surgical

generator in a first frequency band. The data circuit element may communicate with the surgical generator using an amplitude-modulated communication protocol transmitted in a second frequency band. The second frequency band may be higher than the first frequency band.

[0022] In one embodiment, the control circuit may comprise a first circuit portion comprising at least one first switch. The first circuit portion may receive a first interrogation signal transmitted from a surgical generator over a conductor pair. The control circuit may also comprise a second circuit portion comprising at least one of a resistive element and an inductive element disposed in an instrument of the device. The second circuit portion may receive a second interrogation signal transmitted from the surgical generator over the conductor pair. The second circuit portion may be frequency-band separated from the first circuit portion. A characteristic of the first interrogation signal, when received through the first circuit portion, may be indicative of a state of the at least one first switch. A characteristic of the second interrogation signal, when received through the second circuit portion, may uniquely identify the instrument of the device.

[0023] In one embodiment, the control circuit may comprise a first circuit portion comprising a first switch network and a second switch network. The first switch network may comprise at least one first switch, and the second switch network may comprise at least one second switch. The first circuit portion may communicate with a surgical generator over a conductor pair. The control circuit may also comprise a second circuit portion comprising a data circuit element. The data circuit element may be disposed in an instrument of the surgical device and may transmit or receive data. The data circuit element may be in data communication with the surgical generator over at least one conductor of the conductor pair.

[0024] In accordance with various embodiments, a surgical generator for providing a drive signal to a surgical device may comprise a surgical generator body having an aperture. The surgical generator may also comprise a receptacle assembly positioned in the aperture. The receptacle assembly may comprise a receptacle body and a flange having an inner wall and an outer wall. The inner wall may be comprised of at least one curved section and at least one linear section. The inner wall may define a cavity. A central protruding portion may be positioned in the cavity and may comprise a plurality of sockets and a magnet. An outer periphery of the central protruding portion may comprise at least one curved section and at least one linear section.

[0025] In accordance with various embodiments, a surgical instrument may comprises an electrical connector assembly. The electrical connector assembly may comprise a flange

defining a central cavity and a magnetically compatible pin extending into the central cavity. The electrical connector assembly may comprise a circuit board and a plurality of electrically conductive pins coupled to the circuit board. Each of the plurality of electrically conductive pins may extend into the central cavity. The electrical connector assembly may further comprise a strain relief member and a boot.

[0026] In accordance with various embodiments, a surgical instrument system may comprise a surgical generator comprising a receptacle assembly. The receptacle assembly may comprise at least one curved section and at least one linear portion. The surgical instrument system may comprise a surgical instrument comprising a connector assembly and an adapter assembly operatively coupled to the receptacle assembly and the connector assembly. The adapter assembly may comprise a distal portion contacting the receptacle assembly. The distal portion may comprise a flange with the flange having at least one curved section and at least one linear portion. The adapter assembly may comprise a proximal portion contacting the connector assembly. The proximal portion may define a cavity dimensioned to receive at least a portion of the connector assembly. The adapter assembly may further comprise a circuit board.

[0027] In accordance with various embodiments, methods may be utilized (e.g., in conjunction with surgical instruments) to accomplish various surgical objectives. For example, methods to control electrical power provided to tissue via first and second electrodes may comprise providing a drive signal to the tissue via the first and second electrodes and modulating a power provided to the tissue via the drive signal based on a sensed tissue impedance according to a first power curve. The first power curve may define, for each of a plurality of potential sensed tissue impedances, a first corresponding power. The methods may also comprise monitoring a total energy provided to the tissue via the first and second electrodes. When the total energy reaches a first energy threshold, the methods may comprise determining whether an impedance of the tissue has reached a first impedance threshold. The methods may further comprise, conditioned upon the impedance of the tissue failing to reach the first impedance threshold, modulating the power provided to the tissue via the drive signal based on the sensed tissue impedance according to a second power curve. The second power curve may define, for each of the plurality of potential sensed tissue impedances, a second corresponding power.

[0028] In accordance with various embodiments, methods for controlling electrical power provided to tissue via first and second electrodes may comprise providing a drive signal to the tissue via the first and second electrodes and determining a power to be provided to the

tissue. The determining may comprise receiving an indication of a sensed tissue impedance; determining a first corresponding power for the sensed tissue impedance according to a power curve; and multiplying the corresponding power by a multiplier. The power curve may define a corresponding power for each of a plurality of potential sensed tissue impedances. The methods may further comprise modulating the drive signal to provide the determined power to the tissue and, conditioned upon the impedance of the tissue failing to reach a first impedance threshold, increasing the multiplier as a function of the total energy provided to the tissue.

[0029] In accordance with various embodiments, methods for controlling electrical power provided to tissue via first and second electrodes may comprise providing a drive signal to the tissue via the first and second electrodes and determining a power to be provided to the tissue. The determining may comprise receiving an indication of a sensed tissue impedance; determining a first corresponding power for the sensed tissue impedance according to a power curve; and multiplying the corresponding power by a first multiplier to find a determined power. The power curve may define a corresponding power for each of a plurality of potential sensed tissue impedances. The methods may further comprise modulating the drive signal to provide the determined power to the tissue and monitoring a total energy provided to the tissue via the first and second electrodes. In addition, the methods may comprise, when the total energy reaches a first energy threshold, determining whether the impedance of the tissue has reached a first impedance threshold; and, conditioned upon the impedance of the tissue not reaching the first impedance threshold, increasing the first multiplier by a first amount.

[0030] In accordance with various embodiments, methods for controlling electrical power provided to tissue via a surgical device may comprise providing a drive signal to a surgical device; receiving an indication of an impedance of the tissue; calculating a rate of increase of the impedance of the tissue; and modulating the drive signal to hold the rate of increase of the impedance greater than or equal to a predetermined constant.

[0031] In accordance with various embodiments, methods for controlling electrical power provided to tissue via a surgical device may comprise providing a drive signal. A power of the drive signal may be proportional to a power provided to the tissue via the surgical device. The methods may also comprise periodically receiving indications of an impedance of the tissue and applying a first composite power curve to the tissue, wherein applying the first composite power curve to the tissue comprises. Applying the first composite power curve to the tissue may comprise modulating a first predetermined number of first composite power curve pulses on the drive signal; and for each of the first composite power curve pulses, determining a pulse power and a pulse width according to a first function of the impedance of the tissue. The

methods may also comprise applying a second composite power curve to the tissue. Applying the second composite power curve to the tissue may comprise modulating at least one second composite power curve pulse on the drive signal; and for each of the at least one second composite power curve pulses, determining a pulse power and a pulse width according to a second function of the impedance of the tissue.

FIGURES

[0032] The novel features of the various embodiments are set forth with particularity in the appended claims. The described embodiments, however, both as to organization and methods of operation, may be best understood by reference to the following description, taken in conjunction with the accompanying drawings in which:

[0033] Figure 1 illustrates one embodiment of a surgical system comprising a generator and various surgical instruments usable therewith;

[0034] Figure 2 illustrates one embodiment of an example ultrasonic device that may be used for transection and/or sealing;

[0035] Figure 3 illustrates one embodiment of the end effector of the example ultrasonic device of Figure 2.

[0036] Figure 4 illustrates one embodiment of an example electrosurgical device that may also be used for transection and sealing;

[0037] Figures 5, 6 and 7 illustrate one embodiment of the end effector shown in Figure 4;

[0038] Figure 8 is a diagram of the surgical system of Figure 1;

[0039] Figure 9 is a model illustrating motional branch current in one embodiment;

[0040] Figure 10 is a structural view of a generator architecture in one embodiment;

[0041] Figures 11A-11C are functional views of a generator architecture in one embodiment;

[0042] Figure 12 illustrates a controller for monitoring input devices and controlling output devices in one embodiment;

[0043] Figure 13 illustrates structural and functional aspects of one embodiment of the generator;

[0044] Figures 14-32 and 33A-33C illustrate embodiments of control circuits;

[0045] Figure 33D-33I illustrate embodiments of cabling and adaptor configurations for connecting various generators and various surgical instruments;

[0046] Figure 34 illustrates one embodiment of a circuit 300 for active cancellation of leakage current.

[0047] Figure 35 illustrates one embodiment of a circuit that may be implemented by the generator of Figure 1 to provide active cancellation of leakage current;

[0048] Figure 36 illustrates an alternative embodiment of a circuit that may be implemented by the generator of Figure 1 to provide active cancellation of leakage current;

[0049] Figure 37 illustrates an alternative embodiment of a circuit that may be implemented by the generator of Figure 1 to provide active cancellation of leakage current;

[0050] Figure 38 illustrates yet another embodiment of a circuit that may be implemented by the generator of Figure 1 to provide active cancellation of leakage current;

[0051] Figure 39 illustrates an embodiment of a circuit that may be implemented by the generator of Figure 1 to provide cancellation of leakage current;

[0052] Figure 40 illustrates another embodiment of a circuit that may be implemented by the generator of Figure 1 to provide cancellation of leakage current;

[0053] Figure 41 illustrates a receptacle and connector interface in one embodiment;

[0054] Figure 42 is an exploded side view of the receptacle assembly in one embodiment;

[0055] Figure 43 is an exploded side view of the connector assembly in one embodiment;

[0056] Figure 44 is a perspective view of the receptacle assembly shown in Figure 41;

[0057] Figure 45 is a exploded perspective view of the receptacle assembly in one embodiment;

[0058] Figure 46 is a front elevation view of the receptacle assembly in one embodiment;

[0059] Figure 47 is a side elevation view of the receptacle assembly in one embodiment;

[0060] Figure 48 is an enlarged view of a socket in one embodiment;

[0061] Figure 49 is a perspective view of the connector assembly in one embodiment;

[0062] Figure 50 is an exploded perspective view of the connector assembly in one embodiment;

[0063] Figure 51 is a side elevation view of a connector body in one embodiment;

[0064] Figure 52 is perspective view of the distal end of a connector body in one embodiment;

[0065] Figure 53 is perspective view of the proximal end of a connector body in one embodiment;

- [0066]** Figure 54 illustrates a ferrous pin in one embodiment;
- [0067]** Figure 55 illustrates electrically conductive pins and a circuit board in one embodiment;
- [0068]** Figure 56 illustrates a strain relief member in one embodiment;
- [0069]** Figure 57 illustrates a boot in one embodiment;
- [0070]** Figure 58 illustrates two adaptor assemblies in accordance with various non-limiting embodiments;
- [0071]** Figure 59 illustrates a surgical generator in one embodiment;
- [0072]** Figure 60 illustrates a connector assembly connected to an adaptor assembly in one embodiment;
- [0073]** Figure 61 illustrates an adaptor assembly inserted into a receptacle assembly of a surgical generator in one embodiment;
- [0074]** Figure 62 illustrates a connector assembly connected to an adaptor assembly in one embodiment;
- [0075]** Figure 63 illustrates a perspective view of a back panel of a generator in one embodiment;
- [0076]** Figure 64 illustrates a back panel of a generator in one embodiment;
- [0077]** Figures 65 and 66 illustrate different portions of a back panel of a generator in one embodiment;
- [0078]** Figure 67 illustrates a neural network for controlling a generator in one embodiment;
- [0079]** Figure 68 illustrates measured temperature versus estimated temperature output by a surgical instrument controlled by a generator in one embodiment;
- [0080]** Figure 69 illustrates one embodiment of a chart showing example power curves;
- [0081]** Figure 70 illustrates one embodiment of a process flow for applying one or more power curves to a tissue bite;
- [0082]** Figure 71 illustrates one embodiment of a chart showing example power curves that may be used in conjunction with the process flow of Figure 70;
- [0083]** Figure 72 illustrates one embodiment of a chart showing example common shape power curves that may be used in conjunction with the process flow of Figure 70;
- [0084]** Figure 73A illustrates one embodiment of a routine that may be performed by a digital device of the generator of Figure 1 to act upon a new tissue bite;
- [0085]** Figure 73B illustrates one embodiment of a routine that may be performed by a digital device of the generator of Figure 1 to monitor tissue impedance;

[0086] Figure 73C illustrates one embodiment of a routine that may be performed by a digital device of the generator of Figure 1 to provide one or more power curves to a tissue bite;

[0087] Figure 74 illustrates one embodiment of a process flow for applying one or more power curves to a tissue bite;

[0088] Figure 75 illustrates one embodiment of a block diagram describing the selection and application of composite load curves by the generator of Figure 1;

[0089] Figure 76 illustrates shows a process flow illustrating one embodiment of the algorithm of Figure 75, as implemented by the generator of Figure 1;

[0090] Figure 77 illustrates one embodiment of a process flow for generating a first composite load curve pulse;

[0091] Figure 78 illustrates one embodiment of a pulse timing diagram illustrating an example application of the algorithm of Figure 76 by the generator of Figure 1;

[0092] Figure 79 illustrates a graphical representation of drive signal voltage, current and power according to an example composite load curve;

[0093] Figures 80-85 illustrate a graphical representations of example composite load curves; and

[0094] Figure 86 illustrates one embodiment of a block diagram describing the application of an algorithm for maintaining a constant tissue impedance rate of change.

DESCRIPTION

[0095] Before explaining various embodiments of surgical devices and generators in detail, it should be noted that the illustrative embodiments are not limited in application or use to the details of construction and arrangement of parts illustrated in the accompanying drawings and description. The illustrative embodiments may be implemented or incorporated in other embodiments, variations and modifications, and may be practiced or carried out in various ways. Further, unless otherwise indicated, the terms and expressions employed herein have been chosen for the purpose of describing the illustrative embodiments for the convenience of the reader and are not for the purpose of limitation thereof. Also, it will be appreciated that one or more of the following-described embodiments, expressions of embodiments and/or examples, can be combined with any one or more of the other following-described embodiments, expressions of embodiments and/or examples.

[0096] Various embodiments are directed to improved ultrasonic surgical devices, electrosurgical devices and generators for use therewith. Embodiments of the ultrasonic surgical devices can be configured for transecting and/or coagulating tissue during surgical

procedures, for example. Embodiments of the electrosurgical devices can be configured for transecting, coagulating, scaling, welding and/or desiccating tissue during surgical procedures, for example.

[0097] Embodiments of the generator utilize high-speed analog-to-digital sampling (e.g., approximately 200x oversampling, depending on frequency) of the generator drive signal current and voltage, along with digital signal processing, to provide a number of advantages and benefits over known generator architectures. In one embodiment, for example, based on current and voltage feedback data, a value of the ultrasonic transducer static capacitance, and a value of the drive signal frequency, the generator may determine the motional branch current of an ultrasonic transducer. This provides the benefit of a virtually tuned system, and simulates the presence of a system that is tuned or resonant with any value of the static capacitance (e.g., C_0 in Figure 9) at any frequency. Accordingly, control of the motional branch current may be realized by tuning out the effects of the static capacitance without the need for a tuning inductor. Additionally, the elimination of the tuning inductor may not degrade the generator's frequency lock capabilities, as frequency lock can be realized by suitably processing the current and voltage feedback data.

[0098] High-speed analog-to-digital sampling of the generator drive signal current and voltage, along with digital signal processing, may also enable precise digital filtering of the samples. For example, embodiments of the generator may utilize a low-pass digital filter (e.g., a finite impulse response (FIR) filter) that rolls off between a fundamental drive signal frequency and a second-order harmonic to reduce the asymmetrical harmonic distortion and EMI-induced noise in current and voltage feedback samples. The filtered current and voltage feedback samples represent substantially the fundamental drive signal frequency, thus enabling a more accurate impedance phase measurement with respect to the fundamental drive signal frequency and an improvement in the generator's ability to maintain resonant frequency lock. The accuracy of the impedance phase measurement may be further enhanced by averaging falling edge and rising edge phase measurements, and by regulating the measured impedance phase to 0°.

[0099] Various embodiments of the generator may also utilize the high-speed analog-to-digital sampling of the generator drive signal current and voltage, along with digital signal processing, to determine real power consumption and other quantities with a high degree of precision. This may allow the generator to implement a number of useful algorithms, such as, for example, controlling the amount of power delivered to tissue as the impedance of the tissue

changes and controlling the power delivery to maintain a constant rate of tissue impedance increase.

[00100] Various embodiments of the generator may have a wide frequency range and increased output power necessary to drive both ultrasonic surgical devices and electrosurgical devices. The lower voltage, higher current demand of electrosurgical devices may be met by a dedicated tap on a wideband power transformer, thereby eliminating the need for a separate power amplifier and output transformer. Moreover, sensing and feedback circuits of the generator may support a large dynamic range that addresses the needs of both ultrasonic and electrosurgical applications with minimal distortion.

[00101] Various embodiments may provide a simple, economical means for the generator to read from, and optionally write to, data circuit (e.g., a single-wire bus device, such as a 1-wire® protocol EEPROM) disposed in an instrument attached to the handpiece using existing multi-conductor generator/handpiece cables. In this way, the generator is able to retrieve and process instrument-specific data from an instrument attached to the handpiece. This may enable the generator to provide better control and improved diagnostics and error detection. Additionally, the ability of the generator to write data to the instrument makes possible new functionality in terms of, for example, tracking instrument usage and capturing operational data. Moreover, the use of frequency band permits the backward compatibility of instruments containing a bus device with existing generators.

[00102] Disclosed embodiments of the generator provide active cancellation of leakage current caused by unintended capacitive coupling between non-isolated and patient-isolated circuits of the generator. In addition to reducing patient risk, the reduction of leakage current may also lessen electromagnetic emissions.

[00103] These and other benefits of embodiments of the present invention will be apparent from the description to follow.

[00104] It will be appreciated that the terms “proximal” and “distal” are used herein with reference to a clinician gripping a handpiece. Thus, an end effector is distal with respect to the more proximal handpiece. It will be further appreciated that, for convenience and clarity, spatial terms such as “top” and “bottom” may also be used herein with respect to the clinician gripping the handpiece. However, surgical devices are used in many orientations and positions, and these terms are not intended to be limiting and absolute.

[00105] Figure 1 illustrates one embodiment of a surgical system 100 comprising a generator 102 configurable for use with surgical devices. According to various embodiments, the generator 102 may be configurable for use with surgical devices of different types, including,

for example, the ultrasonic surgical device 104 and electrosurgical or RF surgical device 106. Although in the embodiment of Figure 1 the generator 102 is shown separate from the surgical devices 104, 106, in certain embodiments the generator 102 may be formed integrally with either of the surgical devices 104, 106 to form a unitary surgical system.

[00106] Figure 2 illustrates one embodiment of an example ultrasonic device 104 that may be used for transection and/or sealing. The device 104 may comprise a hand piece 116 which may, in turn, comprise an ultrasonic transducer 114. The transducer 114 may be in electrical communication with the generator 102, for example, via a cable 122 (e.g., a multi-conductor cable). The transducer 114 may comprise piezoceramic elements, or other elements or components suitable for converting the electrical energy of a drive signal into mechanical vibrations. When activated by the generator 102, the ultrasonic transducer 114 may cause longitudinal vibration. The vibration may be transmitted through an instrument portion 124 of the device 104 (e.g., via a waveguide embedded in an outer sheath) to an end effector 126 of the instrument portion 124.

[00107] Figure 3 illustrates one embodiment of the end effector 126 of the example ultrasonic device 104. The end effector 126 may comprise a blade 151 that may be coupled to the ultrasonic transducer 114 via the wave guide (not shown). When driven by the transducer 114, the blade 151 may vibrate and, when brought into contact with tissue, may cut and/or coagulate the tissue, as described herein. According to various embodiments, and as illustrated in Figure 3, the end effector 126 may also comprise a clamp arm 155 that may be configured for cooperative action with the blade 151 of the end effector 126. With the blade 151, the clamp arm 155 may comprise a set of jaws 140. The clamp arm 155 may be pivotally connected at a distal end of a shaft 153 of the instrument portion 124. The clamp arm 155 may include a clamp arm tissue pad 163, which may be formed from TEFLON® or other suitable low-friction material. The pad 163 may be mounted for cooperation with the blade 151, with pivotal movement of the clamp arm 155 positioning the clamp pad 163 in substantially parallel relationship to, and in contact with, the blade 151. By this construction, a tissue bite to be clamped may be grasped between the tissue pad 163 and the blade 151. The tissue pad 163 may be provided with a sawtooth-like configuration including a plurality of axially spaced, proximally extending gripping teeth 161 to enhance the gripping of tissue in cooperation with the blade 151. The clamp arm 155 may transition from the open position shown in Figure 3 to a closed position (with the clamp arm 155 in contact with or proximity to the blade 151) in any suitable manner. For example, the hand piece 116 may comprise a jaw closure trigger 138. When actuated by a clinician, the jaw closure trigger 138 may pivot the clamp arm 155 in any suitable manner.

[00108] The generator 102 may be activated to provide the drive signal to the transducer 114 in any suitable manner. For example, the generator 102 may comprise a foot switch 120 coupled to the generator 102 via a footswitch cable 122 (Figure 8). A clinician may activate the transducer 114, and thereby the transducer 114 and blade 151, by depressing the foot switch 120. In addition, or instead of the foot switch 120 some embodiments of the device 104 may utilize one or more switches positioned on the hand piece 116 that, when activated, may cause the generator 102 to activate the transducer 114. In one embodiment, for example, the one or more switches may comprise a pair of toggle buttons 136a, 136b, for example, to determine an operating mode of the device 104. When the toggle button 136a is depressed, for example, the ultrasonic generator 102 may provide a maximum drive signal to the transducer 114, causing it to produce maximum ultrasonic energy output. Depressing toggle button 136b may cause the ultrasonic generator 102 to provide a user-selectable drive signal to the transducer 114, causing it to produce less than the maximum ultrasonic energy output. The device 104 additionally or alternatively may comprise a second switch to, for example, indicate a position of a jaw closure trigger 138 for operating jaws 140 of the end effector 126. Also, in some embodiments, the ultrasonic generator 102 may be activated based on the position of the jaw closure trigger 138, (e.g., as the clinician depresses the jaw closure trigger 138 to close the jaws 140, ultrasonic energy may be applied.

[00109] Additionally or alternatively, the one or more switches may comprises a toggle button 136c that, when depressed, causes the generator 102 to provide a pulsed output. The pulses may be provided at any suitable frequency and grouping, for example. In certain embodiments, the power level of the pulses may be the power levels associated with toggle buttons 136a,b (maximum, less than maximum), for example.

[00110] It will be appreciated that a device 104 may comprise any combination of the toggle buttons 136a,b,c. For example, the device 104 could be configured to have only two toggle buttons: a toggle button 136a for producing maximum ultrasonic energy output and a toggle button 136c for producing a pulsed output at either the maximum or less than maximum power level per. In this way, the drive signal output configuration of the generator 102 could be 5 continuous signals and 5 or 4 or 3 or 2 or 1 pulsed signals. In certain embodiments, the specific drive signal configuration may be controlled based upon, for example, EEPROM settings in the generator 102 and/or user power level selection(s).

[00111] In certain embodiments, a two-position switch may be provided as an alternative to a toggle button 136c. For example, a device 104 may include a toggle button 136a for producing a continuous output at a maximum power level and a two-position toggle button 136b.

In a first detented position, toggle button 136b may produce a continuous output at a less than maximum power level, and in a second detented position the toggle button 136b may produce a pulsed output (e.g., at either a maximum or less than maximum power level, depending upon the EEPROM settings).

[00112] In some embodiments, the end effector 126 may also comprise a pair of electrodes 159, 157. The electrodes 159, 157 may be in communication with the generator 102, for example, via the cable 122. The electrodes 159, 157 may be used, for example, to measure an impedance of a tissue bite present between the clamp arm 155 and the blade 151. The generator 102 may provide a signal (e.g., a non-therapeutic signal) to the electrodes 159, 157. The impedance of the tissue bite may be found, for example, by monitoring the current, voltage, etc. of the signal.

[00113] Figure 4 illustrates one embodiment of an example electrosurgical device 106 that may also be used for transection and sealing. According to various embodiments, the transection and sealing device 106 may comprise a hand piece assembly 130, a shaft 165 and an end effector 132. The shaft 165 may be rigid (e.g., for laparoscopic and/or open surgical application) or flexible, as shown, (e.g., for endoscopic application). In various embodiments, the shaft 165 may comprise one or more articulation points. The end effector 132 may comprise jaws 144 having a first jaw member 167 and a second jaw member 169. The first jaw member 167 and second jaw member 169 may be connected to a clevis 171, which, in turn, may be coupled to the shaft 165. A translating member 173 may extend within the shaft 165 from the end effector 132 to the hand piece 130. At the hand piece 130, the shaft 165 may be directly or indirectly coupled to a jaw closure trigger 142 (Figure 4).

[00114] The jaw members 167, 169 of the end effector 132 may comprise respective electrodes 177, 179. The electrodes 177, 179 may be connected to the generator 102 via electrical leads 187a, 187b (Figure 5) extending from the end effector 132 through the shaft 165 and hand piece 130 and ultimately to the generator 102 (e.g., by a multiconductor cable 128). The generator 102 may provide a drive signal to the electrodes 177, 179 to bring about a therapeutic effect to tissue present within the jaw members 167, 169. The electrodes 177, 179 may comprise an active electrode and a return electrode, wherein the active electrode and the return electrode can be positioned against, or adjacent to, the tissue to be treated such that current can flow from the active electrode to the return electrode through the tissue. As illustrated in Figure 4, the end effector 132 is shown with the jaw members 167, 169 in an open position. A reciprocating blade 175 is illustrated between the jaw members 167, 169.

[00115] Figures 5, 6 and 7 illustrate one embodiment of the end effector 132 shown in Figure 4. To close the jaws 144 of the end effector 132, a clinician may cause the jaw closure trigger 142 to pivot along arrow 183 from a first position to a second position. This may cause the jaws 144 to open and close according to any suitable method. For example, motion of the jaw closure trigger 142 may, in turn, cause the translating member 173 to translate within a bore 185 of the shaft 165. A distal portion of the translating member 173 may be coupled to a reciprocating member 197 such that distal and proximal motion of the translating member 173 causes corresponding distal and proximal motion of the reciprocating member. The reciprocating member 197 may have shoulder portions 191a, 191b, while the jaw members 167, 169 may have corresponding cam surfaces 189a, 189b. As the reciprocating member 197 is translated distally from the position shown in Figure 6 to the position shown in Figure 7, the shoulder portions 191a, 191b may contact the cam surfaces 189a, 189b, causing the jaw members 167, 169 to transition to the closed position. Also, in various embodiments, the blade 175 may be positioned at a distal end of the reciprocating member 197. As the reciprocating member extends to the fully distal position shown in Figure 7, the blade 175 may be pushed through any tissue present between the jaw members 167, 169, in the process, severing it.

[00116] In use, a clinician may place the end effector 132 and close the jaws 144 around a tissue bite to be acted upon, for example, by pivoting the jaw closure trigger 142 along arrow 183 as described. Once the tissue bite is secure between the jaws 144, the clinician may initiate the provision of RF or other electro-surgical energy by the generator 102 and through the electrodes 177, 179. The provision of RF energy may be accomplished in any suitable way. For example, the clinician may activate the foot switch 120 (Figure 8) of the generator 102 to initiate the provision of RF energy. Also, for example, the hand piece 130 may comprise one or more switches 181 that may be actuated by the clinician to cause the generator 102 to begin providing RF energy. Additionally, in some embodiments, RF energy may be provided based on the position of the jaw closure trigger 142. For example, when the trigger 142 is fully depressed (indicating that the jaws 144 are closed), RF energy may be provided. Also, according to various embodiments, the blade 175 may be advanced during closure of the jaws 144 or may be separately advanced by the clinician after closure of the jaws 144 (e.g., after a RF energy has been applied to the tissue).

[00117] Figure 8 is a diagram of the surgical system 100 of Figure 1. In various embodiments, the generator 102 may comprise several separate functional elements, such as modules and/or blocks. Different functional elements or modules may be configured for driving the different kinds of surgical devices 104, 106. For example an ultrasonic generator module

108 may drive an ultrasonic device, such as the ultrasonic device 104. An electrosurgery/RF generator module 110 may drive the electrosurgical device 106. For example, the respective modules 108, 110 may generate respective drive signals for driving the surgical devices 104, 106. In various embodiments, the ultrasonic generator module 108 and/or the electrosurgery/RF generator module 110 each may be formed integrally with the generator 102. Alternatively, one or more of the modules 108, 110 may be provided as a separate circuit module electrically coupled to the generator 102. (The modules 108 and 110 are shown in phantom to illustrate this option.) Also, in some embodiments, the electrosurgery/RF generator module 110 may be formed integrally with the ultrasonic generator module 108, or vice versa.

[00118] In accordance with the described embodiments, the ultrasonic generator module 108 may produce a drive signal or signals of particular voltages, currents, and frequencies, e.g. 55,500 cycles per second (Hz). The drive signal or signals may be provided to the ultrasonic device 104, and specifically to the transducer 114, which may operate, for example, as described above. In one embodiment, the generator 102 may be configured to produce a drive signal of a particular voltage, current, and/or frequency output signal that can be stepped with high resolution, accuracy, and repeatability.

[00119] In accordance with the described embodiments, the electrosurgery/RF generator module 110 may generate a drive signal or signals with output power sufficient to perform bipolar electrosurgery using radio frequency (RF) energy. In bipolar electrosurgery applications. The drive signal may be provided, for example, to the electrodes 177, 179 of the electrosurgical device 106, for example, as described above. Accordingly, the generator 102 may be configured for therapeutic purposes by applying electrical energy to the tissue sufficient for treating the tissue (e.g., coagulation, cauterization, tissue welding, etc.).

[00120] The generator 102 may comprise an input device 145 (Figure 1) located, for example, on a front panel of the generator 102 console. The input device 145 may comprise any suitable device that generates signals suitable for programming the operation of the generator 102. In operation, the user can program or otherwise control operation of the generator 102 using the input device 145. The input device 145 may comprise any suitable device that generates signals that can be used by the generator (e.g., by one or more processors contained in the generator) to control the operation of the generator 102 (e.g., operation of the ultrasonic generator module 108 and/or electrosurgery/RF generator module 110). In various embodiments, the input device 145 includes one or more of buttons, switches, thumbwheels, keyboard, keypad, touch screen monitor, pointing device, remote connection to a general purpose or dedicated computer. In other embodiments, the input device 145 may

comprise a suitable user interface, such as one or more user interface screens displayed on a touch screen monitor, for example. Accordingly, by way of the input device 145, the user can set or program various operating parameters of the generator, such as, for example, current (I), voltage (V), frequency (f), and/or period (T) of a drive signal or signals generated by the ultrasonic generator module 108 and/or electrosurgery/RF generator module 110.

[00121] The generator 102 may also comprise an output device 147 (Figure 1) located, for example, on a front panel of the generator 102 console. The output device 147 includes one or more devices for providing a sensory feedback to a user. Such devices may comprise, for example, visual feedback devices (e.g., an LCD display screen, LED indicators), audio feedback devices (e.g., a speaker, a buzzer) or tactile feedback devices (e.g., haptic actuators).

[00122] Although certain modules and/or blocks of the generator 102 may be described by way of example, it can be appreciated that a greater or lesser number of modules and/or blocks may be used and still fall within the scope of the embodiments. Further, although various embodiments may be described in terms of modules and/or blocks to facilitate description, such modules and/or blocks may be implemented by one or more hardware components, e.g., processors, Digital Signal Processors (DSPs), Programmable Logic Devices (PLDs), Application Specific Integrated Circuits (ASICs), circuits, registers and/or software components, e.g., programs, subroutines, logic and/or combinations of hardware and software components.

[00123] In one embodiment, the ultrasonic generator drive module 108 and electrosurgery/RF drive module 110 may comprise one or more embedded applications implemented as firmware, software, hardware, or any combination thereof. The modules 108, 110 may comprise various executable modules such as software, programs, data, drivers, application program interfaces (APIs), and so forth. The firmware may be stored in nonvolatile memory (NVM), such as in bit-masked read-only memory (ROM) or flash memory. In various implementations, storing the firmware in ROM may preserve flash memory. The NVM may comprise other types of memory including, for example, programmable ROM (PROM), erasable programmable ROM (EPROM), electrically erasable programmable ROM (EEPROM), or battery backed random-access memory (RAM) such as dynamic RAM (DRAM), Double-Data-Rate DRAM (DDRAM), and/or synchronous DRAM (SDRAM).

[00124] In one embodiment, the modules 108, 110 comprise a hardware component implemented as a processor for executing program instructions for monitoring various measurable characteristics of the devices 104, 106 and generating a corresponding output drive signal or signals for operating the devices 104, 106. In embodiments in which the generator 102 is used in conjunction with the device 104, the drive signal may drive the ultrasonic

transducer 114 in cutting and/or coagulation operating modes. Electrical characteristics of the device 104 and/or tissue may be measured and used to control operational aspects of the generator 102 and/or provided as feedback to the user. In embodiments in which the generator 102 is used in conjunction with the device 106, the drive signal may supply electrical energy (e.g., RF energy) to the end effector 132 in cutting, coagulation and/or desiccation modes. Electrical characteristics of the device 106 and/or tissue may be measured and used to control operational aspects of the generator 102 and/or provided as feedback to the user. In various embodiments, as previously discussed, the hardware components may be implemented as DSP, PLD, ASIC, circuits, and/or registers. In one embodiment, the processor may be configured to store and execute computer software program instructions to generate the step function output signals for driving various components of the devices 104, 106, such as the ultrasonic transducer 114 and the end effectors 126, 132.

[00125] Figure 9 illustrates an equivalent circuit 150 of an ultrasonic transducer, such as the ultrasonic transducer 114, according to one embodiment. The circuit 150 comprises a first “motional” branch having a serially connected inductance L_s , resistance R_s and capacitance C_s that define the electromechanical properties of the resonator, and a second capacitive branch having a static capacitance C_0 . Drive current I_g may be received from a generator at a drive voltage V_g , with motional current I_m flowing through the first branch and current $I_g - I_m$ flowing through the capacitive branch. Control of the electromechanical properties of the ultrasonic transducer may be achieved by suitably controlling I_g and V_g . As explained above, known generator architectures may include a tuning inductor L_t (shown in phantom in Figure 9) for tuning out in a parallel resonance circuit the static capacitance C_0 at a resonant frequency so that substantially all of generator's current output I_g flows through the motional branch. In this way, control of the motional branch current I_m is achieved by controlling the generator current output I_g . The tuning inductor L_t is specific to the static capacitance C_0 of an ultrasonic transducer, however, and a different ultrasonic transducer having a different static capacitance requires a different tuning inductor L_t . Moreover, because the tuning inductor L_t is matched to the nominal value of the static capacitance C_0 at a single resonant frequency, accurate control of the motional branch current I_m is assured only at that frequency, and as frequency shifts down with transducer temperature, accurate control of the motional branch current is compromised.

[00126] Various embodiments of the generator 102 may not rely on a tuning inductor L_t to monitor the motional branch current I_m . Instead, the generator 102 may use the measured value of the static capacitance C_0 in between applications of power for a specific ultrasonic

surgical device 104 (along with drive signal voltage and current feedback data) to determine values of the motional branch current I_m on a dynamic and ongoing basis (e.g., in real-time). Such embodiments of the generator 102 are therefore able to provide virtual tuning to simulate a system that is tuned or resonant with any value of static capacitance C_0 at any frequency, and not just at a single resonant frequency dictated by a nominal value of the static capacitance C_0 .

[00127] Figure 10 is a simplified block diagram of one embodiment of the generator 102 for providing inductorless tuning as described above, among other benefits. Figures 11A-11C illustrate an architecture of the generator 102 of Figure 10 according to one embodiment. With reference to Figure 10, the generator 102 may comprise a patient isolated stage 152 in communication with a non-isolated stage 154 via a power transformer 156. A secondary winding 158 of the power transformer 156 is contained in the isolated stage 152 and may comprise a tapped configuration (e.g., a center-tapped or non-center tapped configuration) to define drive signal outputs 160a, 160b, 160c for outputting drive signals to different surgical devices, such as, for example, an ultrasonic surgical device 104 and an electrosurgical device 106. In particular, drive signal outputs 160a, 160c may output a drive signal (e.g., a 420V RMS drive signal) to an ultrasonic surgical device 104, and drive signal outputs 160b, 160c may output a drive signal (e.g., a 100V RMS drive signal) to an electrosurgical device 106, with output 160b corresponding to the center tap of the power transformer 156. The non-isolated stage 154 may comprise a power amplifier 162 having an output connected to a primary winding 164 of the power transformer 156. In certain embodiments the power amplifier 162 may comprise a push-pull amplifier, for example. The non-isolated stage 154 may further comprise a programmable logic device 166 for supplying a digital output to a digital-to-analog converter (DAC) 168, which in turn supplies a corresponding analog signal to an input of the power amplifier 162. In certain embodiments the programmable logic device 166 may comprise a field-programmable gate array (FPGA), for example. The programmable logic device 166, by virtue of controlling the power amplifier's 162 input via the DAC 168, may therefore control any of a number of parameters (e.g., frequency, waveform shape, waveform amplitude) of drive signals appearing at the drive signal outputs 160a, 160b, 160c. In certain embodiments and as discussed below, the programmable logic device 166, in conjunction with a processor (e.g., processor 174 discussed below), may implement a number of digital signal processing (DSP)-based and/or other control algorithms to control parameters of the drive signals output by the generator 102.

[00128] Power may be supplied to a power rail of the power amplifier 162 by a switch-mode regulator 170. In certain embodiments the switch-mode regulator 170 may comprise an

adjustable buck regulator, for example. The non-isolated stage 154 may further comprise a processor 174, which in one embodiment may comprise a DSP processor such as an Analog Devices ADSP-21469 SHARC DSP, available from Analog Devices, Norwood, MA, for example. In certain embodiments the processor 174 may control operation of the switch-mode power converter 170 responsive to voltage feedback data received from the power amplifier 162 by the processor 174 via an analog-to-digital converter (ADC) 176. In one embodiment, for example, the processor 174 may receive as input, via the ADC 176, the waveform envelope of a signal (e.g., an RF signal) being amplified by the power amplifier 162. The processor 174 may then control the switch-mode regulator 170 (e.g., via a pulse-width modulated (PWM) output) such that the rail voltage supplied to the power amplifier 162 tracks the waveform envelope of the amplified signal. By dynamically modulating the rail voltage of the power amplifier 162 based on the waveform envelope, the efficiency of the power amplifier 162 may be significantly improved relative to a fixed rail voltage amplifier schemes.

[00129] In certain embodiments and as discussed in further detail in connection with Figure 13, the programmable logic device 166, in conjunction with the processor 174, may implement a direct digital synthesizer (DDS) control scheme to control the waveform shape, frequency and/or amplitude of drive signals output by the generator 102. In one embodiment, for example, the programmable logic device 166 may implement a DDS control algorithm 268 by recalling waveform samples stored in a dynamically-updated look-up table (LUT), such as a RAM LUT which may be embedded in an FPGA. This control algorithm is particularly useful for ultrasonic applications in which an ultrasonic transducer, such as the ultrasonic transducer 114, may be driven by a clean sinusoidal current at its resonant frequency. Because other frequencies may excite parasitic resonances, minimizing or reducing the total distortion of the motional branch current may correspondingly minimize or reduce undesirable resonance effects. Because the waveform shape of a drive signal output by the generator 102 is impacted by various sources of distortion present in the output drive circuit (e.g., the power transformer 156, the power amplifier 162), voltage and current feedback data based on the drive signal may be input into an algorithm, such as an error control algorithm implemented by the processor 174, which compensates for distortion by suitably pre-distorting or modifying the waveform samples stored in the LUT on a dynamic, ongoing basis (e.g., in real-time). In one embodiment, the amount or degree of pre-distortion applied to the LUT samples may be based on the error between a computed motional branch current and a desired current waveform shape, with the error being determined on a sample-by sample basis. In this way, the pre-distorted LUT samples, when processed through the drive circuit, may result in a motional branch drive signal

having the desired waveform shape (e.g., sinusoidal) for optimally driving the ultrasonic transducer. In such embodiments, the LUT waveform samples will therefore not represent the desired waveform shape of the drive signal, but rather the waveform shape that is required to ultimately produce the desired waveform shape of the motional branch drive signal when distortion effects are taken into account.

[00130] The non-isolated stage 154 may further comprise an ADC 178 and an ADC 180 coupled to the output of the power transformer 156 via respective isolation transformers 182, 184 for respectively sampling the voltage and current of drive signals output by the generator 102. In certain embodiments, the ADCs 178, 180 may be configured to sample at high speeds (e.g., 80 Msps) to enable oversampling of the drive signals. In one embodiment, for example, the sampling speed of the ADCs 178, 180 may enable approximately 200x (depending on drive frequency) oversampling of the drive signals. In certain embodiments, the sampling operations of the ADCs 178, 180 may be performed by a single ADC receiving input voltage and current signals via a two-way multiplexer. The use of high-speed sampling in embodiments of the generator 102 may enable, among other things, calculation of the complex current flowing through the motional branch (which may be used in certain embodiments to implement DDS-based waveform shape control described above), accurate digital filtering of the sampled signals, and calculation of real power consumption with a high degree of precision. Voltage and current feedback data output by the ADCs 178, 180 may be received and processed (e.g., FIFO buffering, multiplexing) by the programmable logic device 166 and stored in data memory for subsequent retrieval by, for example, the processor 174. As noted above, voltage and current feedback data may be used as input to an algorithm for pre-distorting or modifying LUT waveform samples on a dynamic and ongoing basis. In certain embodiments, this may require each stored voltage and current feedback data pair to be indexed based on, or otherwise associated with, a corresponding LUT sample that was output by the programmable logic device 166 when the voltage and current feedback data pair was acquired. Synchronization of the LUT samples and the voltage and current feedback data in this manner contributes to the correct timing and stability of the pre-distortion algorithm.

[00131] In certain embodiments, the voltage and current feedback data may be used to control the frequency and/or amplitude (e.g., current amplitude) of the drive signals. In one embodiment, for example, voltage and current feedback data may be used to determine impedance phase. The frequency of the drive signal may then be controlled to minimize or reduce the difference between the determined impedance phase and an impedance phase setpoint (e.g., 0°), thereby minimizing or reducing the effects of harmonic distortion and

correspondingly enhancing impedance phase measurement accuracy. The determination of phase impedance and a frequency control signal may be implemented in the processor 174, for example, with the frequency control signal being supplied as input to a DDS control algorithm implemented by the programmable logic device 166.

[00132] In another embodiment, for example, the current feedback data may be monitored in order to maintain the current amplitude of the drive signal at a current amplitude setpoint. The current amplitude setpoint may be specified directly or determined indirectly based on specified voltage amplitude and power setpoints. In certain embodiments, control of the current amplitude may be implemented by control algorithm, such as, for example, a proportional-integral-derivative (PID) control algorithm, in the processor 174. Variables controlled by the control algorithm to suitably control the current amplitude of the drive signal may include, for example, the scaling of the LUT waveform samples stored in the programmable logic device 166 and/or the full-scale output voltage of the DAC 168 (which supplies the input to the power amplifier 162) via a DAC 186.

[00133] The non-isolated stage 154 may further comprise a processor 190 for providing, among other things user interface (UI) functionality. In one embodiment, the processor 190 may comprise an Atmel AT91SAM9263 processor having an ARM 926EJ-S core, available from Atmel Corporation, San Jose, California, for example. Examples of UI functionality supported by the processor 190 may include audible and visual user feedback, communication with peripheral devices (e.g., via a Universal Serial Bus (USB) interface), communication with the footswitch 120, communication with an input device 112 (e.g., a touch screen display) and communication with an output device 147 (e.g., a speaker). The processor 190 may communicate with the processor 174 and the programmable logic device (e.g., via serial peripheral interface (SPI) buses). Although the processor 190 may primarily support UI functionality, it may also coordinate with the processor 174 to implement hazard mitigation in certain embodiments. For example, the processor 190 may be programmed to monitor various aspects of user input and/or other inputs (e.g., touch screen inputs, footswitch 120 inputs, temperature sensor inputs) and may disable the drive output of the generator 102 when an erroneous condition is detected.

[00134] In certain embodiments, both the processor 174 and the processor 190 may determine and monitor the operating state of the generator 102. For the processor 174, the operating state of the generator 102 may dictate, for example, which control and/or diagnostic processes are implemented by the processor 174. For the processor 190, the operating state of the generator 102 may dictate, for example, which elements of a user interface (e.g., display

screens, sounds) are presented to a user. The processors 174, 190 may independently maintain the current operating state of the generator 102 and recognize and evaluate possible transitions out of the current operating state. The processor 174 may function as the master in this relationship and determine when transitions between operating states are to occur. The processor 190 may be aware of valid transitions between operating states and may confirm if a particular transition is appropriate. For example, when the processor 174 instructs the processor 190 to transition to a specific state, the processor 190 may verify that requested transition is valid. In the event that a requested transition between states is determined to be invalid by the processor 190, the processor 190 may cause the generator 102 to enter a failure mode.

[00135] The non-isolated stage 154 may further comprise a controller 196 for monitoring input devices 145 (e.g., a capacitive touch sensor used for turning the generator 102 on and off, a capacitive touch screen). In certain embodiments, the controller 196 may comprise at least one processor and/or other controller device in communication with the processor 190. In one embodiment, for example, the controller 196 may comprise a processor (e.g., a Mega168 8-bit controller available from Atmel) configured to monitor user input provided via one or more capacitive touch sensors. In one embodiment, the controller 196 may comprise a touch screen controller (e.g., a QT5480 touch screen controller available from Atmel) to control and manage the acquisition of touch data from a capacitive touch screen.

[00136] In certain embodiments, when the generator 102 is in a “power off” state, the controller 196 may continue to receive operating power (e.g., via a line from a power supply of the generator 102, such as the power supply 211 discussed below). In this way, the controller 196 may continue to monitor an input device 145 (e.g., a capacitive touch sensor located on a front panel of the generator 102) for turning the generator 102 on and off. When the generator 102 is in the power off state, the controller 196 may wake the power supply (e.g., enable operation of one or more DC/DC voltage converters 213 of the power supply 211) if activation of the “on/off” input device 145 by a user is detected. The controller 196 may therefore initiate a sequence for transitioning the generator 102 to a “power on” state. Conversely, the controller 196 may initiate a sequence for transitioning the generator 102 to the power off state if activation of the “on/off” input device 145 is detected when the generator 102 is in the power on state. In certain embodiments, for example, the controller 196 may report activation of the “on/off” input device 145 to the processor 190, which in turn implements the necessary process sequence for transitioning the generator 102 to the power off state. In such embodiments, the

controller 196 may have no independent ability for causing the removal of power from the generator 102 after its power on state has been established.

[00137] In certain embodiments, the controller 196 may cause the generator 102 to provide audible or other sensory feedback for alerting the user that a power on or power off sequence has been initiated. Such an alert may be provided at the beginning of a power on or power off sequence and prior to the commencement of other processes associated with the sequence.

[00138] In certain embodiments, the isolated stage 152 may comprise an instrument interface circuit 198 to, for example, provide a communication interface between a control circuit of a surgical device (e.g., a control circuit comprising handpiece switches) and components of the non-isolated stage 154, such as, for example, the programmable logic device 166, the processor 174 and/or the processor 190. The instrument interface circuit 198 may exchange information with components of the non-isolated stage 154 via a communication link that maintains a suitable degree of electrical isolation between the stages 152, 154, such as, for example, an infrared (IR)-based communication link. Power may be supplied to the instrument interface circuit 198 using, for example, a low-dropout voltage regulator powered by an isolation transformer driven from the non-isolated stage 154.

[00139] In one embodiment, the instrument interface circuit 198 may comprise a programmable logic device 200 (e.g., an FPGA) in communication with a signal conditioning circuit 202. The signal conditioning circuit 202 may be configured to receive a periodic signal from the programmable logic device 200 (e.g., a 2 kHz square wave) to generate a bipolar interrogation signal having an identical frequency. The interrogation signal may be generated, for example, using a bipolar current source fed by a differential amplifier. The interrogation signal may be communicated to a surgical device control circuit (e.g., by using a conductive pair in a cable that connects the generator 102 to the surgical device) and monitored to determine a state or configuration of the control circuit. As discussed below in connection with Figures 16-32, for example, the control circuit may comprise a number of switches, resistors and/or diodes to modify one or more characteristics (e.g., amplitude, rectification) of the interrogation signal such that a state or configuration of the control circuit is uniquely discernable based on the one or more characteristics. In one embodiment, for example, the signal conditioning circuit 202 may comprise an ADC for generating samples of a voltage signal appearing across inputs of the control circuit resulting from passage of interrogation signal therethrough. The programmable logic device 200 (or a component of the non-isolated stage 154) may then determine the state or configuration of the control circuit based on the ADC samples.

[00140] In one embodiment, the instrument interface circuit 198 may comprise a first data circuit interface 204 to enable information exchange between the programmable logic device 200 (or other element of the instrument interface circuit 198) and a first data circuit disposed in or otherwise associated with a surgical device. In certain embodiments and with reference to Figures 33E-33G, for example, a first data circuit 206 may be disposed in a cable integrally attached to a surgical device handpiece, or in an adaptor for interfacing a specific surgical device type or model with the generator 102. In certain embodiments, the first data circuit may comprise a non-volatile storage device, such as an electrically erasable programmable read-only memory (EEPROM) device. In certain embodiments and referring again to Figure 10, the first data circuit interface 204 may be implemented separately from the programmable logic device 200 and comprise suitable circuitry (e.g., discrete logic devices, a processor) to enable communication between the programmable logic device 200 and the first data circuit. In other embodiments, the first data circuit interface 204 may be integral with the programmable logic device 200.

[00141] In certain embodiments, the first data circuit 206 may store information pertaining to the particular surgical device with which it is associated. Such information may include, for example, a model number, a serial number, a number of operations in which the surgical device has been used, and/or any other type of information. This information may be read by the instrument interface circuit 198 (e.g., by the programmable logic device 200), transferred to a component of the non-isolated stage 154 (e.g., to programmable logic device 166, processor 174 and/or processor 190) for presentation to a user via an output device 147 and/or for controlling a function or operation of the generator 102. Additionally, any type of information may be communicated to first data circuit 206 for storage therein via the first data circuit interface 204 (e.g., using the programmable logic device 200). Such information may comprise, for example, an updated number of operations in which the surgical device has been used and/or dates and/or times of its usage.

[00142] As discussed previously, a surgical instrument may be detachable from a handpiece (e.g., instrument 124 may be detachable from handpiece 116) to promote instrument interchangeability and/or disposability. In such cases, known generators may be limited in their ability to recognize particular instrument configurations being used and to optimize control and diagnostic processes accordingly. The addition of readable data circuits to surgical device instruments to address this issue is problematic from a compatibility standpoint, however. For example, designing a surgical device to remain backwardly compatible with generators that lack the requisite data reading functionality may be impractical due to, for example, differing signal

schemes, design complexity and cost. Embodiments of instruments discussed below in connection with Figures 16-32 address these concerns by using data circuits that may be implemented in existing surgical instruments economically and with minimal design changes to preserve compatibility of the surgical devices with current generator platforms.

[00143] Additionally, embodiments of the generator 102 may enable communication with instrument-based data circuits, such as those described below in connection with Figures 16-32 and Figures 33A-33C. For example, the generator 102 may be configured to communicate with a second data circuit (e.g., data circuit 284 of Figure 16) contained in an instrument (e.g., instrument 124 or 134) of a surgical device. The instrument interface circuit 198 may comprise a second data circuit interface 210 to enable this communication. In one embodiment, the second data circuit interface 210 may comprise a tri-state digital interface, although other interfaces may also be used. In certain embodiments, the second data circuit may generally be any circuit for transmitting and/or receiving data. In one embodiment, for example, the second data circuit may store information pertaining to the particular surgical instrument with which it is associated. Such information may include, for example, a model number, a serial number, a number of operations in which the surgical instrument has been used, and/or any other type of information. Additionally or alternatively, any type of information may be communicated to second data circuit for storage therein via the second data circuit interface 210 (e.g., using the programmable logic device 200). Such information may comprise, for example, an updated number of operations in which the instrument has been used and/or dates and/or times of its usage. In certain embodiments, the second data circuit may transmit data acquired by one or more sensors (e.g., an instrument-based temperature sensor). In certain embodiments, the second data circuit may receive data from the generator 102 and provide an indication to a user (e.g., an LED indication or other visible indication) based on the received data.

[00144] In certain embodiments, the second data circuit and the second data circuit interface 210 may be configured such that communication between the programmable logic device 200 and the second data circuit can be effected without the need to provide additional conductors for this purpose (e.g., dedicated conductors of a cable connecting a handpiece to the generator 102). In one embodiment, for example, information may be communicated to and from the second data circuit using a 1-wire bus communication scheme implemented on existing cabling, such as one of the conductors used transmit interrogation signals from the signal conditioning circuit 202 to a control circuit in a handpiece. In this way, design changes or modifications to the surgical device that might otherwise be necessary are minimized or reduced. Moreover, as discussed in further detail below in connection with Figures 16-32 and

Figures 33A-33C, because different types of communications can be implemented over a common physical channel (either with or without frequency-band separation), the presence of a second data circuit may be “invisible” to generators that do not have the requisite data reading functionality, thus enabling backward compatibility of the surgical device instrument.

[00145] In certain embodiments, the isolated stage 152 may comprise at least one blocking capacitor 296-1 connected to the drive signal output 160b to prevent passage of DC current to a patient. A single blocking capacitor may be required to comply with medical regulations or standards, for example. While failure in single-capacitor designs is relatively uncommon, such failure may nonetheless have negative consequences. In one embodiment, a second blocking capacitor 296-2 may be provided in series with the blocking capacitor 296-1, with current leakage from a point between the blocking capacitors 296-1, 296-2 being monitored by, for example, an ADC 298 for sampling a voltage induced by leakage current. The samples may be received by the programmable logic device 200, for example. Based on changes in the leakage current (as indicated by the voltage samples in the embodiment of Figure 10), the generator 102 may determine when at least one of the blocking capacitors 296-1, 296-2 has failed. Accordingly, the embodiment of Figure 10 may provide a benefit over single-capacitor designs having a single point of failure.

[00146] In certain embodiments, the non-isolated stage 154 may comprise a power supply 211 for outputting DC power at a suitable voltage and current. The power supply may comprise, for example, a 400 W power supply for outputting a 48 VDC system voltage. The power supply 211 may further comprise one or more DC/DC voltage converters 213 for receiving the output of the power supply to generate DC outputs at the voltages and currents required by the various components of the generator 102. As discussed above in connection with the controller 196, one or more of the DC/DC voltage converters 213 may receive an input from the controller 196 when activation of the “on/off” input device 145 by a user is detected by the controller 196 to enable operation of, or wake, the DC/DC voltage converters 213.

[00147] Figure 13 illustrates certain functional and structural aspects of one embodiment of the generator 102. Feedback indicating current and voltage output from the secondary winding 158 of the power transformer 156 is received by the ADCs 178, 180, respectively. As shown, the ADCs 178, 180 may be implemented as a 2-channel ADC and may sample the feedback signals at a high speed (e.g., 80 Msps) to enable oversampling (e.g., approximately 200x oversampling) of the drive signals. The current and voltage feedback signals may be suitably conditioned in the analog domain (e.g., amplified, filtered) prior to processing by the ADCs 178, 180. Current and voltage feedback samples from the ADCs 178, 180 may be

individually buffered and subsequently multiplexed or interleaved into a single data stream within block 212 of the programmable logic device 166. In the embodiment of Figure 13, the programmable logic device 166 comprises an FPGA.

[00148] The multiplexed current and voltage feedback samples may be received by a parallel data acquisition port (PDAP) implemented within block 214 of the processor 174. The PDAP may comprise a packing unit for implementing any of a number of methodologies for correlating the multiplexed feedback samples with a memory address. In one embodiment, for example, feedback samples corresponding to a particular LUT sample output by the programmable logic device 166 may be stored at one or more memory addresses that are correlated or indexed with the LUT address of the LUT sample. In another embodiment, feedback samples corresponding to a particular LUT sample output by the programmable logic device 166 may be stored, along with the LUT address of the LUT sample, at a common memory location. In any event, the feedback samples may be stored such that the address of an LUT sample from which a particular set of feedback samples originated may be subsequently ascertained. As discussed above, synchronization of the LUT sample addresses and the feedback samples in this way contributes to the correct timing and stability of the pre-distortion algorithm. A direct memory access (DMA) controller implemented at block 216 of the processor 174 may store the feedback samples (and any LUT sample address data, where applicable) at a designated memory location 218 of the processor 174 (e.g., internal RAM).

[00149] Block 220 of the processor 174 may implement a pre-distortion algorithm for pre-distorting or modifying the LUT samples stored in the programmable logic device 166 on a dynamic, ongoing basis. As discussed above, pre-distortion of the LUT samples may compensate for various sources of distortion present in the output drive circuit of the generator 102. The pre-distorted LUT samples, when processed through the drive circuit, will therefore result in a drive signal having the desired waveform shape (e.g., sinusoidal) for optimally driving the ultrasonic transducer.

[00150] At block 222 of the pre-distortion algorithm, the current through the motional branch of the ultrasonic transducer is determined. The motional branch current may be determined using Kirchoff's Current Law based on, for example, the current and voltage feedback samples stored at memory location 218 (which, when suitably scaled, may be representative of I_g and V_g in the model of Figure 9 discussed above), a value of the ultrasonic transducer static capacitance C_0 (measured or known *a priori*) and a known value of the drive frequency. A motional branch current sample for each set of stored current and voltage feedback samples associated with a LUT sample may be determined.

[00151] At block 224 of the pre-distortion algorithm, each motional branch current sample determined at block 222 is compared to a sample of a desired current waveform shape to determine a difference, or sample amplitude error, between the compared samples. For this determination, the sample of the desired current waveform shape may be supplied, for example, from a waveform shape LUT 226 containing amplitude samples for one cycle of a desired current waveform shape. The particular sample of the desired current waveform shape from the LUT 226 used for the comparison may be dictated by the LUT sample address associated with the motional branch current sample used in the comparison. Accordingly, the input of the motional branch current to block 224 may be synchronized with the input of its associated LUT sample address to block 224. The LUT samples stored in the programmable logic device 166 and the LUT samples stored in the waveform shape LUT 226 may therefore be equal in number. In certain embodiments, the desired current waveform shape represented by the LUT samples stored in the waveform shape LUT 226 may be a fundamental sine wave. Other waveform shapes may be desirable. For example, it is contemplated that a fundamental sine wave for driving main longitudinal motion of an ultrasonic transducer superimposed with one or more other drive signals at other frequencies, such as a third order harmonic for driving at least two mechanical resonances for beneficial vibrations of transverse or other modes, could be used.

[00152] Each value of the sample amplitude error determined at block 224 may be transmitted to the LUT of the programmable logic device 166 (shown at block 228 in Figure 13) along with an indication of its associated LUT address. Based on the value of the sample amplitude error and its associated address (and, optionally, values of sample amplitude error for the same LUT address previously received), the LUT 228 (or other control block of the programmable logic device 166) may pre-distort or modify the value of the LUT sample stored at the LUT address such that the sample amplitude error is reduced or minimized. It will be appreciated that such pre-distortion or modification of each LUT sample in an iterative manner across the entire range of LUT addresses will cause the waveform shape of the generator's output current to match or conform to the desired current waveform shape represented by the samples of the waveform shape LUT 226.

[00153] Current and voltage amplitude measurements, power measurements and impedance measurements may be determined at block 230 of the processor 174 based on the current and voltage feedback samples stored at memory location 218. Prior to the determination of these quantities, the feedback samples may be suitably scaled and, in certain embodiments, processed through a suitable filter 232 to remove noise resulting from, for

example, the data acquisition process and induced harmonic components. The filtered voltage and current samples may therefore substantially represent the fundamental frequency of the generator's drive output signal. In certain embodiments, the filter 232 may be a finite impulse response (FIR) filter applied in the frequency domain. Such embodiments may use the fast Fourier transform (FFT) of the output drive signal current and voltage signals. In certain embodiments, the resulting frequency spectrum may be used to provide additional generator functionality. In one embodiment, for example, the ratio of the second and/or third order harmonic component relative to the fundamental frequency component may be used as a diagnostic indicator.

[00154] At block 234, a root mean square (RMS) calculation may be applied to a sample size of the current feedback samples representing an integral number of cycles of the drive signal to generate a measurement I_{rms} representing the drive signal output current.

[00155] At block 236, a root mean square (RMS) calculation may be applied to a sample size of the voltage feedback samples representing an integral number of cycles of the drive signal to determine a measurement V_{rms} representing the drive signal output voltage.

[00156] At block 238, the current and voltage feedback samples may be multiplied point by point, and a mean calculation is applied to samples representing an integral number of cycles of the drive signal to determine a measurement P_r of the generator's real output power.

[00157] At block 240, measurement P_a of the generator's apparent output power may be determined as the product $V_{rms} \cdot I_{rms}$.

[00158] At block 242, measurement Z_m of the load impedance magnitude may be determined as the quotient V_{rms}/I_{rms} .

In certain embodiments, the quantities I_{rms} , V_{rms} , P_r , P_a and Z_m determined at blocks 234, 236, 238, 240 and 242 may be used by the generator 102 to implement any of number of control and/or diagnostic processes. In certain embodiments, any of these quantities may be communicated to a user via, for example, an output device 147 integral with the generator 102 or an output device 147 connected to the generator 102 through a suitable communication interface (e.g., a USB interface). Various diagnostic processes may include, without limitation, handpiece integrity, instrument integrity, instrument attachment integrity, instrument overload, approaching instrument overload, frequency lock failure, over-voltage, over-current, over-power, voltage sense failure, current sense failure, audio indication failure, visual indication failure, short circuit, power delivery failure, blocking capacitor failure, for example.

[00159] Block 244 of the processor 174 may implement a phase control algorithm for determining and controlling the impedance phase of an electrical load (e.g., the ultrasonic

transducer) driven by the generator 102. As discussed above, by controlling the frequency of the drive signal to minimize or reduce the difference between the determined impedance phase and an impedance phase setpoint (e.g., 0°), the effects of harmonic distortion may be minimized or reduced, and the accuracy of the phase measurement increased.

[00160] The phase control algorithm receives as input the current and voltage feedback samples stored in the memory location 218. Prior to their use in the phase control algorithm, the feedback samples may be suitably scaled and, in certain embodiments, processed through a suitable filter 246 (which may be identical to filter 232) to remove noise resulting from the data acquisition process and induced harmonic components, for example. The filtered voltage and current samples may therefore substantially represent the fundamental frequency of the generator's drive output signal.

[00161] At block 248 of the phase control algorithm, the current through the motional branch of the ultrasonic transducer is determined. This determination may be identical to that described above in connection with block 222 of the pre-distortion algorithm. The output of block 248 may thus be, for each set of stored current and voltage feedback samples associated with a LUT sample, a motional branch current sample.

[00162] At block 250 of the phase control algorithm, impedance phase is determined based on the synchronized input of motional branch current samples determined at block 248 and corresponding voltage feedback samples. In certain embodiments, the impedance phase is determined as the average of the impedance phase measured at the rising edge of the waveforms and the impedance phase measured at the falling edge of the waveforms.

[00163] At block 252 of the of the phase control algorithm, the value of the impedance phase determined at block 222 is compared to phase setpoint 254 to determine a difference, or phase error, between the compared values.

[00164] At block 256 of the phase control algorithm, based on a value of phase error determined at block 252 and the impedance magnitude determined at block 242, a frequency output for controlling the frequency of the drive signal is determined. The value of the frequency output may be continuously adjusted by the block 256 and transferred to a DDS control block 268 (discussed below) in order to maintain the impedance phase determined at block 250 at the phase setpoint (e.g., zero phase error). In certain embodiments, the impedance phase may be regulated to a 0° phase setpoint. In this way, any harmonic distortion will be centered about the crest of the voltage waveform, enhancing the accuracy of phase impedance determination.

[00165] Block 258 of the processor 174 may implement an algorithm for modulating the current amplitude of the drive signal in order to control the drive signal current, voltage and

power in accordance with user specified setpoints, or in accordance with requirements specified by other processes or algorithms implemented by the generator 102. Control of these quantities may be realized, for example, by scaling the LUT samples in the LUT 228 and/or by adjusting the full-scale output voltage of the DAC 168 (which supplies the input to the power amplifier 162) via a DAC 186. Block 260 (which may be implemented as a PID controller in certain embodiments) may receive as input current feedback samples (which may be suitably scaled and filtered) from the memory location 218. The current feedback samples may be compared to a “current demand” I_d value dictated by the controlled variable (e.g., current, voltage or power) to determine if the drive signal is supplying the necessary current. In embodiments in which drive signal current is the control variable, the current demand I_d may be specified directly by a current setpoint 262A (I_{sp}). For example, an RMS value of the current feedback data (determined as in block 234) may be compared to user-specified RMS current setpoint I_{sp} to determine the appropriate controller action. If, for example, the current feedback data indicates an RMS value less than the current setpoint I_{sp} , LUT scaling and/or the full-scale output voltage of the DAC 168 may be adjusted by the block 260 such that the drive signal current is increased. Conversely, block 260 may adjust LUT scaling and/or the full-scale output voltage of the DAC 168 to decrease the drive signal current when the current feedback data indicates an RMS value greater than the current setpoint I_{sp} .

[00166] In embodiments in which the drive signal voltage is the control variable, the current demand I_d may be specified indirectly, for example, based on the current required maintain a desired voltage setpoint 262B (V_{sp}) given the load impedance magnitude Z_m measured at block 242 (e.g. $I_d = V_{sp}/Z_m$). Similarly, in embodiments in which drive signal power is the control variable, the current demand I_d may be specified indirectly, for example, based on the current required to maintain a desired power setpoint 262C (P_{sp}) given the voltage V_{rms} measured at blocks 236 (e.g. $I_d = P_{sp}/V_{rms}$).

[00167] Block 268 may implement a DDS control algorithm for controlling the drive signal by recalling LUT samples stored in the LUT 228. In certain embodiments, the DDS control algorithm be a numerically-controlled oscillator (NCO) algorithm for generating samples of a waveform at a fixed clock rate using a point (memory location)-skipping technique. The NCO algorithm may implement a phase accumulator, or frequency-to-phase converter, that functions as an address pointer for recalling LUT samples from the LUT 228. In one embodiment, the phase accumulator may be a D step size, modulo N phase accumulator, where D is a positive integer representing a frequency control value, and N is the number of LUT samples in the LUT 228. A frequency control value of $D=1$, for example, may cause the phase accumulator to

sequentially point to every address of the LUT 228, resulting in a waveform output replicating the waveform stored in the LUT 228. When $D > 1$, the phase accumulator may skip addresses in the LUT 228, resulting in a waveform output having a higher frequency. Accordingly, the frequency of the waveform generated by the DDS control algorithm may therefore be controlled by suitably varying the frequency control value. In certain embodiments, the frequency control value may be determined based on the output of the phase control algorithm implemented at block 244. The output of block 268 may supply the input of (DAC) 168, which in turn supplies a corresponding analog signal to an input of the power amplifier 162.

[00168] Block 270 of the processor 174 may implement a switch-mode converter control algorithm for dynamically modulating the rail voltage of the power amplifier 162 based on the waveform envelope of the signal being amplified, thereby improving the efficiency of the power amplifier 162. In certain embodiments, characteristics of the waveform envelope may be determined by monitoring one or more signals contained in the power amplifier 162. In one embodiment, for example, characteristics of the waveform envelope may be determined by monitoring the minima of a drain voltage (e.g., a MOSFET drain voltage) that is modulated in accordance with the envelope of the amplified signal. A minima voltage signal may be generated, for example, by a voltage minima detector coupled to the drain voltage. The minima voltage signal may be sampled by ADC 176, with the output minima voltage samples being received at block 272 of the switch-mode converter control algorithm. Based on the values of the minima voltage samples, block 274 may control a PWM signal output by a PWM generator 276, which, in turn, controls the rail voltage supplied to the power amplifier 162 by the switch-mode regulator 170. In certain embodiments, as long as the values of the minima voltage samples are less than a minima target 278 input into block 262, the rail voltage may be modulated in accordance with the waveform envelope as characterized by the minima voltage samples. When the minima voltage samples indicate low envelope power levels, for example, block 274 may cause a low rail voltage to be supplied to the power amplifier 162, with the full rail voltage being supplied only when the minima voltage samples indicate maximum envelope power levels. When the minima voltage samples fall below the minima target 278, block 274 may cause the rail voltage to be maintained at a minimum value suitable for ensuring proper operation of the power amplifier 162.

[00169] Figures 33A-33C illustrate control circuits of surgical devices according to various embodiments. As discussed above in connection with Figure 10, a control circuit may modify characteristics of an interrogation signal transmitted by the generator 102. The characteristics of the interrogation signal, which may uniquely indicate a state or configuration of the control

circuit, can be discerned by the generator 102 and used to control aspects of its operation. The control circuits may be contained in an ultrasonic surgical device (e.g., in handpiece 116 of ultrasonic surgical device 104), or in an electrosurgical device (e.g., in handpiece 130 of electrosurgical device 106).

[00170] Referring to the embodiment of Figure 33A, control circuit 300-1 may be connected to the generator 102 to receive an interrogation signal (e.g., a bipolar interrogation signal at 2kHz) from the signal conditioning circuit 202 (e.g., from generator terminals HS and SR (Figure 10) via a conductive pair of cable 112 or cable 128). The control circuit 300-1 may comprise a first branch that includes series-connected diodes D1 and D2 and a switch SW1 connected in parallel with D2. The control circuit 300-1 may also comprise a second branch that includes series-connected diodes D3, D4 and D5, a switch SW2 connected in parallel with D4, and a resistor R1 connected in parallel with D5. In certain embodiments and as shown, D5 may be a Zener diode. The control circuit 300-1 may additionally comprise a data storage element 302 that, together with one or more components of the second branch (e.g., D5, R1), define a data circuit 304. In certain embodiments, the data storage element 302, and possibly other components of the data circuit 304, may be contained in the instrument (e.g., instrument 124, instrument 134) of the surgical device, with other components of the control circuit 300-1 (e.g., SW1, SW2, D1, D2, D3, D4) being contained in the handpiece (e.g., handpiece 116, handpiece 130). In certain embodiments, the data storage element 302 may be a single-wire bus device (e.g., a single-wire protocol EEPROM), or other single-wire protocol or local interconnect network (LIN) protocol device. In one embodiment, for example, the data storage element 302 may comprise a Maxim DS28EC20 1-Wire® EEPROM, available from Maxim Integrated Products, Inc., Sunnyvale, CA. The data storage element 302 is one example of a circuit element that may be contained in the data circuit 304. The data circuit 304 may additionally or alternatively comprise one or more other circuit elements or components capable of transmitting or receiving data. Such circuit elements or components may be configured to, for example, transmit data acquired by one or more sensors (e.g., an instrument-based temperature sensor) and/or receive data from the generator 102 and provide an indication to a user (e.g., an LED indication or other visible indication) based on the received data.

[00171] During operation, an interrogation signal (e.g., a bipolar interrogation signal at 2kHz) from the signal conditioning circuit 202 may be applied across both branches of the control circuit 300-1. In this way, the voltage appearing across the branches may be uniquely determined by the states of SW1 and SW2. For example, when SW1 is open, the voltage drop across the control circuit 300-1 for negative values of the interrogation signal will be sum of the

forward voltage drops across D1 and D2. When SW1 is closed, the voltage drop for negative values of the interrogation signal will be determined by the forward voltage drop of D1 only. Thus, for example, with a forward voltage drop of 0.7 volts for each of D1 and D2, open and closed states of SW1 may correspond to voltage drops of 1.4 volts and 0.7 volts, respectively. In the same way, the voltage drop across the control circuit 300-1 for positive values of the interrogation signal may be uniquely determined by the state of SW2. For example, when SW2 is open, the voltage drop across the control circuit 300-1 will be the sum of the forward voltage drops across D3 and D4 (e.g., 1.4 volts) and the breakdown voltage of D5 (e.g., 3.3 volts). When SW2 is closed, the voltage drop across the control circuit 300-1 will be the sum of the forward voltage drop across D3 and the breakdown voltage of D5. Accordingly, the state or configuration of SW1 and SW2 may be discerned by the generator 102 based on the interrogation signal voltage appearing across the inputs of the control circuit 300-1 (e.g., as measured by an ADC of the signal conditioning circuit 202).

[00172] In certain embodiments, the generator 102 may be configured to communicate with the data circuit 304, and, in particular, with the data storage element 302, via the second data circuit interface 210 (Figure 10) and the conductive pair of cable 112 or cable 128. The frequency band of the communication protocol used to communicate with the data circuit 304 may be higher than the frequency band of the interrogation signal. In certain embodiments, for example, the frequency of the communication protocol for the data storage element 302 may be, for example, 200 kHz or a significantly higher frequency, whereas the frequency of the interrogation signal used to determine the different states of SW1 and SW2 may be, for example, 2 kHz. Diode D5 may limit the voltage supplied to the data storage element 302 to a suitable operating range (e.g., 3.3-5V).

[00173] As explained above in connection with Figure 10, the data circuit 304, and, in particular, the data storage element 302, may store information pertaining to the particular surgical instrument with which it is associated. Such information may be retrieved by the generator 102 and include, for example, a model number, a serial number, a number of operations in which the surgical instrument has been used, and/or any other type of information. Additionally, any type of information may be communicated from the generator 102 to the data circuit 304 for storage in the data storage element 302. Such information may comprise, for example, an updated number of operations in which the instrument has been used and/or dates and/or times of its usage.

[00174] As noted above, the data circuit 304 may additionally or alternatively comprise components or elements other than the data storage element 302 for transmitting or receiving

data. Such components or elements may be configured to, for example, transmit data acquired by one or more sensors (e.g., an instrument-based temperature sensor) and/or receive data from the generator 102 and provide an indication to a user (e.g., an LED indication or other visible indication) based on the received data.

[00175] Embodiments of the control circuit may comprise additional switches. With reference to the embodiment of Figure 33B, for example, control circuit 300-2 may comprise a first branch having a first switch SW1 and a second switch SW2 (for a total of three switches), with each combination of SW1 and SW2 states corresponding to a unique voltage drop across the control circuit 300-2 for negative values of the interrogation signal. For example, the open and closed states of SW1 add or remove, respectively, the forward voltage drops of D2 and D3, and the open and closed states of SW2 add or remove, respectively, the forward voltage drop of D4. In the embodiment of Figure 33C, the first branch of control circuit 300-3 comprises three switches (for a total of four switches), with the breakdown voltage of Zener diode D2 being used to distinguish changes in the voltage drop resulting from the operation of SW1 from voltage changes resulting from the operation of SW2 and SW3.

[00176] Figures 14 and 15 illustrate control circuits of surgical devices according to various embodiments. As discussed above in connection with Figure 10, a control circuit may modify characteristics of an interrogation signal transmitted by the generator 102. The characteristics of the interrogation signal, which may uniquely indicate the state or configuration of the control circuit, can be discerned by the generator 102 and used to control aspects of its operation. The control circuit 280 of Figure 14 may be contained in an ultrasonic surgical device (e.g., in handpiece 116 of ultrasonic surgical device 104), and the control circuit 282 of Figure 15 may be contained in an electrosurgical device (e.g., in handpiece 130 of electrosurgical device 106).

[00177] Referring to Figure 14, control circuit 280 may be connected to the generator 102 to receive an interrogation signal (e.g., a bipolar interrogation signal at 2kHz) from the signal conditioning circuit 202 (e.g., from generator terminals HS and SR (Figure 10) via a conductive pair of cable 112). The control circuit 280 may comprise a first switch SW1 in series with a first diode D1 to define a first branch, and a second switch SW2 in series with a second diode D2 to define a second branch. The first and second branches may be connected in parallel such that the forward conduction direction of D2 is opposite that of D1. The interrogation signal may be applied across both branches. When both SW1 and SW2 are open, the control circuit 280 may define an open circuit. When SW1 is closed and SW2 is open, the interrogation signal may undergo half-wave rectification in a first direction (e.g., positive half of interrogation signal

blocked). When SW1 is open and SW2 is closed, the interrogation signal may undergo half-wave rectification in a second direction (e.g., negative half of interrogation signal blocked). When both SW1 and SW2 are closed, no rectification may occur. Accordingly, based on the different characteristics of the interrogation signal corresponding to the different states of SW1 and SW2, the state or configuration of the control circuit 280 may be discerned by the generator 102 based on a voltage signal appearing across the inputs of the control circuit 280 (e.g., as measured by an ADC of the signal conditioning circuit 202).

[00178] In certain embodiments and as shown in Figure 14, the cable 112 may comprise a data circuit 206. The data circuit 206 may comprise, for example, a non-volatile storage device, such as an EEPROM device. The generator 102 may exchange information with the data circuit 206 via the first data circuit interface 204 as discussed above in connection with Figure 10. Such information may be specific to a surgical device integral with, or configured for use with, the cable 112 and may comprise, for example, a model number, a serial number, a number of operations in which the surgical device has been used, and/or any other type of information. Information may also be communicated from the generator 102 to the data circuit 206 for storage therein, as discussed above in connection with Figure 10. In certain embodiments and with reference to Figures 33E-33G, the data circuit 206 may be disposed in an adaptor for interfacing a specific surgical device type or model with the generator 102.

[00179] Referring to Figure 15, control circuit 282 may be connected to the generator 102 to receive an interrogation signal (e.g., a bipolar interrogation signal at 2kHz) from the signal conditioning circuit 202 (e.g., from generator terminals HS and SR (Figure 10) via a conductive pair of cable 128). The control circuit 282 may comprise series-connected resistors R2, R3 and R4, with switches SW1 and SW2 connected across R2 and R4, respectively. The interrogation signal may be applied across at least one of the series-connected resistors to generate a voltage drop across the control circuit 282. For example, when both SW1 and SW2 are open, the voltage drop may be determined by R2, R3 and R4. When SW1 is closed and SW2 is open, the voltage drop may be determined by R3 and R4. When SW1 is open and SW2 is closed, the voltage drop may be determined by R2 and R3. When both SW1 and SW2 are closed, the voltage drop may be determined by R3. Accordingly, based on the voltage drop across the control circuit 282 (e.g., as measured by an ADC of the signal conditioning circuit 202), the state or configuration of the control circuit 282 may be discerned by the generator 102.

[00180] Figure 16 illustrates one embodiment of a control circuit 280-1 of an ultrasonic surgical device, such as the ultrasonic surgical device 104. The control circuit 280-1, in addition to comprising components of the control circuit 280 of Figure 14, may comprise a data circuit

284 having a data storage element 286. In certain embodiments, the data storage element 286, and possibly other components of the data circuit 284, may be contained in the instrument (e.g., instrument 124) of the ultrasonic surgical device, with other components of the control circuit 280-1 (e.g., SW1, SW2, D1, D2, D3, D4, C1) being contained in the handpiece (e.g., handpiece 116). In certain embodiments, the data storage element 286 may be a single-wire bus device (e.g., a single-wire protocol EEPROM), or other single-wire protocol or local interconnect network (LIN) protocol device. In one embodiment, for example, the data storage element 286 may comprise a Maxim DS28EC20 1-Wire® EEPROM, available from Maxim Integrated Products, Inc., Sunnyvale, CA.

[00181] In certain embodiments, the generator 102 may be configured to communicate with the data circuit 284, and, in particular, with the data storage element 286, via the second data circuit interface 210 (Figure 10) and the conductive pair of the cable 112. In particular, the frequency band of the communication protocol used to communicate with the data circuit 284 may be higher than the frequency band of the interrogation signal. In certain embodiments, for example, the frequency of the communication protocol for the data storage element 286 may be, for example, 200 kHz or a significantly higher frequency, whereas the frequency of the interrogation signal used to determine the different states of SW1 and SW2 may be, for example, 2 kHz. Accordingly, the value of capacitor C1 of the data circuit 284 may be selected such that the data storage element 286 is “hidden” from the relatively low frequency of the interrogation signal while allowing the generator 102 to communicate with the data storage element 286 at the higher frequency of the communication protocol. A series diode D3 may protect the data storage element 286 from negative cycles of the interrogation signal, and a parallel Zener diode D4 may limit the voltage supplied to the data storage element 286 to a suitable operating range (e.g., 3.3-5V). When in the forward conduction mode, D4 may also clamp negative cycles of the interrogation signal to ground.

[00182] As explained above in connection with Figure 10, the data circuit 284, and, in particular, the data storage element 286, may store information pertaining to the particular surgical instrument with which it is associated. Such information may be retrieved by the generator 102 and include, for example, a model number, a serial number, a number of operations in which the surgical instrument has been used, and/or any other type of information. Additionally, any type of information may be communicated from the generator 102 to the data circuit 284 for storage in the data storage element 286. Such information may comprise, for example, an updated number of operations in which the instrument has been used and/or dates and/or times of its usage. Moreover, because the different types of communications between

the generator 102 and the surgical device may be frequency-band separated, the presence of the data storage element 286 may be “invisible” to generators that do not have the requisite data reading functionality, thus enabling backward compatibility of the surgical device.

[00183] In certain embodiments and as shown in Figure 17, the data circuit 284-1 may comprise an inductor L1 to provide isolation of the data storage element 286 from the states of SW1 and SW2. The addition of L1 may additionally enable use of the data circuit 284-1 in electrosurgical devices. Figure 18, for example, illustrates one embodiment of a control circuit 282-1 that combines the control circuit 282 of Figure 15 with the data circuit 284-1 of Figure 17.

[00184] In certain embodiments, a data circuit may comprise one or more switches to modify one or more characteristics (e.g., amplitude, rectification) of an interrogation signal received by the data circuit such that a state or configuration of the one or more switches is uniquely discernable based on the one or more characteristics. Figure 19, for example, illustrates one embodiment of a control circuit 282-2 in which the data circuit 284-2 comprises a switch SW3 connected in parallel with D4. An interrogation signal may be communicated from the generator 102 (e.g., from the signal conditioning circuit 202 of Figure 10) at a frequency sufficient for the interrogation signal to be received by the data circuit 284-2 via C1 but blocked from other portions of the control circuit 282-2 by L1. In this way, one or more characteristics of a first interrogation signal (e.g., a bipolar interrogation signal at 25 kHz) may be used to discern the state of SW3, and one or more characteristics of a second interrogation signal at a lower frequency (e.g., a bipolar interrogation signal at 2 kHz) may be used to discern the states of SW1 and SW2. Although the addition of SW3 is illustrated in connection with the control circuit 282-2 in an electrosurgical device, it will be appreciated that SW3 may be added to a control circuit of an ultrasonic surgical device, such as, for example, the control circuit 280-2 of Figure 17.

[00185] Additionally, it will be appreciated that switches in addition to SW3 may be added to a data circuit. As shown in Figures 20 and 21, for example, embodiments of the data circuit 284-3 and 284-4, respectively, may comprise a second switch SW4. In Figure 20, voltage values of Zener diodes D5 and D6 may be selected such that their voltage values sufficiently differ to allow reliable discrimination of the interrogation signal in the presence of noise. The sum of the voltages values of D5 and D6 may be equal to or less than the voltage value of D4. In certain embodiments, depending upon the voltages values of D5 and D6, it may be possible to eliminate D4 from the embodiment of the data circuit 284-3 illustrated in Figure 20.

[00186] In certain cases, the switches (e.g., SW1-SW4) may impede the ability of the generator 102 to communicate with the data storage element 286. In one embodiment, this

issue may be addressed by declaring an error if the states of the switches are such that they will interfere with communication between the generator 102 and the data storage element 286. In another embodiment, the generator 102 may only permit communication with the data storage element 286 when determined by the generator 102 that the states of the switches will not interfere with the communication. Because the states of the switches may be unpredictable to an extent, the generator 102 may make this determination on a recurring basis. The addition of L1 in certain embodiments may prevent interference caused by switches external to the data circuit (e.g., SW1 and SW2). For switches contained within the data circuit (e.g., SW3 and SW4), isolation of the switches by frequency band separation may be realized by the addition of a capacitor C2 having a capacitance value significantly smaller than C1 (e.g., $C2 \ll C1$). Embodiments of data circuits 284-5, 284-6, 284-7 comprising C2 are shown in Figures 22-24, respectively.

[00187] In any of the embodiments of Figures 16-24, depending on the frequency response characteristics of D4, it may be desirable or necessary to add a fast diode in parallel with D4 and pointing in the same direction.

[00188] Figure 25 illustrates one embodiment of a control circuit 280-5 in which communication between the generator 102 and a data storage element is implemented using an amplitude-modulated communication protocol (e.g., amplitude-modulated 1-Wire® protocol, amplitude-modulated LIN protocol). Amplitude modulation of the communication protocol on a high-frequency carrier (e.g., 8 MHz or higher) substantially increases frequency band separation between low frequency interrogation signals (e.g., interrogation signals at 2 kHz) and the native “baseband” frequency of the communication protocol used in the embodiments of Figures 16-24. The control circuit 280-5 may be similar to the control circuit 280-1 of Figure 16, with the data circuit 288 comprising an additional capacitor C3 and resistor R5, which, in conjunction with D3, demodulate the amplitude-modulated communication protocol for receipt by the data storage element 286. As in the embodiment of Figure 16, D3 may protect the data storage element 286 from negative cycles of the interrogation signal, and D4 may limit the voltage supplied to the data storage element 286 to a suitable operating range (e.g., 3.3-5V) and clamp negative cycles of the interrogation signal to ground when in the forward conduction mode. The increased frequency separation may allow C1 to be somewhat small relative to the embodiments of Figures 16-24. Additionally, the higher frequency of the carrier signal may also improve noise immunity of communications with the data storage element because it is further removed from the frequency range of electrical noise that may be generated by other surgical devices used in the same operating room environment. In certain embodiments, the relatively

high frequency of the carrier in combination with the frequency response characteristics of D4 may make it desirable or necessary to add a fast diode in parallel with D4 and pointing in the same direction.

[00189] With the addition of an inductor L1 to prevent interference with data storage element 286 communications caused by switches external to the data circuit 288 (e.g., SW1 and SW2), the data circuit 288 may be used in control circuits of electrosurgical instruments, as shown in the embodiment of the data circuit 288-1 of Figure 26.

[00190] With the exception of C2 and R3, and the more likely need for D7, the embodiments of Figures 25 and 26 are similar to the “baseband” embodiments of Figures 16-24. For example, the manner in which switches may be added to the data circuits of Figures 19-21 is directly applicable to the embodiments of Figures 25 and 26 (including the possibility of eliminating D4 from the modulated-carrier equivalent of the Figure 20). Modulated-carrier equivalents of the data circuits embodied in Figures 22-24 may simply require the addition of an appropriately-sized inductor L2 in series with C2 in order to isolate the interrogation frequency for the additional switches (e.g., SW3, SW4) to an intermediate frequency band between the carrier frequency and the lower interrogation frequency for switches external to the data circuit. An embodiment of one such data circuit 282-7 is shown in Figure 27.

[00191] In the embodiment of Figure 27, any interference with the generator’s ability to communicate with the data storage element 286 caused by states of SW1 and SW2 may be addressed as described above in connection with the embodiments of Figures 19-24. For example, the generator 102 may declare an error if switch states will prevent communication, or the generator 102 may only permit communication when determined by the generator 102 that the switch states will not cause interference.

[00192] In certain embodiments, the data circuit may not comprise a data storage element 286 (e.g., an EEPROM device) to store information. Figures 28-32 illustrate embodiments of control circuits that utilize resistive and/or inductive elements to modify one or more characteristics of an interrogation signal (e.g., amplitude, phase) such that a state or configuration of the control circuit may be uniquely discerned based on the one or more characteristics.

[00193] In Figure 28, for example, the data circuit 290 may comprise an identification resistor R1, with the value of C1 selected such that R1 is “hidden” from a first low frequency interrogation signal (e.g., an interrogation signal at 2kHz) for determining the states of SW1 and SW2. By measuring the voltage and/or current (e.g., amplitude, phase) at the inputs of the control circuit 280-6 resulting from a second interrogation signal within a substantially higher

frequency band, the generator 102 may measure the value of R1 through C1 in order to determine which of a plurality of identification resistors is contained in the instrument. Such information may be used by the generator 102 to identify the instrument, or a particular characteristic of the instrument, so that control and diagnostic processes may be optimized. Any interference with the generator's ability to measure R1 caused by states of SW1 and SW2 may be addressed by declaring an error if switch states will prevent measurement, or by maintaining the voltage of the second higher-frequency interrogation signal below the turn-on voltages of D1 and D2. Such interference may also be addressed by adding an inductor in series with the switch circuitry (L1 in Figure 29) to block the second higher-frequency interrogation signal while passing the first, lower-frequency interrogation signal. The addition of an inductor in this manner may also enable the use of the data circuit 290 in control circuits of electrosurgical instruments, as shown in the embodiment of the data circuit 290-2 of Figure 30.

[00194] In certain embodiments, multiple capacitors C1 for allowing interrogation at multiple frequencies could be used to differentiate between a larger number of distinct R1 values for a given signal-to-noise ratio, or for a given set of component tolerances. In one such embodiment, inductors may be placed in series with all but the lowest value of C1 to create specific pass bands for different interrogation frequencies, as shown in the embodiment of the data circuit 290-3 in Figure 31.

[00195] In embodiments of control circuits based on the control circuit 280 of Figure 14, identification resistors may be measured without the need for frequency band separation. Figure 32 illustrates one such embodiment, with R1 selected to have a relatively high value.

[00196] Figures 33D-33I illustrate embodiments of multi-conductor cables and adaptors that may be used to establish electrical communication between the generator 102 and a handpiece of a surgical device. In particular, the cables may transmit the generator drive signal to surgical device and enable control-based communications between the generator 102 and a control circuit of the surgical device. In certain embodiments, the cables may be integrally formed with the surgical device or configured for removable engagement by a suitable connector of the surgical device. Cables 112-1, 112-2 and 112-3 (Figures 33E-33G, respectively) may be configured for use with an ultrasonic surgical device (e.g., ultrasonic surgical device 104), and cable 128-1 (Figure 33D) may be configured for use with an electrosurgical device (e.g., electrosurgical device 106). One or more of the cables may be configured to connect directly with the generator 102, such as cable 112-1, for example. In such embodiments, the cable may comprise a data circuit (e.g., data circuit 206) for storing information pertaining to the particular surgical device with which it is associated (e.g., a model

number, a serial number, a number of operations in which the surgical device has been used, and/or any other type of information). In certain embodiments, one or more of the cables may connect to the generator 102 via an adaptor. For example, cables 112-2 and 112-3 may connect to the generator 102 via a first adaptor 292 (Figure 33I), and cable 128-1 may connect to the generator 102 via a second adaptor 294 (Figure 33H). In such embodiments, a data circuit (e.g., data circuit 206) may be disposed in the cable (e.g., cables 112-2 and 112-3) or in the adaptor (e.g., second adaptor 294).

[00197] In various embodiments, the generator 102 may be electrically isolated from the surgical devices 104, 106 in order to prevent undesired and potentially harmful currents in the patient. For example, if the generator 102 and the surgical devices 104, 106 were not electrically isolated, voltage provided to the devices 104, 106 via the drive signal could potentially change the electrical potential of patent tissue being acted upon by the device or devices 104, 106 and, thereby, result in undesired currents in the patient. It will be appreciated that such concerns may be more acute when the using a ultrasonic surgical device 104 that is not intended to pass any current through tissue. Accordingly, the remainder of the description of active cancellation of leakage current is described in terms of a ultrasonic surgical device 104. It will be appreciated, however, that the systems and methods described herein may be applicable to electrosurgical devices 106 as well.

[00198] According to various embodiments, an isolation transformer, such as the isolation transformer 156, may be used to provide electrical isolation between the generator 102 and the surgical device 104. For example, the transformer 156 may provide isolation between the non-isolated stage 154 and the isolated stage 152 described above. The isolated stage 154 may be in communication with the surgical device 104. The drive signal may be provided by the generator 102 (e.g., the generator module 108) to the primary winding 164 of the isolation transformer 156 and provided to the surgical device 104 from the secondary winding 158 of the isolation transformer. Considering the non-idealities of real transformers, however, this arrangement may not provide complete electrical isolation. For example, a real transformer may have stray capacitance between the primary and secondary windings. The stray capacitance may prevent complete electrical isolation and allow electrical potential present on the primary winding to affect the potential of the secondary winding. This may result in leakage currents within the patient.

[00199] Contemporary industry standards, such as the International Electrotechnical Commission (IEC) 60601-1 standard limit allowable patient leakage current to 10 μ A or less. Leakage current may be passively reduced by providing a leakage capacitor between the

secondary winding of the isolation transformer and ground (e.g., earth ground). The leakage capacitor may operate to smooth changes in patient-side potential coupled from the non-isolated side via the stray capacitance of the isolation transformer and thereby reduce leakage current. As the voltage, current, power and/or frequency of the drive signal provided by the generator 102 increase, however, the leakage current may also increase. In various embodiments, induced leakage current may increase beyond the capability of a passive leakage capacitor to keep it below 10 μ A and/or other leakage current standards.

[00200] Accordingly, various embodiments are directed to systems and methods for actively cancelling leakage current. Figure 34 illustrates one embodiment of a circuit 800 for active cancellation of leakage current. The circuit 800 may be implemented as a part of or in conjunction with the generator 102. The circuit may comprise an isolation transformer 802 having a primary winding 804 and a secondary winding 806. The drive signal 816 may be provided across the primary winding 804, generating an isolated drive signal across the secondary winding 806. In addition to the isolated drive signal, stray capacitance 808 of the isolation transformer 802 may couple some component of the potential of the drive signal relative to ground 818 to the secondary winding 806 on the patient side.

[00201] A leakage capacitor 810 and active cancellation circuit 812 may be provided, as shown, connected between the secondary winding 806 and ground 818. The active cancellation circuit 812 may generate an inverse drive signal 814 that may be about 180° out of phase with the drive signal 816. The active cancellation circuit 812 may be electrically coupled to the leakage capacitor 810 to drive the leakage capacitor to a potential that, relative to ground 818, is about 180° out of phase with the drive signal 816. Accordingly, electrical charge on the patient-side secondary winding 806 may reach ground 818 via the leakage capacitor 810 instead of through the patient, reducing leakage current. According to various embodiments, the leakage capacitor 810 may be designed to meet adequate, industry, government and/or design standards for robustness. For example, the leakage capacitor 810 may be a Y-type capacitor complying with the IEC 60384-14 standard and/or may comprise multiple physical capacitors in series.

[00202] Figure 35 illustrates one embodiment of a circuit 820 that may be implemented by the generator 102 to provide active cancellation of leakage current. The circuit 820 may comprise a generator circuit 824 and a patient-side circuit 822. The generator circuit 824 may generate and/or modulate the drive signal, as described herein. For example, in some embodiments, the generator circuit 824 may operate similar to the non-isolated stage 154

described above. Also, for example, the patient-side circuit 822 may operate similar to the isolated state 152 described above.

[00203] Electrical isolation between the generator circuit 824 and the patient-side circuit 822 may be provided by an isolation transformer 826. The primary winding 828 of the isolation transformer 826 may be coupled to the generator circuit 824. For example, the generator circuit 824 may generate the drive signal across the primary winding 828. The drive signal may be generated across the primary winding 828 according to any suitable method. For example, according to various embodiments, the primary winding 828 may comprise a center tap 829 that may be held to a DC voltage (e.g., 48 volts). The generator circuit 824 may comprise output stages 825, 827 that are, respectively, coupled to the other ends of the primary winding 828. Output stages 825, 827 may cause currents corresponding to the drive signal to flow in the primary winding 828. For example, positive portions of the drive signal may be realized when the output stage 827 pulls its output voltage lower than the center tap voltage, causing the output stage 827 to sink current from across the primary winding 828. A corresponding current may be induced in the secondary winding 830. Likewise, negative portions of the drive signal may be implemented when the output stage 825 pulls its output voltage lower than the center tap voltage, causing the output stage 825 to sink an opposite current across the primary winding 828. This may induce a corresponding, opposite current in the secondary winding 830. The patient-side circuit 822 may perform various signal conditioning and/or other processing to the isolated drive signal, which may be provided to a device 104 via output lines 821, 823.

[00204] An active cancellation transformer 832 may have a primary winding 834 and a secondary winding 836. The primary winding 834 may be electrically coupled to the primary winding 828 of the isolation transformer 826 such that the drive signal is provided across the winding 834. For example, the primary winding 834 may comprise two windings 843, 845. A first end 835 of the first winding 845 and a first end 839 of the second winding 843 may be electrically coupled to the center tap 829 of the winding 828. A second end 841 of the first winding 845 may be electrically coupled to the output stage 827, while a second end 837 of the second winding 843 may be electrically coupled to the output stage 825. The secondary winding 836 of the cancellation transformer 832 may be coupled to ground 818 and to a first electrode of a cancellation capacitor 840. The other electrode of the cancellation capacitor 840 may be coupled to the output line 823. An optional load resistor 838 may also be electrically coupled in parallel across the secondary winding 836.

[00205] According to various embodiments, the secondary winding 836 of the active cancellation transformer may be wound and/or wired to the other components 840, 838, 818,

such that its polarity is opposite the polarity of the primary winding 834. For example, an inverse drive signal may be induced across the secondary winding 836. Relative to ground 818, the inverse drive signal may be 180° out of phase with the drive signal provided across the primary winding 834 of the active cancellation transform 832. In conjunction with the load resistor 838, the secondary winding 836 may provide the inverse drive signal at the cancellation capacitor 840. Accordingly, charge causing leakage potential appearing at the patient-side circuit 822 due to the drive signal may be drawn to the cancellation capacitor 840. In this way, the capacitor 840, secondary winding 836 and load resistor 838 may sink potential leakage current to ground 818, minimizing patient leakage current.

[00206] According to various embodiments, the parameters of the components 832, 838, 840 may be selected to maximize leakage current cancellation and, in various embodiments, to lessen electromagnetic emissions. For example, the active cancellation transformer 832 may be made from materials and according to a construction that allows it to match the frequency, temperature, humidity and other characteristics of the isolation transformer 826. Other parameters of the active transformer 832 (e.g., number of turns, turn ratios, etc.) may be selected to achieve a balance between minimizing output-induced current, electromagnetic (EM) emissions and leakage current due to applied external voltage. For example, the circuit 820 may be configured to meet the IEC 60601 or other suitable industry or government standards. The value of the load resistor 838 may be similarly chosen. In addition, the parameters of the cancellation capacitor 840 (e.g., capacitance, etc.) may be selected to match, as well as possible, the characteristics of the stray capacitances responsible for the inducing leakage current.

[00207] Figure 36 illustrates an alternate embodiment of a circuit 842 that may be implemented by the generator 102 to provide active cancellation of leakage current. The circuit 842 may be similar to the circuit 820, however, the secondary winding 836 of the active cancellation transformation 832 may be electrically coupled to the output line 823. The cancellation capacitor 823 may be connected in series between the secondary winding 836 and ground 818. The circuit 842 may operate in a manner similar to that of the circuit 820. According to various embodiments, (e.g., when the active cancellation transformer 832 is a step-up transformer), the total working voltage, for example, as defined in IEC 60601-1, may be minimized.

[00208] Figure 37 illustrates an alternate embodiment of a circuit 844 that may be implemented by the generator 102 to provide active cancellation of leakage current. The circuit 844 may omit the active cancellation transformer 832 and replace it with a second secondary

winding 846 of the isolation transformer 826. The second secondary winding 846 may be connected to the output line 823. The cancellation capacitor 840 may be connected in series between the second secondary winding 846 and ground. The second secondary winding may be wound and or wired with a polarity opposite that of the primary winding 828 and the secondary winding 830. Accordingly, when the drive signal is present across the primary winding 828, the inverse drive signal, as described above, may be present across the secondary winding 846. Accordingly, the circuit 844 may cancel leakage current in a manner similar to that described above with respect to the circuits 820 and 842. Omitting the active cancellation transformer 832, as shown in circuit 844, may reduce part count, cost and complexity.

[00209] Figure 38 illustrates yet another embodiment of a circuit 848 that may be implemented by the generator 102 to provide active cancellation of leakage current. The circuit 848 may be configured to cancel extraneous currents in the patient side circuit 822 due to capacitive coupling, as described above, as well as other external effects such as, for example, frequency-specific effects (e.g., 60 Hz or other frequency noise from power supplies), path effects, load effects, etc. Instead of being electrically coupled to ground 818, the cancellation capacitor 840, as shown in the circuit 848, may be coupled to an correction control circuit 851. The circuit 851 may comprise a digital signal processor (DSP) 850 or other processor. The DSP 850 may receive inputs 858 (e.g., via an analog-to-digital converter). The inputs 858 may be values tending to indicate external effects that may cause additional leakage current. Examples of such inputs may be, for example, power supply parameters, load data such as impedance, impedance or other values describing the path from the circuit 848 to the device 104, etc. Based on the inputs 858, the DSP 85 may derive a cancellation potential that, when provided to the cancellation capacitor 840, may cancel patient-side currents due to the external effects. The cancellation potential may be provided, digitally, to digital-to-analog converter 852, which may provide an analog version of the cancellation potential to the cancellation capacitor 840. Accordingly, the voltage drop across the cancellation capacitor 840 may be a function of the inverse drive signal, present across the second secondary winding 846 and the cancellation potential found by the circuit 851.

[00210] The circuit 848 is shown with the active cancellation transformer 832 omitted and the capacitor 840 and second secondary winding 846 in the configuration of the circuit 844. It will be appreciated, however, that the correction control circuit 851 may be utilized in any of the configurations described herein (e.g., 820, 842, 844, etc.). For example, the correction control circuit 851 may be substituted for ground 818 in any of the circuits 820, 842, 844.

[00211] Figure 39 illustrated an embodiment of a circuit 860 that may be implemented by the generator 102 to provide cancellation of leakage current. According to the circuit 860, the cancellation capacitor 840 may be connected between the primary winding 828 of the isolation transformer 826 and the output line 823 (e.g., the common output line). In this way, the inverse of the drive signal may appear across the cancellation capacitor 840, bringing about a similar leakage current cancellation effect to those described above.

[00212] Figure 40 illustrates another embodiment of a circuit 862 that may be implemented by the generator 102 to provide cancellation of leakage current. The circuit 862 may be similar to the circuit 860 with the exception that the cancellation capacitor may be connected between the output line 823 (e.g., the common output line) and two additional capacitors 864, 866. Capacitor 864 may be connected between the cancellation capacitor 840 and the primary winding 828 of the isolation transformer 826. Capacitor 866 may be connected between the cancellation capacitor 840 and ground 818. The combination of the capacitors 864, 866 may provide a radio frequency (RF) path to ground that may enhance the RF performance of the generator 102 (e.g., by decreasing electromagnetic emissions).

[00213] A surgical generator, such as the generator 102 schematically illustrated in Figure 10, for example, may be electrically coupled to a variety of surgical instruments. The surgical instruments may include, for example, both RF-based instruments and ultrasonic-based devices. Figure 41 illustrates a receptacle and connector interface 900 in accordance with one non-limiting embodiment. In one embodiment, the interface 900 comprises a receptacle assembly 902 and a connector assembly 920. The connector assembly 920 may be electrically coupled to the distal end of a cable 921 that is ultimately connected to a handheld surgical instrument, for example. Figure 59 illustrates a surgical generator 1050 in accordance with one non-limiting embodiment. The surgical generator 1050 may comprise a surgical generator body 1052 that generally includes the outer shell of the generator. The surgical body 1052 may define an aperture 1054 for receiving a receptacle assembly, such as the receptacle assembly 1058 illustrated in Figure 59. Referring now to Figures 41 and 59, the receptacle assembly 902 may comprise a seal 906 to generally prevent fluid ingress into the surgical generator 1050 by way of the aperture 1054. In one embodiment, the seal 906 is an epoxy seal.

[00214] Figure 42 is an exploded side view of the receptacle assembly 902 in accordance with one non-limiting embodiment. The receptacle assembly 902 may include a variety of components, such as a magnet 212, for example. The receptacle assembly 902 may also comprise a plurality of sockets 908 that may be arranged in a generally circular formation, or any other suitable formation. Figure 48 is an enlarged view of a socket 908 in accordance with

one non-limiting embodiment. In one embodiment, the socket 908 is bifurcated and the receptacle assembly 902 includes nine bifurcated sockets 908, while greater or few sockets may be utilized in other embodiments. Each of the sockets 908 may define an inner cavity 910 for receiving electrically conductive pins, as discussed in more detail below. In some embodiments, various sockets 908 will be mounted within the receptacle assembly 902 at different elevations such that certain sockets are contacted prior to other sockets when a connector assembly is inserted into the receptacle assembly.

[00215] Figure 43 is an exploded side view of the connector assembly 920 in accordance with one non-limiting embodiment. The connector assembly 920 may comprise, for example, a connector body 922 that includes an insertion portion 924 that is sized to be received by the receptacle assembly 902, as described in more detail below. The connector assembly 920 may comprise a variety of other components, such as a ferrous pin 926, a circuit board 928, and a plurality of electrically conductive pins 930. As shown in Figure 54, the ferrous pin 926 may be cylindrical. In other embodiments, the ferrous pin 926 may be other shapes, such as rectangular, for example. The ferrous pin 926 may be steel, iron, or any other magnetically compatible material that is attracted to magnetic fields or that may be magnetizable. The ferrous pin 926 may also have a shoulder 927, or other type of laterally extending feature. Referring now to Figure 55, the electrical conductive pins 930 may be affixed to and extend from the circuit board 928. The circuit board 928 may also include device identification circuitry, such as the circuits illustrated in Figures 33E-33G, for example. Thus, in various embodiments, the circuit board 928 may carry EEPROM, resistors, or any other electrical components. In some embodiments, portions of the circuit board 928 may be potted, or otherwise encapsulated, to improve the sterility of the surgical device and assist in water resistance.

[00216] Referring again to Figure 43, the connector assembly 920 may also include a strain relief member 932. As shown in Figure 56, the strain relief member 932 generally accepts cable loading to prevent that loading from being applied to the circuit board 928 and/or the sockets 908. In some embodiments, the strain relief member 932 may include an alignment notch 934 to aid in assembly. Referring again to Figure 43, the connector assembly 920 may also include a boot 936 that is coupled to the connector body 922. Figure 57 illustrates the boot 936 in accordance with one non-limiting embodiment. The boot 936 may generally serve as bend relief for an associated cable and assist in sealing the connector assembly 920. In some embodiments, the boot 936 may snap onto the connector body 922. For autoclave applications, the boot 936 may be an overmolded component. In other embodiments, other attachment techniques may be used, such as adhesives or spin welding, for example.

[00217] Figure 44 is a perspective view of the receptacle assembly 902 shown in Figure 41. Figure 45 is an exploded perspective view of the receptacle assembly 902. Figure 46 is a front elevation view of the receptacle assembly 902. Figure 47 is a side elevation view of the receptacle assembly 902. Referring to Figures 44-47, the receptacle assembly 902 may comprise a flange 950. The flange 950 may have an inner wall 952 and an outer wall 954. Spanning the inner wall 952 and the outer wall 954 is a flange surface 956. The inner wall 952 may include at least one curved portion and at least one linear portion. The inner wall 952 of the flange 950 defines a cavity 960 having a unique geometry. In one embodiment, the cavity 960 is defined by about 270 degrees of a circle and two linear segments that are tangential to the circle and intersect to form an angle Θ . In one embodiment, angle Θ is about 90 degrees. In one embodiment, a central protruding portion 962 having an outer periphery 964 is positioned in the cavity 960. The central protruding portion 962 may have a central surface 966 that defines a recess 968. The magnet 912 (Figure 42) may be positioned proximate the recess 968. As illustrated, the sockets 908 may be positioned through apertures 972 defined by the central surface 966 of the central protruding portion 962. In embodiments utilizing a circular arrangement of sockets 908, the magnet 912 may be positioned internal to the circle defined by the sockets. The receptacle body 904 may also define a rear recess 976 (Figure 47). The rear recess 976 may be sized to receive the seal 906. The flange face 966 may be slanted at an angle β (Figure 47). As illustrated in Figure 61, a face of the body 1052 of the surgical generator 1050 also may be slanted at the angle β as well.

[00218] Figure 49 is a perspective view of the connector assembly 920 and Figure 50 is an exploded perspective view of the connector assembly 920. Figure 51 is a side elevation view of the connector body 922 with Figures 52 and 53 illustrating perspective views of the distal and proximal ends, respectively, of the connector body 922. Referring now to Figures 49-53, connector body 922 may have a flange 980. The flange 980 may comprise at least one curved portion and at least one linear portion.

[00219] The adapter assemblies 1002 and 1004 may comprise substantially the similar components that are contained by the connector body 922 (Figure 50). For example, the adapter assemblies 1002 and 1004 may each house a circuit board with device identification circuitry. The adapter assemblies 1002 and 1004 may also each house one of a ferrous pin and a magnet to aid in the connection with the surgical generator. An outer wall 982 of the flange 980 may generally be shaped similarly to the inner wall 952 of the receptacle assembly 902 (Figure 46). An inner wall 984 of the flange 980 may be shaped similarly to the outer periphery 964 of the central protruding portion 962. The connector body 922 may also have a wall 988

that includes a plurality of apertures 990. The apertures 990 may be sized to receive the electrically conductive pins 930 and the ferrous pin 926. In one embodiment, the shoulder 927 of the ferrous pin 926 is sized so that it can not pass through the aperture 990. In some embodiments, the ferrous pin 926 may be able to translate with respect to the wall 988. When assembled, the shoulder 927 of the ferrous pin 926 may be positioned intermediate the wall 988 and the circuit board 928. The ferrous pin 926 may be positioned such that it encounters the magnetic field of the magnet 912 when the connector assembly 920 is inserted into the receptacle assembly 902. In some embodiments, a proper connection will be denoted by an audible click when the ferrous pin 926 translates to the wall 988 and strikes the magnet 912. As is to be appreciated, various components may be positioned intermediate the ferrous pin 926 and the magnet 912, such as a washer, for example, to reduce incidental wear to the interfacing components. Additionally, in some embodiments the magnet 912 may be coupled to the connector assembly 920 and the ferrous pin 926 may be coupled to the receptacle assembly 902.

[00220] Figure 58 illustrates two adaptor assemblies 1002 and 1004 in accordance with various non-limiting embodiments. The adaptor assemblies 1002 and 1004 allow of connector assemblies having various geometries to be electrically coupled to a receptacle assembly of a surgical generator. Adaptor assembly 1002 is configured to accommodate a surgical instrument having connector assembly 1006 and adaptor assembly 1004 is configured to accommodate a surgical instrument having a connector assembly 1008. In one embodiment, the connector assembly 1006 is associated with an RF-based surgical device via a cable 1060 and the connector assembly 1008 is associated with an ultrasonic-based device via a cable 1062. As is to be appreciated, other embodiments of adaptor assemblies may accommodate surgical instruments have connector assemblies different than those illustrated in Figure 58. Figure 59 illustrates the adaptor assembly 1002 after being inserting into the receptacle assembly 1058 of a surgical generator 1050 in accordance with one non-limiting embodiment. Figure 60 illustrates the connector assembly 1006 after being inserted into the adaptor assembly 1002 and therefore electrically coupled to the surgical generator 1050. Similarly, Figure 61 illustrates the adaptor assembly 1004 after being inserted into the receptacle assembly 1058 of a surgical generator 1050 in accordance with one non-limiting embodiment. Figure 62 illustrates the connector assembly 1008 after being inserted into the adaptor assembly 1004. Accordingly, while connector assemblies 1006 and 1008 each having different geometries, both may be used with the surgical generator 1050.

[00221] Referring to Figures 58-62, in one embodiment, the adaptor assembly 1002 has a distal portion 1010 that comprises a flange 1012. The flange 1012 is configured to be inserted into the receptacle assembly 1058 of the surgical instrument 1050 and may be similar to the flange 980 illustrated in Figure 52, for example. Any number of electrically conductive pins, or other connection components, may be positioned in the distal portion to engage the receptacle assembly 1058. In one embodiment, the adaptor assembly 1002 also has a proximal portion 1014 that defines a cavity 1016. The cavity 1016 may be configured to accept a particular connector assembly, such as connector assembly 1006. As is to be appreciated, the proximal portion 1014 may be configured appropriately based on the type of connector assembly with which it will be used. In one embodiment, the adaptor assembly 1006 has a distal portion 1020 that comprises a flange 1022. The flange 1022 is configured to be inserted into the receptacle assembly 1058 of the surgical instrument 1050 and may be similar to the flange 980 illustrated in Figure 52, for example. The adaptor assembly 1004 also has a proximal portion 1024 that defines a cavity 1026. In the illustrated embodiment, the central portion 1028 is positioned in the cavity 1026 and is configured to accept the connector assembly 1008.

[00222] Figure 63 illustrates a perspective view of a back panel 1100 of a generator 1102 in accordance with one non-limiting embodiment. The generator 1102 may be similar to generator 102 illustrated in Figure 10, for example. The back panel 1100 may comprise various input and/or output ports 1104. The back panel 1100 may also comprise an electronic paper display device 1106. The electronic paper display device 1106 may be based on electrophoresis in which an electromagnetic field is applied to a conductive material such that the conductive material has mobility. Micro particles having conductivity are distributed between thin-type flexible substrates, and positions of the micro particles (or toner particles) are changed due to the change of the polarities of an electromagnetic field, whereby data is displayed. The technical approach to realize the electronic paper may be accomplished using any suitable technique, such as liquid crystals, organic electro luminescence (EL), reflective film reflection-type display, electrophoresis, twist balls, or mechanical reflection-type display, for example. Generally, electrophoresis is a phenomenon in which, when particles are suspended in a medium (i.e., a dispersion medium), the particles are electrically charged, and, when an electric field is applied to the charged particles, the particles move to an electrode having opposite charge through the dispersion medium. Further discussion regarding electronic paper display devices may be found in U.S. Patent Number 7,751,115 entitled ELECTRONIC PAPER DISPLAY DEVICE, MANUFACTURING METHOD AND DRIVING METHOD THEREOF, the entirety of which is incorporated by reference.

[00223] Figure 64 illustrates the back panel 1110 illustrated in Figure 63. Figures 65 and 66 provide enlarged views of the back panel 1110. Referring to Figures 64-66, the electronic paper display device 1106 may display a variety of information, such a serial number, a part number, patent numbers, warning labels, port identifiers, instructions, vendor information, service information, manufacturer information, operational information, or any other type of information. In one embodiment, the information displayed on the electronic paper display device 1106 may be changed or updated through connecting a computing device to a communication port (e.g., a USB port) of the generator 1102.

[00224] As shown in Figure 66, in some embodiments, the back panel 1100 may comprise an interactive portion 1108. In one embodiment, the interactive portion 1108 allows a user to input information to the generator 1102 using input devices, such as buttons 1110. The interactive portion 1108 may also display information that is simultaneously displayed on a front panel (not shown) of the generator 1102.

[00225] In a surgical procedure utilizing an ultrasonic surgical device, such as the ultrasonic surgical device 104, the end effector 126 transmits ultrasonic energy to tissue brought into contact with the end effector 126 to realize cutting and sealing action. The application of ultrasonic energy in this manner may cause localized heating of the tissue. Monitoring and controlling such heating may be desirable to minimize unintended tissue damage and/or to optimize the effectiveness of the cutting and sealing action. Direct measurement of ultrasonic heating requires temperature sensing devices in or near the end effector 126. Although sensor-based measurements of ultrasonic heating is technically feasible, design complexity and other considerations may make direct measurement impractical. Various embodiments of the generator 102 may address this problem by generating an estimate of temperature or heating resulting from an application of ultrasonic energy.

[00226] In particular, one embodiment of the generator 102 may implement an artificial neural network to estimate ultrasonic heating based on a number of input variables 1218. Artificial neural networks are mathematical models that learn complex, nonlinear relationships between inputs and outputs based on exposure to known input and output patterns, a process commonly referred to as "training." An artificial neural network may comprise a network of simple processing units, or nodes, connected together to perform data processing tasks. The structure of an artificial neural network may be somewhat analogous to the structure of biological neural networks in the brain. When an artificial neural network is presented with an input data pattern, it produces an output pattern. An artificial neural network may be trained for a specific processing task by presentation of large amounts of training data. In this way, the

artificial neural network may modify its structure by changing the “strength” of communication between nodes to improve its performance on the training data.

[00227] Figure 67 illustrates one embodiment of an artificial neural network 1200 for generating an estimated temperature T_{est} resulting from an application of ultrasonic energy using an ultrasonic surgical device, such as the ultrasonic surgical device 104. In certain embodiments, the neural network may be implemented in the processor 174 and/or the programmable logic device 166 of the generator 102. The neural network 1200 may comprise an input layer 1202, one or more nodes 1204 defining a hidden layer 1206, and one or more nodes 1208 defining an output layer 1210. For the sake of clarity, only one hidden layer 1206 is shown. In certain embodiments, the neural network 1200 may comprise one or more additional hidden layers in a cascaded arrangement, with each additional hidden layer having a number of nodes 1204 that may be equal to or different from the number of nodes 1204 in the hidden layer 1206.

[00228] Each node 1204, 1208 in the layers 1202, 1210 may include one or more weight values w 1212, a bias value b 1214, and a transform function f 1216. In Figure 67, the use of different subscripts for these values and functions is intended to illustrate that each of these values and functions may be different from the other values and functions. The input layer 1202 comprises one or more input variables p 1218, with each node 1204 of the hidden layer 1206 receiving as input at least one of the input variables p 1218. As shown in Figure 67, for example, each node 1204 may receive all of the input variables p 1218. In other embodiments, less than all of the input variables p 1218 may be received by a node 1204. Each input variable p 1218 received by a particular node 1204 is weighted by a corresponding weight value w 1212, then added to any other similarly weighted input variables p 1218, and to the bias value b 1214. The transform function f 1216 of the node 1204 is then applied to the resulting sum to generate the node's output. In Figure 67, for example, the output of node 1204-1 may be given as $f_1(n_1)$, where $n_1 = (w_{1,1} \cdot p_1 + w_{1,2} \cdot p_2 + \dots + w_{1,j} \cdot p_j) + b_1$.

[00229] A particular node 1208 of the output layer 1210 may receive an output from one or more of the nodes 1204 of the hidden layer 1206 (e.g., each node 1208 receives outputs $f_1(\cdot), f_2(\cdot), \dots, f_i(\cdot)$ from respective nodes 1204-1, 1204-2, ..., 1204-i in Figure 67), with each received output being weighted by a corresponding weight value w 1212 and subsequently added to any other similarly weighted received outputs, and to a bias value b 1214. The transform function f 1216 of the node 1208 is then applied to the resulting sum to generate the node's output, which corresponds to an output of the neural network 1200 (e.g., the estimated temperature T_{est} in the embodiment of Figure 67). Although the embodiment of the neural

network 1200 in Figure 67 comprises only one node 1208 in the output layer 1210, in other embodiments the neural network 1200 may comprise more than one output, in which case the output layer 1210 may comprise multiple nodes 1208.

[00230] In certain embodiments, the transform function f 1216 of a node 1204, 1208 may be a nonlinear transfer function. In one embodiment, for example, one or more of the transform functions f 1216 may be a sigmoid function. In other embodiments, the transform functions f 1216 may include a tangent sigmoid, a hyperbolic tangent sigmoid, a logarithmic sigmoid, a linear transfer function, a saturated linear transfer function, a radial basis transfer function, or some other type of transfer function. The transform function f 1216 of a particular node 1204, 1208 may be the same as, or different from, a transform function f 1216 in another node 1204, 1208.

[00231] In certain embodiments, the input variables p 1218 received by the nodes 1204 of the hidden layer 1206 may represent, for example, signals and/or other quantities or conditions known or believed to have an effect on the temperature or heating resulting from an application of ultrasonic energy. Such variables may comprise, for example, one or more of: drive voltage output by the generator 102, drive current output by the generator 102, drive frequency of the generator output 102, drive power output by the generator 102, drive energy output by the generator 102, impedance of the ultrasonic transducer 114, and time duration over which ultrasonic energy is applied. Additionally, one or more of the input variables p 1218 may be unrelated to outputs of the generator 102 and may comprise, for example, characteristics of the end effector 126 (e.g., blade tip size, geometry, and/or material) and a particular type of tissue targeted by the ultrasonic energy.

[00232] The neural network 1200 may be trained (e.g., by changing or varying the weight values w 1212, the bias values b 1214, and the transform functions f 1216) such that its output (e.g., estimated temperature T_{est} in the embodiment of Figure 67) suitably approximates a measured dependency of the output for known values of the input variables p 1218. Training may be performed, for example, by supplying known sets of input variables p 1218, comparing output of the neural network 1200 to measured outputs corresponding to the known sets of input variables p 1218, and modifying the weight values w 1212, the bias values b 1214, and/or the transform functions f 1216 until the error between the outputs of the neural network 1200 and the corresponding measured outputs is below a predetermined error level. For example, the neural network 1200 may be trained until the mean square error is below a predetermined error threshold. In certain embodiments, aspects of the training process may be implemented by the

neural network 1200 (e.g., by propagating errors back through the network 1200 to adaptively adjust the weight values w 1212 and/or the bias values b 1214).

[00233] Figure 68 illustrates a comparison between estimated temperature values T_{est} and measured temperature values T_m for an implementation of one embodiment of the neural network 1200. The neural network 1200 used to generate T_{est} in Figure 68 comprised six input variables p 1218: drive voltage, drive current, drive frequency, drive power, impedance of the ultrasonic transducer, and time duration over which ultrasonic energy was applied. The hidden layer 1206 comprised 25 nodes, and the output layer 1210 comprised a single node 1208. Training data was generated based on 13 applications of ultrasonic energy to carotid vessels. Actual temperature (T_m) was determined based on IR measurements over a 250-sample range for varying values of the input variables p 1218, with estimated temperatures T_{est} being generated by the neural network 1200 based on corresponding values of the input variables p 1218. The data shown in Figure 68 was generated on a run that was excluded from the training data. The estimated temperatures T_{est} demonstrate a reasonably accurate approximation of the measured temperatures T_m in the region of 110-190°F. It is believed that inconsistencies in estimated temperatures T_{est} appearing in certain regions, such as the region following 110°F, may be minimized or reduced by implementing additional neural networks specific to those regions. Additionally, inconsistencies in the data that may skew the trained output of the neural network 1200 may be identified and programmed in as special cases to further improve performance.

[00234] In certain embodiments, when the estimated temperature exceeds a user-defined temperature threshold T_{th} , the generator 102 may be configured to control the application of ultrasonic energy such that the estimated temperature T_{est} is maintained at or below the temperature threshold T_{th} . For example, in embodiments in which the drive current is an input variable p 1218 to the neural network 1200, the drive current may be treated as a control variable and modulated to minimize or reduce the difference between T_{est} and T_{th} . Such embodiments may be implemented using a feedback control algorithm (e.g., a PID control algorithm), with T_{th} being input to the control algorithm as a setpoint, T_{est} being input to the algorithm as process variable feedback, and drive current corresponding to the controlled output of the algorithm. In cases where the drive current serves as the control variable, suitable variations in drive current value should be represented in the sets of input variables p 1218 used to train the neural network 1200. In particular, the effectiveness of drive current as a control variable may be reduced if the training data reflects constant drive current values, as the neural network 1200 may reduce the weight values w 1212 associated with drive current due to its

apparent lack of effect on temperature. It will be appreciated that input variables p 1218 other than drive current (e.g., drive voltage) may be used to minimize or reduce the difference between T_{est} and T_{th} .

[00235] According to various embodiments, the generator 102 may provide power to a tissue bite according to one or more power curves. A power curve may define a relationship between power delivered to the tissue and the impedance of the tissue. For example as the impedance of the tissue changes (e.g., increases) during coagulation, the power provided by the generator 102 may also change (e.g., decrease) according to the applied power curve.

[00236] Different power curves may be particularly suited, or ill-suited, to different types and/or sizes of tissue bites. Aggressive power curves (e.g., power curves calling for high power levels) may be suited for large tissue bites. When applied to smaller tissue bites, such as small vessels, more aggressive power curves may lead to exterior searing. Exterior searing may reduce the coagulation/weld quality at the exterior and can also prevent complete coagulation of interior portions of the tissue. Similarly, less aggressive power curves may fail to achieve hemostasis when applied to larger tissue bites (e.g., larger bundles).

[00237] Figure 69 illustrates one embodiment of a chart 1300 showing example power curves 1306, 1308, 1310. The chart 1300 comprises an impedance axis 1302 illustrating increasing potential tissue impedances from left to right. A power axis 1304 illustrates increasing power from down to up. Each of the power curves 1306, 1308, 1310 may define a set of power levels, on the power axis 1304, corresponding to a plurality of potential sensed tissue impedances, in the impedance axis 1302. In general, power curves may take different shapes, and this is illustrated in Figure 69. Power curve 1306 is shown with a step-wise shape, while power curves 1308, 1310 are shown with curved shapes. It will be appreciated that power curves utilized by various embodiments may take any usable continuous or non-continuous shape. The rate of power delivery or aggressiveness of a power curve may be indicated by its position on the chart 1300. For example, power curves that deliver higher power for a given tissue impedance may be considered more aggressive. Accordingly, between two power curves, the curve positioned highest on the power axis 1304 may be the more aggressive. It will be appreciated that some power curves may overlap.

[00238] The aggressiveness of two power curves may be compared according to any suitable method. For example, a first power curve may be considered more aggressive than a second power curve over a given range of potential tissue impedances if the first power curve has a higher delivered power corresponding to at least half of the range of potential tissue impedances. Also, for example, a first power curve may be considered more aggressive than a

second power curve over a given range of potential tissue impedances if the area under the first curve over the range is larger than the area under the second curve over the range.

Equivalently, when power curves are expressed discretely, a first power curve may be considered more aggressive than a second power curve over a given set of potential tissue impedances if the sum of the power values for the first power curve over the set of potential tissue impedances is greater than the sum of the power values for the second power curve over the set of potential tissue impedances.

[00239] According to various embodiments, the power curve shifting algorithms described herein may be used with any kind of surgical device (e.g., ultrasonic device 104, electrosurgical device 106). In embodiments utilizing a ultrasonic device 104, tissue impedance readings may be taken utilizing electrodes 157, 159. With an electrosurgical device, such as 106, tissue impedance readings may be taken utilizing first and second electrodes 177, 179.

[00240] In some embodiments, an electrosurgical device 104 may comprise a positive temperature coefficient (PTC) material positioned between one or both of the electrodes 177, 179 and the tissue bite. The PTC material may have an impedance profile that remains relatively low and relatively constant until it reaches a threshold or trigger temperature, at which point the impedance of the PTC material may increase. In use, the PTC material may be placed in contact with the tissue while power is applied. The trigger temperature of the PTC material may be selected such that it corresponds to a tissue temperature indicating the completion of welding or coagulation. Accordingly, as a welding or coagulation process is completed, the impedance of the PTC material may increase, bringing about a corresponding decrease in power actually provided to the tissue.

[00241] It will be appreciated that during the coagulation or welding process, tissue impedance may generally increase. In some embodiments, tissue impedance may display a sudden impedance increase indicating successful coagulation. The increase may be due to physiological changes in the tissue, a PTC material reaching its trigger threshold, etc., and may occur at any point in the coagulation process. The amount of energy that may be required to bring about the sudden impedance increase may be related to the thermal mass of the tissue being acted upon. The thermal mass of any given tissue bite, in turn, may be related to the type and amount of tissue in the bite.

[00242] Various embodiments may utilize this sudden increase in tissue impedance to select an appropriate power curve for a given tissue bite. For example, the generator 102 may select and apply successively more aggressive power curves until the tissue impedance reaches an impedance threshold indicating that the sudden increase has occurred. For

example, reaching the impedance threshold may indicate that coagulation is progressing appropriately with the currently applied power curve. The impedance threshold may be a tissue impedance value, a rate of change of tissue impedance, and/or a combination of impedance and rate of change. For example, the impedance threshold may be met when a certain impedance value and/or rate of change are observed. According to various embodiments, different power curves may have different impedance thresholds, as described herein.

[00243] Figure 70 illustrates one embodiment of a process flow 1330 for applying one or more power curves to a tissue bite. Any suitable number of power curves may be used. The power curves may be successively applied in order of aggressiveness until one of the power curves drives the tissue to the impedance threshold. At 1332, the generator 102 may apply a first power curve. According to various embodiments, the first power curve may be selected to deliver power at a relatively low rate. For example, the first power curve may be selected to avoid tissue searing with the smallest and most vulnerable expected tissue bites.

[00244] The first power curve may be applied to the tissue in any suitable manner. For example, the generator 102 may generate a drive signal implementing the first power curve. The power curve may be implemented by modulating the power of the drive signal. The power of the drive signal may be modulated in any suitable manner. For example, the voltage and/or current of the signal may be modulated. Also, in various embodiments, the drive signal may be pulsed. For example, the generator 102 may modulate the average power by changing the pulse width, duty cycle, etc. of the drive signal. The drive signal may be provided to the first and second electrodes 177, 179 of the electrosurgical device 106. Also, in some embodiments the drive signal implementing the first power curve may be provided to an ultrasonic generator 114 of the ultrasonic device 104 described above.

[00245] While applying the first power curve, the generator 102 may monitor the total energy provided to the tissue. The impedance of the tissue may be compared to the impedance threshold at one or more energy thresholds. There may be any suitable number of energy thresholds, which may be selected according to any suitable methodology. For example, the energy thresholds may be selected to correspond to known points where different tissue types achieve the impedance threshold. At 1334, the generator 102 may determine whether the total energy delivered to the tissue has met or exceeded a first energy threshold. If the total energy has not yet reached the first energy threshold, the generator 102 may continue to apply the first power curve at 1332.

[00246] If the total energy has reached the first energy threshold, the generator 102 may determine whether the impedance threshold has been reached (1336). As described above, the

impedance threshold may be a predetermined rate of impedance change (e.g., increase) a predetermined impedance, or combination of the two. If the impedance threshold is reached, the generator 102 may continue to apply the first power curve at 1332. For example, reaching the impedance threshold in the first power curve may indicate that the aggressiveness of the first power curve is sufficient to bring about suitable coagulation or welding.

[00247] In the event that the impedance threshold is not reached at 1336, the generator 102 may increment to the next most aggressive power curve at 1338 and apply the power curve as the current power curve at 1332. When the next energy threshold is reached at 1334, the generator 102 again may determine whether the impedance threshold is reached at 1336. If it is not reached, the generator 102 may again increment to the next most aggressive power curve at 1338 and deliver that power curve at 1332.

[00248] The process flow 1330 may continue until terminated. For example, the process flow 1330 may be terminated when the impedance threshold is reached at 1336. Upon reaching the impedance threshold, the generator 102 may apply the then-current power curve until coagulation or welding is complete. Also, for example, the process flow 1330 may terminate upon the exhaustion of all available power curves. Any suitable number of power curves may be used. If the most aggressive power curve fails to drive the tissue to the impedance threshold, the generator 102 may continue to apply the most aggressive power curve until the process is otherwise terminated (e.g., by a clinician or upon reaching a final energy threshold).

[00249] According to various embodiments, the process flow 1330 may continue until the occurrence of a termination threshold. The termination threshold may indicate that coagulation and/or welding is complete. For example, the termination threshold may be based on one or more of tissue impedance, tissue temperature, tissue capacitance, tissue inductance, elapsed time, etc. These may be a single termination threshold or, in various embodiments, different power curves may have different termination thresholds. According to various embodiments, different power curves may utilize different impedance thresholds. For example, the process flow 1330 may transition from a first to a second power curve if the first power curve has failed to drive the tissue to a first tissue impedance threshold and may, subsequently, shift from the second to a third power curve if the second power curve has failed to drive the tissue to a second impedance threshold.

[00250] Figure 71 illustrates one embodiment of a chart 1380 showing example power curves 1382, 1384, 1386, 1388 that may be used in conjunction with the process flow 1330. Although four power curves 1382, 1384, 1386, 1388 are shown, it will be appreciated that any

suitable number of power curves may be utilized. Power curve 1382 may represent the least aggressive power curve and may be applied first. If the impedance threshold is not reached at the first energy threshold, then the generator 102 may provide the second power curve 1384. The other power curves 1386, 1388 may be utilized, as needed, for example in the manner described above.

[00251] As illustrated in Figure 71, the power curves 1382, 1384, 1386, 1388 are of different shapes. It will be appreciated, however, that some or all of a set of power curves implemented by the process flow 1330 may be of the same shape. Figure 72 illustrates one embodiment of a chart showing example common shape power curves 1392, 1394, 1396, 1398 that may be used in conjunction with the process flow of Figure 70. According to various embodiments, common shape power curves, such as 1392, 1394, 1396, 1398 may be constant multiples of one another. Accordingly, the generator 102 may implement the common shape power curves 1392, 1394, 1396, 1398 by applying different multiples to a single power curve. For example, the curve 1394 may be implemented by multiplying the curve 1392 by a first constant multiplier. The curve 1396 may be generated by multiplying the curve 1392 by a second constant multiplier. Likewise, the curve 1398 may be generated by multiplying the curve 1392 by a third constant multiplier. Accordingly, in various embodiments, the generator 102 may increment to a next most aggressive power curve at 1338 by changing the constant multiplier.

[00252] According to various embodiments, the process flow 1330 may be implemented by a digital device (e.g., a processor, digital signal processor, field programmable gate array (FPGA), etc.) of the generator 102. Examples of such digital devices include, for example, processor 174, programmable logic device 166, processor 190, etc.). Figures 73A-73C illustrate process flows describing routines that may be executed by a digital device of the generator 102 to generally implement the process flow 1330 described above. Figure 73A illustrates one embodiment of a routine 1340 for preparing the generator 102 to act upon a new tissue bite. The activation or start of the new tissue bite may be initiated at 1342. At 1344, the digital device may point to a first power curve. The first power curve, as described above, may be the least aggressive power curve to be implemented as a part of the process flow 1330. Pointing to the first power curve may comprise pointing to a deterministic formula indicating the first power curve, pointing to a look-up table representing the first power curve, pointing to a first power curve multiplier, etc.

[00253] At 1346, the digital device may reset an impedance threshold flag. As described below, setting the impedance threshold flag may indicate that the impedance threshold has

been met. Accordingly, resetting the flag may indicate that the impedance threshold has not been met, as may be appropriate at the outset of the process flow 1330. At 1348, the digital device may continue to the next routine 1350.

[00254] Figure 73B illustrates one embodiment of a routine 1350 that may be performed by the digital device to monitor tissue impedance. At 1352, load or tissue impedance may be measured. Tissue impedance may be measured according to any suitable method and utilizing any suitable hardware. For example, according to various embodiments, tissue impedance may be calculated according to Ohm's law utilizing the current and voltage provided to the tissue. At 1354, the digital device may calculate a rate of change of the impedance. The impedance rate of change may likewise be calculated according to any suitable manner. For example, the digital device may maintain prior values of tissue impedance and calculate a rate of change by comparing a current tissue impedance value or values with the prior values. Also, it will be appreciated that the routine 1350 assumes that the impedance threshold is a rate of change. In embodiments where the impedance threshold is a value, 1354 may be omitted. If the tissue impedance rate of change (or impedance itself) is greater than the threshold (1356), then the impedance threshold flag may be set. The digital device may continue to the next routing at 1360.

[00255] Figure 73C illustrates one embodiment of a routine 1362 that may be performed by the digital device to provide one or more power curves to a tissue bite. At 1364, power may be delivered to the tissue, for example, as described above with respect to 1334 of Figure 70. The digital device may direct the delivery of the power curve, for example, by applying the power curve to find a corresponding power for each sensed tissue impedance, modulating the corresponding power onto a drive signal provided to the first and second electrodes A20, A22, the transducer 114, etc.

[00256] At 1366, the digital device may calculate the total accumulated energy delivered to the tissue. For example, the digital device may monitor the total time of power curve delivery and the power delivered at each time. Total energy may be calculated from these values. At 1368, the digital device may determine whether the total energy is greater than or equal to a next energy threshold, for example, similar to the manner described above with respect to 1334 of Figure 70. If the next energy threshold is not met, the current power curve may continue to be applied at 1378 and 1364.

[00257] If the next energy threshold is met at 1368, then at 1370, the digital device may determine whether the impedance threshold flag is set. The state of the impedance threshold flag may indicate whether the impedance threshold has been met. For example, the impedance

threshold flag may have been set by the routine 1350 if the impedance threshold has been met. If the impedance flag is not set (e.g., the impedance threshold is not met), then the digital device may determine, at 1372, whether any more aggressive power curves remain to be implemented. If so, the digital device may point the routine 1362 to the next, more aggressive power curve at 1374. The routine 1362 may continue (1378) to deliver power according to the new power curve at 1364. If all available power curves have been applied, then the digital device may disable calculating and checking of accumulated energy for the remainder of the tissue operation at 1376.

[00258] If the impedance flag is set at 1370 (e.g., the impedance threshold has been met), then the digital device may disable calculating and checking of accumulated energy for the remainder of the tissue operation at 1376. It will be appreciated that, in some embodiments, accumulated energy calculation may be continued, while 1370, 1372, 1374, and 1376 may be discontinued. For example, the generator 102 and/or digital device may implement an automated shut-off when accumulated energy reaches a predetermined value.

[00259] Figure 74 illustrates one embodiment of a process flow 1400 for applying one or more power curves to a tissue bite. For example, the process flow 1400 may be implemented by the generator 102 (e.g., the digital device of the generator 102). At 1402, the generator 102 may deliver a power curve to the tissue. The power curve may be derived by applying a multiplier to a first power curve. At 1404, the generator 102 may determine if the impedance threshold has been met. If the impedance threshold has not been met, the generator 102 may increase the multiplier as a function of the total applied energy. This may have the effect of increasing the aggressiveness of the applied power curve. It will be appreciated that the multiplier may be increased periodically or continuously. For example, the generator 102 may check the impedance threshold (1404) and increase the multiplier (1406) at a predetermined periodic interval. In various embodiments, the generator 102 may continuously check the impedance threshold (1404) and increase the multiplier (1406). Increasing the multiplier as a function of total applied energy may be accomplished in any suitable manner. For example, the generator 102 may apply a deterministic equation that receives total received energy as input and provides a corresponding multiplier value as output. Also, for example, the generator 102 may store a look-up table that comprises a list of potential values for total applied energy and corresponding multiplier values. According to various embodiments, the generator 102 may provide a pulsed drive signal to tissue (e.g., via one of the surgical devices 104, 106). According to various embodiments, when the impedance threshold is met, the multiplier may be held constant. The generator 102 may continue to apply power, for example, until a termination

threshold is reached. The termination threshold may be constant, or may depend on the final value of the multiplier.

[00260] In some embodiments utilizing a pulsed drive signal, the generator 102 may apply one or more composite load curves to the drive signal, and ultimately to the tissue. Composite load curves, like other power curves described herein, may define a level of power to be delivered to the tissue as a function of a measured tissue property or properties (e.g., impedance). Composite load curves may, additionally, define pulse characteristics, such as pulse width, in terms of the measured tissue properties.

[00261] Figure 75 illustrates one embodiment of a block diagram 1450 describing the selection and application of composite load curves by the generator 102. It will be appreciated that the block diagram 1450 may be implemented with any suitable type of generator or surgical device. According to various embodiments, the block diagram 1450 may be implemented utilizing an electrosurgical device, such as the device 106 described above with respect to Figures 4-7. Also, in various embodiments, the block diagram 1450 may be implemented with a ultrasonic surgical device, such as the surgical device 104 described above with respect to Figures 2-3. In some embodiments, the block diagram 1450 may be utilized with a surgical device having cutting as well as coagulating capabilities. For example, an RF surgical device, such as the device 106, may comprise a cutting edge, such as the blade 175 for severing tissue either before or during coagulation.

[00262] Referring back to Figure 75, an algorithm 1452 may be executed, for example by a digital device of the generator 102 to select and apply composite load curves 1456, 1458, 1460, 1462. The algorithm 1452 may receive a time input from a clock 1454 and may also receive loop input 1472 from sensors 1468. The loop input 1472 may represent properties or characteristics of the tissue that may be utilized in the algorithm 1452 to select and/or apply a composite load curve. Examples of such characteristics may comprise, for example, current, voltage, temperature, reflectivity, force applied to the tissue, resonant frequency, rate of change of resonant frequency, etc. The sensors 1468 may be dedicated sensors (e.g., thermometers, pressure sensors, etc.) or may be software implemented sensors for deriving tissue characteristics based on other system values (e.g., for observing and/or calculating voltage, current, tissue temperature, etc., based on the drive signal). The algorithm 1452 may select one of the composite load curves 1456, 1458, 1460, 1462 to apply, for example based on the loop input 1472 and/or the time input from the clock 1454. Although four composite load curves are shown, it will be appreciated that any suitable number of composite load curves may be used.

[00263] The algorithm 1452 may apply a selected composite load curve in any suitable manner. For example, the algorithm 1452 may use the selected composite load curve to calculate a power level and one or more pulse characteristics based on tissue impedance (e.g., currently measured tissue impedance may be a part of, or may be derived from, the loop input) or resonant frequency characteristics of a ultrasonic device 104. Examples of pulse characteristics that may be determined based on tissue impedance according to a composite load curve may include pulse width, ramp time, and off time.

[00264] At set point 1464, the derived power and pulse characteristics may be applied to the drive signal. In various embodiments, a feedback loop 1474 may be implemented to allow for more accurate modulation of the drive signal. At the output of the set point 1464, the drive signal may be provided to an amplifier 1466, which may provide suitable amplification. The amplified drive signal may be provided to a load 1470 (e.g., via sensors 1468). The load 1470 may comprise the tissue, the surgical device 104, 106, and/or any cable electrically coupling the generator 102 with the surgical device 104, 106 (e.g., cables 112, 128).

[00265] Figure 76 illustrates shows a process flow illustrating one embodiment of the algorithm 1452, as implemented by the generator 102 (e.g., by a digital device of the generator 102). The algorithm 1452 may be activated at 1476. It will be appreciated that the algorithm 1452 may be activated in any suitable manner. For example, the algorithm 1452 may be activated by a clinician upon actuation of the surgical device 104, 106 (e.g., by pulling or otherwise actuating a jaw closure trigger 138, 142, switch, handle, etc.).

[00266] According to various embodiments, the algorithm 1452 may comprise a plurality of regions 1478, 1480, 1482, 1484. Each region may represent a different stage of the cutting and coagulation of a tissue bite. For example, in the first region 1478, the generator 102 may perform an analysis of initial tissue conditions (e.g., impedance). In the second region 1480, the generator 102 may apply energy to the tissue in order to prepare the tissue for cutting. In the third or cut region 1482, the generator 102 may continue to apply energy while the surgical device 104, 106 cuts the tissue (e.g., with the electrosurgical device 106, cutting may be performed by advancing the blade A18). In the fourth or completion region 1484, the generator 102 may apply energy post-cut to complete coagulation.

[00267] Referring now to the first region 1478, the generator 102 may measure any suitable tissue condition or conditions including, for example, current, voltage, temperature, reflectivity, force applied to the tissue, etc. In various embodiments, an initial impedance of the tissue may be measured according to any suitable manner. For example, the generator 102 may modulate the drive signal to provide a known voltage or current to the tissue. Impedance

may be derived from the known voltage and the measured current or vice versa. It will be appreciated that tissue impedance may alternately or additionally be measured in any other suitable manner. According to the algorithm 1452, the generator 102 may proceed from the first region 1478 to the second region 1480. In various embodiments, the clinician may end the algorithm 1452 in the first region 1478, for example, by deactivating the generator 102 and/or the surgical device 104, 106. If the clinician terminates the algorithm 1542, RF (and/or ultrasonic) delivery may also be terminated at 1486.

[00268] In the second region 1480, the generator 102 may begin to apply energy to the tissue via the drive signal to prepare the tissue for cutting. Energy may be applied according to the composite load curves 1456, 1458, 1460, 1462, as described below. Applying energy according to the second region 1480 may comprise modulating pulses onto the drive signal according to some or all of the composite load curves 1456, 1458, 1460, 1462. In various embodiments, the composite load curves 1456, 1458, 1460, 1462 may be successively applied in order of aggressiveness (e.g., to accommodate various types of tissue-volume clamped in the instrument jaws).

[00269] The first composite load curve 1456 may be applied first. The generator 102 may apply the first composite load curve 1456 by modulating one or more first composite load curve pulses onto the drive signal. Each first composite load curve pulse may have a power and pulse characteristics determined according to the first composite load curve and considering measured tissue impedance. Measured tissue impedance for the first pulse may be the impedance measured at the first region 1478. In various embodiments, the generator 102 may utilize all or a portion of the first composite load curve pulses to take additional measurements of tissue impedance or resonant frequency. The additional measurements may be used to determine the power and other pulse characteristics of a subsequent pulse or pulses.

[00270] Figure 77 illustrates one embodiment of a process flow 1488 for generating a first composite load curve pulse. The process flow 1488 may be executed by the generator 102 (e.g., by a digital device of the generator 102), for example, as a part of the algorithm 1452. At 1490, the generator 102 may calculate a pulse width (T_{pw}). The pulse width may be determined considering the most recent measured tissue impedance (Z) and according to the first composite load curve 1456.

[00271] At 1492, the generator 102 may ramp the power of the drive signal up to a pulse power ($PLimit$) over a ramp time (t_{ramp}), thereby applying the pulse to the tissue. The pulse power may be determined, again, considering the most recent measured tissue impedance (Z)

and according to the first composite load curve 1456. The ramp time may be determined according to the composite load curve considering tissue impedance or may be constant (e.g., constant for all first composite load curve pulses, constant for all pulses, etc.). The generator 102 may apply the pulse power to the drive signal in any suitable manner including, for example, modulating a current and/or voltage provided by the drive signal. According to various embodiments, the drive signal may be an alternating current (A/C) signal, and therefore the pulse itself may comprise multiple cycles of the drive signal.

[00272] The drive signal may be held at the pulse power for the pulse width at 1494. At the conclusion of the pulse, the drive signal may be ramped down, at 1496, over a fall time (T_{fall}). The fall time may be determined according to the first composite load curve considering tissue impedance, or may be constant (e.g., constant for all first composite load curve pulses, constant for all pulses, etc.). It will be appreciated that, depending on the embodiment, the ramp time and fall time may or may not be considered part of the pulse width. At 1498, the generator 102 may pause for an off time (T_{off}). Like the ramp time and fall time, the off time may be determined according to the first composite load curve considering tissue impedance, or may be constant (e.g., constant for all first composite load curve pulses, constant for all pulses, etc.).

[00273] At the completion of the off time, the generator 102 may repeat the process flow 1488 as long as the first composite load curve 1456 is applied. According to various embodiments, the generator 102 may apply the first composite load curve 1456 for a predetermined amount of time. Accordingly, the process flow 1488 may be repeated until the predetermined amount of time has elapsed (e.g., as determined based on the time input received from the clock 1454). Also, in various embodiments, the first composite load curve may be applied for a predetermined number of pulses. Because the applied pulse width varies according to measured tissue impedance, the total time that the first composite load curve is applied may also vary with measured tissue impedance. According to various embodiments, the first composite load curve 1456 (as well as the other composite load curves 1458, 1460, 1462) may specify decreasing pulse widths as tissue impedance increases. Therefore, a higher initial tissue impedance may lead to less time spent in the first composite load curve.

[00274] Upon completion of the first composite load curve 1456, the generator 102 may successively apply the remaining consolidated load curves 1458, 1460, 1462 throughout the application of the second region 1480. Each load curve 1458, 1460, 1462 may be applied in a manner similar to that of the load curve 1456 described above. For example, pulses according to a current load curve may be generated until the completion of that load curve (e.g., the expiration of a predetermined amount of time or a predetermined number of pulses). The

predetermined number of pulses may be the same for each composite load curve 1456, 1458, 1460, 1462 or may be different. According to various embodiments, pulses according to the load curves 1458, 1460, 1462 may be generated in a manner similar to process flow 1488, except that pulse power, pulse width and, in some embodiments, ramp time, fall time, and off time, may be derived according to the current composite load curve.

[00275] The second region 1480 may be terminated upon the occurrence of various events. For example, if the total RF application time has exceeded a timeout time, then the generator 102 may end the tissue operation by terminating RF (and/or ultrasonic) delivery at 1486. Also, various events may cause the generator 102 to transition from the second region 1480 to the third region 1482. For example, the generator 102 may transition to the third region 1482 when the tissue impedance (Z) exceeds a threshold tissue impedance (Z_{term}) and RF energy has been delivered for at least more than a minimum time (T_{start}). The threshold tissue impedance may be an impedance and/or an impedance rate of change indicating that the tissue bite is adequately prepared for cutting by the blade 175.

[00276] According to various embodiments, if the final load curve 1462 is completed in the second region 1480 before completion of the second region 1480, then the final power curve 1462 may be continuously applied, for example, until the tissue impedance threshold is met, the maximum second region time is reached and/or the timeout time is reached. Also, it will be appreciated that, with some tissue cuts, the second region 1480 may be completed before all available consolidated load curves 1456, 1458, 1460, 1462 are executed.

[00277] At the third region 1482, the generator 102 may continue to modulate pulses onto the drive signal. Generally, third region pulses may be modulated onto the drive signal according to any suitable manner including, for example, that described above with reference to the process flow 1488. The power and pulse characteristics of the third region pulses may be determined according to any suitable method and, in various embodiments, may be determined based on the composite load curve that was being executed at the completion of the second region 1480 (the current load curve). According to various embodiments, the current load curve may be utilized to determine the pulse power of third region pulses, while the pulse characteristics (e.g., pulse width, ramp time, fall time, off time, etc.) may be constant regardless of composite load curve. In some embodiments, the third region 1482 may utilize a third-region-specific composite load curve that may be one of the load curves 1456, 1458, 1460, 1462 utilized in the second region 1480, or may be a different composite load curve (not shown).

[00278] The generator 102 may continue to execute the third region 1482 until receiving an indication that the tissue cut is complete. In embodiments utilizing surgical implements

having a blade, such as 175, the indication may be received when the blade 175 reaches its distal-most position, as shown in Figure 6. This may trip a knife limit sensor (not shown) indicating that the blade 175 has reached the end of its throw. Upon receiving the indication that the tissue cut is complete, the generator 102 may continue to the fourth region 1484. It will also be appreciated that, in some embodiments, the generator 102 may transition from the third region 1482 directly to RF (and/or ultrasonic) termination at 1486, for example, if the timeout time has been reached.

[00279] In the fourth region 1484, the generator 102 may provide an energy profile designed to complete coagulation of the now-cut tissue. For example, according to various embodiments, the generator 102 may provide a predetermined number of pulses. The pulses may be provided in a manner similar to that described above with respect to the process flow 1488. The power and pulse characteristics of the pulses may be determined according to any suitable manner. For example, power and pulse characteristics of the fourth region pulses may be determined based on the current composite load curve, the third-region-specific load curve, or a fourth-region-specific composite load curve. In some embodiments, power may be determined based on the current composite load curve, while pulse characteristics may be fourth region-specific. Also, according to various embodiments, the power and pulse characteristics of fourth region pulses may be determined independent of the current composite load curve.

[00280] Figure 78 illustrates one embodiment of a pulse timing diagram 1474 illustrating an example application of the algorithm 1452 by the generator 102 (e.g., by a digital device of the generator 102). A first region pulse 1502 is shown in the first region 1478. The first region pulse 1502 may be utilized, as described, to measure an initial tissue impedance. At the completion of the first region pulse (1509), second region 1480 may begin with second region pulses 1504 applied. The second region pulses 1504 may be applied according to the various composite load curves 1456, 1458, 1460, 1462, for example, as described herein. In the example diagram 1474, the second region 1480 concludes at 1510 when the tissue reaches the threshold impedance (Z_{term}). The third region 1482 is then implemented, with third region pulses 1506, as described above, applied until a knife limit signal is received at 1512. At that point, the fourth region 1484 may commence, with fourth region pulses 1508, as described above, applied until cycle completion at 1514.

[00281] According to various embodiments, the generator 102 may implement a user interface in conjunction with the algorithm 1452. For example, the user interface may indicate the current region of the algorithm. The user interface may be implemented visually and/or

audibly. For example, the generator 102 may comprise a speaker for generating audible tones or other audible indication. At least one audible indication may correspond to the second region 1480. The third and fourth regions 1482, 1484 may also have region-specific audible indications. According to various embodiments, the first region 1478 may have a region-specific audible indication as well. According to various embodiments, the audible indications may comprise pulsed tones generated by the generator 102. The frequency of the tones and/or the pitch of the tones themselves may indicate the current region. In addition to, or instead of, the audible indications, the generator 102 may also provide a visual indication of the current region (e.g., on output device 147). It will be appreciated that the clinician may utilize the described user interface to properly use the generator 102 and associated surgical devices 104, 106. For example, the indication of the second region 1480 may let the clinician know that tissue treatment has begun. The indication of the third region 1482 may let the clinician know that the tissue is ready for the cutting operation. The indication of the fourth region 1484 may let the clinician know that the cutting operation is complete. The cessation of the indication and/or a final indication may indicate that the total cutting/coagulation operation is complete.

[00282] Figure 79 illustrates a graphical representation of drive signal voltage, current and power according to an example load curve 1520. In the chart 1520, drive signal voltage is represented by line 1522, drive signal current is represented by line 1524 and drive signal power is represented by line 1526. Pulse width is not indicated in Figure 79. In various embodiments, the values for voltage 1522, current 1524 and power 1526 indicated by the graph 1520 may represent possible values within a single pulse. Accordingly, the load curve 1520 may be expressed as a composite load curve by adding a curve (not shown) indicating a pulse width as a function of tissue impedance or another tissue condition. As shown for the load curve 1520, the maximum voltage 1522 is 100 Volts Root Mean Square (RMS), the maximum current is 3 Amps RMS and the maximum power is 135 Watts RMS.

[00283] Figures 79-84 illustrate graphical representations of various example composite load curves 1530, 1532, 1534, 1536, 1538, 1540. Each of the composite load curves 1530, 1532, 1534, 1536, 1538, 1540 may indicate both pulse power and pulse width in terms of measured tissue impedance. The composite load curves 1530, 1532, 1534, 1536 may be implemented either in isolation or as part of a pattern of successively more aggressive composite load curves, as described above with respect to the algorithm 1452.

[00284] Figure 80 illustrates a graphical representation of a first example composite load curve 1530. The composite load curve 1530 may have a maximum pulse power of 45 Watts RMS and a maximum pulse width of 0.35 seconds. In Figure 80, the power as a function of

tissue impedance is indicated by 1542, while the pulse width as a function of tissue impedance is indicated by 1544. Table 1 below illustrates values for the composite load curve 1530 for tissue impedances from 0Ω to 475Ω .

Table 1

	V	I	P	
Load,	Lim,	Lim,	Lim,	PW,
Ohms	RMS	RMS	W	Sec
0-24	85	1.4	45	0.35
25-49	85	1.4	45	0.35
50-74	85	1.4	45	0.3
75-99	85	1.4	45	0.3
100-124	85	1.4	45	0.25
125-149	85	1.4	45	0.25
150-174	85	1.4	45	0.2
175-199	85	1.4	45	0.2
200-224	85	1.4	44	0.15
225-249	85	1.4	40	0.15
250-274	85	1.4	36	0.1
275-299	85	0.31	24	0.1
300-324	85	0.28	22	0.1
325-349	85	0.26	20	0.1
350-374	85	0.25	19	0.1
375-399	85	0.22	18	0.1
400-424	85	0.21	17	0.1
425-449	85	0.2	16	0.1
450-475	85	0.19	15	0.1
475+	85	0.15	14	0.1

In various embodiments, the composite load curve 1530 may be suited to smaller surgical devices and/or smaller tissue bites.

[00285] Figure 81 illustrates a graphical representation of a second example composite load curve 1532. The composite load curve 1532 may have a maximum pulse power of 45 Watts RMS and a maximum pulse width of 0.5 seconds. In Figure 81, the power as a function of tissue impedance is indicated by 1546, while the pulse width as a function of tissue

impedance is indicated by 1548. Table 2 below illustrates values for the composite load curve 1532 for tissue impedances from 0Ω to 475Ω .

Table 2

Load, Ohms	V Lim, RMS	I Lim, RMS	P Lim, W	PW, Sec
0-24	85	3	45	0.5
25-49	85	2	45	0.5
50-74	85	1.4	45	0.5
75-99	85	1.1	45	0.5
100-124	85	0.9	45	0.5
125-149	85	0.7	45	0.5
150-174	85	0.55	45	0.5
175-199	85	0.48	45	0.5
200-224	85	0.42	32	0.5
225-249	85	0.38	28	0.5
250-274	85	0.33	26	0.3
275-299	85	0.31	24	0.3
300-324	85	0.28	22	0.25
325-349	85	0.26	20	0.25
350-374	85	0.25	19	0.25
375-399	85	0.22	18	0.25
400-424	85	0.21	17	0.25
425-449	85	0.2	16	0.25
450-475	85	0.19	15	0.25
475+	85	0.15	14	0.25

The composite load curve 1532 may be targeted at small, single vessel tissue bites and, according to various embodiments, may be a first composite power curve applied in region two 1480.

[00286] Figure 82 illustrates a graphical representation of a third example composite load curve 1534. The composite load curve 1534 may have a maximum pulse power of 60 Watts RMS and a maximum pulse width of 2 seconds. In Figure 82, the power as a function of tissue impedance is indicated by 1550, while the pulse width as a function of tissue impedance is

indicated by 1552. Table 3 below illustrates values for the composite load curve 1534 for tissue impedances from 0Ω to 475Ω .

Table 3

Load, Ohms	V Lim, RMS	I Lim, RMS	P Lim, W	PW, Sec
0-24	85	3	60	2
25-49	85	3	60	2
50-74	100	3	60	2
75-99	100	3	60	2
100-124	100	3	60	2
125-149	100	3	60	2
150-174	100	3	55	0.5
175-199	100	3	50	0.5
200-224	85	0.42	32	0.3
225-249	85	0.38	28	0.3
250-274	85	0.33	26	0.3
275-299	85	0.31	24	0.3
300-324	85	0.28	22	0.25
325-349	85	0.26	20	0.25
350-374	85	0.25	19	0.25
375-399	85	0.22	18	0.25
400-424	85	0.21	17	0.25
425-449	85	0.2	16	0.25
450-475	85	0.19	15	0.25
475+	85	0.15	14	0.25

The composite load curve 1534 may be more aggressive than the prior curve 1532 by virtue of its generally higher power. The composite load curve 1534 may also, initially, have higher pulse widths than the prior curve 1532, although the pulse widths of the composite load curve 1534 may begin to drop at just 150Ω . According to various embodiments, the composite load curve 1536 may be utilized in the algorithm 1542 as a load curve implemented sequentially after the composite load curve 1532.

[00287] Figure 83 illustrates a graphical representation of a fourth example composite load curve 1536. The composite load curve 1536 may have a maximum pulse power of 90 Watts RMS and a maximum pulse width of 2 seconds. In Figure 83, the power as a function of tissue impedance is indicated by 1554, while the pulse width as a function of tissue impedance is indicated by 1556. Table 4 below illustrates values for the composite load curve 1536 for tissue impedances from 0Ω to 475Ω.

Table 4

Load, Ohms	V	P		
	Lim, RMS	I Lim, RMS	Lim, W	PW, Sec
0-24	85	3	90	2
25-49	85	3	90	2
50-74	100	3	90	2
75-99	100	3	90	2
100-124	100	3	80	2
125-149	100	3	65	2
150-174	100	3	55	0.5
175-199	100	3	50	0.5
200-224	85	0.42	32	0.3
225-249	85	0.38	28	0.3
250-274	85	0.33	26	0.3
275-299	85	0.31	24	0.3
300-324	85	0.28	22	0.25
325-349	85	0.26	20	0.25
350-374	85	0.25	19	0.25
375-399	85	0.22	18	0.25
400-424	85	0.21	17	0.25
425-449	85	0.2	16	0.25
450-475	85	0.19	15	0.25
475+	85	0.15	14	0.25

The composite load curve 1536 may, again, be more aggressive than the prior curve 1534 and, therefore, may be implemented sequentially after the curve 1534 in the algorithm 1452. Also,

according to various embodiments, the composite load curve 1536 maybe suited to larger tissue bundles.

[00288] Figure 84 illustrates a graphical representation of a fifth example composite load curve 1538. The composite load curve 1538 may have a maximum pulse power of 135 Watts RMS and a maximum pulse width of 2 seconds. In Figure 84, the power as a function of tissue impedance is indicated by 1558, while the pulse width as a function of tissue impedance is indicated by 1560. Table 5 below illustrates values for the composite load curve 1538 for tissue impedances from 0Ω to 475Ω.

Table 5

Load,	V	I	P	PW,
Ohms	Lim,	Lim,	Lim,	Sec
	RMS	RMS	W	
0-24	85	3	135	2
25-49	85	3	135	2
50-74	100	3	135	2
75-99	100	3	100	2
100-124	100	3	80	2
125-149	100	3	65	2
150-174	100	3	55	0.5
175-199	100	3	50	0.5
200-224	85	0.42	32	0.3
225-249	85	0.38	28	0.3
250-274	85	0.33	26	0.3
275-299	85	0.31	24	0.3
300-324	85	0.28	22	0.25
325-349	85	0.26	20	0.25
350-374	85	0.25	19	0.25
375-399	85	0.22	18	0.25
400-424	85	0.21	17	0.25
425-449	85	0.2	16	0.25
450-475	85	0.19	15	0.25
475+	85	0.15	14	0.25

The composite load curve 1538 may be used sequentially after the prior curve 1536 in the algorithm 1452.

[00289] Figure 85 illustrates a graphical representation of a sixth example composite load curve 1540. The composite load curve 1540 may have a maximum pulse power of 90 Watts RMS and a maximum pulse width of 2 seconds. In Figure 85, the power as a function of tissue impedance is indicated by 1562, while the pulse width as a function of tissue impedance is indicated by 1564. Table 6 below illustrates values for the composite load curve 1540 for tissue impedances from 0Ω to 475Ω.

Table 6

Load,	V	I	P	PW,
Ohms	Lim,	Lim,	Lim,	Sec
	RMS	RMS	W	
0-24	85	3	90	2
25-49	85	3	90	2
50-74	100	3	90	2
75-99	100	3	90	2
100-124	100	3	80	2
125-149	100	3	65	2
150-174	100	3	55	0.5
175-199	100	3	50	0.5
200-224	85	0.42	32	0.3
225-249	85	0.38	28	0.3
250-274	85	0.33	26	0.3
275-299	85	0.31	24	0.3
300-324	85	0.28	22	0.25
325-349	85	0.26	20	0.25
350-374	85	0.25	19	0.25
375-399	85	0.22	18	0.25
400-424	85	0.21	17	0.25
425-449	85	0.2	16	0.25
450-475	85	0.19	15	0.25
475+	85	0.15	14	0.25

The composite power curve 1540 is less aggressive than the prior power curve 1538.

According to various embodiments, the composite power curve 1540 may be implemented in the algorithm 1452 sequentially after the curve 1538. Also, in some embodiments, the composite power curve 1540 may be implemented in the algorithm 1452 as a third or fourth region-specific composite power curve.

[00290] As described above, the various composite power curves used in the algorithm 1452 may each be implemented for a predetermined number of pulses. Table 7 below illustrates the number of pulses per composite power curve for an example embodiment utilizing the power curves 1532, 1534, 1536, 1540 sequentially in the algorithm 1452.

Table 7

Composite Load Curve	Number of Pulses
1532	4
1534	2
1536	2
1538	8
1540	n/a

The last composite power curve 1540 is shown without a corresponding number of pulses. For example, the composite power curve 1540 may be implemented until the clinician terminates the operation, until the timeout time is reached, until the threshold tissue impedance is reached, etc.

[00291] According to various embodiments, the generator 102 may provide power to a tissue bite in a manner that brings about a desired value of other tissue parameters. Figure 86 illustrates one embodiment of a block diagram 1570 describing the application of an algorithm 1572 for maintaining a constant tissue impedance rate of change. The algorithm 1572 may be implemented by the generator 102 (e.g., by a digital device of the generator 102). For example, the algorithm 1572 may be utilized by the generator 102 to modulate the drive signal. Sensors 1574 may sense a tissue condition, such as tissue impedance and/or a rate of change of tissue impedance. The sensors 1574 may be hardware sensors or, in various embodiments may be software implemented sensors. For example, the sensors 1574 may calculate tissue impedance based on measured drive signal current and voltage. The drive signal may be provided by the generator 102 to the cable/implement/load 1576, which may be the electrical

combination of the tissue, the surgical device 104,106 and a cable 112, 128 electrically coupling the generator 102 to the device 104, 106.

[00292] The generator 102, by implementing the algorithm 1572, may monitor the impedance of the tissue or load including, for example, the rate of change of impedance. The generator 102 may modulate one or more of the voltage, current and/or power provided via the drive signal to maintain the rate of change of tissue impedance at a predetermined constant value. Also, according to various embodiments, the generator 102 may maintain the rate of change of the tissue impedance at above a minimum impedance rate of change.

[00293] It will be appreciated that the algorithm 1572 may be implemented in conjunction with various other algorithms described herein. For example, according to various embodiments, the generator 102 may sequentially modulate the tissue impedance to different, increasingly aggressive rates similar to the method 1330 described herein with reference to Figure 70 herein. For example, a first impedance rate of change may be maintained until the total energy delivered to the tissue exceeds a predetermined energy threshold. At the energy threshold, if tissue conditions have not reached a predetermined level (e.g., a predetermined tissue impedance), then the generator 102 may utilize the drive signal to drive the tissue to a second, higher impedance rate of change. Also, in various embodiments, tissue impedance rates of change may be used in a manner similar to that described above with respect to composite load curves. For example, instead of utilizing plurality of composite load curves, the algorithm 1452 of Figure 75 may call for applying a plurality of rates of tissue impedance change. Each rate of tissue impedance change may be maintained for a predetermined amount of time and/or a predetermined number of pulses. The rates may be successively applied in order of value (e.g., rates may successively increase). In some embodiments, however, the driven rates of tissue impedance change may peak, and then be reduced.

[00294] Although the various embodiments of the devices have been described herein in connection with certain disclosed embodiments, many modifications and variations to those embodiments may be implemented. For example, different types of end effectors may be employed. Also, where materials are disclosed for certain components, other materials may be used. The foregoing description and following claims are intended to cover all such modification and variations.

[00295] Any patent, publication, or other disclosure material, in whole or in part, that is said to be incorporated by reference herein is incorporated herein only to the extent that the incorporated materials does not conflict with existing definitions, statements, or other disclosure material set forth in this disclosure. As such, and to the extent necessary, the disclosure as

explicitly set forth herein supersedes any conflicting material incorporated herein by reference. Any material, or portion thereof, that is said to be incorporated by reference herein, but which conflicts with existing definitions, statements, or other disclosure material set forth herein will only be incorporated to the extent that no conflict arises between that incorporated material and the existing disclosure material.

CLAIMS

We claim:

1. A generator to communicate a drive signal to a surgical device, the generator comprising:

a power amplifier to receive a time-varying drive signal waveform, the drive signal waveform generated by a digital-to-analog conversion of at least a portion of a plurality of drive signal waveform samples, an output of the power amplifier for generating a drive signal, the drive signal comprising one of: a first drive signal to be communicated to an ultrasonic surgical device, a second drive signal to be communicated to an electrosurgical device;

a sampling circuit to generate samples of current and voltage of the drive signal when the drive signal is communicated to the surgical device, generation of the samples synchronized with the digital-to-analog conversion of the drive signal waveform samples such that, for each digital-to-analog conversion of a drive signal waveform sample, the sampling circuit generates a corresponding set of current and voltage samples;

at least one device programmed to, for each drive signal waveform sample and corresponding set of current and voltage samples:

store the current and voltage samples in a memory of the at least one device to associate the stored samples with the drive signal waveform sample;

when the drive signal comprises the first drive signal:

determine a motional branch current sample of the ultrasonic surgical device based on the stored current and voltage samples;

compare the motional branch current sample to a target sample selected from a plurality of target samples that define a target waveform, the target sample selected based on the drive signal waveform sample;

determine an amplitude error between the target sample and the motional branch current sample; and

modify the drive signal waveform sample such that an amplitude error determined between the target sample and a subsequent motional branch current sample based on current and voltage samples associated with the modified drive signal waveform sample is reduced.

2. The generator of claim 1, comprising a power transformer to generate the drive signal based on the power amplifier output, the first drive signal to be communicated to the ultrasonic

surgical device via first power transformer outputs, the second drive signal to be communicated to the electrosurgical device via second power transformer outputs.

3. The generator of claim 1, wherein the plurality of drive signal waveform samples are stored in a look-up table (LUT), and wherein the at least one device is programmed to selectively recall from the LUT the at least a portion of the plurality of drive signal waveform samples used to generate the drive signal waveform.

4. The generator of claim 3, wherein the at least one device is programmed to implement a direct digital synthesis (DDS) algorithm to selectively recall the at least a portion of the plurality of drive signal waveform samples used to generate the drive signal waveform.

5. The generator of claim 3, wherein the at least one device is programmed to:
when the drive signal comprises the first drive signal:

determine an impedance phase of the ultrasonic surgical instrument based on a plurality of motional branch current samples and a plurality of voltage samples corresponding to the plurality of motional branch current samples; and

control a frequency of the drive signal waveform to regulate the impedance phase to a 0-degree impedance phase setpoint.

6. The generator of claim 3, wherein the at least one device is programmed to:

control an amplitude of the drive signal current in accordance with at least one of a drive signal current setpoint, a drive signal voltage setpoint and a drive signal power setpoint, wherein the amplitude of the drive signal current is controlled by at least one of:

controlling a scale of the drive signal waveform samples stored in the LUT; and

controlling a full-scale output voltage of a digital-to-analog converter (DAC) used to perform the digital-to-analog conversion of the least a portion of the plurality of drive signal waveform samples.

7. The generator of claim 1, wherein the at least one device is programmed to:

control a rail voltage of the power amplifier based on a signal envelope of the time-varying drive signal waveform received by the power amplifier.

8. The generator of claim 1, wherein the at least one device is programmed to:
determine at least one of: root-mean-square (RMS) current of the drive signal, RMS voltage of the drive signal, real power of the drive signal, apparent power of the drive signal, and impedance magnitude of a load driven by the drive signal.
9. The generator of claim 1, wherein the at least one device is programmed to:
apply a filter to the current and voltage samples to reduce harmonic distortion content of the samples.
10. The generator of claim 1, wherein the sampling circuit comprises a first analog-to-digital converter (ADC) and a second ADC to generate samples of current and voltage of the drive signal, respectively.
11. The generator of claim 1, wherein the sampling circuit comprises a first analog-to-digital converter (ADC) and a two-way multiplexer coupled to an input of the first ADC.
12. The generator of claim 1, wherein the sampling circuit is configured to oversample at 200x.
13. The generator of claim 1, wherein the at least one device comprises a logic circuit in communication with a first processor, wherein the first processor comprises a digital signal processor.
14. The generator of claim 13, wherein the logic circuit comprises a field-programmable gate array (FPGA).
15. The generator of claim 13, wherein the at least one device comprises a second processor in communication with the logic circuit and the first processor, the second processor programmed to receive user input via at least one input device and to provide user feedback via at least one output device.
16. The generator of claim 1, wherein the generator comprises an instrument interface circuit to enable communication between the generator and a control circuit of the surgical device over a conductive pair.

17. The generator of claim 16, wherein the instrument interface is to enable communication between the generator and the control circuit of the surgical device using multiple communication channels.

18. The generator of claim 17, wherein the instrument interface is to enable communication between the generator and the control circuit of the surgical device using frequency-band separated communication channels.

19. The generator of claim 18, wherein the instrument interface circuit is to communicate with a first portion of the control circuit using an interrogation signal transmitted in a first frequency band, and wherein the instrument interface circuit is configured to communicate with a second portion of the control circuit via a communication protocol transmitted in a second frequency band.

20. The generator of claim 19, wherein the communication protocol is a single-wire communication protocol.

21. The generator of claim 2, wherein the second power transformer outputs comprise a first blocking capacitor in series with a second blocking capacitor, and wherein the at least one device is programmed to monitor a voltage between the first and second capacitors to determine when one of the first and second capacitors has failed.

22. A method for determining motional branch current in an ultrasonic transducer of an ultrasonic surgical device over multiple frequencies of a transducer drive signal, the method comprising:

- at each of a plurality of frequencies of the transducer drive signal:
 - oversampling a current and voltage of the transducer drive signal;
 - receiving, by a processor, the current and voltage samples;
 - determining, by the processor, the motional branch current based on the current and voltage samples, a static capacitance of the ultrasonic transducer and the frequency of the transducer drive signal.

23. A method for controlling a waveform shape of a motional branch current in an ultrasonic transducer of a surgical device, the method comprising:

generating a transducer drive signal by selectively recalling, using a direct digital synthesis (DDS) algorithm, drive signal waveform samples stored in a look-up table (LUT);

generating samples of current and voltage of the transducer drive signal when the transducer drive signal is communicated to the surgical device;

determining samples of the motional branch current based on the current and voltage samples, a static capacitance of the ultrasonic transducer and a frequency of the transducer drive signal;

comparing each sample of the motional branch current to a respective target sample of a target waveform to determine an error amplitude; and

modifying the drive signal waveform samples stored in the LUT such that an amplitude error between subsequent samples of the motional branch current and respective target samples is reduced.

24. The method of claim 23, wherein the target waveform comprises a sinusoid waveform.

25. The method of claim 23, wherein the target waveform comprises at least two superimposed waveforms.

26. The method of claim 25, wherein the target waveform comprises a sinusoid waveform superimposed with an n-order harmonic of the sinusoid waveform, wherein n is a positive integer.

27. A generator to communicate a drive signal to a surgical device, the generator comprising:

a memory;

a device coupled to the memory, the device to receive, for each of a plurality of drive signal waveform samples used to synthesize the drive signal, a corresponding set of current and voltage samples of the drive signal, and, for each drive signal waveform sample and corresponding set of current and voltage samples, the device to:

store the samples in a memory of the device to associate the stored samples with the drive signal waveform sample;

when the drive signal comprises a first drive signal to be communicated to an ultrasonic surgical device:

determine a motional branch current sample of the ultrasonic surgical device based on the stored samples;

compare the motional branch current sample to a target sample selected from a plurality of target samples that define a target waveform, the target sample selected based on the drive signal waveform sample;

determine an amplitude error between the target sample and the motional branch current sample; and

modify the drive signal waveform sample such that an amplitude error determined between the target sample and a subsequent motional branch current sample based on current and voltage samples associated with the modified drive signal waveform sample is reduced.

28. A surgical generator for providing a drive signal to a surgical device, the generator comprising:

a first transformer comprising a first primary winding and a first secondary winding;

a second transformer comprising a second primary winding and a second secondary winding;

a generator circuit to generate the drive signal, wherein the generator circuit is electrically coupled to the first primary winding to provide the drive signal across the first primary winding;

a patient-side circuit electrically isolated from the generator circuit, wherein the patient-side circuit is electrically coupled to the first secondary winding, and wherein the patient-side circuit comprises first and second output lines to provide the drive signal to the surgical device; and

a capacitor, wherein the capacitor and the second secondary winding are electrically coupled in series between the first output line and ground.

29. The surgical generator of claim 28, wherein the capacitor has a first electrode electrically coupled to the first output line and a second electrode electrically coupled to the second secondary winding.

30. The surgical generator of claim 29, wherein the second secondary winding comprises a first electrode electrically coupled to the second electrode of the capacitor and a second electrode electrically coupled to ground.

31. The surgical generator of claim 30, wherein the load resistor has a first electrode electrically coupled to the first electrode of the second secondary winding and a second electrode electrically coupled to the second electrode of the second secondary winding.

32. The surgical generator of claim 28, wherein the second secondary winding comprises a first electrode electrically coupled to the first output line and a second electrode electrically coupled to the capacitor.

33. The surgical generator of claim 28, wherein the capacitor comprises a first electrode electrically coupled to the second electrode of the second secondary winding and a second electrode electrically coupled to ground.

34. The surgical generator of claim 28, further comprising:
a correction circuit positioned in series between the capacitor and ground; and
a correction control circuit, wherein the correction circuit is programmed to:
 receive input describing at least one of a current of the drive signal, a voltage of the drive signal and a load condition describing a property of tissue acted upon by the drive signal;
 calculate a correction signal; and
 provide the correction signal to the correction circuit;

35. The surgical generator of claim 34, wherein the correction control circuit comprises:
at least one processor;
at least one analog-to-digital converter to convert the input to digital; and
at least one digital-to-analog converter to convert the correction signal to analog.

36. The surgical generator of claim 28, wherein the capacitor is a Y-type capacitor.

37. The surgical generator of claim 28, further comprising a load resistor electrically coupled in parallel with the second secondary winding, wherein a polarity of the second secondary winding relative to second primary winding is opposite of a polarity of the first secondary winding.

38. A surgical generator for providing a drive signal to a surgical device, the generator comprising:

a first transformer comprising a primary winding, a first secondary winding, and a second secondary winding, wherein a polarity of the first secondary winding relative to the primary winding is opposite the polarity of the second secondary winding;

a generator circuit to generate the drive signal, wherein the generator circuit is electrically coupled to the first primary winding to provide the drive signal across the first primary winding;

a patient-side circuit electrically isolated from the generator circuit, wherein the patient-side circuit is electrically coupled to the first secondary winding, and wherein the patient-side circuit comprises first and second output lines to provide the drive signal to the surgical device; and

a capacitor, wherein the capacitor and second secondary winding are electrically coupled in series between the first output line and ground.

39. The surgical generator of claim 38, wherein the capacitor has a first electrode electrically coupled to the first output line and a second electrode electrically coupled to the second secondary winding.

40. The surgical generator of claim 39, wherein the second secondary winding comprises a first electrode electrically coupled to the second electrode of the capacitor and a second electrode electrically coupled to ground.

41. The surgical generator of claim 40, further comprising a load resistor electrically coupled in parallel with the second secondary winding, wherein the load resistor has a first electrode electrically coupled to the first electrode of the second secondary winding and a second electrode electrically coupled to the second electrode of the second secondary winding.

42. The surgical generator of claim 38, wherein the second secondary winding comprises a first electrode electrically coupled to the first output line and a second electrode electrically coupled to the capacitor.

43. The surgical generator of claim 38, wherein the capacitor comprises a first electrode electrically coupled to the second electrode of the second secondary winding and a second electrode electrically coupled to ground.

44. The surgical generator of claim 38, further comprising:
a correction control circuit positioned in series between the capacitor and ground; and
a correction control circuit, wherein the correction circuit is programmed to:
receive input describing at least one of a current of the drive signal, a voltage of the drive signal and a load condition describing a property of tissue acted upon by the drive signal;
calculate a correction signal; and
provide the correction signal to the correction circuit;

45. The surgical generator of claim 44, wherein the correction control circuit comprises:
at least one processor;
at least one analog-to-digital converter to convert the input to digital; and
at least one digital-to-analog converter to convert the correction signal to analog.

46. The surgical generator of claim 38, wherein the capacitor is a Y-type capacitor.

47. A surgical generator for providing a drive signal to a surgical device, the generator comprising:
a first transformer comprising a primary winding and a secondary winding;
a generator circuit to generate the drive signal, wherein the generator circuit is electrically coupled to the first primary winding to provide the drive signal across the first primary winding;
a patient-side circuit electrically isolated from the generator circuit, wherein the patient-side circuit is electrically coupled to the secondary winding, and wherein the patient-side circuit comprises first and second output lines to provide the drive signal to the surgical device;

a capacitor, wherein the capacitor and is electrically coupled to the primary winding and electrically coupled to the first output line.

48. The surgical generator of claim 47, wherein the capacitor is a Y-type capacitor.

49. A surgical generator for providing a drive signal to a surgical device, the generator comprising:

a first transformer comprising a primary winding and a secondary winding;

a generator circuit to generate the drive signal, wherein the generator circuit is electrically coupled to the first primary winding to provide the drive signal across the first primary winding;

a patient-side circuit electrically isolated from the generator circuit, wherein the patient-side circuit is electrically coupled to the secondary winding, and wherein the patient-side circuit comprises first and second output lines to provide the drive signal to the surgical device;

a first capacitor, wherein a first electrode of the first capacitor and is electrically coupled to the primary winding;

a second capacitor, wherein a first electrode of the second capacitor is electrically coupled to the first output line and a second electrode of the second capacitor is electrically coupled to a second electrode of the first capacitor;

a third capacitor, wherein the a first electrode of the third capacitor is electrically coupled to the second electrode of the first capacitor and the second electrode of the second capacitor, and wherein a second electrode of the third capacitor is electrically coupled to ground.

50. The surgical generator of claim 49, wherein the second capacitor is a Y-type capacitor.

51. A control circuit of a surgical device, the control circuit comprising:

a first circuit portion comprising at least one first switch, the first circuit portion to communicate with a surgical generator over a conductor pair; and

a second circuit portion comprising a data circuit element, the data circuit element disposed in an instrument of the surgical device and to transmit or receive data, the data circuit element to implement data communications with the surgical generator over at least one conductor of the conductor pair.

52. The control circuit of claim 51, wherein the data circuit element comprises a single-wire bus device to implement data communications with the surgical generator over a single conductor of the conductor pair.

53. The control circuit of claim 51, wherein the data circuit element comprises a data storage device for storing data to be retrieved by the surgical generator.

54. The control circuit of claim 53, wherein at least a portion of the data stored by the data storage device is transmitted to the data storage device by the surgical generator.

55. The control circuit of claim 53, wherein the data storage device comprises an electrically erasable programmable read-only memory (EEPROM).

56. The control circuit of claim 51, wherein the data circuit element comprises a data input device.

57. The control circuit of claim 56, wherein the data circuit element comprises an indicator to provide a user indication based on data received by the data circuit element from the surgical generator.

58. The control circuit of claim 51, wherein the data circuit element comprises a data output device.

59. The control circuit of claim 58, wherein the data circuit element is to communicate with a sensor disposed in the instrument, and wherein the data circuit element is to transmit sensor data to the surgical generator.

60. The control circuit of claim 51, wherein communications between the surgical generator and the first and second circuit portions are frequency-band separated.

61. The control circuit of claim 60, wherein the first circuit portion is to receive a first interrogation signal transmitted from the surgical generator in a first frequency band, and wherein the first interrogation signal is blocked from the second circuit portion.

62. The control circuit of claim 61, wherein the data circuit element is to communicate with the surgical generator using a communication protocol transmitted in a second frequency band.
63. The control circuit of claim 61, wherein a characteristic of the first interrogation signal, when received through the first circuit portion, is indicative of a state of the at least one first switch.
64. The control circuit of claim 63, wherein the characteristic of the first interrogation signal comprises at least one of: voltage, current, amplitude, and phase.
65. The control circuit of claim 61, wherein the first interrogation signal comprises a bipolar current signal.
66. The control circuit of claim 61, wherein the first interrogation signal has a frequency of about 2 kHz.
67. The control circuit of claim 60, wherein the second circuit portion comprises an inductive element to isolate the at least one first switch from the data circuit element.
68. The control circuit of claim 61, wherein the second circuit portion comprises at least one second switch.
69. The control circuit of claim 68, wherein the second circuit portion is to receive a second interrogation signal transmitted from the surgical generator in a third frequency band.
70. The control circuit of claim 69, wherein a characteristic of the second interrogation signal, when received through the second circuit portion, is indicative of a state of the at least one second switch.
71. The control circuit of claim 69, wherein the at least one second switch is frequency-band separated from the data circuit element and from the first circuit portion such that the second interrogation signal is blocked from the data circuit element and the first circuit portion.
72. A control circuit of surgical device, the control circuit comprising:

a first circuit portion comprising at least one first switch, the first circuit portion to communicate with a surgical generator over a conductor pair; and

a second circuit portion comprising a data circuit element, the data circuit element disposed in an instrument of the surgical device and to transmit or receive data, the data circuit element to implement data communications with the surgical generator over at least one conductor of the conductor pair;

wherein the first circuit portion is to receive a first interrogation signal transmitted from the surgical generator in a first frequency band; and

wherein the data circuit element is to communicate with the surgical generator using an amplitude-modulated communication protocol transmitted in a second frequency band, wherein the second frequency band is higher than the first frequency band.

73. The control circuit of claim 72, wherein the first interrogation signal comprises a bipolar current signal at a frequency of about 2 kHz, and wherein a carrier frequency of the amplitude-modulated communication protocol is at least 8 MHz.

74. The control circuit of claim 72, wherein the second circuit portion comprises a demodulation circuit to demodulate the amplitude-modulated communication protocol.

75. The control circuit of claim 72, wherein the second circuit portion comprises an inductive element to isolate the at least one first switch from the data circuit element.

76. The control circuit of claim 72, wherein the second circuit portion comprises at least one second switch.

77. The control circuit of claim 76, wherein the second circuit portion is to receive a second interrogation signal transmitted from the surgical generator in a third frequency band, wherein a characteristic of the second interrogation signal, when received through the second circuit portion, is indicative of a state of the at least one second switch.

78. The control circuit of claim 77, wherein the at least one second switch is frequency-band separated from the data circuit element and from the first circuit portion such that the second interrogation signal is blocked from the data circuit element and the first circuit portion.

79. A control circuit of a surgical device, the control circuit comprising:
a first circuit portion comprising at least one first switch, wherein the first circuit portion is to receive a first interrogation signal transmitted from a surgical generator over a conductor pair;
and
a second circuit portion comprising at least one of a resistive element and an inductive element disposed in an instrument of the device, wherein the second circuit portion is to receive a second interrogation signal transmitted from the surgical generator over the conductor pair;
wherein the second circuit portion is frequency-band separated from the first circuit portion;
wherein a characteristic of the first interrogation signal, when received through the first circuit portion, is indicative of a state of the at least one first switch; and
wherein a characteristic of the second interrogation signal, when received through the second circuit portion, uniquely identifies the instrument of the device.
80. A control circuit of a surgical device, the control circuit comprising:
a first circuit portion comprising a first switch network and a second switch network, the first switch network comprising at least one first switch, the second switch network comprising at least one second switch, the first circuit portion to communicate with a surgical generator over a conductor pair; and
a second circuit portion comprising a data circuit element, the data circuit element disposed in an instrument of the surgical device to transmit or receive data, the data circuit element in data communication with the surgical generator over at least one conductor of the conductor pair.
81. The control circuit of claim 80, wherein the data circuit element comprises a single-wire bus device in data communication with the surgical generator over a single conductor of the conductor pair.
82. The control circuit of claim 80, wherein the data circuit element comprises a data storage device for storing data retrievable by the surgical generator.
83. The control circuit of claim 82, wherein at least a portion of the data stored by the data storage device is transmitted to the data storage device by the surgical generator.

84. The control circuit of claim 82, wherein the data storage device comprises an electrically erasable programmable read-only memory (EEPROM).

85. The control circuit of claim 80, wherein the data circuit element comprises a data input device.

86. The control circuit of claim 85, wherein the data circuit element comprises an indicator to provide a user indication based on data received by the data circuit element from the surgical generator.

87. The control circuit of claim 80, wherein the data circuit element comprises a data output device.

88. The control circuit of claim 87, wherein the data circuit element is in communication with a sensor disposed in the instrument, the data circuit element to transmit sensor data to the surgical generator.

89. The control circuit of claim 80, wherein the first switch network comprises a plurality of series-connected first diodes, wherein each first switch is connected in parallel with at least one of the first diodes, wherein the second switch network comprises a plurality of series-connected second diodes, and wherein each second switch is connected in parallel with at least one of the second diodes.

90. The control circuit of claim 89, wherein the first circuit portion is to receive a bipolar current signal transmitted from the surgical generator, wherein a first polarity of the bipolar current signal is received through the first switch network to generate a first voltage across the first circuit portion, and wherein a second polarity of the bipolar current signal is received through the second switch network to generate a second voltage across the first circuit portion.

91. The control circuit of claim 90, wherein a frequency of the bipolar current signal is about 2 kHz.

92. The control circuit of claim 90, wherein the first voltage is measurable by the surgical generator to determine a state of the at least one first switch, and wherein the second voltage is measurable by the surgical generator to determine a state of the at least one second switch.

93. A surgical generator for providing a drive signal to a surgical device, comprising:
a surgical generator body having an aperture; and
a receptacle assembly positioned in the aperture, the receptacle assembly comprising:
a receptacle body;
a flange having an inner wall and an outer wall, the inner wall comprised of at least one curved section and at least one linear section, the inner wall defining a cavity; and
a central protruding portion positioned in the cavity, the central protruding portion comprising:
a plurality of sockets;
a magnet;
an outer periphery comprising at least one curved section and at least one linear section.

94. The surgical generator of claim 93, wherein the at least one curved section of the outer periphery is parallel to the at least one curved section of the inner wall.

95. The surgical generator of claim 94, wherein the at least one linear section of the outer periphery is parallel to the at least one linear section of the inner wall.

96. The surgical generator of claim 93, wherein the central protruding portion defines a central recess, wherein the magnet is positioned proximate the central recess.

97. The surgical generator of claim 93, wherein the flange has a flange surface and the central protruding portion has central surface, wherein the flange surface is slanted with respect to the central surface.

98. The surgical generator of claim 97, wherein the surgical generator body comprises a slanted surface, wherein the aperture is positioned on the slanted surface, and wherein the slanted surface is substantially parallel to the flange outer surface.

99. A surgical instrument, comprising:
an electrical connector assembly, the electrical connector assembly comprising:
a flange defining a central cavity;
a magnetically compatible pin extending into the central cavity;
a circuit board;
a plurality of electrically conductive pins coupled to the circuit board, each of the plurality of electrically conductive pins extending into the central cavity;
a strain relief member; and
a boot.
100. The surgical instrument of claim 99, wherein the flange comprises at least one curved section and at least one linear section.
101. The surgical instrument of claim 99, wherein the electrical connector assembly comprises a wall, the wall defining apertures to receive the magnetically compatible pin and the plurality of electrically conductive pins.
102. The surgical instrument of claim 101, wherein the magnetically compatible pin comprises a shoulder, wherein the shoulder is positioned intermediate the wall and the circuit board.
103. The surgical instrument of claim 99, comprising surgical instrument identification circuitry.
104. The surgical instrument of claim 103, wherein the surgical instrument identification circuitry comprises at least one of an EEPROM and a resistor.
105. A surgical instrument system, comprising:
a surgical generator comprising a receptacle assembly, the receptacle assembly comprising at least one curved section and at least one linear portion;
a surgical instrument comprising a connector assembly;
an adapter assembly operatively coupled to the receptacle assembly and the connector assembly, the adapter assembly comprising:
a distal portion contacting the receptacle assembly, the distal portion

comprising a flange, the flange having at least one curved section and at least one linear portion;

a proximal portion contacting the connector assembly, the proximal portion defining a cavity dimensioned to receive at least a portion of the connector assembly;
a circuit board.

106 The surgical instrument system of claim 105, comprising surgical instrument identification circuitry coupled to the circuit board.

107. The surgical instrument system of claim 106, wherein the surgical instrument identification circuitry comprises at least one of an EEPROM and a resistor.

108. The surgical instrument system of claim 105, wherein the receptacle assembly comprises a flange having an inner wall and an outer wall, the inner wall comprised of the at least one curved section and the at least one linear section, the inner wall defining a cavity.

109. The surgical instrument system of claim 108, wherein the receptacle assembly comprises a central protruding portion positioned in the cavity, the central protruding portion comprising:

a plurality of sockets arranged in a generally circular formation;
a magnet positioned internal to the generally circular formation;
an outer periphery comprising at least one curved section and at least one linear section.

110. The surgical instrument system of claim 109, wherein the adapter assembly comprises a ferrous pin extending into a central cavity defined by the distal flange.

111. The surgical instrument system of claim 110, wherein the ferrous pin is cylindrical and comprises a shoulder.

112. The surgical instrument system of claim 110, wherein the adapter assembly comprises a plurality of electrically conductive pins coupled to the circuit board and extending into the central cavity defined by the distal flange.

113. A method for controlling electrical power provided to tissue via first and second electrodes, the method comprising:

- providing a drive signal to the tissue via the first and second electrodes;
- modulating a power provided to the tissue via the drive signal based on a sensed tissue impedance according to a first power curve, wherein the first power curve defines, for each of a plurality of potential sensed tissue impedances, a first corresponding power;
- monitoring a total energy provided to the tissue via the first and second electrodes;
- when the total energy reaches a first energy threshold, determining whether an impedance of the tissue has reached a first impedance threshold; and
- conditioned upon the impedance of the tissue failing to reach the first impedance threshold, modulating the power provided to the tissue via the drive signal based on the sensed tissue impedance according to a second power curve, wherein the second power curve defines, for each of the plurality of potential sensed tissue impedances, a second corresponding power.

114. The method of claim 113, wherein the first corresponding power is less than the second corresponding power for at least half of the plurality of potential sensed tissue impedances.

115. The method of claim 113, wherein a sum of the first corresponding power over the plurality of potential sensed tissue impedance is less than a sum of the second corresponding power over the plurality of potential sensed tissue impedances.

116. The method of claim 113, further comprising:

- while modulating the power provided to the second tissue via the drive signal according to the second power curve, when the total energy reaches a second energy threshold, determining whether the sensed tissue impedance has reached the first impedance threshold; and
- conditioned upon the sensed tissue impedance failing to reach the first impedance threshold, modulating the power provided to the tissue via the drive signal according to a third power curve, wherein the third power curve defines, for each of the plurality of potential sensed tissue impedances, a third corresponding power.

117. The method of claim 116, wherein the second corresponding power is less than the third corresponding power for at least half of the plurality of potential sensed tissue impedances.

118. The method of claim 113, further comprising:
while modulating the power provided to the second tissue via the drive signal according to the second power curve, when the total energy reaches a second energy threshold, determining whether the sensed tissue impedance has reached a second impedance threshold; and

conditioned upon the sensed tissue impedance failing to reach a second impedance threshold, modulating the power provided to the tissue via the drive signal according to a third power curve, wherein the third power curve defines, for each of the plurality of potential sensed tissue impedances, a third corresponding power.

119. The method of claim 113, wherein the first impedance threshold is a predetermined tissue impedance.

120. The method of claim 113, wherein the first impedance threshold is a predetermined tissue impedance rate of change.

121. The method of claim 113, wherein the first impedance threshold is based on both a predetermined tissue impedance and a predetermined tissue impedance rate of change.

122. The method of claim 113, wherein modulating the power provided to the tissue via the drive signal comprises at least one action selected from the group consisting of: modulating a current level of the drive signal; modulating a voltage level of the drive signal; and modulating a duty cycle of the drive signal.

123. The method of claim 113, wherein for each of the plurality of potential sensed tissue impedances, the second corresponding power is equal to the first corresponding power multiplied by a constant.

124. The method of claim 113, further comprising terminating the provision of energy to the tissue when a termination threshold is reached.

125. The method of claim 124, wherein the termination threshold is based on a power curve.

126. A surgical system, the surgical system comprising:
a generator comprising at least one processor and operatively associated memory, wherein the memory comprises instructions that, when executed by the at least one processor, cause the surgical system to:
provide a drive signal to the tissue via first and second electrodes;
modulate a power provided to the tissue via the drive signal based on a sensed tissue impedance according to a first power curve, wherein the first power curve defines, for each of a plurality of potential sensed tissue impedances, a first corresponding power;
monitor a total energy provided to the tissue via the first and second electrodes;
when the total energy reaches a first energy threshold, determine whether an impedance of the tissue has reached a first impedance threshold; and
conditioned upon the impedance of the tissue failing to reach the first impedance threshold, modulate the power provided to the tissue via the drive signal based on the sensed tissue impedance according to a second power curve, wherein the second power curve defines, for each of the plurality of potential sensed tissue impedances, a second corresponding power.

127. The surgical device of claim 126, wherein the surgical system further comprises a surgical device in communication with the generator, wherein the surgical device comprises the first and second electrodes.

128. A method for controlling electrical power provided to tissue via first and second electrodes, the method comprising:
providing a drive signal to the tissue via the first and second electrodes;
determining a power to be provided to the tissue, wherein the determining comprises:
receiving an indication of a sensed tissue impedance;
determining a first corresponding power for the sensed tissue impedance according to a power curve, wherein the power curve defines a corresponding power for each of a plurality of potential sensed tissue impedances;

multiplying the corresponding power by a multiplier;
modulating the drive signal to provide the determined power to the tissue;
conditioned upon the impedance of the tissue failing to reach a first impedance threshold, increasing the multiplier as a function of the total energy provided to the tissue.

129. The method of claim 128 further comprising conditioned upon the impedance of the tissue reaching the first impedance threshold, maintaining the multiplier at its current value.

130. The method of claim 126, further comprising continuing to apply energy with the multiplier at its current value until a termination threshold is reached.

131. The method of claim 130, wherein the termination threshold is based at least in part on the current value of the multiplier.

132. The method of claim 128, wherein modulating the drive signal to provide the determined power to the tissue comprises at least one action selected from the group consisting of: modulating a current level of the drive signal; modulating a voltage level of the drive signal; and modulating a duty cycle of the drive signal.

133. The method of claim 128, wherein the first impedance threshold is a predetermined tissue impedance.

134. The method of claim 128, wherein the first impedance threshold is a predetermined tissue impedance rate of change.

135. The method of claim 128, wherein the first impedance threshold is based on both a predetermined tissue impedance and a predetermined tissue impedance rate of change.

136. A surgical system, the surgical system comprising:
a generator comprising at least one processor and operatively associated memory, wherein the memory comprises instructions that, when executed by the at least one processor, cause the surgical system to:
provide a drive signal to the tissue via first and second electrodes;

determine a power to be provided to the tissue, wherein the determining comprises:

- receiving an indication of a sensed tissue impedance;
- determining a first corresponding power for the sensed tissue impedance according to a power curve, wherein the power curve defines a corresponding power for each of a plurality of potential sensed tissue impedances;
- multiplying the corresponding power by a multiplier;
- modulate the drive signal to provide the determined power to the tissue;
- conditioned upon the impedance of the tissue failing to reach a first impedance threshold, increase the multiplier as a function of the total energy provided to the tissue.

137 The surgical device of claim 136, wherein the surgical system further comprises a surgical device in communication with the generator, wherein the surgical device comprises the first and second electrodes.

138. A method for controlling electrical power provided to tissue via first and second electrodes, the method comprising:

- providing a drive signal to the tissue via the first and second electrodes;
- determining a power to be provided to the tissue, wherein the determining comprises:
 - receiving an indication of a sensed tissue impedance;
 - determining a first corresponding power for the sensed tissue impedance according to a power curve, wherein the power curve defines a corresponding power for each of a plurality of potential sensed tissue impedances;
 - multiplying the corresponding power by a first multiplier to find a determined power;
- modulating the drive signal to provide the determined power to the tissue;
- monitoring a total energy provided to the tissue via the first and second electrodes;
- when the total energy reaches a first energy threshold, determining whether the impedance of the tissue has reached a first impedance threshold; and
- conditioned upon the impedance of the tissue not reaching the first impedance threshold, increasing the first multiplier by a first amount.

139. The method of claim 138, further comprising:

when the total energy reaches a second energy threshold, determining whether the impedance of the tissue has reached the second impedance threshold; and

conditioned upon the impedance of the tissue not reaching the second impedance threshold, increasing the first multiplier by a second amount.

140. The method of claim 138, wherein the first impedance threshold is a predetermined tissue impedance.

141. The method of claim 138, wherein the first impedance threshold is a predetermined tissue impedance rate of change.

142. The method of claim 138, wherein the first impedance threshold is based on both a predetermined tissue impedance and a predetermined tissue impedance rate of change.

143. The method of claim 138, wherein modulating a power provided to the tissue via the drive signal comprises at least one action selected from the group consisting of: modulating a current level of the drive signal; modulating a voltage level of the drive signal; and modulating a duty cycle of the drive signal.

144. A surgical system, the surgical system comprising:
a generator comprising at least one processor and operatively associated memory, wherein the memory comprises instructions that, when executed by the at least one processor, cause the surgical device to:

provide a drive signal to tissue via first and second electrodes;

determine a power to be provided to the tissue, wherein the determining comprises:

receiving an indication of a sensed tissue impedance;

determining a first corresponding power for the sensed tissue impedance according to a power curve, wherein the power curve defines a corresponding power for each of a plurality of potential sensed tissue impedances;

multiplying the corresponding power by a first multiplier;

modulate the drive signal to provide the determined power to the tissue;

monitor a total energy provided to the tissue via the first and second electrodes;

when the total energy reaches a first energy threshold, determine whether the impedance of the tissue has reached a first impedance threshold; and

conditioned upon the impedance of the tissue not reaching the first impedance threshold, increase the first multiplier by a first amount.

145. The surgical system of claim 144, wherein the surgical system further comprises a surgical device in communication with the generator, wherein the surgical device comprises the first and second electrodes.

146. A method for controlling electrical power provided to tissue via a surgical device, the method comprising:

providing a drive signal to a surgical device;
receiving an indication of an impedance of the tissue;
calculating a rate of increase of the impedance of the tissue;
modulating the drive signal to hold the rate of increase of the impedance greater than or equal to a predetermined constant.

147. The method of claim 146, further comprising modulating the drive signal to hold the rate of increase of the impedance equal to the predetermined constant.

148. The method of claim 146, further comprising:
determining a total energy provided to the tissue via the surgical device at a first time;
conditioned upon the total energy exceeding a first energy threshold, determining if the impedance of the tissue has reached a first impedance threshold;
conditioned upon the tissue not having reached the first impedance threshold, modulating the drive signal to hold the rate of increase of the impedance greater than or equal to a second predetermined constant, wherein the second predetermined constant is greater than the first predetermined constant.

149. The method of claim 148, further comprising
determining a total energy provided to the tissue via the surgical device at a second time;
conditioned upon the second total energy exceeding a second energy threshold, determining if the impedance of the tissue has reached a second impedance threshold;

conditioned upon the tissue not having reached the second impedance threshold, modulating the drive signal to hold the rate of increase of the impedance greater than or equal to a third predetermined constant, wherein the third predetermined constant is greater than the first predetermined constant.

150. The method of claim 146, further comprising:
modulating the drive signal to hold the rate of increase of the impedance greater than or equal to a predetermined constant for a first predetermined time period; and
at the expiration of the first predetermined time period, modulating the drive signal to hold the rate of increase of the impedance greater than or equal to a second predetermined constant.

151. The method of claim 150, wherein the second predetermined constant is greater than the first predetermined constant.

152. The method of claim 150, further comprising:
at the expiration of the first predetermined time period, modulating the drive signal to hold the rate of increase of the impedance greater than or equal to a second predetermined constant for a second predetermined time period; and
at the expiration of the second predetermined time period, modulating the drive signal to hold the rate of increase of the impedance greater than or equal to a third predetermined constant.

153. The method of claim 152, wherein the third predetermined constant is greater than the second predetermined constant.

154. The method of claim 152, wherein the third predetermined constant is less than the second predetermined constant.

155. The method of claim 146, wherein providing the drive signal comprises providing the drive signal to first and second electrodes, wherein the tissue is in electrical communication with the first and second electrodes.

156. A surgical system, the surgical system comprising:

a generator comprising at least one processor and operatively associated memory, wherein the memory comprises instructions that, when executed by the at least one processor, cause the generator to:

providing a drive signal to a surgical device;

receive an indication of an impedance of the tissue;

calculate a rate of increase of the impedance of the tissue;

modulate the drive signal to hold the rate of increase of the impedance greater than or equal to a predetermined constant.

157. The system of claim 156, wherein the memory further comprises instructions that, when executed by the at least one processor, cause the generator to modulate the drive signal to hold the rate of increase of the impedance equal to the predetermined constant.

158. The system of claim 156, wherein the memory further comprises instructions that, when executed by the at least one processor, cause the generator to:

determine a total energy provided to the tissue via the surgical device at a first time;

conditioned upon the total energy exceeding a first energy threshold, determine if the impedance of the tissue has reached a first impedance threshold;

conditioned upon the tissue not having reached the first impedance threshold, modulate the drive signal to hold the rate of increase of the impedance greater than or equal to a second predetermined constant, wherein the second predetermined constant is greater than the first predetermined constant.

159. The system of claim 158, wherein the memory further comprises instructions that, when executed by the at least one processor, cause the generator to:

determine a total energy provided to the tissue via the surgical device at a second time;

conditioned upon the second total energy exceeding a second energy threshold, determine if the impedance of the tissue has reached a second impedance threshold;

conditioned upon the tissue not having reached the second impedance threshold, modulate the drive signal to hold the rate of increase of the impedance greater than or equal to a third predetermined constant, wherein the third predetermined constant is greater than the first predetermined constant.

160. The system of claim 156, wherein the memory further comprises instructions that, when executed by the at least one processor, cause the generator to:

modulate the drive signal to hold the rate of increase of the impedance greater than or equal to a predetermined constant for a first predetermined time period; and

at the expiration of the first predetermined time period, modulate the drive signal to hold the rate of increase of the impedance greater than or equal to a second predetermined constant.

161. The system of claim 160, wherein the second predetermined constant is greater than the first predetermined constant.

162. The system of claim 160, wherein the memory further comprises instructions that, when executed by the at least one processor, cause the generator to:

at the expiration of the first predetermined time period, modulate the drive signal to hold the rate of increase of the impedance greater than or equal to a second predetermined constant for a second predetermined time period; and

at the expiration of the second predetermined time period, modulate the drive signal to hold the rate of increase of the impedance greater than or equal to a third predetermined constant.

163. The system of claim 162, wherein the third predetermined constant is greater than the second predetermined constant.

164. The system of claim 162, wherein the third predetermined constant is less than the second predetermined constant.

165. The system of claim 156, wherein providing the drive signal comprises providing the drive signal to first and second electrodes, wherein the tissue is in electrical communication with the first and second electrodes.

166. A method for controlling electrical power provided to tissue via a surgical device:

providing a drive signal, wherein a power of the drive signal is proportional to a power provided to the tissue via the surgical device;

periodically receiving indications of an impedance of the tissue;

applying a first composite power curve to the tissue, wherein applying the first composite power curve to the tissue comprises:

modulating a first predetermined number of first composite power curve pulses on the drive signal; and

for each of the first composite power curve pulses, determining a pulse power and a pulse width according to a first function of the impedance of the tissue;

applying a second composite power curve to the tissue, wherein applying the second composite power curve to the tissue comprises:

modulating at least one second composite power curve pulse on the drive signal; and

for each of the at least one second composite power curve pulses, determining a pulse power and a pulse width according to a second function of the impedance of the tissue.

167. The method of claim 166, further comprising:
conditioned upon the impedance of the tissue rising above the predetermined impedance threshold, interrupting the application of the second composite power curve.

168. The method of claim 167, further comprising:
conditioned upon the impedance of the tissue rising above the predetermined impedance threshold, modulating at least one cut-region power curve pulse on the drive signal; and
determining a pulse power for the at least one cut-region pulse according to the second function of the impedance of the tissue.

169. The method of claim 168, wherein a pulse width for the at least one cut region pulse is constant.

170. The method of claim 168, further comprising:
receiving an indication that a cut is complete;
upon receiving the indication that the cut is complete, modulating a predetermined number of completion pulses on the drive signal.

171. The method of claim 168, further comprising determining a power of the predetermined number of completion pulses according to the second function of the impedance of the tissue.

172. The method of claim 166, further comprising terminating the drive signal when a total time of the drive signal exceeds a timeout time.

173. The method of claim 166, wherein determining a pulse power and a pulse width of a first composite power curve pulse comprises accessing a look-up table comprising indications of potential values for the impedance of the tissue and corresponding values for pulse power and pulse width.

174. The method of claim 166, wherein modulating the at least one second composite power curve pulse on the drive signal comprises modulating a second predetermined number of second composite power curve pulses on the drive signal, and wherein the method further comprises:

applying a third composite power curve to the tissue, wherein applying the third composite power curve to the tissue comprises modulating at least one third composite power curve pulse on the drive signal, wherein each of the at least one third composite power curve pulses comprises a pulse power and a pulse width selected according to a third function of the impedance of the tissue.

175. The method of claim 166, wherein providing the drive signal comprises providing the drive signal to a harmonic transducer in mechanical communication with a harmonic end effector.

176. The method of claim 166, wherein providing the drive signal comprises providing the drive signal to first and second electrodes in electrical communication with the tissue.

177. A surgical generator for providing a drive signal to a surgical device, the generator comprising at least one processor and operatively associated memory, wherein the memory comprises instructions that, when executed by the at least one processor, cause the generator to:

generate a drive signal, wherein a power of the drive signal is proportional to a power provided to tissue via the surgical device;

periodically receive indications of an impedance of the tissue;

apply a first composite power curve to the tissue, wherein applying the first composite power curve to the tissue comprises:

modulating a first predetermined number of first composite power curve pulses on the drive signal; and

for each of the first composite power curve pulses, determine a pulse power and a pulse width according to a first function of the impedance of the tissue;

apply a second composite power curve to the tissue, wherein applying the second composite power curve to the tissue comprises:

modulating at least one second composite power curve pulse on the drive signal; and

for each of the at least one second composite power curve pulses, determining a pulse power and a pulse width according to a second function of the impedance of the tissue.

178. The surgical generator of claim 177, wherein the memory comprises instructions that, when executed by the at least one processor, cause the generator to:

conditioned upon the impedance of the tissue rising above the predetermined impedance threshold, interrupt the application the second composite power curve.

179. The surgical generator of claim 178, wherein the memory comprises instructions that, when executed by the at least one processor, cause the generator to:

conditioned upon the impedance of the tissue rising above the predetermined impedance threshold, modulate at least one cut-region power curve pulse on the drive signal; and

determine a pulse power for the at least one cut-region pulse according to the second function of the impedance of the tissue.

180. The surgical generator of claim 179, wherein a pulse width for the at least one cut region pulse is constant.

181. The surgical generator of claim 179, wherein the memory comprises instructions that, when executed by the at least one processor, cause the generator to:

receive an indication that a cut is complete;

upon receiving the indication that the cut is complete, modulate a predetermined number of completion pulses on the drive signal.

182. The surgical generator of claim 179, wherein the memory comprises instructions that, when executed by the at least one processor, cause the generator to determine a power of the predetermined number of completion pulses according to the second function of the impedance of the tissue.

183. The surgical generator of claim 177, wherein the memory comprises instructions that, when executed by the at least one processor, cause the generator to terminate the drive signal when a total time of the drive signal exceeds a timeout time.

184. The surgical generator of claim 177, wherein determining a pulse power and a pulse width of a first composite power curve pulse comprises accessing a look-up table comprising indications of potential values for the impedance of the tissue and corresponding values for pulse power and pulse width.

185. The surgical generator of claim 177, wherein modulating the at least one second composite power curve pulse on the drive signal comprises modulating a second predetermined number of second composite power curve pulses on the drive signal, and wherein the memory comprises instructions that, when executed by the at least one processor, cause the generator to:

apply a third composite power curve to the tissue, wherein applying the third composite power curve to the tissue comprises modulating at least one third composite power curve pulse on the drive signal, wherein each of the at least one third composite power curve pulses comprises a pulse power and a pulse width selected according to a third function of the impedance of the tissue.

186. The surgical generator of claim 177, wherein providing the drive signal comprises providing the drive signal to a harmonic transducer in mechanical communication with a harmonic end effector.

187. The surgical generator of claim 177, wherein providing the drive signal comprises providing the drive signal to first and second electrodes in electrical communication with the tissue.






FIG. 1

FIG. 2




2/61

FIG. 3



3/61






FIG. 5




FIG. 6




FIG. 7

7/61




FIG. 8




FIG. 9




FIG. 10




FIG. 11A (FIG. 11B)

(FIG. 11B)

(Fig. 11B)





FIG. 11B

11/61



12/61

1962




FIG. 12




FIG. 13

14/61




FIG. 14




FIG. 15

15/61




FIG. 16




FIG. 17




FIG. 18




FIG. 19

17/61




FIG. 20




FIG. 21




FIG. 22




FIG. 23

19/61




FIG. 24




FIG. 25

20/61




FIG. 26




FIG. 27




FIG. 28




FIG. 29

22/61




FIG. 30




FIG. 31

23/61





FIG. 32

CABLES


FIG. 33D



128-1


ADAPTERS

FIG. 33H




294

206



292

FIG. 33I




300-1

304

302

FIG. 33A




300-2

304

302

FIG. 33B




300-3

304

302


FIG. 33C



112-1

FIG. 33E


206



112-2

FIG. 33F

206



112-3

FIG. 33G

206





FIG. 34

26/61



27/61




FIG. 36

28/61





FIG. 37

29/61










FIG. 39

31/61





33/61




FIG. 44





FIG. 45






FIG. 49







FIG. 50






FIG. 54




FIG. 55




FIG. 56




FIG. 57




FIG. 58

39/61




FIG. 59




FIG. 60

40/61




FIG. 61




FIG. 62

41/61




FIG. 63




FIG. 64

42/61




FIG. 65




FIG. 66




FIG. 67

44/61




FIG. 68




FIG. 69

46/61

1330




FIG. 70

47/61




FIG. 71






FIG. 7Z


49/61



50/61



51/61



52/61




FIG. 74





FIG. 7S



55/61





FIG. 77



1520




FIG. 79

58/61




FIG. 80




FIG. 81

59/61




FIG. 82




FIG. 83

60/61




FIG. 84




FIG. 85

1570 ✓




FIG. 86

专利名称(译)	用于超声波装置和电外科装置的外科发生器		
公开(公告)号	EP2485670A2	公开(公告)日	2012-08-15
申请号	EP2010768130	申请日	2010-10-07
[标]申请(专利权)人(译)	伊西康内外科公司		
申请(专利权)人(译)	爱惜康内镜手术 , INC.		
当前申请(专利权)人(译)	爱惜康内镜手术 , INC.		
[标]发明人	WEINER EITAN T ALDRIDGE JEFFREY L MESSERLY JEFFREY D GIORDANO JAMES R STULEN FOSTER B MILLER MATTHEW C WILEY JEFFREY P PRICE DANIEL W KOCH ROBERT L BROTZ JOSEPH A HEIN JOHN E VOEGELE AARON C ABBOTT DANIEL J KILLINGER SCOTT B DAVISON MARK A YATES DAVID C MONSON GAVIN M TEBBE MARK E CLEM WILLIAM E		
发明人	WEINER, EITAN, T. ALDRIDGE, JEFFREY, L. MESSERLY, JEFFREY, D. GIORDANO, JAMES, R. STULEN, FOSTER, B. MILLER, MATTHEW, C. WILEY, JEFFREY, P. PRICE, DANIEL, W. KOCH, ROBERT, L. BROTZ, JOSEPH, A. HEIN, JOHN, E. VOEGELE, AARON, C. ABBOTT, DANIEL, J. KILLINGER, SCOTT, B. DAVISON, MARK, A. YATES, DAVID, C. MONSON, GAVIN, M. TEBBE, MARK E. CLEM, WILLIAM E.		
IPC分类号	A61B18/12 B06B1/02 A61B17/32		
CPC分类号			

A61B18/1206 A61B18/1233 A61B18/14 A61B18/1445 A61B2017/00017 A61B2017/00477 A61B2017/00482 A61B2017/00486 A61B2017/2934 A61B2017/2936 A61B2017/320069 A61B2017/320071 A61B2017/320094 A61B2017/320095 A61B2018/00178 A61B2018/00666 A61B2018/00678 A61B2018/00779 A61B2018/00875 A61B2018/00994 A61B2018/00684 A61B2018/00702 A61B2018/0072 A61B2018/00732 A61B2018/00767 A61B2018/00827 A61B2018/00892 H01R2201/12 A61B17/320092 A61B2018/00988 H01L41/042 A61B2018/00601 A61B2018/0063 A61B2018/00803

优先权

12/896384 2010-10-01 US
12/896470 2010-10-01 US
12/896479 2010-10-01 US
12/896451 2010-10-01 US
12/896360 2010-10-01 US
12/896467 2010-10-01 US
12/896345 2010-10-01 US
61/250217 2009-10-09 US

其他公开文献

EP2485670B1

外部链接

[Espacenet](#)

摘要(译)

一种外科发生器，其可以产生驱动信号或特定电压，电流和频率的信号，例如，每秒55,500个周期（Hz）。一个或多个驱动信号可以提供给超声外科手术设备，具体地提供给换能器。在一个实施例中，发生器可以被配置为产生特定电压，电流和/或频率输出信号的驱动信号，该信号可以以高分辨率，精确度和可重复性步进。另外，外科发生器可产生驱动信号或信号，其输出功率足以使用射频（RF）能量执行双极电外科手术。例如，可以将驱动信号提供给电外科装置的电极。因此，发生器可以被配置用于治疗目的，通过向超声换能器施加电信号或者向组织施加足以处理组织的电能（例如，切割，凝结，烧灼，组织焊接等）。