



US 20050182339A1

(19) **United States**(12) **Patent Application Publication** (10) **Pub. No.: US 2005/0182339 A1****Lee et al.**(43) **Pub. Date: Aug. 18, 2005**(54) **EXCISIONAL BIOPSY DEVICES AND METHODS**(52) **U.S. Cl. 600/564; 606/167; 600/567**(76) **Inventors: Roberta Lee**, Redwood City, CA (US);
James W. Vetter, Portola Valley, CA (US);
Ary S. Chernomorsky, Millbrae, CA (US)(57) **ABSTRACT**


Correspondence Address:

YOUNG LAW FIRM**A PROFESSIONAL CORPORATION****4370 ALPINE ROAD SUITE 106****PORTOLA VALLEY, CA 94028**

An excisional biopsy system includes a tubular member that has a proximal end and a distal end in which one or more windows are defined. A first removable probe has a proximal portion that includes a cutting tool extender and a distal portion that includes a cutting tool. The first removable probe may be configured to fit at least partially within the tubular member to enable the cutting tool to selectively bow out of and to retract within one of the windows when the cutting tool extender is activated. A second removable probe has a proximal section that includes a tissue collection device extender and a distal section that includes a tissue collection device. The second removable probe may also be configured to fit at least partially within the tubular member to enable the tissue collection device to extend out of and to retract within one of the windows when the tissue collection device extender is activated. A third removable probe may also be provided. The third removable probe may also be configured to fit at least partially within the tubular member and may include an imaging device, such as an ultrasound transducer, mounted therein. By selectively activating the cutting tool and the tissue collection device while rotating the excisional device, a tissue specimen may be cut from the surrounding tissue and collected for later analysis.

(21) **Appl. No.: 11/045,006**(22) **Filed: Jan. 26, 2005****Related U.S. Application Data**

(60) Division of application No. 10/066,353, filed on Jan. 31, 2002, now Pat. No. 6,863,676, which is a continuation of application No. 09/565,611, filed on May 4, 2000, now Pat. No. 6,440,147, which is a continuation-in-part of application No. 09/417,520, filed on Oct. 13, 1999, now Pat. No. 6,423,081, which is a division of application No. 09/146,743, filed on Sep. 3, 1998, now Pat. No. 6,022,362.

Publication Classification(51) **Int. Cl.⁷ A61B 17/32; A61B 10/00**




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2A




FIG. 2B







FIG. 2C






FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15



FIG. 16




FIG. 17




FIG. 18




FIG. 19







FIG. 20






FIG. 24B

FIG. 24A




FIG. 25




FIG. 26

FIG. 27A




FIG. 27B






FIG. 27C



**FIG. 28**

EXCISIONAL BIOPSY DEVICES AND METHODS

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] The present application is a continuation-in-part of U.S. patent application Ser. No. 09/417,520, which is a divisional patent application of U.S. patent application Ser. No. 09/146,743, now U.S. Pat. No. 6,022,362.

BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] The present invention pertains to the field of soft tissue excisional biopsy devices and methods. In particular, the present invention relates to the field of devices and methods for excising suspicious lesions from soft tissue, such as breast tissue.

[0004] 2. Description of the Related Art

[0005] Breast cancer is a major threat and concern to women. Early detection and treatment of suspicious or cancerous lesions in the breast has been shown to improve long-term survival of the patient. The trend is, therefore, to encourage women not only to perform monthly self-breast examination and obtain a yearly breast examination by a qualified physician, but also to undergo annual screening mammography commencing at age 40. Mammography is the only screening modality available today that can detect small, nonpalpable lesions. These nonpalpable lesions may appear as opaque densities relative to normal breast parenchyma and fat or as clusters of microcalcifications.

[0006] The conventional method for diagnosing, localizing and excising nonpalpable lesions detected by mammography generally involves a time-consuming, multi-step process. First, the patient goes to the radiology department where the radiologist finds and localizes the lesion either using mammography or ultrasound guidance. Once localized, a radio-opaque wire is inserted into the breast. The distal end of the wire may include a small hook or loop. Ideally, this is placed adjacent to the suspicious area to be biopsied. The patient is then transported to the operating room. Under general or local anesthesia, the surgeon performs a procedure called a needle-localized breast biopsy. In the needle-localized breast biopsy, the surgeon, guided by the wire previously placed in the patient's breast, excises a mass of tissue around the distal end of the wire. The specimen is sent to the radiology department where a specimen radiograph is taken to confirm that the suspicious lesion is contained within the excised specimen. Meanwhile, the surgeon, patient, anesthesiologist and operating room staff, wait in the operating room for confirmation of that fact from the radiologist before the operation is completed. The suspicious lesion should ideally be excised in toto with a small margin or rim of normal breast tissue on all sides. Obtaining good margins of normal tissue is extremely dependent upon the skill and experience of the surgeon, and often an excessively large amount of normal breast tissue is removed to ensure that the lesion is located within the specimen. This increases the risk of post-operative complications, including bleeding and permanent breast deformity. As 80% of breast biopsies today are benign, many women unnecessarily suffer from permanent scarring and deformity from such benign breast biopsies.

[0007] More recently, less invasive techniques have been developed to sample or biopsy the suspicious lesions to obtain a histological diagnosis. The simplest of the newer techniques is to attempt visualization of the lesion by external ultrasound. If seen by external ultrasound, the lesion can be biopsied while being continuously visualized. This technique allows the physician to see the biopsy needle as it actually enters the lesion, thus ensuring that the correct area is sampled. Current sampling systems for use with external ultrasound guidance include a fine needle aspirate, core needle biopsy or vacuum-assisted biopsy devices.

[0008] Another conventional technique localizes the suspicious lesion using stereotactic digital mammography. The patient is placed prone on a special table that includes a hole to allow the designated breast to dangle therethrough. The breast is compressed between two mammography plates, which stabilizes the breast to be biopsied and allows the digital mammograms to be taken. At least two images are taken 30 degrees apart to obtain stereotactic views. The x, y and z coordinates targeting the lesion are calculated by a computer. The physician then aligns a special mechanical stage mounted under the table that places the biopsy device into the breast to obtain the sample or samples. There are believed to be three methods available to biopsy lesions using a stereotactic table: (1) fine needle aspiration, (2) core needle biopsy and (3) vacuum-assisted core needle biopsy.

[0009] Fine needle aspiration uses a small gauge needle, usually 20 to 25 gauge, to aspirate a small sample of cells from the lesion or suspicious area. The sample is smeared onto slides that are stained and examined by a cytopathologist. In this technique, individual cells in the smears are examined, and tissue architecture or histology is generally not preserved. Fine needle aspiration is also very dependent upon the skill and experience of the operator and can result in a high non-diagnostic rate (up to about 83%), due to inadequate sample collection or preparation.

[0010] Core needle biopsy uses a larger size needle, usually 14 gauge to sample the lesion. Tissue architecture and histology are preserved with this method. A side-cutting device, consisting of an inner trough with an outer cutting cannula is attached to a spring-loaded device for a rapid semi-automated firing action. After the lesion is localized, local anaesthetic is instilled and a small incision is made in the skin with a scalpel. The device enters the breast and the needle tip is guided into the breast up to the targeted lesion. The device is fired. First, the inner cannula containing the trough rapidly penetrates the lesion. Immediately following this, the outer cutting cannula rapidly advances over the inner cannula cutting a sample of tissue off in the trough. The whole device is then removed and the sample retrieved. Multiple penetrations of the core needle through the breast and into the lesion are required to obtain an adequate sampling of the lesion. Over 10 samples have been recommended by some.

[0011] The vacuum-assisted breast biopsy system is a larger semi-automated side-cutting device. It is usually 11 gauge in diameter and is more sophisticated than the core needle biopsy device. Multiple large samples can, be obtained from the lesion without having to reinsert the needle each time. A vacuum is added to suck the tissue into the trough. The rapid firing action of the spring-loaded core needle device is replaced with an oscillating outer cannula

that cuts the breast tissue off in the trough. The physician controls the speed at which the outer cannula advances over the trough and can rotate the alignment of the trough in a clockwise fashion to obtain multiple samples.

[0012] If a fine needle aspirate, needle core biopsy or vacuum-assisted biopsy shows malignancy or a specific benign diagnosis of atypical hyperplasia, then the patient needs to undergo another procedure, the traditional needle-localized breast biopsy, to fully excise the area with an adequate margin of normal breast tissue. Sometimes the vacuum-assisted device removes the whole targeted lesion. If this occurs, a small titanium clip should be placed in the biopsy field. This clip marks the area if a needle-localized breast biopsy is subsequently required for the previously mentioned reasons.

[0013] Another method of biopsying the suspicious lesion utilizes a large end-cutting core device measuring 0.5 cm to 2.0 cm in diameter. This also uses the stereotactic table for stabilization and localization. After the lesion coordinates are calculated and local anesthesia instilled, an incision large enough to permit entry of the bore is made at the entry site with a scalpel. The breast tissue is cored down to and past the lesion. Once the specimen is retrieved, the patient is turned onto her back and the surgeon cauterizes bleeding vessels under direct vision. The incision, measuring 0.5 to larger than 2.0 cm is sutured closed.

[0014] The stereotactic table requires awkward positioning of the patient and may be extremely uncomfortable. The woman must lie prone during the entire procedure, which may be impossible for some patients. In addition, the lesion to be biopsied must be in the center working area of the mammography plates. This may be extremely difficult and uncomfortable for the patient if the lesion is very posterior near the chest wall or high towards the axilla.

[0015] The woman is subjected to increased radiation exposure as multiple radiographs are required throughout the course of the procedure to: (1) confirm that the lesion is within the working area of the mammography plates, (2) obtain the stereotactic coordinates (at least two views), (3) verify the positioning of the biopsy needle prior to obtaining tissue, and (4) verify that the lesion was indeed sampled. If any difficulty is encountered during the procedure, additional radiographic exposures are required to verify correction of the problem.

[0016] Using the core needle biopsy or vacuum-assisted device, bleeding is controlled only by manual pressure. Bleeding is generally not an issue with fine needle aspiration, but is a legitimate complication of the former two methods. Ecchymoses, breast edema and hematomas can occur. This causes increased post-procedural pain and delays healing. Rarely, the patient may require an emergency operation to control and evacuate a tense hematoma.

[0017] Another major concern is the possibility of tumor dissemination. The core needle biopsy and vacuum-assisted devices both cut into the tumor and carve out multiple samples for examination. While cutting into the tumor, cancerous cells may be dislodged. Cutting across blood vessels at the same time may allow the freed cancerous cells access to the blood stream, thus possibly seeding the tumor beyond its original locus. The long-term consequences of tumor seeding with the risk of bloodborne metastases are

unknown at this time, as the techniques are relatively new. However, documented instances of cancerous cells seeding locally into needle tracks exist. There are numerous reports of metastases growing in needle tracks from previous biopsies of a cancerous mass. Most of these are from lung or liver cancers. However, at least one case of mucinous carcinoma of the breast growing in a needle track has been reported. The long-term consequences of neoplasm seeding into needle tracks are currently unknown, again because the techniques are relatively new. Some recommend excision of the entire needle track, including the skin entry site, during the definitive surgical procedure for a diagnosed cancer, whether it is a lumpectomy or a mastectomy. Others assume that with a lumpectomy, the post-operative radiation therapy will destroy any displaced cancer cells in the needle track. With the trend towards treating very small cancers only by excision and without a post-excision course of radiation therapy, the risk of cancer cells metastasizing and growing in needle tracks is very real.

[0018] The large core cutting device (0.5 cm to 2.0 cm) generally eliminates the risk of needle track seeding as it is designed to excise the lesion intact. A stereotactic table is required with the same inherent awkwardness for the patient, as discussed above. Bleeding is controlled, albeit manually, requiring that the patient wait until the end of the procedure to be turned over. Compression is used to stabilize the breast and localize the lesions. The breast, however, may be torqued and distorted between the compression plates such that when the plates are removed after the biopsy, the large core track left behind may not be straight, but actually tortuous. This can result in permanent breast deformity.

[0019] The location of the insertion site into the breast is dictated by the positioning of the breast in the machine and not by the physician. The entry site is usually away from the nipple-areolar complex and is usually located on the more exposed areas of the breast. For the fine needle aspirate, core biopsy and vacuum-assisted devices, the incision is usually very small and the scar almost unappreciable. However, in the case of the large core biopsy device (0.5 to 2.0 cm), a large incision is needed. Such a large incision often results in a non-aesthetically placed scar.

[0020] The newer conventional minimally invasive breast biopsy devices have improved in some ways the ability to diagnose mammographically detected nonpalpable lesions. These devices give the patient a choice as to how she wants the diagnosis to be made. Moreover, these devices are substantially less expensive than the older traditional needle-localized breast biopsy. They are not, however, the final solution. Due to the above-discussed problems and risks associated with compression, needle-track seeding, blood borne metastases, bleeding, radiation exposure and awkwardness of the stereotactic table, more refined devices and methods are needed to resolve these issues. Also, the conventional biopsy devices do not consider margins in their excisions and if cancer is diagnosed, the patient must undergo a needle-localized breast lumpectomy to ensure that adequate margins are removed around the cancer. Devices and methods, therefore, must address the problem of obtaining adequate margins so that a second procedure is not required. Margins, moreover, cannot be assessed while the breast is being compressed.

SUMMARY OF THE INVENTION

[0021] It is, therefore, an object of the present invention to provide devices and methods to efficiently and safely excise suspicious lesions from the breast. It is also an object of the present invention to provide devices and methods that remove the entire lesion intact with the minimum amount of normal tissue surrounding the lesion needed to provide adequate margins. It is a further object of the present invention to provide devices and methods that provide hemostasis in the breast to minimize complications of ecchymosis, hematoma formation, and breast edema. It is another object of the present invention to provide methods and devices to provide intra-tissue ultrasonic guidance to provide real time, in situ monitoring of the procedure. A still further object is to provide devices and methods that allow the physician to minimize the size of the incision through which the procedure is performed and to leave an aesthetically acceptable scar on the breast.

[0022] In accordance with the above-described objects and those that will be mentioned and will become apparent below, an embodiment of an excisional biopsy system according to the present invention comprises a tubular member including a proximal end and a distal end, the tubular member defining a first window near the distal end, and a first removable probe that includes a proximal portion including cutting tool extending means, a distal portion and a cutting tool near the distal portion, the first removable probe being configured to fit at least partially within the tubular member to enable the cutting tool to selectively bow out of and to retract within the first window when the cutting tool extending means are activated.

[0023] The first removable probe may further include a window slide and the proximal end may further include a window slide extending means, the window slide being configured to selectively cover a portion of the first window when the window slide extending means are activated. The cutting tool may include one of a thin ribbon sharpened on a leading edge thereof and a wire. The cutting tool may include an RF cutting tool and the first removable probe may be adapted to be connected to an RF power source. The cutting tool may include a monopolar or a bipolar RF cutting tool. The tubular member may include a first internal guide that is configured to enable the first removable probe to slide within the tubular member. The first removable probe may include a second internal guide, the second internal guide enabling the cutting tool to slide within the first removable probe when the cutting tool extending means are activated. The first removable probe may include a third internal guide, the third internal guide enabling the window slide to slide within the first removable probe when the window slide extending means are activated. The biopsy system may further include a second removable probe comprising a proximal section including a tissue collection device extending means and a distal section including a tissue collection device, the second removable probe being configured to fit at least partially within the tubular member to enable the tissue collection device to extend out of and to retract within the first window when the tissue collection device extending means are activated. Alternatively, the tubular member may define a second window near the distal end thereof, and the biopsy system may further include a second removable probe comprising a proximal section including a tissue collection device extending means and a distal section

including a tissue collection device, the second removable probe being configured to fit at least partially within the tubular member to enable the tissue collection device to selectively extend out of and to retract within the second window when the tissue collection device extending means are activated.

[0024] The tissue collection device may include a thin ribbon or a wire, as well as a thin flexible sheet of material attached to the thin ribbon or wire, the thin flexible sheet at least partially encapsulating a tissue specimen as the thin ribbon or wire is extended and the tubular member rotated. The thin flexible sheet of material may include a bag attached to the ribbon or wire so as to open and close when the ribbon or wire is extended and retracted, respectively. The tissue collection device may include a thin ribbon or a wire, and a thin flexible sheet of material may be attached to the thin ribbon or wire, the thin flexible sheet at least partially encapsulating a tissue specimen as the thin ribbon or wire is extended and the tubular member rotated. The thin flexible sheet of material may include a bag attached to the thin ribbon or wire so as to open and close when the thin ribbon or wire is extended and retracted, respectively. The tubular member may include a first internal guide that is configured to enable one of the first and the second removable probe to slide within the tubular member until the cutting tool and/or the tissue collection device faces out of the first window. Similarly, the tubular member may include a second internal guide that is configured to enable the second removable probe to slide within the tubular member until the tissue collection device faces out of the second window. The distal portion of the first removable probe may further include a tissue collection device near a trailing edge of the cutting tool, the tissue collection device being configured to selectively extend out of and retract into the first window. The proximal portion of the first removable probe may include a tissue collection device extending means, the tissue collection device extending means being adapted to enable the tissue collection device to extend out of and to retract within the first window independently of the cutting tool. The tissue collection device may be coupled to the cutting tool and the cutting tool extending means may also be configured to selectively extend the tissue collection device out of the first window and retract the tissue collection device into the first window as the cutting tool is extended and retracted, respectively. The first removable probe may include an insulator between the tissue collection device and the cutting tool. The insulator may include an air gap and/or an insulating material attached to and separating the cutting tool from the tissue collection device. The first removable probe may define one or more internal lumens that terminate near the distal portion as an opening formed in a surface of the first removable probe, the opening being adapted to deliver a pharmaceutical agent and/or to provide suction.

[0025] A third removable probe may be provided, the third removable probe being configured to fit at least partially within the tubular member and including an imaging device mounted therein. The imaging device may include an ultrasound sensor, such as a linear array of ultrasound transducers, for example. The ultrasound sensor may be disposed near a distal tip of the third removable probe and away from the cutting tool, so that the ultrasound sensor sweeps a plane ahead of the cutting tool as the tubular member rotates. The ultrasound sensor may be tuned within the range from about

7.5 MHz to about 20 MHz. The ultrasound sensor may be disposed within the tubular member at an angle α relative to the cutting tool, the angle α being no smaller than that necessary to effectively control the operation of the cutting tool in response to information gathered from the ultrasound transducer as the tubular member rotates. For example, the angle α may be less than about 90 degrees.

[0026] The tubular member, first removable probe, the second removable probe and/or the third removable may be configured for a single use and may be disposable.

[0027] The present invention is also a soft tissue treatment method, comprising the steps of inserting a generally tubular member into the soft tissue, the tubular member defining a first window in a surface thereof, the tubular member being configured to accept a removable probe inserted therein; inserting a first removable probe into the tubular member, the first removable probe including a cutting tool that is adapted to face out of the first window; selectively activating the cutting tool to cut a tissue specimen while rotating the tubular member within the tissue; removing the first removable probe from the tubular member while the tubular member stays in place; inserting a second removable probe into the tubular member, the second removable probe including a tissue collection device that is adapted to face out of the first window, and selectively activating the tissue collection device to encapsulate the tissue specimen rotating the tubular member.

[0028] The first removable probe may be inserted into the tubular member before the tubular member is inserted into the soft tissue. The method may further include the steps of inserting a third removable probe into the tubular member, the third removable probe including an imaging device therein that is configured to face out of the first window, and rotating the tubular member while activating the imaging device to image the soft tissue at least one of before and after the tissue collection device is activated. The tubular member may define a second window in the surface thereof and the method may further include the steps of inserting a third removable probe into the tubular member, the third removable probe including an imaging device therein that is configured to face out of the second window, and rotating the tubular member while activating the imaging device to image the soft tissue at least one of before, during and after the tissue collection device is activated.

[0029] Steps may be carried out to display information received from the imaging device on a display device and to vary the operation of the cutting tool and/or the tissue collection device during the first and/or second activating steps based upon the displayed information from the imaging device. The cutting tool may include an electrosurgical blade and the method may further include the step of varying a power applied to the electrosurgical blade based upon information received from the imaging device or feedback to the RF generator. A step of stabilizing the soft tissue in an uncompressed state prior to the first inserting step may also be carried out.

[0030] The tubular member and/or the first removable probe may define an internal lumen and a plurality of through holes in fluid communication with the internal lumen, and the method may further comprise one or more of the following steps: delivering a pharmaceutical agent to the

tissue via the plurality of through holes, and suctioning smoke and/or fluids from the soft tissue via the plurality of through holes.

[0031] The present invention may also be viewed as a soft tissue treatment method, comprising the steps of inserting a generally tubular member into the soft tissue, the tubular member defining a first window in a surface thereof, the tubular member being configured to accept a removable probe inserted therein; inserting a first removable probe into the tubular member, the first removable probe including a cutting tool and a tissue collection device that are adapted to face out of the first window; selectively activating the cutting tool to cut a tissue specimen while rotating the tubular member within the soft tissue, and selectively activating the tissue collection device to encapsulate the tissue specimen while rotating the tubular member.

[0032] The first removable probe may be inserted into the tubular member before the tubular member is inserted into the soft tissue. The tubular member may define a second window in the surface thereof and the method may further include the steps of inserting a second removable probe into the tubular member, the second removable probe including an imaging device therein that is configured to face out of the second window, and rotating the tubular member while activating the imaging device to image the soft tissue at least one of before, during and after at least one of the cutting tool and the tissue collection device are activated. The method may also include the steps of displaying information received from the imaging device on a display device; and varying an operation of at least one of the cutting tool and the tissue collection device during at least one the first and second rotating steps based upon the displayed information from the imaging device.

[0033] The first and second activating steps may be carried out simultaneously and the cutting tool and the tissue collection device may be coupled to one another. Alternatively, the first and second activating steps may be carried out simultaneously or consecutively and the cutting tool and the tissue collection device may be activated independently of one another.

[0034] According to another embodiment thereof, the present invention is also an excisional biopsy system for soft tissue, comprising a tubular member defining a first, a second and a third window near a distal tip thereof; a first removable probe comprising a proximal portion that includes cutting tool extending means, a distal portion and a cutting tool near the distal portion, the first removable probe being configured to fit at least partially within the tubular member to enable the cutting tool to selectively bow out of and to retract within the first window when the cutting tool extending means are activated; a second removable probe comprising a proximal section including a tissue collection device extending means and a distal section including a tissue collection device, the second removable probe being configured to fit at least partially within the tubular member to enable the tissue collection device to extend out of and to retract within the second window when the tissue collection device extending means are activated, and a third removable probe, the third removable probe being configured to fit at least partially within the tubular member and including an imaging device mounted therein that is configured to face out of the third window.

[0035] The present invention may also be viewed as an excisional biopsy system for soft tissue, comprising a tubular member defining a first and a second window near a distal tip thereof; a first removable probe comprising a proximal portion and a distal portion, the proximal portion including a tool extending means, the distal portion including a cutting tool and a tissue collection tool, the first removable probe being configured to fit at least partially within the tubular member to enable the cutting and tissue collection tools to selectively extend out of and to retract within the first window when the tool extending means are activated, and a second removable probe, the third removable probe being configured to fit at least partially within the tubular member and including an imaging device mounted therein that is configured to face out of the second window.

[0036] The cutting and tissue collection tools may be mechanically coupled to one another. The cutting and tissue collection tools may also be independently activated and the tool extending means may include a cutting tool extending means operative to extend and to retract the cutting tool out of and into the first window and a tissue collection extending means operative to extend and to retract the tissue collection tool into and out of the first window.

BRIEF DESCRIPTION OF THE DRAWINGS

[0037] For a further understanding of the objects and advantages of the present invention, reference should be made to the following detailed description, taken in conjunction with the accompanying figures, in which:

[0038] **FIG. 1A** shows an embodiment of the excisional device according to the present invention with the cutting tool in its flat, retracted configuration.

[0039] **FIG. 1B** shows the excisional device of **FIG. 1A** with its cutting tool in an extended, bowed configuration.

[0040] **FIG. 1C** shows another view of the excisional device of **FIG. 1A**.

[0041] **FIG. 2A** depicts the distal region of another embodiment of the excisional device according to the present invention, showing the excisional device together with the external tissue collection attached thereto in the open configuration.

[0042] **FIG. 2B** shows the excisional device of **FIG. 2A** together with the external tissue collection attached thereto in the closed configuration.

[0043] **FIG. 2C** shows an embodiment of the proximal region of the excisional device according to the present invention.

[0044] **FIG. 3A** depicts the operation of an embodiment of the excisional device and method according to the present invention.

[0045] **FIG. 3B** further shows the operation of an embodiment of the excisional device and method according to the present invention.

[0046] **FIG. 3C** further depicts the operation of an embodiment of the excisional device and method according to the present invention.

[0047] **FIG. 4** shows a detailed view of a cutting tool suitable for use with the excisional device according to the present invention.

[0048] **FIG. 5** shows a cross section of the cutting tool, taken along line AA' in **FIG. 4**.

[0049] **FIG. 6** shows a detailed view of another cutting tool suitable for use with the excisional device according to the present invention.

[0050] **FIG. 7** shows a cross section of the cutting tool, taken along line BB' in **FIG. 6**.

[0051] **FIG. 8** shows another embodiment of a cutting tool suitable for use with the excisional biopsy device according to the present invention.

[0052] **FIG. 9** is a cross-sectional schematic of the tubular member **110**, to illustrate the relative placements of the cutter window **120** and of the transducer **270** about the circumference of the tubular member **110**. Unnecessary details have been omitted for clarity.

[0053] **FIG. 10** shows an excisional device according to another embodiment of the present invention, in which the tubular member of the excisional device includes an internal lumen through which a removable transducer core may be inserted.

[0054] **FIG. 11** shows an embodiment of a removable transducer core according to the present invention.

[0055] **FIG. 12** shows a cross section of the embodiment of the excisional device of **FIG. 10**, taken along line AA'.

[0056] **FIG. 13** shows the removable transducer core of **FIG. 11** inserted within an expandable sheath, according to a further embodiment of the present invention.

[0057] **FIG. 14** shows another embodiment of a soft tissue excisional device assembly according to the present invention, in which a removable transducer core is inserted and secured within the excisional device so that the active element faces out of the transducer window.

[0058] **FIG. 15** shows another embodiment of a cutting tool (and method of making same) that is suitable for use within the excisional device according to the present invention.

[0059] **FIG. 16** shows a view of the completed cutting tool of **FIG. 15**.

[0060] **FIG. 17** shows an embodiment of the method of excisional biopsy method according to the present invention.

[0061] **FIG. 18** is a top view of a removable cutting probe, according to an embodiment of the present invention.

[0062] **FIG. 19** is a side view of the removable cutting probe of **FIG. 18**, showing the adjustable window slide in a first position, according to an embodiment of the present invention.

[0063] **FIG. 20** is a side view of the removable cutting probe of **FIG. 18**, showing the adjustable window slide in a second position, according to an embodiment of the present invention.

[0064] **FIG. 21** is a top view of a removable tissue collection probe, according to an embodiment of the present invention.

[0065] **FIG. 22** is a detail view of a removable tissue collection probe of **FIG. 21**.

[0066] FIG. 23 is a side view of the removable tissue collection probe of FIG. 21, showing the tissue collection device thereof in an extended (bowed) configuration.

[0067] FIG. 24A is a top view of a removable cutting and tissue collection combination probe, according to an embodiment of the present invention.

[0068] FIG. 24B is a partial cross-sectional view of the removable cutting and tissue collection combination probe of FIG. 24A, taken along lines AA'.

[0069] FIG. 25 is a top view of a removable cutting and tissue collection combination probe, according to another embodiment of the present invention.

[0070] FIG. 26 is a side view of a removable cutting and tissue collection combination probe, according to a still further embodiment of the present invention, wherein the cutting device and tissue collection devices are shown in their extended configuration.

[0071] FIG. 27A is a partial cross-section of a tissue collection probe, taken at the level of the tissue collection device thereof, wherein the tissue collection device is in its initial, non-extended configuration.

[0072] FIG. 27B is a partial cross-section of a tissue collection probe of FIG. 27A, wherein the tissue collection device is in its extended configuration.

[0073] FIG. 27C is a partial cross-section of a tissue collection probe of FIG. 27B, wherein the tissue collection device has returned to its non-extended configuration after capturing the target tissue.

[0074] FIG. 28 is a flowchart of a soft tissue treatment method, according to another embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0075] FIGS. 1A, 1B and 1C show an embodiment of the distal region 105 of the excisional biopsy device 100 according to the present invention. Considering FIGS. 1A, 1B and 1C collectively, the distal region 105 of the excisional biopsy device 100 includes a generally tubular member 110 having a generally tapered distal tip 115. The distal tip 115 is configured to penetrate soft tissue, such as breast tissue, lung tissue, liver tissue and the like. Preferably, therefore, the distal tip 115 and the distal region 105 of the excisional biopsy device 100 present a smooth, and relatively atraumatic profile to the soft tissue in which it is designed to penetrate. Alternatively, the tip 115 may be sharply pointed and/or may include an energy source (not shown) to facilitate cutting through the tissue. The tubular member 110 may be formed of rigid and hard plastic, or may be made of stainless steel, for example. Preferably, the tubular member 100 is used once and disposed of, for both safety and functional reasons.

[0076] A cutter window 120 is disposed within the tubular member 110. The cutter window 120 may be, for example, a shallow trench formed in the tubular member 110. As best seen in FIG. 1C, the cutter window 120 may be a shallow and substantially rectangular trench in the tubular member 110, or may be, for example, a thin, shallow I-shaped trench. The excisional biopsy device 125 includes a work element,

such as a cutting tool 125. The distal end of the cutting tool 125 is attached to the tubular member 110 near its distal tip 115. For example, the distal end of the cutting tool 125 may be attached to the distal-most point 121 of the cutter window 120. The cutting tool 125, however, may alternatively be attached to other points within the distal region 105. The distal portion of the cutting tool 125 is exposed through the cutter window 120. The remaining portion of the cutting tool 125 is disposed within an internal guide or lumen 130 of the generally tubular member 110. The internal guide 130 constrains the movement of the cutting tool 125 and allows the cutting tool 125 to freely slide therein, parallel to the longitudinal axis of the tubular member 110. With particular reference now to FIG. 2C, the proximal portion 225 of the cutting tool 125 emerges from the internal lumen 130 near the proximal end 215 of the tubular member 110. The proximal end of the cutting tool 125 may, for example, include a push or turn knob 226. The push or turn knob 226 allows the operator of the excisional biopsy device 100 to selectively push the cutting tool 125 in the distal direction (away from the physician and toward the distal tip 115) or retract the cutting tool 125 in the proximal direction (toward the physician and away from the distal tip 115). To assist in controlling the movement of the cutting tool 125, the cutting tool is preferably biased in the proximal direction, as symbolized by the arrow 227 in FIG. 2C. This biasing may be effectuated by means of a spring 228 attached at or near the proximal end 215 of the tubular member 110 and to the proximal portion 225 of the cutting tool 125. In this manner, the default configuration of the cutting tool 125 is the retracted position, wherein the cutting tool 125 lies substantially flat within the cutter window 120 of the tubular member 110.

[0077] The cutting tool 125, when pushed in the distal direction by the physician applying pressure in the distal direction on the push or turn knob 226 or equivalent structure, slides within the internal guide 130 of the tubular member 110. As the distal end of the cutting tool 125 is attached near the distal end of the tubular member 110 or to the distal-most point 121 of the cutter window 120, the portion thereof exposed through the cutter window 120 tends to bow outwardly, extending out of the cutter window 120, as shown in FIG. 1B. The extension out of the cutter window 120 and the degree of bowing may be controlled by the physician, by appropriate action on the push or turn knob 226. Thus, the possible range of extension and bowing is potentially infinite, being limited only by the physician's ability to control the cutting tool 125 by finely pushing and retracting the push or turn knob 226. The degree of extension, as well as the shape of the bowed portion of the cutting tool, therefore, may be controlled by selectively sliding the cutting tool within the internal guide 130 of the tubular member 110.

[0078] The shape of the bowed portion and the ease with which the distal portion of the cutting tool 125 bows outwardly may be varied by varying the physical characteristics of the cutting tool 125. Preferably, the cutting tool is formed of a resilient, readily deformable material that, when unstressed, returns to its original unbiased configuration. For example, a nickel titanium alloy may be used for the cutting tool 125, to allow the cutting tool 125 to exhibit shape-memory characteristics. The shape of the cutting tool 125 in its bowed and extended configuration (FIG. 2) may be further controlled by varying, for example, the thickness of

the cutting tool over the portion thereof exposed through the cutter window 120. A locally thicker portion of the cutting tool 125 will not bend as readily as a locally relatively thinner portion thereof. Judiciously varying the thickness, for example, of the cutting tool 125, therefore, allows the curvature of the bowed portion thereof to be controlled.

[0079] As shown in FIGS. 1A, 1B, and with reference to FIG. 1C, pushing on the push or turn knob 226 (or any such functionally equivalent structure) causes the cutting tool 125 to bow outwardly and extend out from the cutter window 120 of the tubular member 110, as shown in FIG. 1B. Similarly, retracting the push or turn knob 226 (or any such functionally equivalent structure) causes the cutting tool 125 to flatten out within the cutter window 120 and to assume a configuration (shown in FIG. 1A) that may be substantially flush with the outer surface of the tubular member 110. In this configuration, the tubular member 110 may easily penetrate soft tissue, such as breast, lung, liver or other soft body tissue.

[0080] In operation, the surgeon makes an incision into the patient's skin, such as the surface of the breast. The excisional biopsy device 100 then may be directly introduced into the breast tissue, or an expandable sheath (shown at reference numeral 495 in FIG. 13) may be introduced into the incision and thereafter expanded as the excisional biopsy device 100 is introduced therein. In any event, the excisional biopsy device is introduced into the breast tissue itself and positioned, for example, adjacent to the lesion in the breast or adjacent the target site from which the excision is to take place. During the introduction of the excisional biopsy device 100 into the soft tissue, the cutting tool 125 is in its retracted configuration wherein the portion thereof exposed through the cutter window 120 is substantially flat. The excisional device 100, in this configuration, therefore, exhibits a smooth and tapered profile to the surrounding tissue. Once the device 100 has been determined to have been properly positioned within the soft tissue, the device is rotated about its longitudinal axis. The rotation may be carried out manually, or the rotation of the device may be carried out by a motorized unit disposed within the proximal region of the device 100. As the device 100 rotates, the surgeon causes the cutting tool 125 to bow outwardly and to extend from the cutter window 120. Preferably, the degree of bowing and outward extension is at least sufficient to include the lesion (such as the targeted microcalcification within the breast) within the space between the cutter window 120 and the cutting tool 125. The cutting tool 125 cuts the tissue as the device 100 is rotated, thereby severing the lesion from its surrounding breast tissue mass. By completing at least one revolution within the breast tissue, the cutting tool 125 sweeps a volume of revolution of breast tissue and severs that volume from the main tissue mass. Such volume of revolution includes at least the targeted lesion. Preferably, the volume of revolution severed from the main tissue mass not only includes the targeted lesion, but also includes a margin of healthy tissue surrounding the lesion. The degree of extension and bowing of the cutting tool 125 may be varied within a given revolution of the excisional biopsy device 100. In this manner, it is possible to exert fine control over the amount of tissue cut away from the main tissue mass, as well as fine control over the shape of the severed mass.

[0081] After the lesion and preferably a margin of healthy tissue around the lesion have been severed, the severed tissue may be removed from the main tissue mass. This removal of the severed tissue may be effectuated by any number of means, including the retraction of the excisional biopsy device 100 from the main tissue mass. Alternately, severed tissue extraction may be carried out by means of the structure and method to be described below.

[0082] The cutting tool 125 may, as shown in FIG. 1C, be configured as a thin ribbon. The thin ribbon 125 shown in FIG. 1C is preferably sharpened on its leading edge to facilitate cutting through tissue and sometimes fibrous and calcified masses. The leading edge of the cutting tool 125 is that edge thereof that first comes into contact with the tissue to be severed as the device 100 is rotated. Such a sharpened leading edge is shown in FIG. 4 at reference numeral 127. The width of such a ribbon cutting tool 125 is preferably smaller than the width of the cutter window 120 into which it recedes when the cutting tool 125 is retracted in the proximal direction.

[0083] Another embodiment of the cutting tool 125 is shown in FIG. 8. To decrease the forward resistance of the cutting tool 125 as it slowly cuts through tissue, the leading edge of the portion thereof exposed through the cutter window 120 may be serrated, including a plurality of teeth 127. In turn, the leading edge of the plurality of teeth 127 may include a sharpened edge. In this manner, as the excisional device 100 rotates, only the forward-most tips of the teeth 127 will initially come into contact with the tissue to be cut, thus reducing the tissue surface upon which the force of the rotating cutting blade 125 is applied. Thus, the cutting blade 125 of FIG. 8 is believed to be highly effective in cutting through even relatively dense or fibrous tissue while minimizing the torque to be applied to the excisional biopsy device 100 as it is caused to rotate within the main soft tissue mass.

[0084] Referring to FIG. 4 and also to FIG. 5, the cutting tool 125 may further comprise an interior lumen 128 running an entire length or a portion of the length of the cutting tool 125. The cutting tool 125 may further include a plurality of through holes 126 in the distal portion of the cutting tool 125 exposed through the cutter window 120. The plurality of through holes 126 are in fluid communication with the internal lumen 128. In use, the internal lumen 128 may be connected, in the proximal portion of the excisional biopsy device 100, to a fluid reservoir. The fluid reservoir, which may be internal or external to the proximal section of the device 100, supplies the distal portion of the cutting tool 125 with, for example, anaesthetic (such as, for example, lidocaine) and/or antibiotic fluid. In this manner, such anaesthetic and/or antibiotic fluid (or other fluid) may be delivered precisely to the tissue surrounding the cutting tool 125 as it rotates. A precisely dosed anaesthetic, for example, may be delivered to the very site where it is most needed. As such anaesthetic is delivered only where it is needed, the effect thereof is near instantaneous, and the patient feels little or no pain as the excisional biopsy device 100 according to the present invention is rotated within her breast, or other soft tissue. FIG. 5 shows a cross-section of the cutting tool 125 of FIG. 4, taken along line AA' in FIG. 4.

[0085] Care should be exercised in selecting the configuration and materials for the cutting tool 125 shown in FIGS.

4 and 5. Indeed, the configuration and materials selected should allow the cutting tool **125** to bow and extend out of the cutter window **120** of the device **100** without, however, pinching or substantially disrupting the flow of fluid delivered via the internal lumen **128** of the cutting tool **125**, if the cutting tool **125** is provided with such. For example, the cutting tool **125** may be made of a shape-memory metal, such as nickel-titanium and/or the proximal portion of the cutting tool **125** may be formed relatively thicker than other portions thereof.

[0086] Another embodiment of the cutting tool **125** is shown in **FIGS. 15 and 16**. As shown therein, the cutting tool **125** may be formed by a thin sheet of steel or shape memory alloy. The sheet may include a plurality of through holes **126** to allow the anaesthetic or other fluid to be instilled therethrough. A small tube **540** may be disposed on the sheet, aligned with the through holes **126**. The sheet may be folded in the direction indicated by the arrows **530**, thus securing the tube **540** between the two folded sides of the sheet. The edges **550** of the sheet may be sealed together to render them fluid tight. For example, the sides **550** of the sheet may be welded together or secured by other means known to those of skill in the metal working arts. The edges **560** between the through holes **126** may be sharpened, to allow the cutting tool **125** to efficiently cut through soft tissue. As shown in **FIG. 16**, the tube **540** may deliver anaesthetic or other fluid to the cutting tool **125**, which delivers minute amounts thereof precisely where it is needed: where the cutting edges **560** of the cutting tool **125**, thereby affording the patient immediate relief and minimizing the amount of anaesthetic that need be delivered. The proximal end of the tube **540** may be in fluid communication with an anaesthetic reservoir (not shown) and/or an anaesthetic pump (also not shown).

[0087] Alternatively, the cutting tool **125** may include a thin wire, such as shown at **125** in **FIGS. 6 and 7**. In this case, an external radio frequency (hereafter, RF) power source **240** (shown at **240** in **FIG. 2C**) supplies the cutting tool **125** with RF energy via two bipolar electrodes (not shown) attached to the cutting tool **125** of **FIG. 6**. Other energy sources may also be used within the context of the present invention, RF power being discussed herein for illustrative purposes only. The RF power delivered by the RF power source **240** allows the cutting tool **125** of **FIG. 6** to become an electrosurgical cutting and/or an electrocoagulating tool by selectively varying the power applied to the cutting tool **125**. Suitable generators for such an electrosurgical cutting device **125** are known to those of skill in this art. An example of such a suitable generator is described in U.S. Pat. No. 4,903,696 issued Feb. 27, 1990 and assigned to Everest Medical Corporation, Brooklyn Center, Minn., the disclosure of which is incorporated herewith in its entirety. As with the cutting tool **125** shown in **FIGS. 4 and 5**, the cutting tool **125** of **FIGS. 6 and 7** includes an internal lumen **128** and a plurality of through holes **126** to allow anaesthetic or other fluid to be delivered to the surrounding tissue as the cutting tool **125** cuts through the soft tissue as the device **100** is rotated.

[0088] As alluded to above, the excisional biopsy device **100** according to the present invention cuts out a (not necessarily symmetrical) volume of revolution as it cuts through the soft tissue upon rotation of the generally tubular member **110**. This severed mass of tissue may be stabilized

using an extendable tissue anchoring device, which anchoring device also assists in the retrieval of the severed tissue sample from the breast. The anchoring device may, for example, include a suction device or other substantially rigid anchor member to anchor the tissue sample. Alternatively, the severed tissue sample may be collected in a tissue collection device, as shown at reference numeral **260** in **FIGS. 2A and 2B**. The tissue collection device **260** is attached externally to the tubular member **110**, and preferably also to the trailing edge of the cutting tool **125**. The tissue collection device **260** is preferably formed of a thin and flexible plastic membrane shaped like a bag. The opening of the bag-shaped collection device **260** is preferably co-extensive with the opening **120** and is preferably attached to the tubular member **110** and to the trailing edge of the cutting tool **125**. In this manner, the opening or "mouth" of the bag-shaped collection device **260** opens and closes along with the bowing and retraction, respectively, of the cutting tool **125**. Indeed, the "mouth" of the bag-shaped collection device **260** is opened when the cutting tool **125** is bowed and extended out of the cutter window **120** and substantially closed when the same is retracted within the cutter window **120**, as the two edges (one attached to the tubular member **110** just adjacent to the edge of the cutter window **120** and the other attached to the trailing edge of the cutting tool **125**) of the collection device are then pressed together.

[0089] Therefore, when the excisional device **100** is inserted into soft tissue and rotated, the cutting tool **125** may be caused to bow and to extend outwardly from the cutter window **120** and caused to cut tissue coming into contact therewith. As the device **100** rotates and cuts, the tissue between the cutting tool **125** and the tubular member **110** tends to advance toward and into the collection device. As the cutting tool **125** is in its bowed and extended state, the "mouth" or opening of the bag-shaped collection device **260** is also correspondingly open, allowing the severed tissue to collect therein. As the revolution of the tubular member **100** is completed, the cutting tool **125** may be retracted and caused to assume a configuration wherein it is disposed within the recessed cutter window **120**, substantially flush with the outer surface of the tubular member **110**, as shown in **FIG. 2B**. In this configuration, the collection device **260** is closed, thereby securing the excised tissue sample therein. The device **100** may then be safely retracted from the main tissue mass, such as the breast. As the excised sample is physically isolated from the remaining tissue mass, the probability of seeding the surrounding tissue with potentially abnormal cells is markedly decreased. This probability is also further decreased, as the excisional device **100** according to the present invention allows the surgeon to obtain adequate margins of healthy tissue surrounding the target lesion by choosing the degree of bowing and extension of the cutting tool **125**. In this manner, the integrity of the lesion itself is not violated, thereby maintaining tissue architecture intact.

[0090] As the collection device **260** is preferably formed of a thin and flexible membrane, it is able to lay substantially flat against the outer surface of the tubular member **110** or slightly recessed within the cutter window **120** during insertion thereof into the soft tissue. The collection device **260**, therefore, offers little additional drag and resistance to the device **100** as it is inserted into the incision made in the patient's skin during or prior to the procedure. Suitable

materials for the tissue collection device **260** include plastics and nylon, for example. Any strong adhesive may be utilized to secure the tissue collection device **260** to the tubular member **110** and to the cutting tool **125**. Other means of securing the collection device **260** may also be employed without, however, departing from the scope of the present invention. Likewise, the tissue collection device **260** may be formed of a material other than specifically enumerated herein while remaining within the spirit of the present invention. Preferably, the shape and size of the tissue collection device **260** are such as to minimize drag on the excisional biopsy device **100** as it is inserted and rotated into the tissue. For example, the tissue collection device **260** preferably should be only as large as necessary to contain the excised tissue sample.

[0091] The excisional biopsy device **100** according to the present invention is preferably accurately positioned adjacent to the lesion within the breast or other organ. Toward that end, the present invention allows the surgeon to gain near real time or real time information as to the internal structure of the soft tissue during the procedure itself. Referring now back to **FIGS. 1 and 2C**, the present invention may include a transducer **270** mounted within the distal portion of the tubular member **110**. This transducer **270** is preferably adapted to image tissue about to be cut by the cutting tool **125** as the excisional biopsy device **100** is rotated within the soft tissue. Indeed, the transducer **270** preferably generates information relative to the tissue about to be cut—that is, tissue that has not yet been brought into contact with the cutting tool **125** as the tubular member **110** rotates about its longitudinal axis. In this manner, as the rotational speed of the excisional biopsy device **100** is preferably quite slow (the rotation may be manually carried out or may be caused by a slow moving motorized unit attached to the tubular member **110**), the surgeon may evaluate the information generated by the transducer **270** and may, based upon this information, vary the degree of bowing and extension of the cutting tool **125**. For example, when the device **100** is positioned adjacent to the lesion of interest and rotated, the transducer **270** will detect the presence and location of the lesion before the lesion comes into contact with the cutting tool **125**. After the lesion has been detected by the transducer **270**, the surgeon may push on the push or turn knob **226** or other structure that causes the cutting tool to bow and extend from the cutter window **120**. The lesion (and preferably an adequate margin of healthy tissue) will then be severed from the main mass, and optionally collected, for example, in the tissue collection device **260**. When the transducer **270** indicates that the rotation of the tubular member has brought the cutting tool **125** past the lesion, the cutting tool **125** may be retracted within the cutter window **120**. The cutting, it can be seen, may be specifically tailored to the size and shape of the lesion within the main tissue mass in near real time or in real time, thereby allowing the surgeon to excise all of the tissue required and only the tissue that is necessary to achieve the intended results.

[0092] Preferably, the transducer **270** is an ultrasound sensor mounted substantially flush with the external surface of the tubular member **110**. The ultrasound sensor **270** is preferably electrically connected, via a communication channel such as electrical conductors, to at least one data processing and display device, shown at reference **250** in **FIG. 2C**. The data processing and display device(s) **250**

allows the surgeon to see, in near real time or in real time, the internal structure of the tissue about to be cut by the cutting tool **125**. This allows the surgeon not only to see a graphical representation of the internal structure of the tissue during the procedure itself, but also allows the surgeon to assure himself or herself that the entire lesion or group of lesions has been properly excised by, for example, rotating the tubular device within the tissue while the cutting tool is retracted within the cutter window **120** while the transducer **270** is energized. Viewed from another aspect, therefore, the present invention is an intra-tissue ultrasound imaging device that may, but need not include a cutting tool, such as referenced by numeral **125** in the figures.

[0093] In operation, the (e.g., ultrasound) transducer sweeps a plane (graphically shown at **280** in **FIG. 3A**) within the tissue ahead of the work element, such as cutting tool **125**. In selecting the operational characteristics of the ultrasound transducer **270**, the surgeon must balance the required resolution (i.e., the smallest feature that must be discernable) with the degree of penetration of the ultrasound waves within the tissue and the intensity of the ultrasonic waves generated. In general, higher frequencies allow better resolution. However, high frequencies do not penetrate the tissue as far as do lower frequency ultrasound waves. Preferably, the ultrasound transducer **270** is tuned within the range from about 5 MHz to about 20 MHz. More preferably, the ultrasound transducer **270** is tuned within the range of about 7.5 MHz to about 20 MHz. For example, in the case wherein the excisional biopsy device **100** according to the present invention is used within the female breast, the ultrasound transducer may be tuned within the range of about 10 MHz to about 13 MHz.

[0094] To effectively image the internal tissue structure prior to cutting it with, for example, the cutting tool **125**, the transducer **270** must be positioned within the tubular member **110** away from the cutting tool **125**. With reference to **FIG. 9**, the transducer **270** may be disposed within the tubular member at an angle α relative to the cutting tool **125**. The angle α is preferably no smaller than that necessary to effectively control the operation of the work element (such as cutting element **125**) in response to information gathered from the transducer **125** as the tubular member **110** rotates. This angle α , therefore, is dependent at least upon the rotational speed imposed upon the tubular member **110** and upon the time necessary for the surgeon to assimilate the information generated by the transducer and to effectively control the cutting tool **125** in response to such information. Preferably, the angle α is less than about 180 degrees.

[0095] When used in conjunction with an intra-tissue ultrasound transducer, such as shown at **270**, the excisional biopsy device **100** according to the present invention may include a variety of work elements in place of or in addition to the cutting tool **125**. Such work elements include, for example, an abrasive device, a reciprocating cutting device, an electrosurgical device or a vibrating device.

[0096] In the case of lesions within the breast, it is useful to stabilize the breast prior to imaging and performing invasive procedures. Such stabilization is conventionally performed by compression plates that squeeze the breast and compress the tissue therein. Such compression is necessary to allow x-ray radiation, as used in mammography, to produce a useful image. Although such compression is not

needed or believed to be desirable according to the present invention, stabilization of the breast remains necessary. For this purpose, the breast stabilization devices described in commonly assigned U.S. patent application Ser. No. 09/158,215 entitled "Breast Stabilization Devices And Methods" filed on Sep. 22, 1998, and Ser. No. 09/200,661 entitled "Breast Stabilization Devices And Imaging And Interventional Methods Using Same" filed on Nov. 25, 1998, the disclosures of each being incorporated herein in their entirety, may be useful.

[0097] Reference is now made to **FIGS. 3A, 3B** and **3C**, which illustrate an embodiment of the excisional biopsy method according to the present invention. Although **FIGS. 3A-3C** illustrate an embodiment of the present invention within the context of breast surgery, it is to be understood that the present inventive method is equally applicable to other soft tissue masses, such as, for example, lung, thyroid or liver tissue, with only minor modifications that will become apparent to skilled practitioners in this art.

[0098] Turning first to **FIG. 3A**, a small incision **331** is made in the breast **310**, preferably in the peri-areolar region. Preferably, the breast is stabilized, using, for example, the breast stabilizing devices disclosed in U.S. patent application Ser. No. 09/158,215 or 09/200,661 referred to above. The portion of the device **100** that remains outside of the soft tissue may include attachment means (not shown) for clamping the device to a rim structure, for example, to allow stable operation and precise guidance thereof. The small incision is preferably made on the border of the areola **330** surrounding the nipple **320**, as this provides a better cosmetic scar than on the skin on the side of the breast **310**. Depending on the size of the lesion and the size of the excisional biopsy device **100** to be inserted therein, an expandable sheath (an example of which is shown at reference numeral **495** in **FIG. 13**) may be inserted into the breast tissue. In any event, the excisional biopsy device **100** is inserted into the breast tissue and positioned adjacent the lesion **300**, which may be, for example, a microcalcification or other abnormal lesion. Once in position, the device **100** is rotated, for example, in the direction indicated in **FIG. 3A**. The portion of the excisional biopsy device **100** that remains outside the soft tissue may have a greater diameter than the portion thereof that is designed to penetrate the soft tissue. This aids in manual rotation of the device **100**. In the configuration depicted in **FIG. 3A**, the cutting tool **125** is retracted within the cutter window **120** and the tissue collection device **260**, if present, is substantially flat against the external surface of the tubular member **110**. The device **110** is rotated about its longitudinal axis and the transducer **270** is energized, the information therefrom being transmitted to, for example, the display device **250** shown in **FIG. 2C**. When the lesion **300** comes into view, the surgeon then gauges the size, shape and location thereof and controls the bowing and extension of the work element, such as cutting tool **125** based on the information received from the transducer **270** and displayed upon the display **250**. **FIG. 3B** depicts the situation wherein the lesion **300** has been imaged and the surgeon has extended the cutting tool **125** to sever the lesion **300** from the surrounding breast tissue. The severed tissue may be received and collected in a tissue collection device **260**, as the device **100** rotates. Anaesthetic and/or antibiotic (or other) fluids may be delivered directly to the affected tissue by through holes **126** (best seen in **FIGS. 2A, 2B** and **FIGS. 4-7**), greatly decreasing pain during the procedure.

[0099] After the lesion and any desired margin of healthy tissue is severed from the main breast tissue mass, the cutting tool **125** is retracted within the cutter window **120**. This closes the tissue collection device **260**, if present, and allows the entire device **100** to be retracted from the breast in the direction of arrow **350**, as shown in **FIG. 3C**. If the tissue collection device **260** is present, the lesion **300** will be isolated from surrounding tissue by the membrane of the tissue collection device **260**, thus minimizing any possibility of seeding potentially abnormal cells to surrounding breast tissue. Moreover, the tissue architecture of the retrieved lesion **300** is substantially preserved, thereby allowing accurate histopathology to be performed upon the entire mass excised from the breast. Indeed, any compression such tissue may undergo is believed to be solely due to the retraction of the device back through the entrance track of the device **100** in the uncompressed breast tissue. Thereafter, when the excisional device **100** is removed from the breast **310**, the push or turn knob **226** may be acted upon to extend and bow the cutting tool **125**, thereby allowing the excised lesion to be retrieved from the tissue collection device **260** for examination. If the tissue collection device is not present, conventional suction means may be employed to extract the severed lesion from the surrounding breast tissue. Bleeding is controlled by suitably varying the RF or other power source applied to the electrosurgical cutting tool **125**, if present, to stem the bleeding by cauterizing the tissue coagulating the blood.

[0100] After the procedure, a small cavity remains in the breast where the lesion had previously been. However, since no compression of the breast was carried out, no expansion of the tissue occurs after the procedure, unlike conventional techniques. Therefore, the cavity and the entrance and exit path of the device remain as small as possible, leading to fewer complications, less tissue trauma and improved aesthetics.

[0101] According to another embodiment of the present invention, shown in **FIGS. 10, 11** and **12**, the transducer **270** is replaced by a removable transducer core **400**. The removable transducer core **400** includes an active element **440** configured to perform intra-tissue imaging and of relaying information back to a display device (shown in **FIG. 14**) via a communication channel, such as shown at reference numeral **460**. The communication channel **460** may be wireless or may include, for example, optical fibers and/or electrical conductors. The active element **440** may draw power from an internal battery (not shown) or from a power source, such as shown at reference numeral **480**. The active element **440** may include an ultrasound transducer. Other types of transducers may be used instead of or in addition to an ultrasound transducer. The removable transducer core **400** preferably includes a generally tubular shaft **430**. A proximal section **450** is included near the proximal portion of the transducer core **400**.

[0102] To accommodate the removable transducer core **400**, the excisional device **100** of **FIG. 10** defines an internal lumen **420** through which the removable transducer core **400** may be inserted. Preferably, the excisional device **100** is used once and disposed of, for safety and functional reasons. The removable transducer core **400**, however, may either be disposable or re-usable for a limited number of uses. To allow the active element **440** of the transducer core **400** to image the lesion to be excised and the surrounding tissue,

the generally tubular member 110 of the excisional device 100 includes a transducer window 410. When the removable transducer core 400 is inserted within the internal lumen 420, the proximal section 450 of the core 400 preferably snaps into a locked configuration with the proximal end of the excisional device 100. When in its locked configuration, the active element 440 of the transducer core 400 is aligned with and faces the transducer window 410, to allow the active element 440 to image the lesion and the surrounding tissue therethrough. To facilitate insertion of the tubular member 110 in the patient's soft tissue the distal-most tip thereof may include an (mono or bipolar) RF electrosurgical element or wire, as indicated at reference numeral 116, which may be energized by an RF source, as shown at 240 in FIGS. 2C and 14.

[0103] FIG. 11 shows an embodiment of the removable core 400 according to the present invention. As the removable core 400 may advantageously be used independently of the excisional device 100, the removable core 400 includes a distal tapered tip 470, to allow it to easily penetrate soft tissue. Moreover, its thin profile allows the surgeon to insert the removable core 400 within soft tissue without, however, unduly damaging the tissue or making a large incision. The removable core 400 allows the surgeon to precisely localize the lesion to be excised from within the tissue itself. For example, the active element 440 of the removable core 400 may include an ultrasound transducer having similar characteristics as the sensor 270, and may be used alone or in addition to surface ultrasound to localize the lesion with a great degree of precision.

[0104] FIG. 12 shows a cross section of the embodiment of the excisional device 100 of FIG. 10, taken along line AA'. As shown in FIG. 12, the cutting tool 125 is exposed through the cutter window 120. The window 120 may, as shown in FIG. 12, include support guides 122 to support and guide the cutting tool 125 as it is outwardly extended and bowed. The tissue collection device 260, for clarity, is not shown in either FIG. 10 or 12. However, to accommodate the bulk of the excised tissue sample collected in the tissue collection device 260 after the cutting and collecting operation described herein, the tubular member 110 may include a recessed section 131. The recessed section provides space for the collected (e.g., bagged) tissue sample in the tissue collection device 260 when the excisional device is removed from the soft tissue mass. In this manner, the collected tissue sample within the tissue collection device 260 does not protrude from the generally smooth outer surface of the excisional device 100 upon retraction of the latter from the soft tissue mass from which the tissue sample is excised. The internal lumen 420 allows the removable core 400 to slide therein and to properly position the active element 440 facing the transducer window 410.

[0105] FIG. 13 shows the removable core 400 inserted within an expandable sheath 495. The expandable sheath includes a proximal base section 510. Attached to the proximal base section 510 is a generally cylindrical expandable meshwork 500 of, for example, plastic or nylon fibers. The meshwork 500 may be somewhat tapered at its distal end 520, to provide a smooth transition between the expandable meshwork 500 and the removable core device 400. The proximal section 450 of the core 400 may snap-fit to the proximal base section 510 of the expandable sheath 495, so as to be securely and removably attached thereto. As shown

in FIG. 13, the expandable meshwork 500 expands just enough to accommodate the removable core 400 inserted therein. In practice, the expandable sheath 495 and removable core 400 assembly may be inserted within the soft tissue together, to allow the surgeon to image the lesion prior to inserting the somewhat greater diameter excisional device 100 therein. Thereafter, the surgeon may retract the removable core 400 from the expandable sheath 495, leaving the expandable sheath 495 in place within the soft tissue, such as the breast.

[0106] FIG. 14 shows another embodiment of a soft tissue excisional device assembly 600 according to the present invention. In the configuration shown in FIG. 14, the removable core 400 is inserted and secured within the excisional device 100 so that the active element 440 faces out of the transducer window 410. As in FIG. 10, the tissue collection device 260 is not shown, for clarity. In FIG. 14, the excisional device 100 is shown inserted within the expandable sheath 495. Indeed, the excisional device 100, in FIG. 14, is shown inserted within and past the distal end 520 of the meshwork 500, so the distal portion of the excisional device 100 including the cutting tool 125 and the transducer window 410 extends therethrough. The meshwork 500, in FIG. 14, has expanded to accommodate the diameter of the excisional device 100. The proximal portion of the excisional device 100 may extend from the proximal base section of the expandable sheath 495. This allows the push or turn knob 226 (a turn knob 226 shown in FIG. 14) to be manually accessible to the surgeon. A number of peripheral devices may be connected to the assembly 600. Examples of such include a core power source 480, which may be, for example, an electrical source for an ultrasound transducer, one or more data processing and display devices 250 on which the internal structure of the tissue imaged by the active element 440 of the core 400 may be displayed, suction means 490, a cutting tool power source (a variable RF energy source, for example), and/or other devices 590. The suction device 490 may provide a suction force to the window 120 through an internal lumen to facilitate cutting of the tissue by the cutting tool 125.

[0107] The excisional device assembly 600 may be rotated in toto, or the excisional device 100 may be rotated independently of the expandable sheath 495, depending upon the degree of friction between the two. Preferably, the excisional device 100 is removable from the expanded sheath 495 shown in FIG. 14, while leaving the expanded sheath 495 in place within the soft tissue. In this manner, after retraction of the excisional device 100 from the sheath 495, the sheath 495 remains in place within the soft tissue to allow other instruments to be inserted therethrough. For example, the removable core 400 may, after the excisional procedure proper, be re-inserted through the expanded sheath 495 to the excision site. Thereafter, the surgeon may cause the active element 440 of the removable core 400 to become energized, to image the excision site to insure that the complete lesion has been removed from the soft tissue mass. To do this, the surgeon may rotate the removable core 400 within the expanded sheath 495 while observing the display or displays for signs of the lesion. If none is found, it is probable that the entire lesion has been successfully removed and the surgeon may then retract the core 400 from the sheath 495 and the sheath from the tissue mass and repair the incision made prior to inserting the assembly therein.

Alternatively, the surgeon may choose to remove both the expanded sheath 495 and the core 400 simultaneously.

[0108] FIG. 17 shows an embodiment of the method of excisional biopsy method according to the present invention. In FIG. 17, it is assumed that the soft tissue from which the lesion is to be excised is breast tissue and that the active element 440 of the removable core 400 is an ultrasound transducer. Other combinations are possible, and the present invention should not be limited to applications related to breast tissue and ultrasound. The removable core 400 and the active element 440, in FIG. 17, are together abbreviated as "US CORE", a shorthand expression for the phrase "ultrasound core" and the word "assembly" is abbreviated to "Ass'y". Moreover, it is to be understood that the steps shown in FIG. 17 constitute but a broad outline of one possible embodiment of the present inventive method. Therefore, other additional steps may be inserted between the steps shown in FIG. 17, or other steps may be substituted for some of the displayed steps without, however, departing from the scope of the present invention.

[0109] The method starts at step S0. In step S1, the lesion within the breast is grossly targeted, using, for example, standard or stereotactic surface ultrasound. In step S1, a rough estimate of the location of the lesion within the breast is obtained. The surgeon, after having located the general location of the lesion, may mark the location thereof on the ultrasound display or displays and/or on the corresponding surface of the breast, with an "X", for example. The breast is stabilized in step S2. Preferably, the breast is stabilized in an uncompressed or slightly expanded state, in the manner disclosed in the commonly assigned and co-pending U.S. patent application Ser. No. 09/158,215 or 09/200,661 previously discussed and incorporated by reference herein. The woman's other breast is preferably placed within a counterpart breast stabilizing device, which helps to immobilize the woman during the procedure. One of the ultrasound ports of the breast stabilizing device is aligned with the lesion, for example, by aligning one of its ultrasound ports with the marked location on the breast. Suction is then applied to the breast stabilizing device, in the manner described in the above-referenced application and a correctly oriented surface ultrasound device is secured to the ultrasound port of the stabilizing device. Other means of stabilizing the breast may also be used without, however, departing from the present invention.

[0110] In step S3, an entry site on the breast is chosen. Preferably, the peri-areolar region is chosen as the incision site, as scars within the peri-areolar region are less visible than scars in more exposed regions of the breast and for other anatomical reasons. The incision site is then anaesthetized, both on the skin surface and subcutaneously. Also in step S3, a small incision is made at the chosen incision site. Preferably, the incision is large enough to accommodate the expandable sheath 495 with the removable core 400 inserted therein. In step S4, the expandable sheath 495, together with the removable core inserted therethrough, is inserted into the incision made in step S3. Under surface ultrasound guidance, for example, the sheath 495/core 400 assembly is navigated adjacent to the lesion. If the sheath 495/core 400 assembly can be properly positioned adjacent to the target lesion, the method according to the present invention proceeds to step S5. If the sheath 495/core 400 assembly cannot be properly positioned adjacent to the target lesion, all or a

portion of the above-detailed steps are repeated until proper positioning of the sheath 495/core 400 assembly is achieved, adjacent to the target lesion.

[0111] Assuming now that step S4 has been completed to the surgeon's satisfaction, the core 400 is removed from the expandable sheath 495 and the expandable sheath 495 is left in place within the breast, as shown in step S5. In step S6, the removable core 400 is inserted within the internal lumen 420 of the tubular member of the excisional device 100 and locked securely in place, so that the active element 440 (in this case, an ultrasound transducer) is aligned with and faces out of the transducer window 410 of the device 100. Again leaving the expandable sheath 495 in place within the breast, the excisional device 100 (with the core 400 secured therein) is advanced through the expandable sheath 495. The sheath 495 then expands within the breast tissue to accommodate the somewhat larger diameter of the excisional device 100. The excisional device 100 is advanced past the tapered distal end 520 of the sheath 495, so the assembly including the sheath 495, the excisional device 100 and the removable core 400 is positioned adjacent to the target lesion within the breast tissue, as shown in step S7.

[0112] In step S8, the correct position adjacent the target lesion and the correct rotational orientation of the aforementioned assembly (FIG. 14) are confirmed, using surface ultrasound and/or the core ultrasound 400. The active element 440 of the core 400 is particularly well suited for this task, as the excisional device 100 may be rotated within the tissue, and positioned so the cutting tool 125 is properly positioned to allow it to rotate, extend and bow outwardly in such a manner as to precisely sever the lesion from the surrounding tissue with an adequate margin of healthy tissue. Indeed, the ultrasound transducer 440, as it rotates along with the excisional device 100, images the lesion before the cutting tool 125 cuts it, thereby allowing the surgeon to optimally deploy the cutting tool based upon his or her observation of the imaged tissue on a display or displays. In step 9, the surgeon may activate an anaesthetic infusion, the anaesthetic being delivered by the cutting tool 125 via the plurality of through holes 126, best seen in FIGS. 4 and 6. Step S9 may be skipped if the cutting tool 125 does not provide for through holes 126 or if the surgeon does not deem it necessary to anaesthetize the tissue during the rotation of the cutting tool 125. For example, the tissue may have been previously anaesthetized. While rotating at least the excisional device 100 (with the removable core 400 secured therein), the cutting tool 125 is extended using, for example the push or turn knob 226 shown in FIGS. 2C and 14, thereby causing the cutting tool 125 to extend from the window 410 and to bow outwardly, as shown in step S10. Depending on the amount of friction between the excisional device 100 and the expandable sheath 495 (which may be freely chosen depending upon the choice of material for the meshwork 500 and the configuration of the mesh), the sheath 495 may rotate along with the excisional device 100. The degree of extension and bowing may be finely controlled by the surgeon as the excisional device 100 is rotated, either manually or by a motorized unit (not shown) coupled thereto. As the cutting tool is rotated, the severed tissue sample is preferably collected (e.g., bagged) in a tissue collection device 260 (FIGS. 2A and 2B), as shown at step S11. The blood vessels may be coagulated as the cutting tool rotates and cuts the tissue, or afterwards. In step S12, after the excisional device 100 has completed at least one

revolution within the breast and has cut a volume of revolution therein, including at least the target lesion and preferably a margin of healthy tissue surrounding the lesion, the excisional biopsy device **100** and removable core **400** assembly are retracted through the sheath **495**, leaving the sheath **495** once again in place within the breast. Preferably, the tissue collection device **260** and the tissue sample it encloses lie within the recessed section **131** of the generally tubular member **110**. In this manner, the filled collection device **260** does not protrude or protrude too much from the surface of the tubular member **110**, thereby allowing the retrieved tissue sample to be readily retracted with the excisional device **100** through the sheath **495**.

[0113] After retraction of the excisional device **100**, the core **400** may be retracted from the device **100** and reinserted through the sheath **495** left in place within the breast. The core **400** is then advanced adjacent to the excision site, and rotated to allow the surgeon to image the excision site to insure that the entire lesion has indeed been removed, as shown in step S13. Some or all of the above steps may be repeated should the imaging of the excision site by the core **400** within the sheath **495** reveal that a portion of the target lesion was not excised. Assuming that the entire target lesion has been removed, the incision is repaired by, for example, suturing the peri-areolar incision site. The method ends at step S16.

[0114] The removable transducer core **400** of FIG. 11 is not the only removable probe that may be fitted to and within the tubular member **110** of the excisional device **100** (see FIG. 10, for example). Indeed, FIG. 18 shows a top view of a removable cutting probe **700**, according to an embodiment of the present invention. The removable probe **700** includes a proximal portion **702** and a distal portion **704**. The proximal portion **702** may include cutting tool extending means **718** and the distal portion **704** may include a cutting tool **706**, such as a wire or ribbon cutting tools described above. The cutting tool **706** may be sharpened on its leading edge. The first removable probe **700** is preferably configured to fit at least partially within the tubular member **110** to enable the cutting tool **706** to selectively bow out of and to retract within a first window **710** when the cutting tool extending means **718** are activated. The first window **710** is defined within the surface of the removable probe **700**. According to an embodiment of the present invention, the removable cutting probe **700** may be inserted within the internal lumen **420** (or guided within guides internal to the tubular member **110**) of the tubular member **110** in such a manner that the window **710** defined within the probe **700** faces the window **410** (FIG. 10) defined within the surface of the tubular member **110**. Alternatively, the tubular member **110** may define one or more additional windows similar to that shown at **410** in FIG. 10. In this case, the removable probe **700** (and those to be described relative to FIGS. 21-27C) may be inserted within the tubular member **110** such that the window **710** faces one of these additional windows (hereinafter collectively referenced by numeral **410**) and/or the window **410** in FIGS. 10 and 12.

[0115] According to an embodiment of the present invention, the cutting tool **706** may include an RF cutting tool. In this case, the RF cutting tool and the removable cutting probe **700** may be connected to an RF power source, such as shown at **240** in FIGS. 2C, 14 and 18. The RF cutting tool,

for example, may be either a monopolar or a bipolar RF cutting tool, as disclosed above.

[0116] The removable cutting probe **700** may also include an internal guide **712** (or may define an internal lumen) to enable the cutting tool **706** to slide within the removable cutting probe **700** when cutting tool extending means **718** are activated. The cutting tools extending means **718** are shown as a thumb-activated dial in FIGS. 18-20. However, any other means of advancing and retracting the cutting tool **706** may also advantageously be used within the context of the present invention. According to a still further embodiment, the distal portion **704** of the removable cutting probe **700** may further include a window slide **708** disposed within the window **710** and the proximal end **702** may further include window slide extending means **716**. The window slide **708** is coupled to the window slide extending means **716** and is guided within the removable cutting probe **700** by an internal guide or lumen **714** along the length of the probe **700**. According to the present invention, the window slide **708** is configured to selectively cover a portion of the window **710** when the window slide extending means **716** are activated. The window slide extending means **716** are shown in FIGS. 18-20 as thumb-activated dials. However, any means of extending the window slide **708** within the window **710** to selectively cover a portion thereof may readily be implemented within the removable cutting probe **700**, as those of skill will recognize. Functionally, the window slide **708** covers a portion of the window **710** to selectively vary the width of the window **710** through which the cutting tool **706** is allowed to extend or bow.

[0117] The operation of the removable cutting probe **700** is graphically shown in FIGS. 19 and 20. FIG. 19 is a side view of the removable cutting probe of FIG. 18, showing the adjustable window slide **708** in a first position, according to an embodiment of the present invention, whereas FIG. 20 is a side view of the removable cutting probe of FIG. 18, showing the adjustable window slide **708** in a second position. As shown in FIG. 19, the window slide **708** is less engaged within the window **710** and it is in FIG. 20. Consequently, the cutting tool **706** in FIG. 19 is able to extend over a wider portion of the window **710** than it is able to when the window slide **708** is in the relatively more engaged position shown in FIG. 20. For example, the window slide **708** may be further engaged within the window **710** (FIG. 20) when the physician wants to cut a smaller tissue specimen than would otherwise be cut when the probe **700** is in the configuration illustrated in FIG. 19.

[0118] FIG. 21 is a top view of a removable tissue collection probe **800**, according to an embodiment of the present invention. As shown therein, the removable tissue collection probe **800** includes a proximal section **802** and a distal section **804**. The proximal section **802** may include a tissue collection device extending means **814** and the distal section **804** may include a tissue collection device **808**, **810**. Similar to the removable cutting probe **700** of FIGS. 18-20, the removable tissue collection probe **800** may be configured to fit at least partially within the tubular member **110** to enable the tissue collection device **808**, **810** to extend out of and to retract within the window **410** (or other window defined within the surface of the tubular member **110**) when the tissue collection device extending means **814** are activated. Similar to the activating means **716**, **718** of FIGS. 18-20, the tissue collection device extending means **814** may

be configured as a thumb-dial or a wheel or as any other suitable means for extending the tissue collection device **808**, **810**, such as a lever, for example. As shown in the top view of **FIG. 21** and in the detail top view of **FIG. 22**, the tissue collection device **808**, **810** may include a ribbon or wire **808** that may be configured to extend or bow out of and retract back within the window **806** in the probe **800**. Attached to the wire or ribbon **808** is a thin flexible sheet of non-porous or porous material **810**, such as polyethylene or polyethylene terephthalate (PET), for example. A non-porous material is preferable to isolate the tissue specimen from the surrounding tissue. Such isolation is used to prevent possible cancer cells from seeding along the insertion track of the probe and/or the excisional device **100**. A non-porous flexible material **810** prevents fluid and cell leakage therefrom and insures isolation of the cut tissue specimen. The thin flexible sheet of material **810** may be dispensed from a roll **814** of such material, the free end of the sheet **810** being attached to the ribbon or wire **808**. In this manner, the roll **814** may dispense the material **810** as the ribbon or wire **808** is extended or bowed out of the window **806** (and out of a corresponding (facing) window in the tubular member **110**) and completely or partially encompass or encapsulate the tissue specimen (see reference numeral **1008** in **FIGS. 27A-27C**) as the tubular member **110** and contained probe **800** are rotated within the patient's soft tissue. Alternatively, the tissue collection device **808**, **810** may be configured as shown and described relative to **FIGS. 2A and 2B**, for example. When the tissue collection device extending means **814** are activated, the ribbon or wire **808** slides along the internal lumen or guide **812** defined in the probe **800** and causes the ribbon or wire **808** to bow and extend out of the window **806** defined in the probe **800**, thereby deploying the flexible material **810** and encapsulating the tissue specimen. These embodiments allow the tissue specimen to be removed in one piece for best histological analysis by a pathologist. **FIGS. 27A through 27C** show still another tissue collection device configuration, as will be described below.

[0119] **FIG. 23** shows a side view of the removable tissue collection probe **800** of **FIG. 21**, showing the tissue collection device **808**, **810** in an extended configuration. As shown therein, the tissue collection device extending means **814** has been (manually, for example) activated to cause the bowing of the tissue collection device **808**, **810** out of the window **806** defined within the tissue collection probe **800**. This bowing, or extension, of the wire or ribbon **808** causes the thin sheet of material **810** to be unrolled or otherwise deployed. As the tubular member **110** of the excisional device **100** is rotated, the tissue collection probe contained therein is also rotated, in the direction shown by arrow **816**, for example. The tissue collection device extending means **814** may be activated extended (bowed) so as to cause the ribbon or wire **808** to follow substantially the same path within the tissue, as did the cutting tool **706**. This eases the collection process, as the ribbon or wire **808** merely follows the path of the incision previously made by the cutting tool **706** or **125**. As the excisional device is rotated, the tissue specimen (i.e., lesion) is captured within the sheet of material or bag **810**, whereupon it may readily be extracted from the patient for pathological examination.

[0120] **FIG. 24A** is a top view of a removable cutting and tissue collection combination probe **900**, according to an embodiment of the present invention, whereas **FIG. 24B** is

a partial cross-sectional view of the removable cutting and tissue collection combination probe **900** of **FIG. 24A**, taken along lines AA'. As shown in **FIG. 24A**, the combination cutting and tissue collection removable probe **900** includes a proximal end **902** and a distal end **904**. In the embodiment of **FIG. 24A**, the proximal end **902** may include cutting tool extending means **908** and tissue collection device extending means **906**. The extending means **906**, **908** may be configured as thumb dials or as any devices that are operative to extend the tissue collection device **918** and/or the cutting tool **914**, such as a lever, for example. As shown in **FIG. 24B**, the wires and/or ribbons that constitute the cutting tool **914** and part of the tissue collection device **918** extend from the extending means **906**, **908** along the length of the probe **900**. The cutting tool **914** and the wire or ribbon of the tissue collection device **918** may be guided within the probe **900** by guides **912** and **910**, respectively. Alternatively, the cutting tool **914** and the wire or ribbon of the tissue collection device **918** may be guided within the probe **900** by one or more internal lumens defined therein, in a manner similar as described relative to internal lumen **420** of tubular member **110**, shown in **FIG. 10**. As the cutting tool **914** may be energized by RF energy, the cutting tool **914** may be separated from the tissue collection device **918** by an air gap **920** (for example) of sufficient width to prevent arcing therebetween.

[0121] **FIG. 25** is a top view of a removable cutting and tissue collection combination probe **925**, according to another embodiment of the present invention. The embodiment of **FIG. 25** differs from that shown in **FIG. 24A** in that the cutting tool **914** is separated from the tissue collection device **918** not by an air gap, but by an insulating material **922**, such as a flexible plastic insulator. In the case wherein the cutting tool **914** includes an RF cutting device, the cutting tool **914** is electrically coupled to an RF power source, such as shown at **240**. The configuration of the proximal end **902** of the probe shown in **FIG. 25** also differs from that shown in **FIG. 24A**, in that a single extending means **926** is configured to activate both the cutting tool **914** and the tissue collection device **918**, as the cutting tool **914** and the tissue collection device **918** are mechanically coupled to one another. The assembly including the mechanically coupled cutting tool **914** and tissue collection device **918** is coupled to the extending means **926** along the length of the probe, and is guided there along by an internal guide or lumen **924**.

[0122] **FIG. 26** is a side view of a removable cutting and tissue collection combination probe **950**, according to a still further embodiment of the present invention, wherein the cutting tool **930** and the tissue collection device **932**, **934** are shown in their extended (bowed) configurations. As shown, the probe **950** includes a proximal portion **902** and a distal portion **904**. In the embodiment of **FIG. 26**, the proximal portion **902** includes a cutting tool extending means **926** that is configured to activate the cutting tool **930** and a tissue collection device extending means **944** that is configured to activate and extend the tissue collection device **932**, **934**. The tissue collection device **932**, **934** may include a ribbon or wire **932** that is adapted to bow (extend) out of and to retract back within a first window **942** defined within the probe **950**. A thin and flexible sheet of material **934** is attached to the trailing edge of the wire or ribbon **932** to encapsulate or otherwise capture the cut tissue specimen upon activation of the tissue collection device **932**, **934** and

rotation of the tubular member **110** and probe **950**, in the direction indicated by arrow **928**, for example. Similarly, the cutting tool **930** (including an RF cutting tool, for example) is configured to extend out of and retract back into a second window **936**. Both of the first and second windows **942**, **936**, when the probe **950** is inserted into the tubular member **110**, are aligned with corresponding windows defined within the tubular member **110**. One such window is shown in **FIG. 10** at reference numeral **410**.

[0123] The combination probe **950** of **FIG. 26** may also include a plurality of through holes in fluid communication with an internal lumen **940** defined within the internal wall of the probe **950**. In turn, the internal lumen **940** is in fluid communication with a port **942**, which may be disposed at the proximal end of the probe **950**. The through holes **938** may be utilized for the delivery of a fluid to the patient during the excisional procedure, such as antibiotic agents, analgesic agents or most any pharmaceutical agent. Such agents may be administered to the patient from the port **942**. Alternatively, the port **942** may be coupled to suction and the through holes **938** may be utilized to suction out the excisional site of smoke, blood or other bodily fluids during or after the excisional procedure. Alternatively still, more than one port **942** may be provided in the proximal portion **902** and more than one lumen **940** may be defined along the length of the probe **950**. The additional lumen may be in fluid communication with selected through holes **938**. By this structure, both delivery of a pharmaceutical agent and suctioning may be provided within a single probe **950**.

[0124] Although the probes shown in **FIGS. 18-26** have been described as removable probes adapted to fit at least partially within the excisional device **110**, it should be noted that they need not be utilized therewith, and may be utilized independently thereof. For example, the cutting probe of **FIGS. 18-20** may be inserted and operated within soft tissue by themselves, without being inserted in the excisional device **110** of **FIG. 10**. Likewise, the tissue collection probe **800** may be utilized without the excisional device **110**. For example, the cutting probe **700** of **FIGS. 18-20** may be utilized to cut the tissue specimen from the surrounding soft tissue, whereupon the tissue collection probe **800** of **FIGS. 21-23** may be inserted after removal of the cutting probe **700**. Moreover, the features of each of the probes of **FIGS. 18-27C** may be combined to best suit the application envisaged. The present invention, therefore, is not to be limited by the specific embodiments illustrated in **FIGS. 18-27C**, as various other combinations of the disclosed features are possible, as those of skill will readily recognize.

[0125] **FIG. 27A-27C** are partial cross-sections of a tissue collection probe **1000**, taken at the level of the tissue collection device **1018** thereof, as the probe **1000** captures and encapsulates a tissue specimen (lesion) **1008** within the patient's soft tissue, such as the breast. Turning first to **FIG. 27A**, the tissue collection device **1018** includes a thin sheet of flexible material **1002**, which is folded on itself. One end of the thin flexible sheet of material **1002** is coupled at **1006** to the ribbon **1004**, while the other end thereof is attached to the body of the probe **1000**. The ribbon **1004** is configured to selectively extend out of and retract back into a window, such as shown at **806** in **FIG. 23**, for example. A tissue specimen (lesion) **1008** is to be excised from the soft tissue **1018**. To do so, the excisional device **110** (and thus the probe **1000** fitted therein) is rotated in the direction of the arrow

1010, while the ribbon **1004** is extended (bowed) in the direction of arrow **1012**, shown in **FIG. 27B**. As the ribbon **1004** is extended, it unfolds and deploys the thin sheet of flexible material **1002**, to at least partially encapsulate the tissue specimen **1008**. As shown in **FIG. 27C**, the ribbon **1004** of the tissue collection device **1018** may then be retracted in the direction of arrow **1016** after the rotation **1014** (**FIG. 27B**) of the excisional device **110** causes the tissue specimen **1008** to be fully encompassed or encapsulated by the thin sheet of flexible material **1002**. The excisional device **110** may then be removed from the patient, along with the collected tissue specimen **1008**. To aid in the visualization of the tissue collection device **1018** during the excisional procedure, the ribbon **1004** thereof may include or be coated with a radiopaque material or may include a material readily visible by surface or intra-tissue ultrasound.

[0126] **FIG. 28** is a flowchart of a soft tissue treatment method, according to another embodiment of the present invention. As shown in step **S281**, the cutting probe, such as shown at **700** in **FIGS. 18-20**, is inserted into the excisional device **100**. The excisional device **100** and cutting probe assembly **700** is then inserted into the patient's soft tissue, at the site of interest. The cutting tool **710** of the probe assembly **700** is extended (bowed) to cut the tissue specimen of interest from the surrounding tissue and the excisional device **100** is then rotated, as shown at step **S282**. Step **S283** calls for the removal of the cutting probe **700** from the excisional device **100**, leaving the excisional device **100** in place within the patient. A tissue collection probe, such as shown at **800** in **FIGS. 21-23**, may then be inserted within the excisional device **100** (if not already inserted therein), as shown at **S284**. The tissue collection device **808-810** may be extended (bowed) out from the excisional device **100** and the assembly including the excisional device **100** and tissue collection probe **800** may then be rotated (in a direction opposite from the direction of rotation during the cutting step **S282**, for example). As noted in step **S285**, this extends the collection device **808-810** along the same path as traveled by the cutting tool **710** of the cutting probe **700** in step **S282** and causes the tissue collection device **808-810** to at least partially encompass (encapsulate) the tissue specimen, as shown, for example in **FIG. 27C**. The assembly including the excisional device **100** and tissue collection device **800** and the encapsulated tissue specimen may then be retracted from the patient, as shown at **S286**, and the specimen forwarded for histological analysis.

[0127] Alternatively, the combination cutting and tissue collection probe **900** may be inserted in the excisional device, instead of consecutively inserted the cutting probe **700** and tissue collection probe **800** therein. In this case, the tissue collection device **918** or **932**, **934** may be activated simultaneously with or after the deployment of the cutting tool **914**. Moreover, to better control the deployment of the cutting tool of **FIGS. 18-20** or **24A-26** and/or the tissue collection device of **FIGS. 21-23**, **24A-26** or **27A-27C**, an intra-tissue ultrasound sensor such as described relative to **FIGS. 1-17** may be used, to sweep a plane ahead of the cutting tool and/or tissue collection device as the tubular member **110** of the excisional device **100** rotates.

[0128] While the foregoing detailed description has described several embodiments of this invention, it is to be understood that the above description is illustrative only and not limiting of the disclosed invention. For example, the

method of the present invention may also be carried out without the use of the tubular member **110**, by inserting the probes disclosed herein relative to **FIGS. 18-27C** directly in the patient's soft tissue, as the present cutting and tissue collection probes have utility independent of the excisional device **100**. A number of other modifications will no doubt occur to persons of skill in this art. For example, the shape and placement of the cutting device and tissue collection extending means (**814, 906, 908, 926, 944**) may differ from that illustrated and described herein, for ergonomic or other concerns. All such modifications, however, should be deemed to fall within the scope of the present invention. Thus, the invention is to be limited only by the claims as set forth below.

1-77. (canceled)

78. A device configured to remove a specimen of breast tissue that is cut from surrounding breast tissue, comprising:

a shaft, and

a tissue collection element coupled to the shaft, the tissue collection element including a thin flexible membrane, the tissue collection device being movable from a

retracted position to an expanded position, the thin flexible membrane being configured to encapsulate the cut specimen while maintaining the cut specimen intact and isolating the captured specimen from contact with the surrounding breast tissue.

79. The device of claim 78, wherein the tissue collection element includes a flexible element to which the thin flexible membrane is attached and wherein the flexible element is configured to selectively bow away from and retract toward the shaft.

80. The device of claim 78, wherein the thin flexible membrane forms a bag.

81. The device of claim 80, wherein the bag is configured to selectively open to capture the cut specimen and close to encapsulate the cut specimen as the tissue collection element bows away from and retracts toward the shaft, respectively.

82. The device of claim 78, wherein the tissue collection element is configured to expand to a size at least equal to the size of the cut specimen.

* * * * *

专利名称(译)	切除活组织检查装置和方法		
公开(公告)号	US20050182339A1	公开(公告)日	2005-08-18
申请号	US11/045006	申请日	2005-01-26
[标]申请(专利权)人(译)	LEE ROBERTA VETTER JAMES W CHERNOMORSKY ARY 小号		
申请(专利权)人(译)	LEE ROBERTA VETTER 詹姆斯· CHERNOMORSKY ARY S.		
当前申请(专利权)人(译)	ENCAPSULE 医药有限责任公司		
[标]发明人	LEE ROBERTA VETTER JAMES W CHERNOMORSKY ARY S		
发明人	LEE, ROBERTA VETTER, JAMES W. CHERNOMORSKY, ARY S.		
IPC分类号	A61B10/02 A61B8/12 A61B10/00 A61B10/04 A61B17/22 A61B18/12 A61B18/14 A61B19/00 A61B17/32		
CPC分类号	A61B10/0041 A61B10/02 A61B10/0266 A61B10/04 A61B17/320725 A61B18/1482 A61B2218/002 A61B2018/00333 A61B2018/1407 A61B2018/1475 A61B2019/5278 A61B2019/528 A61B2018/00011 A61B2090/3782 A61B2090/3784		
外部链接	Espacenet USPTO		

摘要(译)

切除活组织检查系统包括管状构件，该管状构件具有近端和远端，在该远端中限定一个或多个窗口。第一可移除探针具有包括切割工具延伸器的近端部分和包括切割工具的远端部分。第一可移除探针可构造成为至少部分地配合在管状构件内，以使切割工具能够在切割工具扩展器被激活时选择性地从一个窗口中弯出和缩回。第二可移除探针具有包括组织收集装置延伸器的近端部分和包括组织收集装置的远端部分。第二可移除探针还可以被配置成至少部分地配合在管状构件内，以在组织收集装置扩展器被激活时使组织收集装置能够伸出窗口中的一个窗口并在其中缩回。还可以提供第三可移除探针。第三可移除探针还可以被配置为至少部分地配合在管状构件内，并且可以包括安装在其中的成像装置，例如超声换能器。通过在旋转切除装置的同时选择性地激活切割工具和组织收集装置，可以从周围组织切割组织样本并收集以用于以后的分析。

