




US 20130006285A1

(19) **United States**(12) **Patent Application Publication**
Whitman(10) **Pub. No.: US 2013/0006285 A1**(43) **Pub. Date: Jan. 3, 2013**(54) **BIPOLAR OR ULTRASONIC SURGICAL
DEVICE****Publication Classification**(75) Inventor: **Michael P. Whitman**, New Hope, PA
(US)(51) **Int. Cl.**
A61B 17/32 (2006.01)(73) Assignee: **Tyco Healthcare Group LP**, Mansfield,
MA (US)(52) **U.S. Cl.** **606/169**(21) Appl. No.: **13/611,273**(57) **ABSTRACT**(22) Filed: **Sep. 12, 2012****Related U.S. Application Data**(62) Division of application No. 10/128,768, filed on Apr.
22, 2002, now Pat. No. 8,292,888.(60) Provisional application No. 60/285,113, filed on Apr.
20, 2001, provisional application No. 60/289,370,
filed on May 8, 2001.

An electro-mechanical surgical device, system and/or method may include a housing, at least two opposing jaw, and at least one electrical contact associated with at least one of the jaws. The electrical contact may include at least one of a bipolar electrical contact and an ultrasonic electrical contact. The electrical contact may be a row of electrodes located on one or all of the jaws. A sensor may also be associated with any tissue located between the jaws to sense and report the temperature of that tissue. A piercable ampulla containing fluid may also be placed on at least one of the jaws so that the fluid is releasable when the jaws are in closed position and the electrode(s) pass through the tissue into the piercable ampulla.






FIG. 1a




FIG. 1b




FIG. 1c




FIG. 1d




FIG. 1e




FIG. 1f




FIG. 1g




FIG. 1h




FIG. 2a




FIG. 2b





FIG. 2c



2007




FIG. 2e




FIG. 2f




FIG. 2g




FIG. 2h






FIG. 2i






FIG. 3a







FIG. 3d







FIG. 4a






FIG. 5a




FIG. 5b




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

BIPOLAR OR ULTRASONIC SURGICAL DEVICE

CROSS-REFERENCES TO RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Patent Application Ser. No. 60/285,113, filed on Apr. 20, 2001, and of U.S. Provisional Patent Application Ser. No. 60/289,370, filed on May 8, 2001, each of which is expressly incorporated herein in its entirety by reference thereto.

[0002] This application also expressly incorporates in its entirety by reference thereto International Published Patent Application No. WO 00172765. This application also expressly incorporates in its entirety by reference thereto U.S. patent application Ser. No. 09/723,715, filed on Nov. 28, 2000, which is a continuation-in-part of U.S. patent application Ser. No. 09/324,451, filed on Jun. 2, 1999, now U.S. Pat. No. 6,315,184, issued on Nov. 13, 2001, a continuation-in-part of U.S. patent application Ser. No. 09/324,452, filed on Jun. 2, 1999, a continuation-in-part of U.S. patent application Ser. No. 09/351,534, filed on Jul. 12, 1999, now U.S. Pat. No. 6,264,087, issued on Jul. 24, 2001, a continuation-in-part of U.S. patent application Ser. No. 09/510,923, filed on Feb. 22, 2000, a continuation-in-part of U.S. patent application Ser. No. 09/510,927, filed on Feb. 22, 2000, which is a continuation-in-part of U.S. patent application Ser. No. 09/324,452, and a continuation-in-part of U.S. patent application Ser. No. 09/510,932, filed on Feb. 22, 2000, each of which is expressly incorporated herein in its entirety by reference thereto.

FIELD OF THE INVENTION

[0003] The present invention relates to a bipolar and/or ultrasonic surgical device.

BACKGROUND INFORMATION

[0004] Various bipolar, ultrasonic, and/or electro-mechanical surgical devices exist which are used to cauterize and coagulate tissue in a surgical procedure. Some devices use bipolar electrical energy in order to cut and/or coagulate tissue. Generally, bipolar surgical instruments clamp the tissue prior to the application of the electro surgical energy. Some devices provide opposing jaws to perform the clamping or grasping procedure where an electrode(s) is disposed on the inner surface of the jaws. These bipolar surgical instruments coagulate, cut and separate tissue by charging the electrode(s) to apply heat to the tissue between the jaws.

[0005] During the use of bipolar surgical instruments, the heat generated by the electrodes causes the desired coagulation and cutting of tissue. Several of the bipolar surgical instruments may encounter problems with the application of the heat of the tissue. Adjacent tissue may be damaged due to application of excessive heat. Conversely, where less energy is applied to the electrodes in order to prevent over heating, the coagulation of the tissue may require more time than desired.

[0006] Fully mechanical surgical devices are also available in order to perform the above procedure. The mechanical devices require the application of force to staple and cut the tissue. Many of the existing mechanical devices use four rows of staples in order to ensure the proper results. Due to the cutting and stapling functions, many of these mechanical surgical instruments require an excessive amount of force in order to effectively perform their functions.

[0007] Therefore, an object of the present invention provides an electro-mechanical that allows greater control of heat applied to the tissue by the bipolar electrodes and allows the use of less mechanical force when incorporating the use of mechanical force.

SUMMARY

[0008] The above and other beneficial objects and advantages of the present invention may be effectively attained by providing a bipolar, ultrasonic and/or electro-mechanical surgical device as described herein.

[0009] In an example embodiment and/or example method, the present invention provides for an electro-mechanical surgical device including a housing, at least two opposing jaw, and at least one electrical contact associated with at least one of the jaws. In a further example embodiment of the present invention, the electrical contact is at least one of a bipolar electrical contact and an ultrasonic electrical contact.

[0010] In a further example embodiment and/or example method of the present invention, the surgical device includes a row of electrical contacts associated with the at least one of the opposing jaws. In a further example embodiment and/or example method of the present invention, the surgical device includes at least two rows of electrical contacts associated with at least one of the opposing jaws.

[0011] In a further example embodiment and/or example method of the present invention, the surgical device includes a sensor configured and arranged to sense temperature of tissue disposed between the upper jaw and the lower jaw. In a further example embodiment and/or example method of the present invention, the sensor may be configured to transmit a signal to the surgical device via, e.g., a data transfer cable. the signal indicating the temperature of the tissue disposed between the upper jaw and the lower jaw. Further, the signal transmitted by the sensor may effect a movement of the jaw(s) and/or a change in the heating effect of the electrode(s) on the tissue.

[0012] In a further example embodiment and/or example method of the present invention, the surgical device includes, on at least one of the jaws, at least one pierceable ampulla containing fluid so that the fluid is releasable when the upper jaw and the lower jaw are in the closed position and so that the electrode passes through the tissue disposed between the upper jaw and the lower jaw into the at least one pierceable ampulla. That fluid may include, for example, a variety of fluids or matters or dyes, for example, collagen, fibrin, dye, matter configured to effect anastomosis, matter configured to seal tissue and matter configured to effect hemostasis, etc. In a further example embodiment and/or example method of the present invention, the electrode and/or row(s) of electrodes may be activated so that the tissue is coagulated to induce hemostasis.

[0013] In a further example embodiment and/or example method of the present invention, an electro-mechanical surgical system may include a surgical device and a surgical instrument. The surgical device may include a housing, an elongated shaft extending from the housing, a distal end of the elongated shaft configured to detachably couple with a surgical instrument, a steering arrangement, the steering arrangement configured to steer the distal end of the elongated shaft, and a motor system disposed within the housing, the motor system configured to drive the drive shafts and the steering arrangement. The surgical instrument may include an upper jaw, a lower jaw, the lower jaw opposing the upper

jaw and the lower jaw configured to detachably couple with the distal end of the elongated shaft of the surgical device, and an electrode or row(s) of electrodes provided on at least one of the lower jaw and the upper jaw. The electrode(s) may be associated with any one of more of the jaws, such as, for example, the inner surface of an upper jaw of two opposing jaws.

[0014] In a further example embodiment and/or example method of the present invention, one of the opposing jaws, e.g., the lower jaw, includes at least two rows of staples and a cutting device.

[0015] In further example embodiments and/or example methods of the present invention, there may be a reduced number of staples and thus less mechanical force to form staples and transect tissue. Further, example embodiments and/or example methods may use bipolar radio-frequency (RF) energy and/or staples to coagulate and cut tissue. Further, example embodiments and/or example methods may include one row of staples or no staples. Further, example embodiments may include an energy surgical attachment (DLU) which consists of two opposing jaws where the two opposing jaws may include, e.g., one or two, rows of bipolar electrical contacts.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] FIG. 1*a* is a perspective view of an electro-mechanical driver device, which may be coupled to the surgical device according to the present invention.

[0017] FIG. 1*b* is a detailed view of the interior of a flexible shaft of the electro-mechanical surgical device illustrated in FIG. 1*a*.

[0018] FIG. 1*c* is a schematic top view of a remote control unit of the electro-mechanical surgical device.

[0019] FIG. 1*d* is a perspective view of a surgical device according to one embodiment of the present invention.

[0020] FIG. 1*e* is an example embodiment of a memory device according to the present invention.

[0021] FIG. 1*f* is an end view of an example embodiment of a coupling.

[0022] FIG. 1*g* is a front end view of a second coupling

[0023] FIG. 1*h* is a schematic top view of another example embodiment of a remote control unit.

[0024] FIG. 2*a* illustrates an example embodiment of parallel expanding jaws in a closed position.

[0025] FIG. 2*b* illustrates an example embodiment of parallel expanding jaws in an open position.

[0026] FIG. 2*c* illustrates an example embodiment of the components of the parallel expanding jaws in a closed position.

[0027] FIG. 2*d* illustrates an example embodiment of the components of the parallel expanding jaws in an open position.

[0028] FIG. 2*e* is cross-sectioned view of the parallel expanding jaws.

[0029] FIG. 2*f* illustrates an example embodiment of the parallel expanding jaws where the lower jaw includes electrodes.

[0030] FIG. 2*g* illustrates an example embodiment of the parallel expanding jaws where the lower jaw includes electrodes and a stapling mechanism.

[0031] FIG. 2*h* illustrates another example embodiment of the parallel expanding jaws where the lower jaw includes electrodes.

[0032] FIG. 2*i* illustrates another example embodiment of the parallel expanding jaws where the lower jaw includes electrodes and a stapling mechanism.

[0033] FIG. 2*j* illustrates an example embodiment of the parallel expanding jaws which includes ultrasonic pins.

[0034] FIG. 2*k* illustrates an example embodiment of the parallel expanding jaws which includes surgical barb pins.

[0035] FIG. 3*a* illustrates an example embodiment of an electrode and staple configuration according to the present invention.

[0036] FIG. 3*b* illustrates an example embodiment of an electrode and staple configuration disposed on a lower jaw.

[0037] FIG. 3*c* illustrates an example embodiment of an electrode configuration disposed on a lower jaw.

[0038] FIG. 3*d* illustrates an example embodiment of an electrode configuration according to the present invention.

[0039] FIG. 3*e* illustrates an example embodiment of an electrode configuration disposed on a lower jaw.

[0040] FIG. 4*a* illustrates an example embodiment of scissor-like jaws in a closed position.

[0041] FIG. 4*b* illustrates an example embodiment of scissor-like jaws in an open position.

[0042] FIG. 5*a* illustrates a perspective view of an example embodiment of the present invention.

[0043] FIG. 5*b* illustrates an example embodiment of a front panel of an electro-mechanical device.

[0044] FIG. 6 illustrates an example embodiment of an electrode arrangement according to the present invention.

[0045] FIG. 7 illustrates another example embodiment of an electrode arrangement according to the present invention.

[0046] FIG. 8 is a side view of an example electrode configuration according to the present invention.

[0047] FIG. 9 illustrates an example embodiment of an electrode configuration according to the present invention.

[0048] FIG. 10 illustrates an example embodiment of the present invention which includes the use of ultrasonic technology.

[0049] FIG. 11 illustrates an example embodiment where surgical barbs are used as electrodes.

DETAILED DESCRIPTION

[0050] Referring to FIG. 1*a*, a perspective view of an electro-mechanical driver device **101** according to one example embodiment of the present invention is illustrated. Such an electro-mechanical driver device is described in, for example, U.S. patent application Ser. No. 09/723,715, entitled "Electro-Mechanical Surgical Device," which is expressly incorporated herein in its entirety by reference thereto. Electro-mechanical driver device **101** may include, for example, a remote power console **102**, which includes a housing **104** having a front panel **103**. Mounted on front panel **103** are a display device **106** and indicators **108a** and **108b**. A flexible shaft **105** may extend from housing **104** and may be detachably secured thereto via a first coupling **107**. The distal end **109** of flexible shaft **105** may include a second coupling **106** adapted to detachably secure a surgical instrument or attachment to the distal end **109** of the flexible shaft **105**. In accordance with the example embodiment of the present invention, the surgical instrument or attachment may be, for example, a surgical stapler and cutter device that utilizes electrical energy to cut and/or coagulate tissue. Other surgical instruments are described, for example, in U.S. patent application Ser. No. 09/324,451, entitled "A Stapling Device for Use with an Electro-mechanical Driver Device for Use with Anasto-

mosing, Stapling, and Resecting Instruments,” U.S. patent application Ser. No. 09/324,452, entitled “Electro-mechanical Driver Device for Use with Anastomosing, Stapling, and Resecting Instruments,” U.S. patent application Ser. No. 09/351,534, entitled “Automated Surgical Stapling System,” U.S. patent application Ser. No. 09/510,926, entitled “A Vessel and Lumen Expander Attachment for Use with an Electro-mechanical Driver Device,” U.S. patent application Ser. No. 09/510,927, entitled “Electro-mechanical Driver and Remote Surgical Instruments Attachment Having Computer Assisted Control Capabilities,” U.S. patent application Ser. No. 09/510,931, entitled “A Tissue Stapling Attachment for Use with an Electro-mechanical Driver Device,” U.S. patent application Ser. No. 09/510,932, entitled “A Fluid Delivery Mechanism for Use with Anastomosing, Stapling, and Resecting Instruments,” and U.S. patent application Ser. No. 09/510,933, entitled “A Fluid Delivery Device for Use with Anastomosing, Stapling, and Resecting Instruments,” each of which is expressly incorporated herein in its entirety by reference thereto.

[0051] According to a further example embodiment, flexible shaft **105** may include a tubular outer sheath, which may include a coating or other sealing arrangement to provide a fluid-tight seal between the interior channel thereof and the environment. The sheath may be formed of a tissue-compatible, sterilizable elastomeric material. The sheath may also be formed of a material that is autoclavable. An example embodiment of such a flexible shaft, is described, for example, in U.S. patent application Ser. No. 10/099,634, entitled “Electro-mechanical Surgical Device,” which is expressly incorporated herein in its entirety by reference thereto.

[0052] As illustrated in FIG. 1b, disposed within the interior channel **150** of the flexible shaft **105**, and extending along the length thereof, may be a first rotatable drive shaft **152**, a second rotatable drive shaft **154**, a first steering cable **156**, a second steering cable **158**, a third steering cable **160**, a fourth steering cable **162**, one or more data transfer cables **164**, and/or two leads **166** and **168**, all terminating at the second coupling **106**, at the distal end **109** of the flexible shaft **105**. The leads **166** and **168** may be provided to, for example, transmit current to and/or from an attached surgical instrument or attachment. The remote power console **102** may include a motor system, which includes one or more motors configured to rotate the first and second rotatable drive shafts **152**, **154** and to apply tension or otherwise drive the steering cables to thereby steer the distal end **109** of the flexible shaft **105**. An example embodiment of a motor arrangement is described, for example, in U.S. patent application Ser. No. 09/510,923, entitled “A Carriage Assembly For Controlling A Steering Wire Steering Mechanism Within A Flexible Shaft,” which is expressly incorporated herein in its entirety by reference thereto.

[0053] Referring to FIG. 1c, there is shown a top schematic view of a remote control unit (“RCU”) **130** for remotely controlling the electro-mechanical driver device **101** illustrated in FIG. 1a. The RCU **130** may be, for example, a wired remote control unit, a wireless remote control unit, a hybrid remote control unit, etc. The RCU **130** may include a number of operable control elements **300**, **312**, **314**, **320** and **346** which may be, for example, toggle switches, button switches, analog switches, control knobs, potentiometers, etc. The RCU **130** may also include indicators **108a'**, **108b'** and a display device **110'**. Although FIG. 1c illustrates five control

elements **300**, **312**, **314**, **320** and **346**, any appropriate number of control elements may be provided. In a further example embodiment of the present invention, RCU **130** may be configured to clamp onto the sheath of the flexible shaft **105**.

[0054] Referring to FIG. 1d, there is illustrated a perspective view of a further example embodiment of the surgical device according to the present invention. The surgical device **200** may be used in combination with the electro-mechanical driver device **101** illustrated in FIG. 1a. The surgical device **200** may also be used in combination with a manually-operable driver device.

[0055] The surgical device **200** according to the example embodiment includes a coupling **11** adapted and configured to detachably couple the surgical device **200** with the second coupling device **106** of the flexible shaft **105** of the driver device **101** illustrated in FIG. 1a. The couplings **11**, **106** may include a quick-connect type fitting, such as a rotary quick-connect type fitting, a bayonet type fitting, etc. The couplings **11** and **106** may also be threaded couplings. In an alternative example embodiment, the surgical device **200** is permanently connected to or integral with the driver device, electro-mechanical or manual, for example.

[0056] The surgical device **200** includes an upper jaw **4a** and a lower jaw **4b**. In the example embodiment illustrated in FIG. 1d, the lower jaw **4b** is connected to coupling **11**.

[0057] Electrodes **3a**, **3b** may be provided on an inner surface of lower jaw **4b**. In alternative example embodiments, electrodes may be provided on the upper jaw **4a**, or on both the upper jaw **4a** and the lower jaw **4b**. In this alternative example embodiment, the lower jaw **4b** may also include two rows of staples **201**, **202** and a cutting device **203**.

[0058] The surgical device **200** may also include sensors **205**, **206**. These sensors may be configured and arranged to, for example, sense the temperature of tissue disposed between jaws **4a** and **4b**. When coupled to the driver device **101** of FIG. 1a, for example, signals from the sensors **205**, **206** may be transmitted to the driver device, e.g., via data transfer cables.

[0059] The upper jaw **4a** illustrated in FIG. 1d may include pierceable ampullae **5**, which may contain fluid or matter to induce hemostasis. The fluid may include, for example, collagen, fibrin, etc. The use of other fluids or matters is, of course, possible. This fluid or matter, for example, collagen, fibrin, dye, matter configured to effect anastomosis, matter configured to seal tissue and matter configured to effect hemostasis, etc. may be released when the jaws **4a**, **4b** are closed and the electrodes **3a**, **3b** pass through the tissue and into the ampullae **5**, releasing the fluid or matter. Simultaneously, the electrodes **3a**, **3b** are activated and tissue may be coagulated to induce hemostasis. Sensors **205**, **206** monitor the amount of heat provided and duration of application. While the current passes between the electrodes **3a**, **3b**, a driver may advance to eject two rows of staples **201**, **202** on either side of the cutting device **203**. In a further example embodiment, the stapling mechanism includes a replaceable tray or cartridge of open staples set within the lower jaw **4b** and a set of corresponding staple guides within the upper jaw **4a**, such that when the surgical device **200** is in a closed position, the open staples are arranged to oppose the corresponding staple guides. The stapling mechanism may also include a wedge pushing system whereby once the linear clamping mechanism is in a closed position, a wedge arranged in a channel below the tray of open staples is pushed through the channel. As the wedge moves through the chan-

nel, a sloping surface of the wedge pushes the open staples against the corresponding staple guides, thereby closing the staples. After the staples have been closed, the wedge is pulled back through the channel. The second drive extension pushes or pulls the wedge through the channel, depending on the turning direction of the corresponding motor in the, for example, electro-mechanical driver device, by engaging a threaded horizontal shaft upon which the wedge, having a matching inner thread, rides. An example embodiment of such a stapling device is described, for example, in U.S. patent application Ser. No. 09/324,451, entitled "A Stapling Device For Use With An Electromechanical Driver Device For Use With Anastomosing, Stapling and Resecting Instruments," and in U.S. patent application Ser. No. 09/999,546, entitled "Surgical Device," each of which is expressly incorporated herein in its entirety by reference thereto.

[0060] In a further example embodiment of the present invention, the surgical device 200 includes a memory device 204. The memory device 204 may be, for example, a read-only memory, a programmable memory, a random access memory, etc. The memory device 204 may be configured and arranged to store, for example, a unique serial number of the surgical device 200, and/or a device type indication. The memory device 204 may also be configured and arranged to store counter data indicating how many times the surgical device 200 has been used. When coupled to the driver device 101 illustrated in FIG. 1a, for example, this memory device 204 may be read by the driver device 101, e.g., via a data transfer cable. In operation, the surgical device 200 is first connected to the electro-mechanical driver device 101 illustrated in FIG. 1a via coupling 11. A driver device may read the memory device 204 to determine, for example, the device type, so that the driver device may execute the movements of the surgical device 200 in a suitable fashion.

[0061] FIG. 1e is a schematic view of memory unit 204. As illustrated, data connector 742 includes contacts 744, each electrically and logically connected to memory unit 204 via a respective line 748. Memory unit 204 is configured to store, for example, a serial number data 715, an attachment type identifier (ID) data 725 and a usage data 735. Memory unit 204 may additionally store other data. Both the serial number data 715 and the ID data 725 may be configured as read-only data. In the example embodiment, serial number data 715 is data uniquely identifying the particular surgical instrument or attachment, whereas the ID data 725 is data identifying the type of the attachment, such as, for example, a bipolar surgical device, an ultrasonic surgical device, a circular surgical stapler attachment, a linear surgical stapler attachment, etc. The usage data 735 represents usage of the particular attachment, such as, for example, the number of times that jaws 4a, 4b of surgical device 200 have been actuated.

[0062] Each type of surgical instrument or attachment attachable to the distal end 109 of the flexible shaft 105 may be designed and configured to be used a single time or multiple times. The surgical instrument or attachment may also be designed and configured to be used a predetermined number of times. Accordingly, the usage data 735 may be used to determine whether the surgical instrument or attachment has been used and whether the number of uses has exceeded the maximum number of permitted uses. In a further example embodiment, an attempt to use a surgical instrument or attachment after the maximum number of permitted uses has been reached may generate an ERROR condition.

[0063] A controller within the electro-mechanical device 101, for example, as illustrated in FIG. 1a, may be configured to execute an operating program or algorithm based on the read ID data 725. Such a controller is described, for example, in U.S. patent application Ser. No. 09/723,715, entitled "Electro-Mechanical Surgical Device" and U.S. patent application Ser. No. 09/836,781 entitled "Electro-Mechanical Surgical Device," each of which is expressly incorporated herein in its entirety by reference thereto. The remote power console 102, for example, as illustrated in FIG. 1a, may include a memory unit which may be configured to store the operating programs or algorithms for each available type of surgical instrument or attachment, the controller selects and/or reads the operating program or algorithm from the memory unit in accordance with the ID data 725 read from the memory unit 204 of an attached surgical instrument or attachment. The operating programs or algorithms stored in the memory unit may be updated, added, deleted, improved or otherwise revised as necessary. In a further example embodiment, the serial number data 715 and/or usage data 735 may also be used to determine which of a plurality of operating programs or algorithms is read or selected from the memory unit. In a further example embodiment, the operating program or algorithm may alternatively be stored in the memory unit 204 of the surgical instrument or attachment and transferred to the controller via the data transfer cables 164. Once the appropriate operating program or algorithm is read or selected by, or transmitted to, the controller, the controller may cause the operating program or algorithm to be executed in accordance with operations performed by the user, e.g., via the RCU 130. The controller may be electrically and logically connected with one or more motors arranged in the remote power console 102, for example, as illustrated in FIG. 1a, and may be configured to control these motors in accordance with the read, selected or transmitted operating program or algorithm.

[0064] According to a further example embodiment of the present invention, surgical device 200 includes a system configured to open and close the jaws 4a, 4b relative to one another, and a system configured to drive the staples 201, 202 and to drive the cutting device 203. Examples of such systems are described in detail in U.S. patent application Ser. No. 09/324,421, entitled "Electromechanical Driver Device For Use With Anastomosing, Stapling and Resecting Instruments," U.S. patent application Ser. No. 09/324,451, entitled "A Stapling Device For Use With An Electromechanical Driver Device With Anastomosing, Stapling, and Resecting Instruments," U.S. patent application Ser. No. 09/351,534, entitled "Expanding Parallel Jaw Device For Use With An Electromechanical Driver Device," each of which is expressly incorporated herein in its entirety by reference thereto.

[0065] FIG. 1f is an end view of an example embodiment of coupling 107 illustrated in FIG. 1a. The coupling 107 includes a first connector 444, a second connector 448, a third connector 452 and a fourth connector 456, each rotatably secured to the coupling 107. Each of the connectors 444, 448, 452 and 456 includes a respective recess 446, 450, 454 and 458. As illustrated in FIG. 1f, each recess 446, 450, 454 and 458 may be hexagonally shaped. It should be appreciated, however, that the recesses 446, 450, 454 and 458 may have any shape and configuration to non-rotatably couple and rigidly attach the connectors 444, 448, 452, 456 to respective drive shafts of a motor arrangement contained within driver device 101 illustrated in FIG. 1a. Complementary projections

may be provided on respective drive shafts of the motor arrangement to thereby drive the drive elements of the flexible shaft **105**. It should also be appreciated that the recesses may be provided on the drive shafts and complementary projections may be provided on the connectors **444**, **448**, **452**, **456**. Any other coupling arrangement configured to non-rotatably and releasably couple the connectors **444**, **448**, **452**, **456** and the drive shafts of the motor arrangement may be provided. Coupling **107** also includes contacts **500**, **501** configured to transfer additional voltage from the remote power console **102** through flexible shaft **105**.

[0066] One of the connectors **444**, **448**, **452**, **456** is non-rotatably secured to the first drive shaft **152**, and another one of the connectors **444**, **448**, **452**, **456** is non-rotatably secured to the second drive shaft **154**. The remaining two of the connectors engage with transmission elements configured to apply tensile forces on the steering cables **156**, **158**, **160** and **162** to thereby steer the distal end **109** of the flexible shaft **205**. The data transfer cable **164** is electrically and logically connected with data connector **460**. Data connector **460** includes, for example, electrical contacts **462**, corresponding to and equal in number to the number of individual wires contained in the data cable **164**. First coupling **422** includes a key structure **442** to properly orient the first coupling **422** to a mating and complementary coupling arrangement disposed on the housing **104**. Such key structure **442** may be provided on either one, or both, of the first coupling **422** and the mating and complementary coupling arrangement disposed on the housing **104**. First coupling **422** may include a quick-connect type connector, which may be configured, for example, so that a simple pushing motion engages the first coupling **422** to the housing **104**. Seals may be provided in conjunction with any of the several connectors to provide a fluid-tight seal between the interior of first coupling **422** and the environment.

[0067] FIG. 1g is a front end view of the second coupling **106** of flexible shaft **105**. Second coupling **106** includes a first connector **660** and a second connector **680**, each rotatably secured to the second coupling **106** and each non-rotatably secured to a distal end of a respective one of the first and second drive shafts **152**, **154**. A quick-connect type fitting **645** is provided on the second coupling **106** to detachably secure a surgical instrument or attachment thereto. The quick-connect type fitting **645** may include, for example, a rotary quick-connect type fitting, a bayonet type fitting, etc. A key structure **740** is provided on the second coupling **106** to properly align the surgical instrument or attachment to the second coupling **106**. The key structure or other arrangement to properly align the surgical instrument or attachment to the flexible shaft **105** may be provided on either one, or both, of the second coupling **106** and the surgical instrument or attachment. In addition, the quick-connect type fitting may be provided on the surgical instrument or attachment. A data connector **700**, having electrical contacts **720**, is also provided in the second coupling **106**. Like the data connector **60** of first coupling **422**, the data connector **700** of second coupling **106** includes contacts **720** electrically and logically connected to the respective wires of data transfer cable **164** and contacts **462** of data connector **460**. Seals may be provided in conjunction with the connectors **660**, **680**, **700** to provide a fluid-tight seal between the interior of second coupling **106** and the environment. In a further example embodiment, electrical contacts **620**, **640** receive any additional voltage that may be sent from the remote power console **102** to the surgical instrument or

device. In a further example embodiment, the surgical instrument or device may use the additional voltage provided by electrical contacts **620**, **640** to charge electrodes that may be included within the surgical instrument or device.

[0068] FIG. 1h illustrates an example embodiment of a wireless RCU **130** which provides the user with controls for the electro-mechanical device **101** and the surgical device **200**. Wireless RCU **130** includes a steering engage/disengage switch **312**, the operation of which controls the operation of one or more motors in order to selectively engage and disengage the steering mechanism. Wireless RCU **130** also may include a two-way rocker **314** having first and second switches **316**, **318** operable thereby. The operation of these switches **316**, **318** controls certain functions of the electro-mechanical surgical device **101** and any surgical instrument or attachment attached to the flexible shaft **105** in accordance with the operating program or algorithm corresponding to the attached surgical instrument or attachment, if any. For example, operation of the two-way rocker **314** may control the advancement and retraction of the flexible shaft **105**. Wireless RCU **130** is provided with yet another switch **320**, the operation of which may further control the operation of the electro-mechanical surgical device **101** and any surgical instrument or attachment attached to the flexible shaft **20** in accordance with the operating program or algorithm corresponding to the attached surgical instrument or attachment, if any. For example, when the surgical device **200** is attached to the flexible shaft **105**, operation of the switch **320** may initiate the advancement of staples into tissue between jaws **4a**, **4b**.

[0069] Wireless RCU **130** may also include a controller **322**, which is electrically and logically connected with the switches **302**, **304**, **306**, **308** via line **324**, with the switches **316**, **318** via line **326**, with switch **312** via line **328** and with switch **320** via line **330**. Wireless RCU **130** may include indicators **108a'**, **108b'**, corresponding to the indicators **108a**, **108b** of front panel **103**, and a display device **110'**, corresponding to the display device **110** of the front panel **103**. If provided, the indicators **108a'**, **108b'** are electrically and logically connected to controller **322** via respective lines **332**, **334**, and the display device **110'** is electrically and logically connected to controller **322** via line **336**. Controller **322** is electrically and logically connected to a transceiver **338** via line **340**, and transceiver **338** is electrically and logically connected to a receiver/transmitter **342** via line **344**. A power supply, for example, a battery, may be provided in wireless RCU **130** to power the same. Thus, the wireless RCU **130** may be used to control the operation of the electro-mechanical surgical device **101** and any surgical instrument or attachment attached to the flexible shaft **105** via wireless link **160**.

[0070] Wireless RCU **130** may include a switch **346** connected to controller **322** via line **348**. Operation of switch **346** transmits a data signal to the transmitter/receiver **146** of the remote power console **102**, for example as illustrated in FIG. 1a, via wireless link **160**. The data signal may include, for example, identification data uniquely identifying the wireless RCU **130**. This identification data may be used by a controller within the electro-mechanical surgical or driver device **101** to prevent unauthorized operation of the electro-mechanical driver device **101** and to prevent interference with the operation of the electro-mechanical driver device **101** by another wireless RCU. Each subsequent communication between the wireless RCU **130** and the electro-mechanical driver device **101** may include the identification data. Thus, the controller may discriminate between wireless RCUs and thereby allow

only a single, identifiable wireless RCU 130 to control the operation of the electro-mechanical driver device 101 and any surgical instrument or attachment attached to the flexible shaft 105. In another example embodiment, RCU 130 is connected to remote power console 102, for example, as illustrated in FIG. 1a, via wires or an optical connection.

[0071] FIGS. 2a to 2e illustrates further example embodiments of a surgical device 200' having expandable jaws that remain parallel. In such example embodiments, surgical device 200' includes a parallel separable jaw system that has a lower jaw 40b and an upper jaw 40a having a proximal end 220.

[0072] Referring to FIGS. 2c, 2d and 2e, the proximal end 220 of the upper jaw 40a has a pair of threaded vertical bores 225, through which extend a corresponding pair of vertical shafts 227. Inner threads 226 of the vertical bores 225 match outer threads 228 of the vertical shafts 227. The vertical shafts 227 engage a threaded upper horizontal shaft 235 at a distal end 240 of the upper horizontal shaft 235. Outer threads 237 of the upper horizontal shaft 235 interlock with the outer threads 228 of the vertical shafts 227. The upper horizontal shaft 235 has at a proximal end 242, an upper drive socket 244.

[0073] The example embodiments of the surgical device 200' as illustrated in FIGS. 2a to 2e attaches to coupling 106 of the electro-mechanical driver device 101 such that an upper drive socket 244 and a lower drive socket 272, illustrated in FIG. 2e, engages the flexible shaft 105 at the distal end 109. Thus, rotation of the upper horizontal shaft 235 is effected by rotation of the upper drive socket 244 which is effected by rotation of the corresponding flexible drive shaft of flexible shaft 105. Clockwise or counter-clockwise rotation is achieved depending on the direction of the corresponding motor within the remote power console 102. Similarly, rotation of the lower horizontal shaft 287 is effected by rotation of the lower drive socket 272 which is effected by rotation of the corresponding flexible drive shaft of flexible shaft 105. Also, the clockwise or counter-clockwise rotation of the lower horizontal shaft 287 is achieved depending on the direction of the corresponding motor within remote power console 102. Surgical device 200' also includes contact nodes 254', 256' which transfer additional voltage to surgical device 200'.

[0074] As illustrated in FIGS. 2c and 2d, the surgical device 200' further includes a first sensor electrode 250 configured to electrically communicate via communication wires with a first contact pad 251, which is configured to electrically communicate with a second contact pad via direct contact, which is configured to electrically communicate via communications wires with a first contact node 254, as illustrated in FIGS. 2c and 2d. Similarly, the surgical device 200' further includes a second sensor electrode 252 configured to electrically communicate via communication wires with a second contact node 256. The contact nodes 254, 256 are configured to electrically communicate with communication wires in the electro-mechanical driver device 101 to form a sensor circuit, such that when the upper jaw 40a and the lower jaw 40b are clamped together, the sensor electrodes 250, 252 are in contact, the sensor circuit is closed, and the surgeon is alerted via other circuit components to the clamped position of the jaws 40a, 40b, and is therefore informed that it is safe and/or appropriate to active the stapling mechanism.

[0075] The example embodiment illustrated may include a wedge pushing system within lower jaw 40b. FIGS. 2c and 2d show the wedge pushing system including a replaceable tray

or cartridge 275 housing one or more fastening staples, and an upper jaw 40a one or more staple guides 284 corresponding to the staples 280. Each of the staples 280 has a butt 282 protruding below the tray 275 and a pair of prongs 284 extending to the top of the tray 275. The wedge pushing system further includes a wedge guide, or channel 286, illustrated in FIG. 2e, extending beneath the tray 275. Within the channel 286 extends a threaded lower horizontal shaft 287 having outer threads 288. Upon the lower horizontal shaft 287 is arranged a wedge 289 having a sloped top face 290, a horizontal threaded bore 292 coaxial with the channel 286, having inner threads 293 matching the outer threads 288 of the lower horizontal threaded shaft 287, and an upwardly extending cutting member 277.

[0076] FIGS. 2f to 2k illustrate various electrode and/or stapling mechanism configurations associated with the surgical device 200' illustrated in FIGS. 2a to 2e. FIGS. 2f is a side view of the jaws 40a, 40b. As illustrated in FIG. 2f, the surgical device 200' includes electrodes 30 disposed over lower jaw 40b, a pierceable ampullae 32c, which may be similar to pierceable ampullae 5 described above, and sensors 250, 252. Electrodes 30 protrude from the lower jaw 40b and are applied to and may pierce tissue placed between the jaws in order to anastomose the tissue. Accordingly, the electrodes 30 may be rigid and conductive in regard to the material used for their construction. The electrodes 30 may also have features that may enhance tissue penetrating attributes and electrical contact between any opposing electrodes. Various configurations may be provided to enhance contact with tissue where electrode height, width and density of spacing are adjusted in order to accommodate various tissue thickness and texture. The electrodes 30 are charged through voltage sent from remote power console 102 through leads 166, 168 of flexible shaft 105. Contact nodes 254', 256' electrically connect to electrical contacts 620, 640 of coupling 106 and current flows through to electrodes 30. As described above, electrical contacts 620, 640 are electrically connected to leads 166, 168 of the flexible shaft 105. Sensors 250, 252 monitor the amount of heat generated by the charging of electrodes 30 and duration of application. Sensors 250, 252 transfer signals to the remote power console 102 which provides the user with information regarding current conditions related to the operation of the surgical device 200'.

[0077] FIG. 2g illustrates the electrodes 30 used in conjunction the wedge pushing system as described above. In this example embodiment, the wedge pushing system is similar the wedge pushing system as described with reference to FIGS. 2e to 2d. The wedge pushing system is operated in conjunction with the electrodes 30 in order to coagulate and/or anastomose tissue between the parallel jaws 40a, 40b.

[0078] FIG. 2h illustrates an electrode configuration of another example embodiment of the present invention. As illustrated electrodes 30 are disposed over the inner face of the lower jaw 40b. The electrodes 30 are charged positively and receptacles 20 are negatively charged (ground) and configured for alignment with electrodes 30. This configuration induces current to flow from lower jaw 40b to the upper jaw 40a when the jaws 40a, 40b are closed. The amount of RF energy transferred between jaws 40a, 40b may be varied depending upon whether staples are used in conjunction with the electrodes, as illustrated in FIG. 2i, or if the anastomose is performed solely through the use of the electrode configuration. In an example embodiment, the electrodes 30 and receptacles 20 electrically communicate with the remote power

console 102 through contact nodes 254', 256' as described above in reference to FIGS. 2f and 2g. As described above with reference to FIG. 2g, FIG. 2i illustrates the electrode configuration illustrated in FIG. 2h used in conjunction with the wedge pushing system which provides a stapling mechanism.

[0079] FIG. 2j illustrates yet another example embodiment of the present invention is illustrated. The electrode configuration illustrated in FIG. 2j provides ultrasonic energy which is transmitted through ultrasonic resonator pins 27 which are configured on the inner surface of the lower jaw 4b. Similar to the electrode configurations described above, the ultrasonic pins 27 may be configured in various formations conducive to the type and form of the tissue which is placed between the jaws for coagulation, anastomosing and/or cutting. In addition to the ultrasonic resonator pins 27, the lower jaw 4b also includes an ultrasonic transducer 25. The ultrasonic transducer 25 generates the ultrasonic energy that resonates through the pins 27. The ultrasonic resonator pins 27 may be used with or without staples, as described with regard to the electrode configurations above, enable the reduction of the number of staples used or the elimination thereof and lessen the mechanical force needed in order to complete coagulation and cutting. The ultrasonic energy use in this example embodiment may be transmitted through contact nodes 254', 256' as described in the foregoing example embodiments.

[0080] FIG. 2k illustrates yet another example embodiment of the present invention in which electrodes 29 are configured as surgical barbs. The configuration of electrodes 29 provide for an improved configuration for penetrating tissue. The electrodes 29 may follow the polarity schemes described above in order apply RF energy to the tissue. The electrodes 29 may be used as illustrated with electrodes arranged on the lower jaw 40b only. However this surgical barb type electrode may also be arranged on the inner surface of the upper jaw 40a in order to provide even more effective penetrating results. Furthermore, as described above with reference to FIG. 2f, a pierceable ampulla 32c may be incorporated in the upper jaw 40a and used to induce hemostasis. The electrodes 29 receive the RF energy through contact nodes 254', 256' as described in the foregoing example embodiments.

[0081] FIG. 3a is a view of an example electrode/staple configuration which may be disposed on the inner surface of lower jaw 4a or lower jaw 40a. As illustrated, in this example embodiment, this configuration includes two rows of electrodes 30a, 30b, two rows of staples 32a, 32b and a cutting device 34. The cutting device 34 is between the rows of staples 32a, 32b, and electrodes 30a, 30b is outside of the rows of staples 32a, 32b. The polarities 36 associated with the respective electrodes are indicated to the left of electrodes 30a. In this example embodiment, the polarities 36 of the electrodes alternate between positive ("+") and negative ("-") along the vertical row of electrodes. In operation, the RF energy applied to the electrodes corresponds the polarities as indicated. The alternating polarities allow for current to pass from one electrode to another where the current travels parallel to the electrode members 30a, 30b. In an alternative example embodiment, each row of electrodes may be either all positive or all negative. In this example embodiment, corresponding contacts of opposite polarity may be provided on the upper jaw 4b.

[0082] FIG. 3b illustrates the electrode and staple configuration of FIG. 3a on the lower jaw 40b. The example embodiment illustrated in FIG. 3b includes the rows of electrodes 30a

and 30b which during operation receive their charge via current supplied through leads 166, 168 of flexible shaft 105 from the remote power console 102, as described above. The polarities associated with the rows of electrodes 30a, 30b may vary as described above and illustrated in FIG. 3a. In one example embodiment, the user controls the movement of flexible shaft 105, the actuation of jaws, the movement of staples and the polarities and charge associated with the electrodes by using RCU 130 in conjunction with remote power console 102.

[0083] The configuration illustrated in FIG. 3a may be placed on the inner surface of the lower jaw 4b, 40b or disposed on both jaws of surgical device 200. The electrodes 30a, 30b provided may be bipolar and may be arranged in various configurations which create either alternating or opposing polarities as explained below in the various example embodiments described. In operation, the present invention may be used with one row of staples or no staples to enable the closure of tissue.

[0084] If the configuration illustrated in FIG. 3a is used on the inner surfaces of both jaws 4a, 4b, the polarities of electrodes may be the same for both jaws 4a, 4b which may allow current to flow parallel to the respective columns of electrodes. Alternatively, the polarities of the electrodes may be switch between the jaws 4a, 4b, where opposite polarities may exist for the respective corresponding electrode columns between the jaws 4a, 4b which may allow current to flow between jaws 4a, 4b once they are in a closed position.

[0085] Another example embodiment is illustrated in FIG. 3c, in which two rows of electrodes 30a and 30b are illustrated without any staples or stapling configuration. The example embodiment illustrated in FIG. 3c solely involves the use of electrodes which may induce an appropriate level of heat in order to coagulate tissue during operation. FIG. 3d illustrates an alternative electrode configuration. The electrodes are arranged with two electrode rows on each side of cutting device 34. FIG. 3e illustrates the dual row of electrode configuration 30a, 30b on the inner surface of lower jaw 40b.

[0086] In another example embodiment of the present invention, staple lines may be removed from the electrode configuration as illustrated in FIGS. 3c and 3d. FIG. 3d illustrates four rows of electrodes 30a, 30b where two columns are placed on each side of the cutting device 34. The electrodes may have alternating polarities of RF energy applied in order to produce a current flow. Polarities may alternate vertically, or an entire column of electrodes may be positively charged and the respective adjacent column may be negatively charged in order to induce current flow between the two columns on each respective side of cutting device 34. As described with the electrode configuration illustrated in FIG. 3a, the electrode configurations illustrated in FIGS. 3c and 3d may be placed on both inner surfaces of jaws 4a, 4b. Also, the upper jaw 4a may incorporate pierceable ampulla and function, as described above, with electrodes 30 as illustrated in FIG. 2f. In the example embodiments, described above, electrodes configured to pierce tissue are illustrated. Of course, it is also possible to use surface-type electrodes to perform coagulation and/or anastomosing.

[0087] FIGS. 4a and 4b illustrate two alternative example embodiments of surgical device 200 according to the present invention. The first example embodiment, illustrated in FIG. 4a, includes a separating jaw system including a lower jaw 4b, an upper jaw 4a and a coupling 11. Coupling 11 includes two hexagonal shaped sockets 556a, 556b into which coupling

106 of flexible shaft 105 fits. Each of the sockets is formed in the end of a corresponding horizontal turning shaft 558a, 558b.

[0088] The upper horizontal turning shaft 558a is coupled, by a transverse gearing member, to a threaded vertical shaft 560 which extends through a correspondingly threaded bore 562 of the upper jaw 4a. The upper jaw 4a has a linear track coupling means 566 which corresponds and couples to a linear track 568 formed in the side of the interface end member 554 which is opposite the driver coupling sockets 556a, 556b. Subsequent turning of the upper horizontal turning shaft 558a causes the vertical turning shaft 560 to turn. As this shaft 560 turns, the upper jaw 4a rides up and down within the track of the end member 554.

[0089] The lower horizontal turning shaft 558b extends axially through the lower jaw 4b, which, in turn is fixed to the proximal end member 554. Mounted around this axially extending shaft 558b is a wedge driver mechanism 566 which includes a threaded bore. This threaded member 566 is locked within a track 567, which prevents the member 566 from rotating when the shaft 558b turns. Rather, the wedge member 566 rides linearly along the track 567 and along the threading of the shaft 558b. Mounted within a recess 568 in the face of the lower jaw 4b which opposes the upper jaw 4a directly above the wedge member 566 is a replaceable tray of staples. The wedge driver has a sloped frontal surface 572 which contacts the staples 282 and causes it to be driven upwardly. When the upper jaw 4a is in close proximity to the lower jaw 4b, the staples are closed when they contact the opposing face of the upper jaw 4a by the action of staple closing guide recesses 576 formed therein.

[0090] At the distal tip of the upper and lower jaws are two opposing magnetic sensors 578a, 578b, each coupled to a circuit component which connects to the electro-mechanical driver 102 via flexible shaft 105. When the jaws come together, the circuit is closed, and indicators 108a and 108b provide a signal indicating that the staples may be safely fired.

[0091] Referring now FIG. 4b, another example embodiment of the surgical device 200 of the present invention is described. In the example embodiment, the coupling 11 is substantially equivalent to the first example embodiment. As before, the shafts of the driver component turn rotating members within the attachment. In this example embodiment however, both turning members 558a, 558b are horizontal. Mounted to the shaft interfacing member is a fixed lower jaw 4b and a moving upper jaw 4a. In this example embodiment, the upper jaw 4a is mounted to the lower jaw 4b by a spring loaded pivot, which biases the upper jaw 4a into an open disposition relative to the lower jaw 4b. Mounted to the upper turning shaft however, is a linearly tracked cuff 587 which seats around the upper and lower jaw, the advancement of which causes the jaws to come together. The lower jaw includes the same staple 574 tray recess and linearly driven threaded wedge staple pushing mechanism 566. Also, the electromagnetic sensor and circuit of the first example embodiment is included to indicate to the surgeon when the section of tissue has been fully clamped and the staples should be driven.

[0092] More particularly, after the surgeon has resected the diseased portion of the tissue, the end of the tissue is placed between the jaws of the attachment. By actuating a trigger and driving the upper shaft, the cuff member 587 advances axially along the outside of the upper and lower jaws 4a, 4b, thus closing the upper jaw onto the tissue and lower jaw. Once

fully closed, the electromagnetic sensor circuit indicates to the surgeon operator that the staples may be fired, and correspondingly, actuation of the second trigger causes the wedge driver to advance and drive the staples through the tissue section. Reverse rotation of the motor for the upper turning shaft causes the cuff to retract and the upper jaw to open, thus releasing the now-sealed tissue end.

[0093] The surgical device 200 as illustrated in FIGS. 4a and 4b may also include electrodes used either in conjunction with the stapling mechanism or alone. FIG. 4b illustrates a row of electrodes 30 disposed along the lower jaw 4b. The electrodes 30 may receive RF energy through contacts 553, 555, similar to the energy transfer to the electrodes of the surgical device 200' as described above. Furthermore, the example embodiments illustrated in FIGS. 4a and 4b may include pierceable ampullae as described above with reference to FIGS. 1d and 2f. The surgical device 200 as illustrated in FIGS. 4a and 4b, may incorporate the various electrode and/or stapling configurations described above with reference to FIGS. 3a to 3e.

[0094] FIG. 5a is a perspective view of the present invention. Upper jaw 4a and lower jaw 4b are attached to a shaft 11 which connects to an electro-mechanical device 6. In operation, these jaws 4a, 4b are closed in order to coagulate and cut tissue positioned between them. As illustrated, the jaws 4a, 4b are attached to a first end of shaft 11 wherein the second end of shaft 11 connects to the electro-mechanical device 6. The electro-mechanical device 6 controls the movement of shaft 11 and jaws 4a, 4b. The shaft 11 may be flexible or rigid and may enable the mechanical actuation of the jaws 4a, 4b. The jaws 4a, 4b may include electrode members 3a, 3b on the inner surface of lower jaw 4b, or the electrode members 3a, 3b may be provided on both jaws 4a and 4b. The electrode members 3a, 3b provided on the lower jaw 4b may be bipolar and may be arranged in various configurations which create either alternating or opposing polarities. In operation, the present invention may be used with one row of staples or no staples to enable the closure of tissue. The jaws 4a, 4b mechanically and electrically accomplish the desired functions, i.e., cutting and coagulating tissue.

[0095] The second end of the shaft 11, illustrated in FIG. 5a, connects to electro-mechanical device 6, illustrated in FIG. 5b, at a shaft connection 7. The shaft 11 includes cables which transmit signals that control the movement of the DLU and the actuation of jaws 4a, 4b.

[0096] FIG. 5b illustrates other components of front panel 9, including a display device 8 and indicators 10a, 10b which provide positioning information to the user.

[0097] FIG. 6 illustrates an electrode configuration according to the present invention. This electrode configuration may be provided on the inner surface of lower jaw 4b or on both jaws 4a, 4b. The inner surface of lower jaw 4b includes two columns of electrode members 3a, 3b, two staple lines 2a, 2b and a cutting blade 12. The cutting blade 12 is between the staple lines 2a, 2b and electrode members 3a, 3b is outside of the staple lines 2a, 2b. The polarities associated with the respective electrodes are indicated to the left of electrode members 3a. The polarities of the electrodes alternate between + and - along the vertical column of electrodes. In operation, the RF energy applied to the electrodes corresponds the polarities as indicated. The alternating polarities allow for current to pass from one electrode to another where the current travels parallel to the electrode members 3a, 3b.

[0098] The upper jaw **4a** may incorporate pierceable ampulla **5**, shown in FIG. **5a**, which may contain fluid for hemostasis. This fluid or matter, e.g., collagen, fibrin, dye, matter configured to effect anastomosis, matter configured to seal tissue and matter configured to effect hemostasis, etc., may be released when the jaws **4a**, **4b** are closed and the electrode members **3a**, **3b** pass through the tissue and into the ampulla **5** thus releasing the fluid. Simultaneously, the electrode members **3a**, **3b** are activated and tissue may be coagulated to induce hemostasis. Sensors may be configured and arranged to monitor the amount of heat provided and duration of application. In another example embodiment, while the current is passing between the electrode members **3a**, **3b**, a driver may advance to form two single rows of staples **2a**, **2b** on either side of the cutting blade **12**. In each of these example embodiments, the stapling mechanism includes a replaceable tray of open staples set within the lower jaw **4b** and a set of corresponding staple guides within the upper jaw **4a**, such that when the linear clamping mechanism is in a closed position, the open staples immediately oppose the corresponding staple guides. The stapling mechanism further includes a wedge pushing system whereby once the linear clamping mechanism is in a closed position, a wedge riding in a channel below the tray of open staples is pushed through the channel. As the wedge moves through the channel, a sloping surface of the wedge pushes the open staples against the corresponding staple guides, thereby closing the staples. After the staples have been closed, the wedge is pulled back through the channel. The second drive extension pushes or pulls the wedge through the channel, depending on the turning direction of the corresponding motor in the electro-mechanical driver, by engaging a threaded horizontal shaft upon which the wedge, having a matching inner thread, rides.

[0099] If the configuration illustrated in FIG. **6** is provided on the inner surfaces of both jaws **4a**, **4b**, the polarities of electrode members may be the same for both jaws **4a**, **4b** which may allow current to flow parallel to the respective columns of electrodes. Alternatively, the polarities of the electrode members may be switch between the jaws **4a**, **4b**, where opposite polarities would exist for the respective corresponding electrode columns between the jaws **4a**, **4b** which would allow current to flow between jaws **4a**, **4b** once they are in a closed position.

[0100] In another example embodiment of the present invention, staple lines may be removed from the electrode configuration as illustrated in FIG. **7**. FIG. **7** illustrated four rows of electrode members **3a**, **3b**, including two columns are placed on each side of the cutting blade **12**. The electrode members may have alternating polarities of RF energy applied in order to produce a current flow. Polarities may alternate vertically or an entire column of electrodes may be positively charged and the respective adjacent column may be negatively charged in order to induce current flow between the two columns on each respective side of cutting blade **12**. As described with reference to the electrode configuration illustrated in FIG. **6**, the electrode configuration illustrated in FIG. **7** may be placed on both inner surfaces of jaws **4a**, **4b**. Also, the upper jaw **4a** may incorporate pierceable ampulla and function, as described above, with electrode members **3a**, **3b** as illustrated in FIG. **7**.

[0101] FIG. **8** is a side view of the jaws **4a**, **4b**. The electrode members **3** protrude from the lower jaw **4b** and are applied to tissue placed between the jaws in order to perform anastomosing, sealing and/or stapling. Accordingly, the elec-

trodes may be rigid, flexible, elastic, inelastic, planar, non-planar, etc., with regard to the material used for their construction. The electrode members **3** may also have features that may enhance tissue penetrating attributes and electrical contact between any opposing electrodes. Various configurations may be employed to enhance contact with tissue where electrode height, width and density of spacing are adjusted in order to accommodate various tissue thickness and texture.

[0102] FIG. **9** illustrates an electrode configuration of another example embodiment of the present invention. As illustrated electrode members **15** are disposed over the inner face of the lower jaw **4b**. The electrodes **15** are charged positively and receptacles **20** are negatively charged (ground) and configured to align with electrodes **15**. This configuration induces current to flow from lower jaw **4b** to the upper jaw **4a** when the jaws **4a**, **4b** are closed. The amount of RF energy transferred between jaws **4a**, **4b** may be varied depending upon whether staples are used in conjunction with the electrodes or if the anastomose is performed solely through the use of the electrode configuration.

[0103] FIG. **10** illustrates another example embodiment of the present invention. The electrode configuration illustrated in FIG. **10** provides ultrasonic levels of energy which are transmitted through ultrasonic resonator pins **27** which are configured on the inner surface of the lower jaw **4b**. Similar to the electrodes described above, the ultrasonic pins **27** may be configured in various formations conducive to the type and form of the tissue which is placed between the jaws for coagulation, anastomosing and/or cutting. In addition to the ultrasonic resonator pins **27**, the lower jaw **4b** also includes an ultrasonic transducer **25**. The ultrasonic transducer **25** is configured to generate the ultrasonic energy that resonates through the pins **27**. The ultrasonic resonator pins **27** may be used with or without staples and as described above with reference to the electrode configurations, enable the reduction of the number of staples used and lessen the mechanical force necessary in order to complete coagulation and cutting.

[0104] FIG. **11** illustrates another example embodiment of the present invention. The electrodes **29** are configured as surgical barbs. The configuration of electrodes **29** provide for an improved configuration for penetrating tissue. The electrodes **29** may follow the polarity schemes described above in order to apply RF energy to the tissue. The electrodes **29** may be used as illustrated with electrodes arranged on the lower jaw **4b** only, however this surgical barb type electrode may be arranged on the inner surface of the upper jaw **4a** in order to provide even more effective penetrating results. Furthermore, as described above, pierceable ampulla **5** may be provided in the upper jaw **4a** and used to induce hemostasis.

[0105] Those skilled in the art will appreciate that numerous modifications of the example embodiment described hereinabove may be made without departing from the spirit and scope of the invention. Although example embodiments and/or example methods of the present invention have been described and disclosed in detail herein, it should be understood that this invention is in no sense limited thereby and that its scope is to be determined by that of the appended claims.

1. An electro-mechanical surgical device, comprising:
 - a first jaw;
 - a second jaw opposing the first jaw, the first jaw and the second jaw configured to clamp tissue therebetween;
 - a plurality of ultrasonic resonator pins arranged on at least one of the first jaw and the second jaw; and

an ultrasonic transducer configured to supply ultrasonic energy to the plurality of ultrasonic resonator pins.

2. The electro-mechanical surgical device according to claim 1, further comprising at least one sensor configured to sense temperature of the tissue.

3. The electro-mechanical surgical device according to claim 2, wherein the sensor is configured to transmit a signal to indicate the temperature of the tissue.

4. The electro-mechanical surgical device according to claim 1, wherein at least one of the upper jaw and the lower jaw includes at least one pierceable ampulla containing matter, the ampulla configured to release the matter when the first jaw and the second jaw are in a closed position and the at least one pin passes through the tissue clamped between the first jaw and the second jaw into the at least one pierceable ampulla.

5. The electro-mechanical surgical device according to claim 4, wherein the matter includes at least one of collagen, fibrin, dye, matter configured to effect anastomosis, matter configured to seal tissue and matter configured to effect hemostasis.

6-7. (canceled)

8. The electro-mechanical surgical device according to claim 1, wherein at least one of height, width and density of spacing of the resonator pins is adjustable,

9. An electro-mechanical surgical system, comprising:

a surgical instrument including:

a first jaw,

a second jaw opposing the first jaw, the first jaw and second jaw configured to clamp tissue therebetween, and

a plurality of ultrasonic resonator pins arranged on at least one of the first jaw and the second jaw;

an ultrasonic transducer configured to supply ultrasonic energy to the plurality of ultrasonic resonator pins; and an elongated shaft having a distal end configured to detachably couple with surgical instrument.

10-11. (canceled)

12. The electro-mechanical surgical system according to claim 9, further comprising at least one sensor configured to sense temperature of the tissue clamped between the first jaw and the second jaw.

13. The electro-mechanical surgical system according to claim 12, wherein the sensor is configured to transmit a signal to indicate the temperature of the tissue.

14. The electro-mechanical surgical system according to claim 9, wherein at least one of the first jaw and the second jaw include at least one pierceable ampulla containing matter, the ampulla configured to release the matter when the first jaw and the second jaw are in a closed position and at least one pin passes through the tissue clamped between the first jaw and the second jaw into the at least one pierceable ampulla.

15. The electro-mechanical surgical system according to claim 14, wherein the matter includes at least one of collagen, fibrin, dye, matter configured to effect anastomosis, matter configured to seal tissue and matter configured to effect hemostasis.

16. The electro-mechanical surgical system according to claim 9, wherein the elongated shaft is configured to detachably couple with the surgical instrument via at least one of a rotary quick-connect fitting, a bayonet fitting, a threaded coupling, a permanent coupling and an integral connector.

17. The electro-mechanical surgical system according to claim 9, wherein at least one of height, width and density of spacing of the resonator pins is adjustable.

18-26. (canceled)

27. An electro-mechanical surgical device, comprising:

a first jaw;

a second jaw opposing the first jaw, the first jaw and the second jaw configured to clamp tissue therebetween;

a plurality of ultrasonic resonator pins arranged on at least one of the first jaw and the second jaw;

an ultrasonic transducer configured to supply ultrasonic energy to the plurality of ultrasonic resonator pins; and

a stapling device configured to staple tissue clamped between the first jaw and the second jaw.

28. The electro-mechanical surgical device according to claim 27, further comprising a cutting device configured to cut the tissue clamped between the first jaw and the second jaw.

* * * * *

专利名称(译)	双极或超声手术装置		
公开(公告)号	US20130006285A1	公开(公告)日	2013-01-03
申请号	US13/611273	申请日	2012-09-12
[标]申请(专利权)人(译)	柯惠有限合伙公司		
申请(专利权)人(译)	泰科医疗集团LP		
当前申请(专利权)人(译)	泰科医疗集团LP		
[标]发明人	WHITMAN MICHAEL P		
发明人	WHITMAN, MICHAEL P.		
IPC分类号	A61B17/32 A61B17/3201 A61B17/28 A61B18/00 A61B18/12 A61B18/14 A61N7/02		
CPC分类号	A61B17/07207 A61B17/285 A61B17/320068 A61B17/320092 A61B18/1442 A61B18/1477 A61B17/068 A61B2018/145 A61B2019/448 A61N7/02 A61B5/01 A61B5/4836 A61B2018/1425 A61B90/98 A61B2017/320069 A61B2017/320071 A61B2017/320094 A61B2017/320095 A61B2017/320097		
优先权	60/285113 2001-04-20 US 60/289370 2001-05-08 US		
其他公开文献	US8523890		
外部链接	Espacenet USPTO		

摘要(译)

机电手术装置，系统和/或方法可包括壳体，至少两个相对的钳口，以及至少一个钳口相关联的至少一个电触头。电触头可以包括双极电触头和超声电触头中的至少一个。电触点可以是位于一个或所有钳口上的一排电极。传感器还可以与位于钳口之间的任何组织相关联，以感测和报告该组织的温度。包含流体的可刺穿壶液也可以放置在至少一个钳口上，使得当钳口处于闭合位置时，流体可释放，并且电极穿过组织进入可刺穿的壶腹。

