



US009326788B2

(12) **United States Patent**
Batross et al.

(10) **Patent No.:** **US 9,326,788 B2**
(45) **Date of Patent:** **May 3, 2016**

(54) **LOCKOUT MECHANISM FOR USE WITH
ROBOTIC ELECTROSURGICAL DEVICE**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(75) Inventors: **Jonathan T. Batross**, Mason, OH (US);
Gregory A. Trees, Loveland, OH (US);
Foster B. Stulen, Mason, OH (US);
Randolph Stewart, Cincinnati, OH
(US); **Chad P. Boudreaux**, Cincinnati,
OH (US)

969,528 A	9/1910	Disbrow
1,570,025 A	1/1926	Young
1,813,902 A	7/1931	Bovie
2,442,966 A	6/1948	Wallace
2,704,333 A	3/1955	Calosi et al.

(Continued)

FOREIGN PATENT DOCUMENTS

AU	2003241752 A1	9/2003
CN	1634601 A	7/2005

(Continued)

OTHER PUBLICATIONS

International Search Report for PCT/US2013/045814, dated Oct. 24, 2013 (4 pages).

(Continued)

Primary Examiner — Joseph Dietrich

(57)

ABSTRACT

A robotically controlled surgical tool including a lockout mechanism is provided. The surgical tool may comprise an instrument mounting portion. The instrument mounting portion includes a housing, a plate, a shaft assembly comprising an end effector, and a coupler to couple the shaft assembly to the instrument mounting portion. The end effector comprises a first jaw member and a second jaw member, the first and second jaw members defining a channel therebetween, and a blade slideably receivable within the channel to cut tissue located between the first and second jaw members. The surgical tool may include an actuation mechanism to actuate the end effector to provide reciprocating movement of the blade within the channel. A lockout mechanism is coupled to the actuation mechanism. The lockout mechanism may selectively enable reciprocating movement of the blade. An interface mechanically and electrically couples the instrument mounting portion to a robotic manipulator.

20 Claims, 48 Drawing Sheets

(73) Assignee: **Ethicon Endo-Surgery, LLC**,
Guaynabo, PR (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 663 days.

(21) Appl. No.: **13/539,110**

(22) Filed: **Jun. 29, 2012**

(65) **Prior Publication Data**

US 2014/0005654 A1 Jan. 2, 2014

(51) **Int. Cl.**


A61B 17/32	(2006.01)
A61B 18/14	(2006.01)
A61B 19/00	(2006.01)
A61B 17/29	(2006.01)

(52) **U.S. Cl.**

CPC **A61B 17/320092** (2013.01); **A61B 18/14**
(2013.01); **A61B 19/2203** (2013.01); **A61B**
19/30 (2013.01); **A61B 2017/2927** (2013.01);
A61B 2018/1455 (2013.01)

(58) **Field of Classification Search**

CPC **A61B 17/320092**; **A61B 2018/1455**
USPC **606/27**
See application file for complete search history.



(56)

References Cited

U.S. PATENT DOCUMENTS

2,736,960 A	3/1956	Armstrong	4,878,493 A	11/1989	Pasternak et al.
2,849,788 A	9/1958	Creek	4,881,550 A	11/1989	Kothe
2,874,470 A	2/1959	Richards	4,896,009 A	1/1990	Pawlowski
2,990,616 A	7/1961	Balamuth et al.	4,903,696 A	2/1990	Stasz et al.
RE25,033 E	8/1961	Balamuth et al.	4,915,643 A	4/1990	Samejima et al.
3,015,961 A	1/1962	Roney	4,922,902 A	5/1990	Wuchinich et al.
3,053,124 A	9/1962	Balamuth et al.	4,965,532 A	10/1990	Sakurai
3,082,805 A	3/1963	Royce	4,979,952 A	12/1990	Kubota et al.
3,432,691 A	3/1969	Shoh	4,981,756 A	1/1991	Rhandhawa
3,433,226 A	3/1969	Boyd	5,013,956 A	5/1991	Kurozumi et al.
3,489,930 A	1/1970	Shoh	5,015,227 A	5/1991	Broadwin et al.
3,513,848 A	5/1970	Winston et al.	5,026,370 A	6/1991	Lottick
3,526,219 A	9/1970	Balamuth	5,026,387 A	6/1991	Thomas
3,554,198 A	1/1971	Tatoian et al.	5,042,707 A	8/1991	Taheri
3,614,484 A	10/1971	Shoh	5,084,052 A	1/1992	Jacobs
3,616,375 A	10/1971	Inoue	5,105,117 A	4/1992	Yamaguchi
3,629,726 A	12/1971	Popescu	5,109,819 A	5/1992	Custer et al.
3,636,943 A	1/1972	Balamuth	5,112,300 A	5/1992	Ureche
3,668,486 A	6/1972	Silver	5,123,903 A	6/1992	Quaid et al.
3,702,948 A	11/1972	Balamuth	5,126,618 A	6/1992	Takahashi et al.
3,776,238 A	12/1973	Peyman et al.	D327,872 S	7/1992	McMills et al.
3,805,787 A	4/1974	Banko	5,152,762 A	10/1992	McElhenney
3,809,977 A	5/1974	Balamuth et al.	5,162,044 A	11/1992	Gahn et al.
3,830,098 A	8/1974	Antonevich	5,163,421 A	11/1992	Bernstein et al.
3,854,737 A	12/1974	Gilliam, Sr.	5,163,537 A	11/1992	Radev
3,862,630 A	1/1975	Balamuth	5,167,725 A	12/1992	Clark et al.
3,875,945 A	4/1975	Friedman	5,174,276 A	12/1992	Crockard
3,885,438 A	5/1975	Harris, Sr. et al.	D332,660 S	1/1993	Rawson et al.
3,900,823 A	8/1975	Sokal et al.	5,176,677 A	1/1993	Wuchinich
3,918,442 A	11/1975	Nikolaev et al.	5,176,695 A	1/1993	Dulebohn
3,924,335 A	12/1975	Balamuth et al.	5,184,605 A	2/1993	Grezeszykowski
3,946,738 A	3/1976	Newton et al.	5,188,102 A	2/1993	Idemoto et al.
3,955,859 A	5/1976	Stella et al.	D334,173 S	3/1993	Liu et al.
3,956,826 A	5/1976	Perdreux, Jr.	5,209,719 A	5/1993	Baruch et al.
4,012,647 A	3/1977	Balamuth et al.	5,213,569 A	5/1993	Davis
4,074,719 A	2/1978	Semm	5,214,339 A	5/1993	Naito
4,156,187 A	5/1979	Murry et al.	5,218,529 A	6/1993	Meyer et al.
4,167,944 A	9/1979	Banko	5,221,282 A	6/1993	Wuchinich
4,188,927 A	2/1980	Harris	5,226,909 A	7/1993	Evans et al.
4,200,106 A	4/1980	Douvas et al.	5,226,910 A	7/1993	Kajiyama et al.
4,203,444 A	5/1980	Bonnell et al.	5,241,236 A	8/1993	Sasaki et al.
4,300,083 A	11/1981	Heiges	5,241,968 A	9/1993	Slater
4,302,728 A	11/1981	Nakamura	5,242,460 A	9/1993	Klein et al.
4,306,570 A	12/1981	Matthews	5,254,129 A	10/1993	Alexander
4,445,063 A	4/1984	Smith	5,257,988 A	11/1993	L'Esperance, Jr.
4,491,132 A	1/1985	Aikins	5,261,922 A	11/1993	Hood
4,494,759 A	1/1985	Kieffer	5,263,957 A	11/1993	Davison
4,504,264 A	3/1985	Kelman	5,264,925 A	11/1993	Shipp et al.
4,512,344 A	4/1985	Barber	5,275,166 A	1/1994	Vaitekunas et al.
4,526,571 A	7/1985	Wuchinich	5,275,609 A	1/1994	Pingleton et al.
4,545,374 A	10/1985	Jacobson	5,282,800 A	2/1994	Foshee et al.
4,574,615 A	3/1986	Bower et al.	5,282,817 A	2/1994	Hoogeboom et al.
4,617,927 A	10/1986	Manes	5,285,795 A	2/1994	Ryan et al.
4,633,119 A	12/1986	Thompson	5,300,068 A	4/1994	Rosar et al.
4,634,420 A	1/1987	Spinosa et al.	5,304,115 A	4/1994	Pflueger et al.
4,640,279 A	2/1987	Beard	D347,474 S	5/1994	Olson
4,641,053 A	2/1987	Takeda	5,307,976 A	5/1994	Olson et al.
4,646,738 A	3/1987	Trott	5,312,023 A	5/1994	Green et al.
4,646,756 A	3/1987	Watmough et al.	5,312,425 A	5/1994	Evans et al.
4,649,919 A	3/1987	Thimsen et al.	5,322,055 A	6/1994	Davison et al.
4,662,068 A	5/1987	Polonsky	5,324,299 A	6/1994	Davison et al.
4,674,502 A	6/1987	Imonti	5,326,013 A	7/1994	Green et al.
4,708,127 A	11/1987	Abdelghani	5,326,342 A	7/1994	Pflueger et al.
4,712,722 A	12/1987	Hood et al.	5,344,420 A	9/1994	Hilal et al.
4,808,154 A	2/1989	Freeman	5,345,937 A	9/1994	Middleman et al.
4,819,635 A	4/1989	Shapiro	5,346,502 A	9/1994	Estabrook et al.
4,827,911 A	5/1989	Broadwin et al.	5,353,474 A	10/1994	Good et al.
4,832,683 A	5/1989	Idemoto et al.	5,357,164 A	10/1994	Imabayashi et al.
4,836,186 A	6/1989	Scholz	5,357,423 A	10/1994	Weaver et al.
4,838,853 A	6/1989	Parisi	5,359,994 A	11/1994	Krauter et al.
4,844,064 A	7/1989	Thimsen et al.	5,366,466 A	11/1994	Christian et al.
4,850,354 A	7/1989	McGurk-Burleson et al.	5,368,557 A	11/1994	Nita et al.
4,852,578 A	8/1989	Companion et al.	5,370,645 A	12/1994	Klicek et al.
4,865,159 A	9/1989	Jamison	5,371,429 A	12/1994	Manna
4,867,157 A	9/1989	McGurk-Burleson et al.	5,374,813 A	12/1994	Shipp
			D354,564 S	1/1995	Medema
			5,381,067 A	1/1995	Greenstein et al.
			5,387,215 A	2/1995	Fisher
			5,389,098 A	2/1995	Tsuruta et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

5,394,187	A	2/1995	Shipp	5,828,160	A	10/1998	Sugishita
5,396,266	A	3/1995	Brimhall	5,833,696	A	11/1998	Whitfield et al.
5,403,312	A	4/1995	Yates et al.	5,836,897	A	11/1998	Sakurai et al.
5,403,334	A	4/1995	Evans et al.	5,836,957	A	11/1998	Schulz et al.
5,408,268	A	4/1995	Shipp	5,843,109	A	12/1998	Mehta et al.
D358,887	S	5/1995	Feinberg	5,851,212	A	12/1998	Zirps et al.
5,411,481	A	5/1995	Allen et al.	5,858,018	A	1/1999	Shipp et al.
5,419,761	A	5/1995	Narayanan et al.	5,873,873	A	2/1999	Smith et al.
5,421,829	A	6/1995	Olichney et al.	5,873,882	A	2/1999	Straub et al.
5,423,844	A	6/1995	Miller	5,878,193	A	3/1999	Wang et al.
5,438,997	A	8/1995	Sieben et al.	5,879,364	A	3/1999	Bromfield et al.
5,445,639	A	8/1995	Kuslich et al.	5,883,615	A	3/1999	Fago et al.
5,449,370	A	9/1995	Vaitekunas	5,893,835	A	4/1999	Witt et al.
5,451,220	A	9/1995	Ciervo	5,897,523	A	4/1999	Wright et al.
5,456,684	A	10/1995	Schmidt et al.	5,897,569	A	4/1999	Kellogg et al.
5,471,988	A	12/1995	Fujio et al.	5,903,607	A	5/1999	Tailliet
5,472,443	A	12/1995	Cordis et al.	5,904,681	A	5/1999	West, Jr.
5,478,003	A	12/1995	Green et al.	5,906,627	A	5/1999	Spaulding
5,483,501	A	1/1996	Park et al.	5,906,628	A	5/1999	Miyawaki et al.
5,486,162	A	1/1996	Brumbach	5,911,699	A	6/1999	Anis et al.
5,490,860	A	2/1996	Middle et al.	5,916,229	A	6/1999	Evans
5,500,216	A	3/1996	Julian et al.	5,929,846	A	7/1999	Rosenberg et al.
5,501,654	A	3/1996	Failla et al.	5,935,143	A	8/1999	Hood
5,505,693	A	4/1996	Mackool	5,935,144	A	8/1999	Estabrook
5,507,738	A	4/1996	Ciervo	5,938,633	A	8/1999	Beaupre
5,527,331	A	6/1996	Kresch et al.	5,944,718	A	8/1999	Austin et al.
5,540,693	A	7/1996	Fisher	5,944,737	A	8/1999	Tsonton et al.
5,558,671	A	9/1996	Yates	5,947,984	A	9/1999	Whipple
5,562,609	A	10/1996	Brumbach	5,954,736	A	9/1999	Bishop et al.
5,562,610	A	10/1996	Brumbach	5,954,746	A	9/1999	Holthaus et al.
5,562,659	A	10/1996	Morris	5,957,882	A	9/1999	Nita et al.
5,573,424	A	11/1996	Poppe	5,957,943	A	9/1999	Vaitekunas
5,577,654	A	11/1996	Bishop	5,968,007	A	10/1999	Simon et al.
5,591,187	A	1/1997	Dekel	5,968,060	A	10/1999	Kellogg
5,593,414	A	1/1997	Shipp et al.	5,974,342	A	10/1999	Petrofsky
5,601,601	A	2/1997	Tal et al.	D416,089	S	11/1999	Barton et al.
5,603,773	A	2/1997	Campbell	5,980,510	A	11/1999	Tsonton et al.
5,607,436	A	3/1997	Pratt et al.	5,980,546	A	11/1999	Hood
5,618,304	A	4/1997	Hart et al.	5,989,274	A	11/1999	Davison et al.
5,618,492	A	4/1997	Auten et al.	5,989,275	A	11/1999	Estabrook et al.
5,620,447	A	4/1997	Smith et al.	5,993,465	A	11/1999	Shipp et al.
5,626,587	A	5/1997	Bishop et al.	5,993,972	A	11/1999	Reich et al.
5,626,595	A	5/1997	Sklar et al.	5,994,855	A	11/1999	Lundell et al.
5,628,760	A	5/1997	Knoepfler	6,024,741	A	2/2000	Williamson, IV et al.
5,630,420	A	5/1997	Vaitekunas	6,024,750	A	2/2000	Mastri et al.
D381,077	S	7/1997	Hunt	6,027,515	A	2/2000	Cimino
5,651,780	A	7/1997	Jackson et al.	6,031,526	A	2/2000	Shipp
5,653,713	A	8/1997	Michelson	6,033,375	A	3/2000	Brumbach
5,669,922	A	9/1997	Hood	6,033,399	A	3/2000	Gines
5,674,235	A	10/1997	Parisi	6,036,667	A	3/2000	Manna et al.
5,678,568	A	10/1997	Uchikubo et al.	6,036,707	A	3/2000	Spaulding
5,690,269	A	11/1997	Bolanos et al.	6,048,224	A	4/2000	Kay
5,694,936	A	12/1997	Fujimoto et al.	6,050,943	A	4/2000	Slayton et al.
5,704,534	A	1/1998	Huitema et al.	6,051,010	A	4/2000	DiMatteo et al.
5,709,680	A	1/1998	Yates et al.	6,056,735	A	5/2000	Okada et al.
5,711,472	A	1/1998	Bryan	6,063,098	A	5/2000	Houser et al.
5,713,896	A	2/1998	Nardella	6,066,132	A	5/2000	Chen et al.
5,715,817	A	2/1998	Stevens-Wright et al.	6,066,151	A	5/2000	Miyawaki et al.
5,717,306	A	2/1998	Shipp	6,068,627	A	5/2000	Orszulak et al.
5,728,130	A	3/1998	Ishikawa et al.	6,068,647	A	5/2000	Witt et al.
5,730,752	A	3/1998	Alden et al.	6,077,285	A	6/2000	Boukhny
5,733,074	A	3/1998	Stöck et al.	6,083,191	A	7/2000	Rose
5,741,226	A	4/1998	Strukel et al.	6,086,584	A	7/2000	Miller
5,766,164	A	6/1998	Mueller et al.	6,090,120	A	7/2000	Wright et al.
5,772,659	A	6/1998	Becker et al.	6,096,033	A	8/2000	Tu et al.
5,792,135	A	8/1998	Madhani et al.	6,099,542	A	8/2000	Cohn et al.
5,792,138	A	8/1998	Shipp	6,109,500	A	8/2000	Alli et al.
5,792,165	A	8/1998	Klieman et al.	6,110,127	A	8/2000	Suzuki
5,805,140	A	9/1998	Rosenberg et al.	6,113,594	A	9/2000	Savage
5,808,396	A	9/1998	Boukhny	6,117,152	A	9/2000	Huitema
5,810,859	A	9/1998	DiMatteo et al.	6,126,629	A	10/2000	Perkins
5,817,084	A	10/1998	Jensen	6,129,735	A	10/2000	Okada et al.
5,817,119	A	10/1998	Klieman et al.	6,129,740	A	10/2000	Michelson
5,823,197	A	10/1998	Edwards	6,132,368	A	10/2000	Cooper
5,827,323	A	10/1998	Klieman et al.	6,132,427	A	10/2000	Jones et al.
				6,132,448	A	10/2000	Perez et al.
				6,139,320	A	10/2000	Hahn
				6,139,561	A	10/2000	Shibata et al.
				6,142,615	A	11/2000	Qiu et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,142,994	A	11/2000	Swanson et al.	6,443,969	B1	9/2002	Novak et al.
6,147,560	A	11/2000	Erhage et al.	6,449,006	B1	9/2002	Shipp
6,152,902	A	11/2000	Christian et al.	6,454,781	B1	9/2002	Witt et al.
6,154,198	A	11/2000	Rosenberg	6,454,782	B1	9/2002	Schwemberger
6,159,160	A	12/2000	Hsei et al.	6,458,142	B1	10/2002	Faller et al.
6,159,175	A	12/2000	Strukel et al.	6,475,215	B1	11/2002	Tanrisever
6,162,194	A	12/2000	Shipp	6,480,796	B2	11/2002	Wiener
6,165,150	A	12/2000	Banko	6,485,490	B2	11/2002	Wampler et al.
6,174,310	B1	1/2001	Kirwan, Jr.	6,491,708	B2	12/2002	Madan et al.
6,179,853	B1	1/2001	Sachse et al.	6,497,715	B2	12/2002	Satou
6,183,426	B1	2/2001	Akisada et al.	6,500,176	B1	12/2002	Truckai et al.
6,193,709	B1	2/2001	Miyawaki et al.	6,500,188	B2	12/2002	Harper et al.
6,204,592	B1	3/2001	Hur	6,500,312	B2	12/2002	Wedekamp
6,205,855	B1	3/2001	Pfeiffer	6,506,208	B2	1/2003	Hunt et al.
6,206,844	B1	3/2001	Reichel et al.	6,511,478	B1	1/2003	Burnside et al.
6,210,337	B1	4/2001	Dunham et al.	6,511,493	B1	1/2003	Moutafis et al.
6,210,402	B1	4/2001	Olsen et al.	6,514,267	B2	2/2003	Jewett
6,210,403	B1	4/2001	Klicek	6,524,251	B2	2/2003	Rabiner et al.
6,214,023	B1	4/2001	Whipple et al.	6,524,316	B1	2/2003	Nicholson et al.
6,228,080	B1	5/2001	Gines	6,527,736	B1	3/2003	Attinger et al.
6,231,565	B1	5/2001	Tovey et al.	6,533,784	B2	3/2003	Truckai et al.
6,233,476	B1	5/2001	Strommer et al.	6,537,272	B2	3/2003	Christopherson et al.
6,238,366	B1	5/2001	Savage et al.	6,537,291	B2	3/2003	Friedman et al.
6,245,065	B1	6/2001	Panescu et al.	6,543,452	B1	4/2003	Lavigne
6,252,110	B1	6/2001	Uemura et al.	6,543,456	B1	4/2003	Freeman
D444,365	S	7/2001	Bass et al.	6,544,260	B1	4/2003	Markel et al.
D445,092	S	7/2001	Lee	6,558,376	B2	5/2003	Bishop
D445,764	S	7/2001	Lee	6,561,983	B2	5/2003	Cronin et al.
6,254,623	B1	7/2001	Haibel, Jr. et al.	6,565,558	B1	5/2003	Lindenmeier et al.
6,257,241	B1	7/2001	Wampler	6,572,563	B2	6/2003	Ouchi
6,258,034	B1	7/2001	Hanafy	6,572,632	B2	6/2003	Zisterer et al.
6,267,761	B1	7/2001	Ryan	6,575,969	B1	6/2003	Rittman, III et al.
6,270,831	B2	8/2001	Kumar et al.	6,582,427	B1	6/2003	Goble et al.
6,273,852	B1	8/2001	Lehe et al.	6,582,451	B1	6/2003	Marucci et al.
6,274,963	B1	8/2001	Estabrook et al.	D477,408	S	7/2003	Bromley
6,277,115	B1	8/2001	Saadat	6,588,277	B2	7/2003	Giordano et al.
6,278,218	B1	8/2001	Madan et al.	6,589,200	B1	7/2003	Schwemberger et al.
6,280,407	B1	8/2001	Manna et al.	6,589,239	B2	7/2003	Khandkar et al.
6,283,981	B1	9/2001	Beaupre	6,607,540	B1	8/2003	Shipp
6,287,344	B1	9/2001	Wampler et al.	6,610,059	B1	8/2003	West, Jr.
6,290,575	B1	9/2001	Shipp	6,616,450	B2	9/2003	Mossle et al.
6,306,157	B1	10/2001	Shchervinsky	6,619,529	B2	9/2003	Green et al.
6,309,400	B2	10/2001	Beaupre	6,623,500	B1	9/2003	Cook et al.
6,319,221	B1	11/2001	Savage et al.	6,623,501	B2	9/2003	Heller et al.
6,325,795	B1	12/2001	Lindemann et al.	6,626,848	B2	9/2003	Neuenfeldt
6,325,799	B1	12/2001	Goble	6,626,926	B2	9/2003	Friedman et al.
6,325,811	B1	12/2001	Messerly	6,629,974	B2	10/2003	Penny et al.
6,328,751	B1	12/2001	Beaupre	6,633,234	B2	10/2003	Wiener et al.
6,332,891	B1	12/2001	Himes	6,644,532	B2	11/2003	Green et al.
6,338,657	B1	1/2002	Harper et al.	6,652,513	B2	11/2003	Panescu et al.
6,340,352	B1	1/2002	Okada et al.	6,652,539	B2	11/2003	Shipp et al.
6,350,269	B1	2/2002	Shipp et al.	6,652,545	B2	11/2003	Shipp et al.
6,352,532	B1	3/2002	Kramer et al.	6,656,132	B1	12/2003	Ouchi
6,358,264	B2	3/2002	Banko	6,656,177	B2	12/2003	Truckai et al.
6,364,888	B1	4/2002	Niemeyer et al.	6,660,017	B2	12/2003	Beaupre
6,379,320	B1	4/2002	Lafon et al.	6,662,127	B2	12/2003	Wiener et al.
D457,958	S	5/2002	Dycus et al.	6,663,941	B2	12/2003	Brown et al.
6,383,194	B1	5/2002	Pothula	6,666,860	B1	12/2003	Takahashi
6,384,690	B1	5/2002	Wilhelmsson et al.	6,666,875	B1	12/2003	Sakurai et al.
6,387,109	B1	5/2002	Davison et al.	6,669,690	B1	12/2003	Okada et al.
6,388,657	B1	5/2002	Natoli	6,669,710	B2	12/2003	Moutafis et al.
6,391,042	B1	5/2002	Cimino	6,676,660	B2	1/2004	Wampler et al.
6,398,779	B1	6/2002	Buyse et al.	6,678,621	B2	1/2004	Wiener et al.
6,402,743	B1	6/2002	Orszulak et al.	6,679,875	B2	1/2004	Honda et al.
6,402,748	B1	6/2002	Schoenman et al.	6,679,899	B2	1/2004	Wiener et al.
6,405,733	B1	6/2002	Fogarty et al.	6,682,544	B2	1/2004	Mastri et al.
6,416,486	B1	7/2002	Wampler	6,685,701	B2	2/2004	Orszulak et al.
6,423,073	B2	7/2002	Bowman	6,685,703	B2	2/2004	Pearson et al.
6,423,082	B1	7/2002	Houser et al.	6,689,145	B2	2/2004	Lee et al.
6,428,539	B1	8/2002	Baxter et al.	6,689,146	B1	2/2004	Nimes
6,432,118	B1	8/2002	Messerly	6,716,215	B1	4/2004	David et al.
6,436,114	B1	8/2002	Novak et al.	6,719,692	B2	4/2004	Kleffner et al.
6,436,115	B1	8/2002	Beaupre	6,719,776	B2	4/2004	Baxter
6,440,062	B1	8/2002	Ouchi	6,723,091	B2	4/2004	Goble et al.
6,443,968	B1	9/2002	Holthaus et al.	D490,059	S	5/2004	Conway et al.
				6,731,047	B2	5/2004	Kauf et al.
				6,733,506	B1	5/2004	McDevitt et al.
				6,739,872	B1	5/2004	Turri
				6,740,079	B1	5/2004	Eggers et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

D491,666	S	6/2004	Kimmell et al.	7,074,218	B2	7/2006	Washington et al.
6,743,245	B2	6/2004	Lobdell	7,074,219	B2	7/2006	Levine et al.
6,746,284	B1	6/2004	Spink, Jr.	7,077,039	B2	7/2006	Gass et al.
6,746,443	B1	6/2004	Morley et al.	7,077,845	B2	7/2006	Hacker et al.
6,752,815	B2	6/2004	Beaupre	7,077,853	B2	7/2006	Kramer et al.
6,755,825	B2	6/2004	Shoenman et al.	7,083,619	B2	8/2006	Truckai et al.
6,761,698	B2	7/2004	Shibata et al.	7,087,054	B2	8/2006	Truckai et al.
6,762,535	B2	7/2004	Take et al.	7,090,672	B2	8/2006	Underwood et al.
6,770,072	B1	8/2004	Truckai et al.	7,101,371	B2	9/2006	Dycus et al.
6,773,409	B2	8/2004	Truckai et al.	7,101,378	B2	9/2006	Salameh et al.
6,773,443	B2	8/2004	Truwit et al.	7,104,834	B2	9/2006	Robinson et al.
6,773,444	B2	8/2004	Messerly	7,108,695	B2	9/2006	Witt et al.
6,778,023	B2	8/2004	Christensen	7,111,769	B2	9/2006	Wales et al.
6,783,524	B2	8/2004	Anderson et al.	7,112,201	B2	9/2006	Truckai et al.
6,786,382	B1	9/2004	Hoffman	D531,311	S	10/2006	Guerra et al.
6,786,383	B2	9/2004	Stegelmann	7,117,034	B2	10/2006	Kronberg
6,790,173	B2	9/2004	Saadat et al.	7,118,564	B2	10/2006	Ritchie et al.
6,790,216	B1	9/2004	Ishikawa	7,124,932	B2	10/2006	Isacson et al.
6,796,981	B2	9/2004	Wham et al.	7,125,409	B2	10/2006	Truckai et al.
D496,997	S	10/2004	Dycus et al.	7,128,720	B2	10/2006	Podany
6,802,843	B2	10/2004	Truckai et al.	7,131,860	B2	11/2006	Sartor et al.
6,808,525	B2	10/2004	Latterell et al.	7,135,018	B2	11/2006	Ryan et al.
6,809,508	B2	10/2004	Donofrio	7,135,030	B2	11/2006	Schwemberger et al.
6,810,281	B2	10/2004	Brock et al.	7,137,980	B2	11/2006	Buyse et al.
6,827,712	B2	12/2004	Tovey et al.	7,144,403	B2	12/2006	Booth
6,828,712	B2	12/2004	Battaglin et al.	7,153,315	B2	12/2006	Miller
6,835,082	B2	12/2004	Gonnering	D536,093	S	1/2007	Nakajima et al.
6,849,073	B2	2/2005	Hoeey et al.	7,156,189	B1	1/2007	Bar-Cohen et al.
6,860,878	B2	3/2005	Brock	7,156,853	B2	1/2007	Muratsu
6,863,676	B2	3/2005	Lee et al.	7,157,058	B2	1/2007	Marhasin et al.
6,869,439	B2	3/2005	White et al.	7,159,750	B2	1/2007	Racenet et al.
6,875,220	B2	4/2005	Du et al.	7,160,296	B2	1/2007	Pearson et al.
6,877,647	B2	4/2005	Green et al.	7,160,299	B2	1/2007	Baily
6,882,439	B2	4/2005	Ishijima	7,163,548	B2	1/2007	Stulen et al.
6,887,209	B2	5/2005	Kadziauskas et al.	7,169,144	B2	1/2007	Hoeey et al.
6,887,252	B1	5/2005	Okada et al.	7,169,146	B2	1/2007	Truckai et al.
6,899,685	B2	5/2005	Kermode et al.	7,179,254	B2	2/2007	Pendekanti et al.
6,905,497	B2	6/2005	Truckai et al.	7,179,271	B2	2/2007	Friedman et al.
6,908,472	B2	6/2005	Wiener et al.	7,186,253	B2	3/2007	Truckai et al.
6,913,579	B2	7/2005	Truckai et al.	7,189,233	B2	3/2007	Truckai et al.
6,915,623	B2	7/2005	Dey et al.	D541,418	S	4/2007	Schechter et al.
6,923,804	B2	8/2005	Eggers et al.	7,204,820	B2	4/2007	Akahoshi
6,926,712	B2	8/2005	Phan	7,207,997	B2	4/2007	Shipp et al.
6,926,716	B2	8/2005	Baker et al.	7,210,881	B2	5/2007	Greenberg
6,929,602	B2	8/2005	Hirakui et al.	7,211,079	B2	5/2007	Treat
6,929,632	B2	8/2005	Nita et al.	7,217,128	B2	5/2007	Atkin et al.
6,929,644	B2	8/2005	Truckai et al.	7,217,269	B2	5/2007	El-Galley et al.
6,933,656	B2	8/2005	Matsushita et al.	7,220,951	B2	5/2007	Truckai et al.
D509,589	S	9/2005	Wells	7,223,229	B2	5/2007	Inman et al.
6,942,660	B2	9/2005	Pantera et al.	7,229,455	B2	6/2007	Sakurai et al.
6,942,677	B2	9/2005	Nita et al.	7,235,071	B2	6/2007	Gonnering
6,945,981	B2	9/2005	Donofrio et al.	7,244,262	B2	7/2007	Wiener et al.
6,946,779	B2	9/2005	Birgel	7,258,688	B1	8/2007	Shah et al.
6,948,503	B2	9/2005	Refior et al.	7,269,873	B2	9/2007	Brewer et al.
D511,145	S	11/2005	Donofrio et al.	7,273,483	B2	9/2007	Wiener et al.
6,974,450	B2	12/2005	Weber et al.	D552,241	S	10/2007	Bromley et al.
6,976,844	B2	12/2005	Hickok et al.	7,282,048	B2	10/2007	Goble et al.
6,976,969	B2	12/2005	Messerly	7,285,895	B2	10/2007	Beaupre
6,977,495	B2	12/2005	Donofrio	7,300,431	B2	11/2007	Dubrovsky
6,979,332	B2	12/2005	Adams	7,300,435	B2	11/2007	Wham et al.
6,981,628	B2	1/2006	Wales	7,300,446	B2	11/2007	Beaupre
6,984,220	B2	1/2006	Wuchinich	7,303,531	B2	12/2007	Lee et al.
6,994,708	B2	2/2006	Manzo	7,303,557	B2	12/2007	Wham et al.
7,001,335	B2	2/2006	Adachi et al.	7,306,597	B2	12/2007	Manzo
7,011,657	B2	3/2006	Truckai et al.	7,309,849	B2	12/2007	Truckai et al.
7,014,638	B2	3/2006	Michelson	7,311,706	B2	12/2007	Schoenman et al.
7,033,357	B2	4/2006	Baxter et al.	7,311,709	B2	12/2007	Truckai et al.
7,037,306	B2	5/2006	Podany	7,317,955	B2	1/2008	McGreevy
7,041,083	B2	5/2006	Chu et al.	7,318,831	B2	1/2008	Alvarez et al.
7,041,088	B2	5/2006	Nawrocki et al.	7,326,236	B2	2/2008	Andreas et al.
7,041,102	B2	5/2006	Truckai et al.	7,331,410	B2	2/2008	Yong et al.
7,044,949	B2	5/2006	Orszulak et al.	7,335,165	B2	2/2008	Truwit et al.
7,066,893	B2	6/2006	Hibner et al.	7,335,997	B2	2/2008	Wiener
7,066,895	B2	6/2006	Podany	7,337,010	B2	2/2008	Howard et al.
7,070,597	B2	7/2006	Truckai et al.	7,353,068	B2	4/2008	Tanaka et al.
				7,354,440	B2	4/2008	Truckai et al.
				7,364,577	B2	4/2008	Wham et al.
				RE40,388	E	6/2008	Gines
				7,380,695	B2	6/2008	Doll et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,380,696 B2	6/2008	Shelton, IV et al.	7,766,210 B2	8/2010	Shelton, IV et al.
7,381,209 B2	6/2008	Truckai et al.	7,766,693 B2	8/2010	Sartor et al.
7,390,317 B2	6/2008	Taylor et al.	7,770,774 B2	8/2010	Mastri et al.
7,404,508 B2	7/2008	Smith et al.	7,770,775 B2	8/2010	Shelton, IV et al.
7,408,288 B2	8/2008	Hara	7,771,425 B2	8/2010	Dycus et al.
7,416,101 B2	8/2008	Shelton, IV et al.	7,771,444 B2	8/2010	Patel et al.
7,416,437 B2	8/2008	Sartor et al.	7,775,972 B2	8/2010	Brock et al.
D576,725 S	9/2008	Shumer et al.	7,778,733 B2	8/2010	Nowlin et al.
7,419,490 B2	9/2008	Falkenstein et al.	7,780,054 B2	8/2010	Wales
7,422,139 B2	9/2008	Shelton, IV et al.	7,780,593 B2	8/2010	Ueno et al.
7,422,463 B2	9/2008	Kuo	7,780,651 B2	8/2010	Madhani et al.
D578,643 S	10/2008	Shumer et al.	7,780,659 B2	8/2010	Okada et al.
D578,644 S	10/2008	Shumer et al.	7,784,662 B2	8/2010	Wales et al.
D578,645 S	10/2008	Shumer et al.	7,796,969 B2	9/2010	Kelly et al.
7,431,704 B2	10/2008	Babaev	7,798,386 B2	9/2010	Schall et al.
7,441,684 B2	10/2008	Shelton, IV et al.	7,799,020 B2	9/2010	Shores et al.
7,455,208 B2	11/2008	Wales et al.	7,799,045 B2	9/2010	Masuda
7,462,181 B2	12/2008	Kraft et al.	7,803,152 B2	9/2010	Honda et al.
7,464,846 B2	12/2008	Shelton, IV et al.	7,806,891 B2	10/2010	Nowlin et al.
7,472,815 B2	1/2009	Shelton, IV et al.	7,810,693 B2	10/2010	Broehl et al.
7,473,263 B2	1/2009	Johnston et al.	7,811,283 B2	10/2010	Moses et al.
7,479,148 B2	1/2009	Beaupre	7,819,819 B2	10/2010	Quick et al.
7,479,160 B2	1/2009	Branch et al.	D627,066 S	11/2010	Romero
7,481,775 B2	1/2009	Weikel, Jr. et al.	7,824,401 B2	11/2010	Manzo et al.
7,488,285 B2	2/2009	Honda et al.	7,832,611 B2	11/2010	Boyden et al.
7,494,468 B2	2/2009	Rabiner et al.	7,834,484 B2	11/2010	Sartor
7,502,234 B2	3/2009	Goliszek et al.	7,837,699 B2	11/2010	Yamada et al.
7,503,893 B2	3/2009	Kucklick	7,845,537 B2	12/2010	Shelton, IV et al.
7,503,895 B2	3/2009	Rabiner et al.	7,846,155 B2	12/2010	Houser et al.
7,506,790 B2	3/2009	Shelton, IV	7,846,161 B2	12/2010	Dumbauld et al.
7,506,791 B2	3/2009	Omaits et al.	7,854,735 B2	12/2010	Houser et al.
7,524,320 B2	4/2009	Tierney et al.	D631,155 S	1/2011	Peine et al.
7,530,986 B2	5/2009	Beaupre et al.	7,861,906 B2	1/2011	Doll et al.
7,534,243 B1	5/2009	Chin et al.	7,862,560 B2	1/2011	Marion
D594,983 S	6/2009	Price et al.	7,876,030 B2	1/2011	Taki et al.
7,540,871 B2	6/2009	Gonnering	D631,965 S	2/2011	Price et al.
7,544,200 B2	6/2009	Houser	7,878,991 B2	2/2011	Babaev
7,549,564 B2	6/2009	Boudreaux	7,879,033 B2	2/2011	Sartor et al.
7,559,450 B2	7/2009	Wales et al.	7,892,606 B2	2/2011	Thies et al.
7,567,012 B2	7/2009	Namikawa	7,901,400 B2	3/2011	Wham et al.
7,569,057 B2	8/2009	Liu et al.	7,901,423 B2	3/2011	Stulen et al.
7,572,266 B2	8/2009	Young et al.	7,905,881 B2	3/2011	Masuda et al.
7,578,820 B2	8/2009	Moore et al.	7,909,824 B2	3/2011	Masuda et al.
7,582,084 B2	9/2009	Swanson et al.	7,922,061 B2	4/2011	Shelton, IV et al.
7,582,095 B2	9/2009	Shipp et al.	7,922,651 B2	4/2011	Yamada et al.
7,585,181 B2	9/2009	Olsen	D637,288 S	5/2011	Houghton
7,588,176 B2	9/2009	Timm et al.	D638,540 S	5/2011	Ijiri et al.
7,601,119 B2	10/2009	Shahinian	7,936,203 B2	5/2011	Zimlich
7,621,930 B2	11/2009	Houser	7,951,095 B2	5/2011	Makin et al.
7,641,653 B2	1/2010	Dalla Betta et al.	7,951,165 B2	5/2011	Golden et al.
7,654,431 B2	2/2010	Hueil et al.	7,959,050 B2	6/2011	Smith et al.
7,659,833 B2	2/2010	Warner et al.	7,959,626 B2	6/2011	Hong et al.
7,665,647 B2	2/2010	Shelton, IV et al.	7,972,329 B2	7/2011	Refior et al.
7,670,334 B2	3/2010	Hueil et al.	7,976,544 B2	7/2011	McClurken et al.
7,670,338 B2	3/2010	Albrecht et al.	7,981,050 B2	7/2011	Ritchart et al.
7,674,263 B2	3/2010	Ryan	7,998,157 B2	8/2011	Culp et al.
7,678,069 B1	3/2010	Baker et al.	8,038,693 B2	10/2011	Allen
7,678,125 B2	3/2010	Shipp	8,057,498 B2	11/2011	Robertson
7,682,366 B2	3/2010	Sakurai et al.	8,058,771 B2	11/2011	Giordano et al.
7,686,770 B2	3/2010	Cohen	8,061,014 B2	11/2011	Smith et al.
7,686,826 B2	3/2010	Lee et al.	8,070,711 B2	12/2011	Bassinger et al.
7,688,028 B2	3/2010	Phillips et al.	8,070,762 B2	12/2011	Escudero et al.
7,691,098 B2	4/2010	Wallace et al.	8,075,558 B2	12/2011	Truckai et al.
7,699,846 B2	4/2010	Ryan	8,089,197 B2	1/2012	Rinner et al.
7,713,202 B2	5/2010	Boukhny et al.	8,097,012 B2	1/2012	Kagarise
7,714,481 B2	5/2010	Sakai	8,105,323 B2	1/2012	Buyse et al.
7,717,312 B2	5/2010	Beetel	8,142,461 B2	3/2012	Houser et al.
7,717,915 B2	5/2010	Miyazawa	8,152,825 B2	4/2012	Madan et al.
D618,797 S	6/2010	Price et al.	8,157,145 B2	4/2012	Shelton, IV et al.
7,726,537 B2	6/2010	Olson et al.	8,161,977 B2	4/2012	Shelton, IV et al.
7,727,177 B2	6/2010	Bayat	8,162,966 B2	4/2012	Connor et al.
7,738,969 B2	6/2010	Bleich	8,172,846 B2	5/2012	Brunnett et al.
7,740,594 B2	6/2010	Hibner	8,172,870 B2	5/2012	Shipp
7,751,115 B2	7/2010	Song	8,177,800 B2	5/2012	Spitz et al.
D621,503 S	8/2010	Otten et al.	8,182,502 B2	5/2012	Stulen et al.
			8,186,877 B2	5/2012	Klimovitch et al.
			D661,801 S	6/2012	Price et al.
			D661,802 S	6/2012	Price et al.
			D661,803 S	6/2012	Price et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

D661,804 S	6/2012	Price et al.	8,523,889 B2	9/2013	Stulen et al.
8,197,472 B2	6/2012	Lau et al.	8,531,064 B2	9/2013	Robertson et al.
8,197,502 B2	6/2012	Smith et al.	8,535,340 B2	9/2013	Allen
8,210,411 B2	7/2012	Yates et al.	8,535,341 B2	9/2013	Allen
8,226,675 B2	7/2012	Houser et al.	8,546,996 B2	10/2013	Messerly et al.
8,235,917 B2	8/2012	Joseph et al.	8,546,999 B2	10/2013	Houser et al.
8,236,019 B2	8/2012	Houser	8,568,400 B2	10/2013	Gilbert
8,236,020 B2	8/2012	Smith et al.	8,573,461 B2	11/2013	Shelton, IV et al.
8,241,271 B2	8/2012	Millman et al.	8,573,465 B2	11/2013	Shelton, IV
8,246,575 B2	8/2012	Viola	8,579,928 B2	11/2013	Robertson et al.
8,246,615 B2	8/2012	Behnke	8,591,506 B2	11/2013	Wham et al.
8,252,012 B2	8/2012	Stulen	8,591,536 B2	11/2013	Robertson
8,253,303 B2	8/2012	Giordano et al.	D695,407 S	12/2013	Price et al.
8,257,377 B2	9/2012	Wiener et al.	D696,631 S	12/2013	Price et al.
8,257,387 B2	9/2012	Cunningham	8,602,031 B2	12/2013	Reis et al.
8,273,087 B2	9/2012	Kimura et al.	8,602,288 B2	12/2013	Shelton, IV et al.
D669,992 S	10/2012	Schafer et al.	8,608,745 B2	12/2013	Guzman et al.
D669,993 S	10/2012	Merchant et al.	8,616,431 B2	12/2013	Timm et al.
8,286,846 B2	10/2012	Smith et al.	8,623,027 B2	1/2014	Price et al.
8,287,485 B2	10/2012	Kimura et al.	8,650,728 B2	2/2014	Wan et al.
8,287,528 B2	10/2012	Wham et al.	8,652,155 B2	2/2014	Houser et al.
8,287,532 B2	10/2012	Carroll et al.	8,659,208 B1	2/2014	Rose et al.
8,292,888 B2	10/2012	Whitman	8,690,582 B2	4/2014	Rohrbach et al.
8,298,223 B2	10/2012	Wham et al.	8,696,366 B2	4/2014	Chen et al.
8,298,225 B2	10/2012	Gilbert	8,704,425 B2	4/2014	Giordano et al.
8,303,576 B2	11/2012	Brock	8,709,031 B2	4/2014	Stulen
8,303,580 B2	11/2012	Wham et al.	8,749,116 B2	6/2014	Messerly et al.
8,319,400 B2	11/2012	Houser et al.	8,752,749 B2	6/2014	Moore et al.
8,323,302 B2	12/2012	Robertson et al.	8,753,338 B2	6/2014	Widenhouse et al.
8,333,778 B2	12/2012	Smith et al.	8,754,570 B2	6/2014	Voegelé et al.
8,333,779 B2	12/2012	Smith et al.	8,764,735 B2	7/2014	Coe et al.
8,334,468 B2	12/2012	Palmer et al.	8,773,001 B2	7/2014	Wiener et al.
8,334,635 B2	12/2012	Voegelé et al.	8,779,648 B2	7/2014	Giordano et al.
8,337,407 B2	12/2012	Quistgaard et al.	8,808,319 B2	8/2014	Houser et al.
8,338,726 B2	12/2012	Palmer et al.	8,827,992 B2	9/2014	Koss et al.
8,344,596 B2	1/2013	Nield et al.	8,845,537 B2	9/2014	Tanaka et al.
8,348,967 B2	1/2013	Stulen	8,882,791 B2	11/2014	Stulen
8,357,103 B2	1/2013	Mark et al.	8,888,776 B2	11/2014	Dietz et al.
8,372,099 B2	2/2013	Deville et al.	8,888,809 B2	11/2014	Davison et al.
8,372,101 B2	2/2013	Smith et al.	8,900,259 B2	12/2014	Houser et al.
8,372,102 B2	2/2013	Stulen et al.	8,911,460 B2	12/2014	Neurohr et al.
8,374,670 B2	2/2013	Selkee	8,951,248 B2	2/2015	Messerly et al.
8,377,059 B2	2/2013	Deville et al.	8,951,272 B2	2/2015	Robertson et al.
8,377,085 B2	2/2013	Smith et al.	8,956,349 B2	2/2015	Aldridge et al.
8,382,748 B2	2/2013	Geisel	8,961,547 B2	2/2015	Dietz et al.
8,382,775 B1	2/2013	Bender et al.	8,968,355 B2	3/2015	Malkowski et al.
8,382,782 B2	2/2013	Robertson et al.	8,974,477 B2	3/2015	Yamada
8,403,948 B2	3/2013	Deville et al.	8,979,890 B2	3/2015	Boudreaux
8,403,949 B2	3/2013	Palmer et al.	8,986,287 B2	3/2015	Park et al.
8,403,950 B2	3/2013	Palmer et al.	8,986,302 B2	3/2015	Aldridge et al.
8,418,349 B2	4/2013	Smith et al.	8,989,903 B2	3/2015	Weir et al.
8,419,757 B2	4/2013	Smith et al.	9,017,326 B2	4/2015	DiNardo et al.
8,419,758 B2	4/2013	Smith et al.	9,039,695 B2	5/2015	Giordano et al.
8,419,759 B2	4/2013	Dietz	9,044,261 B2	6/2015	Houser
8,425,545 B2	4/2013	Smith et al.	9,050,093 B2	6/2015	Aldridge et al.
8,430,898 B2	4/2013	Wiener et al.	9,050,124 B2	6/2015	Houser
8,435,257 B2	5/2013	Smith et al.	9,060,775 B2	6/2015	Wiener et al.
8,439,912 B2	5/2013	Cunningham et al.	9,060,776 B2	6/2015	Yates et al.
8,439,939 B2	5/2013	Deville et al.	9,066,747 B2	6/2015	Robertson
8,444,637 B2	5/2013	Podmore et al.	9,072,539 B2	7/2015	Messerly et al.
8,444,662 B2	5/2013	Palmer et al.	9,089,360 B2	7/2015	Messerly et al.
8,444,664 B2	5/2013	Balanev et al.	9,095,367 B2	8/2015	Olson et al.
8,461,744 B2	6/2013	Wiener et al.	9,107,689 B2	8/2015	Robertson et al.
8,469,981 B2	6/2013	Robertson et al.	2001/0025173 A1	9/2001	Ritchie et al.
8,479,969 B2	7/2013	Shelton, IV	2001/0025183 A1	9/2001	Shahidi et al.
8,480,703 B2	7/2013	Nicholas et al.	2001/0025184 A1	9/2001	Messerly
8,485,413 B2	7/2013	Scheib et al.	2001/0031950 A1	10/2001	Ryan
8,486,057 B2	7/2013	Behnke, II	2001/0039419 A1	11/2001	Francischelli et al.
8,486,096 B2	7/2013	Robertson et al.	2002/0002377 A1	1/2002	Cimino
8,491,578 B2	7/2013	Manwaring et al.	2002/0019649 A1	2/2002	Sikora et al.
D687,549 S	8/2013	Johnson et al.	2002/0022836 A1	2/2002	Goble et al.
8,506,555 B2	8/2013	Ruiz Morales	2002/0029055 A1	3/2002	Bonutti
8,509,318 B2	8/2013	Tailliet	2002/0049551 A1	4/2002	Friedman et al.
8,512,359 B2	8/2013	Whitman et al.	2002/0052617 A1	5/2002	Anis et al.
8,512,365 B2	8/2013	Wiener et al.	2002/0077550 A1	6/2002	Rabiner et al.
			2002/0156466 A1	10/2002	Sakurai et al.
			2002/0156493 A1	10/2002	Houser et al.
			2003/0014087 A1	1/2003	Fang et al.
			2003/0036705 A1	2/2003	Hare et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2003/0050572	A1	3/2003	Brautigam et al.	2007/0055228	A1	3/2007	Berg et al.
2003/0055443	A1	3/2003	Spotnitz	2007/0056596	A1	3/2007	Fanney et al.
2003/0114851	A1	6/2003	Truckai et al.	2007/0060915	A1	3/2007	Kucklick
2003/0144680	A1	7/2003	Kellogg et al.	2007/0060935	A1	3/2007	Schwardt et al.
2003/0199794	A1	10/2003	Sakurai et al.	2007/0063618	A1	3/2007	Bromfield
2003/0204199	A1	10/2003	Novak et al.	2007/0074584	A1	4/2007	Talarico et al.
2003/0212332	A1	11/2003	Fenton et al.	2007/0106317	A1	5/2007	Shelton, IV et al.
2003/0212363	A1	11/2003	Shipp	2007/0129716	A1	6/2007	Daw et al.
2003/0212392	A1	11/2003	Fenton et al.	2007/0130771	A1	6/2007	Ehlert et al.
2003/0212422	A1	11/2003	Fenton et al.	2007/0131034	A1	6/2007	Ehlert et al.
2003/0229344	A1	12/2003	Dycus et al.	2007/0149881	A1	6/2007	Rabin
2004/0030254	A1	2/2004	Babaev	2007/0162050	A1	7/2007	Sartor
2004/0030330	A1	2/2004	Brassell et al.	2007/0166663	A1	7/2007	Telles et al.
2004/0047485	A1	3/2004	Sherrit et al.	2007/0173803	A1	7/2007	Wham et al.
2004/0054364	A1	3/2004	Aranyi et al.	2007/0173813	A1	7/2007	Odom
2004/0064151	A1	4/2004	Mollenauer	2007/0173872	A1	7/2007	Neuenfeldt
2004/0092921	A1	5/2004	Kadziauskas et al.	2007/0175949	A1	8/2007	Shelton, IV et al.
2004/0092992	A1	5/2004	Adams et al.	2007/0185380	A1	8/2007	Kucklick
2004/0097912	A1	5/2004	Gonnering	2007/0191712	A1	8/2007	Messerly et al.
2004/0097919	A1	5/2004	Wellman et al.	2007/0219481	A1	9/2007	Babaev
2004/0097996	A1	5/2004	Rabiner et al.	2007/0239028	A1	10/2007	Houser et al.
2004/0116952	A1	6/2004	Sakurai et al.	2007/0239101	A1	10/2007	Kellogg
2004/0132383	A1	7/2004	Langford et al.	2007/0249941	A1	10/2007	Salehi et al.
2004/0147934	A1	7/2004	Kiester	2007/0260234	A1	11/2007	McCullagh et al.
2004/0167508	A1	8/2004	Wham et al.	2007/0265560	A1	11/2007	Soltani et al.
2004/0176686	A1	9/2004	Hare et al.	2007/0275348	A1	11/2007	Lemon
2004/0176751	A1	9/2004	Weitzner et al.	2007/0282335	A1	12/2007	Young et al.
2004/0199193	A1	10/2004	Hayashi et al.	2007/0287933	A1	12/2007	Phan et al.
2004/0204728	A1	10/2004	Haefner	2008/0009848	A1	1/2008	Paraschiv et al.
2004/0243147	A1	12/2004	Lipow	2008/0013809	A1	1/2008	Zhu et al.
2004/0260300	A1	12/2004	Gorenssek et al.	2008/0051812	A1	2/2008	Schmitz et al.
2005/0021018	A1	1/2005	Anderson et al.	2008/0058585	A1	3/2008	Novak et al.
2005/0021065	A1	1/2005	Yamada et al.	2008/0058775	A1	3/2008	Darian et al.
2005/0033337	A1	2/2005	Muir et al.	2008/0058845	A1	3/2008	Shimizu et al.
2005/0049546	A1	3/2005	Messerly et al.	2008/0077145	A1	3/2008	Boyden et al.
2005/0070800	A1	3/2005	Takahashi	2008/0082039	A1	4/2008	Babaev
2005/0096683	A1	5/2005	Ellins et al.	2008/0082098	A1	4/2008	Tanaka et al.
2005/0099824	A1	5/2005	Dowling et al.	2008/0114364	A1	5/2008	Goldin et al.
2005/0103819	A1	5/2005	Racenet et al.	2008/0125768	A1	5/2008	Tahara et al.
2005/0143769	A1	6/2005	White et al.	2008/0140158	A1	6/2008	Hamel et al.
2005/0149108	A1	7/2005	Cox	2008/0147092	A1	6/2008	Rogge et al.
2005/0165345	A1	7/2005	Lauffer et al.	2008/0171938	A1	7/2008	Masuda et al.
2005/0177184	A1	8/2005	Easley	2008/0172051	A1	7/2008	Masuda et al.
2005/0182339	A1	8/2005	Lee et al.	2008/0177268	A1	7/2008	Daum et al.
2005/0188743	A1	9/2005	Land	2008/0188878	A1	8/2008	Young
2005/0192610	A1	9/2005	Houser et al.	2008/0200940	A1	8/2008	Eichmann et al.
2005/0209620	A1	9/2005	Du et al.	2008/0208108	A1	8/2008	Kimura
2005/0222598	A1	10/2005	Ho et al.	2008/0208231	A1	8/2008	Ota et al.
2005/0234484	A1	10/2005	Houser et al.	2008/0214967	A1	9/2008	Aranyi et al.
2005/0249667	A1	11/2005	Tuszynski et al.	2008/0234709	A1	9/2008	Houser
2005/0256405	A1	11/2005	Makin et al.	2008/0243106	A1	10/2008	Coe et al.
2005/0261581	A1	11/2005	Hughes et al.	2008/0243162	A1	10/2008	Shibata et al.
2005/0261588	A1	11/2005	Makin et al.	2008/0245371	A1	10/2008	Gruber
2005/0273090	A1	12/2005	Nieman et al.	2008/0249553	A1	10/2008	Gruber et al.
2005/0288659	A1	12/2005	Kimura et al.	2008/0255423	A1	10/2008	Kondo et al.
2006/0030797	A1	2/2006	Zhou et al.	2008/0262490	A1	10/2008	Williams
2006/0058825	A1	3/2006	Ogura et al.	2008/0281200	A1	11/2008	Voic et al.
2006/0063130	A1	3/2006	Hayman et al.	2008/0281315	A1	11/2008	Gines
2006/0066181	A1	3/2006	Bromfield et al.	2008/0281322	A1	11/2008	Sherman et al.
2006/0074442	A1	4/2006	Noriega et al.	2008/0287948	A1	11/2008	Newton et al.
2006/0079879	A1	4/2006	Faller et al.	2009/0023985	A1	1/2009	Ewers
2006/0084963	A1	4/2006	Messerly	2009/0048537	A1	2/2009	Lydon et al.
2006/0095046	A1	5/2006	Trieu et al.	2009/0054886	A1	2/2009	Yachi et al.
2006/0190034	A1	8/2006	Nishizawa et al.	2009/0054894	A1	2/2009	Yachi
2006/0206100	A1	9/2006	Eskridge et al.	2009/0076506	A1	3/2009	Baker
2006/0206115	A1	9/2006	Schomer et al.	2009/0082716	A1	3/2009	Akahoshi
2006/0211943	A1	9/2006	Beaupre	2009/0112229	A1	4/2009	Omori et al.
2006/0217729	A1	9/2006	Eskridge et al.	2009/0118751	A1	5/2009	Wiener et al.
2006/0235306	A1	10/2006	Cotter et al.	2009/0118802	A1	5/2009	Mioduski et al.
2006/0247558	A1	11/2006	Yamada	2009/0138006	A1	5/2009	Bales et al.
2006/0253050	A1	11/2006	Yoshimine et al.	2009/0143799	A1	6/2009	Smith et al.
2006/0264809	A1	11/2006	Hansmann et al.	2009/0143800	A1	6/2009	Deville et al.
2006/0271030	A1	11/2006	Francis et al.	2009/0143806	A1	6/2009	Witt et al.
2007/0016235	A1	1/2007	Tanaka et al.	2009/0149801	A1	6/2009	Crandall et al.
2007/0016236	A1	1/2007	Beaupre	2009/0207923	A1	8/2009	Dress
				2009/0216157	A1	8/2009	Yamada
				2009/0223033	A1	9/2009	Houser
				2009/0254077	A1	10/2009	Craig
				2009/0254080	A1	10/2009	Honda

(56)

References Cited

U.S. PATENT DOCUMENTS

2009/0270771	A1	10/2009	Takahashi	2012/0177005	A1	7/2012	Liang et al.
2009/0270812	A1	10/2009	Litscher et al.	2012/0184946	A1	7/2012	Price et al.
2009/0270853	A1	10/2009	Yachi et al.	2012/0199630	A1	8/2012	Shelton, IV
2009/0270899	A1	10/2009	Carusillo et al.	2012/0199632	A1	8/2012	Spivey et al.
2009/0275940	A1	11/2009	Malackowski et al.	2012/0203143	A1	8/2012	Sanai et al.
2009/0318945	A1	12/2009	Yoshimine et al.	2012/0203247	A1	8/2012	Shelton, IV et al.
2009/0327715	A1	12/2009	Smith et al.	2012/0209289	A1	8/2012	Duque et al.
2010/0004508	A1	1/2010	Naito et al.	2012/0209303	A1	8/2012	Frankhouser et al.
2010/0016785	A1	1/2010	Takuma	2012/0210223	A1	8/2012	Eppolito
2010/0016852	A1	1/2010	Manzo et al.	2012/0215220	A1	8/2012	Manzo et al.
2010/0022825	A1	1/2010	Yoshie	2012/0245582	A1	9/2012	Kimball et al.
2010/0030233	A1	2/2010	Whitman et al.	2012/0253370	A1	10/2012	Ross et al.
2010/0030248	A1	2/2010	Palmer et al.	2012/0265196	A1	10/2012	Turner et al.
2010/0036370	A1	2/2010	Mirel et al.	2012/0269676	A1	10/2012	Houser et al.
2010/0042077	A1	2/2010	Okada	2012/0330307	A1	12/2012	Ladtchow et al.
2010/0049180	A1	2/2010	Wells et al.	2013/0012957	A1	1/2013	Shelton, IV et al.
2010/0063525	A1	3/2010	Beaupre et al.	2013/0030433	A1	1/2013	Heard
2010/0063528	A1	3/2010	Beaupre	2013/0035680	A1	2/2013	Ben-Haim et al.
2010/0069940	A1	3/2010	Miller et al.	2013/0053840	A1	2/2013	Krapohl et al.
2010/0158307	A1	6/2010	Kubota et al.	2013/0072856	A1	3/2013	Frankhouser et al.
2010/0187283	A1	7/2010	Crainich et al.	2013/0072857	A1	3/2013	Frankhouser et al.
2010/0222714	A1	9/2010	Muir et al.	2013/0079762	A1	3/2013	Twomey et al.
2010/0228264	A1	9/2010	Robinson et al.	2013/0103023	A1	4/2013	Monson et al.
2010/0234906	A1	9/2010	Koh	2013/0103024	A1	4/2013	Monson et al.
2010/0262134	A1	10/2010	Jensen et al.	2013/0110145	A1	5/2013	Weitzman
2010/0274160	A1	10/2010	Yachi et al.	2013/0123776	A1	5/2013	Monson et al.
2010/0280407	A1	11/2010	Polster	2013/0123777	A1	5/2013	Monson et al.
2010/0292691	A1	11/2010	Brogna	2013/0123782	A1	5/2013	Trees et al.
2010/0298743	A1	11/2010	Nield et al.	2013/0123822	A1	5/2013	Wellman et al.
2010/0298851	A1	11/2010	Nield	2013/0131660	A1	5/2013	Monson et al.
2010/0331742	A1	12/2010	Masuda	2013/0165929	A1	6/2013	Muir et al.
2011/0004233	A1	1/2011	Muir et al.	2013/0211397	A1	8/2013	Parihar et al.
2011/0009850	A1	1/2011	Main et al.	2013/0217967	A1	8/2013	Mohr et al.
2011/0015631	A1	1/2011	Wiener et al.	2013/0226207	A1	8/2013	Stulen et al.
2011/0077648	A1	3/2011	Lee et al.	2013/0226208	A1	8/2013	Wiener et al.
2011/0087218	A1	4/2011	Boudreaux et al.	2013/0245659	A1	9/2013	Robertson et al.
2011/0112526	A1	5/2011	Fritz et al.	2013/0267975	A1	10/2013	Timm et al.
2011/0125151	A1	5/2011	Strauss et al.	2013/0274734	A1	10/2013	Maass et al.
2011/0125174	A1	5/2011	Babaev	2013/0282003	A1	10/2013	Messerly et al.
2011/0144806	A1	6/2011	Sandhu et al.	2013/0282038	A1	10/2013	Dannaher et al.
2011/0196399	A1	8/2011	Robertson et al.	2013/0282039	A1	10/2013	Wiener et al.
2011/0224689	A1	9/2011	Larkin et al.	2013/0285758	A1	10/2013	Aldridge et al.
2011/0238065	A1	9/2011	Hunt et al.	2013/0289591	A1	10/2013	Boudreaux et al.
2011/0257650	A1	10/2011	Deville et al.	2013/0296908	A1	11/2013	Schulte et al.
2011/0270126	A1	11/2011	Gunday et al.	2013/0338661	A1	12/2013	Behnke, II
2011/0290853	A1	12/2011	Shelton, IV et al.	2013/0345689	A1	12/2013	Ruddenklau et al.
2011/0290856	A1	12/2011	Shelton, IV et al.	2014/0005640	A1	1/2014	Shelton, IV et al.
2012/0004655	A1	1/2012	Kim et al.	2014/0005653	A1	1/2014	Shelton, IV et al.
2012/0022525	A1	1/2012	Dietz et al.	2014/0005656	A1	1/2014	Mucilli et al.
2012/0022530	A1	1/2012	Woodruff et al.	2014/0005661	A1	1/2014	Shelton, IV et al.
2012/0022583	A1	1/2012	Sugalski et al.	2014/0005662	A1	1/2014	Shelton, IV et al.
2012/0059289	A1	3/2012	Nield et al.	2014/0005667	A1	1/2014	Stulen et al.
2012/0065628	A1	3/2012	Naito	2014/0005668	A1	1/2014	Rhee et al.
2012/0071863	A1	3/2012	Lee et al.	2014/0005676	A1	1/2014	Shelton, IV et al.
2012/0078139	A1	3/2012	Aldridge et al.	2014/0005680	A1	1/2014	Shelton, IV et al.
2012/0078243	A1	3/2012	Worrell et al.	2014/0005681	A1	1/2014	Gee et al.
2012/0078244	A1	3/2012	Worrell et al.	2014/0005682	A1	1/2014	Worrell et al.
2012/0078247	A1	3/2012	Worrell et al.	2014/0005701	A1	1/2014	Olson et al.
2012/0078278	A1	3/2012	Bales, Jr. et al.	2014/0005702	A1	1/2014	Timm et al.
2012/0080332	A1	4/2012	Shelton, IV et al.	2014/0005703	A1	1/2014	Stulen et al.
2012/0101495	A1	4/2012	Young et al.	2014/0005704	A1	1/2014	Vakharia et al.
2012/0109159	A1	5/2012	Jordan et al.	2014/0005705	A1	1/2014	Weir et al.
2012/0116379	A1	5/2012	Yates et al.	2014/0005708	A1	1/2014	Shelton, IV et al.
2012/0116391	A1	5/2012	Houser et al.	2014/0005718	A1	1/2014	Shelton, IV et al.
2012/0116394	A1	5/2012	Timm et al.	2014/0012299	A1	1/2014	Stoddard et al.
2012/0116395	A1	5/2012	Madan et al.	2014/0066962	A1	3/2014	Robertson et al.
2012/0130256	A1	5/2012	Buyse et al.	2014/0087569	A1	3/2014	Lee
2012/0130365	A1	5/2012	McLawnhorn	2014/0107538	A1	4/2014	Wiener et al.
2012/0136354	A1	5/2012	Rupp	2014/0114327	A1	4/2014	Boudreaux et al.
2012/0138660	A1	6/2012	Shelton, IV	2014/0135804	A1	5/2014	Weisenburgh, II et al.
2012/0143211	A1	6/2012	Kishi	2014/0155921	A1	6/2014	Price et al.
2012/0150170	A1	6/2012	Buyse et al.	2014/0180280	A1	6/2014	Sigmon, Jr.
2012/0165816	A1	6/2012	Kersten et al.	2014/0243864	A1	8/2014	Voegele et al.
2012/0172873	A1	7/2012	Artale et al.	2014/0276738	A1	9/2014	Price et al.
2012/0172904	A1	7/2012	Muir et al.	2014/0276970	A1	9/2014	Messerly et al.
				2014/0336686	A1	11/2014	Houser et al.
				2015/0045819	A1	2/2015	Houser et al.
				2015/0066067	A1	3/2015	Stulen
				2015/0073460	A1	3/2015	Stulen

(56)

References Cited

U.S. PATENT DOCUMENTS

2015/0112335 A1 4/2015 Boudreaux et al.
 2015/0119914 A1 4/2015 Neurohr et al.
 2015/0119915 A1 4/2015 Neurohr et al.
 2015/0119916 A1 4/2015 Dietz et al.
 2015/0123348 A1 5/2015 Robertson et al.
 2015/0157355 A1 6/2015 Price et al.
 2015/0157356 A1 6/2015 Gee
 2015/0164533 A1 6/2015 Felder et al.
 2015/0164534 A1 6/2015 Felder et al.
 2015/0164535 A1 6/2015 Felder et al.
 2015/0164536 A1 6/2015 Czarnecki et al.
 2015/0164537 A1 6/2015 Cagle et al.
 2015/0164538 A1 6/2015 Aldridge et al.
 2015/0182251 A1 7/2015 Messerly et al.
 2015/0182276 A1 7/2015 Wiener et al.
 2015/0182277 A1 7/2015 Wiener et al.
 2015/0196318 A1 7/2015 Messerly et al.

FOREIGN PATENT DOCUMENTS

CN 1640365 A 7/2005
 CN 1694649 A 11/2005
 CN 1922563 A 2/2007
 CN 1951333 A 4/2007
 CN 101040799 A 9/2007
 CN 101467917 A 1/2009
 DE 3904558 A1 8/1990
 DE 9210327 U1 11/1992
 DE 4323585 A1 1/1995
 DE 19608716 C1 4/1997
 DE 20021619 U1 3/2001
 DE 10042606 A1 8/2001
 EP 0136855 B1 9/1984
 EP 0171967 A2 2/1986
 EP 1839599 A1 10/1987
 EP 0336742 A2 4/1989
 EP 0342448 A1 11/1989
 EP 0424685 B1 5/1991
 EP 0443256 A1 8/1991
 EP 0456470 A1 11/1991
 EP 0598976 A2 1/1994
 EP 0677275 A2 3/1995
 EP 0482195 B1 1/1996
 EP 0695535 A1 2/1996
 EP 0741996 A2 11/1996
 EP 0612570 B1 6/1997
 EP 1108394 A2 6/2001
 EP 0908148 B1 1/2002
 EP 1229515 A2 8/2002
 EP 1285634 A1 2/2003
 EP 0908155 B1 6/2003
 EP 0705570 B1 4/2004
 EP 0765637 B1 7/2004
 EP 0870473 B1 9/2005
 EP 0624346 B1 11/2005
 EP 1594209 A1 11/2005
 EP 1199044 B1 12/2005
 EP 1609428 A1 12/2005
 EP 1199043 B1 3/2006
 EP 1433425 B1 6/2006
 EP 1256323 B1 9/2006
 EP 1698289 A2 9/2006
 EP 1704824 A1 9/2006
 EP 1749479 A1 2/2007
 EP 1815950 A1 8/2007
 EP 1844720 A1 10/2007
 EP 1862133 A1 12/2007
 EP 1875875 A1 1/2008
 EP 1199045 B1 6/2008
 EP 1964530 A1 9/2008
 EP 1972264 A1 9/2008
 EP 1974771 A1 10/2008
 EP 1435852 B1 12/2008
 EP 1498082 B1 12/2008

EP 1707131 B1 12/2008
 EP 1997438 A2 12/2008
 EP 1477104 B1 1/2009
 EP 2014218 A2 1/2009
 EP 2042112 A2 4/2009
 EP 1832259 B1 6/2009
 EP 2074959 A1 7/2009
 EP 2106758 A1 10/2009
 EP 2111813 A1 10/2009
 EP 2200145 A1 6/2010
 EP 1214913 B1 7/2010
 EP 2238938 A1 10/2010
 EP 2298154 A2 3/2011
 EP 1510178 B1 6/2011
 EP 2305144 A1 6/2011
 EP 2335630 A1 6/2011
 EP 1502551 B1 7/2011
 EP 2361562 A1 8/2011
 EP 2365608 A2 9/2011
 EP 2422721 A2 2/2012
 EP 1927321 B1 4/2012
 EP 2510891 A1 10/2012
 EP 2316359 B1 3/2013
 EP 1586275 B1 5/2013
 EP 1616529 B1 9/2013
 EP 2583633 B1 10/2014
 GB 1482943 A 8/1977
 GB 2032221 A 4/1980
 GB 2379878 B 11/2004
 GB 2447767 B 8/2011
 JP S 50-100891 12/1973
 JP S 59-68513 10/1982
 JP S 59141938 A 8/1984
 JP 62-221343 A 9/1987
 JP S 62-227343 10/1987
 JP 62-292153 A 12/1987
 JP S 62-292154 A 12/1987
 JP 63-109386 A 5/1988
 JP 63-315049 A 12/1988
 JP H 01-151452 A 6/1989
 JP H 01-198540 A 8/1989
 JP 02-71510 U 5/1990
 JP 2-286149 A 11/1990
 JP H 02-292193 A 12/1990
 JP H 03-37061 A 2/1991
 JP 04-25707 U 2/1992
 JP H 04-64351 A 2/1992
 JP 4-30508 U 3/1992
 JP H 04-150847 A 5/1992
 JP H 04-152942 A 5/1992
 JP 05-095955 A 4/1993
 JP H 05-115490 A 5/1993
 JP H 06-070938 A 3/1994
 JP 6-104503 A 4/1994
 JP 6-507081 A 8/1994
 JP H 06-217988 A 8/1994
 JP H 7-508910 A 10/1995
 JP 7-308323 A 11/1995
 JP 8-24266 A 1/1996
 JP 8-275951 A 10/1996
 JP H 08-299351 A 11/1996
 JP H 08-336545 A 12/1996
 JP H 09-503146 A 3/1997
 JP H 09-135553 A 5/1997
 JP H 09-140722 A 6/1997
 JP H 10-005237 A 1/1998
 JP 10-295700 A 11/1998
 JP H 11-501543 A 2/1999
 JP H 11-128238 A 5/1999
 JP H 11-192235 A 7/1999
 JP 11-253451 A 9/1999
 JP H 11-318918 A 11/1999
 JP 2000-041991 A 2/2000
 JP 2000-070279 A 3/2000
 JP 2000-210299 A 8/2000
 JP 2000-287987 A 10/2000
 JP 2001-029353 A 2/2001
 JP 2001-502216 A 2/2001
 JP 2003612 A 6/2001

(56)

References Cited

FOREIGN PATENT DOCUMENTS

JP	2001-309925	A	11/2001
JP	2002-186901	A	7/2002
JP	2002-204808	A	7/2002
JP	2002-263579	A	9/2002
JP	2002-301086	A	10/2002
JP	2002-330977	A	11/2002
JP	2002-542690	A	12/2002
JP	2003-000612	A	1/2003
JP	2003-010201	A	1/2003
JP	2003-510158	A	3/2003
JP	2003-116870	A	4/2003
JP	2003-126110	A	5/2003
JP	2003-310627	A	5/2003
JP	2003-530921	A	10/2003
JP	2003-339730	A	12/2003
JP	2004-147701	A	5/2004
JP	2005027026	A	1/2005
JP	2005-040222	A	2/2005
JP	2005-066316	A	3/2005
JP	2005-074088	A	3/2005
JP	2005-534451	A	11/2005
JP	2006-6410	A	1/2006
JP	2006-512149	A	4/2006
JP	2006-116194	A	5/2006
JP	2006-158525	A	6/2006
JP	2006-218296	A	8/2006
JP	2006217716	A	8/2006
JP	2006-288431	A	10/2006
JP	2007-050181	A	3/2007
JP	2003-126104	A	5/2007
JP	2007-229454	A	9/2007
JP	2007-527747	A	10/2007
JP	2008-508065	A	3/2008
JP	2008-119250	A	5/2008
JP	2008-521503	A	6/2008
JP	2008-212679	A	9/2008
JP	2008-536562	A	9/2008
JP	2008-284374	A	11/2008
JP	2009-511206	A	3/2009
JP	2009-517181	A	4/2009
JP	4262923	B2	5/2009
JP	2009-523567	A	6/2009
JP	2009-236177	A	10/2009
JP	2009-254819	A	11/2009
JP	2010-000336	A	1/2010
JP	2010-514923	A	5/2010
JP	2010-534522	A	11/2010
JP	2010-540186	A	12/2010
JP	2011-505198	A	2/2011
JP	2012-235658	A	11/2012
JP	5208761	B2	6/2013
WO	WO 92/22259	A2	12/1992
WO	WO 93/08757	A1	5/1993
WO	WO 93/14708	A1	8/1993
WO	WO 93/16646	A1	9/1993
WO	WO 93/20877	A1	10/1993
WO	WO 94/21183	A1	9/1994
WO	WO 94/24949	A1	11/1994
WO	WO 95/09572	A1	4/1995
WO	WO 96/30885	A1	10/1996
WO	WO 96/39086	A1	12/1996
WO	WO 98/16156	A1	4/1998
WO	WO 98/26739	A1	6/1998
WO	WO 98/35621	A1	8/1998
WO	WO 98/37815	A1	9/1998
WO	WO 99/20213	A1	4/1999
WO	WO 99/52489	A1	10/1999
WO	WO 00/64358	A2	11/2000
WO	WO 00/74585	A2	12/2000
WO	WO 01/54590	A1	8/2001
WO	WO 01/67970	A1	9/2001
WO	WO 01/95810	A2	12/2001
WO	WO 02/24080	A2	3/2002
WO	WO 02/38057	A1	5/2002
WO	WO 02/062241	A1	8/2002

WO	WO 03/082133	A1	10/2003
WO	WO 2004/012615	A1	2/2004
WO	WO 2004/026104	A2	4/2004
WO	WO 2004/032754	A2	4/2004
WO	WO 2004/032762	A1	4/2004
WO	WO 2004/032763	A2	4/2004
WO	WO 2004/037095	A2	5/2004
WO	WO 2004/098426	A1	11/2004
WO	WO 2004/112618	A2	12/2004
WO	WO 2005/122917	A1	12/2005
WO	WO 2006/012797	A1	2/2006
WO	WO 2006/042210	A2	4/2006
WO	WO 2006/058223	A2	6/2006
WO	WO 2006/063199	A2	6/2006
WO	WO 2006/083988	A1	8/2006
WO	WO 2006/119139	A2	11/2006
WO	WO 2006/119376	A2	11/2006
WO	WO 2006/129465	A1	12/2006
WO	WO 2007/008703	A2	1/2007
WO	WO 2007/008710	A2	1/2007
WO	WO 2007/040818	A1	4/2007
WO	WO 2007/047380	A2	4/2007
WO	WO 2007/047531	A2	4/2007
WO	WO 2007/056590	A1	5/2007
WO	WO 2007/087272	A2	8/2007
WO	WO 2007/143665	A2	12/2007
WO	WO 2008/016886	A2	2/2008
WO	WO 2008/042021	A1	4/2008
WO	WO 2008/049084	A2	4/2008
WO	WO 2008/051764	A2	5/2008
WO	WO 2008/089174	A2	7/2008
WO	WO 2008/118709	A1	10/2008
WO	WO 2008/130793	A1	10/2008
WO	WO 2009/018067	A1	2/2009
WO	WO 2009/018406	A2	2/2009
WO	WO 2009/027065	A1	3/2009
WO	WO 2009/046234	A2	4/2009
WO	WO 2009/073402	A2	6/2009
WO	WO 2009/120992	A2	10/2009
WO	WO 2010/068783	A1	6/2010
WO	WO 2011/008672	A2	1/2011
WO	WO 2011/052939	A2	5/2011
WO	WO 2011/100321	A2	8/2011
WO	WO 2011/144911	A1	11/2011
WO	WO 2012/061722	A2	5/2012
WO	WO 2012/128362	A1	9/2012
WO	WO 2012/135705	A1	10/2012
WO	WO 2012/135721	A1	10/2012
WO	WO 2013/018934	A1	2/2013
WO	WO 2013/062978	A2	5/2013

OTHER PUBLICATIONS

Technology Overview, printed from www.harmonicscalpel.com, Internet site, website accessed on Jun. 13, 2007, (3 pages).

Sheritt et al., "Novel Horn Designs for Ultrasonic/Sonic Cleaning Welding, Soldering, Cutting and Drilling," Proc. SPIE Smart Structures Conference, vol. 4701, Paper No. 34, San Diego, CA, pp. 353-360, Mar. 2002.

AST Products, Inc., "Principles of Video Contact Angle Analysis," 20 pages, (2006).

Lim et al., "A Review of Mechanism Used in Laparoscopic Surgical Instruments," Mechanism and Machine Theory, vol. 38, pp. 1133-1147, (2003).

Gooch et al., "Recommended Infection-Control Practices for Dentistry, 1993," Published: May 28, 1993; [retrieved on Aug. 23, 2008]. Retrieved from the internet: URL: <http://wonder.cdc.gov/wonder/prevguid/p0000191/p0000191.asp> (15 pages).

Huston et al., "Magnetic and Magnetostrictive Properties of Cube Textured Nickel for Magnetostrictive Transducer Applications," IEEE Transactions on Magnetics, vol. 9(4), pp. 636-640 (Dec. 1973).

Incropera et al., "Fundamentals of Heat and Mass Transfer", Wiley, New York (1990). (Book—not attached).

F. A. Duck, "Optical Properties of Tissue Including Ultraviolet and Infrared Radiation," pp. 43-71 in *Physical Properties of Tissue* (1990).

Orr et al., "Overview of Bioheat Transfer," pp. 367-384 in *Optical-Thermal Response of Laser-Irradiated Tissue*, A. J. Welch and M. J. C. van Gemert, eds., Plenum, New York (1995).

(56)

References Cited

OTHER PUBLICATIONS

Campbell et al, "Thermal Imaging in Surgery," p. 19-3, in *Medical Infrared Imaging*, N. A. Diakides and J. D. Bronzino, Eds. (2008).

Sullivan, "Cost-Constrained Selection of Strand Diameter and Number in a Litz-Wire Transformer Winding," IEEE Transactions on Power Electronics, vol. 16, No. 2, Mar. 2001, pp. 281-288.

Sullivan, "Optimal Choice for Number of Strands in a Litz-Wire Transformer Winding," IEEE Transactions on Power Electronics, vol. 14, No. 2, Mar. 1999, pp. 283-291.

Graff, K.F., "Elastic Wave Propagation in a Curved Sonic Transmission Line," IEEE Transactions on Sonics and Ultrasonics, SU-17(1), 1-6 (1970).

Makarov, S. N., Ochmann, M., Desinger, K., "The longitudinal vibration response of a curved fiber used for laser ultrasound surgical therapy," Journal of the Acoustical Society of America 102, 1191-1199 (1997).

Morley, L. S. D., "Elastic Waves in a Naturally Curved Rod," Quarterly Journal of Mechanics and Applied Mathematics, 14: 155-172 (1961).

Walsh, S. J., White, R. G., "Vibrational Power Transmission in Curved Beams," Journal of Sound and Vibration, 233(3), 455-488 (2000).

<http://www.apicalinstr.com/generators.htm>.

<http://www.dotmed.com/listing/electrosurgical-unit/ethicon/ultracision-g110-/1466724>.

<http://www.ethicon.com/gb-en/healthcare-professionals/products/energy-devices/capital/ge...>

<http://www.4-traders.com/JOHNSON-JOHNSON-4832/news/Johnson-Johnson-Ethicon-E...>

<http://www.medicalexpo.com/medical-manufacturer/electrosurgical-generator-6951.html>.

http://www.megadyne.com/es_generator.php.

<http://www.valleylab.com/product/es/generators/index.html>.


Covidien 501(k) Summary Sonication, dated Feb. 24, 2011 (7 pages).

Gerhard, Glen C., "Surgical Electrotechnology: Quo Vadis?," Biomedical Engineering, IEEE Transactions on, vol. BME-31, No. 12, pp. 787, 792, Dec. 1984.

Fowler, K.R., "A programmable, arbitrary waveform electrosurgical device," Engineering in Medicine and Biology Society, 1988. Proceedings of the Annual International Conference of the IEEE, vol., No., pp. 1324, 1325 vol. 3, Nov. 4-7, 1988.

LaCourse, J.R.; Vogt, M.C.; Miller, W.T., III; Selikowitz, S.M., "Spectral analysis interpretation of electro-surgical generator nerve and muscle stimulation," Biomedical Engineering, IEEE Transactions on, vol. 35, No. 7, pp. 505, 509, Jul. 1988.

U.S. Appl. No. 13/751,680, filed Jan. 28, 2013.






FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 7




FIG. 6




FIG. 8




FIG. 9





FIG. 10






FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18A




FIG. 18B




FIG. 18C




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23





FIG. 24






FIG. 26




FIG. 27






FIG. 28






FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36





FIG. 37






FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46A




FIG. 46B




FIG. 46C




FIG. 47




FIG. 48




FIG. 49

LOCKOUT MECHANISM FOR USE WITH ROBOTIC ELECTROSURGICAL DEVICE

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is related to the following, concurrently-filed U.S. patent applications, which are incorporated herein by reference in their entirety:

U.S. application Ser. No. 13/539,096, entitled "Haptic Feedback Devices for Surgical Robot,";

U.S. application Ser. No. 13/539,117, entitled "Closed Feedback Control for Electrosurgical Device,";

U.S. application Ser. No. 13/538,588, entitled "Surgical Instruments with Articulating Shafts,";

U.S. application Ser. No. 13/538,601, entitled "Ultrasonic Surgical Instruments with Distally Positioned Transducers,";

U.S. application Ser. No. 13/538,700, entitled "Surgical Instruments with Articulating Shafts,";

U.S. application Ser. No. 13/538,711, entitled "Ultrasonic Surgical Instruments with Distally Positioned Jaw Assemblies,";

U.S. application Ser. No. 13/538,720, entitled "Surgical Instruments with Articulating Shafts,";

U.S. application Ser. No. 13/538,733, entitled "Ultrasonic Surgical Instruments with Control Mechanisms,"; and

U.S. application Ser. No. 13/539,122, entitled "Surgical Instruments with Fluid Management System,".

BACKGROUND

The present disclosure relates generally to the field of robotic surgery. In particular, the present disclosure relates to, although not exclusively, robotically controlled surgical instruments. More particularly, the present disclosure relates to, although not exclusively, lockout mechanism for use with electrosurgical and ultrasonic robotic surgical instruments.

Ultrasonic surgical devices, such as ultrasonic scalpels, are used in many applications in surgical procedures by virtue of their unique performance characteristics. Depending upon specific device configurations and operational parameters, ultrasonic surgical devices can provide substantially simultaneous transection of tissue and homeostasis by coagulation, desirably minimizing patient trauma. An ultrasonic surgical device comprises a proximally-positioned ultrasonic transducer and an instrument coupled to the ultrasonic transducer having a distally-mounted end effector comprising an ultrasonic blade to cut and seal tissue. The end effector is typically coupled either to a handle and/or a robotic surgical implement via a shaft. The blade is acoustically coupled to the transducer via a waveguide extending through the shaft. Ultrasonic surgical devices of this nature can be configured for open surgical use, laparoscopic, or endoscopic surgical procedures including robotic-assisted procedures.

Ultrasonic energy cuts and coagulates tissue using temperatures lower than those used in electrosurgical procedures. Vibrating at high frequencies (e.g., 55,500 times per second), the ultrasonic blade denatures protein in the tissue to form a sticky coagulum. Pressure exerted on tissue by the blade surface collapses blood vessels and allows the coagulum to form a haemostatic seal. A surgeon can control the cutting speed and coagulation by the force applied to the tissue by the end effector, the time over which the force is applied and the selected excursion level of the end effector.

Also used in many surgical applications are electrosurgical devices. Electrosurgical devices apply electrical energy to tissue in order to treat tissue. An electrosurgical device may

comprise an instrument having a distally-mounted end effector comprising one or more electrodes. The end effector can be positioned against tissue such that electrical current is introduced into the tissue. Electrosurgical devices can be configured for bipolar or monopolar operation. During bipolar operation, current is introduced into and returned from the tissue by active and return electrodes, respectively, of the end effector. During monopolar operation, current is introduced into the tissue by an active electrode of the end effector and returned through a return electrode (e.g., a grounding pad) separately located on a patient's body. Heat generated by the current flow through the tissue may form hemostatic seals within the tissue and/or between tissues and thus may be particularly useful for sealing blood vessels, for example. The end effector of an electrosurgical device sometimes also comprises a cutting member that is movable relative to the tissue and the electrodes to transect the tissue.

Electrical energy applied by an electrosurgical device can be transmitted to the instrument by a generator. The electrical energy may be in the form of radio frequency ("RF") energy. RF energy is a form of electrical energy that may be in the frequency range of 300 kHz to 1 MHz. During its operation, an electrosurgical device can transmit low frequency RF energy through tissue, which causes ionic agitation, or friction, in effect resistive heating, thereby increasing the temperature of the tissue. Because a sharp boundary may be created between the affected tissue and the surrounding tissue, surgeons can operate with a high level of precision and control, without sacrificing un-targeted adjacent tissue. The low operating temperatures of RF energy may be useful for removing, shrinking, or sculpting soft tissue while simultaneously sealing blood vessels. RF energy may work particularly well on connective tissue, which is primarily comprised of collagen and shrinks when contacted by heat.

In many cases, it is desirable to prevent a cutting member from moving prior to the application of electrosurgical or ultrasonic energy to the blade element. In a robotic surgical system, a surgeon is typically not in the room with the patient and is unable to visually verify that energy has been applied to surgical instrument prior to activating the cutting member. It would be desirable to provide a mechanism for robotic surgical systems to prevent actuation of a cutting member prior to the application of electrosurgical or ultrasonic energy.

SUMMARY

In one embodiment, a robotically controlled surgical tool comprising including a lockout mechanism is provided. The surgical tool may comprise an instrument mounting portion. The instrument mounting portion includes a housing, a plate, a shaft assembly comprising an end effector, and a coupler to couple the shaft assembly to the instrument mounting portion. The end effector comprises a first jaw member and a second jaw member, the first and second jaw members defining a channel therebetween, and a blade slideably receivable within the channel to cut tissue located between the first and second jaw members. The surgical tool may include an actuation mechanism to actuate the end effector to provide reciprocating movement of the blade within the channel. A lockout mechanism is coupled to the actuation mechanism. The lockout mechanism may selectively enable reciprocating movement of the blade. An interface mechanically and electrically couples the instrument mounting portion to a robotic manipulator.

BRIEF DESCRIPTION OF THE FIGURES

The features of the various embodiments are set forth with particularity in the appended claims. The various embodi-

ments, however, both as to organization and methods of operation, together with advantages thereof, may best be understood by reference to the following description, taken in conjunction with the accompanying drawings as follows:

FIG. 1 illustrates one embodiment of a surgical system including a surgical instrument and an ultrasonic generator.

FIG. 2 illustrates one embodiment of the surgical instrument shown in FIG. 1.

FIG. 3 illustrates one embodiment of an ultrasonic end effector.

FIG. 4 illustrates another embodiment of an ultrasonic end effector.

FIG. 5 illustrates an exploded view of one embodiment of the surgical instrument shown in FIG. 1.

FIG. 6 illustrates a cut-away view of one embodiment of the surgical instrument shown in FIG. 1.

FIG. 7 illustrates various internal components of the surgical instrument shown in FIG. 1.

FIG. 8 illustrates a top view of one embodiment of a surgical system including a surgical instrument and an ultrasonic generator.

FIG. 9 illustrates one embodiment of a rotation assembly included in one example embodiment of the surgical instrument of FIG. 1.

FIG. 10 illustrates one embodiment of a surgical system including a surgical instrument having a single element end effector.

FIG. 11 is a perspective view of one embodiment of an electrical energy surgical instrument.

FIG. 12 is a side view of a handle of one embodiment of the surgical instrument of FIG. 1 with a half of a handle body removed to illustrate some of the components therein.

FIG. 13 illustrates a perspective view of one embodiment of the end effector of the surgical instrument of FIG. 11 with the jaws open and the distal end of an axially movable member in a retracted position.

FIG. 14 illustrates a perspective view of one embodiment of the end effector of the surgical instrument of FIG. 11 with the jaws closed and the distal end of an axially movable member in a partially advanced position.

FIG. 15 illustrates a perspective view of one embodiment of the axially moveable member of the surgical instrument of FIG. 11.

FIG. 16 illustrates a section view of one embodiment of the end effector of the surgical instrument of FIG. 11.

FIG. 17 illustrates a section a perspective view of one embodiment of a cordless electrical energy surgical instrument.

FIG. 18A illustrates a side view of a handle of one embodiment of the surgical instrument of FIG. 17 with a half handle body removed to illustrate various components therein.

FIG. 18B illustrates an RF drive and control circuit, according to one embodiment.

FIG. 18C illustrates the main components of the controller, according to one embodiment.

FIG. 19 illustrates a block diagram of one embodiment of a robotic surgical system.

FIG. 20 illustrates one embodiment of a robotic arm cart.

FIG. 21 illustrates one embodiment of the robotic manipulator of the robotic arm cart of FIG. 20.

FIG. 22 illustrates one embodiment of a robotic arm cart having an alternative set-up joint structure.

FIG. 23 illustrates one embodiment of a controller that may be used in conjunction with a robotic arm cart, such as the robotic arm carts of FIGS. 19-22.

FIG. 24 illustrates one embodiment of an ultrasonic surgical instrument adapted for use with a robotic system.

FIG. 25 illustrates one embodiment of an electrosurgical instrument adapted for use with a robotic system.

FIG. 26 illustrates one embodiment of an instrument drive assembly that may be coupled to surgical manipulators to receive and control the surgical instrument shown in FIG. 24.

FIG. 27 illustrates another view of the instrument drive assembly embodiment of FIG. 26 including the surgical instrument of FIG. 24.

FIG. 28 illustrates another view of the instrument drive assembly embodiment of FIG. 26 including the electrosurgical instrument of FIG. 25.

FIGS. 29-31 illustrate additional views of the adapter portion of the instrument drive assembly of FIG. 26.

FIGS. 32-34 illustrate one embodiment of the instrument mounting portion of FIGS. 24-25 showing components for translating motion of the driven elements into motion of the surgical instrument.

FIGS. 35-37 illustrate an alternate embodiment of the instrument mounting portion of FIGS. 24-25 showing an alternate example mechanism for translating rotation of the driven elements into rotational motion about the axis of the shaft and an alternate example mechanism for generating reciprocating translation of one or more members along the axis of the shaft 538.

FIGS. 38-42 illustrate an alternate embodiment of the instrument mounting portion FIGS. 24-25 showing another alternate example mechanism for translating rotation of the driven elements into rotational motion about the axis of the shaft.

FIGS. 43-46A illustrate an alternate embodiment of the instrument mounting portion showing an alternate example mechanism for differential translation of members along the axis of the shaft (e.g., for articulation).

FIGS. 46B-46C illustrate one embodiment of a tool mounting portion comprising internal power and energy sources.

FIG. 47 illustrates one embodiment of an instrument mounting portion comprising a lockout mechanism and an end of stroke switch.

FIG. 48 illustrates one embodiment of the lockout mechanism interfaced with a first gear and the end-of-stroke switch interfaced with a second gear.

FIG. 49 illustrates one embodiment of the lockout mechanism interfaced with a worm gear mounted to the shaft assembly.

DESCRIPTION

Various example embodiments are directed to a control system for a robotic surgical system.

Various embodiments of surgical instruments and robotic surgical systems are described herein. It will be understood by those skilled in the art that the various embodiments of the surgical tool lockout mechanism may be used with the described surgical instruments and robotic surgical systems. The descriptions are provided for example only, and those skilled in the art will understand that the disclosed surgical tool lockout mechanism is not limited to only the devices disclosed herein, but may be used with any compatible surgical instrument or robotic surgical system.

Reference will now be made in detail to several embodiments, including embodiments showing example implementations of robotic surgical instruments with end effectors comprising ultrasonic and/or electrosurgical elements. Wherever practicable similar or like reference numbers may be used in the figures and may indicate similar or like functionality. The figures depict example embodiments of the methods of use for purposes of illustration only. One skilled in the

art will readily recognize from the following description that alternative example embodiments of the structures and methods illustrated herein may be employed without departing from the principles described herein.

FIG. 1 is a right side view of one embodiment of an ultrasonic surgical instrument 10. In the illustrated embodiment, the ultrasonic surgical instrument 10 may be employed in various surgical procedures including endoscopic or traditional open surgical procedures. In one example embodiment, the ultrasonic surgical instrument 10 comprises a handle assembly 12, an elongated shaft assembly 14, and an ultrasonic transducer 16. The handle assembly 12 comprises a trigger assembly 24, a distal rotation assembly 13, and a switch assembly 28. The elongated shaft assembly 14 comprises an end effector assembly 26, which comprises elements to dissect tissue or mutually grasp, cut, and coagulate vessels and/or tissue, and actuating elements to actuate the end effector assembly 26. The handle assembly 12 is adapted to receive the ultrasonic transducer 16 at the proximal end. The ultrasonic transducer 16 is mechanically engaged to the elongated shaft assembly 14 and portions of the end effector assembly 26. The ultrasonic transducer 16 is electrically coupled to a generator 20 via a cable 22. Although the majority of the drawings depict a multiple end effector assembly 26 for use in connection with laparoscopic surgical procedures, the ultrasonic surgical instrument 10 may be employed in more traditional open surgical procedures and in other embodiments, and may be configured for use in endoscopic procedures. For the purposes herein, the ultrasonic surgical instrument 10 is described in terms of an endoscopic instrument; however, it is contemplated that an open and/or laparoscopic version of the ultrasonic surgical instrument 10 also may include the same or similar operating components and features as described herein.

In various embodiments, the generator 20 comprises several functional elements, such as modules and/or blocks. Different functional elements or modules may be configured for driving different kinds of surgical devices. For example, an ultrasonic generator module 21 may drive an ultrasonic device, such as the ultrasonic surgical instrument 10. In some example embodiments, the generator 20 also comprises an electrosurgery/RF generator module 23 for driving an electrosurgical device (or an electrosurgical embodiment of the ultrasonic surgical instrument 10). In various embodiments, the generator 20 may be formed integrally within the handle assembly 12. In such implementations, a battery would be co-located within the handle assembly 12 to act as the energy source. FIG. 18A and accompanying disclosures provide one example of such implementations.

In some embodiments, the electrosurgery/RF generator module 23 may be configured to generate a therapeutic and/or a sub-therapeutic energy level. In the example embodiment illustrated in FIG. 1, the generator 20 includes a control system 25 integral with the generator 20 and a foot switch 29 connected to the generator via a cable 27. The generator 20 may also comprise a triggering mechanism for activating a surgical instrument, such as the instrument 10. The triggering mechanism may include a power switch (not shown) as well as a foot switch 29. When activated by the foot switch 29, the generator 20 may provide energy to drive the acoustic assembly of the surgical instrument 10 and to drive the end effector 18 at a predetermined excursion level. The generator 20 drives or excites the acoustic assembly at any suitable resonant frequency of the acoustic assembly and/or derives the therapeutic/sub-therapeutic electromagnetic/RF energy.

In one embodiment, the electrosurgical/RF generator module 23 may be implemented as an electrosurgery unit (ESU)

capable of supplying power sufficient to perform bipolar electrosurgery using radio frequency (RF) energy. In one embodiment, the ESU can be a bipolar ERBE ICC 350 sold by ERBE USA, Inc. of Marietta, Ga. In bipolar electrosurgery applications, as previously discussed, a surgical instrument having an active electrode and a return electrode can be utilized, wherein the active electrode and the return electrode can be positioned against, or adjacent to, the tissue to be treated such that current can flow from the active electrode to the return electrode through the tissue. Accordingly, the electrosurgical/RF module 23 generator may be configured for therapeutic purposes by applying electrical energy to the tissue T sufficient for treating the tissue (e.g., cauterization).

In one embodiment, the electrosurgical/RF generator module 23 may be configured to deliver a sub-therapeutic RF signal to implement a tissue impedance measurement module. In one embodiment, the electrosurgical/RF generator module 23 comprises a bipolar radio frequency generator as described in more detail below. In one embodiment, the electrosurgical/RF generator module 12 may be configured to monitor electrical impedance Z, of tissue T and to control the characteristics of time and power level based on the tissue T by way of a return electrode on provided on a clamp member of the end effector assembly 26. Accordingly, the electrosurgical/RF generator module 23 may be configured for sub-therapeutic purposes for measuring the impedance or other electrical characteristics of the tissue T. Techniques and circuit configurations for measuring the impedance or other electrical characteristics of tissue T are discussed in more detail in commonly assigned U.S. Patent Publication No. 2011/0015631, titled "Electrosurgical Generator for Ultrasonic Surgical Instruments," the disclosure of which is herein incorporated by reference in its entirety.

A suitable ultrasonic generator module 21 may be configured to functionally operate in a manner similar to the GEN300 sold by Ethicon Endo-Surgery, Inc. of Cincinnati, Ohio as is disclosed in one or more of the following U.S. patents, all of which are incorporated by reference herein: U.S. Pat. No. 6,480,796 (Method for Improving the Start Up of an Ultrasonic System Under Zero Load Conditions); U.S. Pat. No. 6,537,291 (Method for Detecting Blade Breakage Using Rate and/or Impedance Information); U.S. Pat. No. 6,662,127 (Method for Detecting Presence of a Blade in an Ultrasonic System); U.S. Pat. No. 6,678,899 (Method for Detecting Transverse Vibrations in an Ultrasonic Surgical System); U.S. Pat. No. 6,977,495 (Detection Circuitry for Surgical Handpiece System); U.S. Pat. No. 7,077,853 (Method for Calculating Transducer Capacitance to Determine Transducer Temperature); U.S. Pat. No. 7,179,271 (Method for Driving an Ultrasonic System to Improve Acquisition of Blade Resonance Frequency at Startup); and U.S. Pat. No. 7,273,483 (Apparatus and Method for Alerting Generator Function in an Ultrasonic Surgical System).

It will be appreciated that in various embodiments, the generator 20 may be configured to operate in several modes. In one mode, the generator 20 may be configured such that the ultrasonic generator module 21 and the electrosurgical/RF generator module 23 may be operated independently. One example of the independent operations of the ultrasonic generator module 21 and the electrosurgical/RF generator module 23 from the generator 20 is shown in FIG. 1, with the modules 21 and 23 optionally placed outside of and coupled to the generator 20.

For example, the ultrasonic generator module 21 may be activated to apply ultrasonic energy to the end effector assembly 26 and subsequently, either therapeutic sub-therapeutic RF energy may be applied to the end effector assembly 26 by

the electrosurgical/RF generator module **23**. As previously discussed, the sub-therapeutic electrosurgical/RF energy may be applied to tissue clamped between claim elements of the end effector assembly **26** to measure tissue impedance to control the activation, or modify the activation, of the ultrasonic generator module **21**. Tissue impedance feedback from the application of the sub-therapeutic energy also may be employed to activate a therapeutic level of the electrosurgical/RF generator module **23** to seal the tissue (e.g., vessel) clamped between claim elements of the end effector assembly **26**.

In another embodiment, the ultrasonic generator module **21** and the electrosurgical/RF generator module **23** may be activated simultaneously. In one example, the ultrasonic generator module **21** is simultaneously activated with a sub-therapeutic RF energy level to measure tissue impedance simultaneously while the ultrasonic blade of the end effector assembly **26** cuts and coagulates the tissue (or vessel) clamped between the clamp elements of the end effector assembly **26**. Such feedback may be employed, for example, to modify the drive output of the ultrasonic generator module **21**. In another example, the ultrasonic generator module **21** may be driven simultaneously with electrosurgical/RF generator module **23** such that the ultrasonic blade portion of the end effector assembly **26** is employed for cutting the damaged tissue while the electrosurgical/RF energy is applied to electrode portions of the end effector clamp assembly **26** for sealing the tissue (or vessel).

When the generator **20** is activated via the triggering mechanism, electrical energy is continuously applied by the generator **20** to a transducer stack or assembly of the acoustic assembly. A phase-locked loop in the control system of the generator **20** may monitor feedback from the acoustic assembly. In another embodiment, electrical energy is intermittently applied (e.g., pulsed) by the generator **20**. The phase lock loop adjusts the frequency of the electrical energy sent by the generator **20** to match the resonant frequency of the selected longitudinal mode of vibration of the acoustic assembly. In addition, a second feedback loop in the control system **25** maintains the electrical current supplied to the acoustic assembly at a pre-selected constant level in order to achieve substantially constant excursion at the end effector **18** of the acoustic assembly. In yet another embodiment, a third feedback loop in the control system **25** monitors impedance between electrodes located in the end effector assembly **26**. Although FIGS. 1-9 show a manually operated ultrasonic surgical instrument, it will be appreciated that ultrasonic surgical instruments may also be used in robotic applications, for example, as described herein, as well as combinations of manual robotic applications.

In ultrasonic operation mode, the electrical signal supplied to the acoustic assembly may cause the distal end of the end effector **18**, to vibrate longitudinally in the range of, for example, approximately 20 kHz to 250 kHz. According to various embodiments, the blade **22** may vibrate in the range of about 54 kHz to 56 kHz, for example, at about 55.5 kHz. In other embodiments, the blade **22** may vibrate at other frequencies including, for example, about 31 kHz or about 80 kHz. The excursion of the vibrations at the blade can be controlled by, for example, controlling the amplitude of the electrical signal applied to the transducer assembly of the acoustic assembly by the generator **20**. As noted above, the triggering mechanism of the generator **20** allows a user to activate the generator **20** so that electrical energy may be continuously or intermittently supplied to the acoustic assembly. The generator **20** also has a power line for insertion in an electro-surgical unit or conventional electrical outlet. It is

contemplated that the generator **20** can also be powered by a direct current (DC) source, such as a battery. The generator **20** can comprise any suitable generator, such as Model No. GEN04, and/or Model No. GEN11 available from Ethicon Endo-Surgery, Inc.

FIG. 2 is a left perspective view of one example embodiment of the ultrasonic surgical instrument **10** showing the handle assembly **12**, the distal rotation assembly **13**, the elongated shaft assembly **14**, and the end effector assembly **26**. In the illustrated embodiment the elongated shaft assembly **14** comprises a distal end **52** dimensioned to mechanically engage the end effector assembly **26** and a proximal end **50** that mechanically engages the handle assembly **12** and the distal rotation assembly **13**. The proximal end **50** of the elongated shaft assembly **14** is received within the handle assembly **12** and the distal rotation assembly **13**. More details relating to the connections between the elongated endoscopic shaft assembly **14**, the handle assembly **12**, and the distal rotation assembly **13** are provided in the description of FIGS. 5 and 7.

In the illustrated embodiment, the trigger assembly **24** comprises a trigger **32** that operates in conjunction with a fixed handle **34**. The fixed handle **34** and the trigger **32** are ergonomically formed and adapted to interface comfortably with the user. The fixed handle **34** is integrally associated with the handle assembly **12**. The trigger **32** is pivotally movable relative to the fixed handle **34** as explained in more detail below with respect to the operation of the ultrasonic surgical instrument **10**. The trigger **32** is pivotally movable in direction **33A** toward the fixed handle **34** when the user applies a squeezing force against the trigger **32**. A spring element **98** (FIG. 5) causes the trigger **32** to pivotally move in direction **33B** when the user releases the squeezing force against the trigger **32**.

In one example embodiment, the trigger **32** comprises an elongated trigger hook **36**, which defines an aperture **38** between the elongated trigger hook **36** and the trigger **32**. The aperture **38** is suitably sized to receive one or multiple fingers of the user therethrough. The trigger **32** also may comprise a resilient portion **32a** molded over the trigger **32** substrate. The overmolded resilient portion **32a** is formed to provide a more comfortable contact surface for control of the trigger **32** in outward direction **33B**. In one example embodiment, the overmolded resilient portion **32a** may be provided over a portion of the elongated trigger hook **36**. The proximal surface of the elongated trigger hook **32** remains uncoated or coated with a non-resilient substrate to enable the user to easily slide their fingers in and out of the aperture **38**. In another embodiment, the geometry of the trigger forms a fully closed loop which defines an aperture suitably sized to receive one or multiple fingers of the user therethrough. The fully closed loop trigger also may comprise a resilient portion molded over the trigger substrate.

In one example embodiment, the fixed handle **34** comprises a proximal contact surface **40** and a grip anchor or saddle surface **42**. The saddle surface **42** rests on the web where the thumb and the index finger are joined on the hand. The proximal contact surface **40** has a pistol grip contour that receives the palm of the hand in a normal pistol grip with no rings or apertures. The profile curve of the proximal contact surface **40** may be contoured to accommodate or receive the palm of the hand. A stabilization tail **44** is located towards a more proximal portion of the handle assembly **12**. The stabilization tail **44** may be in contact with the uppermost web portion of the hand located between the thumb and the index finger to stabilize the handle assembly **12** and make the handle assembly **12** more controllable.

In one example embodiment, the switch assembly 28 may comprise a toggle switch 30. The toggle switch 30 may be implemented as a single component with a central pivot 304 located within inside the handle assembly 12 to eliminate the possibility of simultaneous activation. In one example embodiment, the toggle switch 30 comprises a first projecting knob 30a and a second projecting knob 30b to set the power setting of the ultrasonic transducer 16 between a minimum power level (e.g., MIN) and a maximum power level (e.g., MAX). In another embodiment, the rocker switch may pivot between a standard setting and a special setting. The special setting may allow one or more special programs to be implemented by the device. The toggle switch 30 rotates about the central pivot as the first projecting knob 30a and the second projecting knob 30b are actuated. The one or more projecting knobs 30a, 30b are coupled to one or more arms that move through a small arc and cause electrical contacts to close or open an electric circuit to electrically energize or de-energize the ultrasonic transducer 16 in accordance with the activation of the first or second projecting knobs 30a, 30b. The toggle switch 30 is coupled to the generator 20 to control the activation of the ultrasonic transducer 16. The toggle switch 30 comprises one or more electrical power setting switches to activate the ultrasonic transducer 16 to set one or more power settings for the ultrasonic transducer 16. The forces required to activate the toggle switch 30 are directed substantially toward the saddle point 42, thus avoiding any tendency of the instrument to rotate in the hand when the toggle switch 30 is activated.

In one example embodiment, the first and second projecting knobs 30a, 30b are located on the distal end of the handle assembly 12 such that they can be easily accessible by the user to activate the power with minimal, or substantially no, repositioning of the hand grip, making it suitable to maintain control and keep attention focused on the surgical site (e.g., a monitor in a laparoscopic procedure) while activating the toggle switch 30. The projecting knobs 30a, 30b may be configured to wrap around the side of the handle assembly 12 to some extent to be more easily accessible by variable finger lengths and to allow greater freedom of access to activation in awkward positions or for shorter fingers.

In the illustrated embodiment, the first projecting knob 30a comprises a plurality of tactile elements 30c, e.g., textured projections or "bumps" in the illustrated embodiment, to allow the user to differentiate the first projecting knob 30a (MAX) from the second projecting knob 30b (MIN). It will be appreciated by those skilled in the art that several ergonomic features may be incorporated into the handle assembly 12. Such ergonomic features are described in U.S. Pat. App. Pub. No. 2009/0105750 entitled "Ergonomic Surgical Instruments" which is incorporated by reference herein in its entirety.

In one example embodiment, the toggle switch 30 may be operated by the hand of the user. The user may easily access the first and second projecting knobs 30a, 30b at any point while also avoiding inadvertent or unintentional activation at any time. The toggle switch 30 may readily operated with a finger to control the power to the ultrasonic assembly 16 and/or to the ultrasonic assembly 16. For example, the index finger may be employed to activate the first contact portion 30a to turn on the ultrasonic assembly 16 to a maximum (MAX) power level. The index finger may be employed to activate the second contact portion 30b to turn on the ultrasonic assembly 16 to a minimum (MIN) power level. In another embodiment, the rocker switch may pivot the instrument 10 between a standard setting and a special setting. The special setting may allow one or more special programs to be

implemented by the instrument 10. The toggle switch 30 may be operated without the user having to look at the first or second projecting knob 30a, 30b. For example, the first projecting knob 30a or the second projecting knob 30b may comprise a texture or projections to tactilely differentiate between the first and second projecting knobs 30a, 30b without looking.

In other embodiments, the trigger 32 and/or the toggle switch 30 may be employed to actuate the electrosurgical/RF module 23 individually or in combination with activation of the ultrasonic generator module 21.

In one example embodiment, the distal rotation assembly 13 is rotatable without limitation in either direction about a longitudinal axis "T." The distal rotation assembly 13 is mechanically engaged to the elongated shaft assembly 14. The distal rotation assembly 13 is located on a distal end of the handle assembly 12. The distal rotation assembly 13 comprises a cylindrical hub 46 and a rotation knob 48 formed over the hub 46. The hub 46 mechanically engages the elongated shaft assembly 14. The rotation knob 48 may comprise fluted polymeric features and may be engaged by a finger (e.g., an index finger) to rotate the elongated shaft assembly 14. The hub 46 may comprise a material molded over the primary structure to form the rotation knob 48. The rotation knob 48 may be overmolded over the hub 46. The hub 46 comprises an end cap portion 46a that is exposed at the distal end. The end cap portion 46a of the hub 46 may contact the surface of a trocar during laparoscopic procedures. The hub 46 may be formed of a hard durable plastic such as polycarbonate to alleviate any friction that may occur between the end cap portion 46a and the trocar. The rotation knob 48 may comprise "scallops" or flutes formed of raised ribs 48a and concave portions 48b located between the ribs 48a to provide a more precise rotational grip. In one example embodiment, the rotation knob 48 may comprise a plurality of flutes (e.g., three or more flutes). In other embodiments, any suitable number of flutes may be employed. The rotation knob 48 may be formed of a softer polymeric material overmolded onto the hard plastic material. For example, the rotation knob 48 may be formed of pliable, resilient, flexible polymeric materials including Versaflex® TPE alloys made by GLS Corporation, for example. This softer overmolded material may provide a greater grip and more precise control of the movement of the rotation knob 48. It will be appreciated that any materials that provide adequate resistance to sterilization, are biocompatible, and provide adequate frictional resistance to surgical gloves may be employed to form the rotation knob 48.

In one example embodiment, the handle assembly 12 is formed from two (2) housing portions or shrouds comprising a first portion 12a and a second portion 12b. From the perspective of a user viewing the handle assembly 12 from the distal end towards the proximal end, the first portion 12a is considered the right portion and the second portion 12b is considered the left portion. Each of the first and second portions 12a, 12b includes a plurality of interfaces 69 (FIG. 7) dimensioned to mechanically align and engage each another to form the handle assembly 12 and enclosing the internal working components thereof. The fixed handle 34, which is integrally associated with the handle assembly 12, takes shape upon the assembly of the first and second portions 12a and 12b of the handle assembly 12. A plurality of additional interfaces (not shown) may be disposed at various points around the periphery of the first and second portions 12a and 12b of the handle assembly 12 for ultrasonic welding purposes, e.g., energy direction/deflection points. The first and second portions 12a and 12b (as well as the other components described below) may be assembled together in any fashion

known in the art. For example, alignment pins, snap-like interfaces, tongue and groove interfaces, locking tabs, adhesive ports, may all be utilized either alone or in combination for assembly purposes.

In one example embodiment, the elongated shaft assembly 14 comprises a proximal end 50 adapted to mechanically engage the handle assembly 12 and the distal rotation assembly 13; and a distal end 52 adapted to mechanically engage the end effector assembly 26. The elongated shaft assembly 14 comprises an outer tubular sheath 56 and a reciprocating tubular actuating member 58 located within the outer tubular sheath 56. The proximal end of the tubular reciprocating tubular actuating member 58 is mechanically engaged to the trigger 32 of the handle assembly 12 to move in either direction 60A or 60B in response to the actuation and/or release of the trigger 32. The pivotably moveable trigger 32 may generate reciprocating motion along the longitudinal axis "T." Such motion may be used, for example, to actuate the jaws or clamping mechanism of the end effector assembly 26. A series of linkages translate the pivotal rotation of the trigger 32 to axial movement of a yoke coupled to an actuation mechanism, which controls the opening and closing of the jaws of the clamping mechanism of the end effector assembly 26. The distal end of the tubular reciprocating tubular actuating member 58 is mechanically engaged to the end effector assembly 26. In the illustrated embodiment, the distal end of the tubular reciprocating tubular actuating member 58 is mechanically engaged to a clamp arm assembly 64, which is pivotable about a pivot point 70, to open and close the clamp arm assembly 64 in response to the actuation and/or release of the trigger 32. For example, in the illustrated embodiment, the clamp arm assembly 64 is movable in direction 62A from an open position to a closed position about a pivot point 70 when the trigger 32 is squeezed in direction 33A. The clamp arm assembly 64 is movable in direction 62B from a closed position to an open position about the pivot point 70 when the trigger 32 is released or outwardly contacted in direction 33B.

In one example embodiment, the end effector assembly 26 is attached at the distal end 52 of the elongated shaft assembly 14 and includes a clamp arm assembly 64 and a blade 66. The jaws of the clamping mechanism of the end effector assembly 26 are formed by clamp arm assembly 64 and the blade 66. The blade 66 is ultrasonically actuable and is acoustically coupled to the ultrasonic transducer 16. The trigger 32 on the handle assembly 12 is ultimately connected to a drive assembly, which together, mechanically cooperate to effect movement of the clamp arm assembly 64. Squeezing the trigger 32 in direction 33A moves the clamp arm assembly 64 in direction 62A from an open position, wherein the clamp arm assembly 64 and the blade 66 are disposed in a spaced relation relative to one another, to a clamped or closed position, wherein the clamp arm assembly 64 and the blade 66 cooperate to grasp tissue therebetween. The clamp arm assembly 64 may comprise a clamp pad (not shown) to engage tissue between the blade 66 and the clamp arm 64. Releasing the trigger 32 in direction 33B moves the clamp arm assembly 64 in direction 62B from a closed relationship, to an open position, wherein the clamp arm assembly 64 and the blade 66 are disposed in a spaced relation relative to one another.

The proximal portion of the handle assembly 12 comprises a proximal opening 68 to receive the distal end of the ultrasonic assembly 16. The ultrasonic assembly 16 is inserted in the proximal opening 68 and is mechanically engaged to the elongated endoscopic shaft assembly 14.

In one example embodiment, the elongated trigger hook 36 portion of the trigger 32 provides a longer trigger lever with a shorter span and rotation travel. The longer lever of the elon-

gated trigger hook 36 allows the user to employ multiple fingers within the aperture 38 to operate the elongated trigger hook 36 and cause the trigger 32 to pivot in direction 33B to open the jaws of the end effector assembly 26. For example, the user may insert three fingers (e.g., the middle, ring, and little fingers) in the aperture 38. Multiple fingers allows the surgeon to exert higher input forces on the trigger 32 and the elongated trigger hook 36 to activate the end effector assembly 26. The shorter span and rotation travel creates a more comfortable grip when closing or squeezing the trigger 32 in direction 33A or when opening the trigger 32 in the outward opening motion in direction 33B lessening the need to extend the fingers further outward. This substantially lessens hand fatigue and strain associated with the outward opening motion of the trigger 32 in direction 33B. The outward opening motion of the trigger may be spring-assisted by spring element 98 (FIG. 5) to help alleviate fatigue. The opening spring force is sufficient to assist the ease of opening, but not strong enough to adversely impact the tactile feedback of tissue tension during spreading dissection.

For example, during a surgical procedure either the index finger may be used to control the rotation of the elongated shaft assembly 14 to locate the jaws of the end effector assembly 26 in a suitable orientation. The middle and/or the other lower fingers may be used to squeeze the trigger 32 and grasp tissue within the jaws. Once the jaws are located in the desired position and the jaws are clamped against the tissue, the index finger can be used to activate the toggle switch 30 to adjust the power level of the ultrasonic transducer 16 to treat the tissue. Once the tissue has been treated, the user may release the trigger 32 by pushing outwardly in the distal direction against the elongated trigger hook 36 with the middle and/or lower fingers to open the jaws of the end effector assembly 26. This basic procedure may be performed without the user having to adjust their grip of the handle assembly 12.

FIGS. 3-4 illustrate the connection of the elongated endoscopic shaft assembly 14 relative to the end effector assembly 26. As previously described, in the illustrated embodiment, the end effector assembly 26 comprises a clamp arm assembly 64 and a blade 66 to form the jaws of the clamping mechanism. The blade 66 may be an ultrasonically actuable blade acoustically coupled to the ultrasonic transducer 16. The trigger 32 is mechanically connected to a drive assembly. Together, the trigger 32 and the drive assembly mechanically cooperate to move the clamp arm assembly 64A to an open position in direction 62B wherein the clamp arm assembly 64 and the blade 66 are disposed in spaced relation relative to one another, to a clamped or closed position in direction 62B wherein the clamp arm assembly 64 and the blade 66 cooperate to grasp tissue therebetween. The clamp arm assembly 64 may comprise a clamp pad (not shown) to engage tissue between the blade 66 and the clamp arm 64. The distal end of the tubular reciprocating tubular actuating member 58 is mechanically engaged to the end effector assembly 26. In the illustrated embodiment, the distal end of the tubular reciprocating tubular actuating member 58 is mechanically engaged to the clamp arm assembly 64, which is pivotable about the pivot point 70, to open and close the clamp arm assembly 64 in response to the actuation and/or release of the trigger 32. For example, in the illustrated embodiment, the clamp arm assembly 64 is movable from an open position to a closed position in direction 62B about a pivot point 70 when the trigger 32 is squeezed in direction 33A. The clamp arm assembly 64 is movable from a closed position to an open position in direction 62A about the pivot point 70 when the trigger 32 is released or outwardly contacted in direction 33B.

As previously discussed, the clamp arm assembly 64 may comprise electrodes electrically coupled to the electrosurgical/RF generator module 23 to receive therapeutic and/or sub-therapeutic energy, where the electrosurgical/RF energy may be applied to the electrodes either simultaneously or non-simultaneously with the ultrasonic energy being applied to the blade 66. Such energy activations may be applied in any suitable combinations to achieve a desired tissue effect in cooperation with an algorithm or other control logic.

FIG. 5 is an exploded view of the ultrasonic surgical instrument 10 shown in FIG. 2. In the illustrated embodiment, the exploded view shows the internal elements of the handle assembly 12, the handle assembly 12, the distal rotation assembly 13, the switch assembly 28, and the elongated endoscopic shaft assembly 14. In the illustrated embodiment, the first and second portions 12a, 12b mate to form the handle assembly 12. The first and second portions 12a, 12b each comprises a plurality of interfaces 69 dimensioned to mechanically align and engage one another to form the handle assembly 12 and enclose the internal working components of the ultrasonic surgical instrument 10. The rotation knob 48 is mechanically engaged to the outer tubular sheath 56 so that it may be rotated in circular direction 54 up to 360°. The outer tubular sheath 56 is located over the reciprocating tubular actuating member 58, which is mechanically engaged to and retained within the handle assembly 12 via a plurality of coupling elements 72. The coupling elements 72 may comprise an O-ring 72a, a tube collar cap 72b, a distal washer 72c, a proximal washer 72d, and a thread tube collar 72e. The reciprocating tubular actuating member 58 is located within a reciprocating yoke 84, which is retained between the first and second portions 12a, 12b of the handle assembly 12. The yoke 84 is part of a reciprocating yoke assembly 88. A series of linkages translate the pivotal rotation of the elongated trigger hook 32 to the axial movement of the reciprocating yoke 84, which controls the opening and closing of the jaws of the clamping mechanism of the end effector assembly 26 at the distal end of the ultrasonic surgical instrument 10. In one example embodiment, a four-link design provides mechanical advantage in a relatively short rotation span, for example.

In one example embodiment, an ultrasonic transmission waveguide 78 is disposed inside the reciprocating tubular actuating member 58. The distal end 52 of the ultrasonic transmission waveguide 78 is acoustically coupled (e.g., directly or indirectly mechanically coupled) to the blade 66 and the proximal end 50 of the ultrasonic transmission waveguide 78 is received within the handle assembly 12. The proximal end 50 of the ultrasonic transmission waveguide 78 is adapted to acoustically couple to the distal end of the ultrasonic transducer 16 as discussed in more detail below. The ultrasonic transmission waveguide 78 is isolated from the other elements of the elongated shaft assembly 14 by a protective sheath 80 and a plurality of isolation elements 82, such as silicone rings. The outer tubular sheath 56, the reciprocating tubular actuating member 58, and the ultrasonic transmission waveguide 78 are mechanically engaged by a pin 74. The switch assembly 28 comprises the toggle switch 30 and electrical elements 86a,b to electrically energize the ultrasonic transducer 16 in accordance with the activation of the first or second projecting knobs 30a, 30b.

In one example embodiment, the outer tubular sheath 56 isolates the user or the patient from the ultrasonic vibrations of the ultrasonic transmission waveguide 78. The outer tubular sheath 56 generally includes a hub 76. The outer tubular sheath 56 is threaded onto the distal end of the handle assembly 12. The ultrasonic transmission waveguide 78 extends through the opening of the outer tubular sheath 56 and the

isolation elements 82 isolate the ultrasonic transmission waveguide 78 from the outer tubular sheath 56. The outer tubular sheath 56 may be attached to the waveguide 78 with the pin 74. The hole to receive the pin 74 in the waveguide 78 may occur nominally at a displacement node. The waveguide 78 may screw or snap into the hand piece handle assembly 12 by a stud. Flat portions on the hub 76 may allow the assembly to be torqued to a required level. In one example embodiment, the hub 76 portion of the outer tubular sheath 56 is preferably constructed from plastic and the tubular elongated portion of the outer tubular sheath 56 is fabricated from stainless steel. Alternatively, the ultrasonic transmission waveguide 78 may comprise polymeric material surrounding it to isolate it from outside contact.

In one example embodiment, the distal end of the ultrasonic transmission waveguide 78 may be coupled to the proximal end of the blade 66 by an internal threaded connection, preferably at or near an antinode. It is contemplated that the blade 66 may be attached to the ultrasonic transmission waveguide 78 by any suitable means, such as a welded joint or the like. Although the blade 66 may be detachable from the ultrasonic transmission waveguide 78, it is also contemplated that the single element end effector (e.g., the blade 66) and the ultrasonic transmission waveguide 78 may be formed as a single unitary piece.

In one example embodiment, the trigger 32 is coupled to a linkage mechanism to translate the rotational motion of the trigger 32 in directions 33A and 33B to the linear motion of the reciprocating tubular actuating member 58 in corresponding directions 60A and 60B. The trigger 32 comprises a first set of flanges 97 with openings formed therein to receive a first yoke pin 94a. The first yoke pin 94a is also located through a set of openings formed at the distal end of the yoke 84. The trigger 32 also comprises a second set of flanges 96 to receive a first end 92a of a link 92. A trigger pin 90 is received in openings formed in the link 92 and the second set of flanges 96. The trigger pin 90 is received in the openings formed in the link 92 and the second set of flanges 96 and is adapted to couple to the first and second portions 12a, 12b of the handle assembly 12 to form a trigger pivot point for the trigger 32. A second end 92b of the link 92 is received in a slot 93 formed in a proximal end of the yoke 84 and is retained therein by a second yoke pin 94b. As the trigger 32 is pivotally rotated about the pivot point 190 formed by the trigger pin 90, the yoke translates horizontally along longitudinal axis "T" in a direction indicated by arrows 60A,B.

FIG. 8 illustrates one example embodiment of an ultrasonic surgical instrument 10. In the illustrated embodiment, a cross-sectional view of the ultrasonic transducer 16 is shown within a partial cutaway view of the handle assembly 12. One example embodiment of the ultrasonic surgical instrument 10 comprises the ultrasonic signal generator 20 coupled to the ultrasonic transducer 16, comprising a hand piece housing 99, and an ultrasonically actuatable single or multiple element end effector assembly 26. As previously discussed, the end effector assembly 26 comprises the ultrasonically actuatable blade 66 and the clamp arm 64. The ultrasonic transducer 16, which is known as a "Langevin stack", generally includes a transduction portion 100, a first resonator portion or end-bell 102, and a second resonator portion or fore-bell 104, and ancillary components. The total construction of these components is a resonator. The ultrasonic transducer 16 is preferably an integral number of one-half system wavelengths ($n\lambda/2$; where "n" is any positive integer; e.g., $n=1, 2, 3 \dots$) in length as will be described in more detail later. An acoustic assembly 106 includes the ultrasonic transducer 16, a nose cone 108, a velocity transformer 118, and a surface 110.

15

In one example embodiment, the distal end of the end-bell 102 is connected to the proximal end of the transduction portion 100, and the proximal end of the fore-bell 104 is connected to the distal end of the transduction portion 100. The fore-bell 104 and the end-bell 102 have a length determined by a number of variables, including the thickness of the transduction portion 100, the density and modulus of elasticity of the material used to manufacture the end-bell 102 and the fore-bell 104, and the resonant frequency of the ultrasonic transducer 16. The fore-bell 104 may be tapered inwardly from its proximal end to its distal end to amplify the ultrasonic vibration amplitude as the velocity transformer 118, or alternately may have no amplification. A suitable vibrational frequency range may be about 20 Hz to 32 kHz and a well-suited vibrational frequency range may be about 30-10 kHz. A suitable operational vibrational frequency may be approximately 55.5 kHz, for example.

In one example embodiment, the piezoelectric elements 112 may be fabricated from any suitable material, such as, for example, lead zirconate-titanate, lead meta-niobate, lead titanate, barium titanate, or other piezoelectric ceramic material. Each of positive electrodes 114, negative electrodes 116, and the piezoelectric elements 112 has a bore extending through the center. The positive and negative electrodes 114 and 116 are electrically coupled to wires 120 and 122, respectively. The wires 120 and 122 are encased within the cable 22 and electrically connectable to the ultrasonic signal generator 20.

The ultrasonic transducer 16 of the acoustic assembly 106 converts the electrical signal from the ultrasonic signal generator 20 into mechanical energy that results in primarily a standing acoustic wave of longitudinal vibratory motion of the ultrasonic transducer 16 and the blade 66 portion of the end effector assembly 26 at ultrasonic frequencies. In another embodiment, the vibratory motion of the ultrasonic transducer may act in a different direction. For example, the vibratory motion may comprise a local longitudinal component of a more complicated motion of the tip of the elongated shaft assembly 14. A suitable generator is available as model number GEN11, from Ethicon Endo-Surgery, Inc., Cincinnati, Ohio. When the acoustic assembly 106 is energized, a vibratory motion standing wave is generated through the acoustic assembly 106. The ultrasonic surgical instrument 10 is designed to operate at a resonance such that an acoustic standing wave pattern of predetermined amplitude is produced. The amplitude of the vibratory motion at any point along the acoustic assembly 106 depends upon the location along the acoustic assembly 106 at which the vibratory motion is measured. A minimum or zero crossing in the vibratory motion standing wave is generally referred to as a node (i.e., where motion is minimal), and a local absolute value maximum or peak in the standing wave is generally referred to as an anti-node (i.e., where local motion is maximal). The distance between an anti-node and its nearest node is one-quarter wavelength ($\lambda/4$).

The wires 120 and 122 transmit an electrical signal from the ultrasonic signal generator 20 to the positive electrodes 114 and the negative electrodes 116. The piezoelectric elements 112 are energized by the electrical signal supplied from the ultrasonic signal generator 20 in response to an actuator 224, such as a foot switch, for example, to produce an acoustic standing wave in the acoustic assembly 106. The electrical signal causes disturbances in the piezoelectric elements 112 in the form of repeated small displacements resulting in large alternating compression and tension forces within the material. The repeated small displacements cause the piezoelectric elements 112 to expand and contract in a continuous manner

16

along the axis of the voltage gradient, producing longitudinal waves of ultrasonic energy. The ultrasonic energy is transmitted through the acoustic assembly 106 to the blade 66 portion of the end effector assembly 26 via a transmission component or an ultrasonic transmission waveguide portion 78 of the elongated shaft assembly 14.

In one example embodiment, in order for the acoustic assembly 106 to deliver energy to the blade 66 portion of the end effector assembly 26, all components of the acoustic assembly 106 must be acoustically coupled to the blade 66. The distal end of the ultrasonic transducer 16 may be acoustically coupled at the surface 110 to the proximal end of the ultrasonic transmission waveguide 78 by a threaded connection such as a stud 124.

In one example embodiment, the components of the acoustic assembly 106 are preferably acoustically tuned such that the length of any assembly is an integral number of one-half wavelengths ($n\lambda/2$), where the wavelength λ is the wavelength of a pre-selected or operating longitudinal vibration drive frequency f_d of the acoustic assembly 106. It is also contemplated that the acoustic assembly 106 may incorporate any suitable arrangement of acoustic elements.

In one example embodiment, the blade 66 may have a length substantially equal to an integral multiple of one-half system wavelengths ($n\lambda/2$). A distal end of the blade 66 may be disposed near an antinode in order to provide the maximum longitudinal excursion of the distal end. When the transducer assembly is energized, the distal end of the blade 66 may be configured to move in the range of, for example, approximately 10 to 500 microns peak-to-peak, and preferably in the range of about 30 to 64 microns at a predetermined vibrational frequency of 55 kHz, for example.

In one example embodiment, the blade 66 may be coupled to the ultrasonic transmission waveguide 78. The blade 66 and the ultrasonic transmission waveguide 78 as illustrated are formed as a single unit construction from a material suitable for transmission of ultrasonic energy. Examples of such materials include Ti6Al4V (an alloy of Titanium including Aluminum and Vanadium), Aluminum, Stainless Steel, or other suitable materials. Alternately, the blade 66 may be separable (and of differing composition) from the ultrasonic transmission waveguide 78, and coupled by, for example, a stud, weld, glue, quick connect, or other suitable known methods. The length of the ultrasonic transmission waveguide 78 may be substantially equal to an integral number of one-half wavelengths ($n\lambda/2$), for example. The ultrasonic transmission waveguide 78 may be preferably fabricated from a solid core shaft constructed out of material suitable to propagate ultrasonic energy efficiently, such as the titanium alloy discussed above (i.e., Ti6Al4V) or any suitable aluminum alloy, or other alloys, for example.

In one example embodiment, the ultrasonic transmission waveguide 78 comprises a longitudinally projecting attachment post at a proximal end to couple to the surface 110 of the ultrasonic transmission waveguide 78 by a threaded connection such as the stud 124. The ultrasonic transmission waveguide 78 may include a plurality of stabilizing silicone rings or compliant supports 82 (FIG. 5) positioned at a plurality of nodes. The silicone rings 82 dampen undesirable vibration and isolate the ultrasonic energy from an outer protective sheath 80 (FIG. 5) assuring the flow of ultrasonic energy in a longitudinal direction to the distal end of the blade 66 with maximum efficiency.

FIG. 9 illustrates one example embodiment of the proximal rotation assembly 128. In the illustrated embodiment, the proximal rotation assembly 128 comprises the proximal rotation knob 134 inserted over the cylindrical hub 135. The

proximal rotation knob **134** comprises a plurality of radial projections **138** that are received in corresponding slots **130** formed on a proximal end of the cylindrical hub **135**. The proximal rotation knob **134** defines an opening **142** to receive the distal end of the ultrasonic transducer **16**. The radial projections **138** are formed of a soft polymeric material and define a diameter that is undersized relative to the outside diameter of the ultrasonic transducer **16** to create a friction interference fit when the distal end of the ultrasonic transducer **16**. The polymeric radial projections **138** protrude radially into the opening **142** to form "gripper" ribs that firmly grip the exterior housing of the ultrasonic transducer **16**. Therefore, the proximal rotation knob **134** securely grips the ultrasonic transducer **16**.

The distal end of the cylindrical hub **135** comprises a circumferential lip **132** and a circumferential bearing surface **140**. The circumferential lip engages a groove formed in the housing **12** and the circumferential bearing surface **140** engages the housing **12**. Thus, the cylindrical hub **135** is mechanically retained within the two housing portions (not shown) of the housing **12**. The circumferential lip **132** of the cylindrical hub **135** is located or "trapped" between the first and second housing portions **12a**, **12b** and is free to rotate in place within the groove. The circumferential bearing surface **140** bears against interior portions of the housing to assist proper rotation. Thus, the cylindrical hub **135** is free to rotate in place within the housing. The user engages the flutes **136** formed on the proximal rotation knob **134** with either the finger or the thumb to rotate the cylindrical hub **135** within the housing **12**.

In one example embodiment, the cylindrical hub **135** may be formed of a durable plastic such as polycarbonate. In one example embodiment, the cylindrical hub **135** may be formed of a siliconized polycarbonate material. In one example embodiment, the proximal rotation knob **134** may be formed of pliable, resilient, flexible polymeric materials including Versaflex® TPE alloys made by GLS Corporation, for example. The proximal rotation knob **134** may be formed of elastomeric materials, thermoplastic rubber known as Santoprene®, other thermoplastic vulcanizates (TPVs), or elastomers, for example. The embodiments, however, are not limited in this context.

FIG. 10 illustrates one embodiment of a surgical system **200** including a surgical instrument **210** having single element end effector **278**. The system **200** may include a transducer assembly **216** coupled to the end effector **278** and a sheath **256** positioned around the proximal portions of the end effector **278** as shown. The transducer assembly **216** and end effector **278** may operate in a manner similar to that of the transducer assembly **16** and end effector **18** described above to produce ultrasonic energy that may be transmitted to tissue via blade **226**.

FIGS. 11-18C illustrate various embodiments of surgical instruments that utilize therapeutic or sub-therapeutic electrical energy to treat and/or destroy tissue or provide feedback to the generators (e.g., electrosurgical instruments). The embodiments of FIGS. 11-18C are adapted for use in a manual or hand-operated manner although electrosurgical instruments may be utilized in robotic applications as well. FIG. 11 is a perspective view of one example embodiment of a surgical instrument system **300** comprising an electrical energy surgical instrument **310**. The electrosurgical instrument **310** may comprise a proximal handle **312**, a distal working end or end effector **326** and an introducer or elongated shaft **314** disposed in-between.

The electrosurgical system **300** can be configured to supply energy, such as electrical energy, ultrasonic energy, heat

energy, or any combination thereof, to the tissue of a patient either independently or simultaneously as described, for example, in connection with FIG. 1, for example. In one example embodiment, the electrosurgical system **300** includes a generator **320** in electrical communication with the electrosurgical instrument **310**. The generator **320** is connected to electrosurgical instrument **310** via a suitable transmission medium such as a cable **322**. In one example embodiment, the generator **320** is coupled to a controller, such as a control unit **325**, for example. In various embodiments, the control unit **325** may be formed integrally with the generator **320** or may be provided as a separate circuit module or device electrically coupled to the generator **320** (shown in phantom to illustrate this option). Although in the presently disclosed embodiment, the generator **320** is shown separate from the electrosurgical instrument **310**, in one example embodiment, the generator **320** (and/or the control unit **325**) may be formed integrally with the electrosurgical instrument **310** to form a unitary electrosurgical system **300**, where a battery located within the electrosurgical instrument **310** is the energy source and a circuit coupled to the battery produces the suitable electrical energy, ultrasonic energy, or heat energy. Once such example is described herein below, in connection with FIGS. 17-18C.

The generator **320** may comprise an input device **335** located on a front panel of the generator **320** console. The input device **335** may comprise any suitable device that generates signals suitable for programming the operation of the generator **320**, such as a keyboard, or input port, for example. In one example embodiment, various electrodes in the first jaw **364A** and the second jaw **364B** may be coupled to the generator **320**. The cable **322** may comprise multiple electrical conductors for the application of electrical energy to positive (+) and negative (-) electrodes of the electrosurgical instrument **310**. The control unit **325** may be used to activate the generator **320**, which may serve as an electrical source. In various embodiments, the generator **320** may comprise an RF source, an ultrasonic source, a direct current source, and/or any other suitable type of electrical energy source, for example, which may be activated independently or simultaneously.

In various embodiments, the electrosurgical system **300** may comprise at least one supply conductor **331** and at least one return conductor **333**, wherein current can be supplied to electrosurgical instrument **300** via the supply conductor **331** and wherein the current can flow back to the generator **320** via the return conductor **333**. In various embodiments, the supply conductor **331** and the return conductor **333** may comprise insulated wires and/or any other suitable type of conductor. In certain embodiments, as described below, the supply conductor **331** and the return conductor **333** may be contained within and/or may comprise the cable **322** extending between, or at least partially between, the generator **320** and the end effector **326** of the electrosurgical instrument **310**. In any event, the generator **320** can be configured to apply a sufficient voltage differential between the supply conductor **331** and the return conductor **333** such that sufficient current can be supplied to the end effector **110**.

FIG. 12 is a side view of one example embodiment of the handle **312** of the surgical instrument **310**. In FIG. 12, the handle **312** is shown with half of a first handle body **312A** (see FIG. 11) removed to illustrate various components within second handle body **312B**. The handle **312** may comprise a lever arm **321** (e.g., a trigger) which may be pulled along a path **33**. The lever arm **321** may be coupled to an axially moveable member **378** (FIGS. 13-16) disposed within elongated shaft **314** by a shuttle **384** operably engaged to an

extension 398 of lever arm 321. The shuttle 384 may further be connected to a biasing device, such as a spring 388, which may also be connected to the second handle body 312B, to bias the shuttle 384 and thus the axially moveable member 378 in a proximal direction, thereby urging the jaws 364A and 364B to an open position as seen in FIG. 11. Also, referring to FIGS. 11-12, a locking member 190 (see FIG. 12) may be moved by a locking switch 328 (see FIG. 11) between a locked position, where the shuttle 384 is substantially prevented from moving distally as illustrated, and an unlocked position, where the shuttle 384 may be allowed to freely move in the distal direction, toward the elongated shaft 314. In some embodiments, the locking switch 328 may be implemented as a button. The handle 312 can be any type of pistol-grip or other type of handle known in the art that is configured to carry actuator levers, triggers or sliders for actuating the first jaw 364A and the second jaw 364B. The elongated shaft 314 may have a cylindrical or rectangular cross-section, for example, and can comprise a thin-wall tubular sleeve that extends from handle 312. The elongated shaft 314 may include a bore extending therethrough for carrying actuator mechanisms, for example, the axially moveable member 378, for actuating the jaws and for carrying electrical leads for delivery of electrical energy to electrosurgical components of the end effector 326.

The end effector 326 may be adapted for capturing and transecting tissue and for the contemporaneously welding the captured tissue with controlled application of energy (e.g., RF energy). The first jaw 364A and the second jaw 364B may close to thereby capture or engage tissue about a longitudinal axis "T" defined by the axially moveable member 378. The first jaw 364A and second jaw 364B may also apply compression to the tissue. In some embodiments, the elongated shaft 314, along with first jaw 364A and second jaw 364B, can be rotated a full 360° degrees, as shown by arrow 196 (see FIG. 11), relative to handle 312. For example, a rotation knob 348 may be rotatable about the longitudinal axis of the elongated shaft 314 and may be coupled to the elongated shaft 314 such that rotation of the knob 348 causes corresponding rotation of the elongated shaft 314. The first jaw 364A and the second jaw 364B can remain openable and/or closeable while rotated.

FIG. 13 shows a perspective view of one example embodiment of the end effector 326 with the jaws 364A, 364B open, while FIG. 14 shows a perspective view of one example embodiment of the end effector 326 with the jaws 364A, 364B closed. As noted above, the end effector 326 may comprise the upper first jaw 364A and the lower second jaw 364B, which may be straight or curved. The first jaw 364A and the second jaw 364B may each comprise an elongated slot or channel 362A and 362B, respectively, disposed outwardly along their respective middle portions. Further, the first jaw 364A and second jaw 364B may each have tissue-gripping elements, such as teeth 363, disposed on the inner portions of first jaw 364A and second jaw 364B. The first jaw 364A may comprise an upper first outward-facing surface 369A and an upper first energy delivery surface 365A. The second jaw 364B may comprise a lower second outward-facing surface 369B and a lower second energy delivery surface 365B. The first energy delivery surface 365A and the second energy delivery surface 365B may both extend in a "U" shape about the distal end of the end effector 326.

The lever arm 321 of the handle 312 (FIG. 12) may be adapted to actuate the axially moveable member 378, which may also function as a jaw-closing mechanism. For example, the axially moveable member 378 may be urged distally as the lever arm 321 is pulled proximally along the path 33 via the

shuttle 384, as shown in FIG. 12 and discussed above. FIG. 15 is a perspective view of one example embodiment of the axially moveable member 378 of the surgical instrument 310. The axially moveable member 378 may comprise one or several pieces, but in any event, may be movable or translatable with respect to the elongated shaft 314 and/or the jaws 364A, 364B. Also, in at least one example embodiment, the axially moveable member 378 may be made of 17-4 precipitation hardened stainless steel. The distal end of axially moveable member 378 may comprise a flanged "I"-beam configured to slide within the channels 362A and 362B in jaws 364A and 364B. The axially moveable member 378 may slide within the channels 362A, 362B to open and close the first jaw 364A and the second jaw 364B. The distal end of the axially moveable member 378 may also comprise an upper flange or "c"-shaped portion 378A and a lower flange or "c"-shaped portion 378B. The flanges 378A and 378B respectively define inner cam surfaces 367A and 367B for engaging outward facing surfaces of the first jaw 364A and the second jaw 364B. The opening-closing of jaws 364A and 364B can apply very high compressive forces on tissue using cam mechanisms which may include movable "I-beam" axially moveable member 378 and the outward facing surfaces 369A, 369B of jaws 364A, 364B.

More specifically, referring now to FIGS. 13-15, collectively, the inner cam surfaces 367A and 367B of the distal end of axially moveable member 378 may be adapted to slidably engage the first outward-facing surface 369A and the second outward-facing surface 369B of the first jaw 364A and the second jaw 364B, respectively. The channel 362A within first jaw 364A and the channel 362B within the second jaw 364B may be sized and configured to accommodate the movement of the axially moveable member 378, which may comprise a tissue-cutting element 371, for example, comprising a sharp distal edge. FIG. 14, for example, shows the distal end of the axially moveable member 378 advanced at least partially through channels 362A and 362B (FIG. 13). The advancement of the axially moveable member 378 may close the end effector 326 from the open configuration shown in FIG. 13. In the closed position shown by FIG. 14, the upper first jaw 364A and lower second jaw 364B define a gap or dimension D between the first energy delivery surface 365A and second energy delivery surface 365B of first jaw 364A and second jaw 364B, respectively. In various embodiments, dimension D can equal from about 0.0005" to about 0.040", for example, and in some embodiments, between about 0.001" to about 0.010", for example. Also, the edges of the first energy delivery surface 365A and the second energy delivery surface 365B may be rounded to prevent the dissection of tissue.

FIG. 16 is a section view of one example embodiment of the end effector 326 of the surgical instrument 310. The engagement, or tissue-contacting, surface 365B of the lower jaw 364B is adapted to deliver energy to tissue, at least in part, through a conductive-resistive matrix, such as a variable resistive positive temperature coefficient (PTC) body, as discussed in more detail below. At least one of the upper and lower jaws 364A, 364B may carry at least one electrode 373 configured to deliver the energy from the generator 320 to the captured tissue. The engagement, or tissue-contacting, surface 365A of upper jaw 364A may carry a similar conductive-resistive matrix (i.e., a PTC material), or in some embodiments the surface may be a conductive electrode or an insulative layer, for example. Alternatively, the engagement surfaces of the jaws can carry any of the energy delivery components disclosed in U.S. Pat. No. 6,773,409, filed Oct. 22, 2001, entitled ELECTROSURGICAL JAW STRUC-

TURE FOR CONTROLLED ENERGY DELIVERY, the entire disclosure of which is incorporated herein by reference.

The first energy delivery surface **365A** and the second energy delivery surface **365B** may each be in electrical communication with the generator **320**. The first energy delivery surface **365A** and the second energy delivery surface **365B** may be configured to contact tissue and deliver electrosurgical energy to captured tissue which are adapted to seal or weld the tissue. The control unit **325** regulates the electrical energy delivered by electrical generator **320** which in turn delivers electrosurgical energy to the first energy delivery surface **365A** and the second energy delivery surface **365B**. The energy delivery may be initiated by an activation button **328** (FIG. 12) operably engaged with the lever arm **321** and in electrical communication with the generator **320** via cable **322**. In one example embodiment, the electrosurgical instrument **310** may be energized by the generator **320** by way of a foot switch **329** (FIG. 11). When actuated, the foot switch **216** triggers the generator **320** to deliver electrical energy to the end effector **326**, for example. The control unit **325** may regulate the power generated by the generator **320** during activation. Although the foot switch **329** may be suitable in many circumstances, other suitable types of switches can be used.

As mentioned above, the electrosurgical energy delivered by electrical generator **320** and regulated, or otherwise controlled, by the control unit **325** may comprise radio frequency (RF) energy, or other suitable forms of electrical energy. Further, the opposing first and second energy delivery surfaces **365A** and **365B** may carry variable resistive positive temperature coefficient (PTC) bodies that are in electrical communication with the generator **320** and the control unit **325**. Additional details regarding electrosurgical end effectors, jaw closing mechanisms, and electrosurgical energy-delivery surfaces are described in the following U.S. patents and published patent applications: U.S. Pat. Nos. 7,087,054; 7,083,619; 7,070,597; 7,041,102; 7,011,657; 6,929,644; 6,926,716; 6,913,579; 6,905,497; 6,802,843; 6,770,072; 6,656,177; 6,533,784; and 6,500,312; and U.S. Pat. App. Pub. Nos. 2010/0036370 and 2009/0076506, all of which are incorporated herein in their entirety by reference and made a part of this specification.

In one example embodiment, the generator **320** may be implemented as an electrosurgery unit (ESU) capable of supplying power sufficient to perform bipolar electrosurgery using radio frequency (RF) energy. In one example embodiment, the ESU can be a bipolar ERBE ICC **350** sold by ERBE USA, Inc. of Marietta, Ga. In some embodiments, such as for bipolar electrosurgery applications, a surgical instrument having an active electrode and a return electrode can be utilized, wherein the active electrode and the return electrode can be positioned against, adjacent to and/or in electrical communication with, the tissue to be treated such that current can flow from the active electrode, through the positive temperature coefficient (PTC) bodies and to the return electrode through the tissue. Thus, in various embodiments, the electrosurgical system **300** may comprise a supply path and a return path, wherein the captured tissue being treated completes, or closes, the circuit. In one example embodiment, the generator **320** may be a monopolar RF ESU and the electrosurgical instrument **310** may comprise a monopolar end effector **326** in which one or more active electrodes are integrated. For such a system, the generator **320** may require a return pad in intimate contact with the patient at a location remote from the operative site and/or other suitable return path. The return pad may be connected via a cable to the generator **320**. In other embodiments, the operator **20** may

provide sub-therapeutic RF energy levels for purposes of evaluating tissue conditions and providing feedback in the electrosurgical system **300**. Such feedback may be employed to control the therapeutic RF energy output of the electrosurgical instrument **310**.

During operation of electrosurgical instrument **300**, the user generally grasps tissue, supplies energy to the captured tissue to form a weld or a seal (e.g., by actuating button **328** and/or pedal **216**), and then drives a tissue-cutting element **371** at the distal end of the axially moveable member **378** through the captured tissue. According to various embodiments, the translation of the axial movement of the axially moveable member **378** may be paced, or otherwise controlled, to aid in driving the axially moveable member **378** at a suitable rate of travel. By controlling the rate of the travel, the likelihood that the captured tissue has been properly and functionally sealed prior to transection with the cutting element **371** is increased.

FIG. 17 is a perspective view of one example embodiment of a surgical instrument system comprising a cordless electrical energy surgical instrument **410**. The electrosurgical system is similar to the electrosurgical system **300**. The electrosurgical system can be configured to supply energy, such as electrical energy, ultrasonic energy, heat energy, or any combination thereof, to the tissue of a patient either independently or simultaneously as described in connection with FIGS. 1 and 11, for example. The electrosurgical instrument may utilize the end effector **326** and elongated shaft **314** described herein in conjunction with a cordless proximal handle **412**. In one example embodiment, the handle **412** includes a generator circuit **420** (see FIG. 18A). The generator circuit **420** performs a function substantially similar to that of generator **320**. In one example embodiment, the generator circuit **420** is coupled to a controller, such as a control circuit. In the illustrated embodiment, the control circuit is integrated into the generator circuit **420**. In other embodiments, the control circuit may be separate from the generator circuit **420**.

In one example embodiment, various electrodes in the end effector **326** (including jaws **364A**, **364B** thereof) may be coupled to the generator circuit **420**. The control circuit may be used to activate the generator **420**, which may serve as an electrical source. In various embodiments, the generator **420** may comprise an RF source, an ultrasonic source, a direct current source, and/or any other suitable type of electrical energy source, for example. In one example embodiment, a button **328** may be provided to activate the generator circuit **420** to provide energy to the end effectors **326**, **326**.

FIG. 18A is a side view of one example embodiment of the handle **412** of the cordless surgical instrument **410**. In FIG. 18, the handle **412** is shown with half of a first handle body removed to illustrate various components within second handle body **434**. The handle **412** may comprise a lever arm **424** (e.g., a trigger) which may be pulled along a path **33** around a pivot point. The lever arm **424** may be coupled to an axially moveable member **478** disposed within elongated shaft **314** by a shuttle operably engaged to an extension of lever arm **424**. In one example embodiment, the lever arm **424** defines a shepherd's hook shape comprising a distal member **424a** and a proximal member **424b**.

In one example embodiment, the cordless electrosurgical instrument comprises a battery **437**. The battery **437** provides electrical energy to the generator circuit **420**. The battery **437** may be any battery suitable for driving the generator circuit **420** at the desired energy levels. In one example embodiment, the battery **437** is a 100 mAh, triple-cell Lithium Ion Polymer battery. The battery may be fully charged prior to use in a surgical procedure, and may hold a voltage of about 12.6V.

The battery **437** may have two fuses fitted to the cordless electrosurgical instrument **410**, arranged in line with each battery terminal. In one example embodiment, a charging port **439** is provided to connect the battery **437** to a DC current source (not shown).

The generator circuit **420** may be configured in any suitable manner. In some embodiments, the generator circuit comprises an RF drive and control circuit **440** FIG. **18B** illustrates an RF drive and control circuit **440** according to one embodiment. FIG. **18B** is a part schematic part block diagram illustrating the RF drive and control circuitry **440** used in this embodiment to generate and control the RF electrical energy supplied to the end effector **326**. As will be explained in more detail below, in this embodiment, the drive circuitry **440** is a resonant mode RF amplifier comprising a parallel resonant network on the RF amplifier output and the control circuitry operates to control the operating frequency of the drive signal so that it is maintained at the resonant frequency of the drive circuit, which in turn controls the amount of power supplied to the end effector **326**. The way that this is achieved will become apparent from the following description.

As shown in FIG. **18B**, the RF drive and control circuit **440** comprises the above described battery **437** are arranged to supply, in this example, about 0V and about 12V rails. An input capacitor (C_m) **442** is connected between the 0V and the 12V for providing a low source impedance. A pair of FET switches **443-1** and **443-2** (both of which are N-channel in this embodiment to reduce power losses) is connected in series between the 0V rail and the 12V rail. FET gate drive circuitry **805** is provided that generates two drive signals—one for driving each of the two FETs **443**. The FET gate drive circuitry **445** generates drive signals that causes the upper FET (**443-1**) to be on when the lower FET (**443-2**) is off and vice versa. This causes the node **447** to be alternately connected to the 12V rail (when the FET **443-1** is switched on) and the 0V rail (when the FET **443-2** is switched on). FIG. **18B** also shows the internal parasitic diodes **448-1** and **448-2** of the corresponding FETs **443**, which conduct during any periods that the FETs **443** are open.

As shown in FIG. **18B**, the node **447** is connected to an inductor-inductor resonant circuit **450** formed by inductor L_s **452** and inductor L_m **454**. The FET gate driving circuitry **445** is arranged to generate drive signals at a drive frequency (f_d) that opens and crosses the FET switches **443** at the resonant frequency of the parallel resonant circuit **450**. As a result of the resonant characteristic of the resonant circuit **450**, the square wave voltage at node **447** will cause a substantially sinusoidal current at the drive frequency (f_d) to flow within the resonant circuit **450**. As illustrated in FIG. **18B**, the inductor L_m **454** is the primary of a transformer **455**, the secondary of which is formed by inductor L_{sec} **456**. The inductor L_{sec} **456** of the transformer **455** secondary is connected to an inductor-capacitor-capacitor parallel resonant circuit **457** formed by inductor L_2 **458**, capacitor C_4 **460**, and capacitor C_2 **462**. The transformer **455** up-converts the drive voltage (V_d) across the inductor L_m **454** to the voltage that is applied to the output parallel resonant circuit **457**. The load voltage (V_L) is output by the parallel resonant circuit **457** and is applied to the load (represented by the load resistance R_{load} **459** in FIG. **18B**) corresponding to the impedance of the forceps' jaws and any tissue or vessel gripped by the end effector **326**. As shown in FIG. **18B**, a pair of DC blocking capacitors C_{bl} **480-1** and **480-2** is provided to prevent any DC signal being applied to the load **459**.

In one embodiment, the transformer **455** may be implemented with a Core Diameter (mm), Wire Diameter (mm), and Gap between secondary windings in accordance with the following specifications:

Core Diameter, D (mm)

$D=19.9 \times 10^{-3}$

Wire diameter, W (mm) for 22 AWG wire

$W=7.366 \times 10^{-4}$

Gap between secondary windings, in gap=0.125

$G=\text{gap}/25.4$

In this embodiment, the amount of electrical power supplied to the end effector **326** is controlled by varying the frequency of the switching signals used to switch the FETs **443**. This works because the resonant circuit **450** acts as a frequency dependent (loss less) attenuator. The closer the drive signal is to the resonant frequency of the resonant circuit **450**, the less the drive signal is attenuated. Similarly, as the frequency of the drive signal is moved away from the resonant frequency of the circuit **450**, the more the drive signal is attenuated and so the power supplied to the load reduces. In this embodiment, the frequency of the switching signals generated by the FET gate drive circuitry **445** is controlled by a controller **481** based on a desired power to be delivered to the load **459** and measurements of the load voltage (V_L) and of the load current (I_L) obtained by conventional voltage sensing circuitry **483** and current sensing circuitry **485**. The way that the controller **481** operates will be described in more detail below.

In one embodiment, the voltage sensing circuitry **483** and the current sensing circuitry **485** may be implemented with high bandwidth, high speed rail-to-rail amplifiers (e.g., LMH6643 by National Semiconductor). Such amplifiers, however, consume a relatively high current when they are operational. Accordingly, a power save circuit may be provided to reduce the supply voltage of the amplifiers when they are not being used in the voltage sensing circuitry **483** and the current sensing circuitry **485**. In one-embodiment, a step-down regulator (e.g., LT3502 by Linear Technologies) may be employed by the power save circuit to reduce the supply voltage of the rail-to-rail amplifiers and thus extend the life of the battery **437**.

FIG. **18C** illustrates the main components of the controller **481**, according to one embodiment. In the embodiment illustrated in FIG. **18C**, the controller **481** is a microprocessor based controller and so most of the components illustrated in FIG. **16** are software based components. Nevertheless, a hardware based controller **481** may be used instead. As shown, the controller **481** includes synchronous I,Q sampling circuitry **491** that receives the sensed voltage and current signals from the sensing circuitry **483** and **485** and obtains corresponding samples which are passed to a power, V_{rms} and I_{rms} calculation module **493**. The calculation module **493** uses the received samples to calculate the RMS voltage and RMS current applied to the load **459** (FIG. **18B**; end effector **326** and tissue/vessel gripped thereby) and from them the power that is presently being supplied to the load **459**. The determined values are then passed to a frequency control module **495** and a medical device control module **497**. The medical device control module **497** uses the values to determine the present impedance of the load **459** and based on this determined impedance and a pre-defined algorithm, determines what set point power (P_{set}) should be applied to the frequency control module **495**. The medical device control module **497** is in turn controlled by signals received from a user input module **499** that receives inputs from the user (for example pressing buttons or activating the control levers **114**, **110** on

the handle **104**) and also controls output devices (lights, a display, speaker or the like) on the handle **104** via a user output module **461**.

The frequency control module **495** uses the values obtained from the calculation module **493** and the power set point (P_{set}) obtained from the medical device control module **497** and predefined system limits (to be explained below), to determine whether or not to increase or decrease the applied frequency. The result of this decision is then passed to a square wave generation module **463** which, in this embodiment, increments or decrements the frequency of a square wave signal that it generates by 1 kHz, depending on the received decision. As those skilled in the art will appreciate, in an alternative embodiment, the frequency control module **495** may determine not only whether to increase or decrease the frequency, but also the amount of frequency change required. In this case, the square wave generation module **463** would generate the corresponding square wave signal with the desired frequency shift. In this embodiment, the square wave signal generated by the square wave generation module **463** is output to the FET gate drive circuitry **445**, which amplifies the signal and then applies it to the FET **443-1**. The FET gate drive circuitry **445** also inverts the signal applied to the FET **443-1** and applies the inverted signal to the FET **443-2**.

The electrosurgical instrument **410** may comprise additional features as discussed with respect to electrosurgical system **300**. Those skilled in the art will recognize that electrosurgical instrument **410** may include a rotation knob **348**, an elongated shaft **314**, and an end effector **326**. These elements function in a substantially similar manner to that discussed above with respect to the electrosurgical system **300**. In one example embodiment, the cordless electrosurgical instrument **410** may include visual indicators **435**. The visual indicators **435** may provide a visual indication signal to an operator. In one example embodiment, the visual indication signal may alert an operator that the device is on, or that the device is applying energy to the end effector. Those skilled in the art will recognize that the visual indicators **435** may be configured to provide information on multiple states of the device.

Over the years a variety of minimally invasive robotic (or "telesurgical") systems have been developed to increase surgical dexterity as well as to permit a surgeon to operate on a patient in an intuitive manner. Robotic surgical systems can be used with many different types of surgical instruments including, for example, ultrasonic or electrosurgical instruments, as described herein. Example robotic systems include those manufactured by Intuitive Surgical, Inc., of Sunnyvale, Calif., U.S.A. Such systems, as well as robotic systems from other manufacturers, are disclosed in the following U.S. Patents which are each herein incorporated by reference in their respective entirety: U.S. Pat. No. 5,792,135, entitled "Articulated Surgical Instrument For Performing Minimally Invasive Surgery With Enhanced Dexterity and Sensitivity", U.S. Pat. No. 6,231,565, entitled "Robotic Arm DLUS For Performing Surgical Tasks", U.S. Pat. No. 6,783,524, entitled "Robotic Surgical Tool With Ultrasound Cauterizing and Cutting Instrument", U.S. Pat. No. 6,364,888, entitled "Alignment of Master and Slave In a Minimally Invasive Surgical Apparatus", U.S. Pat. No. 7,524,320, entitled "Mechanical Actuator Interface System For Robotic Surgical Tools", U.S. Pat. No. 7,691,098, entitled "Platform Link Wrist Mechanism", U.S. Pat. No. 7,806,891, entitled "Repositioning and Reorientation of Master/Slave Relationship in Minimally Invasive Telesurgery", and U.S. Pat. No. 7,824,401, entitled "Surgical Tool With Writed Monopolar Electrosurgical End Effectors".

Many of such systems, however, have in the past been unable to generate the magnitude of forces required to effectively cut and fasten tissue.

FIGS. **19-46C** illustrate example embodiments of robotic surgical systems. In some embodiments, the disclosed robotic surgical systems may utilize the ultrasonic or electrosurgical instruments described herein. Those skilled in the art will appreciate that the illustrated robotic surgical systems are not limited to only those instruments described herein, and may utilize any compatible surgical instruments. Those skilled in the art will further appreciate that while various embodiments described herein may be used with the described robotic surgical systems, the disclosure is not so limited, and may be used with any compatible robotic surgical system.

FIGS. **19-25** illustrate the structure and operation of several example robotic surgical systems and components thereof. FIG. **19** shows a block diagram of an example robotic surgical system **500**. The system **500** comprises at least one controller **508** and at least one arm cart **510**. The arm cart **510** may be mechanically coupled to one or more robotic manipulators or arms, indicated by box **512**. Each of the robotic arms **512** may comprise one or more surgical instruments **514** for performing various surgical tasks on a patient **504**. Operation of the arm cart **510**, including the arms **512** and instruments **514** may be directed by a clinician **502** from a controller **508**. In some embodiments, a second controller **508'**, operated by a second clinician **502'** may also direct operation of the arm cart **510** in conjunction with the first clinician **502**. For example, each of the clinicians **502**, **502'** may control different arms **512** of the cart or, in some cases, complete control of the arm cart **510** may be passed between the clinicians **502**, **502'**. In some embodiments, additional arm carts (not shown) may be utilized on the patient **504**. These additional arm carts may be controlled by one or more of the controllers **508**, **508'**. The arm cart(s) **510** and controllers **508**, **508'** may be in communication with one another via a communications link **516**, which may be any suitable type of wired or wireless communications link carrying any suitable type of signal (e.g., electrical, optical, infrared, etc.) according to any suitable communications protocol. Example implementations of robotic surgical systems, such as the system **500**, are disclosed in U.S. Pat. No. 7,524,320 which has been herein incorporated by reference. Thus, various details of such devices will not be described in detail herein beyond that which may be necessary to understand various embodiments of the claimed device.

FIG. **20** shows one example embodiment of a robotic arm cart **520**. The robotic arm cart **520** is configured to actuate a plurality of surgical instruments or instruments, generally designated as **522** within a work envelope **527**. Various robotic surgery systems and methods employing master controller and robotic arm cart arrangements are disclosed in U.S. Pat. No. 6,132,368, entitled "Multi-Component Telesurgery System and Method", the full disclosure of which is incorporated herein by reference. In various forms, the robotic arm cart **520** includes a base **524** from which, in the illustrated embodiment, three surgical instruments **522** are supported. In various forms, the surgical instruments **522** are each supported by a series of manually articulatable linkages, generally referred to as set-up joints **526**, and a robotic manipulator **528**. These structures are herein illustrated with protective covers extending over much of the robotic linkage. These protective covers may be optional, and may be limited in size or entirely eliminated in some embodiments to minimize the inertia that is encountered by the servo mechanisms used to manipulate such devices, to limit the volume of moving components so as to avoid collisions, and to limit the

overall weight of the cart 520. Cart 520 will generally have dimensions suitable for transporting the cart 520 between operating rooms. The cart 520 may be configured to typically fit through standard operating room doors and onto standard hospital elevators. In various forms, the cart 520 would preferably have a weight and include a wheel (or other transportation) system that allows the cart 520 to be positioned adjacent an operating table by a single attendant.

FIG. 21 shows one example embodiment of the robotic manipulator 528 of the robotic arm cart 520. In the example shown in FIG. 21, the robotic manipulators 528 may include a linkage 530 that constrains movement of the surgical instrument 522. In various embodiments, linkage 530 includes rigid links coupled together by rotational joints in a parallelogram arrangement so that the surgical instrument 522 rotates around a point in space 532, as more fully described in issued U.S. Pat. No. 5,817,084, the full disclosure of which is herein incorporated by reference. The parallelogram arrangement constrains rotation to pivoting about an axis 534a, sometimes called the pitch axis. The links supporting the parallelogram linkage are pivotally mounted to set-up joints 526 (FIG. 20) so that the surgical instrument 522 further rotates about an axis 534b, sometimes called the yaw axis. The pitch and yaw axes 534a, 534b intersect at the remote center 536, which is aligned along a shaft 538 of the surgical instrument 522. The surgical instrument 522 may have further degrees of driven freedom as supported by manipulator 540, including sliding motion of the surgical instrument 522 along the longitudinal instrument axis "LT-LT". As the surgical instrument 522 slides along the instrument axis LT-LT relative to manipulator 540 (arrow 534c), remote center 536 remains fixed relative to base 542 of manipulator 540. Hence, the entire manipulator 540 is generally moved to re-position remote center 536. Linkage 530 of manipulator 540 is driven by a series of motors 544. These motors 544 actively move linkage 530 in response to commands from a processor of a control system. As will be discussed in further detail below, motors 544 are also employed to manipulate the surgical instrument 522.

FIG. 22 shows one example embodiment of a robotic arm cart 520' having an alternative set-up joint structure. In this example embodiment, a surgical instrument 522 is supported by an alternative manipulator structure 528' between two tissue manipulation instruments. Those of ordinary skill in the art will appreciate that various embodiments of the claimed device may incorporate a wide variety of alternative robotic structures, including those described in U.S. Pat. No. 5,878,193, the full disclosure of which is incorporated herein by reference. Additionally, while the data communication between a robotic component and the processor of the robotic surgical system is primarily described herein with reference to communication between the surgical instrument 522 and the controller, it should be understood that similar communication may take place between circuitry of a manipulator, a set-up joint, an endoscope or other image capture device, or the like, and the processor of the robotic surgical system for component compatibility verification, component-type identification, component calibration (such as off-set or the like) communication, confirmation of coupling of the component to the robotic surgical system, or the like.

FIG. 23 shows one example embodiment of a controller 518 that may be used in conjunction with a robotic arm cart, such as the robotic arm carts 520, 520' depicted in FIGS. 20-22. The controller 518 generally includes master controllers (generally represented as 519 in FIG. 23) which are grasped by the clinician and manipulated in space while the clinician views the procedure via a stereo display 521. A surgeon feed back meter 515 may be viewed via the display

521 and provide the surgeon with a visual indication of the amount of force being applied to the cutting instrument or dynamic clamping member. The master controllers 519 generally comprise manual input devices which preferably move with multiple degrees of freedom, and which often further have a handle or trigger for actuating instruments (for example, for closing grasping saws, applying an electrical potential to an electrode, or the like).

FIG. 24 shows one example embodiment of an ultrasonic surgical instrument 522 adapted for use with a robotic surgical system. For example, the surgical instrument 522 may be coupled to one of the surgical manipulators 528, 528' described hereinabove. As can be seen in FIG. 24, the surgical instrument 522 comprises a surgical end effector 548 that comprises an ultrasonic blade 550 and clamp arm 552, which may be coupled to an elongated shaft assembly 554 that, in some embodiments, may comprise an articulation joint 556. FIG. 25 shows another example embodiment having an electrosurgical instrument 523 in place of the ultrasonic surgical instrument 522. The surgical instrument 523 comprises a surgical end effector 548 that comprises closable jaws 551A, 551B having energy deliver surfaces 553A, 553B for engaging and providing electrical energy to tissue between the jaws 551A, 551B. A tissue cutting element or knife 555 may be positioned at the distal end of an axially movable member 557 that may extend through the elongated shaft assembly 554 to the instrument mounting portion 558. FIG. 26 shows one example embodiment of an instrument drive assembly 546 that may be coupled to one of the surgical manipulators 528, 528' to receive and control the surgical instruments 522, 523. The instrument drive assembly 546 may also be operatively coupled to the controller 518 to receive inputs from the clinician for controlling the instrument 522, 523. For example, actuation (i.e., opening and closing) of the clamp arm 552, actuation (i.e., opening and closing) of the jaws 551A, 551B, actuation of the ultrasonic blade 550, extension of the knife 555 and actuation of the energy delivery surfaces 553A, 553B, etc. may be controlled through the instrument drive assembly 546 based on inputs from the clinician provided through the controller 518. The surgical instrument 522 is operably coupled to the manipulator by an instrument mounting portion, generally designated as 558. The surgical instruments 522 further include an interface 560 which mechanically and electrically couples the instrument mounting portion 558 to the manipulator.

FIG. 27 shows another view of the instrument drive assembly of FIG. 26 including the ultrasonic surgical instrument 522. FIG. 28 shows another view of the instrument drive assembly of FIG. 26 including the electrosurgical instrument 523. The instrument mounting portion 558 includes an instrument mounting plate 562 that operably supports a plurality of (four are shown in FIG. 26) rotatable body portions, driven discs or elements 564, that each include a pair of pins 566 that extend from a surface of the driven element 564. One pin 566 is closer to an axis of rotation of each driven elements 564 than the other pin 566 on the same driven element 564, which helps to ensure positive angular alignment of the driven element 564. The driven elements 564 and pins 566 may be positioned on an adapter side 567 of the instrument mounting plate 562.

Interface 560 also includes an adaptor portion 568 that is configured to mountingly engage the mounting plate 562 as will be further discussed below. The adaptor portion 568 may include an array of electrical connecting pins 570, which may be coupled to a memory structure by a circuit board within the instrument mounting portion 558. While interface 560 is described herein with reference to mechanical, electrical, and

magnetic coupling elements, it should be understood that a wide variety of telemetry modalities might be used, including infrared, inductive coupling, or the like.

FIGS. 29-31 show additional views of the adapter portion 568 of the instrument drive assembly 546 of FIG. 26. The adapter portion 568 generally includes an instrument side 572 and a holder side 574 (FIG. 29). In various embodiments, a plurality of rotatable bodies 576 are mounted to a floating plate 578 which has a limited range of movement relative to the surrounding adaptor structure normal to the major surfaces of the adaptor 568. Axial movement of the floating plate 578 helps decouple the rotatable bodies 576 from the instrument mounting portion 558 when the levers 580 along the sides of the instrument mounting portion housing 582 are actuated (See FIGS. 24, 25). Other mechanisms/arrangements may be employed for releasably coupling the instrument mounting portion 558 to the adaptor 568. In at least one form, rotatable bodies 576 are resiliently mounted to floating plate 578 by resilient radial members which extend into a circumferential indentation about the rotatable bodies 576. The rotatable bodies 576 can move axially relative to plate 578 by deflection of these resilient structures. When disposed in a first axial position (toward instrument side 572) the rotatable bodies 576 are free to rotate without angular limitation. However, as the rotatable bodies 576 move axially toward instrument side 572, tabs 584 (extending radially from the rotatable bodies 576) laterally engage detents on the floating plates so as to limit angular rotation of the rotatable bodies 576 about their axes. This limited rotation can be used to help drivingly engage the rotatable bodies 576 with drive pins 586 of a corresponding instrument holder portion 588 of the robotic system, as the drive pins 586 will push the rotatable bodies 576 into the limited rotation position until the pins 586 are aligned with (and slide into) openings 590.

Openings 590 on the instrument side 572 and openings 590 on the holder side 574 of rotatable bodies 576 are configured to accurately align the driven elements 564 (FIGS. 27, 28) of the instrument mounting portion 558 with the drive elements 592 of the instrument holder 588. As described above regarding inner and outer pins 566 of driven elements 564, the openings 590 are at differing distances from the axis of rotation on their respective rotatable bodies 576 so as to ensure that the alignment is not 33 degrees from its intended position. Additionally, each of the openings 590 may be slightly radially elongated so as to fittingly receive the pins 566 in the circumferential orientation. This allows the pins 566 to slide radially within the openings 590 and accommodate some axial misalignment between the instrument 522, 523 and instrument holder 588, while minimizing any angular misalignment and backlash between the drive and driven elements. Openings 590 on the instrument side 572 may be offset by about 90 degrees from the openings 590 (shown in broken lines) on the holder side 574, as can be seen most clearly in FIG. 31.

Various embodiments may further include an array of electrical connector pins 570 located on holder side 574 of adaptor 568, and the instrument side 572 of the adaptor 568 may include slots 594 (FIG. 31) for receiving a pin array (not shown) from the instrument mounting portion 558. In addition to transmitting electrical signals between the surgical instrument 522, 523 and the instrument holder 588, at least some of these electrical connections may be coupled to an adaptor memory device 596 (FIG. 30) by a circuit board of the adaptor 568.

A detachable latch arrangement 598 may be employed to releasably affix the adaptor 568 to the instrument holder 588. As used herein, the term "instrument drive assembly" when

used in the context of the robotic system, at least encompasses various embodiments of the adapter 568 and instrument holder 588 and which has been generally designated as 546 in FIG. 26. For example, as can be seen in FIG. 26, the instrument holder 588 may include a first latch pin arrangement 600 that is sized to be received in corresponding clevis slots 602 provided in the adaptor 568. In addition, the instrument holder 588 may further have second latch pins 604 that are sized to be retained in corresponding latch clevises 606 in the adaptor 568. See FIG. 30. In at least one form, a latch assembly 608 is movably supported on the adapter 568 and is biasable between a first latched position wherein the latch pins 600 are retained within their respective latch clevis 602 and an unlatched position wherein the second latch pins 604 may be into or removed from the latch clevises 606. A spring or springs (not shown) are employed to bias the latch assembly into the latched position. A lip on the instrument side 572 of adaptor 568 may slidably receive laterally extending tabs of instrument mounting housing 582.

As described the driven elements 564 may be aligned with the drive elements 592 of the instrument holder 588 such that rotational motion of the drive elements 592 causes corresponding rotational motion of the driven elements 564. The rotation of the drive elements 592 and driven elements 564 may be electronically controlled, for example, via the robotic arm 512, in response to instructions received from the clinician 502 via a controller 508. The instrument mounting portion 558 may translate rotation of the driven elements 564 into motion of the surgical instrument 522, 523.

FIGS. 32-34 show one example embodiment of the instrument mounting portion 558 showing components for translating motion of the driven elements 564 into motion of the surgical instrument 522, 523. FIGS. 32-34 show the instrument mounting portion with a shaft 538 having a surgical end effector 610 at a distal end thereof. The end effector 610 may be any suitable type of end effector for performing a surgical task on a patient. For example, the end effector may be configured to provide RF and/or ultrasonic energy to tissue at a surgical site. The shaft 538 may be rotatably coupled to the instrument mounting portion 558 and secured by a top shaft holder 646 and a bottom shaft holder 648 at a coupler 650 of the shaft 538.

In one example embodiment, the instrument mounting portion 558 comprises a mechanism for translating rotation of the various driven elements 564 into rotation of the shaft 538, differential translation of members along the axis of the shaft (e.g., for articulation), and reciprocating translation of one or more members along the axis of the shaft 538 (e.g., for extending and retracting tissue cutting elements such as 555, overtubes and/or other components). In one example embodiment, the rotatable bodies 612 (e.g., rotatable spools) are coupled to the driven elements 564. The rotatable bodies 612 may be formed integrally with the driven elements 564. In some embodiments, the rotatable bodies 612 may be formed separately from the driven elements 564 provided that the rotatable bodies 612 and the driven elements 564 are fixedly coupled such that driving the driven elements 564 causes rotation of the rotatable bodies 612. Each of the rotatable bodies 612 is coupled to a gear train or gear mechanism to provide shaft articulation and rotation and clamp jaw open/close and knife actuation.

In one example embodiment, the instrument mounting portion 558 comprises a mechanism for causing differential translation of two or more members along the axis of the shaft 538. In the example provided in FIGS. 32-34, this motion is used to manipulate articulation joint 556. In the illustrated embodiment, for example, the instrument mounting portion

558 comprises a rack and pinion gearing mechanism to provide the differential translation and thus the shaft articulation functionality. In one example embodiment, the rack and pinion gearing mechanism comprises a first pinion gear 614 coupled to a rotatable body 612 such that rotation of the corresponding driven element 564 causes the first pinion gear 614 to rotate. A bearing 616 is coupled to the rotatable body 612 and is provided between the driven element 564 and the first pinion gear 614. The first pinion gear 614 is meshed to a first rack gear 618 to convert the rotational motion of the first pinion gear 614 into linear motion of the first rack gear 618 to control the articulation of the articulation section 556 of the shaft assembly 538 in a left direction 620L. The first rack gear 618 is attached to a first articulation band 622 (FIG. 32) such that linear motion of the first rack gear 618 in a distal direction causes the articulation section 556 of the shaft assembly 538 to articulate in the left direction 620L. A second pinion gear 626 is coupled to another rotatable body 612 such that rotation of the corresponding driven element 564 causes the second pinion gear 626 to rotate. A bearing 616 is coupled to the rotatable body 612 and is provided between the driven element 564 and the second pinion gear 626. The second pinion gear 626 is meshed to a second rack gear 628 to convert the rotational motion of the second pinion gear 626 into linear motion of the second rack gear 628 to control the articulation of the articulation section 556 in a right direction 620R. The second rack gear 628 is attached to a second articulation band 624 (FIG. 33) such that linear motion of the second rack gear 628 in a distal direction causes the articulation section 556 of the shaft assembly 538 to articulate in the right direction 620R. Additional bearings may be provided between the rotatable bodies and the corresponding gears. Any suitable bearings may be provided to support and stabilize the mounting and reduce rotary friction of shaft and gears, for example.

In one example embodiment, the instrument mounting portion 558 further comprises a mechanism for translating rotation of the driven elements 564 into rotational motion about the axis of the shaft 538. For example, the rotational motion may be rotation of the shaft 538 itself. In the illustrated embodiment, a first spiral worm gear 630 coupled to a rotatable body 612 and a second spiral worm gear 632 coupled to the shaft assembly 538. A bearing 616 (FIG. 17) is coupled to a rotatable body 612 and is provided between a driven element 564 and the first spiral worm gear 630. The first spiral worm gear 630 is meshed to the second spiral worm gear 632, which may be coupled to the shaft assembly 538 and/or to another component of the instrument 522, 523 for which longitudinal rotation is desired. Rotation may be caused in a clockwise (CW) and counter-clockwise (CCW) direction based on the rotational direction of the first and second spiral worm gears 630, 632. Accordingly, rotation of the first spiral worm gear 630 about a first axis is converted to rotation of the second spiral worm gear 632 about a second axis, which is orthogonal to the first axis. As shown in FIGS. 32-33, for example, a CW rotation of the second spiral worm gear 632 results in a CW rotation of the shaft assembly 538 in the direction indicated by 634CW. A CCW rotation of the second spiral worm gear 632 results in a CCW rotation of the shaft assembly 538 in the direction indicated by 634CCW. Additional bearings may be provided between the rotatable bodies and the corresponding gears. Any suitable bearings may be provided to support and stabilize the mounting and reduce rotary friction of shaft and gears, for example.

In one example embodiment, the instrument mounting portion 558 comprises a mechanism for generating reciprocating translation of one or more members along the axis of the shaft 538. Such translation may be used, for example to drive a

tissue cutting element, such as 555, drive an overtube for closure and/or articulation of the end effector 610, etc. In the illustrated embodiment, for example, a rack and pinion gearing mechanism may provide the reciprocating translation. A first gear 636 is coupled to a rotatable body 612 such that rotation of the corresponding driven element 564 causes the first gear 636 to rotate in a first direction. A second gear 638 is free to rotate about a post 640 formed in the instrument mounting plate 562. The first gear 636 is meshed to the second gear 638 such that the second gear 638 rotates in a direction that is opposite of the first gear 636. In one example embodiment, the second gear 638 is a pinion gear meshed to a rack gear 642, which moves in a linear direction. The rack gear 642 is coupled to a translating block 644, which may translate distally and proximally with the rack gear 642. The translation block 644 may be coupled to any suitable component of the shaft assembly 538 and/or the end effector 610 so as to provide reciprocating longitudinal motion. For example, the translation block 644 may be mechanically coupled to the tissue cutting element 555 of the RF surgical device 523. In some embodiments, the translation block 644 may be coupled to an overtube, or other component of the end effector 610 or shaft 538.

FIGS. 35-37 illustrate an alternate embodiment of the instrument mounting portion 558 showing an alternate example mechanism for translating rotation of the driven elements 564 into rotational motion about the axis of the shaft 538 and an alternate example mechanism for generating reciprocating translation of one or more members along the axis of the shaft 538. Referring now to the alternate rotational mechanism, a first spiral worm gear 652 is coupled to a second spiral worm gear 654, which is coupled to a third spiral worm gear 656. Such an arrangement may be provided for various reasons including maintaining compatibility with existing robotic systems 500 and/or where space may be limited. The first spiral worm gear 652 is coupled to a rotatable body 612. The third spiral worm gear 656 is meshed with a fourth spiral worm gear 658 coupled to the shaft assembly 538. A bearing 760 is coupled to a rotatable body 612 and is provided between a driven element 564 and the first spiral worm gear 738. Another bearing 760 is coupled to a rotatable body 612 and is provided between a driven element 564 and the third spiral worm gear 652. The third spiral worm gear 652 is meshed to the fourth spiral worm gear 658, which may be coupled to the shaft assembly 538 and/or to another component of the instrument 522, 523 for which longitudinal rotation is desired. Rotation may be caused in a CW and a CCW direction based on the rotational direction of the spiral worm gears 656, 658. Accordingly, rotation of the third spiral worm gear 656 about a first axis is converted to rotation of the fourth spiral worm gear 658 about a second axis, which is orthogonal to the first axis. As shown in FIGS. O and P, for example, the fourth spiral worm gear 558 is coupled to the shaft 538, and a CW rotation of the fourth spiral worm gear 658 results in a CW rotation of the shaft assembly 538 in the direction indicated by 634CW. A CCW rotation of the fourth spiral worm gear 658 results in a CCW rotation of the shaft assembly 538 in the direction indicated by 634CCW. Additional bearings may be provided between the rotatable bodies and the corresponding gears. Any suitable bearings may be provided to support and stabilize the mounting and reduce rotary friction of shaft and gears, for example.

Referring now to the alternate example mechanism for generating reciprocating translation of one or more members along the axis of the shaft 538, the instrument mounting portion 558 comprises a rack and pinion gearing mechanism to provide reciprocating translation along the axis of the shaft

538 (e.g., translation of a tissue cutting element 555 of the RF surgical device 523). In one example embodiment, a third pinion gear 660 is coupled to a rotatable body 612 such that rotation of the corresponding driven element 564 causes the third pinion gear 660 to rotate in a first direction. The third pinion gear 660 is meshed to a rack gear 662, which moves in a linear direction. The rack gear 662 is coupled to a translating block 664. The translating block 664 may be coupled to a component of the device 522, 523, such as, for example, the tissue cutting element 555 of the RF surgical device and/or an overtube or other component which is desired to be translated longitudinally.

FIGS. 38-42 illustrate an alternate embodiment of the instrument mounting portion 558 showing another alternate example mechanism for translating rotation of the driven elements 564 into rotational motion about the axis of the shaft 538. In FIGS. 38-42, the shaft 538 is coupled to the remainder of the mounting portion 558 via a coupler 676 and a bushing 678. A first gear 666 coupled to a rotatable body 612, a fixed post 668 comprising first and second openings 672, first and second rotatable pins 674 coupled to the shaft assembly, and a cable 670 (or rope). The cable is wrapped around the rotatable body 612. One end of the cable 670 is located through a top opening 672 of the fixed post 668 and fixedly coupled to a top rotatable pin 674. Another end of the cable 670 is located through a bottom opening 672 of the fixed post 668 and fixedly coupled to a bottom rotating pin 674. Such an arrangement is provided for various reasons including maintaining compatibility with existing robotic systems 500 and/or where space may be limited. Accordingly, rotation of the rotatable body 612 causes the rotation about the shaft assembly 538 in a CW and a CCW direction based on the rotational direction of the rotatable body 612 (e.g., rotation of the shaft 538 itself). Accordingly, rotation of the rotatable body 612 about a first axis is converted to rotation of the shaft assembly 538 about a second axis, which is orthogonal to the first axis. As shown in FIGS. 38, 39, for example, a CW rotation of the rotatable body 612 results in a CW rotation of the shaft assembly 538 in the direction indicated by 634CW. A CCW rotation of the rotatable body 612 results in a CCW rotation of the shaft assembly 538 in the direction indicated by 634CCW. Additional bearings may be provided between the rotatable bodies and the corresponding gears. Any suitable bearings may be provided to support and stabilize the mounting and reduce rotary friction of shaft and gears, for example.

FIGS. 43-46A illustrate an alternate embodiment of the instrument mounting portion 558 showing an alternate example mechanism for differential translation of members along the axis of the shaft 538 (e.g., for articulation). For example, as illustrated in FIGS. 43-46A, the instrument mounting portion 558 comprises a double cam mechanism 680 to provide the shaft articulation functionality. In one example embodiment, the double cam mechanism 680 comprises first and second cam portions 680A, 680B. First and second follower arms 682, 684 are pivotally coupled to corresponding pivot spools 686. As the rotatable body 612 coupled to the double cam mechanism 680 rotates, the first cam portion 680A acts on the first follower arm 682 and the second cam portion 680B acts on the second follower arm 684. As the cam mechanism 680 rotates the follower arms 682, 684 pivot about the pivot spools 686. The first follower arm 682 may be attached to a first member that is to be differentially translated (e.g., the first articulation band 622). The second follower arm 684 is attached to a second member that is to be differentially translated (e.g., the second articulation band 624). As the top cam portion 680A acts of the first follower arm 682, the first and second members are differen-

tially translated. In the example embodiment where the first and second members are the respective articulation bands 622 and 624, the shaft assembly 538 articulates in a left direction 620L. As the bottom cam portion 680B acts of the second follower arm 684, the shaft assembly 538 articulates in a right direction 620R. In some example embodiments, two separate bushings 688, 690 are mounted beneath the respective first and second follower arms 682, 684 to allow the rotation of the shaft without affecting the articulating positions of the first and second follower arms 682, 684. For articulation motion, these bushings reciprocate with the first and second follower arms 682, 684 without affecting the rotary position of the jaw 902. FIG. 46A shows the bushings 688, 690 and the dual cam assembly 680, including the first and second cam portions 680B, 680B, with the first and second follower arms 682, 684 removed to provide a more detailed and clearer view.

In various embodiments, the instrument mounting portion 558 may additionally comprise internal energy sources for driving electronics and provided desired ultrasonic and/or RF frequency signals to surgical tools. FIGS. 46B-46C illustrate one embodiment of a tool mounting portion 558' comprising internal power and energy sources. For example, surgical instruments (e.g., instruments 522, 523) mounted utilizing the tool mounting portion 558' need not be wired to an external generator or other power source. Instead, the functionality of the various generators 20, 320 described herein may be implemented on board the mounting portion 558.

As illustrated in FIGS. 46B-46C, the instrument mounting portion 558' may comprise a distal portion 702. The distal portion 702 may comprise various mechanisms for coupling rotation of drive elements 592 to end effectors of the various surgical instruments 522, 523, for example, as described herein above. Proximal of the distal portion 702, the instrument mounting portion 558' comprises an internal direct current (DC) energy source and an internal drive and control circuit 704. In the illustrated embodiment, the energy source comprises a first and second battery 706, 708. In other respects, the tool mounting portion 558' is similar to the various embodiments of the tool mounting portion 558 described herein above.

The control circuit 704 may operate in a manner similar to that described above with respect to generators 20, 320. For example, when an ultrasonic instrument 522 is utilized, the control circuit 704 may provide an ultrasonic drive signal in a manner similar to that described above with respect to generator 20. Also, for example, when an RF instrument 523 or ultrasonic instrument 522 capable of providing a therapeutic or non-therapeutic RF signal is used, the control circuit 704 may provide an RF drive signal, for example, as described herein above with respect to the module 23 of generator 20 and/or the generator 300. In some embodiments, the control circuit 704 may be configured in a manner similar to that of the control circuit 440 described herein above with respect to FIGS. 18B-18C.

In some embodiments, it may be desirable to prevent actuation of an electrosurgical or ultrasonic end effector, such as, for example, the electrosurgical end effector 523, until energy has been applied to the electrosurgical or ultrasonic end effector. FIG. 47 shows one embodiment of an instrument mounting portion 758 comprising a lockout mechanism 722. In the embodiment shown in FIG. 47, actuation of the one or more members of end effector 723, such as, for example, a blade, may be prohibited through the use of a lockout mechanism 722. The lockout mechanism 722 operably interfaces with one or more of the mechanisms for generating reciprocating translation of one or more members along the axis of the shaft 738. In the embodiment shown in FIG. 47, the lockout mecha-

nism interfaces directly with the shaft 738 to prevent reciprocal movement of the one or more members along the axis of the shaft 738. In other embodiments, the lockout mechanism 722 may interface with the one or more of the gears, such as, for example, the first gear 636 of the instrument mounting portion 758.

As shown in FIG. 47, the lockout mechanism may be directly connected to a switch 714, such as, for example, a foot switch. The switch 714 may be operated by a user to selectively disengage (or selectively engage) the lockout mechanism 722 to prevent reciprocating movement of the end effector 723. In the illustrated embodiment, the switch 714 is directly connected to the lockout mechanism 722 by a wire 716. It will be appreciated by those skilled in the art that the switch 714 and the lockout mechanism 722 may be in signal communication by a suitable method, including, but not limited to, direct communication, communication through one or more controllers, such as, for example, the robotic surgical control systems disclosed in co-filed application

END7042USNP/110388. In other embodiments, the lockout mechanism 722 and the switch 714 may be in wireless communication using any suitable wireless communication protocol, such as, for example, Bluetooth communication. The switch 714 may also be connected to the generator 712. The generator 712 is configured to provide one or more electrosurgical signals to the end effector 723. The electrosurgical signals delivered by the generator 712 may include, but are not limited to, ultrasonic signals, radiofrequency signals, or a combination thereof. A user may cause the generator to deliver the electrosurgical signal to the end effector 723 by activating the switch 714. In the illustrated embodiment, the lockout mechanism 722 and the generator 712 are controlled by the switch 714 such that reciprocating movement of the end effector 723 is allowed only when electrosurgical energy is being delivered to the end effector 723.

In another embodiment, the lockout mechanism 722 may be directly coupled to the generator 712 or the end effector 723. In this embodiment, the lockout mechanism 722 may be controlled by sensing the presence of the electrosurgical signal delivered by the generator 712 to the end effector 723. In this embodiment, the lockout mechanism 722 may prevent actuation of the one or more members of the end effector 723 if the generator 712 is faulty or is has not delivered the proper amount of energy to the end effector 723.

The instrument mounting portion 758 comprises an end-of-stroke switch 718 operatively coupled to the reciprocating movement element 724. The end-of-stroke switch 718 provides a signal indicative of the location of the one or more members within the end effector 723. In one embodiment, the end-of-stroke switch 718 may provide a feedback signal to a user indicating that the one or more members have reached the distal most point of the reciprocating travel path. The user may then activate a reverse stroke algorithm to cause the one or more members to return from the distal most position to a proximal most, or starting, position. In another embodiment, the end-of-stroke switch 718 may cause the reverse stroke algorithm to automatically activate. In one embodiment, the end-of-stroke switch 718 may be connected to the lockout mechanism 722 such that the end-of-stroke switch 718 may engage the lockout mechanism 722 to prevent the one or more members of the end effector 723 from extending beyond a maximum distal displacement. In one embodiment, the end-of-stroke switch may prevent a signal from the switch 714 from being transmitted to the lockout mechanism 722 when the end-of-stroke switch 718 is activated, causing the lockout mechanism 722 to assume the default, locked position.

FIG. 48 illustrates one embodiment of instrument mounting portion 558 including a lockout mechanism 802. The lockout mechanism 802 mechanically interfaces with the first gear 636, which is coupled to a rotatable body 612. The lockout mechanism 802 prevents rotation of the first gear 636 by providing a mechanical stoppage interfaced with the first gear 636 from rotating. The mechanical stoppage may be, for example, a solenoid, a third gear, or any other suitable lockout device.

In one embodiment, the lockout mechanism is electrically coupled to a control switch located on the controller 518 (not shown). The control switch may be configured to control the delivery of energy to the end effector 610 from a generator, such as, for example, generator 320 (see FIG. 11). By actuating the control switch, a user may cause electrical energy to be delivered to the end effector 610 sufficient for use in electrosurgical applications.

In one embodiment, the control switch, in addition to allowing delivery of electrical energy to the end effector 610, causes the lockout mechanism 802 to disengage from the first gear 636, allowing rotation of the first gear 636 by the rotatable body 612. In this embodiment, the lockout mechanism 802 is directly connected to the delivery of electrical energy to the end effector 610. In other embodiments, the lockout mechanism 802 may be controlled by a second switch which is not used for delivery of electrical energy to the end effector 610.

In one embodiment, the end effector 723 may have a first state and a second state. In one embodiment, the first state may comprise a default, de-energized state wherein no energy is being applied by the generator 712 to the end effector 723. The second state may correspond to an energized state wherein the end effector 723 is energized by one or more forms of energy delivered by the generator 712. In one embodiment, in the energized state, the end effector may be energized with ultrasonic energy, radiofrequency energy, or both forms of energy. The lockout mechanism 722 may be electrically coupled to the end effector 723 such that the lockout mechanism 722 prevents actuation of the one or more members of the end effector 723 when the end effector 723 is in the first state and allows actuation of the one or more members when the end effector 723 is in the second state. In another embodiment, the first and second states may correspond to one or more mechanical states of the end effector 723, such as, for example, an end effector 723 comprising a staple cartridge may have a first state in which the staple cartridge is unloaded and a second state in which the staple cartridge is loaded. Those skilled in the art will appreciate that the first and second states may correspond to any suitable functions of the end effector 723.

As shown in FIG. 48, in one embodiment the lockout mechanism may comprise a solenoid 820. The solenoid 820 may be a linear pull type solenoid. In a pull type solenoid the plunger, such as, for example, armature 822, is biased in an extended position by a spring located within the solenoid. When the solenoid is energized, a coil (in the case of an electromagnetic solenoid) or a cylinder (in the case of a pneumatic solenoid) causes the plunger to retract into the body of the solenoid. The plunger returns to its biased, extended state when the solenoid is no longer energized. The solenoid 820 is a pull type solenoid with a default position of an extended armature 822, causing the default position of the lockout mechanism 802 to engage the first gear 636. Therefore, the default position of the lockout mechanism 802 is in a locked position. The solenoid 820 may also be a push type

solenoid, wherein the biased and unbiased positions are reversed, and therefore would have a default position of an unlocked position.

In one embodiment, the instrument mounting portion **558** further comprises an end-of-stroke switch **818**. The end-of-stroke switch **818** is operatively coupled to the mechanism for generating reciprocating translation of one or more members along the axis of the shaft **538**. In the embodiment shown in FIG. **48**, the end-of-stroke switch **818** is operatively coupled to the second gear **638**. The end-of-stroke switch **818** provides a signal indicating that the one or more members have reached the distal most point of its reciprocating travel path within channel of the end effector **610**.

In one embodiment, the end-of-stroke switch **818** may provide a feedback signal to a user indicating that the one or more members have reached the distal most point of the reciprocating travel path. The user may then activate a reverse stroke algorithm to cause the one or more members to return from the distal most position to a proximal most, or starting, position. In another embodiment, the end-of-stroke switch **818** may cause the reverse stroke algorithm to automatically activate. In this embodiment, the end-of-stroke switch **818** may be connected to a processor or other controller to reverse the direction of rotation of the rotatable body **612**. In this embodiment, a user may activate a switch on a controller, such as controller **518**, causing energy to be applied to the end effector **610**. After energy has been applied, the controller may then actuate the solenoid **820** allowing the first gear **636** to rotate in response to rotation of the rotatable body **612** in a first direction. The rotation of the rotatable body **612** in the first direction causes one or more members, such as tissue cutting element **555**, to advance in a distal direction with respect to the instrument mounting portion housing **582**. Once the tissue cutting element **555** has reached the distal-most point of travel, the end-of-stroke switch **818** activates, causing the controller to reverse the direction of rotation of the rotatable body and the tissue cutting element **555** to travel in a proximal direction relative to the instrument mounting portion housing **582**. Once the tissue cutting element **555** has returned to the proximal most position, the end-of-stroke switch **818** is again activated by the second gear **638**, which causes the rotatable body **612** to cease rotating and re-engages the lockout mechanism **802** with the first gear **636**.

FIG. **49** illustrates one embodiment of the lockout mechanism **902** directly interfaced with the fourth spiral worm gear **658** of the shaft assembly **538**. In this embodiment, the lockout mechanism **902** prevents the fourth spiral worm gear **658** from being rotated by the third spiral worm gear **656**. In this embodiment, the lockout mechanism **902** prevents reciprocating movement of the one or more members by preventing rotation of the fourth worm gear **656** which is coupled to the shaft assembly **538**.

In one embodiment, the lockout mechanism **722**, **802**, **902** may be controlled by one or more logic controls (not shown). The one or more logic controls may be located, for example, in the instrument mounting portion assembly **558** or on the controller **518**. The one or more logic controls may control the lockout mechanism **722** to allow reciprocating movement of the one or more members during specific sequences controlled by the one or more logic controls, such as, for example, a cutting and sealing algorithm controlled by one or more processors included with the controller **518**. The one or more logic controls may be any suitable logic for controlling the lockout mechanism **722**, such as, for example, a computer processor running one or more software programs thereon or a programmable logic circuit, such as a field programmable gate array.

In one embodiment, the end-of-stroke switch **718** may be coupled to the one or more logic controls to provide a control signal for one or more functions controlled by the one or more logic controls. For example, in one embodiment, the end-of-stroke switch **718** may provide a signal to the one or more logic controls which cause the one or more logic controls to reverse the direction of travel of the one or more members of the end effector **723**. In this embodiment, the one or more logic controls may automatically retract the one or more members to a proximal, or starting, position after the end-of-stroke switch **718** indicates that the one or more members have reached the distal-most position.

NON-LIMITING EXAMPLES

In one embodiment a surgical system is provided. The surgical system comprises a surgical tool, comprising an instrument mounting portion comprising a housing; a plate; a shaft assembly comprising an end effector, the end effector comprising a first jaw member and a second jaw member, the first and second jaw members defining a channel therebetween, and a blade slideably receivable within the channel to cut tissue located between the first and second jaw members; and a coupler to couple the shaft assembly to the instrument mounting portion; an actuation mechanism to actuate the end effector, wherein the actuation mechanism provides reciprocating movement of the blade within the channel; a lockout mechanism coupled to the actuation mechanism, the lockout mechanism to selectively enable reciprocating movement of the blade; and an interface to mechanically and electrically couple the instrument mounting portion to a manipulator; and a triggering mechanism for selectively activating the lockout mechanism.

In one embodiment a surgical tool is provided. The surgical tool comprises an instrument mounting portion housing; an instrument mounting portion plate; and a coupler to couple a shaft assembly to the instrument mounting portion, the shaft assembly comprising a RF end effector, the RF end effector having a first state wherein the RF end effector is energized with RF energy and a second state wherein the RF end effector is not energized with RF energy; an end effector actuation mechanism configured to actuate the RF end effector; a lockout mechanism coupled to the end effector actuation mechanism, wherein the wherein the lockout mechanism is mechanically coupled to the end effector actuation mechanism to allow actuation of the end effector actuation mechanism when the RF end effector is in the first state and to prevent actuation of the end effector actuation mechanism when the RF end effector is in the second state, wherein the lockout mechanism is a solenoid; and an interface to mechanically and electrically couple the instrument mounting portion to a manipulator.

Applicant also owns the following patent applications that are each incorporated by reference in their respective entireties:

U.S. patent application Ser. No. 13/536,271, filed on Jun. 28, 2012 and entitled "Flexible Drive Member,";

U.S. patent application Ser. No. 13/536,288, filed on Jun. 28, 2012 and entitled "Multi-Functional Powered Surgical Device with External Dissection Features,";

U.S. patent application Ser. No. 13/536,295, filed on Jun. 28, 2012 and entitled "Rotary Actuatable Closure Arrangement for Surgical End Effector,";

U.S. patent application Ser. No. 13/536,326, filed on Jun. 28, 2012 and entitled "Surgical End Effectors Having Angled Tissue-Contacting Surfaces,";

U.S. patent application Ser. No. 13/536,303, filed on Jun. 28, 2012 and entitled “Interchangeable End Effector Coupling Arrangement,”;

U.S. patent application Ser. No. 13/536,393, filed on Jun. 28, 2012 and entitled “Surgical End Effector Jaw and Electrode Configurations,”;

U.S. patent application Ser. No. 13/536,362, filed on Jun. 28, 2012 and entitled “Multi-Axis Articulating and Rotating Surgical Tools,”; and

U.S. patent application Ser. No. 13/536,417, filed on Jun. 28, 2012 and entitled “Electrode Connections for Rotary Driven Surgical Tools,”.

It will be appreciated that the terms “proximal” and “distal” are used throughout the specification with reference to a clinician manipulating one end of an instrument used to treat a patient. The term “proximal” refers to the portion of the instrument closest to the clinician and the term “distal” refers to the portion located furthest from the clinician. It will further be appreciated that for conciseness and clarity, spatial terms such as “vertical,” “horizontal,” “up,” or “down” may be used herein with respect to the illustrated embodiments. However, surgical instruments may be used in many orientations and positions, and these terms are not intended to be limiting or absolute.

Various embodiments of surgical instruments and robotic surgical systems are described herein. It will be understood by those skilled in the art that the various embodiments described herein may be used with the described surgical instruments and robotic surgical systems. The descriptions are provided for example only, and those skilled in the art will understand that the disclosed embodiments are not limited to only the devices disclosed herein, but may be used with any compatible surgical instrument or robotic surgical system.

Reference throughout the specification to “various embodiments,” “some embodiments,” “one example embodiment,” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one example embodiment. Thus, appearances of the phrases “in various embodiments,” “in some embodiments,” “in one example embodiment,” or “in an embodiment” in places throughout the specification are not necessarily all referring to the same embodiment. Furthermore, the particular features, structures, or characteristics illustrated or described in connection with one example embodiment may be combined, in whole or in part, with features, structures, or characteristics of one or more other embodiments without limitation.

While various embodiments herein have been illustrated by description of several embodiments and while the illustrative embodiments have been described in considerable detail, it is not the intention of the applicant to restrict or in any way limit the scope of the appended claims to such detail. Additional advantages and modifications may readily appear to those skilled in the art. For example, it is generally accepted that endoscopic procedures are more common than laparoscopic procedures. Accordingly, the present invention has been discussed in terms of endoscopic procedures and apparatus. However, use herein of terms such as “endoscopic”, should not be construed to limit the present invention to an instrument for use only in conjunction with an endoscopic tube (e.g., trocar). On the contrary, it is believed that the present invention may find use in any procedure where access is limited to a small incision, including but not limited to laparoscopic procedures, as well as open procedures.

It is to be understood that at least some of the figures and descriptions herein have been simplified to illustrate elements that are relevant for a clear understanding of the disclosure,

while eliminating, for purposes of clarity, other elements. Those of ordinary skill in the art will recognize, however, that these and other elements may be desirable. However, because such elements are well known in the art, and because they do not facilitate a better understanding of the disclosure, a discussion of such elements is not provided herein.

While several embodiments have been described, it should be apparent, however, that various modifications, alterations and adaptations to those embodiments may occur to persons skilled in the art with the attainment of some or all of the advantages of the disclosure. For example, according to various embodiments, a single component may be replaced by multiple components, and multiple components may be replaced by a single component, to perform a given function or functions. This application is therefore intended to cover all such modifications, alterations and adaptations without departing from the scope and spirit of the disclosure as defined by the appended claims.

Any patent, publication, or other disclosure material, in whole or in part, that is said to be incorporated by reference herein is incorporated herein only to the extent that the incorporated materials does not conflict with existing definitions, statements, or other disclosure material set forth in this disclosure. As such, and to the extent necessary, the disclosure as explicitly set forth herein supersedes any conflicting material incorporated herein by reference. Any material, or portion thereof, that is said to be incorporated by reference herein, but which conflicts with existing definitions, statements, or other disclosure material set forth herein will only be incorporated to the extent that no conflict arises between that incorporated material and the existing disclosure material.

What is claimed is:

1. A surgical tool, comprising:

an instrument mounting portion comprising:

a housing;

a plate;

a shaft assembly comprising an end effector, the end effector comprising a first jaw member and a second jaw member, the first and second jaw members defining a channel therebetween, and a blade slideably receivable within the channel, the blade configured to cut tissue located between the first and second jaw members; and

a coupler configured to couple the shaft assembly to the instrument mounting portion;

an actuation mechanism configured to actuate the end effector, wherein the actuation mechanism provides reciprocating movement of the blade within the channel;

a lockout mechanism coupled to the instrument mounting portion and in communication with the actuation mechanism, the lockout mechanism configured to selectively enable reciprocating movement of the blade; and

an interface configured to mechanically and electrically couple the instrument mounting portion to a manipulator.

2. The surgical tool of claim 1, wherein:

the end effector has a first state and a second state, wherein the lockout mechanism is configured to enable operation of the end effector actuation mechanism when the end effector is in the first state and to disable operation of the end effector actuation mechanism when the end effector is in the second state.

3. The surgical tool of claim 2, wherein the first state comprises an energized state and the second state comprises a de-energized state.

41

4. The surgical tool of claim 3, wherein the energized state comprises energizing the end effector with electrosurgical energy.

5. The surgical tool of claim 3, wherein the energized state comprises energizing the end effector with ultrasonic energy.

6. The surgical tool of claim 3, wherein the energized state comprises energizing the end effector with electrosurgical energy and ultrasonic energy.

7. The surgical tool of claim 1, wherein the lockout mechanism comprises a mechanical actuator arranged to engage the actuation mechanism when in a deployed state, wherein the mechanical actuator prevents movement of the actuation mechanism while in the deployed state.

8. The surgical tool of claim 7, wherein the mechanical actuator is a solenoid.

9. The surgical tool of claim 1, comprising an end of stroke indicator coupled to the end effector actuation mechanism such that the end of stroke indicator prevents the end effector actuation mechanism from extending beyond a predetermined maximum deployment.

10. A surgical system, comprising:

a surgical tool, comprising:

an instrument mounting portion comprising:

a housing;

a plate;

a shaft assembly comprising an end effector, the end effector comprising a first jaw member and a second jaw member, the first and second jaw members defining a channel therebetween, and a blade slidably receivable within the channel to cut tissue located between the first and second jaw members; and

a coupler configured to couple the shaft assembly to the instrument mounting portion;

an actuation mechanism configured to actuate the end effector, wherein the actuation mechanism provides reciprocating movement of the blade within the channel;

a lockout mechanism coupled to the instrument mounting portion and in communication with the actuation mechanism, the lockout mechanism configured to selectively enable reciprocating movement of the blade; and

an interface configured to mechanically and electrically couple the instrument mounting portion to a manipulator; and

a triggering mechanism for selectively activating the lockout mechanism.

11. The surgical system of claim 10, wherein the controller controls a state of the end effector, wherein the end effector has a first state wherein the end effector is energized by an energy source and a second state wherein the end effector is

42

not energized by an energy source, and wherein the controller may selectively place the end effector in the first and second states.

12. The surgical system of claim 11,

wherein the lockout mechanism is configured to allow actuation of the end effector actuation mechanism when the end effector is in the first state; and

wherein the lockout mechanism is configured to prevent actuation of the end effector actuation mechanism when the end effector is in the second state.

13. The surgical system of claim 11, wherein the controller is a foot pedal.

14. The surgical system of claim 10, comprising an end of stroke indicator.

15. The surgical system of claim 14, wherein the end of stroke indicator activates a return-path action for the blade.

16. The surgical system of claim 10, wherein the end effector actuation mechanism comprises a rack and pinion.

17. The surgical system of claim 10, wherein the end effector actuation mechanism comprises one or more worm gears.

18. The surgical system of claim 10, wherein the lockout mechanism comprises a mechanical actuator arranged to engage the end effector actuation mechanism when in a deployed state.

19. The surgical system of claim 18, wherein the mechanical actuator is a solenoid.

20. A surgical tool, comprising:

an instrument mounting portion housing;

an instrument mounting portion plate;

a coupler to couple a shaft assembly to the instrument mounting portion plate, the shaft assembly comprising a radio frequency (RF) end effector, the RF end effector having a first state wherein the RF end effector is energized with RF energy and a second state wherein the RF end effector is not energized with RF energy;

an end effector actuation mechanism configured to actuate the RF end effector;

a lockout mechanism coupled to the instrument mounting portion housing and the end effector actuation mechanism, wherein the lockout mechanism is mechanically coupled to the end effector actuation mechanism configured to allow actuation of the end effector actuation mechanism when the RF end effector is in the first state and to prevent actuation of the end effector actuation mechanism when the RF end effector is in the second state, and wherein the lockout mechanism is a solenoid; and

an interface configured to mechanically and electrically couple the instrument mounting portion plate to a manipulator.

* * * * *

专利名称(译)	用于机器人电外科设备的锁定机构		
公开(公告)号	US9326788	公开(公告)日	2016-05-03
申请号	US13/539110	申请日	2012-06-29
[标]申请(专利权)人(译)	BATROSS JONATHAN 树格雷高里 STULEN FOSTER 斯图尔特伦道夫 德留克斯Chad P制作		
申请(专利权)人(译)	BATROSS , JONATHAN T. 树木 , GREGORY A. STULEN , FOSTER B. STEWART , 兰多夫 包德留克斯 , 乍得P.		
当前申请(专利权)人(译)	爱惜康内镜外科 , LLC		
[标]发明人	BATROSS JONATHAN T TREES GREGORY A STULEN FOSTER B STEWART RANDOLPH BOUDREAUX CHAD P		
发明人	BATROSS, JONATHAN T. TREES, GREGORY A. STULEN, FOSTER B. STEWART, RANDOLPH BOUDREAUX, CHAD P.		
IPC分类号	A61B17/32 A61B18/14 A61B17/29		
CPC分类号	A61B17/320092 A61B18/14 A61B34/30 A61B90/03 A61B2018/1455 A61B2017/2927 A61B2017/320093 A61B2017/320094 A61B2017/320095 A61B2017/320097 A61B18/1445 A61B2017/2929 A61B2018/00642 A61B2018/00994		
审查员(译)	DIETRICH , JOSEPH		
其他公开文献	US20140005654A1		
外部链接	Espacenet USPTO		

摘要(译)

提供了一种包括锁定机构的机器人控制的手术工具。手术工具可包括器械安装部分。器械安装部分包括壳体，板，包括末端执行器的轴组件，以及将轴组件连接到器械安装部分的耦合器。末端执行器包括第一钳口构件和第二钳口构件，第一和第二钳口构件在其间限定通道，以及可滑动地容纳在通道内以切割位于第一和第二钳口构件之间的组织的刀片。手术工具可包括致动机构，以致动末端执行器以提供刀片在通道内的往复运动。锁定机构联接到致动机构。锁定机构可以选择性地实现叶片的往复运动。接口将仪器安装部分机械地和电气地耦合到机器人操纵器。

