




US 20130310833A1

(19) **United States**(12) **Patent Application Publication**
Brown et al.(10) **Pub. No.: US 2013/0310833 A1**(43) **Pub. Date: Nov. 21, 2013**(54) **METHODS AND DEVICES FOR ACCESS
ACROSS ADJACENT TISSUE LAYERS**filed on Nov. 16, 2012, provisional application No.
61/767,577, filed on Feb. 21, 2013.(71) Applicants: **Peter Brown**, Palo Alto, CA (US); **Sith
Khoun**, Fremont, CA (US); **Keke
Lepulu**, Menlo Park, CA (US); **Ryan
Donovan**, Mountain View, CA (US);
Kenneth F. Binmoeller, Rancho Santa
Fe, CA (US)**Publication Classification**(51) **Int. Cl.****A61B 17/34** (2006.01)**A61B 17/11** (2006.01)**A61B 18/12** (2006.01)(52) **U.S. Cl.**CPC **A61B 17/3476** (2013.01); **A61B 18/1206**
(2013.01); **A61B 17/1114** (2013.01)USPC **606/45**; 606/39(72) Inventors: **Peter Brown**, Palo Alto, CA (US); **Sith
Khoun**, Fremont, CA (US); **Keke
Lepulu**, Menlo Park, CA (US); **Ryan
Donovan**, Mountain View, CA (US);
Kenneth F. Binmoeller, Rancho Santa
Fe, CA (US)

(57)

ABSTRACT(21) Appl. No.: **13/871,978**(22) Filed: **Apr. 26, 2013****Related U.S. Application Data**(60) Provisional application No. 61/648,544, filed on May
17, 2012, provisional application No. 61/727,629,Adjacent tissue layers can be accessed using a catheter device
with a distal tip having a conductive portion including a first
cutting feature and one or more projections extending from
the first cutting feature towards an outer diameter of the distal
tip. Electrical energy can be supplied to the conductive por-
tion of the device to cut tissue. A stent can be delivered to form
a fluid communication between the adjacent tissue layers.




FIG. 1




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4B




FIG. 4A




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 6A







FIG. 6B






FIG. 7A




FIG. 7C




FIG. 7B




FIG. 7D




FIG. 8B




FIG. 8A




FIG. 9A




FIG. 9B




FIG. 10A




FIG. 10B




FIG. 11A




FIG. 11B




FIG. 12A




FIG. 12B




FIG. 13C



FIG. 13A




FIG. 13B




FIG. 14A




FIG. 14B




FIG. 14C




FIG. 14D




FIG. 15B




FIG. 15D




FIG. 15A




FIG. 15C




FIG. 15E




FIG. 15F




FIG. 16E




FIG. 16F




FIG. 16G




FIG. 16H




FIG. 16A




FIG. 16B




FIG. 16C




FIG. 16D




FIG. 17




FIG. 18A




FIG. 18B




FIG. 18C




FIG. 18D




FIG. 18E




FIG. 18F




FIG. 19A




FIG. 19B




FIG. 19C




FIG. 19D




FIG. 19E




FIG. 19F






FIG. 19G

FIG. 19H

FIG. 19I






FIG. 21A




FIG. 21B




FIG. 21C

FIG. 21D




FIG. 22B

FIG. 22A

METHODS AND DEVICES FOR ACCESS ACROSS ADJACENT TISSUE LAYERS

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to U.S. Provisional Application No. 61/648,544 filed on May 17, 2012, U.S. Provisional Application No. 61/727,629 filed on Nov. 16, 2012, and U.S. Provisional Application No. 61/767,577 filed on Feb. 21, 2013, the disclosure of each of which is incorporated by reference herein in their entirety.

[0002] This application is related to U.S. application Ser. No. 13/281,410, filed Oct. 25, 2011, U.S. application Ser. No. 13/363,297, filed Jan. 31, 2012, U.S. application Ser. No. 12/772,762, filed May 3, 2010, U.S. application Ser. No. 12/790,553, filed May 28, 2010, U.S. application Ser. No. 12/427,254, filed Apr. 21, 2009, and U.S. application Ser. No. 12/427,215, filed Apr. 21, 2009, the disclosures of which are incorporated herein by reference.

INCORPORATION BY REFERENCE

[0003] All publications and patent applications mentioned in this specification are herein incorporated by reference to the same extent as if each individual publication or patent application was specifically and individually indicated to be incorporated by reference.

FIELD

[0004] The present disclosure relates generally to medical methods and apparatus. More particularly, the present disclosure relates to methods and apparatus for penetrating adjacent tissue layers and enlarging the resulting penetration.

BACKGROUND

[0005] A number of inter and intra-luminal endoscopic procedures require precise placement of anchors or stents. For example, a number of procedures may be performed by entering the gastrointestinal (GI) tract through a first organ or structure, such as the esophagus, stomach, duodenum, small intestine, or large intestine, and delivering the anchor or stent to adjacent organs and lumen or tissue structures such as an adjacent portion of the GI tract, the bile duct, the pancreatic duct, the gallbladder, the pancreas, cysts, pseudocysts, abscesses, and the like. While primarily intended for use in the GI tract, such methods and apparatus can also be used for access to and from portions of the urinary tract, such as the urinary bladder and ureter, the pulmonary tract, such as the trachea and bronchi, and the biliary tract, such as the bile duct and gallbladder, as well.

[0006] Intra-ductal stents are commonly used to facilitate the opening of closed vessels for access, drainage or other purposes. Tissue anchors are used to secure adjacent tissues or organs. Inter-luminal tissue anchors, which include a central lumen, are used to facilitate fluid communication between adjacent ducts, organs or lumens. Often, the precise placement of the tissue anchor or stent is necessary, especially when the tissue anchor or stent has well defined anchoring elements at the proximal and/or distal ends, and the device is used to secure adjacent lumens.

[0007] When deploying a stent or other tissue anchor between adjacent body lumens, organs, or other structures, it is typically necessary to penetrate both a wall of the first body lumen through which access is established and a wall of a

second body lumen which is the target for the procedure. When initially forming such access penetrations, there is a significant risk of leakage from either or both of the access body lumen and the target body lumen into the surrounding space including, but not limited to the peritoneal cavity. In some procedures, such as those involving transgastric or transduodenal bile duct access, loss of body fluid into surrounding tissues and body cavities can present a substantial risk to the patient. The risk can be exacerbated when it is necessary to not only penetrate the luminal walls to gain initial access, usually with a needle, but to subsequently enlarge or dilate the initial penetration, for example by passing a tapered dilator over the needle used to establish initial access. Dilation of the initial tissue penetration can cause additional damage to the tissue penetration and is an additional opportunity for leakage.

[0008] Thus, it would be desirable to establish initial luminal wall penetrations and to subsequently dilate said penetrations in order to deploy a stent, anchor, or for other purposes, while minimizing the risk of body fluid leakage. It is also desirable for improved access to body lumens while minimizing trauma and damage to the tissue surrounding the initial luminal wall penetration. It would be further desirable to provide improved protocols and access tools which are capable of being deployed from endoscopes present in a first body lumen to access adjacent body lumens or cavities while minimizing the risk of leakage. Such access tools and protocols should be compatible with a wide variety of procedures, such as placement of stents or other tissue anchors between adjacent luminal walls, and will preferably reduce or eliminate the need to exchange tools during the access procedure.

SUMMARY OF THE DISCLOSURE

[0009] Methods for advancing a catheter distally through opposed first and second luminal walls of first and second body lumens are disclosed herein. The methods include positioning a catheter with a distal tip proximal to the first luminal wall, the catheter including a stent; providing an electrical current to a conductive portion of the distal tip; advancing distally the distal tip of the catheter through the first and second luminal walls to create a passage therethrough, wherein the conductive portion of the distal tip includes a first cutting feature and one or more projections extending from the first cutting feature towards an outer diameter of the distal tip; deploying a distal flange of the stent in the second body lumen; and drawing proximally on the distal flange to pull the first and second luminal walls towards each other. The methods can include releasing a proximal flange of the stent into the first body lumen. The methods can include attaching the catheter to an endoscope prior to positioning the catheter.

[0010] The methods can also include forming a hole in the first and second body lumens using a needle prior to positioning the catheter. In some embodiments the catheter can be positioned using a guidewire. In some embodiments a guidewire is not used for positioning the catheter and the distal tip does not have a guidewire lumen.

[0011] In some embodiments the first cutting feature and one or more projections can have an arced configuration. In some embodiments the first cutting feature comprises a concentric ring that is concentric to a lumen in the distal tip of the catheter. In some embodiments the catheter is disposed about a guidewire and positioning includes advancing the catheter along the guidewire, wherein the concentric ring is configured to be disposed about the guidewire. In some embodi-

ments the catheter includes a sheath radially constraining the stent, the stent being a self-expanding stent. Deploying the proximal and distal flanges can include retracting the sheath to allow the proximal and distal flanges of the stent to expand. In some embodiments the methods include verifying the deployment of the distal flange prior to drawing proximally. Verifying the deployment of the distal flange can be done using ultrasound.

[0012] In some embodiments advancing the distal tip through the first and second luminal walls to create the passage therethrough forms a first patterned hole in the first luminal wall and a second patterned hole in the second luminal wall. The first and second patterned holes can have a diameter that is less than the maximum diameter of the distal tip. The first and second patterned holes can each include a central hole with one or more projections radiating from the central hole.

[0013] The first body lumen can be within the digestive tract. In some embodiments the first body lumen is selected from the group consisting of: esophagus, stomach, duodenum, jejunum, small intestine, large intestine, colon, and rectum. The second body lumen can be part of the digestive tract or biliary tree. In some embodiments the second body lumen is selected from the group consisting of: esophagus, stomach, duodenum, jejunum, small intestine, large intestine, colon, bile duct, pancreatic duct, gallbladder, and pancreas. In some embodiments the first and second body lumens are sections of the colon. In some embodiments the first body lumen is the stomach or duodenum and the second body lumen is the gallbladder. In some embodiments the first and second body lumens are a fundal pouch and a section of the duodenum or jejunum.

[0014] The methods can include forming an anastomosis between the first and second body lumens. The methods can include removing the stent after forming the anastomosis.

[0015] Catheter assemblies are disclosed herein. The catheter assemblies can include a catheter body having a proximal end, a distal end, and a central passage therethrough; and a tip positioned near the distal end of the catheter body, the tip having a conductive portion including a first cutting feature and one or more projections outwardly extending from the first cutting feature towards an outer diameter of the tip, the conductive portion configured to be electrically coupled to an electrosurgical generator.

[0016] In some embodiments the first cutting feature and one or more projections has an arced configuration. In some embodiments the first cutting feature comprises a concentric ring. In some embodiments the catheter has a guidewire lumen and the concentric ring is configured to be disposed about and insulated from the guidewire lumen. In some embodiments the tip does not have a guidewire lumen.

[0017] In some embodiments the conductive portion including two projections. In some embodiments the conductive portion including four projections. In some embodiments the conductive portion includes an exterior portion made of stainless steel and an interior portion comprising copper electrically coupled to the exterior portion and configured to be electrically coupled to an electrosurgical generator.

[0018] In some embodiments the one or more outwardly extending projections extend from the first cutting feature to a maximum radial position, the maximum radial position defining a length between the radial position and a center point of the distal tip, wherein the length is less than 50% of the outer diameter of the tip. In some embodiments the one or

more projections outwardly extending from the first cutting feature towards the outer diameter of the tip include a covered portion adjacent to a maximum diameter of the tip.

[0019] In some embodiments the catheter includes a compartment within the catheter body configured to hold a stent. A stent can be included within the compartment within the catheter body. The stent can be self-expanding. The self-expanding stent can be radially restrained by a movable sheath. The stent can be configured to expand to form distal and proximal double-walled flanges. In some embodiments the stent can have a pull-out strength of greater than about 400 grams.

[0020] The catheter can be configured to be attached to an endoscope. The catheter can also include a control handle configured to control the energy provided by the electrosurgical generator to the first cutting feature and the one or more projections. The electrosurgical generator can be configured to supply about 50 watts to about 100 watts of power to the conductive portion of the tip.

[0021] In some embodiments the catheter assembly includes an inner catheter shaft engaged with the distal tip and configured to move relative to the catheter body within the central passage of the catheter body. The inner catheter shaft and distal tip can be configured to be removable from the catheter body.

[0022] In some embodiments methods for advancing a catheter distally through a luminal wall of a first body lumen are provided. The methods include positioning a catheter comprising an outer tubular body and inner body with a distal tip proximal to the luminal wall of the first body lumen; providing an electrical current to a conductive portion of the distal tip; advancing distally the distal tip of the catheter through the first luminal wall along with a portion of the outer tubular body to create a passage therethrough, wherein the conductive portion of the distal tip includes a first cutting feature and one or more projections extending from the first cutting feature towards an outer diameter of the distal tip; and withdrawing the inner body and distal tip through the outer tubular body leaving a portion of the outer tubular body in the passage in the luminal wall of the first body lumen. The first luminal wall can be the transgastric wall or transduodenal wall. The methods can include forming a hole in a pseudocyst during advancing distally. The methods can also include passing a catheter, stent, or drainage device through the outer tubular body and into the hole in the pseudocyst.

[0023] Positioning can include following a guidewire to a target location of the luminal wall of the first body lumen. The first cutting feature can be a concentric ring that is concentric to a lumen in the distal tip of the catheter. The first cutting feature and one or more projections can be an arced configuration.

[0024] In some embodiments the methods include deploying a distal flange of a stent in the pseudocyst and deploying a proximal flange of the stent in contact with the transgastric wall or transduodenal wall.

BRIEF DESCRIPTION OF THE DRAWINGS

[0025] The novel features of the invention are set forth with particularity in the claims that follow. A better understanding of the features and advantages of the present invention will be obtained by reference to the following detailed description that sets forth illustrative embodiments, in which the principles of the invention are utilized, and the accompanying drawings of which:

[0026] FIG. 1 is a perspective view of a catheter constructed in accordance with the principles of the present disclosure.

[0027] FIG. 2A illustrates one embodiment of a distal tip of the catheter of FIG. 1. FIG. 2B illustrates one embodiment of a handle of the catheter of FIG. 1.

[0028] FIGS. 3A-3C illustrate various views of a distal tip of a catheter in accordance with an embodiment.

[0029] FIG. 4A is an image of a distal tip of a catheter in accordance with an embodiment. FIG. 4B is an image of a prior art catheter tip.

[0030] FIGS. 5A-5E illustrate the use of the catheter of FIG. 1 for penetrating opposed luminal walls in accordance with an embodiment.

[0031] FIGS. 6A-6E illustrate various views of a distal tip in accordance with an embodiment.

[0032] FIGS. 7A-7D illustrate various views of a distal tip in accordance with an embodiment.

[0033] FIGS. 8A-8B illustrate various views of a distal tip in accordance with an embodiment.

[0034] FIGS. 9A-9B illustrate various views of a distal tip in accordance with an embodiment.

[0035] FIGS. 10A-10B illustrate various views of a distal tip in accordance with an embodiment.

[0036] FIGS. 11A-11B illustrate various views of a distal tip in accordance with an embodiment.

[0037] FIGS. 12A-12B illustrate various views of a distal tip in accordance with an embodiment.

[0038] FIGS. 13A-13C illustrate additional distal tip designs in accordance with embodiments.

[0039] FIGS. 14A-14D illustrate additional distal tip designs in accordance with embodiments.

[0040] FIGS. 15A-15F illustrate additional distal tip designs in accordance with embodiments.

[0041] FIGS. 16A-16H illustrate various tissue access patterns made by the devices disclosed herein.

[0042] FIG. 17 is an image of a tissue access pattern made using the tip illustrated in FIGS. 3A-3C.

[0043] FIGS. 18A-18F illustrate various configurations of stents that can be delivered using the devices disclosed herein in accordance with embodiments.

[0044] FIGS. 19A-19I illustrate various configurations of stents that can be delivered using the devices disclosed herein in accordance with embodiments.

[0045] FIGS. 20A-20B illustrate a stent configuration in accordance with an embodiment.

[0046] FIGS. 21A-21D illustrate various configurations of stents that can be delivered using the devices disclosed herein in accordance with embodiments.

[0047] FIGS. 22A-22B is a drawing with dimensions of a stent in accordance with an embodiment.

DETAILED DESCRIPTION

[0048] Improved catheter tip designs are disclosed herein. The designs disclosed herein offer a number of advantages over prior art designs. The devices disclosed herein can more quickly and efficiently cut through tissue with less leakage, trauma, and thermal damage to surrounding tissue than previous designs. Conventional blunt tip designs require higher power that can cause excessive heating that can also damage tissue adjacent to the target area. The prior art tip designs can also require longer amounts of time to cut the tissue. The longer exposure times can further exacerbate thermal damage to tissue. It is desirable for improved catheter tip designs to overcome many of the problems with the prior art tip designs.

[0049] The device 10 of FIG. 1 includes a control handle 12 having a body 14 with a first slide actuator 15 with knob 16 and lock 20. A second slide actuator 18 with lock 22, scope locking mechanism 24, electrical plug 23, catheter body 26, a sheath 27, shaft 28, stent lock 30, distal tapered tip 32 and stent or other tissue anchor 34 (FIG. 2A). FIG. 2A is an enlarged portion of the end of the device 10, including the distal tapered tip 32. FIG. 2B is an enlarged portion of the handle of the device 10, including the electrical plug 23. An electrical source can be plugged into electrical plug 23 to provide electricity.

[0050] The distal tapered tip 32 includes a distal tip base 33. The sheath 27 can contact the distal tapered tip and engage with an outer diameter of the distal tip base 33. The stent lock 30 and/or sheath 27 can radially constrain the stent 34 and prevent the stent 34 from expanding. The distal tapered tip 32 includes a conductive portion with a cutting element 35. The illustrated cutting element 35 has a concentric design about a guidewire lumen 39. The conductive projections 36 extend from the cutting element 35 towards the outer diameter of the distal tip 32. The illustrated projections 36 enter into a recessed portion 41 (FIG. 3B) of the distal tip 32.

[0051] The conductive areas of the tip, such as the cutting element 35 and projections 36 can be configured to cut, heat, and/or cauterize tissue in a patient. Electrical energy is supplied to energize the conductive areas of the tip. Electrical energy can be supplied to the conductive portions of the tip, such as radiofrequency (RF) and high-frequency (HF) energy. The electrical energy can be supplied through electrical plug 23. The handle includes an electrical control to control the electrical energy supplied to the tip.

[0052] The cutting element 35 and illustrated projections 36 can be made out of a conductive medical grade material that is biocompatible, such as stainless steel. A different conductive material, such as copper, can be used to supply electrical energy to the cutting element 35 and projections 36. The projections 36 can connect to the wiring 38 at connection 37. The wiring 38 is in electrical contact with the electrical plug 23. The electrical plug 23 supplies electrical energy through the wiring 38 to the cutting element 35 and projections 36. The distal tip 32 is made out of an insulating material to insulate the cutting element 35 and projections 36 from the surrounding device structure.

[0053] FIGS. 3A-3C illustrate enlarged views of the distal tip 32. FIG. 3A is a side view showing the projections 36 entering the distal tip 32 just short of the outer diameter of the distal tip 32. FIG. 3B is a top view of the distal tip 32 showing the projections 36 entering into the recessed portion 41 of the distal tip 32. FIG. 3C is an isometric view of the distal tip 32. FIG. 4A is an image of the distal tip illustrated in FIGS. 3A-3C.

[0054] The distal tip shown in FIGS. 3A-3C can produce a tissue cut pattern that contains a central cut region with two linear cuts protruding radially from the central region or ring as shown in FIG. 16B and FIG. 17. The projections 36 in FIGS. 3A-3C recede into the recessed portion 41 of the distal tip 32 before the distal tip 32 reaches its maximum diameter. In some embodiments the projections can be covered adjacent to the outer diameter such that the exposed portion of the projections do not reach the maximum outer diameter of the distal tip 32. The slits made in the tissue by the projections 36 are slightly shorter than the diameter of the tip. Some force can be applied to push the distal tip through the tissue slits made by the energized tip. The elasticity of the tissue can

accommodate the slightly larger diameter of the distal tip and catheter. The tight fit can prevent leakage of biological material from the body lumen.

[0055] The outwardly extending projections can extend from the first cutting feature to a maximum radial position. The maximum radial position of a projection defines a length between the maximum radial position and the center point of the distal tip. The length between the maximum radial position and center of the tip is less than 50% of the outer diameter of the tip (e.g. two times the length between the maximum radial position and center of the tip is less than 100% of the outer diameter of the tip). In some embodiments the length between the maximum radial position and center of the tip is less than about 47.5% of the outer diameter of the tip. In some embodiments the length between the maximum radial position and center of the tip is less than about 45% of the outer diameter of the tip (e.g. less than about 90% of the outer radius of the tip). In some embodiments the length between the maximum radial position and center of the tip is less than about 40% of the outer diameter of the tip (e.g. less than about 80% of the outer radius of the tip). In some embodiments the length between the maximum radial position and center of the tip is less than about 37.5% of the outer diameter of the tip (e.g. less than about 75% of the outer radius of the tip).

[0056] FIGS. 1, 2A, 2B, and 3A-3B illustrate a mono-polar tip that receives current from the wire 38 disposed within the catheter body 14. The wire 38 can extend along the length of the catheter body 14 terminating within the handle 12 of FIG. 1. The wiring 38 and conductive areas of the tip can receive electrical energy, such as RF energy, from a generator unit (not shown) electrically coupled to the handle 12 at the electrical plug 23. The electrical plug 23 is illustrated as a mono-polar plug in FIG. 2B. When the tip comprises a mono-polar design, a grounding pad can be used on the patient. In alternative embodiments, the RF tip can comprise a bi-polar design. In some embodiments providing electrical energy to the conductive areas of the tip can be controlled by an activation switch, dial, or other structure on the handle (not shown). In some embodiments providing electrical energy to the conductive areas of the tip can be controlled using an external switch accessory or foot pedal associated with the electrosurgical generator.

[0057] The tip designs disclosed herein allow for an increased electrical current density that can facilitate quicker cutting through tissue and reduced trauma to the surrounding tissue areas. The tip designs reduce the likelihood of leakage and complications for the surgical procedures. FIG. 4B shows a conventional blunt nose conical tip with a welded electrical connection produced by Cook Medical Inc. The tip produced by Cook Medical provides electrical power to the entire blunt tip. The tip requires a relatively large amount of power and carries a lower electrical current density. The lower electrical current density requires longer times to cut through tissue, which can produce excessive heating that can cause damage to the surrounding tissue areas and the surrounding catheter parts. The blunt nose can also cause tearing of the tissue, which increases the chances of leakage of biological material.

[0058] FIGS. 5A-5E illustrate steps for accessing adjacent body lumens, such as lumen L1 and lumen L2. The catheter device 10 is attached to an endoscope 40. The distal end of endoscope or echo-endoscope 40 (FIG. 5A-5E) is positioned usually via trans-oral entry adjacent to a target location within the GI tract.

[0059] Initial access between lumen L1 and lumen L2 can be done using a 19 gauge needle. For example, a puncture can be made at the desired location using a 19 gauge needle, such as an electrosurgical needle, followed by placement of a guidewire 102 through the needle lumen. In some embodiments a guidewire is not used. In some embodiments the catheter device 10 can be used for initial access to make a puncture between lumen L1 and lumen L2. Electrical energy can be provided to the cutting element 35 and projections 36 to make the initial puncture in lumen L1 and lumen L2.

[0060] As illustrated in FIG. 5A, after initial access, the catheter body 26 is advanced over the guidewire 102 through the working channel of the endoscope 40 and is secured to the proximal end of a working channel using scope locking mechanism 24 to locate the catheter body 26 with a tip 32 approximately 1 cm outside of the distal end of the working channel.

[0061] Initial access using a needle typically forms a hole smaller than the diameter of the catheter device 10. The tissue holes in tissue T1 and tissue T2 can be dilated before or during the advancement of the distal tip 32 of the catheter through the penetrations in tissue T1 and tissue T2. Electrical energy can be supplied to the cutting element 35 in order to enlarge the initial penetration in the tissue and facilitate the movement of the catheter shaft through the penetration in tissue T1 and tissue T2. As illustrated in FIG. 5B, the first slide actuator 15 is distally advanced using knob 16, after releasing lock 20, on handle 12, thus moving the assembly of catheter body 26, shaft 28, and stent 34, in the distal direction and through the tract formed through tissue T1 and tissue T2 and moving distal tapered tip 32 from lumen L1 to lumen L2. The electrical plug 23 supplies electrical energy to cutting element 35 and projections 36 to cut the tissue and enlarge the hole. Lock 20 is then reengaged, securing first slide actuator 15 to control handle body 14.

[0062] The distal tip 32, cutting element 35, and projections 36 can cut the tissue to enlarge the hole. The tip design illustrated in FIGS. 3A-3C illustrates projections 36 that recede into the inner volume of the distal tip 32 prior to expanding radially to the full diameter of the distal tip 32. The projections 36 cut the tissue T1 and tissue T2 a little bit less than the full diameter of the distal tip 32. The catheter shaft 28 fits snugly into the enlarged holes in tissue T1 and tissue T2 and stretches the openings in tissue T1 and tissue T2 to conform to the diameter of the shaft 28. This forms a tight seal between the catheter shaft 28 and the holes in tissue T1 and tissue T2 thereby limiting the leakage of material enclosed in lumen L1 and lumen L2.

[0063] A distal flange segment 42 of the tissue stent or anchor 34 is now expanded by moving the second slide actuator 18 in the proximal direction to retract sheath 27. The second slide actuator is pulled back to a predetermined position part way along the proximal extension 17 of the first slide actuator 15, after releasing second lock 22 as in FIG. 5C. A portion of lock 22 (FIG. 1) of second slide actuator 18 moves in a track (not shown), where said lock 22 engages a stop at a predetermined position, thereby stopping the proximal movement of actuator 18. The predetermined position can be calibrated to allow only the distal flange 42 of tissue anchor 34 to be released from constraint by sheath 27 and to expand. Said proximal motion of second slide actuator 18 retracts the sheath 27, while the shaft 28 is held in place, this releasing the distal portion of tissue anchor 34 from constraint. The catheter operator can pause after deploying the distal flange to

verify the expansion of the distal flange. In some embodiments ultrasound can be used to visualize the expansion of the distal flange segment 42. In some embodiments direct visualization of the expansion of the distal flange segment 42 is possible. In some embodiments the sheath can have a visible marker that can be visualized after partial retraction of the sheath. The marker on the sheath can be obscured by the tissue walls prior to retraction. After retracting the sheath a distance sufficient to remove the restraint from the distal flange, the marker on the sheath can then be visible. The marker can be visible under ultrasound imaging, direct visualization, or fluoroscopy. In some cases multiple markers can be used on the sheath with different colors or patterns that can be visually differentiated and correspond to retraction of the sheath over various distances.

[0064] The first slide actuator 15 is now moved slowly in the proximal direction using knob 16, after releasing lock 20, on handle 12, thus moving the expanded distal anchor flange 42 against the inner surface of tissue T2 of lumen L2, and positioning tissue T1 closer to tissue T2, holding lumen L1 and L2 in close apposition as in FIG. 5D. The distal flange 42 can be used to engage and control lumen L2. The distal flange 42 can be used to approximate and adhere lumen L1 and L2.

[0065] Stent lock 30 (FIG. 2A) holds the proximal end of the tissue/stent anchor 34 firmly allowing proximal traction against tissue T2. Lock 20 is then reengaged, securing first slide actuator 15 to control handle body 14. The engagement of distal flange 42 with lumen L2 and tissue T2 can be verified prior to releasing the proximal end of the stent 34. The engagement of the distal flange 42 with lumen L2 can be verified using ultrasound or through visualization of a marker on the sheath. The marker on the sheath can be visible once the sheath has been retracted and the distal flange is engaged with tissue T2. For example the marker could be at a distance from the end of the sheath slightly greater than the thickness of the tissue walls T1 and T2. Thus, the marker would only be visible after retracting the sheath to expand the distal flange 42 and engaging the distal flange 42 with tissue T2 thereby making the marker on the sheath visible to the endoscope within lumen L1.

[0066] A proximal segment 44 of the tissue anchor stent 34 is now expanded by moving the second slide actuator 18 in the proximal direction to a position at or near the proximal end of the first slide actuator 15, after releasing lock 22 as in FIG. 5E to further retract the sheath 27. The proximal end of the tissue anchor stent 34 releases from stent lock 30 (FIG. 2A) as the second slide actuator 18 reaches the proximal end of its travel. This releases the entire tissue anchor, which in this example has a central lumen 46 allowing fluid communication between lumens L1 and L2. The device 10 is now removed, leaving the tissue anchor 34 with central lumen 46 implanted between lumen L1 and lumen L2 with fluid communication being established. The stent 34 can promote the formation of a healthy anastomosis between lumen L1 and lumen L2 by firmly holding tissues T1 and T2 together while minimizing damage to the tissue walls. The stent 34 can be removed at a later date.

[0067] The stent 34 is illustrated with a double walled flange structure. The configuration of the flanges and diameter and length of the central lumen 46 can be selected based on the body lumens L1 and L2 and the thickness of the tissue walls T1 and T2. A variety of stent shapes and materials can be used, such as the stent structures illustrated in FIGS. 18A-18E and described in greater detail below.

[0068] A variety of different tip designs can be used for the conductive portion and cutting elements. Additional tip designs are illustrated in FIGS. 3-15 and discussed in greater detail below.

[0069] In some embodiments, the devices disclosed herein have a smaller cutting surface area than prior art cone devices. The surface area of the external conductive portion illustrated in FIGS. 3A-3C is less than one sixth of the surface area for a cone having similar dimensions.

[0070] The blunt cone shaped tip was calculated to have a surface area of approximately 20.2 mm². The tip design in the embodiment illustrated in FIGS. 3A-3C was calculated to have a cutting surface area of about 3.17 mm². In some embodiments the conductive cutting portion of the distal tip has a surface area of less than about 10 mm². In some embodiments the conductive cutting portion of the distal tip has a surface area of less than about 5 mm². In some embodiments the conductive cutting portion of the distal tip has a surface area of less than about 4 mm².

[0071] The smaller cutting surface area will have a higher current density than a larger surface area (e.g. with a cone shape) for a given power. The higher current density on the cutting surface area can facilitate quicker cutting of the tissue. The faster cutting can minimize the thermal injury to the tissue that is cut along with adjacent tissue. Examples of thermal damage to tissue include coagulation, loss of elasticity of the tissue, denaturing of proteins, and necrosis. The devices disclosed herein can minimize tissue damage thereby maintaining tissue elasticity after cutting the tissue.

[0072] The devices disclosed herein can operate at a wide range of powers, for example from about 30 Watts to about 200 Watts or greater. In some embodiments about 50 Watts to about 100 Watts can be used to provide power to the conductive cutting surface. The reduced surface area of the cutting surface can facilitate the operation of the device at lower powers because the current running through the cutting surface area can still be high enough to cut through the tissue.

[0073] The devices disclosed herein can operate with a higher energy density, represented by the power divided by the surface area of the conductive cutting surface area, for a given power versus conventional cone shaped energized tip designs. The tip design in the embodiment illustrated in FIGS. 3A-3C was calculated to have an energy density of 9.4 Watts/mm² at a power of 30 Watts, 31.5 Watts/mm² at a power of 100 Watts, and 63.0 Watts/mm² at a power of 200 Watts. A conventional blunt conical shaped tip design was calculated to have an energy density of 1.5 Watts/mm² at a power of 30 Watts, 5.0 Watts/mm² at a power of 100 Watts, and 9.9 Watts/mm² at a power of 200 Watts. The calculated power density for the tip design illustrated in FIGS. 3A-3C was over six times higher than the power density for the same power supplied to a blunt conical shaped tip with similar dimensions.

[0074] In some embodiments the energy density of the conductive cutting surface area of the distal tip is between about 5 Watts/mm² and 100 Watts/mm². In some embodiments the energy density of the conductive cutting surface area of the distal tip is greater than about 10 Watts/mm². In some embodiments the energy density of the conductive cutting surface area of the distal tip is greater than about 30 Watts/mm². In some embodiments the energy density of the conductive cutting surface area of the distal tip is greater than about 60 Watts/mm².

[0075] The devices disclosed herein can also use a lower mass as less metal is used for the cutting surface and the other

portions of the tip can be made out of lighter weight insulating materials such as ceramics, plastics, and other light-weight materials.

[0076] In some embodiments a scalpel-like cut through multiple tissue layers using HF current can be done. Some embodiments use a central HF powered feature located adjacent to the guidewire to form an initial cut into the tissue and HF powered projections extending out radially from the center feature to cut a slit in the tissue planes.

[0077] In some embodiments different frequencies or power can be supplied to different conductive areas on the tip. In some embodiments two or more conductive areas can be used, which can be supplied power by one or more power sources.

[0078] In some embodiments the devices disclosed herein can use a metallic ring (concentric or non-concentric in nature) or a segmented metallic ring (concentric or non-concentric in nature) with a projection or projections extending radially outward from the ring. The ring and projections are connected to the energy source, such as a RF or HF generator or energy source. The projections and central cutting feature may be connected to a single channel of an energy source. Alternatively, the projections and central cutting feature may be connected to two or more channels of an energy source or sources, such that different energy profiles may be applied to various features. A portion of the cutting features can be partially embedded in the insulating material.

[0079] In some embodiments the portion of the conductive area that is exposed at the outer surface of the distal tip can be segmented or discontinuous. In some embodiments the projections can be discontinuous or segmented. Each of the segments or discontinuous portions can be in electrical communication with each other and/or one or more electrical sources.

[0080] In some embodiments the central feature and projections do not include a ring. For example, the central feature and projections can be an arc extending from one side of the distal tip to the opposing side of the distal tip in an arc configuration.

[0081] In some embodiments the tip design includes one or more outward projections. In some embodiments one or more (1-N) features or projections protrude in a radial fashion. The projections can have a linear design, curved or arced shapes, and other geometric shapes. Additional examples include a helical twist and interconnected rings from a central point or HF powered feature. Each feature would result in a linear cut in the tissue radiating outward from a central point. The (1 . . . N) features would result in (1 . . . N) cuts and subsequently N number of tissue leaflets or valve leaflets. In the case of a single feature, one linear feature creates 2 tissue leaflets. These leaflets in turn act as valves preventing excessive material transfer (fluid, tissue, matter) from passing from the target anatomical structure to the access structure or from the access structure to the target anatomical structure.

[0082] In some embodiments the devices can be used with a guidewire lumen or hole in the tip. The guidewire is shielded from the current supplied to the tip. The devices disclosed herein can follow a guidewire placed within the target anatomical structure. The guidewire can be placed in the target anatomical structure using a needle, such as a 19 gauge needle. The devices can follow the guidewire until the tip is at the target anatomical structure. Energy can be supplied to the tip of the device, such as radiofrequency (RF), high-frequency (HF), or other types of energy. An electrosurgical

generator can be used to power the tip in some embodiments. The energized tip of the device can then cut through the tissue to create luminal access into the target anatomical structure. The high current density tip is designed to cut through a tissue plane resulting in minimal thermal injury to the tissue planes and timely access to the target anatomical structure.

[0083] In some embodiments the catheter devices and tip designs does not follow a guidewire with the energized tip used for initial access to the body lumens. In some embodiments the catheter devices do not include a guidewire lumen and can be used without a guidewire. In some embodiments the catheter devices can be positioned without a guidewire but may include a guidewire lumen for placing a guidewire after initial access to the body lumens.

[0084] The methods and devices disclosed herein can be used to cut in any angular catheter orientation. For example, the tip and cutting element can follow a guidewire and cut tissue orientated in any angle relative to the guidewire. The cutting element can cut tissue when the guidewire forms an acute angle with the tissue plane. Prior art blunt cone devices do not cut tissue well when they intersect the tissue at an acute angle and often cause tissue tearing and trauma while sliding along the tissue surface. The prior art blunt cones can also have a difficult time following a guidewire path at an acute angle with the tissue surface and undesirably change the shape and orientation of the resulting tissue penetration.

[0085] Minimal tenting and displacement of the tissue plane of the target anatomical structure is also desired. Minimizing the displacement and tenting of the tissue plane can help prevent excessive biological matter leakage and provide a level of safety given the path following the guidewire. In addition minimal displacement is important because if the tissue/target is moved significantly the physician may lose visibility of the field, in particular when visualization is done by ultrasound imaging.

[0086] A variety of distal tip **32** designs can be used in the devices disclosed herein. The tip designs disclosed herein can be designed to minimize or prevent leakage from the opening cut in the passage of the targeted anatomical structures given the large diameter of the catheter entering the anatomical structures. The tip can be designed to achieve a desired cut tissue pattern in the luminal walls. FIGS. **3A-3C** illustrate a cutting element **35** with a concentric design and two projections **36** at about 180 degrees from each other. The cut pattern delivered by the tip illustrated in FIGS. **3A-3C** can mimic a bi-leaflet valve opening while allowing the passage of the device through the tissue planes limiting biological material leakage across those tissue planes. FIGS. **17A-17H** and **18** show examples of tissue cut patterns. In some embodiments the tissue cut pattern can be a bi, tri, quad . . . n leaflet valve opening type.

[0087] FIGS. **6A-6E** illustrate various views of a distal tip **32** in accordance with an embodiment. The distal tip **32** is connected to the shaft **28**. The distal tip **32** includes two insulating sections **61a** and **61b** with a cutting element **63** sandwiched between the sections **61a** and **61b**. The cutting element **63** includes a central cutting feature **64** with a semi-circular configuration and two outward projections **65**. Electrical energy can be supplied to the cutting element **63** to cut tissue. The cutting element **63** can be stamped or machined in the desired configuration. The semi-circular configuration **64** can be sized to fit the outer diameter of the shaft **28**. In some embodiments a second cutting element can be used with a shape mirroring the cutting element **63** to form a circular

cutting feature. In some embodiments wire can be used to form a circular conductive feature about the shaft **28** at the distal portion of the cutting element **63**. The design illustrated in FIGS. **6A-6E** can be manufactured from a stamped metal such as stainless steel and co-molded with an insulating material to form the remainder of the distal tip **32**.

[0088] FIGS. **7A-7D** illustrate various views of a distal tip **32**. The distal tip **32** includes an insulating portion **71** and two cutting elements **72** in accordance with an embodiment. Each cutting element **72** includes a central cutting feature **73** with an arced configuration and outward projections **74**. Electrical energy can be supplied to the cutting element **72** to cut tissue by connecting a wire to the cutting element. The cutting element **72** can be stamped or machined to form the desired configuration. The arced configuration **73** can be sized to engage with the outer diameter of the shaft. In some embodiments more than two cutting elements **72** can be embedded in the tip. In some embodiments three or four cutting elements can be embedded in the distal tip.

[0089] FIGS. **8A** and **8B** illustrate various views of a distal tip **32** in accordance with an embodiment. The distal tip **32** includes an insulating portion **81** and a cutting element **82**. The cutting element **82** includes a central cutting feature **83** with a circular shape and outward projections **84**. The outward projections extend outwardly towards the outer diameter of the tip **32** in a helical configuration. The projections **84** extend radially to an outer diameter that is less than the outer diameter of the insulating portion **81**. FIGS. **8A** and **8B** illustrate a clockwise spiral for the projections **84**. A counter clockwise spiral configuration can also be used. In some embodiments the projections can be straight. In some embodiments the projections can have a sinusoidal configuration. Electrical energy can be supplied to the cutting element **82** to cut tissue by connecting a wire to the cutting element.

[0090] FIGS. **9A** and **9B** illustrate a distal end of a catheter device **90** with multiple rings **91**, **92** in accordance with an embodiment. The inner ring **91** and outer ring **92** can be energized by electrical energy. The inner ring **91** and outer ring **92** can have separate wiring and electrical power sources. The power and type of electrical energy provided to the inner ring **91** and outer ring **92** can be different and separately controlled for each ring. The inner ring **91** can be used to make the initial access hole in the body lumen or enlarge an initial penetration formed by a needle. The outer ring **92** can be used to enlarge the passageway formed by the inner ring **91**.

[0091] FIGS. **10A** and **10B** illustrate a distal tip of a catheter device **100** in accordance with an embodiment. The distal tip has a cutting feature **101** made out of a conductive material and an insulating portion **103**. The device **100** is configured to be used without a guidewire. Electrical energy is supplied to the cutting feature **101** to cut tissue. FIGS. **11A** and **11B** illustrate a distal tip of a catheter device **110** similar to catheter device **100** but with a guidewire lumen **39** offset from the center of the catheter device **110** in accordance with an embodiment. The catheter device **110** includes an insulating portion **111** and cutting feature **112**.

[0092] FIGS. **12A** and **12B** illustrate a distal tip of a catheter device **120** in accordance with an embodiment. The distal tip has a cutting feature **122** made out of a conductive material and an insulating portion **121**. The catheter device includes a guidewire lumen **39**. The cutting feature **122** is offset from the center of the distal tip and has an arced configuration.

[0093] In some embodiments the catheter devices do not have a guidewire lumen. The catheter device can locate the target tissue without following a guidewire. The energized tip can then be used for the initial penetration in the target tissue. FIGS. **13A-13C** illustrate portions of the tips of catheter devices that can be utilized without a guidewire. FIG. **13A** illustrates a distal tip with a dome shaped tip with a metal cutting element extending from the dome. FIG. **13B** illustrates a cone shaped distal tip with a conductive wire cutting element bent over the distal tip. FIG. **13C** illustrates a dome shaped distal tip with a conductive wire cutting element bent over the dome shaped distal tip.

[0094] FIGS. **14A-D** are images of ring shaped cutting elements with outward projections. FIGS. **14A-14B** illustrate a cutting element formed using stainless steel wire having a diameter of 0.006" and a ceramic cone shaped tip. The outward projections are recessed into the ceramic cone near the outer diameter of the cone. In tests the cutting elements efficiently cut through tissue with little to no damage or coagulation outside of the cut area. FIG. **14C** illustrates a tip design similar to the FIGS. **14A-B** with stainless steel wire wrapped around a distal portion of a guidewire lumen shaft. Stainless steel wire is used for the exterior portions of the wire and copper wiring is used for the internal wiring. FIG. **14D** illustrates a distal tip with a copper wire wrapped over a circular stainless steel electrode disposed about a guidewire lumen shaft. Examples of nose cone shapes include cone shapes and bullet shapes.

[0095] FIGS. **15A-F** are images of additional distal tip designs. FIGS. **15A-15F** illustrate guidewire lumen shafts and cutting elements having different configurations. FIG. **15A** is an image of a dome shaped tip with a cutting element connected to a copper wire with the cutting element offset from the guidewire lumen shaft. FIG. **15B** is an image of a dome shaped tip with a cutting element disposed about the guidewire lumen shaft with wings extending towards the outer diameter of the bullet shaped ceramic tip. FIG. **15C** is an image of a cone shaped tip with a cutting element connected to a copper wire with the guidewire lumen shaft offset from the central portion of the distal tip. FIG. **15D** is an image of a cone shaped tip with a cutting element connected to a copper wire with the cutting element offset from the guidewire lumen shaft. FIG. **15E** is an image of a dome shaped tip with a stainless steel cutting element adjacent to the guidewire lumen shaft. FIG. **15F** is an image of a nose shaped tip with a cutting element concentric to the guidewire lumen shaft.

[0096] FIGS. **16A-16H** illustrates various tissue access patterns made by the different energized tip configurations disclosed herein. The dotted lines in FIGS. **16A-16H** correspond to the outer diameter of the catheter shaft. FIG. **16A** illustrates a tissue cutting or access pattern generated by an offset ring and one outer projection. FIG. **16B** illustrates a tissue cutting pattern generated by a central cutting feature with two outward projections. FIG. **16C** illustrates a tissue cutting pattern generated by a central cutting feature with three outward projections. FIG. **16D** illustrates a tissue cutting pattern generated by a central cutting feature with four outward projections. FIGS. **16E** and **16F** illustrate tissue cutting pattern generated by a central cutting feature helical projections extending counter clockwise and clockwise, respectively. FIG. **16G** illustrates a tissue cutting pattern generated by an offset cutting feature with two outward projections. FIG. **16H** illustrates a tissue cutting pattern generated by an offset cutting feature with an offset arc element. FIG. **17** is an image of

a tissue access pattern generated using the distal tip and cutting features illustrated in FIGS. 3A-3C.

[0097] In some embodiments, as shown, the distal tip **32** can be conically shaped and can have the same outer diameter as the outer diameter of catheter body **12**. In other embodiments, the distal tip can be a truncated cone, a cylinder, a rounded cylinder, semi-spherical, triangular, beveled, wedge shaped, or any other suitable shape for penetrating tissue. In some embodiments, a ceramic insulating ring can be placed between the distal tip and the catheter body and/or between the tip and the stent or any onboard needle to prevent the tip from heating and/or melting the catheter, stent, and any onboard needle. In some embodiments, the distal tip can be tapered as finely as possible (e.g., cone or bougie-shaped) so as to minimize step-off between the guidewire and the distal tip. Any of the distal tip and cutting element designs disclosed herein can be used.

[0098] In some embodiments the devices disclosed herein can be used with a guidewire having an anchor structure as disclosed in co-owned application U.S. Patent Publication No. 2010-0268029, which is incorporated by reference herein in its entirety. The anchor structure can be a shape memory alloy, for example, so that it can be configured to automatically expand to a pre-determined shape upon being advanced distally from a needle.

[0099] In some embodiments, the catheter is disposed within an endoscope, and in other embodiments, the catheter is an endoscope or takes the place of an endoscope.

[0100] The devices and methods disclosed herein can be used in a variety of applications and for obtaining access between a variety of different body lumens. In some embodiments the devices disclosed herein can be used for cross-luminal drainage.

[0101] In some embodiments an anastomosis or fistula can be formed using the devices and methods disclosed herein. For example, a stent can be placed between two body lumens to provide fluid communication between the two body lumens. The two adjacent body lumens can form an anastomosis as they heal around the stent.

[0102] The devices and methods can be used in the gastrointestinal (GI) tract and areas adjacent to a portion of the GI tract. Examples of anatomy in the GI tract include the esophagus, stomach, duodenum, jejunum, small intestine, and large intestine. Non-limiting examples of portions adjacent to the GI tract include the peritoneal cavity, bile duct, pancreatic duct, gall bladder, pancreas, cysts, pseudocysts, abscesses and the like.

[0103] In some embodiments the devices and methods can be used in the urinary tract (e.g. urinary bladder and ureter), pulmonary tract (e.g. trachea and bronchi), biliary tract (e.g. bile duct and gallbladder), and for vascular applications.

[0104] The body lumens can be any organ that can be accessed endoscopically and can be a hollow or solid organ, duct, vessel, or soft tissue structure. Examples of first and second body lumens include the esophagus, stomach, duodenum, jejunum, small intestines, large intestines, colon, bile duct, pancreatic duct, gallbladder, crus muscle, fundus, cysts, pseudocysts, abscesses, pancreas, liver, urinary bladder, rectum, sinus cavity, heart, lung, etc.

[0105] The methods and devices disclosed herein can be useful for a variety of medical procedures. Embodiments can be applied to ERCP applications where there is a need to access target anatomical structures through multiple tissue planes from a guidewire access. Embodiments are useful for

applications and procedures, such as gastrojejunostomy, gastroduodenostomy, gastrocolostomy, transduodenal, transgastric, biliary, pancreatic pseudocysts, transhepatic, transcystic, transpancreatic, transenteric, transbiliary, gastropexy, cystopexy, transesophageal, transbronchial, transgastric, colon resection, gastric bypass, jejunostomy, etc.

[0106] The methods and devices disclosed herein can also be used for cross-luminal therapy or access to body lumens to provide further treatment, such as chemotherapy, placing sensors, placing treatment delivery devices, providing pharmaceutical devices, radioisotope treatment, and others. The access to the body lumens can be through the stent or other device placed in or adjacent to the body lumen of interest for the targeted treatment. The stent can also include additional therapeutic agents, such as pharmaceutical agents, radioactive agents, and other therapeutic agents. The therapeutic agents can be impregnated in the stent or included as a coating. In one example, a stent can be placed next to or adjacent to a tumor. The tumor can be treated with targeted chemotherapy. The chemotherapy can be introduced using the stent or using the stent passageway to facilitate treatment.

[0107] In some embodiments the methods and devices can be used for peritoneal access and TIPS (transjugular intrahepatic portosystemic shunt). In some embodiments the methods and devices can be used in applications and procedures, such as for vascular access, arterial to vascular, pericardial access, and venous insufficiency via transvalve access.

[0108] One application of particular interest in advanced therapeutic endoscopy is the drainage of bile from the gallbladder into the duodenum or stomach. This is accomplished endoscopically from within the GI lumen of the duodenum or stomach and requires that the gallbladder be located using transluminal imaging, such as endoscopic ultrasound (EUS), followed by penetration through the GI lumen and gallbladder wall and precise placement of a drainage stent between these structures. During the placement of the drainage stent, it is necessary that close apposition of the gallbladder and GI lumen be maintained to prevent bile leakage into the peritoneal cavity, a situation that can cause peritonitis which can be fatal. In this instance, delivery of a tissue anchor or luminal approximating stent requires precise control allowing that close apposition is maintained throughout the procedure and throughout the course of therapy. Using the devices disclosed herein, tissue stents and anchors can be precisely delivered.

[0109] The devices disclosed herein can be used for bariatric surgery for gastric bypass and colon resection surgeries. For example, a stent can be delivered between the fundal pouch formed in gastric bypass surgery and a section of the duodenum or jejunum to form an anastomosis. For colon resection surgery a stent can be placed between two sections of the colon to form an anastomosis. The stent and resulting anastomosis can limit leakage, limit the formation of strictures, and create a standard size stoma or anastomosis. For bariatric surgery and colon resection surgery a blocked anastomosis or decreased anastomosis sizes can result in complications with fluid flow and solid food flow. Forming a standard size anastomosis can promote fluid and communication and decrease complications from blocked or too small anastomoses. The anastomosis size would correspond to the stent size so the variability in the anastomosis size would be greatly decreased over current surgical practices that involve manually stapling the tissue together to form the anastomosis.

[0110] The devices disclosed herein can be used to treat metabolic conditions, such as diabetes. Food is first churned

in the stomach before passing into the small intestine. When the lumen of the small intestine comes into contact with nutrients, a number of hormones are released that can inhibit further food intake and have thus been dubbed “satiety factors”. Changes in circulating hormone levels after gastric bypass have been hypothesized to produce reductions in food intake and body weight in obese patients. The devices can be used to make physical changes in the patient that can change hormonal balances that can improve the health of a patient, such as the “satiety factors”. For example, diabetes can be treated through procedures such as a Roux En Y gastric bypass or gastrojejunostomy as described herein. The devices disclosed herein can be used in laparoscopic assisted procedures. The devices disclosed herein can be used with ear, nose, and throat (ENT) delivery. The devices disclosed herein can be used in Natural Orifice Transgastric Endoluminal Surgery (NOTES). The devices disclosed herein can be used with procedures that clamp or rivet tissue.

[0111] In some embodiments the devices disclosed herein can be used to close an opening in mammalian tissue. For example, a tissue anchor or stent with a closed lumen could be placed to seal an opening.

[0112] The devices disclosed herein can be used for access without delivering and placing a stent. For example, the devices can be used for a necrosectomy to remove necrosed tissue as in the case of a necrotizing pancreatitis.

[0113] The devices disclosed herein can also be used to perform a cystotome. The device can be positioned adjacent to the target tissue, e.g. the transgastric or transduodenal wall. Electrical energy can be supplied to the conductive surfaces of the distal tip of the device to electrosurgically puncture a hole in the transgastric or transduodenal wall along with puncturing a pancreatic pseudocyst. The pancreatic pseudocyst can be visibly bulging into the GI tract. The distal tip can be supported by an inner catheter shaft within an outer tubular body of the catheter. The distal tip and inner catheter shaft can move relative to the outer tubular body of the catheter. After puncturing the target areas, e.g. transgastric or transduodenal wall and a pancreatic pseudocyst, the distal tip and inner catheter can be removed thereby leaving the outer tubular body of the catheter within the passageway formed when puncturing the transgastric or transduodenal wall and a pancreatic pseudocyst. The outer tubular body can be used as a working channel for access for additional medical tools. For a cystotome, a drainage kit or stent can be delivered through the outer tubular body to the pseudocyst. The devices disclosed herein have advantages over using a needle for initial access to the pseudocyst location because needle sizes can be limited to smaller thicknesses in order for the needle to maintain the desired flexibility and properties. In contrast, the catheter devices disclosed herein can be used to form an initial passage with a larger working channel than conventional needle procedures. In some embodiments, the outer tubular body can have a diameter of greater than 10 French. For example, the outer tubular body can have an 11 French diameter to leave a large working channel in body lumen. Positioning the catheter for the cystotome can be done without a guidewire. In some cases a guidewire can be used for positioning.

[0114] Various stent shapes and designs can be delivered using the devices and methods disclosed herein. FIGS. 18A-F, 19A-19I, 20A-20B, 21A-21D, and 22A-22B illustrate various stent designs that can be used with the devices disclosed herein. Additional stent designs are disclosed in co-owned

U.S. Patent Publication 2009-0281557, previously incorporated by reference herein. The tissue anchors and stents include a body formed from a woven filament braid. The filament will typically be a metal wire, more typically being a nickel-titanium or other super-elastic or shape memory metal wire. The body can have both an elongated tubular configuration (FIG. 2A) and a foreshortened configuration where proximal and distal ends of the body expand radially into flange structures, as illustrated in FIG. 5E. The stents can expand radially to form a pair of adjacent annular rings which define the flange structures. After such foreshortening and deployment of the flange structures, the body will further have a cylindrical saddle region between the flange structures. When the anchor is deployed in tissue, the flange structures engage the outer surfaces of adjacent tissue layers (e.g. tissue T1 and tissue T2 illustrated in FIGS. 5A-5E) and the saddle region typically resides within a penetration through the tissue layers. The flange structures can have various configurations, including one or more inflection points to provide additional structural support to the stent flanges.

[0115] FIGS. 18A-F illustrate various configurations of the flanges 191 in double-walled configurations. In FIG. 18A, the flanges 191 expand radially. The central saddle region 192 has a length L and a diameter d. The flanges 191 have a diameter D. The stent 34 has lips or cuffs 193 on either end. The cuffs 193 have a diameter d'. FIG. 18A illustrates a covering or membrane 194 over the entire exterior of the stent 34. The cover or membrane inhibits tissue ingrowth and minimizes fluid leakage when the stent is implanted. The cuffs 193 have a diameter d' that is slightly larger than the diameter d of the central saddle region 192 in FIG. 18A. In FIG. 18B, the stent 34 has a cuff 193 diameter d' that is approximately the same as the diameter d of the central saddle region 192. In FIG. 18C, the stent 34 has a smaller diameter d than the stents illustrated in FIGS. 18A and 18B. FIG. 18C illustrates a cuff 193 diameter d' that is approximately the same as the diameter d of the central saddle region 192.

[0116] In FIG. 18D, a stent 34 having a central saddle region 192 with an expanded diameter d and smaller cuff 193 diameter d' is illustrated. In FIG. 18E, a stent 34 having a central saddle region 192 with an expanded diameter d and cuff 193 is illustrated. FIG. 18E has a greater cuff 193 diameter d' than the stent 34 illustrated in FIG. 18D. FIG. 18F illustrates a stent 34 without a cuff.

[0117] FIGS. 19A-19I illustrate cross sections of a quarter portions of stents with flanges 191 and central saddle regions 192. Each of the quarter portions are paired with a similar shape to form the entire flange 191. Each of the flange structures 191 can be paired with any of the other flange structures disclosed herein to form a stent with two flanges. FIG. 19A illustrates a flange with multiple inflections. FIG. 19B illustrates a flange 191 with multiple inflection including multiple flanges. FIG. 19C illustrates a flange 191 with the stent curved back towards the central saddle region. FIG. 19D illustrates a flange 191 with the stent curved away from the central saddle region 192. FIG. 19E illustrates a flange 191 with multiple inflections. FIG. 19F illustrates a flange 191 with a circular configuration. FIG. 19G illustrates a flange that curves towards the opposing flange and back on itself FIG. 19H illustrates a flange 191 with notches or ribs in portions of the stent cross-section. FIG. 19I illustrates a flange 191 with a sinusoidal section to provide additional strength.

[0118] FIG. 20A is a cross-section of the stent illustrated in 20B. The flanges 191 have are inflected with a circular con-

figuration that curves back towards the central saddle region. FIG. 21A illustrates a stent with flanges 191 that have sinusoidal configuration across the cross section of the flange. FIG. 21B illustrates a stent with flanges 191 that curve towards the opposing flanges and the central saddle region 192. FIG. 21C is a cross section of the stent illustrated in FIG. 21D. The stent has a flange 191 with a notch/rib 210 incorporated into the cross section of the rib.

[0119] The diameter D of the flanges 191 and the diameter d of the central saddle region 192 can be selected to allow the desired strength and fluid communication between the body lumens. For example, the diameter d should be large enough to allow for fluid communication between the body lumens. In some cases liquid flows through the central saddle region 192. In other cases particulate matter or solids can flow through the central saddle region 192. The diameter d should be sized to allow for the expected fluids and/or solids to flow through the saddle region 192. The diameter d can also be sized with a diameter close to the size of the hole in the body lumens to reduce the chance of leakage and improve stent engagement with the holes in the body lumens. The cuff length, diameter (d'), and shapes can be configured to achieve the desired physical properties in the stent. For example, the cuff can provide additional strength to the stent structure. The cuff can also have an increased diameter to make it easier for subsequent access to the interior volume of the stent with additional medical instruments or with a device to remove the stent. The tissue anchors of the prior art, such as metal clamps and rivets, have often been either too rigid, providing good attachment but presenting substantial risk of tissue necrosis or adhesion, or too weak, presenting little risk of tissue damage but allowing leakage and movement at the point of tissue penetration. The stents and tissue anchors disclosed herein can provide firm attachment of tissue while minimizing the risk of necrosis and other damage to the tissue. The stents disclosed herein provide enough pressure to hold the tissue walls together with the expanded flange structures but not too much force that can cause trauma to the tissue walls.

[0120] The stents disclosed herein can be used to form an anastomosis between the body lumens. Reducing the damage to the tissue during implantation of the stent and minimizing necrosis of tissue can promote tissue healing and expedite the formation of a healthy anastomosis.

[0121] Prior art stent designs for implantation in vascular applications are designed to be delivered to the target location and held in place permanently. The vascular stents are not designed to be removed or moved after implantation. In contrast to prior art vascular stents, the stents disclosed herein can be removed. The tissue anchors disclosed herein are also removable, both during initial implantation procedures as well as in a subsequent procedure(s) many weeks, months, or even years following the initial implantation.

[0122] The stents can include a coating to prevent tissue in-growth. Preventing tissue in-growth in the stent makes removal of the stent easier. Coatings can also be used to provide a smooth outer surface of the stent and to reduce friction against the tissue when deploying and removing the stent. The coating can reduce or eliminate voids in the stent structure and prevent tissue in-growth. The collapsibility of the stent also facilitates removal. The double walled flange structure can also make removal of the stent easier because the flange structures are easier to grab using medical tools. In some embodiments a snare can be used to grab one of the double walled flanges of the stent. Pulling on the flange can

collapse the stent structure to compress the stent and allow for easy removability of the stent after formation of the anastomosis.

[0123] The length of the saddle region can be optimized based on the thickness of each of the tissue walls such that the flanges securely engage and hold the tissue planes together. Each of the flanges can engage the tissue walls such that the flange ends do not migrate or move. The double walled flanges can hold the opposing tissue planes in place. The flanges can engage the tissue walls to control the positioning of the tissue walls and hold the tissue in a desired orientation to the tissue engaged by the other end of the stent.

[0124] The stents disclosed herein have additional strength over prior art stent designs. The double walled flange structure and cuff on the stent provide additional strength for the stent to engage the opposing tissue planes. The expanded double-walled flange can form an angle of about 90 degrees with the saddle region. The cuff at each end of the stent provides additional strength for the flange to engage the tissue walls.

[0125] The stent can be formed from woven shaped memory metal wires, such as nitinol or elgiloy. The wires can have a relatively small diameter, typically in the range from 0.001 inch to 0.02 inch, usually from 0.002 inch to 0.01 inch, where the braid will include from as few as 10 to as many as 200 wires, more commonly being from 20 wires to 100 wires. In exemplary cases, the wires will be round having diameters in the range from 0.003 inch to 0.007 inch with a total of from 24 to 60 wires. The wires are braided into a tubular geometry by conventional techniques, and the tubular geometry will be heat-treated to impart the desired shape memory. Usually, the braided tube will be formed into the desired final (deployed) configuration with the flanges at each end. Such a flanged configuration will then be heat set or formed into the braid so that, in the absence of a radially constraining or axially elongating force, the anchor will assume the foreshortened configuration with the flanges at each end. Such foreshortened-memory configurations will allow the anchor to be delivered in a constrained configuration (either radially or axially elongated) and thereafter released from constraint so that the body assumes the flanged configuration at the target site. The woven stent design can promote delivery with its flexibility, collapsibility, and elasticity.

[0126] Expanded stent shapes and sizes can be manufactured with controlled dimensions, such as the internal diameter and length for the central saddle region and diameter of the double walled flanges. A stent (illustrated in detail in FIGS. 22A and 22B) with a 15 mm internal diameter of the saddle region (illustrated as d in FIG. 19) with a 10 mm saddle length (illustrated as L in FIG. 19) and 24 mm flange diameter (illustrated as D in FIG. 19) can be used. The stent structures are illustrated in detail in FIGS. 22A (cross-section) and 22B (side-view). FIG. 22B illustrates a cuff or lip diameter of 18 mm.

[0127] A stent with a 10 mm internal diameter of the saddle region with a 10 mm saddle length and 21 mm flange diameter can be used. A stent with a 6 mm internal diameter of the saddle region with an 8 mm saddle length and 15 mm flange diameter can be used. A stent with an 8 mm internal diameter of the saddle region with an 8 mm saddle length and 17 mm flange diameter can be used. A stent with a 10 mm internal diameter of the saddle region with a 6 mm saddle length and 21 mm flange diameter can be used.

[0128] The stents or tissue anchors can be adapted to be delivered by a catheter based delivery device, such as the delivery device disclosed herein, typically an endoscopic delivery catheter. The catheter can have a small diameter in the range from 1 mm to 8 mm, usually from 2 mm to 5 mm. Thus, the elongated tubular configuration of the anchor body will usually have a diameter less than that of the catheter diameter, usually from 0.8 mm to 7.5 mm, more usually from 0.8 mm to 4.5 mm, where the double-walled flanged structures will be expandable significantly, usually being in the range from 3 mm to 70 mm, more usually in the range from 5 mm to 40 mm. The cylindrical saddle region of the anchor will often not increase in diameter during deployment, but may optionally increase to a diameter from 2 mm to 50 mm, more usually from 5 mm to 20 mm. When present, the lumen or passage through the deployed tissue anchor can have a variety of diameters, typically from as small as 0.2 mm to as large as 40 mm, more usually being in the range from 1 mm to 20 mm, and typically having a diameter which is slightly smaller than the expanded diameter of the cylindrical saddle region. The length of the body may also vary significantly. Typically, when in the elongated tubular configuration, the body will have a length in the range from 7 mm to 100 mm, usually from 12 mm to 70 mm. When deployed, the body will be foreshortened, typically by at least 20%, more typically by at least 40% and often by 70% or greater. Thus, the foreshortened length will typically be in the range from 2 mm to 80 mm, usually in the range from 2.5 mm to 60 mm, and more usually being in the range from 3 mm to 40 mm.

[0129] In some embodiments the body of the tissue anchor may consist of the woven filament braid with no other coverings or layers. In some embodiments the tissue anchor may further comprise a membrane or other covering formed over at least a portion of the body. The membrane can be used to prevent or inhibit tissue ingrowth to allow the device to be removed after having been implanted for weeks, months, or longer. Suitable membrane materials include polytetrafluoroethylene (PTFE), expanded PTFE (ePTFE), silicone, polypropylene, urethane polyether block amides (PEBA), polyethyleneterephthalate (PET), polyethylene, C-Flex™, thermoplastic elastomer, Krator™, SEBS and SBS polymers, and the like.

[0130] In some embodiments the membranes may be formed over the entire portion of the anchor or stent. In some embodiments the membrane or covering is formed over only a portion of the anchor or stent. The covering or membrane may be formed over the exterior or interior of the body and will typically be elastomeric so that the membrane conforms to the body in both the elongated and foreshortened configurations.

[0131] The stents can be coated with active compounds, such as therapeutic compounds to provide therapy to the tissue areas adjacent to the stent. In some embodiments the therapeutic compounds can be used to reduce tissue attachment and engagement with the stent during tissue healing after the deployment of the stent. Coatings and surfaces that do not promote tissue in-growth can be used in some embodiments. For example, Sirolimus and its analogs can be used to halt cell proliferation. Taxols can also be used to halt cell proliferation, in addition to being used in cancer treatment. Silicone and other surfaces can be used to stop or slow the rate of cell proliferation and in-growth.

[0132] In some embodiments the therapeutic compounds can promote healing of the tissue and formation of a healthy

anastomosis. The therapeutic compound can be a medicine that is released from the stent over a period of time. In some embodiments the therapeutic compound can be used to treat tissue or anatomy adjacent to the stent location. In some embodiments the therapeutic agent can be used with a stent that is not fully covered to promote tissue in-growth. For example, a titanium oxide layer or coating can be used to promote cell proliferation and tissue in-growth. Biologic compounds such as cytokines and hormones can promote tissue growth as well.

[0133] The number, size, shape, and configuration of the wires along with the expanded shape of the stent (e.g. sizes of the flanges, cuffs, and saddle) can be selected to achieve an expanded stent with a desired properties. The strength of the double-walled flanged structures will depend on the number, size, stiffness, and weave pattern(s) of the individual wires used to form the tubular anchor body. For example, a design with a large number of nitinol wires, for example 48, but a relatively small wire diameter, for example 0.006 inches, will form a braid structure with a saddle region which remains flexible and double-walled flanges which are relatively firm. Use of fewer wires, for example 16, and a larger wire diameter, for example 0.016 inches, will form a braid structure with a relatively rigid saddle region and relatively stiff, non-flexible flanges. Usually, the more flexible design is desirable.

[0134] In some embodiments, it is preferred that the double-walled flange structures have a preselected bending stiffness in the range from 1 g/mm to 100 g/mm, preferably in the range from 4 g/mm to 40 g/mm. Similarly, it is preferred that the central saddle region have a preselected bending stiffness in the range from 1 g/mm to 100 g/mm, preferably from 10 g/mm to 100 g/mm.

[0135] The bending stiffness of the flange can be determined by the following test. The distal flange is secured in a fixture. The outer diameter of the flange is pulled in a direction parallel to the axis of the tissue anchor using a hook attached to a Chatillon force gage. The saddle of anchor is held in a hole in a fixture and force (grams) and deflection (mm) are measured and recorded. The bending stiffness of the flange can be determined by the following test. The distal flange is secured in a fixture. The outer diameter of the flange is pulled in a direction perpendicular to axis of the tissue anchor using a hook attached to a Chatillon force gage. The saddle of anchor is held in a hole in a fixture and force (grams) and deflection (mm) are measured and recorded.

[0136] The pull out strength of the stent can be measured. Upper and lower test fixtures are assembled from a silicon sheet having a set orifice size. The orifice size corresponds to the stent saddle diameter. A force gauge can be mounted to one of the test fixtures with the other fixture attached to a Chatillon test stand. The upper and lower test fixtures are aligned next to each other and a tube can be used to deploy the proximal and distal flanges of the stent on opposing sides of the silicone sheets on the upper and lower test fixtures. The Chatillon test stand speed is set and the force gauge is zeroed. Next, the stent is pulled until either flange slips through the respective orifice. The force required to pull the stent flange through the orifice is recorded for the tested stent.

[0137] Stent pull out strength tests were performed using commercially available stent designs and the designs disclosed herein. Solus™ 10 French double pigtail stents from Cook Medical were tested with pull out strengths ranging from 98 grams (force) to 183 grams. Advanix™ 10 French double pigtail stents from Boston Scientific were tested with

pull out strengths ranging from 162 grams to 380 grams. Cook Zimmon™ 7 French double pigtail stents were tested with pull out strengths ranging from 200 grams to 217 grams. Xlumena stents with a double walled flange structure and a saddle diameter of 10 mm were tested with pull out strengths ranging from 338 grams to 600 grams. The Xlumena stents showed improved pull out strengths over the tested prior art double pig tail stents along with improved fluid communication between the body lumens.

[0138] In some embodiments a stent is deployed with a pull out strength of greater than about 400 grams. In some embodiments a stent is deployed with a pull out strength of greater than about 500 grams. In some embodiments a stent is deployed with a pull out strength of greater than about 600 grams.

[0139] A cylindrical saddle region remains on the anchor body between the deployed flanges, where the flanges are able to press against the tissue layers to provide the approximating force. Typically, the body will be foreshortened to a degree selected to apply sufficient pressure to the tissues to hold them together without causing significant tissue injury or necrosis. Usually, the applied pressure will be in the range from 0.005 g/mm² to 5 g/mm², usually from 0.2 g/mm² to 1 g/mm².

[0140] As used herein “about”, “substantially”, “generally”, and other relative terms refer to approximately or reasonably close to. In some cases the relative terms can refer to plus or minus 10%. In some cases the relative terms can refer to plus or minus 5%. In some cases the relative terms can refer to plus or minus 2%. In some cases the relative terms can refer to plus or minus 1%.

[0141] Although the foregoing invention has been described in some detail by way of illustration and example, for purposes of clarity of understanding, it will be obvious that various alternatives, modifications and equivalents may be used and the above description should not be taken as limiting in scope of the invention which is defined in part by the appended claims.

What is claimed is:

1. A method for advancing a catheter distally through opposed first and second luminal walls of first and second body lumens, the method comprising:

positioning a catheter with a distal tip proximal to the first luminal wall, the catheter including a stent;

providing an electrical current to a conductive portion of the distal tip;

advancing distally the distal tip of the catheter through the first and second luminal walls to create a passage there-through, wherein the conductive portion of the distal tip includes a first cutting feature and one or more projections extending from the first cutting feature towards an outer diameter of the distal tip;

deploying a distal flange of the stent in the second body lumen; and

drawing proximally on the distal flange to pull the first and second luminal walls towards each other.

2. The method of claim 1, further comprising forming a hole in the first and second body lumens using a needle prior to positioning the catheter.

3. The method of claim 1, wherein the first cutting feature and one or more projections comprises an arced configuration.

4. The method of claim 1, wherein a guidewire is not used for positioning the catheter and the distal tip does not have a guidewire lumen.

5. The method of claim 1, wherein the first cutting feature comprises a concentric ring that is concentric to a lumen in the distal tip of the catheter.

6. The method of claim 5, wherein the catheter is disposed about a guidewire and positioning includes advancing the catheter along the guidewire, wherein the concentric ring is configured to be disposed about the guidewire.

7. The method of claim 1, further comprising verifying the deployment of the distal flange prior to drawing proximally.

8. The method of claim 7, wherein verifying the deployment of the distal flange is done using ultrasound.

9. The method of claim 1, further comprising releasing a proximal flange of the stent into the first body lumen.

10. The method of claim 1, wherein the catheter includes a sheath radially constraining the stent, the stent being a self-expanding stent, and deploying the distal flange includes retracting the sheath to allow the distal flange of the stent to expand.

11. The method of claim 9, wherein the catheter includes a sheath radially constraining the stent, the stent being a self-expanding stent, and deploying the proximal flange includes retracting the sheath to allow the proximal flange of the stent to expand.

12. The method of claim 1, further comprising attaching the catheter to an endoscope prior to positioning the catheter.

13. The method of claim 1, wherein advancing the distal tip through the first and second luminal walls to create the passage therethrough forms a first patterned hole in the first luminal wall and a second patterned hole in the second luminal wall.

14. The method of claim 13, wherein the first and second patterned holes have a diameter that is less than the maximum diameter of the distal tip.

15. The method of claim 13, wherein the first and second patterned holes each include a central hole with one or more projections radiating from the central hole.

16. The method of claim 1, wherein the first body lumen is within the digestive tract.

17. The method of claim 16, wherein the first body lumen is selected from the group consisting of: esophagus, stomach, duodenum, jejunum, small intestine, large intestine, colon, and rectum.

18. The method of claim 17, wherein the second body lumen is part of the digestive tract or biliary tree.

19. The method of claim 1, wherein the second body lumen is selected from the group consisting of: esophagus, stomach, duodenum, jejunum, small intestine, large intestine, colon, bile duct, pancreatic duct, gallbladder, and pancreas.

20. The method of claim 1, wherein the first and second body lumens are sections of the colon.

21. The method of claim 1, wherein the first body lumen is the stomach or duodenum and the second body lumen is the gallbladder.

22. The method of claim 1, wherein the first and second body lumens are a fundal pouch and a section of the duodenum or jejunum.

23. The method of claim 9, further comprising forming an anastomosis between the first and second body lumens.

24. The method of claim 23, further comprising removing the stent after forming the anastomosis.

- 25.** A catheter assembly, comprising:
a catheter body having a proximal end, a distal end, and a central passage therethrough; and
a tip positioned near the distal end of the catheter body, the tip having a conductive portion including a first cutting feature and one or more projections outwardly extending from the first cutting feature towards an outer diameter of the tip, the conductive portion configured to be electrically coupled to an electrosurgical generator.
- 26.** The method of claim **25**, wherein the first cutting feature and one or more projections comprises an arced configuration.
- 27.** The method of claim **25**, wherein the tip does not have a guidewire lumen.
- 28.** The catheter assembly of claim **25**, wherein the first cutting feature comprises a concentric ring.
- 29.** The catheter assembly of claim **28**, the catheter further comprising a guidewire lumen, wherein the concentric ring is configured to be disposed about and insulated from the guidewire lumen.
- 30.** The catheter assembly of claim **29**, wherein the one or more outwardly extending projections extend from the first cutting feature to a maximum radial position, the maximum radial position defining a length between the radial position and a center point of the distal tip, wherein the length is less than 50% of the outer diameter of the tip.
- 31.** The catheter assembly of claim **25**, wherein the conductive portion includes an exterior portion made of stainless steel and an interior portion comprising copper electrically coupled to the exterior portion and configured to be electrically coupled to an electrosurgical generator.
- 32.** The catheter assembly of claim **25**, wherein the one or more projections outwardly extending from the first cutting feature towards the outer diameter of the tip include a covered portion adjacent to a maximum diameter of the tip.
- 33.** The catheter assembly of claim **25**, wherein electrosurgical generator is configured to supply about 50 watts to about 100 watts of power to the conductive portion of the tip.
- 34.** The catheter assembly of claim **25**, the conductive portion including two projections.
- 35.** The catheter assembly of claim **25**, the conductive portion including four projections.
- 36.** The catheter assembly of claim **25**, further comprising a compartment within the catheter body configured to hold a stent.
- 37.** The catheter of claim **36**, further comprising a stent within the compartment within the catheter body, wherein the stent is a self-expanding stent and the self-expanding stent is radially restrained by a movable sheath.
- 38.** The catheter of claim **37**, wherein the stent is configured to expand to form distal and proximal double-walled flanges.

39. The catheter of claim **38**, wherein the stent has a pull-out strength of greater than about 400 grams.

40. The catheter of claim **25**, wherein the catheter is configured to be attached to an endoscope.

41. The catheter of claim **25**, further comprising a control handle configured to control the energy provided by the electrosurgical generator to the first cutting feature and the one or more projections.

42. The catheter of claim **25**, the catheter assembly further comprising an inner catheter shaft engaged with the distal tip and configured to move relative to the catheter body within the central passage of the catheter body, wherein the inner catheter shaft and distal tip are configured to be removable from the catheter body.

43. A method for advancing a catheter distally through a luminal wall of a first body lumen, the method comprising:

positioning a catheter comprising an outer tubular body and inner body with a distal tip proximal to the luminal wall of the first body lumen;

providing an electrical current to a conductive portion of the distal tip;

advancing distally the distal tip of the catheter through the first luminal wall along with a portion of the outer tubular body to create a passage therethrough, wherein the conductive portion of the distal tip includes a first cutting feature and one or more projections extending from the first cutting feature towards an outer diameter of the distal tip; and

withdrawing the inner body and distal tip through the outer tubular body leaving a portion of the outer tubular body in the passage in the luminal wall of the first body lumen.

44. The method of claim **43**, wherein the first luminal wall is a transgastric wall or transduodenal wall.

45. The method of claim **44**, further comprising foaming a hole in a pseudocyst during advancing distally.

46. The method of claim **45**, further comprising passing a catheter, stent, or drainage device through the outer tubular body and into the hole in the pseudocyst.

47. The method of claim **43**, wherein positioning includes following a guidewire to a target location of the luminal wall of the first body lumen.

48. The method of claim **46**, further comprising deploying a distal flange of the stent in the pseudocyst and deploying a proximal flange of the stent in contact with the transgastric wall or transduodenal wall.

49. The method of claim **43**, wherein the first cutting feature and one or more projections comprises an arced configuration.

50. The method of claim **43**, wherein the first cutting feature comprises a concentric ring that is concentric to a lumen in the distal tip of the catheter.

* * * * *

专利名称(译)	用于穿过相邻组织层的方法和装置		
公开(公告)号	US20130310833A1	公开(公告)日	2013-11-21
申请号	US13/871978	申请日	2013-04-26
[标]申请(专利权)人(译)	BROWN PETER KHOUNE SITH LEPULU KEKE 多诺万RYAN BINMOELLER KENNETH F		
申请(专利权)人(译)	BROWN , PETER KHOUNE , SITH LEPULU , 咳咳 多诺万RYAN BINMOELLER , KENNETH F.		
当前申请(专利权)人(译)	BROWN , PETER KHOUNE , SITH LEPULU , 咳咳 多诺万RYAN BINMOELLER , KENNETH F.		
[标]发明人	BROWN PETER KHOUNE SITH LEPULU KEKE DONOVAN RYAN BINMOELLER KENNETH F		
发明人	BROWN, PETER KHOUNE, SITH LEPULU, KEKE DONOVAN, RYAN BINMOELLER, KENNETH F.		
IPC分类号	A61B17/34 A61B17/11 A61B18/12		
CPC分类号	A61B17/3476 A61B18/1206 A61B17/1114 A61B17/320016 A61B17/3478 A61B18/1492 A61B2017/00278 A61B2017/3425 A61B2017/3454 A61B2017/346 A61B2018/00345 A61B2018/00494 A61B2018/00601 A61B2018/1407 A61B2018/1412 A61B2018/1425 A61B2018/144 A61F2/95		
优先权	61/648544 2012-05-17 US 61/727629 2012-11-16 US 61/767577 2013-02-21 US		
其他公开文献	US9381041		
外部链接	Espacenet USPTO		

摘要(译)

可以使用具有远端尖端的导管装置来接近相邻的组织层，远端尖端具有导电部分，导电部分包括第一切割特征和从第一切割特征朝向远端尖端的外径延伸的一个或多个凸起。可以将电能提供给装置的导电部分以切割组织。可输送支架以在相邻组织层之间形成流体连通。

