





US 20040224298A1

(19) **United States**(12) **Patent Application Publication** (10) **Pub. No.: US 2004/0224298 A1**  
**Brassil et al.** (43) **Pub. Date: Nov. 11, 2004**(54) **APPARATUS AND METHOD FOR  
DETERMINING EFFECTS OF A SUBSTANCE  
OF AN ORGAN**(76) Inventors: **John Brassil**, Northbrook, IL (US);  
**Douglas Schein**, Arlington Heights, IL  
(US); **Christopher G. Curtis**, Cardiff  
(GB)Correspondence Address:  
**OLIFF & BERRIDGE, PLC**  
**P.O. Box 19928**  
**Alexandria, VA 22320 (US)**(21) Appl. No.: **10/768,167**(22) Filed: **Feb. 2, 2004****Related U.S. Application Data**(60) Continuation-in-part of application No. 10/617,130,  
filed on Jul. 11, 2003.  
Division of application No. 09/645,525, filed on Aug.  
25, 2000, now Pat. No. 6,673,594.  
Continuation-in-part of application No. 09/537,180,  
filed on Mar. 29, 2000.  
Continuation-in-part of application No. 09/162,128,  
filed on Sep. 29, 1998, now abandoned.**Publication Classification**(51) **Int. Cl.<sup>7</sup>** ..... **G01N 33/53**(52) **U.S. Cl.** ..... **435/1.1; 435/7.2**(57) **ABSTRACT**


An organ perfusion apparatus and method monitor, sustain and/or restore viability of organs and preserve organs for storage and/or transport. Other apparatus include an organ transporter, an organ cassette and an organ diagnostic device. The method includes perfusing the organ at hypothermic and/or normothermic temperatures, preferably after hypothermic organ flushing for organ transport and/or storage. The method can be practiced with prior or subsequent static or perfusion hypothermic exposure of the organ. Organ viability is restored by restoring high energy nucleotide (e.g., ATP) levels by perfusing the organ with a medical fluid, such as an oxygenated cross-linked hemoglobin-based bicarbonate medical fluid, at normothermic temperatures. During the period in which the organ is preserved and/or maintained, various drug research and development may be performed on and/or with the organ. The organ may be perfused with a fluid containing a substance such as a test substance to obtain data regarding the organ, the substance and an interaction of the substance and the organ. The data may then be used to ultimately provide information regarding the drugs efficacy in support of regulatory filings for new drugs.



**FIG. 1**



**FIG. 2**



**FIG. 3**




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9









FIG. 10




**FIG. 11A**



**FIG. 11B**



**FIG. 11D**



**FIG. 11C**




FIG. 12




FIG. 13A




FIG. 13B




FIG. 14A




FIG. 14B




FIG. 14C

FIG. 14D




FIG. 14E





FIG. 14F






FIG. 15

# HYPOTHERMIC MOR ORGAN RECOVERY




FIG. 16






FIG. 17






FIG. 17A



**FIG. 18**



**FIG. 18A**




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23





FIG. 24





**FIG. 25**




FIG. 25A




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31

## APPARATUS AND METHOD FOR DETERMINING EFFECTS OF A SUBSTANCE ON AN ORGAN

[0001] This application is a continuation-in-part of U.S. patent application Ser. No. 10/617,130 filed Jul. 11, 2003 which is a Divisional of application Ser. No. 09/645, 525 filed Aug. 25, 2000, which is a continuation-in-part of U.S. patent application Ser. No. 09/537,180, filed Mar. 29, 2000, which is a continuation-in-part of U.S. patent application Ser. No. 09/162,128, filed Sep. 29, 1998, the entire contents of which are hereby incorporated by reference.

### BACKGROUND OF THE INVENTION

#### [0002] 1. Field of Invention

[0003] The invention relates to an apparatus and method for perfusing one or more organs to monitor, sustain and/or restore the viability of the organ(s) and/or for transporting and/or storing the organ(s). This invention further relates to determining if the organ(s) is/are a viable candidate for transplantation. Particularly, if the organ(s) is/are not viable transplantation candidates, then this invention further relates to perfusing the organ(s) with a fluid to acquire data regarding the organ(s) and/or fluid.

#### [0004] 2. Description of Related Art

[0005] Preservation of organs by machine perfusion has been accomplished at hypothermic temperatures with or without computer control with crystalloid perfusates and without oxygenation. See, for example, U.S. Pat. Nos. 5,149,321, 5,395,314, 5,584,804, 5,709,654 and 5,752,929 and U.S. patent application Ser. No. 08/484,601 to Klatz et al., which are hereby incorporated by reference. Hypothermic temperatures provide a decrease in organ metabolism, lower the energy requirements, delay the depletion of high energy phosphate reserves and accumulation of lactic acid and retard the morphological and functional deterioration associated with disruption of blood supply. Oxygen can not be utilized efficiently by mitochondria below approximately 20° C. to produce energy, and the reduction in catalase/superoxide dismutase production and ascorbyl and glutathione regeneration at low temperatures allows high free radical formation. The removal of oxygen from perfusates during low temperature machine perfusion has even proven helpful in improving organ transplant results by some investigators.

[0006] Reduction in potential oxygen damage is also accomplished via the addition of antioxidants to the perfusate. In particular, this has proven useful in reducing organ damage after long warm ischemia times. Numerous other perfusate additives have also been reported to improve the outcome of machine perfusion.

[0007] Ideally organs would be procured in a manner that limits their warm ischemia time to essentially zero. Unfortunately, in reality, many organs, especially from non-beating heart donors, are procured after extended warm ischemia time periods (i.e., 45 minutes or more). The machine perfusion of these organs at low temperature has demonstrated significant improvement (Transpl Int 1996 Daemen). Further, prior art teaches that the low temperature machine perfusion of organs is preferred at low pressures (Transpl. Int 1996 Yland) with roller or diaphragm pumps delivering the perfusate at a controlled pressure. Numerous control circuits and pumping configurations have been uti-

lized to achieve this objective and to machine perfuse organs in general. See, for example, U.S. Pat. Nos. 5,338,662 and 5,494,822 to Sadri; U.S. Pat. No. 4,745,759 to Bauer et al.; U.S. Pat. Nos. 5,217,860 and 5,472,876 to Fahy et al.; U.S. Pat. No. 5,051,352 to Martindale et al.; U.S. Pat. No. 3,995,444 to Clark et al.; U.S. Pat. No. 4,629,686 to Gruenberg; U.S. Pat. Nos. 3,738,914 and 3,892,628 to Thorne et al.; U.S. Pat. Nos. 5,285,657 and 5,476,763 to Bacchi et al.; U.S. Pat. No. 5,157,930 to McGhee et al.; and U.S. Pat. No. 5,141,847 to Sugimachi et al. However, in some situations the use of such pumps for machine perfusion of organs may increase the risk of overpressurization of the organ should the organ perfusion apparatus malfunction. High pressure perfusion (e.g., above about 60 mm Hg) can wash off the vascular endothelial lining of the organ and in general damages organ tissue, in particular at hypothermic temperatures where the organ does not have the neurological or endocrinal connections to protect itself by dilating its vasculature under high pressure.

[0008] Furthermore, the techniques used for assessment of the viability of these machine perfused organs have been a critical factor in limiting the organs from greater use. While increased organ resistance (i.e., pressure/flow) measurements during machine perfusion are a useful indicator, they demonstrate only the worst case situations.

[0009] During low temperature machine perfusion of organs that have been damaged by warm ischemia time or by the machine perfusion itself, the organs will elute intracellular and endothelial as well as membrane constituents. Over the years the appearance of various ubiquitous intracellular enzymes, such as lactic dehydrogenase (LDH) and alkaline phosphatase, in the perfusate has been used as a biomarker of organ damage. Recently, the determination of the presence of alpha glutathione-S-transferase (a-GST) and Pi glutathione-S-transferase (p-GST) in low temperature machine perfusion perfusates has proven a satisfactory indicator in predicting the functional outcome of non-beating heart donor kidney grafts before transplantation (Transpl 1997 Daemen).

[0010] The prior art has also addressed the need to restore or maintain an organ's physiological function after preservation for an extended period of time at hypothermic temperatures. In particular, U.S. Pat. No. 5,066,578 to Wikman-Coffelt discloses an organ preservation solution that contains large amounts of pyruvate. Wikman-Coffelt teaches that flooding of the organ with pyruvate bypasses glycolysis, the step in the cell energy cycle that utilizes adenosine triphosphate (ATP) to produce pyruvate, and pyruvate is then available to the mitochondria for oxidative phosphorylation producing ATP. Wikman-Coffelt teaches perfusing or washing an organ at a warm temperature with a first preservation solution containing pyruvate for removal of blood or other debris from the organ's vessels and to vasodilate, increase flow and load the cells with an energy supply in the form of a clean substrate, namely the pyruvate. Wikman-Coffelt teaches that the pyruvate prevents edema, ischemia, calcium overload and acidosis as well as helps preserve the action potential across the cell membrane. The organ is then perfused with a second perfusion solution containing pyruvate and a small percentage of ethanol in order to stop the organ from working, vasodilate the blood vessels allowing for full vascular flow, continue to load the cells with pyruvate and preserve the energy state of the organ. Finally

the organ is stored in a large volume of the first solution for 24 hours or longer at temperatures between 4° C. and 10° C.

[0011] However, the mitochondria are the source of energy in cells and need significant amounts of oxygen to function. Organs naturally have significant pyruvate levels, and providing an organ with additional pyruvate will not assist in restoring and/or maintaining an organ's full physiological function if the mitochondria are not provided with sufficient oxygen to function. Further, briefly flooding an organ with pyruvate may, in fact, facilitate tearing off of the vascular endothelial lining of the organ.

[0012] U.S. Pat. No. 5,599,659 to Brasile et al. also discloses a preservation solution for warm preservation of tissues, explants, organs and endothelial cells. Brasile et al. teaches disadvantages of cold organ storage, and proposes warm preservation technology as an alternative. Brasile et al. teaches that the solution has an enhanced ability to serve as a medium for the culture of vascular endothelium of tissue, and as a solution for organs for transplantation using a warm preservation technology because it is supplemented with serum albumin as a source of protein and colloid; trace elements to potentiate viability and cellular function; pyruvate and adenosine for oxidative phosphorylation support; transferrin as an attachment factor; insulin and sugars for metabolic support and glutathione to scavenge toxic free radicals as well as a source of impermeant; cyclodextrin as a source of impermeant, scavenger, and potentiator of cell attachment and growth factors; a high Mg<sup>++</sup> concentration for microvessel metabolism support; mucopolysaccharides, comprising primarily chondroitin sulfates and heparin sulfates, for growth factor potentiation and hemostasis; and ENDO GRO™ as a source of colloid, impermeant and specific vascular growth promoters. Brasile et al. further teaches warm perfusing an organ for up to 12 hours at 30° C., or merely storing the organ at temperatures of 25° C. in the preservation solution.

[0013] However, flooding an organ with such chemicals is insufficient to arrest or repair ischemic injury where the mitochondria are not provided with sufficient oxygen to function to produce energy. The oxygen needs of an organ at more than 20° C. are substantial and cannot be met by a simple crystalloid at reasonable flows. Further, assessment of the viability of an organ is necessary before the use of any type of solution can be determined to have been fruitful.

[0014] WO 88/05261 to Owen discloses an organ perfusion system including an organ chamber that is supplied with an emulsion fluid or physiological electrolyte that is transported through a perfusion system. The chamber contains a synthetic sac to hold the organ. Perfusate enters the organ through a catheter inserted into an artery. The perfusate is provided by two independent fluid sources, each of which includes two reservoirs.

#### SUMMARY OF THE INVENTION

[0015] The present invention focuses on avoiding damage to an organ during perfusion while monitoring, sustaining and/or restoring the viability of the organ and preserving the organ for storage, transport, transplantation or other use. The invention is directed to an apparatus and method for perfusing an organ to monitor, sustain and/or restore the viability of the organ and/or for transporting and/or storing and/or using the organ. More particularly, the organ perfusion

apparatus and method according to the invention monitor, sustain and/or restore organ viability by perfusing the organ at hypothermic temperature (hypothermic perfusion mode) and/or normothermic temperatures (normothermic perfusion mode) preferably after flushing of the organ such as by hypothermic flushing followed by static organ storage and/or organ perfusion at hypothermic temperatures for transport and/or storage of the organ.

[0016] The restoring of organ viability may be accomplished by restoring high energy nucleotide (e.g., adenosine triphosphate (ATP)) levels and enzyme levels in the organ, which were reduced by warm ischemia time and/or hypoxia, by perfusing the organ with an oxygenated medical fluid, such as an oxygenated cross-linked hemoglobin-based bicarbonate medical fluid, at normothermic or near-normothermic temperatures. The organ may be flushed with a medical fluid prior to perfusion with the oxygenated medical fluid. Such perfusion can be performed at either normothermic or hypothermic temperatures, preferably at hypothermic temperatures. For hypothermic flush, static storage and hypothermic perfusion, the medical fluid preferably contains little or no oxygen and preferably includes antioxidants, both molecular (e.g., 2-ascorbic acid tocopherol) and enzymatic (e.g., catalase and superoxide dismutase (SOD)). Normothermic and/or hypothermic perfusion, and preferably hypothermic perfusion, can be performed in vivo as well as in vitro. Such perfusion arrests ischemic injury in preparation for transport, storage and/or transplant of the organ.

[0017] The normothermic treatment is preferably employed after an organ has been subjected to hypothermic temperatures, statically and/or under perfusion. Such initial hypothermic exposure can occur, for example, during transport and/or storage of an organ after harvesting. The treatment is also suitable for organs that will ultimately be stored and/or transported under hypothermic conditions. In other words, the treatment can be applied to organs prior to cold storage and/or transport.

[0018] In the normothermic perfusion mode, gross organ perfusion pressure is preferably provided by a pneumatically pressurized medical fluid reservoir controlled in response to a sensor disposed in an end of tubing placed in the organ, which may be used in combination with a stepping motor/cam valve or pinch valve which provides for perfusion pressure fine tuning, prevents overpressurization and/or provides emergency flow cut-off. Alternatively, the organ may be perfused directly from a pump, such as a roller pump or a peristaltic pump, with proper pump control and/or sufficiently fail-safe controllers to prevent overpressurization of the organ, especially as a result of a system malfunction. Substantially eliminating overpressurization prevents and/or reduces damage to the vascular endothelial lining and to the organ tissue in general. Viability of the organ may be monitored, preferably automatically, in the normothermic perfusion mode, preferably by monitoring organ resistance (pressure/flow) and/or pH, pO<sub>2</sub>, pCO<sub>2</sub>, LDH, T/GST, Tprotein, lactate, glucose, base excess and/or ionized calcium levels in the medical fluid that has been perfused through the organ and collected.

[0019] Normothermic perfusion may be preceded by and/or followed by hypothermic perfusion. In the hypothermic mode, the organ is perfused with a medical fluid containing substantially no oxygen, preferably a simple crystalloid



solution that may preferably be augmented with antioxidants, intermittently or at a slow continuous flow rate. Hypothermic perfusion also can be performed in vivo as well as in vitro prior to removal of the organ from the donor. Hypothermic perfusion reduces the organ's metabolic rate, allowing the organ to be preserved for extended periods of time. The medical fluid is preferably fed into the organ by pressure from an intermediary tank which has a low pressure head so overpressurization of the organ is avoided. Alternatively, in embodiments, gravity can be used to feed the medical fluid into the organ from the intermediary tank, if appropriate. Alternatively, the organ may be perfused directly from a pump, such as a roller pump or a peristaltic pump, with proper pump control and/or sufficiently fail-safe controllers to prevent overpressurization of the organ, especially as a result of a system malfunction. Substantially eliminating overpressurization prevents or reduces damage to the vascular endothelial lining of the organ and to the organ tissue in general, in particular at hypothermic temperatures when the organ has less ability to protect itself by vascular constriction. Viability of the organ may also be monitored, preferably automatically, during the recovery process, preferably by monitoring organ resistance (pressure/flow) and/or pH, pO<sub>2</sub>, pCO<sub>2</sub>, LDH, T/GST, Tprotein, lactate, glucose, base excess and/or ionized calcium levels in the medical fluid that has been perfused through the organ and collected.

**[0020]** An organ diagnostic apparatus may also be provided to produce diagnostic data such as an organ viability index. The organ diagnostic apparatus includes features of an organ perfusion apparatus, such as sensors and temperature controllers, as well as cassette interface features, and provides analysis of the organ and input and output fluids in a perfusion system. Typically, the organ diagnostic apparatus is a simplified perfusion apparatus providing diagnostic data in a single pass, in-line perfusion.

**[0021]** An organ viability index may be provided taking into account the various measured factors identified above, such as vascular resistance, pH etc. The index may be organ specific, or may be adaptable to various organs. The index compiles the monitored parameters into a diagnostic summary to be used for making organ therapy decisions and deciding whether to transplant the organ. The index may be automatically generated and provided to the physician.

**[0022]** Embodiments of this invention include a control system for automatically controlling perfusion of one or more organs by selecting between perfusion modes and control parameters. Automatic perfusion may be based on sensed conditions in the system or manually input parameters. The system may be preprogrammed or programmed during use. Default values and viability checks are utilized.

**[0023]** The perfusion apparatus may be used for various organs, such as the kidneys, hearts, and lungs and may be adapted to more complex organs, such as the liver, having multiple vasculature structures, for example, the hepatic and portal vasculatures of the liver.

**[0024]** The present invention also provides an organ cassette which allows an organ to be easily and safely moved between apparatus for perfusing, storing, analyzing and/or transporting the organ. The organ cassette may be configured to provide uninterrupted sterile conditions and efficient heat transfer during transport, recovery, analysis and stor-

age, including transition between the transporter, the perfusion apparatus and the organ diagnostic apparatus.

**[0025]** The present invention also provides an organ transporter which allows for transportation of an organ over long distances. The organ transporter may be used for various organs, such as the kidneys, and may be adapted to more complex organs, such as the liver, having multiple vasculature structures, for example, the hepatic and portal vasculatures of the liver. The organ transporter includes features of an organ perfusion apparatus, such as sensors and temperature controllers, as well as cassette interface features.

**[0026]** The present invention focuses on avoiding damage to an organ during perfusion while monitoring, sustaining and/or restoring the viability of the organ and preserving the organ for storage and/or transport and/or transplantation and/or other use. For various reasons, it may be decided that the organ should not be transplanted. Because of the difficulty in obtaining organs from donors and restoring their viability, it is preferable that no organ should be completely discarded. As such, according to further exemplary embodiments of this invention, even though an organ might not be suitable for transplanting, the same organ can be used for other purposes such as screening the organ with bioactive agents for drug research or the like.

**[0027]** According to exemplary embodiments of the invention, the perfusion, diagnostic and transporter apparatus of the invention may be used in conjunction with the above techniques and methods and/or in conjunction with further techniques and methods, to perform research with an organ or tissue. Except where otherwise specified, organ in the present application includes tissue. During the period in which the organ is preserved and/or maintained, various drug research and development activities may be performed on and/or with the organ. The organ may be perfused with a medical fluid which may contain a substance such as a drug or other bioactive agent or other test substance, to obtain data regarding the interaction of the medical fluid and/or the substance and the organ. The data may then be used to provide information regarding efficacy, toxicity or other properties of the substance, for example in support of regulatory filings for new drugs or new uses thereof.

**[0028]** The perfusion, diagnostic and/or transporter apparatus may be used to perfuse a medical fluid through an organ while monitoring the organ and the organ outflow to analyze the condition of the organ and/or to determine the effect on it from the introduction of the medical fluid and/or substance such as a drug or other bioactive agent.

**[0029]** The data of the organ, the medical fluid and the interaction therebetween can be compiled. Additionally, an organ data index may be provided to be used for storing the data generated from perfusing the organ. The data allows for ready research of organ and medical fluid and information may also be directly recovered from the perfusion, diagnostic or transporter apparatus to monitor the organ status. Various types of data and information may be grouped into sub-records or sub-directories to assist in data management and transfer. All the sub-records may be combined to form an overall organ screening record, which may be disseminated to or retrievable by physicians, scientists or other organizations for research purposes.

**[0030]** The perfusion apparatus, transporter, cassette, and organ diagnostic apparatus may be networked to permit

remote management, tracking and monitoring of the location and therapeutic and diagnostic parameters of the organ or organs being stored or transported. The information systems may be used to compile historical data of organ transport and storage, and provide cross-referencing with hospital and United Network for Organ Sharing (UNOS) data on the donor and recipient. The systems may also provide outcome data to allow for ready research of perfusion parameters and transplant outcomes.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0031] These and other aspects and advantages of the invention will become apparent from the following detailed description of embodiments when taken in conjunction with the accompanying drawings, in which:

[0032] **FIG. 1** is an organ perfusion apparatus according to the invention;

[0033] **FIG. 2** is a schematic diagram of the apparatus of **FIG. 1**;

[0034] **FIG. 3** is a diagram of the electronics of the apparatus of **FIG. 1**;

[0035] **FIG. 4** is an exploded view of a first pump module of a combined pump, filtration, oxygenation and/or debubbler apparatus according to the invention;

[0036] **FIG. 5** is an exploded view of a filtration module of a combined pump, filtration, oxygenation and/or debubbler apparatus according to the invention;

[0037] **FIG. 6** is an exploded view of an oxygenation module of a combined pump, filtration, oxygenation and/or debubbler apparatus according to the invention;

[0038] **FIG. 7** is an exploded view of a debubbler module of a combined pump, filtration, oxygenation and/or debubbler apparatus according to the invention;

[0039] **FIG. 8** is an exploded view of a second pump module of a combined pump, filtration, oxygenation and/or debubbler apparatus according to the invention;

[0040] **FIG. 9** is an exploded perspective view showing the modules of **FIGS. 4-8** assembled together;

[0041] **FIG. 10** is a front perspective view of an assembled modular combined pump, filtration, oxygenation and/or debubbler apparatus according to the invention;

[0042] **FIGS. 11A-11D** show side perspective views of various embodiments of an organ cassette according to the invention;

[0043] **FIG. 12** is a schematic diagram of an organ perfusion apparatus configured to simultaneously perfuse multiple organs;

[0044] **FIGS. 13A and 13B** show a stepping motor/cam valve according to the invention;

[0045] **FIGS. 14A-14F** show another stepping motor/cam valve according to the invention;

[0046] **FIG. 15** shows a block diagram that schematically illustrates a control system according to the invention;

[0047] **FIG. 16** shows an exemplary diagram of possible processing steps according to the invention;

[0048] **FIGS. 17 and 17A** show an embodiment of an organ cassette of the present invention;

[0049] **FIGS. 18 and 18A** show an embodiment of an organ chair according to the present invention;

[0050] **FIG. 19** shows an exterior perspective view of an organ transporter according to the present invention;

[0051] **FIG. 20** shows a cross-section view of an organ transporter of **FIG. 19**;

[0052] **FIG. 21** shows a block diagram of an organ transporter of **FIG. 19**;

[0053] **FIG. 22** shows operation states of an organ transporter of **FIG. 19**;

[0054] **FIG. 23** shows an alternative cross-section view of an organ transporter of **FIG. 19**;

[0055] **FIG. 24** shows data structures and information transfer schemes of a perfusion and organ transplant system of the present invention;

[0056] **FIGS. 25 and 25A** show motor control of a perfusion pump according to the present invention;

[0057] **FIG. 26** shows a liver perfusion apparatus according to the present invention;

[0058] **FIG. 27** shows a close-up view of a peristaltic pump for use in a perfusion apparatus according to **FIG. 26**;

[0059] **FIG. 28** shows an overall view of an organ diagnostic system according to the present invention;

[0060] **FIG. 29** shows a perspective view of an organ evaluation instrument for use in an organ diagnostic system according to **FIG. 28**;

[0061] **FIG. 30** shows an in-line perfusion system for use in an organ diagnostic system according to **FIG. 28**; and

[0062] **FIG. 31** shows a logic circuit for an organ diagnostic system according to **FIG. 28**.

#### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0063] For a general understanding of the features of the invention, reference is made to the drawings. In the drawings, like reference numerals have been used throughout to designate like elements.

[0064] **FIG. 1** shows an organ perfusion apparatus **1** according to the invention. **FIG. 2** is a schematic illustration of the apparatus of **FIG. 1**. The apparatus **1** is preferably at least partially microprocessor controlled, and pneumatically actuated. The microprocessor **150** connection to the sensors, valves, thermoelectric units and pumps of the apparatus **1** is schematically shown in **FIG. 3**. Microprocessor **150** and apparatus **1** may be configured to and are preferably capable of further being connected to a computer network to provide data sharing, for example across a local area network or across the Internet.

[0065] The organ perfusion apparatus **1** is capable of perfusing one or more organs simultaneously, at both normothermic and hypothermic temperatures (hereinafter, normothermic and hypothermic perfusion modes). All medical fluid contact surfaces are preferably formed of or coated with materials compatible with the medical fluid used, more

preferably non-thrombogenic materials. As shown in FIG. 1, the apparatus 1 includes a housing 2 which includes front cover 4, which is preferably translucent, and a reservoir access door 3. The apparatus preferably has one or more control and display areas 5a, 5b, 5c, 5d for monitoring and controlling perfusion.

[0066] As schematically shown in FIG. 2, enclosed within the housing 2 is a reservoir 10 which preferably includes three reservoir tanks 15a, 15b, 17. Two of the reservoir tanks 15a, 15b are preferably standard one liter infusion bags, each with a respective pressure cuff 16a, 16b. A pressure source 20 can be provided for pressurizing the pressure cuffs 16a, 16b. The pressure source 20 is preferably pneumatic and may be an on board compressor unit 21 supplying at least 10 LPM external cuff activation via gas tubes 26, 26a, 26b, as shown in FIG. 2. The invention, however, is not limited to use of an on board compressor unit as any adequate pressure source can be employed, for example, a compressed gas (e.g., air, CO<sub>2</sub>, oxygen, nitrogen, etc.) tank (not shown) preferably with a tank volume of 1.5 liters at 100 psi or greater for internal pressurization. Alternatively, an internally pressurized reservoir tank (not shown) may be used. Reservoir tanks 15a, 15b, 17 may, in embodiments, be bottles or other suitably rigid reservoirs that can supply perfusate by gravity or can be pressurized by compressed gas.

[0067] Gas valves 22-23 are provided on the gas tube 26 to allow for control of the pressure provided by the onboard compressor unit 21. Anti-back flow valves 24a, 24b may be provided respectively on the gas tubes 26a, 26b. Pressure sensors P5, P6 may be provided respectively on the gas tubes 26a, 26b to relay conditions therein to the microprocessor 150, shown in FIG. 3. Perfusion, diagnostic and/or transporter apparatus may be provided with sensors to monitor perfusion fluid pressure and flow in the particular apparatus to detect faults in the particular apparatus, such as pressure elevated above a suitable level for maintenance of the organ. Gas valves GV<sub>1</sub> and GV<sub>2</sub> may be provided to release pressure from the cuffs 16a, 16b. One or both of gas valves GV<sub>1</sub> and GV<sub>2</sub> may be vented to the atmosphere. Gas valve GV<sub>4</sub> in communication with reservoir tanks 15a, 15b via tubing 18a, 18b may be provided to vent air from the reservoir tanks 15a, 15b through tubing 18. Tubing 18, 18a, 18b, 26, 26a and/or 26b may be configured with filters and/or check valves to prevent biological materials from entering the tubing or from proceeding further along the fluid path. The check valves and/or filters may be used to prevent biological materials from leaving one organ perfusion tubeset and being transferred to the tubeset of a subsequent organ in a multiple organ perfusion configuration. The check valves and/or filters may also be used to prevent biological materials, such as bacteria and viruses, from being transferred from organ to organ in subsequent uses of the perfusion apparatus in the event that such biological materials remain in the perfusion apparatus after use. The check valves and/or filters prevent contamination problems associated with reflux in the gas and/or vent lines. For example, the valves may be configured as anti-reflux valves to prevent reflux. The third reservoir tank 17 is preferably pressurized by pressure released from one of the pressure cuffs via gas valve GV<sub>2</sub>.

[0068] The medical fluid may be blood or a synthetic fluid and may, for example, be a simple crystalloid solution, or

may be augmented with an appropriate oxygen carrier. The oxygen carrier may, for example, be washed, stabilized red blood cells, cross-linked hemoglobin, pegolated hemoglobin or fluorocarbon based emulsions. The medical fluid may also contain antioxidants known to reduce peroxidation or free radical damage in the physiological environment and specific agents known to aid in tissue protection. As discussed in detail below, an oxygenated (e.g., cross-linked hemoglobin-based bicarbonate) solution is preferred for the normothermic mode while a non-oxygenated (e.g., simple crystalloid solution preferably augmented with antioxidants) solution is preferred for the hypothermic mode. The specific medical fluids used in both the normothermic and hypothermic modes are designed to reduce or prevent the washing away of or damage to the vascular endothelial lining of the organ. For the hypothermic perfusion mode, as well as for flush and/or static storage, a preferred solution is the solution disclosed in U.S. patent application Ser. No. 09/628,311, filed Jul. 28, 2000, the entire disclosure of which is incorporated herein by reference. Examples of additives which may be used in perfusion solutions for the present invention are also disclosed in U.S. Pat. No. 6,046,046 to Hassanein, the entire disclosure of which is incorporated by reference. Of course, other suitable solutions and materials may be used, as is known in the art.

[0069] The perfusion solution may be provided in a perfusion solution kit, for example, a saleable package preferably containing at least one first container holding a first perfusion solution for normothermic perfusion and at least one second container holding a second, different perfusion solution for hypothermic perfusion, optionally the box 10 shown in FIG. 2. The first perfusion solution may contain at least one oxygen carrier, may be oxygenated and/or may be selected from the group consisting of a cross-linked hemoglobin and stabilized red blood cells. The second perfusion solution may be non-oxygenated, may contain at least one anti-oxidant, and/or may contain at least one vasodilator. Additionally, the solution preferably contains no more than 5 mM of dissolved pyruvate salt. Also, the first container and the second container may be configured to be operably connected to a perfusion machine as perfusion fluid reservoirs in fluid communication with perfusate conduits of said perfusion machine. Further, one of the first and second containers may be compressible to apply pressure to the perfusion solution therein. Furthermore, at least one of the first and second containers may include a first opening for passage of a contained perfusion solution out of the container and a second opening passage of a compressed gas into the container. The package may be a cassette configured to be operably connected to a perfusion machine for connection of the first and second containers within the cassette in fluid communication with perfusate conduits or tubing of the perfusion machine.

[0070] In other embodiments, the perfusion solution kit may contain at least one first container holding a first perfusion solution for hypothermic perfusion at a first temperature and at least one second container holding a second, different perfusion solution for hypothermic perfusion at a second temperature lower than the first temperature. In the kit, the first perfusion solution may contain at least a crystalloid and may contain at least one vasodilator. The second perfusion solution may be oxygen carrier enhanced, where the oxygen carrier is selected from the group consisting of a hemoglobin and stabilized red blood cells. In

addition, the second perfusion solution may, if desired, contain at least one anti-oxidant or free radical scavenger. Preferably, the second solution contains no more than 5 mM of dissolved pyruvate salt. As above, the first container and the second container may be configured to be operably connected to a perfusion machine as perfusion fluid reservoirs in fluid communication with perfusate conduits of said perfusion machine. Further, one of the first and second containers may be compressible to apply pressure to the perfusion solution therein. Furthermore, at least one of the first and second containers may include a first opening for passage of a contained perfusion solution out of the container and a second opening passage of a compressed gas into the container. The package may be a cassette configured to be operably connected to a perfusion machine for connection of the first and second containers within the cassette in fluid communication with perfusate conduits or tubing of the perfusion machine.

[0071] The medical fluid within reservoir 10 is preferably brought to a predetermined temperature by a first thermoelectric unit 30a in heat transfer communication with the reservoir 10. A temperature sensor T3 relays the temperature within the reservoir 10 to the microprocessor 150, which adjusts the thermoelectric unit 30a to maintain a desired temperature within the reservoir 10 and/or displays the temperature on a control and display areas 5a for manual adjustment. Alternatively or in addition, and preferably where the organ perfusion device is going to be transported, the medical fluid within the hypothermic perfusion fluid reservoir can be cooled utilizing a cryogenic fluid heat exchanger apparatus such as that disclosed in co-pending application Ser. No. 09/039,443, which is hereby incorporated by reference.

[0072] An organ chamber 40 is provided which supports a cassette 65, as shown in FIG. 2, which holds an organ to be perfused, or a plurality of cassettes 65, 65, 65, as shown in FIG. 12, preferably disposed one adjacent the other. Various embodiments of the cassette 65 are shown in FIGS. 11A-11D. The cassette 65 is preferably formed of a material that is light but durable so that the cassette 65 is highly portable. The material may also be transparent to allow visual inspection of the organ.

[0073] Preferably the cassette 65 includes side walls 67a, a bottom wall 67b and an organ supporting surface 66, which is preferably formed of a porous or mesh material to allow fluids to pass therethrough. The cassette 65 may also include a top 67d and may be provided with an opening(s) 63 for tubing (see, for example, FIG. 11D). The opening(s) 63 may include seals 63a (e.g., septum seals or o-ring seals) and optionally be provided with plugs (not shown) to prevent contamination of the organ and maintain a sterile environment. Also, the cassette 65 may be provided with a closeable air vent 61 (see, for example, FIG. 11D). Additionally, the cassette 65 may be provided with tubing for connection to the organ or to remove medical fluid from the organ bath and a connection device(s) 64 for connecting the tubing to, for example, tubing 50c, 81, 82, 91 and/or 132 (see, for example, FIG. 11D). The cassette 65, and more particularly the organ support, opening(s), tubing(s) and/or connection(s), may be specifically tailored to the type of organ and/or size of organ to be perfused. Outer edges 67c of the side support walls 67a can be used to support the cassette 65 disposed in the organ chamber 40. The cassette 65 may

further include a handle portion 68 which allows the cassette 65 to be easily handled, as shown, for example, in FIGS. 11C and 11D. Each cassette 65 may also be provided with its own stepping motor/cam valve 75 (for example, in the handle portion 68, as shown in FIG. 11C) for fine tuning the pressure of medical fluid perfused into the organ 60 disposed therein, discussed in more detail below. Alternatively, pressure may, in embodiments, be controlled by way of a pneumatic chamber, such as an individual pneumatic chamber for each organ (not shown), or by any suitable variable valve such as a rotary screw valve or a helical screw valve.

[0074] FIG. 17 shows an alternative embodiment of cassette 65. In FIG. 17, cassette 65 is shown with tubeset 400. Tubeset 400 can be connected to perfusion apparatus 1 or to an organ transporter or an organ diagnostic apparatus, and allows cassette 65 to be moved between various apparatus without jeopardizing the sterility of the interior of cassette 65. Preferably, cassette 65 is made of a sufficiently durable material that it can withstand penetration and harsh impact. Cassette 65 is provided with a lid, preferably two lids, an inner lid 410 and an outer lid 420. The lids 410 and 420 may be removable or may be hinged or otherwise connected to the body of cassette 65. Clasp 405 provides a mechanism to secure lids 410 and 420 to the top of cassette 65. Clasp 405 may additionally be configured with a lock to provide further security and stability. A biopsy port 430 may additionally be included in inner lid 410 or both inner lid 410 and outer lid 420. Biopsy port 430 provides access to the organ to allow for additional diagnosis of the organ with minimal disturbance of the organ. Cassette 65 may also have an overflow trough 440 (shown in FIG. 17A). Overflow trough 440 is a channel present in the top of cassette 65. When lids 410 and 420 are secured on cassette 65, overflow trough 440 provides a region that is easy to check to determine if the inner seal is leaking. Perfusate may be poured into and out of cassette 65 and may be drained from cassette 65 through a stopcock or removable plug.

[0075] Cassette 65 and/or both lids 410 and 420 may be constructed of an optically clear material to allow for viewing of the interior of cassette 65 and monitoring of the organ and to allow for video images or photographs to be taken of the organ. Perfusion apparatus 1 or cassette 65 may be wired and fitted with a video camera or a photographic camera, digital or otherwise, to record the progress and status of the organ. The captured images may be made available over a computer network such as a local area network or the Internet to provide for additional data analysis and remote monitoring. Cassette 65 may also be provided with a tag that would signal, e.g., through a bar code, magnetism, radio frequency, or other means, the location of the cassette, that the cassette is in the apparatus, and/or the identity of the organ to the perfusion apparatus or transporter. Cassette 65 may be sterile packaged and/or may be packaged or sold as a single-use disposable cassette, such as in a peel-open pouch. A single-use package containing cassette 65 may also include tubeset 400.

[0076] Cassette 65 may additionally be provided with an organ chair 1800 shown in FIGS. 18 and 18A. Organ chair 1800 is removable and provides a support surface for the organ within cassette 65. Utilizing a removable organ chair 1800 allows the organ to be cannulated and secured under cold conditions when the organ is recovered from a donor before being placed into cassette 65. Organ chair 1800 may

be reusable or single-use. Organ chair **1800** may be constructed specifically to correspond to each type of organ, such as the kidney, heart or liver. Organ chair **1800** is preferably designed to be form fitting to the organ but to allow for the full anthropometric range of organ sizes.

[0077] Preferably, organ chair **1800** is at least partially perforated to allow fluids to pass through organ chair **1800**. The perforations in organ chair **1800** may be sized to catch organ debris, or an additional filter layer, preferably constructed of cloth, fabric, nylon, plastic, etc., to catch organ debris of at least 15 microns in diameter. In addition, a separate filter may be used on the tubing that intakes fluid directly from the perfusate bath to prevent organ debris of a predetermined size, for example at least 10 to 15 microns in diameter, from entering the perfusion tubing.

[0078] Organ chair **1800** may also be configured with a venous outflow sampler **1810**. Organ chair **1800** funnels the venous outflow into venous outflow sampler **1810**. Venous outflow sampler **1810** provides a readily available source for capturing the venous outflow of the organ. Capturing the venous outflow in this manner permits analysis of the perfusate leaving the organ without cannulating a vein and enables organ viability to be measured with a high degree of sensitivity by analyzing differentially the perfusate flowing into and out of the organ. Alternatively, venous outflow may be captured directly by cannulating a vein, but this method increases the risk of damaging the vein or the organ. Organ chair **1800** may also be raised and lowered within cassette **65** to facilitate sampling from venous outflow sampler **1810**. Alternatively, a sufficient amount of the organ bath may be drained from cassette **65** to obtain access to venous outflow sampler **1810** or to capture venous outflow before the outflow mixes with the rest of the perfusate in the organ bath.

[0079] Organ chair **1800** is preferably additionally configured with a cannula **1820** that attaches to the perfused artery, such as the renal artery. Cannula **1820** may be reusable or may be suitable for single-use, preferably provided in a sterile package with cassette **65**, organ chair **1800** and tubaset **400**. Cannula **1820** is provided with a cannula clamp **1830** to secure cannula **1820** around the perfused artery and to preferably provide leak-tight perfusion. A straight-in flanged cannula may also be used, however clamping around the artery is preferable to prevent contact with the inner surface of the artery, which is easily damaged. Cannula **1820** may also be configured with additional branching connections for accessory arteries. Multiple cannula and cannula clamp sizes may be used to accommodate various artery sizes or an adjustable cannula and cannula clamp may be used to accommodate various sized arteries. Cannula clamp **1830** may be a clam-shell configuration or may be a two-part design. Cannula clamp **1830** may be configured with integral or separate means for tightening cannula clamp **1830** to the proper pressure to provide leak-tight perfusion. In addition, cannula **1820** may be provided with a snap **1840** to hold cannula **1820** closed. Cannula **1820** may also be provided with a vent **1850** to remove air bubbles from cannula **1820**.

[0080] Organ chair **1800** preferably has a detented region **1860** that corresponds to protrusions **1870** on cannula **1820**. Such detents, tracks or grooves on organ chair **1800** allow cannula **1820** to be positioned at several locations to provide

various tensions on the perfused artery. This allows the ideal minimum tension to be set for each artery. Cannula clamp **1830** secures the perfusate tubing to the perfused artery. Cannula **1820** is adjustably secured to organ chair **1800** to provide for positioning the perfused artery to accommodate variations in organ size and artery length to prevent stretching, twisting, sagging or kinking of the artery. The combination of organ chair **1800**, cannula **1820** and additional straps or wide belts provides a secure platform to transport the organ and to transfer the organ between the cassette and the surgical field.

[0081] Organ chair **1800**, cannula **1820** and/or cannula clamp **1830** may be constructed of an optically clear material to facilitate monitoring of the organ and perfusion status.

[0082] The cassette **65** is configured such that it may be removed from the organ perfusion apparatus **1** and transported to another organ perfusion apparatus in a portable transporter apparatus, such as, for example, a conventional cooler or a portable container such as that disclosed in simultaneously filed co-pending U.S. application Ser. No. 09/161,919, or U.S. Pat. No. 5,586,438 to Fahy, which are hereby incorporated by reference in their entirety.

[0083] In embodiments, when transported, the organ is disposed on the organ supporting surface **66** and the cassette **65** is preferably enclosed in a preferably sterile bag **69**, as shown, for example, in FIG. 11A. When the organ is perfused with medical fluid, effluent medical fluid collects in the bag **69** to form an organ bath. Alternatively, the cassette **65** can be formed with a fluid tight lower portion in which the effluent medical fluid may collect, or the effluent medical fluid may collect in the organ chamber **40** to form the organ bath. In either alternative case, the bag **69** would preferably be removed prior to inserting the cassette into the organ chamber **40**. Further, where a plurality of organs are to be perfused, an organ chamber may be provided for each organ. Alternatively, cassette **65** can be transported in the dual-lid cassette of FIG. 17 and additionally carried within a portable organ transporter.

[0084] FIG. 19 shows an external view of an embodiment of transporter **1900** of the invention. The transporter **1900** of FIG. 19 has a stable base to facilitate an upright position and handles **1910** for carrying transporter **1900**. Transporter **1900** may also be fitted with a shoulder strap and/or wheels to assist in carrying transporter **1900**. A control panel **1920** is preferably also provided. Control panel **1920** may display characteristics, such as, but not limited to infusion pressure, power on/off, error or fault condition, flow rate, flow resistance, infusion temperature, bath temperature, pumping time, battery charge, temperature profile (maximums and minimums), cover open or closed, history log or graph, and additional status details and messages, which are preferably further transmittable to a remote location for data storage and/or analysis. Flow and pressure sensors or transducers in transporter **1900** may be used to calculate various organ characteristics including pump pressure and vascular resistance of an organ, which can be stored in computer memory to allow for analysis of, for example, vascular resistance history, as well as to detect faults in the apparatus, such as elevated pressure.

[0085] Transporter **1900** has latches **1930** that require positive user action to open, thus avoiding the possibility that transporter **1900** inadvertently opens during transport.

Latches **1930** hold top **1940** in place on transporter **1900**. Top **1940** or a portion thereof may be constructed with an optically clear material to provide for viewing of the cassette and organ perfusion status. Transporter **1900** may be configured with a cover open detector that monitors and displays if the cover is open or closed. Transporter **1900** may be configured with an insulating exterior of various thicknesses to allow the user to configure transporter **1900** for varying extents and distances of transport. In embodiments, compartment **1950** may be provided to hold patient and organ data such as charts, testing supplies, additional batteries, hand-held computing devices and/or other accessories for use with transporter **1900**. Transporter **1900** may also be configured with means for displaying a UNOS label and/or identification and return shipping information.

[0086] FIG. 20 shows a cross-section view of a transporter **1900**. Transporter **1900** contains cassette **65** and pump **2010**. Cassette **65** may be placed into and taken out of transporter **1900** without disconnecting tubeset **400** from cassette **65**, thus maintaining sterility of the organ. Sensors in transporter **1900** can detect the presence of cassette **65** in transporter **1900**, and depending on the sensor, can read the organ identity from a barcode or radio frequency or other smart tag that may be integral to cassette **65**. This allows for automated identification and tracking of the organ and helps monitor and control the chain of custody. A global positioning system may be added to transporter **1900** and/or cassette **65** to facilitate tracking of the organ. Transporter **1900** can be interfaced to a computer network by hardwire connection to a local area network or by wireless communication while in transit. This interface allows perfusion parameters, vascular resistance, and organ identification and transporter and cassette location to be tracked and displayed in real-time or captured for future analysis.

[0087] Transporter **1900** also preferably contains a filter **2020** to remove sediment and other particulate matter, preferably ranging in size from 0.05 to 15 microns in diameter or larger, from the perfusate to prevent clogging of the apparatus or the organ. Transporter **1900** also contains batteries **2030**, which may be located at the bottom of transporter **1900** or beneath pump **2010** or at any other location that provides easy access to change batteries **2030**. Batteries **2030** may be rechargeable outside of transporter **1900** or while intact within transporter **1900** and/or are preferably hot-swappable one at a time. Batteries **2030** are preferably rechargeable rapidly and without full discharge. Transporter **1900** may also provide an additional storage space **2040** at the bottom of transporter **1900** for power cords, batteries and other accessories. Transporter **1900** may also include a power port for a DC hookup to a vehicle such as an automobile or airplane and/or for an AC hookup.

[0088] FIG. 21 shows a block diagram of transporter **1900**. Transporter **1900** of FIG. 21 is intended to provide primarily hypothermic perfusion, and may operate at any temperatures, for example in the range of  $-25$  to  $60^{\circ}\text{C}$ ., approximately  $0$  to  $8^{\circ}\text{C}$ ., preferably approximately  $4^{\circ}\text{C}$ . The temperature may be adjusted based on the particular fluids used and adapted to the particular transport details, such as length of time of transport. Transporter **1900** is cooled by coolant **2110**, which may be an ice and water bath or a cryogenic material. In embodiments using cryogenic materials, the design should be such that organ freezing is prevented. The temperature of the perfusate bath surround-

ing the organ is monitored by temperature transducer **2115**. Transporter **1900** also contains filters **2020** to remove sediment and particulate, ranging in size from 0.05 to 15 microns in diameter or larger, from the perfusate to prevent clogging of the apparatus or the organ. Using a filter **2020** downstream of pump **2010** allows for capturing inadvertent pump debris and also dampens pressure spikes from pump **2010**.

[0089] The flow of perfusate within transporter **1900** is controlled by pump **2010**, which is preferably a peristaltic or roller pump. Pump **2010** is preferably not in contact with the perfusate to help maintain sterility. In addition, tubeset **400** may be attached to pump **2010** without opening the tubing circuit. Pump **2010** is controlled by a computer or micro-controller. The computer can actively modulate the angular velocity of pump **2010** to reduce the natural pulse actions of pump **2010** to a low level, resulting in essentially non-pulsatile flow. Further computer control can impose a synthesized pressure pulse profile that can be sinusoidal or physiological or otherwise. The average flow rate and pressure can be made independent of pulse repetition rate by pulse width modulating or amplitude modulating the synthesized pressure pulses. Control over some or all of the pulse parameters can be made available to users through control panel **1920** or over a network. Pulse control can be organ specific. In the case of a liver, a single pump can provide continuous flow to the portal vein at, for example, 1 to 3 liters per minute while providing pulsatile flow to the hepatic artery at, for example, 100 to 300 ml per minute. Synchronizing the shunt valves to the pump controller allows independent pressure regulation of the two flows.

[0090] The flow of the perfusate into the organ is monitored by flow sensor **2125**. Pressure transducers **2120** may be present to monitor the pressure the perfusate places on the tubing. Pressure transducers **2120** may be used to monitor the pump pressure and/or the infusion pressure. A pressure transducer **2120** may be present just upstream of the organ to monitor the organ infusion pressure. Transporter **1900** may be configured with a bubble detector **2125** to detect bubbles before the perfusate enters bubble trap **2130**. Bubble detectors, such as bubble detector **2125**, may be used to detect bubbles in, for example, the infuse line and/or in the pump output line. Bubble trap **2130** removes air bubbles from the perfusate and vents the bubbles into the wash tube. Bubble trap **2130** may be disposable and may be constructed integral to tubeset **400**. Perfusate exiting bubble trap **2130** can either continue through infuse valve **2140** or wash valve **2150**. Wash valve **2150** is normally open and infuse valve **2140** is normally closed. Preferably, wash valve **2150** and infuse valve **2140** operate dependently in an on/off manner, such that if one valve is open, the other valve is closed. Although infuse valve **2140** is normally closed, if the sensor and monitors all report suitable perfusion parameters present in transporter **1900**, then infuse valve **2140** may be opened to allow organ perfusion. In the occurrence of a fault, such as elevated perfusion pressure above a suitable level for the organ, infuse valve **2140** switches back to closed and wash valve **2150** is opened to divert fluid flow into the perfusate bath surrounding the organ. This provides a failsafe mechanism that automatically shunts perfusate flow and prevents organ perfusion in case of a power failure or computer or electronics malfunction. A pressure transducer **2120**, such as designated by  $P_2$ , may be hardwired, redundant to the computer and software control, to wash valve **2150** and infuse valve **2140** to quickly deliver a default message to the

valves in the case of a pressure malfunction. In embodiments, the diverted fluid may be separately collected in another container or compartment.

[0091] FIG. 22 shows various operation states of transporter 1900. For example, using the controls provided on control panel 1920, a user may select operations such as perfuse, idle, wash and prime. FIG. 22 shows various options depending on the present state of transporter 1900. The labels idle, prime, wash, perfuse and error handling indicate the state of transporter 1900 that is preferably displayed on control panel 1920 during the corresponding operation. For example, when transporter 1900 is in a wash operation, control panel 1920 displays the wash operation indicator, such as an LED display. The arrows connecting the various operations of transporter 1900 indicate the manual and automatic actions that may occur to transition transporter 1900 between operation states. Manual actions require the user to act, for example by pressing a button or turning a knob or dial. FIG. 22 exemplifies pressing a button or other indicator, for example, to move from a perfusion operation to an idle operation by pressing the stop button (Press Stop). To move directly into a perfuse operation from an idle operation, a user presses the perfuse button (Press Perfuse).

[0092] Automatic operations may be controlled by the passage of time and/or by an internal monitor within transporter 1900. Such automatic operation is shown in FIG. 22, for example, connecting the prime operation to the idle operation. If the prime operation has been completed according to the internal transporter program parameters before the wash button has been pressed, transporter 1900 returns to an idle operation. Another automatic operation occurs during a perfuse operation if a fault or error occurs, such as overpressurization of the organ. When an error or fault occurs, transporter 1900 can move to an error handling operation to determine the extent or degree of the fault or error. If the fault or error is determined to be a small or correctable error, transporter 1900 moves into a wash operation. If transporter 1900 can then adjust the system parameters to handle the fault or error, transporter 1900 moves back to perfuse (Error Recovery). If transporter 1900 can not adjust the system parameters to handle the fault or error, transporter 1900 moves to an idle operation. If the error or fault detected is determined to be substantial, transporter 1900 may move directly into an idle operation.

[0093] FIG. 23 shows an alternative cross-section of transporter 1900. Transporter 1900 may have an outer enclosure 2310 constructed of metal, or preferably a plastic or synthetic resin that is sufficiently strong to withstand penetration and impact. Transporter 1900 contains insulation 2320, preferably a thermal insulation made of, for example, glass wool or expanded polystyrene. Insulation 2320 may be various thicknesses ranging from 0.5 inches to 5 inches thick or more, preferably 1 to 3 inches, such as approximately 2 inches thick. Transporter 1900 is cooled by coolant 2110, which may be, e.g., an ice and water bath or a cryogenic material. In embodiments using cryogenic materials, the design should be such that organ freezing is prevented. An ice and water mixture is preferably in an initial mixture of approximately 1 to 1, however, in embodiments the ice and water bath may be frozen solid. Transporter 1900 can be configured to hold various amounts of coolant, preferably up to 10 to 12 liters. An ice and water bath is preferable because

it is inexpensive and can not get cold enough to freeze the organ. Coolant 2110 preferably lasts for a minimum of 6 to 12 hours and more preferably lasts for a minimum of 30 to 50 hours without changing coolant 2110. The level of coolant 2110 may be viewed through a transparent region of transporter 1900 or may be automatically detected and monitored by a sensor. Coolant 2110 can be replaced without stopping perfusion or removing cassette 65 from transporter 1900. Coolant 2110 is maintained in a watertight compartment 2115 of transporter 1900. Compartment 2115 prevents the loss of coolant 2110 in the event transporter 1900 is tipped or inverted. Heat is conducted from the walls of the perfusion reservoir and cassette 65 into coolant 2110 enabling control within the desired temperature range. Coolant 2110 is a failsafe cooling mechanism because transporter 1900 automatically reverts to cold storage in the case of power loss or electrical or computer malfunction. Transporter 1900 may also be configured with a heater to raise the temperature of the perfusate.

[0094] Transporter 1900 may be powered by batteries or by electric power provided through plug 2330. An electronics module 2335 is also provided in transporter 1900. Electronics module 2335 is cooled by vented air convection 2370, and may further be cooled by a fan. Preferably, electronic module 2335 is positioned separate from the perfusion tubes to prevent the perfusate from wetting electronics module 2335 and to avoid adding extraneous heat from electronics module 2335 to the perfusate. Transporter 1900 has a pump 2010 that provides pressure to perfusate tubing 2360 to deliver perfusate 2340 to organ 2350. Transporter 1900 may be used to perfuse various organs such as a kidney, heart, liver, small intestine and lung. Transporter 1900 and cassette 65 may accommodate various amounts of perfusate 2340, for example up to 3 to 5 liters. Preferably, approximately 1 liter of a hypothermic perfusate 2340 is used to perfuse organ 2350. Organ 2350 may be various organs, including but not limited to a kidney, heart, lung, liver or small intestine.

[0095] Cassette 65 and transporter 1900 are preferably constructed to fit or mate such that efficient heat transfer is enabled. The geometric elements of cassette 65 and transporter 1900 are preferably constructed such that when cassette 65 is placed within transporter 1900, the elements are secure for transport.

[0096] FIG. 24 shows various data structures and information connections that can be facilitated to assist in the overall communication and data transfers that may be beneficial before, during and after organ transplantation. The perfusion apparatus, transporter, cassette, and organ diagnostic apparatus may be networked to permit remote management, tracking and monitoring of the location and therapeutic and diagnostic parameters of the organ or organs being stored or transported. The information systems may be used to compile historical data of organ transport and storage, and provide cross-referencing with hospital and UNOS data on the donor and any recipient and/or information on why transplant may be inappropriate. The systems may also provide outcome data to allow for ready research of perfusion parameters and transplant outcomes. For example, information regarding the donor may be entered at the location where an organ is recovered from a donor. Information may also be directly recovered from the perfusion, diagnostic or transporter apparatus to monitor organ

status and location. Various types of information may be grouped into sub-records or sub-directories to assist in data management and transfer. All the sub-records may be combined to form an overall transplant record, which may be disseminated to or retrievable by physicians, scientists or other organizations for tracking and monitoring purposes.

[0097] Preferred embodiments of transporter **1900** can automatically log much or all of the perfusion process data and transporter **1900** events into an internal database. A radio frequency or barcode labeled tag or the like for each cassette **65** allows transporter **1900** to reference the data uniquely to each organ. When transporter **1900** reaches a docking port, transporter **1900** can upload data to a main database computer over a LAN. Transporter **1900** can also provide real-time status whenever transporter **1900** is connected to the LAN. Transporter **1900** can also be configured with a wireless communications setup to provide real-time data transfer during transport. Perfusion apparatus **1** can also be connected to the LAN and since perfusion apparatus is generally stationary, data uploads can occur continuously and in real-time. The data can be cross-referenced with UNOS data to utilize the UNOS data on organ identification, donor condition, donor logistics, recipient logistics and recipient outcomes. Data may be displayed and accessed on the Internet to facilitate monitoring from any location.

[0098] Within the perfusion, diagnostic and/or transporter apparatus, the organ bath is preferably cooled to a predetermined temperature by a second thermoelectric unit **30b**, as shown in FIG. 2, in heat transfer communication with the organ chamber **40**. Alternatively and preferably where the organ perfusion device is going to be transported, the medical fluid within reservoir **10** can be cooled utilizing a heat transfer device such as an ice and water bath or a cryogenic fluid heat exchanger apparatus such as that disclosed in co-pending application Ser. No. 09/039,443, which is hereby incorporated by reference. A temperature sensor **T2** within the organ chamber **40** relays the temperature of the organ **60** to the microprocessor **150**, which adjusts the thermoelectric unit **30b** to maintain a desired organ temperature and/or displays the temperature on the control and display areas **5c** for manual adjustment.

[0099] Medical fluid may be fed from the bag **15a** directly to an organ **60** disposed in the organ chamber **40** through tubing **50a**, **50b**, **50c** or from bag **15b** through tubing **50d**, **50e**, **50c** by opening valve **LV<sub>4</sub>** or **LV<sub>3</sub>**, respectively. Conventional medical fluid bag and tubing connections may be utilized. All tubing is preferably disposable, easily replaceable and interchangeable. Further, all tubing is preferably formed of or coated with materials compatible with the medical fluids used, more preferably non-thrombogenic materials. An end of the tubing **50c** is inserted into the organ **60**. The tubing may be connected to the organ(s) with conventional methods, for example, with sutures. The tubing may include a lip to facilitate connection to the organ. Alternatively, cannula **1820** described above may be used with or without connection to an organ chair **1800**. However, the specific methods and connection depend on the type of organs(s) to be perfused.

[0100] The microprocessor **150** preferably controls the pressure source **20** in response to signals from the pressure sensor **P1** to control the pressure of the medical fluid fed into the organ **60**. The microprocessor **150** may display the

pressure on the control and display areas **5a**, optionally for manual adjustment. A fluid flow monitor **F1** may also be provided on the tubing **50c** to monitor the flow of medical fluid entering the organ **60** to indicate, for example, whether there are any leaks present in the organ.

[0101] Alternatively, the medical fluid may be fed from the reservoir tank **17** via tubing **51** into an intermediary tank **70** preferably having a pressure head of approximately 5 to 40 mm Hg. Medical fluid is then fed by gravity or, preferably, pressure, from the intermediary tank **70** to the organ **60** along tubing **50c** by activating a valve **LV<sub>6</sub>**. A level sensor **71** may be provided in the intermediary tank **70** in order to maintain the pressure head. Where a plurality of organ chambers **40** and organs **60** are provided, the organs **60** are connected in parallel to the reservoir **10** utilizing suitable tubing duplicative of that shown in FIG. 2. See, for example, FIG. 12. The use of pneumatically pressurized and gravity fed fluid pumps configured to avoid overpressurization even in cases of system failure reduces or prevents general tissue damage to the organ and the washing away of or damage to the vascular endothelial lining of the organ. Thus, organ perfusion in this system can be performed, e.g., with either hydrostatic perfusion (gravity or pressure fed flow) or peristaltic perfusion by introducing flow to the organ from a peristaltic (roller) pump.

[0102] A bubble detection system may be installed to sense bubbles in the perfusate. An air sensor and sensor board are preferably used. The output of the sensor activates a debubbler system, such as an open solenoid valve, to rid bubbles from the perfusate flow prior to organ introduction. As with all of the sensors and detectors in this system, the bubble detector may be positioned at any point in the system that is effective based on the particular parameters or design characteristics of the system. For example, a bubble detector and debubbler system **BD** may be positioned between the cam valve **205** and pressure sensor **P1**, as shown in FIG. 1.

[0103] A stepping motor/cam valve **205**, or other suitable variable valve such as a rotary screw valve, may be arranged on the tubing **50c** to provide pulsatile delivery of the medical fluid to the organ **60**, to decrease the pressure of the medical fluid fed into the organ **60**, and/or to stop flow of medical fluid into the organ **60** if the perfusion pressure exceeds a predetermined amount. Alternatively, a flow diverter or shunt line may be provided in the perfusion apparatus to which the fluid flow is diverted in the occurrence of a fault, such as excess pressure, for example by opening and closing a valve or a series of valves. Specific embodiments of the stepping motor/cam valve are shown in FIGS. 13A-13B and 14A-14F. FIGS. 13A-13B show a stepping motor/rotational type cam valve.

[0104] FIG. 13A is a top view of the apparatus. Tubing, for example, tubing **50c**, is interposed between a support **203** and cam **200**. Cam **200** is connected by a rod **201** to stepping motor **202**. FIG. 13B is a side view of the apparatus. The dashed line shows the rotational span of the cam **200**. In FIG. 13B, the cam **200** is in its non-occluding position. Rotated 180 degrees, the cam **200** totally occludes the tubing **50c** with varying degrees of occlusion therebetween. This stepping motor/cam valve is relatively fast, for example, with respect to the embodiment shown in FIGS. 14A-14F; however, it requires a strong stepping motor.

[0105] FIGS. 14A-14F disclose another stepping motor/cam valve **210** according to the invention. FIG. 14A is a side



view of the apparatus while **FIG. 14C** is a top view. Tubing, for example, tubing **50c**, is interposed between cam **220** and support **223**. The cam **220** is connected to stepping motor **222** by supports **221a-221d** and helical screw **225**, which is connected to the stepping motor **222** via plate **222a**. **FIG. 14B** shows the supports **221a** and plate **222a** in front view. As shown in **FIG. 14D**, where the support **221d** is to the left of the center of the helical screw **225**, the tubing **50c** is not occluded. However, as the helical screw **225** is turned by the stepping motor **222**, the support **221d** moves to the left (with respect to **FIGS. 14D-14F**) toward a position where the cam **220** partially or fully occludes the tubing **50c**. Such apparatus is slower than the apparatus of **FIGS. 13A-13B**, but is more energy efficient.

[0106] Medical fluid expelled from the organ **60** which has collected in the bottom of the bag **69** (the cassette **65** or the organ chamber **40**) is either pumped out through tubing **81** by a pump **80** for filtration, passing through a filter unit **82** and being returned to the organ bath, or is pumped out by a pump **90** for circulation through tubing **91**. The pumps **80**, **90** are preferably conventional roller pumps or peristaltic pumps; however, other types of pumps may also be appropriate.

[0107] **FIG. 25** shows a simplified schematic of a pump and pulse controller **2500** and the interaction of the pump and pulse controller with a perfusion apparatus, such as shown in **FIG. 1**. Pump and pulse controller **2500** receives pressure sensor data input **2510** from pressure sensor **P** and tachometer data input **2520**. A tachometer may be used to set the phase angle of the active wave. Pump and pulse controller **2500** converts this information to motor drive output **2530**, which powers pump **2540**. **FIG. 25A** shows various modes of operation that pump and pulse controller **2500** can provide and how pump and pulse controller **2500** eliminates pressure pulse waves from the perfusate flow and how it modulates perfusate flow rate while maintaining a constant pressure pulse rate.

[0108] A peristaltic pump driven at a constant speed provides a constant pressure wave in the associated tubing. **FIG. 25A** shows in the first mode of operation the waveforms that result from a constant drive speed applied to a peristaltic pump. The second mode of operation, called active continuous, shows how the pressure pulse wave can be eliminated or canceled out by applying a motor drive wave that is opposite to the pressure wave of the pump. In the third mode of operation, called active waveform amplitude modulating, the pump pressure pulse wave is canceled by the motor drive wave, and a selected wave is added with a new amplitude as compared to the original pressure pulse wave amplitude. In the fourth mode of operation, called active waveform pulse width modulating, the pump pressure pulse wave is canceled by the motor drive wave, and a selected wave is added with a new pulse width as compared to the original pressure pulse wave width. In an alternative mode of operation, the frequency may be modulated by adding a new frequency wave to the canceled waves.

[0109] A level sensor **L2** in communication with the microprocessor **150** (see **FIG. 3**) ensures that a predetermined level of effluent medical fluid is maintained within the organ chamber **40**. As shown in **FIG. 2**, a temperature sensor **T1** disposed in the tubing **91** relays the temperature of the medical fluid pumped out of the organ bath along tubing **91**

to the microprocessor **150**, which monitors the same. A pressure sensor **P2** disposed along the tubing **91** relays the pressure therein to the microprocessor **150**, which shuts down the system if the fluid pressure in the tubing **91** exceeds a predetermined limit, or activates an alarm to notify the operator that the system should be shut down, for example, to clean filters or the like.

[0110] As the medical fluid is pumped along tubing **91** it preferably passes through a filter unit **95** (e.g.,  $25\mu$ ,  $8\mu$ ,  $2\mu$ ,  $0.8\mu$ ,  $0.2\mu$ , and/or  $0.1\mu$  filters); a  $\text{CO}_2$  scrubber/ $\text{O}_2$  membrane **100** and an oxygenator **110**, for example, a JOSTRA™ oxygenator. The  $\text{CO}_2$  scrubber/ $\text{O}_2$  membrane **100** is preferably a hydrophobic macroporous membrane with a hydrophilic (e.g., Hypol) coating in an enclosure. A vacuum source (not shown) is utilized to apply a low vacuum on a side opposite the hydrophilic coating by the activation of valve  $\text{VV}_1$ . A hydrostatic pressure of approximately 100 mm Hg is preferred for aqueous passage through the membrane. The mechanical relief valve (not shown) prevents the pressure differential from attaining this level. Immobilized pegolated carbonic anhydrase may be included in the hydrophilic coating. This allows bicarbonate to be converted to  $\text{CO}_2$  and subsequently removed by vacuum venting. However, with organs such as kidneys which have the ability to eliminate bicarbonate, this may be unnecessary except in certain cases.

[0111] The oxygenator **110** is preferably a two stage oxygenator which preferably includes a hydrophilically coated low porosity oxygen permeable membrane. A portion of the medical fluid is diverted around the oxygenator along tubing **111** in which is disposed a viability sensor **V1**, which senses fluid characteristics, such as organ resistance (pressure/flow), pH,  $\text{pO}_2$ ,  $\text{pCO}_2$ , LDH, T/GST, Tprotein, lactate, glucose, base excess and ionized calcium levels indicative of an organ's viability. The viability sensor **V1** is in communication with the microprocessor **150** and allows the organ's viability to be assessed either automatically or manually. One of two gases, preferably 100% oxygen and 95/5% oxygen/carbon dioxide, is placed on the opposite side of the membrane depending on the pH level of the diverted medical fluid. Alternatively, another pump (not shown) may be provided which pumps effluent medical fluid out of the organ chamber **40** and through a viability sensor before returning it to the bath, or the viability sensor can be placed on tubing **81** utilizing pump **80**. In embodiments, the fluid characteristics may be analyzed in a separate diagnostic apparatus and/or analyzer as shown in **FIGS. 28-31**.

[0112] The sensed fluid characteristics, such as organ resistance (pressure/flow), pH,  $\text{pO}_2$ ,  $\text{pCO}_2$ , LDH, T/GST, Tprotein, lactate, glucose, base excess and ionized calcium levels may be used to analyze and determine an organ's viability and/or the effect of applied bioactive or other test substance thereon. The characteristics may be analyzed individually or multiple characteristics may be analyzed to determine the effect of various factors. The characteristics may be measured by capturing the venous outflow of the organ and comparing its chemistry to the perfusate inflow. The venous outflow may be captured directly and measured or the organ bath may be measured to provide a rough approximation of the fluid characteristics for comparisons over a period of time.

[0113] In embodiments, an organ viability index is provided taking into account the various measured factors

identified above, such as vascular resistance, pH, etc. The index may be organ specific, or may be adaptable to various organs. The index compiles the monitored parameters into a diagnostic summary which may be used for making organ therapy decisions and deciding whether to transplant the organ or make other use of it. The index may be automatically generated and provided to the physician. The index is preferably computer generated via a connection to the perfusion apparatus, transporter, cassette and/or organ diagnostic apparatus. The additional information, such as donor specific information, may be entered into a single computer at the site of the perfusion apparatus, transporter, cassette and/or organ diagnostic apparatus or may be entered in a remote computer and linked to the perfusion apparatus, etc. In embodiments, the index may be made available over a computer network such as a local area network or the Internet for quick comparison, remote analysis and data storage.

[0114] The organ viability index provides measurements and normal ranges for each characteristic, such as vascular resistance and perfusate chemistry characteristics based on pH,  $pO_2$ ,  $pCO_2$ , LDH, T/GST, Tprotein, lactate, glucose, base excess and ionized calcium levels. For example, at approximately 5° C., normal pH may be from 7.00 and 8.00, preferably from 7.25 and 7.75 and more preferably from 7.50 and 7.60 and base excess may be in the range of from -10 to -40, preferably from -15 to -30, and more preferably from -20 to -25. Measurements that are outside the normal range may be indicated visually, e.g., by an asterisk or other suitable notation, aurally or by machine perceivable signals. The characteristics give the physician insight into the metabolism of the organ, such as stability of the metabolism, consumption of glucose, creation of lactic acid and oxygen consumption.

[0115] The index may also provide identifying information, such as age, gender, blood type of the donor and any expanded criteria; organ information, such as organ collection date and time, warm ischemia time, cold ischemia time and vascular resistance; apparatus information, such as flow rate, elapsed time the pump has been operating and pressure; and other identifiers such as UNOS number and physician(s) in charge. The index may additionally provide temperature corrections if desired.

[0116] Returning to FIG. 2 and the flow and/or treatment of the medical fluid or perfusate in perfusion apparatus 1, alternative to the pump 90, filter unit 95, the  $CO_2$  scrubber/ $O_2$  membrane 100 and/or the oxygenator 110, a modular combined pump, filtration, oxygenation and/or debubbler apparatus may be employed such as that described in detail in simultaneously filed co-pending U.S. patent application Ser. No. 09/039,318, which is hereby incorporated by reference. As shown in FIGS. 4-10, the apparatus 5001 is formed of stackable modules. The apparatus 5001 is capable of pumping a fluid through a system as well as oxygenating, filtering and/or debubbling the fluid. The modules are each formed of a plurality of stackable support members and are easily combinable to form a compact apparatus containing desired components. Filtration, oxygenation and/or degassing membranes are disposed between the support members.

[0117] FIGS. 4-8 show various modules that may be stacked to form a combined pump, filtration, oxygenation and/or debubbler apparatus, such as the combined pump,

filtration, oxygenation and debubbler apparatus 5001 shown in FIGS. 9-10. As depicted in these figures, the combined pump, filtration, oxygenation and debubbler apparatus 5001 is preferably formed of a plurality of stackable support members groupable to form one or more modules.

[0118] Interposed between the plurality of stackable support member are filtration, oxygenation and/or degassing membranes depending on a particular user's needs. The filtration, oxygenation and/or degassing membranes are preferably commercially available macro-reticular hydrophobic polymer membranes hydrophilically grafted in a commercially known way, such as, for example, ethoxylation, to prevent protein deprivation, enhance biocompatibility with, for example, blood and to reduce clotting tendencies. The filtration membrane(s) is preferably hydrophilically grafted all the way through and preferably has a porosity (pore size) within a range of 15 to 35 $\mu$ , more preferably 20 to 30 $\mu$ , to filter debris in a fluid, preferably without filtering out cellular or molecular components of the fluid. The degassing membrane(s) and oxygenation membrane(s) are hydrophilically surface treated to maintain a liquid-gas boundary. The degassing membrane(s) and oxygenation membrane(s) preferably have a porosity of 15 $\mu$  or less, more preferably 10 $\mu$  or less.

[0119] The modules may include a first pump module 5010, as shown in exploded view in FIG. 4; a filtration module 5020, as shown in exploded view in FIG. 5; an oxygenation module 5030, as shown in exploded view in FIG. 6; a debubbler module 5040, as shown in exploded view in FIG. 7; and a second pump module 5050, as shown in exploded view in FIG. 8. The pump modules are each connected to a source of pump fluid and are actuated either manually or by the microprocessor. The support members are preferably similarly shaped. For example, the support members may each be plate-shaped; however, other shapes may also be appropriate. As shown in FIG. 10, the support members are preferably removably connected by screws or bolts 5065; however, other fasteners for assembling the apparatus may also be appropriate.

[0120] The first pump module 5010 preferably includes a first (end) support member 5011, a second support member 5012 with a cut-out center area 5012c, a diaphragm 5013 and a third support member 5014. The support members of this module and each of the other modules are preferably thin and substantially flat (plate-like), and can be formed of any appropriate material with adequate rigidity and preferably also biocompatibility. For example, various resins and metals may be acceptable. A preferred material is an acrylic/polycarbonate resin.

[0121] The first (end) support member 5011 is preferably solid and provides support for the pump module 5010. The first (end) support member 5011 preferably includes a domed-out cavity for receiving pump fluid such as air. Tubing 5011t is provided to allow the pump fluid to enter the pump module 5010. The diaphragm 5013 may be made of any suitable elastic and preferably biocompatible material, and is preferably polyurethane. The third support member 5014 includes a domed-out fluid cavity 5014d and tubing 5014t for receiving fluid, such as, for example, blood or an artificial perfusate, into the cavity 5014d of the pump module 5010. The first pump module, or any of the other modules, may also include a port 5014p for sensors or the

like. Preferably hemocompatible anti-backflow valves serve to allow unidirectional flow through the pump module **5010**.

[0122] The filtration module **5020** preferably includes a filtration membrane **5021m** which forms a boundary of cavity **5014d**, a first support member **5022** with a cut-out center area **5022c**, a degassing membrane **5022m** and second and third support members **5023** and **5024**. The filtration membrane **5021m** is preferably a  $25\mu$  macro-reticular filtration membrane modified to enhance biocompatibility with, for example, blood and to reduce clotting tendencies (like the other supports, filters and membranes in the device). The degassing membrane **5022m** is preferably a  $0.2-3\mu$  macro-reticular degassing membrane with a reverse flow aqueous pressure differential of at least 100 mmHg for  $\text{CO}_2$  removal surface modified to enhance biocompatibility.

[0123] The first support **5022** includes tubing **5022t** for forwarding fluid into the oxygenation module **30**, or another adjacent module, if applicable, after it has passed through the filtration membrane **5021m** and along the degassing membrane **5022m**. The second support member **5023** of the filtration module **5020** includes a domed-out fluid cavity **5023d** and tubing **5023t** through which a vacuum may be applied to the cavity **5023d** to draw gas out of the fluid through degassing membrane **5022m**. The fourth support member **5024** is preferably solid and provides support for the filtration module **5020**. The third support member can also include tubing **5024t** through which a vacuum may be applied to draw gas out of the fluid through the degassing membrane **5031m** of the oxygenation module **5030** as discussed below. The filtration module **5020**, or any of the other modules, may also include a port **5023p** for sensors or the like.

[0124] The oxygenation module **5030** includes a degassing membrane **5031m**, a first support member **5032**, a filtration membrane **5033m**, an oxygenation membrane **5034m**, a second support member **5034** with a cut-out center area **5034c**, and third and fourth support members **5035**, **5036**. The degassing membrane **5031m** is preferably a  $0.2-3\mu$  macro-reticular degassing membrane with a reverse flow aqueous pressure differential of at least 100 mmHg surface modified to enhance biocompatibility.

[0125] The first support member **5032** includes a domed-out fluid cavity **5032d**. The surface of the domed-out fluid cavity **5032d** preferably forms a tortuous path for the fluid, which enhances the oxygenation and degassing of the fluid. The filtration membrane **5033m** is preferably a  $25\mu$  macro-reticular filtration membrane modified to enhance biocompatibility. The oxygenation membrane **5034m** is preferably a  $0.2-1\mu$  macro-reticular oxygenation membrane with a reverse flow aqueous pressure differential of at least 100 mmHg surface modified to enhance biocompatibility.

[0126] The second support member **5034** includes tubing **5034t** for forwarding fluid out of the oxygenation module **5030** into the debubbler module **5040**, or another adjacent module, if applicable. The third support member **5035** includes a domed-out cavity **5035d** and tubing **5035t** for receiving oxygen from an external source. The fourth support member **5036** is preferably solid and provides support for the oxygenation module **5030**.

[0127] The debubbler module **5040** includes a first support member **5041**, a filtration membrane **5042m**, a degassing

membrane **5043m**, a second support member **5043** having a cut-out center area **5043c**, and a third support member **5044**. The first support member **5041** has a domed-out fluid cavity **5041d**.

[0128] The filtration membrane **5042m** is preferably a  $25\mu$  macro-reticular filtration membrane modified to enhance biocompatibility. The degassing membrane **5043m** is preferably a  $0.2-3\mu$  macro-reticular degassing membrane with a reverse flow aqueous pressure differential of at least 100 mmHg surface modified to enhance biocompatibility. The second support member **5043** has tubing **5043t** for forwarding fluid out of the debubbler module **5040** into the pump module **5050**, or another adjacent module, if applicable. The third support member **5044** includes a domed-out cavity **5044d** and tubing **5044t** through which a vacuum may be applied to draw gas out of the fluid through the degassing membrane **5043m**.

[0129] The second pump module **5050** may correspond to the first pump module **5010**. It preferably includes a first support member **5051**, a diaphragm **5052**, a second support member **5053** with a cut-out center area **5053c**, and a third (end) support member **5054**. The first support member **5051** includes a domed out fluid cavity **5051d** and tubing **5051t** for allowing fluid to exit the pump module. The diaphragm **5052** is preferably a polyurethane bladder.

[0130] The third (end) support piece member **5054** is preferably solid and provides support for the pump module **5050**. Support member **5054** preferably includes a domed out cavity (not shown) for receiving pump fluid. Tubing **5054a** is provided to allow the pump fluid such as air to enter the pump module **5050**. Preferably hemocompatible anti-backflow valves may serve to allow unidirectional flow through the pump module **5050**.

[0131] In operation, blood and/or other medical fluid enters the first pump module **5010** through tube **5014t** passes through the filtration membrane **5021m** and along the degassing membrane **5022m**. A small vacuum is applied through tubing **5023t** to draw gas through the degassing membrane **5022m**. Next, the blood and/or medical fluid travels into the oxygenation module **5030** via internal tubing **5022t**, passing along the degassing membrane **5031m**, through the filtration membrane **5033m** and along the oxygenation membrane **5034m**. Oxygen is received into the domed-out cavity **5035d** of the third support member of the oxygenation module **5030** via tubing **5035t** and passes through the oxygenation membrane **5034m** into the blood and/or other medical fluid as the blood and/or other medical fluid travels along its surface.

[0132] After being oxygenated by the oxygenation module **5030**, the blood and/or other medical fluid then travels via internal tubing **5034t** into the debubbler module **5040**. The blood and/or other medical fluid passes through the filtration membrane **5042m** and along the degassing membrane **5043m**. A small vacuum force is applied through tubing **5044t** to draw gas out of the blood and/or other medical fluid through the degassing membrane **5043m**. After passing through the degassing module **5040**, the blood and/or other medical fluid travels into the second pump module **5050** through tubing **5041t**, and exits the second pump module **5050** via tubing **5051t**.

[0133] After passing through the oxygenator **110**, or alternatively through the combined pump, oxygenation, filtration

and/or degassing apparatus **5001**, the recirculated medical fluid is selectively either directed to the reservoir **15a** or **15b** not in use along tubing **92a** or **92b**, respectively, by activating the respective valve  $LV_2$  and  $LV_5$  on the tubing **92a** or **92b**, or into the organ chamber **40** to supplement the organ bath by activating valve  $LV_1$ . Pressure sensors **P3** and **P4** monitor the pressure of the medical fluid returned to the bag **15a** or **15b** not in use. A mechanical safety valve  $MV_2$  is provided on tubing **91** to allow for emergency manual cut off of flow therethrough. Also, tubing **96** and manual valve  $MV_1$  are provided to allow the apparatus to be drained after use and to operate under a single pass mode in which perfusate exiting the organ is directed to waste rather than being recirculated (recirculation mode.)

[0134] A bicarbonate reservoir **130**, syringe pump **131** and tubing **132**, and an excretion withdrawal unit **120**, in communication with a vacuum (not shown) via vacuum valve  $VV_2$ , and tubing **121a**, **122a** are also each provided adjacent to and in communication with the organ chamber **40**.

[0135] The present invention also provides for perfusion apparatus adapted for organs with complex vasculature structures, such as the liver. Using the liver as an example, **FIG. 26** shows perfusion apparatus **2600**. Perfusion apparatus **2600** has a single pump **2610**, which is preferably a roller pump or peristaltic pump. The tubing splits into two or more directions with, for example, three tubes going toward the portal vein side of the liver (portal tubing **2625**) and one tube going toward the hepatic artery side of the liver (hepatic tubing **2626**). The portal side of perfusion apparatus **2600** has more tubes because the portal side of the liver uses three to ten times the flow that the hepatic side uses. **FIG. 27** shows a perspective view of pump **2610** and the tubing split into portal tubing **2625** and hepatic tubing **2626**.

[0136] Both the portal side and the hepatic side of perfusion apparatus **2600** preferably have a filter **2630**, bubble trap **2640**, pressure transducer **2650**, temperature transducer **2660**, and flow sensor **2670**. An additional temperature transducer **2660** may be present in fluid return tubing **2620**. The organ may be cooled as discussed above, for example by an ice and water bath **2680** or by a cryogenic fluid. In embodiments using cryogenic fluids, the design should be such that organ freezing is prevented.

[0137] Multiple pumps may be used; however, utilizing multiple pumps generally increases the size and cost of the apparatus. Utilizing a single pump **2610** for both vasculature systems provides a variety of modes that can be used to perfuse a liver. After each bubble trap **2640**, the tubing splits into two directions. On the hepatic side, hepatic infusion valve **2685** controls the flow to the hepatic side of the liver and hepatic wash valve **2686** controls the flow into the organ bath. On the portal side, portal infusion valve **2695** controls the flow to the portal side of the liver and portal wash valve **2696** controls the flow into the organ bath. Preferably, each pair of infusion valves and wash valves operates in an on/off or either/or manner. In other words, when, for example, the portal side is set to infuse, the portal wash valve **2696** is closed. The following table shows various modes of operation for perfusion apparatus **2600**.

MODES OF OPERATION	PORTAL VALVES	HEPATIC VALVES	DOMINANT PRESSURE	NOTES
Portal Only	Infuse	Wash	Portal	No hepatic perfusion
Portal Priority	Infuse	Infuse	Portal	Hepatic slave to portal
Hepatic Only	Wash	Infuse	Hepatic	No portal perfusion
Hepatic Priority	Infuse	Infuse	Hepatic	Portal slave to hepatic
Alternating	Infuse	Switching	Alternating	Wavy portal flow; pulsed hepatic flow

[0138] The modes of operation identified in the table above show options for infusing a liver. In the first mode, Portal Only, the portal side of the liver is infused. Therefore, the portal valves are set to infuse, which means that portal infusion valve **2695** is open and portal wash valve **2696** is closed. Also, in a Portal Only mode, hepatic infusion valve **2685** is closed and hepatic wash valve **2686** is open. In a Portal Only mode, the portal pressure is dominant, which means the pressure is controlled by the pressure transducer **2650** on the portal side. In this mode, there is no hepatic infusion.

[0139] In a Portal Priority mode, the portal valves and the hepatic valves are set to infuse. The portal pressure is dominant; and therefore, the hepatic side is a slave to the portal side. In an Alternating mode, the portal valves are set to infuse and the hepatic valves switch between an infuse setting and a wash setting. In an Alternating mode, when the hepatic valves are set to infuse, the hepatic side provides the dominant pressure. When the hepatic valves are set to wash, the portal side provides the dominant pressure. This type of alternating pressure control provides the portal side with a wavy flow and provides the hepatic side with a pulsed flow.

[0140] The present invention also provides an organ diagnostic system **2800** shown in **FIG. 28**. Organ diagnostic system **2800** has a computer **2810** and an analyzer **2820**. Connected to both computer **2810** and analyzer **2820** is an organ evaluation instrument **2830**, also shown in **FIG. 29**. Organ diagnostic system **2800** is preferably provided with suitable displays to show the status of the system and the organ. Organ evaluation instrument **2830** has a perfusate chamber **2840** and an organ chamber **2850**. Connecting analyzer **2820** and organ evaluation instrument **2830** is a transfer line **2860**. Organ diagnostic system **2800** provides analysis of an organ and produces an organ viability index quickly and in a sterile cassette, preferably transferable from perfusion apparatus **1** and/or transporter **1900**. The organ viability index is preferably produced by flow and temperature programmed single-pass perfusion and in-line automatic analysis. The analysis may be performed in a multi-pass system. The multi-pass system will recirculate the flow for analysis while sustaining and evaluating the organ. Flow may be controlled by a valve (not shown) and may recirculate back to the beginning of the system prior to reaching the analyzer **2820**.

[0141] A beneficial aspect of the single-pass system is that it can be configured with a limited number of sensors and

requires only enough perfusate to perform the analysis. Single-pass perfusion also allows for an organ inflow with a perfusate having a known and predetermined chemistry. This increases the flexibility of types and contents of perfusates that may be delivered such as blood or a synthetic blood carrier or a combination thereof, which can be tailored and modified to the particular analysis in process.

[0142] FIG. 29 shows a perspective view of organ evaluation instrument 2830. Organ evaluation instrument 2830 has a perfusate chamber 2840 and an organ chamber 2850. Organ chamber 2850 may be insulated and preferably has a lid 2910 that may be removable or may be hinged. Organ chamber 2850 is preferably configured to receive cassette 65, preferably without opening cassette 65 or jeopardizing the sterility of the interior of cassette 65. Cassette 65 and organ chamber 2850 are preferably constructed to fit or mate such that efficient heat transfer is enabled. The geometric elements of cassette 65 and organ chamber 2850 are preferably constructed such that when cassette 65 is placed within organ chamber 2850, the elements are secure for analysis. A port 2920 is also provided to connect transfer line 2860.

[0143] FIG. 30 shows a single-pass fluid system of organ diagnostic system 2800. The initial perfusion fluids 3000 are contained in a chamber 3010. Chamber 3010 is preferably temperature controlled by a heating and cooling system. Fluid flow within the system is monitored by flow sensor 3020 and controlled by signaling to pinch valves 3030 and pumps 3040. The fluid system also provides a bubble trap 3050, a pressure transducer 3060 and a temperature transducer 3070. Heat exchanger 3080 provides temperature control and heating and cooling to the fluid within the system prior to organ perfusion. The organ is perfused in cassette 65. The fluid in the organ bath may be collected, or the venous outflow may be captured, to be analyzed. The fluid is collected and passed via transfer line 2860 to analyzer 2820. Transfer line 2860 may also be provided with a separate heating and cooling unit. After the fluid is analyzed, it may be collected in a waste receptacle 3090.

[0144] FIG. 31 shows a logic circuit for organ diagnostic system 2800. The computer provides control parameters and receives results and data from the analyzer. The logic circuit shows inputs from the sensors to the microcontroller and outputs to hardware elements, such as perfusate coolers, perfusate heaters, pinch valves, pumps, transferline heater/cooler and displays.

[0145] The method according to the invention preferably utilizes apparatus such as that discussed above to perfuse an organ to sustain, monitor and/or restore the viability of an organ and/or to transport and/or store the organ. Preservation of the viability of an organ is important to a successful organ transplant or other use of the organ. Organs are often deprived of oxygen (known as ischemia) for extended periods of time due to disease or injury to the donor body, during removal of the organ from the donor body and/or during storage and/or transport of the organ. The perfusion, diagnostic, and/or transporter apparatus of the present invention have the ability to detect the cell chemistry of an organ to be transplanted in order to adjust the perfusate and control the cellular metabolism to repair ischemic damage to the organ and to prevent reperfusion injury. One specific outcome of ischemic injury may be apoptosis or programmed

cell death. Specific agents and additives provided to an organ by the perfusion, diagnostic and/or transporter apparatus, under conditions controlled by the particular apparatus, may interrupt, decrease and/or reverse apoptosis.

[0146] In preferred methods of the present invention, an organ or tissue is treated ex vivo by mechanical, physical, chemical or genetic manipulation and/or modification to treat disease and/or treat damage to and/or enhance the properties of the organ or tissue. An organ or tissue sample may be removed from a first body, modified, treated and/or analyzed outside the first body and returned to the first body or transplanted to a second body or otherwise used. An advantage of the apparatus is that it enlarges the time that an organ may be available for ex vivo treatment, e.g., for hours (e.g. 2, 4, 6, 8, 10, 12 or more hours) or even days (e.g. 2, 4, 6, 8, 10, 12 or more days) or weeks (e.g. 1, 2, 3, 4, 5, 6, 7, 8 or more weeks). In preferred embodiments, the perfusion, diagnostic and/or transporter apparatus of the present invention may be used to provide particular solutions or chemicals or agents to an organ or tissue or may be used to perform particular treatments including flushing or washing an organ or tissue with particular solutions or chemicals. Ex vivo treatments may be performed on tissue or an organ to be transplanted, may be performed on tissue or an organ that has been removed from a patient and is to be returned to the patient after the desired procedure is performed, or may be performed on tissue or an organ that is to be used in substance testing or the like. Ex vivo treatments include but are not limited to treatment of tissue or an organ that has endured a period or periods of ischemia and/or apoxia. Ex vivo treatments may involve performing surgical techniques on an organ, such as cutting and suturing an organ, for example to remove necrotic tissue. Any surgical or other treatment technique that may be performed on tissue or an organ in vivo may also be performed on tissue or an organ ex vivo. The benefit of such ex vivo treatment may be seen, for example, in the application of radiation or chemotherapy to treat a tumor present in or on an organ, to prevent other portions of the patient from being subjected to extraneous radiation or chemotherapy during treatment. The perfusion and transporter apparatus of the present invention also provide additional time for a physician to maintain the tissue or organ before, during and/or after performing a particular technique on the tissue or organ.

[0147] Particles trapped in an organ's vasculature may prevent the organ from perfusing properly, or may cause the organ to function improperly, before and/or after transplantation. Perfusion, diagnostic and transporter apparatus of the invention provide ex vivo techniques include perfusing, flushing or washing an organ with suitable amounts of a thrombolytic agent, such as streptokinase, to dissolve blood clots that have formed or to prevent the formation of blood clots in an organ and to open the vasculature of the organ. Such techniques are disclosed, for example, in U.S. patent application Ser. No. 09/938,597, filed Aug. 25, 2000, Attorney Docket No. 106996, the entire disclosure of which is hereby incorporated by reference.

[0148] Another concern with organ transplantation is the degree to which a recipient may be medicated to prevent organ rejection. In organ transplantation, a further ex vivo technique involves modifying the organ to avoid having it activate the immune system of the donee to prevent or reduce organ rejection and to limit or prevent the need to

suppress the donee's immune system before, during and/or after organ transplantation so as to increase the tolerance of the donee to the transplanted organ. Modifications of an organ may, for example, encourage the donee body to recognize the transplanted organ as autologous.

[0149] The perfusion, diagnostic and/or transporter apparatus of the present invention may deliver substances such as chemical compounds, natural or modified antibodies, immunotoxins or the like, to an organ and may assist the organ to adsorb, absorb or metabolize such substances to increase the likelihood that the organ will not be rejected. These substances may also mask the organ by blocking, killing, depleting and/or preventing the maturation of allostimulatory cells (dendritic cells, passenger leukocytes, antigen presenting cells, etc.) so that the recipient's immune system does not recognize it or otherwise recognizes the organ as autologous. An organ may be treated just prior to transplantation or may be pretreated hours, days or weeks before transplantation. Such techniques are further described in U.S. Provisional Patent Application No. 60/227,841, filed Aug. 25, 2000, Attorney Docket No. 100034, the entire disclosure of which is hereby incorporated by reference.

[0150] Substances, such as modified or unmodified immunoglobulin, steroids and/or a solution containing polyethylene glycol (PEG) and an antioxidant such as glutathione, may also be provided to an organ or tissue to mask the organ or to treat the onset of intimal hyperplasia during cryopreservation and/or organ or tissue transplantation. These solutions may be provided to an organ or tissue by perfusion, diagnostic and/or transporter apparatus of the invention. Exemplary such solutions and methods are disclosed in U.S. patent application Ser. No. 09/499,520, the entire disclosure of which is hereby incorporated by reference.

[0151] As discussed above, the present invention involves avoiding damage to an organ during perfusion while monitoring, sustaining and/or restoring the viability of the organ and preserving the organ for storage and/or transport. However, not all organs that are donated and perfused according to the exemplary embodiments discussed above, are ultimately transplanted in a donee. After careful analysis, a determination might be made that the organ might not be suitable for transplanting. The organ, however, should not be unnecessarily discarded. That is, that same organ determined not to be suitable for transplantation may serve another purpose.

[0152] According to further exemplary embodiments of this invention, the organ may be perfused with medical fluids for the purpose of screening bioactive or other test agents and providing data for research and development. Since the organ or tissue may be maintained and/or analyzed at or near physiologic parameters, an organ may be tested for the effects of various treatments using substances such as bioactive agents or drugs, on the organ or tissue, ex vivo. The ex vivo treatment can be utilized for organs of small mammals, large mammals including livestock animals such as cattle, pigs, sheep, and goats, and/or humans. Further, the ex vivo treatment of organs may be used for various organs, such as the kidneys, gut, pancreas, heart and lungs, and may be adapted to more complex organs, such as the liver, having multiple vasculature structures, for example, the hepatic and portal vasculatures of the liver.

[0153] The perfusion, diagnostic and transporter apparatus of the invention may be used in conjunction with the above

techniques and methods and/or in conjunction with further techniques and methods, to perform research on an organ or tissue. The various apparatus may preserve and/or maintain the organ and allow the organ to be available for ex vivo use.

[0154] During the period in which the organ is preserved and/or maintained, various activities may be performed on and/or with the organ. For example, the organ, or multiple organs simultaneously, may be perfused with a fluid containing a substance, such as one or more bioactive agents or other (e.g. putatively inert agents) to obtain data regarding the behavior of the substance and/or the organ and/or the interaction between the substance and the organ.

[0155] The perfusion, diagnostic and/or transporter apparatus may be used to gather data by perfusing blood, a synthetic blood substitute or a combination thereof, or blood cells mixed with a perfusate having known or unknown chemical properties, through an organ while monitoring the organ, organ vascular outflow or other organ outflow, to perform research and to analyze the condition of the organ and/or to determine the effect on the organ by screening with the substance. It

[0156] For example, as discussed with respect to FIGS. 28-31 of the present invention, the organ diagnostic system 2800 has a computer 2810 and an analyzer 2820. Connected to both computer 2810 and analyzer 2820 is an organ evaluation instrument 2830 to provide automatic sampling. The systems and method of the invention allow for manual sampling. The organ diagnostic system 2800 provides analysis of an organ and the perfusate. According to embodiments of this invention, perfusion of the organ allows for an organ inflow with a perfusate having a known and predetermined chemistry. This increases the flexibility of types and contents of perfusates that may be delivered such as blood or a synthetic blood carrier or a combination thereof, which may be tailored and/or modified to the particular analysis in process.

[0157] Fluid flow within the system is monitored by flow sensor 3020. The fluid is collected and passed via transfer line 2860 to analyzer 2820. The sensed characteristics may be measured by capturing any measurable outflow of the organ, such as venous, bile, intraluminal, and urine outflow, and airway measurements from organs such as the lungs and comparing the sensed characteristics, for example, to characteristics of the inflow or of other actual or idealized organs. The venous outflow may be captured directly and measured or the organ bath may be measured to provide a rough approximation of the fluid characteristics for comparisons.

[0158] As discussed above, the organ and medical fluid characteristics may optionally be analyzed, for example, in a separate diagnostic apparatus and/or analyzer as shown in FIGS. 28-31. The sensed characteristics provide researchers a determination of how much of a test substance went into the organ and how much came out. Further, the test substance can be labeled with radioisotopes to help track it and its interaction, if any, with the organ. The radioisotopes can be tracked with instruments such as a mass spectrometer. The result of such sensed characteristics may allow the researcher to analyze organ screening results such as absorption, distribution, metabolism, excretion, pharmacokinetics, pharmacodynamics and toxicity may be used to provide data, for example, for drug development in which the data

ultimately may help determine drug efficacy and/or toxicity. The sensed characteristics may be analyzed individually or multiple characteristics may be analyzed to determine the effect upon and/or interaction between the medical fluid containing a substance and the organ.

[0159] While, as discussed above, the organ diagnostic system 2800 analyzes the organ and/or the perfusate and/or the interaction there between, data may be generated regarding the outcome of the analysis. As discussed above, FIG. 31 shows a logic circuit for organ diagnostic system 2800. The computer provides control parameters and receives results and data from the analyzer 2820. The computer further controls features of the present invention such as auto sampling, control over maintenance of sampling and other quality assurance features. Data gathered in accordance with embodiments of the invention provide for efficiency in gathering of data regarding for example, absorption, distribution, metabolism and excretion (ADME). The data can be generated and displayed in real time, stored, transmitted to a remote site, and/or transferred to a recording medium. Gathering of this type of data allows for scientists and researchers to determine what the substance is doing to the organ and conversely, what the organ is doing to the substance. With this data, researchers are able to contribute to a more effective and safe research process and analyze substances and their effects, if any, on organs prior to testing of such substances on a whole animal level. Additionally, data that may be determined according to the various exemplary embodiments discussed above, includes data relating to presystemic elimination, absorption and drug delivery, pharmacokinetics and metabolism, pharmacodynamics, toxicokinetics, drug-drug interactions, and the like. It is within the spirit and scope of the present invention that the various exemplary embodiments of this invention allow for the gathering of any data relating to the substances, the organ, and the interaction therebetween.

[0160] Various data structures and information connections and analysis sub records can be facilitated to assist in the overall communication and data transfers that may be beneficial before, during and after treatment of an organ. The perfusion apparatus, transporter, and organ diagnostic apparatus may be networked to permit remote management and monitoring of the organ, medical fluids and test substances. The information systems may be used to compile data of the organ, the medical fluid, the test substance, and the interaction therebetween. The systems may also be used for compiling data regarding chemical cleanliness and chemical integrity of the systems themselves and providing information regarding trace amounts of chemical in the system. The systems may also provide outcome data to allow for ready research of organ and medical fluid and substance, and information may also be directly recovered from the perfusion, diagnostic or transporter apparatus to monitor such data. Various types of data and information may be grouped into sub-records or sub-directories to assist in data management and transfer. All the sub-records may be combined to form an overall record, which may be disseminated to or retrievable by physicians, scientists or other organizations for research purposes.

[0161] Preferred embodiments of the perfusion, diagnostic and transporter can automatically log much or all of the data into an internal database. The apparatus may also be connected to a LAN and data uploads can occur intermittently

or continuously and in real-time. Data may be displayed and accessed on the internet to facilitate monitoring from any location.

[0162] According to exemplary embodiments, an organ data index is generated taking into account the various measured and analyzed factors identified above. The data index may be organ specific, or may be adaptable to various organs. The data index compiles the sensed characteristics and data into a diagnostic summary to be used for making organ treatment and research decisions. The data index may be automatically generated and provided to the researcher or physician. The index is preferably computer generated via a connection to the perfusion apparatus, transporter, and/or organ diagnostic apparatus. In embodiments, the index may be made available over a computer network such as a local area network or the internet for quick comparison, remote analysis and data storage. The organ data index may provide measurements and normal ranges for each characteristic, such as for absorption, distribution, metabolism, excretion, pharmacokinetics, pharmacodynamics and toxicity. Measurements that are outside the normal range may be indicated visually, e.g., by an asterisk or other suitable visible notation, aurally or by machine perceivable signals. The characteristics give the physician or researcher insight into effects such as the metabolism of the organ, such as stability of the metabolism, consumption of glucose, creation of lactic acid and oxygen consumption.

[0163] The methods according to the invention preferably utilize apparatus such as that discussed above to perfuse an organ to sustain, monitor and/or restore the viability of an organ and/or to transport and/or store the organ. Organs are often deprived of oxygen (known as ischemia) for extended periods of time due to disease or injury to the donor body, during removal of the organ from the donor body and/or during storage and/or transport. The perfusion, diagnostic, and/or transporter apparatus of the present invention have the ability to detect the cell chemistry of an organ in order to adjust the perfusate and control the cellular metabolism to repair ischemic damage to the organ and to prevent reperfusion injury. One specific outcome of ischemic injury may be apoptosis or programmed cell death. Specific agents and additives provided to an organ by the perfusion, diagnostic and/or transporter apparatus, under conditions controlled by the particular apparatus, may interrupt, decrease and/or reverse apoptosis.

[0164] Preferred methods according to the present invention focus on three concepts in order to preserve an organ's viability prior to transplant of the organ into a donee body, or prior to use of the organ for research and development: treating the cellular mitochondria to maintain and/or restore pre-ischemia energy and enzyme levels, preventing general tissue damage to the organ, and preventing the washing away of or damage to the vascular endothelial lining of the organ.

[0165] The mitochondria are the energy source in cells. They need large amounts of oxygen to function. When deprived of oxygen, their capacity to produce energy is reduced or inhibited. Additionally, at temperatures below 20° C. the mitochondria are unable to utilize oxygen to produce energy. By perfusing the organ with an oxygen rich medical fluid at normothermic temperatures, the mitochondria are provided with sufficient amounts of oxygen so that

pre-ischemia levels of reserve high energy nucleotide, that is, ATP levels, in the organ reduced by the lack of oxygen are maintained and/or restored along with levels of enzymes that protect the organ's cells from free radical scavengers. Pyruvate rich solutions, such as that disclosed in U.S. Pat. No. 5,066,578, are incapable of maintaining and/or restoring an organ's pre-ischemia energy levels and only function in the short term to raise the level of ATP a small amount. That is, organs naturally have significant pyruvate levels. Providing an organ with additional pyruvate will not assist in restoring and/or maintaining the organ's pre-ischemia energy levels if the mitochondria are not provided with sufficient oxygen to produce energy. Thus, the normothermic perfusion fluid may contain pyruvate but may also contain little or no pyruvate. For example, it can contain less than 6 mM of pyruvate, 5 mM, 4 mM, or even no pyruvate. Other known preservation solutions, such as that disclosed in U.S. Pat. No. 5,599,659, also fail to contain sufficient oxygen to restore and/or maintain pre-ischemia energy and enzyme levels.

[0166] After maintaining and/or restoring the organ's pre-ischemia energy levels by perfusing the organ with an oxygen rich first medical fluid at normothermic or near-normothermic temperatures (the normothermic mode), the organ may be perfused with a second medical fluid at hypothermic temperatures (the hypothermic mode). The hypothermic temperatures slow the organ's metabolism and conserve energy during storage and/or transport of the organ. The medical fluid utilized in the hypothermic mode contains little or no oxygen, which cannot be utilized by mitochondria to produce energy below approximately 20° C. The medical fluid may include antioxidants and other tissue protecting agents, such as, for example, ascorbic acid, glutathione, water soluble vitamin E, catalase, or superoxide dismutase to protect against high free radical formation which occurs at low temperatures due to the reduction in catalase/superoxide dismutase production. Further, various drugs and agents such as hormones, vitamins, nutrients, antibiotics and others may be added to either solution where appropriate. Additionally, vasodilators, such as, for example, peptides, may be added to the medical fluid to maintain flow even in condition of injury.

[0167] Prior to any normothermic perfusion with the oxygen rich first medical fluid at normothermic temperatures, the organ may be flushed with a medical solution containing little or no oxygen and preferably containing antioxidants. The flushing is usually performed at hypothermic temperatures but can, if desired and/or as necessary, be performed at normothermic or near-normothermic temperatures. Flushing can be followed by one or more of hypothermic perfusion, normothermic perfusion, and/or static storage, in any necessary and/or desired order. In some cases, normothermic perfusion or hypothermic perfusion may not be necessary.

[0168] The normothermic perfusion, with or without prior hypothermic flushing, may also be performed on an organ that has already been subjected to hypothermic temperatures under static or perfusion conditions, as well as on normothermic organs.

[0169] The organ may be perfused at normothermic or near-normothermic temperatures to sustain, monitor and/or restore its viability prior and/or subsequent to being perfused at hypothermic temperatures for storage and then may be transported without or preferably with hypothermic perfu-

sion. Also, the normothermic perfusion may be performed in vivo prior to removal of the organ from the donor body. Further, the organ may be perfused at normothermic temperatures to sustain, monitor and/or restore its viability prior to being perfused at hypothermic temperatures preparatory to storage and/or transport. Then the organ may be transplanted into a donee body or used for other research while remaining at hypothermic temperatures, or it may first be subjected to normothermic perfusion to help it recover from the effects of storage and/or transport. In the latter case, it may then be transplanted or used at normothermic temperatures, or preferably, be hypothermically perfused again for transplantation at hypothermic temperatures. After transplant, the organ may optionally again be perfused at normothermic temperatures in vivo, or allowed to warm up from the circulation of the donee. Substance research is preferably conducted at normothermic temperatures. Further, it is preferable to conduct substance testing in conditions that are close to normal physiological conditions. For example, temperature, oxygen levels, and the like.

[0170] By way of example only, and without being limited thereto, FIG. 16 shows an exemplary diagram of possible processing steps according to the invention. The Figure shows various possible processing steps of multiple organ recovery (MOR) from organ explant from the organ donor through implant in the donee (or other use), including possible WIT (warm ischemia time) and hypoxia damage assessment. Several exemplary scenarios are set forth in the following discussion.

[0171] For example, in one embodiment of the present invention, the organ can be harvested from the donor under beating heart conditions. Following harvesting, the organ can be flushed, such as with any suitable solution or material including, but not limited to VIASPAN (a preservation solution available from DuPont), other crystalloid solution, dextran, HES (hydroxyethyl starch), solutions described in U.S. patent application Ser. No. 09/628,311, filed Jul. 28, 2000, the entire disclosure of which is hereby incorporated by reference, or the like. The organ can then be stored statically, for example, at ice temperatures (for example of from about 1 to about 10° C.).

[0172] In another embodiment, such as where the organ has minimal WIT and minimal vascular occlusion, a different procedure can be used. Here, the organ can again be harvested under beating heart conditions, followed by flushing, preferably at hypothermic temperatures. If necessary, the organ can be stored in a suitable transporter at, for example, ice temperatures. Flow to the organ can be controlled by a set pressure maximum, where preset pressure minimum and pressure maximum values control the pulse wave configuration. If necessary to store the organ for a longer period of time, such as for greater than 24 hours, the organ can be placed in the MOR. In the MOR, a suitable perfusate can be used, such as a crystalloid solution, dextran or the like, and preferably at hypothermic temperatures. Preferably, the hypothermic temperatures are from about 4 to about 10° C., but higher or lower temperatures can be used, as desired and/or necessary. Preferably, the perfusate solution contains specific markers to allow for damage assessment, although damage assessment can also be made by other known procedures. When desired, the organ can then be returned to the transporter.



[0173] As a variation of the above procedure, an organ having minimal WIT and minimal vascular occlusion can be harvested under non-beating heart conditions. Here, the organ can be flushed, preferably at hypothermic temperatures and, if necessary, stored for transport in a suitable transporter at, for example, ice temperatures. As above, flow to the organ can be controlled by a set pressure maximum, where preset pressure minimum and pressure maximum values control the pulse wave configuration. The organ can be placed in the MOR, either for extended storage and/or for damage assessment and/or repair. In the MOR, a suitable perfusate can be used, such as a crystalloid solution, dextran or the like, and preferably at hypothermic temperatures. Preferably, the hypothermic temperatures are from about 4 to about 10° C., but higher or lower temperatures can be used, as desired and/or necessary. Preferably, the perfusate solution contains specific markers to allow for damage assessment, although damage assessment can also be made by other known procedures. Following hypothermic perfusion, a second perfusion can be utilized, preferably at normothermic temperatures. Any suitable perfusion solution can be used for this process, including solutions that contain, as desired, oxygenated media, nutrients, and/or growth factors. Preferably, the normothermic temperatures are from about 12 to about 24° C., but higher or lower temperatures, including about 37° C. can be used, as desired and/or necessary. The normothermic perfusion can be conducted for any suitable period of time, for example, for from about 1 hour to about 24 hours. Following recovery from the normothermic perfusion, the organ is preferably returned to a hypothermic perfusion using, for example, a suitable solution such as a crystalloid solution, dextran or the like, and preferably at hypothermic temperatures. When desired, the organ can then be returned to the transporter.

[0174] In embodiments where the organ has high WIT, and/or where there is a high likelihood of or actual vascular occlusion, variations on the above processes can be used. For example, in the case where the organ is harvested under non-beating heart conditions, the organ can be flushed as described above. In addition, however, free radical scavengers can be added to the flush solution, if desired. As above, the organ can be stored for transport in a suitable transporter at, for example, ice temperatures, where flow to the organ can be controlled by a set pressure maximum, and where preset pressure minimum and pressure maximum values control the pulse wave configuration. The organ can be placed in the MOR, either for extended storage and/or for damage assessment and/or repair. In the MOR, a suitable perfusate can be used, such as a crystalloid solution, dextran or the like, and preferably at hypothermic temperatures. Preferably, the hypothermic temperatures are from about 4 to about 10° C., but higher or lower temperatures can be used, as desired and/or necessary. Preferably, the perfusate solution contains specific markers to allow for damage assessment, although damage assessment can also be made by other known procedures. Following hypothermic perfusion, a second perfusion can be utilized, preferably at normothermic temperatures. Any suitable perfusion solution can be used for this process, including solutions that contain, as desired, oxygenated media, nutrients, and/or growth factors. Preferably, the normothermic temperatures are from about 12 to about 24° C., but higher or lower temperatures can be used, as desired and/or necessary. The normothermic perfusion can be conducted for any suitable period of time,

for example, for from about 1 hour to about 24 hours. If desired, and particularly in the event that vascular occlusion is determined or assumed to be present, a further perfusion can be conducted at higher normothermic temperatures, for example of from about 24 to about 37° C. This further perfusion can be conducted using a suitable solution that contains a desired material to retard the vascular occlusion. Such materials include, for example, clotbusters such as streptokinase. Following recovery from the normothermic perfusion(s), the organ may be returned to a hypothermic perfusion using, for example, a suitable solution such as a crystalloid solution, dextran or the like, and preferably at hypothermic temperatures. When desired, the organ can then be returned to the transporter.

[0175] The organ cassette according to the present invention allows an organ(s) to be easily transported to an organ recipient and/or between organ perfusion, diagnostic and/or portable transporter apparatus, such as, for example, transporter 1900 described above or a conventional cooler or a portable container such as that disclosed in co-pending U.S. application Ser. No. 09/161,919. Because the organ cassette may be provided with openings to allow the insertion of tubing of an organ perfusion, transporter or diagnostic apparatus into the cassette for connection to an organ disposed therein, or may be provided with its own tubing and connection device or devices to allow connection to tubing from an organ perfusion, transporter or diagnostic apparatus and/or also with its own valve, it provides a protective environment for an organ for storage, analysis and/or transport while facilitating insertion of the organ into and/or connection of an organ to the tubing of an organ perfusion, transporter or diagnostic device. Further, the organ cassette may also include a handle to facilitate transport of the cassette and may be formed of a transparent material so the organ may be visually monitored.

[0176] Optionally, transporter 1900 and/or cassette 65 may include a Global Positioning System (GPS) (not shown) to allow tracking of the location of the organ(s). The apparatus may also include a data logger and/or transmitter (not shown) to allow monitoring of the organ(s) at the location of the apparatus or at another location.

[0177] The method of the invention will be discussed below in terms of the operation of the apparatus shown in FIG. 2. However, other apparatus may be used to perform the inventive method.

[0178] As previously discussed, the apparatus discussed above can operate in two modes: a normothermic perfusion mode and a hypothermic perfusion mode. The normothermic perfusion mode will be discussed first followed by a discussion of hypothermic perfusion mode. Repetitive description will be omitted as much as possible.

[0179] In the normothermic or near-normothermic perfusion mode, an organ is perfused for preferably ½ to 6 hours, more preferably ½ to 4 hours, most preferably ½ to 1 hour, with a medical fluid maintained preferably within a range of approximately 10° C. to 38° C., more preferably 12° C. to 35° C., most preferably 12° C. to 24° C. or 18° C. to 24° C. (for example, room temperature 22-23° C.) by the thermoelectric unit 30a disposed in heat exchange communication with the medical fluid reservoir 10.

[0180] As discussed above, in this mode, the medical fluid is preferably an oxygenated cross-linked hemoglobin-based

bicarbonate solution. Cross-linked hemoglobin-based medical fluids can deliver up to 150 times more oxygen to an organ per perfusate volume than, for example, a simple University of Wisconsin (UW) gluconate type perfusate. This allows normothermic perfusion for one to two hours to partially or totally restore depleted ATP levels. However, the invention is not limited to this preservation solution. Other preservation solutions, such as those disclosed in U.S. Pat. Nos. 5,149,321, 5,234,405 and 5,395,314 and co-pending U.S. patent applications Ser. Nos. 08/484,601 and U.S. patent application Ser. No. 09/628,311, filed Jul. 28, 2000, Attorney Docket No. 101311, the entire disclosures of which are hereby incorporated by reference, may also be appropriate.

[0181] In the normothermic perfusion mode, the medical fluid is fed directly to an organ disposed within the organ chamber 40 from one or the other of bags 15a, 15b via tubing 50a, 50b, 50c or 50d, 50e, 50c, respectively. The organ is perfused at flow rates preferably within a range of approximately 3 to 5 ml/gram/min. Pressure sensor P1 relays the perfusion pressure to the microprocessor 150, which varies the pressure supplied by the pressure source 20 to control the perfusion pressure and/or displays the pressure on the control and display areas 5a for manual adjustment. The pressure is preferably controlled within a range of approximately 10 to 100 mm Hg, preferably 50 to 90 mm Hg, by the combination of the pressure source 20 and pressure cuff 15a, 15b in use and the stepping motor/cam valve 65. The compressor and cuffs provide gross pressure control. The stepping motor/cam valve 65 (or other variable valve or pressure regulator), which is also controlled by the operator, or by the microprocessor 150 in response to signals from the pressure sensor P1, further reduces and fine tunes the pressure and/or puts a pulse wave on the flow into the organ 60. If the perfusion pressure exceeds a predetermined limit, the stepping motor/cam valve 65 may be activated to shut off fluid flow to the organ 60.

[0182] The specific pressures, flow rates and length of perfusion time at the particular temperatures will vary depending on the particular organ or organs being perfused. For example, hearts and kidneys are preferably perfused at a pressure of approximately 10 to 100 mm Hg and a flow rate of approximately 3 to 5 ml/gram/min. for up to approximately 2 to 4 hours at normothermic temperatures to maintain and/or restore the viability of the organ by restoring and/or maintaining pre-ischemia energy levels of the organ, and are then preferably perfused at a pressure of approximately 10 to 30 mm Hg and a flow rate of approximately 1 to 2 ml/gram/min. for as long as approximately 72 hours to 7 days at hypothermic temperatures for storage and/or transport. However, these criteria will vary depending on the condition of the particular organ, the donor body and/or the donee body, the intended use, and/or on the size of the particular organ. One of ordinary skill in the art can select appropriate conditions without undue experimentation in view of the guidance set forth herein.

[0183] Effluent medical fluid collects in the bottom of the organ chamber 40 and is maintained within the stated temperature range by the second thermoelectric unit 30b. The temperature sensor T2 relays the organ temperature to the microprocessor 150, which controls the thermoelectric unit 30a to adjust the temperature of the medical fluid and organ bath to maintain the organ 60 at the desired tempera-

ture, and/or displays the temperature on the control and display areas 5c for manual adjustment.

[0184] Collected effluent medical fluid is pumped out by the pump 80 via tubing 81 through the filter unit 82 and then returned to the organ bath. This filters out surgical and/or cellular debris from the effluent medical fluid and then returns filtered medical fluid to act as the bath for the organ 60. Once the level sensor L2 senses that a predetermined level of effluent medical fluid is present in the organ chamber 40 (preferably enough to maintain the organ 60 immersed in effluent medical fluid), additional effluent medical fluid is pumped out by the pump 90 through tubing 91. The temperature sensor T1 relays the temperature of the organ bath to the microprocessor 150, which controls the thermoelectric unit 30b to adjust the temperature of the medical fluid to maintain the organ 60 at the desired temperature and/or displays the temperature on the control and display area 5c for manual adjustment and monitoring.

[0185] As noted above, the medical fluid can be directed to waste in a single pass mode or recirculated eventually back to the organ and/or bath (recirculation mode.)

[0186] Along tubing 91, the recirculated medical fluid is first pumped through the filter unit 95. Use of a cross-linked hemoglobin medical fluid allows the use of sub-micron filtration to remove large surgical debris and cellular debris, as well as bacteria. This allows the use of minimal antibiotic levels, aiding in preventing organ damage such as renal damage.

[0187] Next, the recirculated medical fluid is pumped through the CO<sub>2</sub> scrubber/O<sub>2</sub> membrane 100. The medical fluid passes over the hydrophobic macroporous membrane with a hydrophilic coating (for example, Hypol) and a low vacuum is applied on the opposite side by activating valve VV<sub>1</sub> which removes CO<sub>2</sub> from the recirculated medical fluid.

[0188] Subsequently, a portion of the medical fluid then enters the oxygenator 110 (for example, a JOSTRA™ oxygenator) and a portion is diverted therearound passing via tubing 111 through the pH, pO<sub>2</sub>, pCO<sub>2</sub>, LDH, T/GST and Tprotein sensor V1. At this point two gases, preferably 100% oxygen and 95/5% oxygen/carbon dioxide, are respectively placed on the opposite sides of the membrane depending on the pH level of the diverted medical fluid. The gases are applied at a pressure of up to 200 mm Hg, preferably 50 to 100 mm Hg, preferably through a micrometer gas valve GV<sub>3</sub>. The cross-linked hemoglobin-based bicarbonate medical fluid may be formulated to require a pCO<sub>2</sub> of approximately 40 mm Hg to be at the mid point (7.35) of a preferred pH range of 7.25-7.45.

[0189] If the medical fluid exiting the oxygenator is within the preferred pH range (e.g., 7.25-7.45), 100% oxygen is delivered to the gas exchange chamber, and valve LV<sub>1</sub> is then not opened, allowing the perfusate to return to the reservoir 10 into the bag 15a or 15b not in use. If the returning perfusate pH is outside the range on the acidic side (e.g., less than 7.25), 100% oxygen is delivered to the gas exchange chamber and valve LV<sub>1</sub> is then opened allowing the perfusate to return to the organ chamber 40. Actuation of syringe pump 131 pumps, for example, one cc of a bicarbonate solution from the bicarbonate reservoir 130, via tubing 132 into the organ bath. Medical fluids with high

hemoglobin content provide significant buffering capacity. The addition of bicarbonate aids in buffering capacity and providing a reversible pH control mechanism.

[0190] If the returning perfusate pH is outside the range on the basic side (e.g., greater than 7.25), 95/5% oxygen/carbon dioxide is delivered to the gas exchange chamber and valve LV<sub>1</sub> is not actuated, allowing the perfusate to return to the bag 15a or 15b not in use. The bag 15a or 15b not in use is allowed to degas (e.g., any excess oxygen) through valve GV<sub>4</sub>. When the bag 15a or 15b in use has approximately 250 ml or less of medical fluid remaining therein, its respective cuff 16a, 16b is allowed to vent via its respective gas valve GV<sub>1</sub>, GV<sub>2</sub>. Then, the respective cuff 16a, 16b of the bag 15a or 15b previously not in use is supplied with gas from the compressed gas source 20 to deliver medical fluid to the organ to continue perfusion of the organ.

[0191] In the hypothermic mode, an organ is perfused with a cooled medical fluid, preferably at a temperature within a range of approximately 1° C. to 15° C., more preferably 4° C. to 10° C., most preferably around 10° C. The medical fluid is preferably a crystalloid perfusate without oxygenation and preferably supplemented with antioxidants and other tissue protecting agents, such as, for example, ascorbic acid, glutathione, water soluble vitamin E, catalase, or superoxide dismutase.

[0192] Instead of feeding the medical fluid directly to the organ, the medical fluid may be fed from the reservoir tank 17 via tubing 51 into an intermediary tank 70 preferably having a pressure head of approximately 5 to 40 mm Hg, more preferably 10 to 30 mm Hg, most preferably around 20 mm Hg. Medical fluid is then fed by gravity or, preferably, pressure, from the intermediary tank 70 to the organ 60 along tubing 50c by activating a valve LV<sub>6</sub>. The level sensor 71 in the intermediary tank 70 is used to control the feed from reservoir tank 17 to maintain the desired pressure head. Because the medical fluid is fed to the organ by gravity or, preferably, pressure, in the hypothermic mode, there is less perfusion pressure induced damage to the delicate microvasculature of the organ. In fact, the pressure at which the organ is perfused is limited by the pressure head to at most 40 mm Hg.

[0193] The stepping motor/cam valve 205 (or other variable valve or pressure regulator) may be arranged on the tubing 50c to provide pulsatile delivery of the medical fluid to the organ 60, to decrease the pressure of the medical fluid fed into the organ 60 for control purposes, or to stop flow of medical fluid into the organ 60, as described above.

[0194] Further, in the hypothermic mode, because the organ 60 has less of a demand for nutrients, the medical fluid may be provided to the organ 60 intermittently (e.g., every two hours at a flow rate of up to approximately 100 ml/min.), or at a slow continuous flow rate (e.g., up to approximately 100 ml/min.) over a long period of time. Intermittent perfusion can be implemented in the single pass mode or recirculation mode. The pump 80, filter unit 82 and tube 81 may be used to filter the organ bath along with use of the pH, pO<sub>2</sub>, pCO<sub>2</sub>, LDH, T/GST and Tprotein sensor; however, because the organ is unable to utilize oxygen at hypothermic temperatures, the oxygenator is not used. If desired and/or necessary, adequate oxygen can be obtained from filtered room air or other suitable source.

[0195] Both the perfusate flow and the temperature regulation can be automatically controlled. Such automatic con-

trol allows a rapid and reliable response to perfusion conditions during operation. Automatic flow control can be based on the parameters measured from the system, including the perfusate flow rate, the perfusate pH exiting the organ, the organ inlet pressure or timed sequences such as pre-selected flow rates or switching between perfusate modes. Preferably, the flow control is based on pressure monitoring of the perfusate inflow into the organ. The benefits of automatic flow control include maintaining proper oxygenation and pH control while operating under continuous flow or controlled intermittent flow. Thermal control of the thermoelectric devices (TED) can regulate the temperature of the organ cassette or container and the perfusate reservoir. The thermal control is based on thermal measurements made for example by thermistor probes in the perfusate solution or inside the organ or by sensors in the TED.

[0196] The automatic control is preferably effected by an interactive control program using easily operated menu icons and displays. The parameters may be prestored for selection by a user or programmed by the user during operation of the system. The control program is preferably implemented on a programmed general purpose computer. However, the controller can also be implemented on a special purpose computer, a programmed microprocessor or microcontroller and peripheral integrated circuit elements, an ASIC or other integrated circuit, a digital signal processor, a hardwired electronic or logic circuit such as a discrete element circuit, a programmable logic device such as a PLD, PLA, FPGA or PAL, or the like. In general, any device capable of implementing a finite state machine that is in turn capable of implementing the control process described herein may be used. The control program is preferably implemented using a ROM. However, it may also be implemented using a PROM, an EPROM, an EEPROM, an optical ROM disk, such as a CD-ROM or DVD-ROM, and disk drive or the like. However, if desired, the control program may be employed using static or dynamic RAM. It may also be implemented using a floppy disk and disk drive, a writable optical disk and disk drive, a hard drive, flash memory or the like.

[0197] In operation, as seen in FIG. 15, the basic steps of operation to control perfusion of one or more organs include first inputting organ data. The organ data includes at least the type of organ and the mass. Then, the program will prompt the user to select one or more types of perfusion modes. The types of perfusion modes, discussed above, include hypothermic perfusion, normothermic perfusion, and sequential perfusion using both normothermic and hypothermic perfusion. When both normothermic and hypothermic perfusion are employed, the user can select between medical fluids at different temperatures. Of course, the system includes default values based on previously stored values appropriate for the particular organ. The user may also select intermittent perfusion, single pass perfusion, and recirculation perfusion. Depending on the type of perfusion selected, aerobic or anaerobic medical fluids may be specified.

[0198] Next, the type of flow control for each selected perfusion mode is set. The flow control selector selects flow control based on at least one of perfusate flow rate, perfusate pH, organ inlet pressure and timed sequences. In the preferred embodiment, the flow control is based on detected

pressure at the perfusion inlet to the organ. The flow of the medical fluid is then based on the selected perfusion mode and flow control.

**[0199]** During operation the conditions experienced by the system, in particular by the organ and the perfusate, are detected and monitored. The detected operating conditions are compared with prestored operating conditions. A signal can then be generated indicative of organ viability based on the comparison. The various detectors, sensors and monitoring devices are described above, but include at least a pressure sensor, a pH detector, an oxygen sensor and a flow meter.

**[0200]** The control system may also include a thermal controller for controlling temperature of at least one of the perfusate and the organ. The thermal controller can control the temperature of the medical fluid reservoirs and the organ container by controlling the TEDs. As noted above, temperature sensors are connected to the controller to facilitate monitoring and control.

**[0201]** The control system may be manually adjusted at any time or set to follow default settings. The system includes a logic circuit to prevent the operator from setting parameters that would compromise the organ's viability. As noted above, the system may also be operated in a manual mode for sequential hypothermic and/or normothermic perfusion, as well as in the computer controlled mode for sequential hypothermic and/or normothermic perfusion.

**[0202]** The above described apparatus and method may be used for child or small organs as well as for large or adult organs with modification as needed of the cassettes and or of the pressures and flow rates accordingly. As previously discussed, the organ cassette(s) can be configured to the shapes and sizes of specific organs or organ sizes. The apparatus and method can also be used to provide an artificial blood supply to, such, for example, artificial placentas cell cultures, for growing/cloning organ(s).

**[0203]** While the invention has been described in conjunction with specific embodiments thereof, it is evident that many alternatives, modifications and variations may be apparent to those skilled in the art. Accordingly, the preferred embodiments of the invention as set forth herein are intended to be illustrative, not limiting. Various changes may be made without departing from the spirit and scope of the invention.

What is claimed is:

1. A method of determining effects of a substance on an organ, comprising:

perfusing the at least one organ with a first medical fluid to preserve the at least one organ;

exposing the at least one organ to at least one test substance; and

gathering data regarding at least one of the at least one organ, the at least one test substance, and interaction between the at least one organ and the at least one test substance.

2. The method of claim 1, wherein the exposing step is carried out by perfusing the organ with a second medical fluid containing the test substance.

3. The method of claim 2, wherein the first and second medical fluids are the same.

4. The method of claim 2, wherein the first and second medical fluids are different.

5. The method of claim 1, wherein at least one of the at least one organ and an effluent from the organ is monitored by a sensor that senses characteristics of at least one of the effluent and the at least one organ.

6. The method of claim 5, further comprising generating data comprised of the sensed characteristics.

7. The method of claim 6, wherein the data can be generated and displayed in real time, stored, transmitted to a remote site, transferred to a recording medium, or relayed to a microprocessor for assessment.

8. The method of claim 2, further comprising collecting the second medical fluid that has passed through the at least one organ from an organ bath and sensing characteristics of the collected medical fluid indicative of the interaction between the at least one organ and the test substance.

9. The method of claim 2, wherein the test substance is a chemical compound.

10. The method of claim 2, wherein the test substance is at least one of natural and modified antibodies.

11. The method of claim 2, wherein the test substance is an immunotoxin.

12. The method of claim 2, wherein the second medical fluid is blood.

13. The method of claim 5, wherein the sensed characteristics relate to at least one of absorption, distribution, metabolism and excretion.

14. The method of claim 5, wherein the sensed characteristics relate to at least one of pharmacokinetics, pharmacodynamics and toxicity.

15. The method of claim 5, wherein the sensed characteristics relate to at least one of determining what the substance is doing to the at least one organ and what the at least one organ is doing to the substance.

16. A method of screening at least one organ with a bioactive agent, comprising:

determining that the at least one organ will not be transplanted;

perfusing said at least one organ with a first medical fluid to preserve the organ;

exposing the at least one organ to at least one test substance; and

gathering data regarding at least one of the at least one organ, the at least one test substance, and interaction between the at least one organ and the at least one test substance.

17. The method of claim 16, wherein the organ is not suitable for transplanting.

18. The method of claim 16, further comprising the steps of:

perfusing the at least one organ with a first medical fluid; and

sensing fluid characteristics indicative of organ viability.

专利名称(译)	用于确定器官物质的效果的装置和方法		
公开(公告)号	<a href="#">US20040224298A1</a>	公开(公告)日	2004-11-11
申请号	US10/768167	申请日	2004-02-02
[标]申请(专利权)人(译)	BRASSIL JOHN SCHEIN DOUGLAS CURTIS CHRISTOPHER 慕		
申请(专利权)人(译)	BRASSIL JOHN SCHEIN DOUGLAS CURTIS 克里斯托弗·		
当前申请(专利权)人(译)	BRASSIL JOHN SCHEIN DOUGLAS CURTIS 克里斯托弗·		
[标]发明人	BRASSIL JOHN SCHEIN DOUGLAS CURTIS CHRISTOPHER G		
发明人	BRASSIL, JOHN SCHEIN, DOUGLAS CURTIS, CHRISTOPHER G.		
IPC分类号	A01N1/02 G01N33/50 G01N33/53		
CPC分类号	A01N1/02 A01N1/0247 G01N33/5082		
其他公开文献	US7749693		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

# 摘要(译)

器官灌注装置和方法监测，维持和/或恢复器官的活力并保存器官以便储存和/或运输。其他装置包括器官转运器，器官盒和器官诊断装置。该方法包括在低温和/或常温下灌注器官，优选在低温器官冲洗后用于器官运输和/或储存。该方法可以通过器官的先前或后续静态或灌注低温暴露来实施。通过在常温下用医用流体（例如氧合交联的基于血红蛋白的碳酸氢盐医用流体）灌注器官来恢复高能核苷酸（例如ATP）水平，从而恢复器官活力。在保存和/或维持器官的期间，可以在器官上和/或与器官一起进行各种药物研究和开发。可以用含有诸如测试物质的物质的流体灌注器官，以获得关于器官，物质和物质与器官的相互作用的数据。然后，该数据可用于最终提供关于药物功效的信息，以支持新药的监管申请。




FIG. 1