

US007045310B2

US 7.045.310 B2

May 16, 2006

## (12) United States Patent

Buck, Jr. et al.

## (56) References Cited

(10) Patent No.:

(45) Date of Patent:

## U.S. PATENT DOCUMENTS

4,293,310 A 10/1981 Weber 4,323,536 A 4/1982 Columbus 4,381,978 A 5/1983 Gratzel et al. 4,478,744 A 10/1984 Mezei et al. 4,526,661 A 7/1985 Steckhan et al. 4,545,382 A 10/1985 Higgins et al. 12/1987 Higgins et al. 4,711,245 A 4,830,959 A 5/1989 McNeil et al. 4,832,814 A 5/1989 Root

(Continued)

#### FOREIGN PATENT DOCUMENTS

EP 0 125 139 A2 11/1984 (Continued)

#### OTHER PUBLICATIONS

Chidsey et al., "Micrometer-Spaced Platinum Interdigitated Array Electrode: Fabrication, Theory, and Initial Use," *Anal. Chem.*, 58, 601-677, 1986.

## (Continued)

Primary Examiner—Christopher L. Chin Assistant Examiner—Gailene R. Gabel (74) Attorney, Agent, or Firm—Barnes & Thornburg LLP

## (57) ABSTRACT

Novel bipyridyl-osmium complex conjugates and their use in electrochemical assays are described. The redox reversible-osmium complexes can be prepared to exhibit unique reversible redox potentials and can thus be used in combination with other electroactive redox reversible species having redox potentials differing by at least 50 millivolts in electrochemical assays designed for use of multiple electroactive species in the same cell and in the same sample without interference between the two or more redox coupled conjugate systems.

## 4 Claims, 13 Drawing Sheets

# (54) REDOX REVERSIBLE BIPYRIDYL-OSMIUM COMPLEX CONJUGATES

(75) Inventors: Harvey B. Buck, Jr., Indianapolis, IN

(US); **Zhi David Deng**, Carmel, lN (US); **Eric R. Diebold**, Noblesville, lN

(US)

(73) Assignee: Roche Diagnostics Operations, Inc.,

Indianapolis, 1N (US)

(\*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 713 days.

(21) Appl. No.: 09/999,110

(22) Filed: Nov. 1, 2001

(65) Prior Publication Data

US 2002/0090632 A1 Jul. 11, 2002

## Related U.S. Application Data

- (62) Division of application No. 09/322,791, filed on May 28, 1999, now Pat. No. 6,352,824.
- (60) Provisional application No. 60/087,576, filed on Jun. 1, 1998.
- (51) **Int. Cl.** *G01N 33/53* (2006.01) *G01N 33/72* (2006.01)
- (52) **U.S. Cl.** 435/7.93; 435/4; 435/5; 435/6; 435/6; 435/7.1; 435/7.93; 436/15; 436/66; 436/67; 436/84; 436/172; 436/805; 436/501; 436/517; 436/518; 436/536; 436/544; 436/545; 530/303; 530/304; 530/385

See application file for complete search history.

#### U.S. PATENT DOCUMENTS

4,945,045 A	7/1990	Forrest et al.
4,954,414 A	9/1990	Adair et al.
4,963,245 A	10/1990	Weetall
4,999,632 A	3/1991	Parks
5,120,420 A	6/1992	Nankai et al.
5,141,868 A	8/1992	Shanks et al.
5,192,415 A	3/1993	Yoshioka et al.
5,243,516 A	9/1993	White
5,264,103 A	11/1993	Yoshioka et al.
5,288,636 A	2/1994	Pollmann et al.
5,312,762 A	5/1994	Guiseppi-Elie
5,352,351 A	10/1994	White et al.
5,366,609 A	11/1994	White et al.
5,405,511 A	4/1995	White et al.
5,427,912 A	6/1995	Brown et al.
5,437,772 A	8/1995	De Castro et al.
5,437,999 A	8/1995	Diebold et al.
5,438,271 A	8/1995	White et al.
5,491,097 A	2/1996	Ribi et al.
5,575,895 A	11/1996	lkeda et al.
5,589,326 A	12/1996	Deng et al.
		-

#### FOREIGN PATENT DOCUMENTS

EP	0 167 248 A3	3 1/1985
EP	0 150 999 A2	8/1985
EP	0 229 780 A2	2 1/1989
EP	0 328 380 A2	8/1989
EP	0 402 126 B1	12/1990
EP	0 142 301 B1	11/1991
EP	0 127 958 B1	3/1992
WO	WO 86.02734	5/1986
WO	WO 86/03837	7/1986
WO	WO 86/04926	8/1986
WO	WO 91/16630	10/1991
WO	WO 92/14741	9/1992
WO	WO 92/14836	9/1992
WO	93/25907	12/1993
WO	94/14066	6/1994
WO	97/01097	1/1997
WO	97/32866	9/1997
WO	WO 97/34140	9/1997

## OTHER PUBLICATIONS

Niwa et al., "Fabrication and Characteristics of Vertically Separated Interdigitated Array Electrodes," *J. Electroanal. Chem.*, 267, 291-297, 1989.

Aoki et al., "Quantitative Analysis of Reversible, diffusion-Controlled Currents of Redox Soluble Species at Interdigitated Array Electrodes Under Steady-State Conditions," *J. Electroanal. Chem.*, 256, 269-82, 1988.

Surridge et al., "Electron and Counterion Diffusion Constants in Mixed-Valent Polymeric Osmium Bipyridine Films," *J. Phys. Chem.*, 98, 917-923, 1994.

Forster et al., "Synthesis, Characterization, and Properties of a Series of Osmium- and Ruthenium-Containing Metallopolymers," *Macromolecules*, 23, 4372-4377, 1990.

Zakeeruddin et al., "Towards Mediator Design: Characterization of Tris-(4,4'-Substituted-2,2'-Bipyridine) Complexes of Iron (II), Ruthenium (II) and Osmium (II) as Mediators for Glucose Oxidase of *Aspergillus niger* and other Redox Proteins," *J. Electroanal. Chem.*, 337, 253-283, 1992.

Collin et al., "Anodic Elecropolymerization of Films of Polypyrrole Functionalized with Metal Terpyridyl Redox Centres," *J. Electroanal: Chem.*, 286, 75-87, 1990.

Heineman et al., "Strategies For Electrochemical lmmunoassay," *Anal. Chem.* 57 (12), 1321-1331, 1985.

Sanderson et al., "Filar Electrodes: Steady-State Currents and Spectroelectrochemistry at Twin Interdigitated Electrodes," *Anal. Chem.*, 57, 2388-2393, 1985.

Xu et al., "Heterogeneous Enzyme Immunoassay of Alpha-Fetoprotein in Maternal Serum by Flow-Injection Amperometric Detection of 4-Aminophenol," *Clin. Chem.*, 36 (11), 1941-1944, 1990.

Thompson et al. "Comparison of Methods for Following Alkaline Phosphatase Catalysis: Spectrophotometric versus Amperometric Detection,", *Anal. Biochem.*, 192, 90-95, 1991.

Wollenberger et al., "Interdigitated Array Microelectrodes for the Determination of Enzyme Activities," *Analyst*, 119, 1245-1249, Jun. 1994.

Wollenberger, "Electrochemical Biosensors—Ways to Improve Sensor Performance," *Biotechnology and Genetic Engineering Reviews*, 13, 27-266, Dec. 1995.

Pishko et al., "Direct Electrical Communication Between Graphite Electrodes and Surface Adsorbed Glucose Oxidase/Redox Polymer Complex," *Angew. Chem. Int. Ed. Engl.*, 29, (1), 82-84, 1990.


Garguilo et al., "Amperometric Sensors for Peroxide, Choline, and Acetylcholine Based on Electron Transfer Between Horseradish Peroxidase and a Redox Polymer," *Anal. Chem.*, 65, 523-528, 1993.


Ohara et al., "Glucose Electrodes Based on Cross-Linked  $[Os(bpy)_2C1]^{+/2+}$  Complexed Poly(1-Vinylimidazole) Films," *Anal Chem.*, 65, 3512-3517, 1993.


Paeschke et al., "Voltammetric Multichannel Measurements Using Silicon Fabricated Microelectrode Arrays," *Electroanalysis*, 8, (10), 891-898, 1996.


Matsue, "Electrochemical Sensors Using Microarray Electrodes,", *Trends Anal. Chem.*, 12 (3), 100-108, 1993.


Aoki et al., "Time-Dependence of Diffusion-Controlled Currents of a Soluble Redox Couple at Interdigitated Microarray Electrodes," *J. Electroanal. Chem.*, 266, 11-20, 1989.




























THE THE

C<sub>49</sub>H<sub>56</sub>N<sub>10</sub>O<sub>3</sub>S0s F.W. 1055.30





# REDOX REVERSIBLE BIPYRIDYL-OSMIUM COMPLEX CONJUGATES

## CROSS REFERENCE TO RELATED APPLICATIONS

This application is a divisional of U.S. application Ser. No. 09/322,791, filed May 28, 1999, now U.S. Pat. No. 6,352,824, which claims priority under 35 U.S.C. § 119(e) to U.S. Provisional Ser. No. 60/087,576, filed Jun. 1, 1998, 10 which is expressly incorporated by reference.

#### FIELD OF THE INVENTION

This invention relates to novel redox-reversible conjugates. More particularly the invention is directed bipyridyl complexed-osmium conjugates useful for detection and quantification of biologically significant analytes in a liquid sample.

## BACKGROUND AND SUMMARY OF THE INVENTION

Therapeutic protocols used today by medical practitioners in treatment of their patient population requires accurate and convenient methods of monitoring patient disease states. 25 Much effort has been directed to research and development of methods for measuring the presence and/or concentration of biologically significant substances indicative of a clinical condition or disease state, particularly in body fluids such as blood, urine or saliva. Such methods have been developed to 30 detect the existence or severity of a wide variety of disease states such as diabetes, metabolic disorders, hormonal disorders, and for monitoring the presence and/or concentration of ethical or illegal drugs. More recently there have been significant advancements in the use of affinity-based elec- 35 trochemical detection/measurement techniques which rely, at least in part, on the formation of a complex between the chemical species being assayed (the "analyte") and another species to which it will bind specifically (a "specific binding partner"). Such methods typically employ a labeled ligand 40 analog of the target analyte, the ligand analog selected so that it binds competitively with the analyte to the specific binding partner. The ligand analog is labeled so that the extent of binding of the labeled ligand analog with the specific binding partner can be measured and correlated with 45 the presence and/or concentration of the target analyte in the biological sample.

Numerous labels have been employed in such affinity based sample analysis techniques, including enzyme labeling, radioisotopic labeling, fluorescent labeling, and labeling 50 with chemical species subject to electrochemical oxidation and/or reduction. The use of redox reversible species, sometimes referred to as electron transfer agents or electron mediators as labels for ligand analogs, have proven to provide a practical and dependable results in affinity-based 55 electrochemical assays. However, the use of electrochemical techniques in detecting and quantifying concentrations of such redox reversible species (correlating with analyte concentrations) is not without problem. Electrochemical measurements are subject to many influences that affect the 60 accuracy of the measurements, including not only those relating to variations in the electrode structure itself and/or matrix effects deriving from variability in liquid samples, but as well those deriving from interference between multiple electroactive species, especially when assay protocols 65 require detection or quantification of multiple electroactive species.

2

The present invention relates to novel diffusible, redoxreversible osmium-bipyridyl conjugates useful in immunosensors based on either indirect amplified electrochemical detection techniques or on direct electrochemical measurement of detectable species with microarray electrodes under bipotentiostatic control. An Os-bipyridyl complex can, for example be covalently attached to a peptide which has amino acid sequence of the binding epitope for an antibody. When Os complex/peptide conjugate is bound to antibody, the conjugate does not function electrochemically; it is said to be "inhibited". Typically an analyte present in sample will compete with Os-bipyridyl complex/peptide conjugate for the limited number of binding sites on the antibody. When more analyte is present, more free Os-bipyridyl complex/ peptide conjugate will be left in an unbound diffusible state producing higher current at a sensor electrode, i.e. one of the working electrodes where measured events (oxidation or reduction) are taking place. In the opposite case, when less analyte is present, more indicator/peptide conjugate will be 20 bound to antibody resulting less free conjugates and producing lower current levels at the working electrodes. Therefore the current detected at either one of the working electrodes will be a function of analyte concentration.

It is frequently desired to measure more than one analyte species in a liquid sample. Measurement of multiple species in a mixture has been achieved with photometry and fluorescence, via selection of the appropriate wavelengths. Electrochemical measurements of a single species in a complex mixture are routinely made by selecting a potential at which only the desired species is oxidized or reduced (amperometry) or by stepping or varying the potential over a range in which only the desired species changes its electrochemical properties (AC and pulse methods). These methods suffer from disadvantages including lack of sensitivity and lack of specificity, interference by charging and matrix polarization currents (pulse methods) and electrode fouling due to the inability to apply an adequate over potential. Moreover, electrochemical measurements are complicated by interference between the multiplicity of electroactive species commonly extant in biological samples.

Electrode structures which generate steady state current via diffusional feedback, including interdigitated array electrodes (IDAs) (FIGS. 1 and 2) and parallel plate arrangements with bipotentiostatic control are known. They have been used to measure reversible species based on the steady state current achieved by cycling of the reversible species. A reversible mediator (redox reversible species) is alternately oxidized and reduced on the interdigitated electrode fingers. The steady state current is proportionate to mediator concentration (FIG. 3) and limited by mediator diffusion. A steady state current is achieved within seconds of applying the predetermined anodic (more positive) and cathodic (less positive or negative) potentials (FIG. 6) to the microelectrode array. The slope of a plot of the IDA current vs. mediator concentration is dependent on IDA dimensions, and the slope increases with narrower electrode spacings

The present invention provides novel osmium-bipyridyl complex conjugates useful in a method for measuring multiple analyte species in the same sample, and optimally on the same electrode structure, thus improving the accuracy of the relative measurements. The present conjugates can be used with other electroactive conjugate species having unique redox potentials to provide an electrochemical biosensor with capacity to provide improved accuracy. Analyte concentration can be measured/calculated from electrometric data obtained on the same liquid sample with the same

electrode structure, thereby minimizing perturbations due to variability in sample or electrode structure.

The diffusible osmium conjugates of this invention find use in assay based on the principle of diffusional recycling, where a diffusible redox reversible species is alternately 5 oxidized and reduced at nearby electrodes (the working electrodes), thereby generating a measurable current. As alternate oxidation and reduction is required for measurement, only electroactive species which are electrochemically reversible at the predetermined redox potential are measured 10 thereby eliminating, or at least reducing, the impact or interference from non-reversible electroactive species in the sample or other reversible-redox species having unique (at least 50 millivolts different) redox potential. Redox reversible species having different oxidation potentials can be 15 independently measured in a mixture by selecting and bipotentiostatically controlling the oxidizing and reducing potentials for neighboring electrode pairs so that only the species of interest is oxidized at the anode and reduced at the cathode. When the working electrodes are dimensioned to 20 allow diffusional recycling of the redox-reversible-species at the selected oxidizing and reducing potentials appropriate for that species, a steady state current is quickly established through the sample and the electrode structure. The magnitude of the current at the working electrodes where the 25 measurable oxidative and reductive events are taking place, is proportional to the concentration of the diffusible redox reversible species in the sample. When two or more redox reversible species are utilized, they are selected to have redox potentials differing by at least 50 millivolts, most 30 preferably at least 200 millivolts, to minimize interference between one species and the other in measurements of the respective steady state currents. The present osmium complex conjugates have unique redox potentials that allow them to be used with/in the presence of other electroactive 35 conjugates without (or with minimal) interference.

The present conjugates can be used in any electrode structure/system which allows for diffusional recycling to achieve steady state current in response to application of pre-selected complex species-specific anodic and cathodic 40 potentials. Suitable electrode structures include interdigitated array microelectrodes and parallel plate electrodes separated by distances within the diffusion distance of the respective redox reversible species. The electrode structures typically include a reference electrode (e.g., Ag/AgCl), at 45 least two working electrodes, and optionally an auxiliary electrode for current control. In use, a programmable bipotentiostat is placed in electrical communication with the electrode structure for applying the respective anodic and cathodic potentials specific for each of the respective redox 50 reversible species utilized in the method/biosensor. Several novel osmium complexes including those of this invention have been developed for use as labels for preparing ligand analog conjugates having potential differences sufficient (at least 50 millivolts) to allow the use of two osmium com- 55 plexes (as opposed to an osmium complex and a ferrocene or other redox reversible label) in multiple conjugate based electrochemical assays.

The present osmium conjugates are useful in a method for measuring the concentration of one or more analytes in a 60 liquid sample. The method includes contacting a portion of the sample with pre-determined amounts of at least a first and second redox reversible species having a redox potential differing by at least 50 millivolts from that of each other species. Each respective species comprises a liquid sample 65 diffusible conjugate of a ligand analog of an analyte in the liquid sample and a redox reversible label. The liquid sample

4

is also contacted with a predetermined amount of at least one specific binding partner for each analyte to be measured. The diffusible conjugate is selected so that it is capable of competitive binding with the specific binding partner for said analyte. The concentration of the diffusible redoxreversible-species in the liquid sample is then determined electrochemically. The sample is contacted with an electrode structure, including a reference electrode and at least first and second working electrodes dimensioned to allow diffusional recycling at least one of the diffusible redox-reversible-species in the sample, when a predetermined redoxreversible-species-dependent cathodic potential is applied to one working electrode and a predetermined redox-reversible-species-dependent anodic potential is applied to the second working electrode. Typically, a first cathodic potential is applied to the first working electrode and a first anodic potential is applied to the second working electrode to establish current flow through the sample due to diffusional recycling of the first redox-reversible-species without significant interference from the second redox-reversible-species. Current flow through one or more of the electrodes at the first anodic and cathodic potentials is measured.

Similarly current flow responsive to application of second cathodic and anodic potentials to electrodes in contact with the sample is measured and correlated with measured current flows for known concentrations of the respective redox-reversible-species, said concentrations being proportionate to the respective analyte concentrations.

The reagent components including the present bipyridylosmium conjugates of the invention and the specific binding partners, can be provided in the form of a test kit for measuring the targeted analyte(s) in a liquid sample, either as separate reagents or, more preferably, combined as a multi-reagent composition, e.g. combined redox reversible species, combined specific binding partners, or combined redox reversible species and specific binding partners. The kit optionally, but preferably, includes an electrode structure dimensioned to allow diffusional redox recycling of diffusible redox reversible species in the liquid sample. The electrode structure includes conductors for connecting the structure to a bipotentiostat programmed to apply redoxreversible-species-dependent-anodic and cathodic potentials to the electrode structure and to sense and measure current flow, typically at one or both of the working electrodes, responsive to such potentials.

This invention is based on the preparation and use of novel electrochemically detectable osmium complexes and covalent conjugates of said complexes having oxidation potentials differing sufficiently from other redox-reversible complexes to enable their use together with other osmium or other metal conjugates. Thus, there are provided novel osmium labeled ligand analogs capable of binding to a specific binding partner of a biologically significant analyte. The electrochemically detectable osmium conjugates comprise a tris(bipyridyl) osmium complex characterized by fast mediation kinetics and low redox potential (+150 mV vs. Ag/AgCl). Another group of osmium complex labeled, electrochemically detectable conjugates that can be used with the present complexes in multi-conjugate assay protocols include bis(bipyridyl) imidazoyl haloosmium complexes, which, like the tris(bipyridyl) osmium complexes are characterized by fast mediation kinetics, but the tris(bipyridyl) complexes have a redox potential sufficiently different from the bis(pyridyl) imidazolyl chloroosmium complexes to allow their use together in assays utilizing microelectrode

The present osmium complex conjugates can be used in combination with another conjugated redox-reversible-species for the measurement of both glycosylated hemoglobin and hemoglobin in a lysed blood sample. One redox-reversible-species preferably comprises an imidazole-osmium complex covalently linked to a ligand analog of either hemoglobin or glycosylated hemoglobin, and a second redox-reversible-species comprising a second redox reversible label covalently bound to a ligand analog of the other of the two target analytes. The method enables measurement of the concentration of both the glycosylated hemoglobin (HbAlc) and the concentration of either total hemoglobin or that of unglycosylated hemoglobin (HbA<sub>0</sub>) thereby enabling calculation of the results as a ratio of the two measurements (% HbAlc). It is advantageous to assay both HbAlc and total hemoglobin (or HbA<sub>0</sub>) using the same principle in a single sample, particularly because ratioing works minimize biases 20 due to environmental effects.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an enlarged plan view of an interdigitated array <sup>25</sup> electrode for reversible mediator measurement.

FIG. 2 is a partial cross-sectional view of the electrode of FIG. 1 illustrating the conditions of steady state current limited by diffusion of mediator (M).

FIG. 3 is a graphic presentation of dose response currents for a bis-(bipyridyl) imidazolyl chloroosmonium mediator peptide conjugate.

FIG. **4** is a graphic illustration of current flow vs. concentration of glycosylated hemoglobin (HbAlc) in blood <sub>35</sub> samples using an osmium conjugate and enzyme amplified DC amperometry.

FIG. **5** is a graphic illustration of the inhibition of current flow due to free conjugate as a function of antibody concentration (Cn) as measured using enzyme amplified DC 40 amperometry  $[C_1,>C_2,>C_3]$ .

FIG. 6 is a graphic illustration of current flow vs. time using an interdigitated array electrode.

FIG. 7 is a graphic illustration of the effect of the dimensions of the interdigitated array electrode structure on current flow as a function of concentration of an osmium conjugate (Os-DSG-Alc).

FIG. **8** is a graphic illustration of current flow as a function of applied potential for a liquid sample containing equimolar (50  $\mu M)$  of a bis-(bipyridyl) imidazolyl chloroosmium complex and a tris(bipyridyl) osmium complex of this invention.

FIG. 9 is a graphic presentation of current flow vs. concentration of a ferrocene-biotin conjugate in the presence of varying amounts of an osmium complex conjugate on interdigitated array electrodes with bipotentiostatic control.

FIG. 10 is a graphic illustration of the effect of concentration of an unlabeled conjugate (BSA-Alc) on current flow in a solution containing osmium labeled conjugate (osmium-DSG-Alc)) in the presence of three separate Alc-recognizing antibody compositions.

FIG. 11 illustrates the structure of a tris(bipyridyl) osmium labeled conjugate of this invention.


FIGS. 12–14 are similar and each depict the chemical 65 structure of a bis(bipyridyl) imidazolyl chloroosmium labeled peptide conjugate.

6

# DETAILED DESCRIPTION OF THE INVENTION

The diffusible redox reversible species of this invention is a liquid-sample-diffusible conjugate of a ligand analog of an analyte and a redox reversible bipyridyl-osmium complex. The term "redox reversible" as used herein refers to a chemical species capable of reversible oxidation and reduction in a liquid sample. Redox reversible labels are well-known in the art and include ligand complexes of transition metal ions, for example iron (ferrocene and ferrocene derivatives), ruthenium and osmium. The conjugate is prepared by linking the ligand analog to the label either covalently through difunctional linking agents or by combination of covalent linkages and art-recognized specific binding entities (for example, biotin-avidin).

More particularly, the present invention is directed to a redox reversible osmium complex of the formula



wherein

R and  $R_1$  are the same or different and are 2,2'-bipyridyl, 4,4'-disubstituted-2,2'-bipyridyl, 5-5'-disubstituted,-2,2'-bipyridyl, 1,10-phenanthrolinyl, 4,7-disubstituted-1,10-phenanthrolinyl, or 5,6-disubstituted-1,10-phenanthrolinyl, wherein each substituent is a methyl, ethyl, or phenyl group,

 $R_5$  is 4-substituted-2,2'-bipyridyl or 4,4'-disubstituted-2, 2'-bipyridyl wherein the 4-substituent is the group  $B-(L)_k$ -Q(CH<sub>2</sub>)<sub>t</sub>— and the 4'-substituent is a methyl, ethyl or phenyl group;

R,  $R_1$  and  $R_5$  are coordinated to Os through their nitrogen atoms;

Q is O, S, or NR<sub>4</sub> wherein R<sub>4</sub> is hydrogen, methyl or ethyl;
—L— is a divalent linker;

k is 1 or 0;

i is 1, 2, 3, 4, 5or 6;

B is hydrogen or a group comprising a ligand capable of binding to a specific binding partner;

d is +2 or +3;

X and Y are anions selected from monovalent anions, chloride, bromide, iodide, fluoride, tetrafluoroborate, perchlorate, and nitrate and divalent anions, e.g., sulfate, carbonate or sulfite wherein x and y are independently 0, 1, 2, or 3 so that the net charge of  $X_xY_y$  is -2 or -3.

Another redox reversible osmium complex that can be used with the present imidazole-osmium conjugates is a compound of the formula

$$\begin{bmatrix} (R_7)_q & & & \\ \hline & & \\$$

wherein

R and  $R_1$  are the same or different and are 2,2'-bipyridyl, 4,4'-disubstituted-2,2'-bipyridyl, 5-5'-disubstituted,-2,2'-bipyridyl, 1,10-phenanthrolinyl, 4,7-disubstituted-1,10-phenanthrolinyl, or 5,6-disubstituted-1,10-phenanthrolinyl, wherein each substituent is a methyl, ethyl, or phenyl group,

R and  $R_1$  are coordinated to Os through their nitrogen atoms;

q is 1 or 0;

 $R_7$  is  $B-(L)_k-Q(CH_2)_i$ —;

 $R_2$  is hydrogen, methyl, or ethyl when q is 1, and  $R_2$  is  $B-(L)_k-Q(CH_2)_i$ —when q is 0; wherein in the group  $B-(L)_k-Q(CH_2)_i$ —Q is O, S, or  $NR_4$  wherein  $R_4$  is hydrogen, methyl or ethyl; —L— is a divalent linker;

k is 1 or 0;

i is 1, 2, 3, 4, 5 or 6; and

B is hydrogen or a group comprising a ligand capable of binding to a specific binding partner;

Z is chloro or bromo;

m is +1 or +2;

X is monovalent anion, e.g., chloride, bromide, iodide, fluoride, tetrafluoroborate, perchlorate, nitrate, or a divalent anion, e.g., sulfate, carbonate, or sulfite;

Y is monovalent anion, e.g., chloride, bromide, iodide, fluoride, tetrafluoroborate, perchlorate or nitrate; and

n is 1 or zero,

provided that when X is a divalent anion, n is zero,

and when m is 1, n is zero and X is not a divalent anion.

Redox reversible conjugate species of each of those formulas are prepared from the corresponding compounds wherein k is 0 and B is hydrogen by reacting such compounds with either a heterofunctional crosslinker of the formula S-L'-T wherein L' is a divalent linker and S and T are different electrophilic groups capable of reacting with a nucleophilic group to form a covalent bond, or with a homofunctional crosslinker of the formula S-L'-T wherein L' is a divalent linker and S and T are the same electrophilic groups capable of reacting with a nucleophilic group to form a covalent bond. The resulting products are then reacted with ligand analogs using classical coupling reaction conditions to product the conjugate species. The oxidizing potentials of the respective bis(bipyridyl) imidazolyl and tris(bipyridyl) osmium complexes defined above is such that the respective complexes can be used as reversible redox labels for the respective redox reversible species in performance of the method. FIG. 8 illustrates a cyclic voltammogram for a liquid sample containing equimolar (50 µM) amounts of a bis(bipyridyl) imidazolyl chloroosmium complex and a tris (bipyridyl) osmium complex.

In one embodiment of the invention the specific binding partner for each analyte is an antibody and the ligand analog is selected so that it binds competitively with the analyte to the antibody. There are, however, other examples of ligand-specific binding partner interactions that can be utilized in developing applications of the present method. Examples of ligands and specific binding partners for said ligands are listed below.

		60
Ligand	Specific Binding Partner	
Antigen (e.g., a drug substance)	Specific antibody	
Antibody	Antigen	
Hormone	Hormone receptor	65
Hormone receptor	Hormone	

8

#### -continued

	Ligand	Specific Binding Partner
5	Polynucleotide	Complementary polynucleotide strand
	Avidin	Biotin
	Biotin	Avidin
	Protein A	Immunoglobulin
	Immunoglobulin	Protein A
	Enzyme	Enzyme cofactor (substrate)
10	Enzyme cofactor (substrate)	Enzyme
	Lectins	Specific carbohydrate
	Specific carbohydrate	Lectins
	of lectins	

The term "antibody" refers to (a) any of the various classes or subclasses of immunoglobulin, e.g., lgG, lgM, derived from any of the animals conventionally used, e.g., sheep, rabbits, goats or mice; (b) monoclonal antibodies; (c)intact molecules or "fragments" of antibodies, monoclonal or polyclonal, the fragments being those which contain the binding region of the antibody, i.e., fragments devoid of the Fc portion (e.g., Fab, Fab', F(ab')<sub>2</sub>) or the so-called "half-molecule" fragments obtained by reductive cleavage of the disulfide bonds connecting the heavy chain components in the intact antibody. The preparation of such antibodies are well-known in the art.

The term "antigen" used in describing and defining the present invention includes both permanently antigenic species (for example, proteins, peptides, bacteria, bacteria fragments, cells, cell fragments and viruses) and haptans which may be rendered antigenic under suitable conditions.

The present osmium labeled conjugates are useful alone or in combination with other conjugates in methods for measuring the concentration of one or more analytes in a liquid sample. One method enables two or more independent amperometric measurements of the sample on a single electrode structure. The method comprises

contacting a volume of said liquid sample with

- 1) predetermined amounts of at least a first and second redox reversible species, each respective species having a redox potential differing by at least 50 millivolts from that of each other species, at least one species comprising a liquid sample diffusible conjugate of a ligand analog of an analyte in the liquid sample and a redox reversible label, said conjugate capable of competitive binding with a specific binding partner for said analyte, and
- 2) a predetermined amount of at least one specific binding partner for each analyte to be measured; and
- electrochemically determining the concentration of each of said diffusible redox-reversible species in the liquid sample by
- contacting said sample with an electrode structure including a reference electrode and at least first and second working electrodes dimensioned to allow diffusional recycling of the diffusible redox reversible species in the sample when a predetermine redox-reversible-species-dependent cathodic potential is applied to one working electrode and a predetermined redox-reversible-species-dependent anodic potential is applied to a second working electrode, said diffusional recycling of said species being sufficient to sustain a measurable current through said sample,

applying a first cathodic potential to the first working electrode and a first anodic potential to the second working electrode, said first cathodic and anodic potentials corresponding to those respective potentials necg

essary to establish current flow through the sample due to diffusional recycling of the first redox reversible species without significant interference from said second redox reversible species,

measuring current flow at said first anodic and cathodic 5 potentials,

applying a second cathodic potential to said first or second working electrode and a second anodic potential to the other working electrode, said second cathodic and anodic potential corresponding to those respective potentials necessary to establish current flow through the sample due to diffusional recycling of the second redox-reversible-species without significant interference from the first redox reversible species,

measuring current flow at said second anodic and cathodic potentials, and

correlating the respective measured current flows to that for known concentrations of the respective diffusible redox reversible species, said concentrations being proportionate to the respective analyte concentrations.

That method has very broad applicability but in particular may be used to assay: drugs, hormones, including peptide hormones (e.g., thyroid stimulating hormone (TSH), luteinizing hormone (LH), follicle stimulating hormone (FSH), insulin and prolactin) or non-peptide hormones (e.g., steroid hormones such as cortisol, estradiol, progesterone and testosterone, or thyroid hormones such as thyroxine (T4) and triiodothyronine), proteins (e.g., human chorionic gonadotropin (hCG), carcino-embryonic antigen (CEA) and alphafetoprotein (AFP)), drugs (e.g., digoxin), sugars, toxins or vitamins.

The method can be performed on liquid samples comprising biological fluids such as saliva, urine, or blood, or the liquid sample can be derived from environmental sources.

The liquid samples can be analyzed "as is," or they can be diluted, buffered or otherwise processed to optimize detection of the targeted analyte(s). Thus, for example, blood samples can be lysed and/or otherwise denatured to solubilize cellular components.

The method can be performed using widely variant sampling handling techniques. Thus, the sample can be premixed with either or both of the specific binding partner for the targeted analytes and the redox reversible species prior to contacting the sample with the electrode structure, or the 45 liquid sample, either neat or pre-processed, can be delivered to a vessel containing predetermined amounts of the redox reversible species and the specific binding partner for subsequent or simultaneous contact with the electrode structure. The order of introduction of the components into the sample 50 is not critical; however, in one embodiment of the invention the predetermined amounts of the specific binding partners are first added to the sample, and thereafter, there is added the predetermined amounts of the redox reversible species. It is also possible to combine the predetermined amounts of 55 the specific binding partners with the redox reversible species to form the respective complexes prior to combining those components with the liquid sample. In that latter case the redox reversible species will be displaced from its respective specific binding partner by the corresponding 60 analyte to provide a concentration of the redox reversible species proportionate to the concentration of analyte in the liquid sample. The reagents, that is, the predetermined amounts of the specific binding partner of each analyte and the predetermined amounts of the corresponding redox 65 reversible species can, for example, be deposited in a vessel for receiving a predetermined volume of the liquid sample.

10

The liquid sample is added to the vessel, and thereafter, or simultaneously, the liquid sample is contacted with the electrode structure.

The electrode structure includes a reference electrode and at least first and second working electrodes dimensioned to allow diffusional recycling of the diffusible redox reversible species in the sample when predetermined redox-reversiblespecies-dependent-cathodic and anodic potential is applied to the working electrodes. The term "working electrode" as used herein refers to an electrode where measured events (i.e. oxidation and/or reduction) take place and resultant current flow can be measured as an indicator of analyte concentration. "Anodic potential" refers to the more positive potential (applied to the anode) and "cathodic potential" refers to the less positive or negative potential applied to the cathode (vs a reference electrode). Electrodes dimension to allow diffusional recycling are well known in the art and are typically in the form of arrays of microdiscs, microholes, or microbands. In one embodiment the electrodes are in the form of an interdigitated arrangement of microband electrodes with micron or submicron spacing. Short average diffusional length and a large number of electrodes are desirable for effective current amplication by recycling of reversible redox species. The microelectrode arrays can be fabricated, for example, as pairs of interdigitated thin film metal electrodes in micron and submicron geometry arranged on an insulator substrate, for example, oxidized silicon. Each of the electrode fingers (FIG. 1) are spaced from its neighboring finger in the nanometer to low micrometer (1–10 microns) range. Microelectrode arrays can be fabricated using photolithography, electron bean lithography, and so-called lift-off technique. Thus, an interdigitated electrode array (IDA) can be deposited on glass, silicon or polyamide utilizing the following general proce-

- 1. Grow thermal oxide layer on silicon substrate;
- 2. Sputter 400 Å chromium seed layer, 2000 Å gold;
- 3. Spin-coat and soft-bake photo resist;
- 4. Expose and develop photo resist with IDA pattern;
- 5. Pattern gold and chromium with ion beam milling;
- 6. Strip photo resist; and
- Cut electrodes into chips by first coating with a
  protective layer, cutting into strips, stripping the protective layer, and cleaning electrode surfaces in oxygen
  plasma.

The electrode structure can be formed on an inner surface of a chamber for receiving the liquid sample, e.g., a cuvette, a capillary fill chamber, or other sample receiving vessel wherein the electrode structure can be contacted with the liquid sample. Alternatively, the electrode structure can form part of a probe for dipping into the liquid sample after the sample has been contacted with the predetermined amounts of the redox reversible species and the specific binding partners. The electrode structure is in contact with conductors that enable application of the respective cathodic and anodic potentials for carrying out the present method. The anodic and cathodic potentials are applied relative to a reference electrode component of the electrode structure using a bipotentiostat. The electrode structure can optionally include an auxiliary electrode for current control. The bipotentiostat is utilized to apply a first cathodic potential to a first working electrode and a first anodic potential to a second working electrode, the first cathodic and anodic potentials corresponding to those respective potentials necessary to establish current flow through the sample due to diffusional recycling of the first redox reversible species. Optionally the potential on one working electrode can be set

at a first diffusible species dependent, anodic potential and current flow is measured as the potential of the other working electrode is swept through a potential corresponding to the predetermined diffusible species dependent cathodic potential (or vice versa).

The cathodic and anodic potentials appropriate for each reversible redox species can be readily determined by empirical measurement. The multiple redox reversible species used in performance of the method of this invention are selected to have redox potentials differing by at least 50 10 millivolts, more preferably at least 100 millivolts, more preferably at least 200 millivolts, from that of each other redox reversible species utilized in the method. The difference in redox potentials of the redox reversible species being used allow each species to be detected without significant 15 interference from the second or any other redox reversible species in the liquid sample. A steady state current flow is rapidly established at each of the working electrodes following application of the anodic and cathodic potentials. Current flow can be measured at either or both working 20 electrodes, and it is proportionate to the concentration of the recycling redox reversible species.

Second cathodic and anodic potentials are applied to the working electrodes wherein said second potentials correspond to those respective potentials necessary to establish 25 current flow through the sample due to diffusional recycling of the second redox reversible species without significant interference from the first redox reversible species, and the resulting steady state current flow is measured. This step is repeated for each redox reversible species utilized in the 30 method. The measured current flows are then correlated to known concentrations of the respective diffusible redox reversible species. Those concentrations are proportionate to the respective analyte concentrations.

The method steps can be conducted using a programed 35 bipotentiostat to control potentials on the electrode structure in contact with the sample. The bipotentiostat can be included either in a desktop or hand-held meter further including means for reading values for steady state current, storing said values, and calculating analyte concentrations 40 using a microprocessor programmed for making such calculations.

The relative amounts of the first and second redox reversible species and the respective specific binding partners for the targeted analytes to be measured in the method can be 45 determined empirically. They are dependent on the concentration ranges of the targeted analyte, and the binding stoichiometry of the specific binding partner, the binding constant, the analyte and the corresponding redox reversible species. The amounts of each reagent appropriate for each 50 analyte being measured can be determined by empirical methods.

The present osmium conjugates can also be used in a method for measuring two proteinaceous analytes in a liquid sample wherein the ligand analog component of the first 55 redox reversible species is a peptide comprising an epitope of a first analyte and the ligand analog component of a second redox reversible species is a peptide comprising an epitope of a second analyte. One specific binding partner utilized in the method is an antibody recognizing the epitope of the first analyte, and the other specific binding partner is an antibody recognizing the epitope of the second analyte. In another application of that method two independent measurements are performed on a single analyte in a liquid sample. In that embodiment the respective ligand analog 65 component of the first and second redox reversible species are different ligand analogs of the targeted analyte. Where

12

the targeted analyte is a proteinaceous compound, the ligand analog component of the first redox reversible species is a peptide comprising a first epitope of the analyte, and the ligand analog of the second redox reversible species is a peptide comprising a second epitope of the analyte, and the specific binding partners are first and second antibodies, each recognizing respective first and second analyte epitopes.

The present osmium conjugates can also be used in a device for detecting or quantifying one or more analytes in a liquid sample. The device comprises

at least two redox reversible species, each capable of diffusion in said liquid sample at least in the presence of a respective predetermined analyte, said redox reversible species having respective redox potentials differing by at least 50 millivolts,

an electrode structure for contact with the liquid sample in said chamber, said electrode structure including a reference electrode and working electrodes dimensioned to allow diffusional recycling of a diffusible redox reversible species in a liquid sample in contact with the electrode system when a predetermined redox-reversible-species-dependent cathodic potential is applied to one working electrode and a predetermined redox-reversible-species-dependent anodic potential is applied to a second working electrode, said diffusional recycling of said species being sufficient to sustain measurable current through each working electrode, and

conductors communicating with the respective electrodes for applying said anodic potential and said cathodic potential and for carrying the current conducted by the electrodes.

The device can be constructed using procedures and techniques that have been previously described in the art for construction of biosensors employing electrometric detection techniques. Thus, for example, the device can include a chamber that has a receiving port, and the chamber is dimensioned so that it fills by capillary flow when the liquid sample is contacted with the sample receiving port. The electrode structure can be formed on a plate that defines a wall of the chamber so that the electrode structure will contact a liquid sample in the chamber. Thus, for example, the device can be constructed using the general procedures and designs described in U.S. Pat. No. 5,141,868, the disclosure of which is expressly incorporated herein by reference. The features of the present invention can also be incorporated into other electrochemical biosensors or test strips, such as those disclosed in U.S. Pat. Nos. 5,120,420; 5,437,999; 5,192,415; 5,264,103; and 5,575,895, the disclosures of which U.S. patents are expressly incorporated herein by reference. The device can be constructed to include the predetermined amounts of the redox reversible species and the specific binding partners. For example, a mixture of such reagents can be coated onto a wall of the sample chamber in said device during device construction, so that the liquid sample is contacted with the reagent mixture as it is delivered into the chamber for containing the sample. In one embodiment the device is constructed for quantifying a first analyte and a second analyte in liquid sample. The device comprises two redox reversible species, a first redox reversible species comprising a conjugate of a ligand analog of the first analyte and a second redox reversible species comprising a conjugate of a ligand analog of the second analyte, and a specific binding partner for each analyte so that each of said analyte analog conjugates are capable of binding competitively with its respective analyte to a specific binding partner.

In another application of the present osmium conjugates, they are used in conjunction with a device that further comprises a bipotentiostat in electrical communication with the conductors for applying a redox- reversible-speciesdependent-cathodic potential to one working electrode and a 5 redox-reversible-species-dependent-anodic potential to a second working electrode. The biopotentiostat can be programmed to apply a sequence of potentials to the respective working electrodes. More particularly, the bipotentiostat can be programmed to apply first cathodic potential to a first working electrode and a first anodic potential to a second working electrode, said first anodic and cathodic potentials corresponding to those potentials necessary to establish current flow to the sample due to diffusional recycling of the first redox reversible species. The bipotentiostat is also 15 programmed to apply a second cathodic potential to said first working electrode and a second potential to the second anodic electrode, said second cathodic and anodic potentials corresponding to those potentials necessary to establish current flow through the sample due to diffusional recycling 20 of the second redox reversible species. In an alternate embodiment the device includes first and second redox reversible species, and at least first and second electrode structures for contact with the liquid sample in the chamber, each of said electrode structures comprising a microarray of 25 working electrodes, and means for switching the bipotentiostat between the first and second electrode structures. In preferred device embodiments there is provided means for measuring current flow through the sample at each of the first and second potentials and preferably storing values for 30 said current flows in a register coupled to a microprocessor programmed to calculate analyte concentrations based on said values.

In still another embodiment the present conjugate is used in a kit for measuring the concentration of one or more <sup>35</sup> analytes in liquid sample. The kit comprises

at least two redox reversible species for contact with the liquid sample, each capable of diffusion in the liquid sample at least in the presence of a predetermined analyte, at least one of such species being a conjugate of a ligand analog of an analyte and a redox reversible label, said redox reversible species having respective redox potentials differing by at least 50 millivolts;

a specific binding partner for each analyte;

an electrode structure for contact with the liquid sample, said electrode structure including a reference electrode and working electrodes dimensioned to allow diffusional recycling of diffusible redox reversible species in the sample when a predetermined redox-reversible-species-dependent-cathodic potential is applied to one working electrode and a predetermined redox-reversible-species-dependent-anodic potential is applied to the second working electrode, said diffusional recycling of said species means sufficient to sustain a measurable current through the sample; and

conductors communicating with the respective electrodes for applying said anodic potential and said cathodic potential and for carrying the current conducted by the electrodes.

In one embodiment, the present redox reversible conjugate species are mixed with other electroactive species as a 60 novel composition for contact with the liquid sample. In another embodiment each of the redox reversible species and the specific binding partner for each analyte is mixed as a novel composition for contact with the liquid sample. Preferably, the redox reversible label of at least one of the 65 redox reversible species comprises an osmium complex of this invention.

14

Preparation of Os Mediator Labels

The Os mediator bis(bipyridyl) imidazolyl chloroosmium has been shown to be an excellent electron mediator for many oxide-reductase enzymes (U.S. Pat. No. 5,589,326). It has fast mediation kinetics (about 500 times faster than ferricyanide with glucose oxidase) and a relatively low redox potential (+150 mV vs. Ag/AgCl). It has also very fast electron transfer rate at electrode surface. More importantly, the organic ligands on Os mediator can be functionalized so that it can be covalently linked to other molecules without detrimental effects on redox properties of the Os center. These unique properties of Os mediator make it an ideal electrochemical indicator for sensors based on immunoaf-finity.

Os mediators with these new ligands were synthesized using the same procedure used for Os free mediator. Their synthesis consists of two major process steps as outlined below. Details of these processing steps are described below.

The first process step involves the synthesis of Os intermediate, cis-bis(2,2'-bipyridyl)dichloroosmium(II), from commercially available osmium salt using the following scheme. The intermediate product is isolated through recrystallization in an ice bath.

$$K_2Os^{IV}Cl_6 + 2bpy\frac{DMF}{\Lambda}[Os^{III}(bpy)_2Cl_2]Cl + 2KCl_2Os^{III}(bpy)_2Cl_2]Cl + 2KCl_2Os^{III}(bpy)_3Cl_2]Cl + Na_2S_2O_4 + 2H_2O_3Cl_2O_4 + 2H_2O_3Cl_2O_5 + 2H_2O_5 + 2H_2O_$$

$$2Os^{II}(bpy)_2Cl_2\downarrow +2Na^+ +2SO_3^- +4H^+ +2Cl$$

The second process step involves the reaction between Os intermediate and histamine or 4-imidazoleacetic acid (or a substituted bipyridine for preparation of the tris(bipyridyl) complexes) to produce Os mediators with the appropriate "handle". The desired product is then precipitated out from solution by addition of ammonium tetrafluoroborate.

$$Os^{II}(bpy)_2Cl_2 + histamine \frac{EtOH/H_2O}{\Delta}[Os^{II}(bpy)_2(histamine)]Cl_2$$

$$[Os^{II}(bpy)_{2}(histamine)Cl]Cl+NH_{4}BF_{4} \rightarrow [Os^{II}(bpy)_{2} + NH_{4}Cl]$$

These Os mediators can also be easily converted to oxidized form, i.e. Os(III) using nitrosonium tetrafluoroborate. However, this is unnecessary since the Os revert back to reduced form anyway at alkaline conditions during conjugation reactions. And it does not require oxidized form of Os(III) for the detection on the biosensor.

A. Simple Mixed Mediator Measurement

- Interdigitated array microelectrodes (IDA) are produced through photolithographic means by art-recognized methods, (See WO 97/34140; EP 0299,780; D. G. Sanderson and L. B. Anderson, *Analytical Chemistry*, 57 (1985), 2388; Koichi Aoki et al., *J Electroanalytical Chemistry*, 256 91988) 269; and D. Niwa et la., *J Electroanalytical Chemistry*, 167 (1989) 291. Other means which are standard in lithographic processing may also be used to produce the desired patterns of a conductor on insulator substrate.
  - 2. Reversible mediators are selected from those described herein and those described references (U.S. Pat. Nos.4,945, 045 and 5,589,325, the disclosures of which are incorporated herein by reference). Preferably two different mediators are selected with potentials which differ by at least 100

mV, more preferably at least 200 mV. Examples of suitable mediators include the Os(bipy)<sub>2</sub>ImCl of this invention and in U.S. Pat. No. 5,589,326, the disclosure of which is incorporated herein by reference, and ferrocene, described in U.S. Pat. No. 4,945,045 and EP 0142301, the disclosures of 5 which are incorporated herein by reference. Mixtures of these mediators are made in aqueous solution, for example phosphate-buffered saline (PBS). Concentrations between about 1 uM and 1000 uM may conveniently be measured.

3. The IDA is connected to a bipotentiostat, an instrument 10 capable of controlling the potential of two separate electrodes. Also provided is a reference electrode. This nonpolarizable electrode serves as the reference for the two applied potentials and may also serve as the counter electrode. Any non-polarizable electrode may be used, for 15 example Ag/AgCl, such as may be obtained from ABI/ Abtech. An auxiliary electrode can also be used for controlling current flow through the working electrodes. The mixtures are placed on the IDA electrode and the reference electrode also contacted with the mixture, or the IDA along 20 with the reference electrode may be dipped into the mixture.

4. To measure Mediator 1 (Os(bipy), ImCl)

A cathodic potential is applied to one set of fingers of the IDA which is capable of reducing mediator 1 (ca -50 mV vs. Ag/AgCl). An anodic potential is applied to the other set of fingers of the IDA which is capable of oxidizing mediator 1 but not mediator 2 (or any other mediators) (ca 250 mV vs Ag/AgCl). After a short time (msec to sec), a steady state current will be measurable which is dependent only on the opinore sequence of Gluc-Val-His-Leu-Thr (SEQ ID NO:1). concentration of mediator 1.

5. To measure Mediator 2 (Ferrocene)

A cathodic potential is applied to one set of fingers of the IDA which is capable of reducing mediator 2 but not mediator 1 (ca 250 mV vs. Ag/AgCl). An anodic potential is 35 applied to the other set of fingers of the IDA which is capable of oxidizing mediator 2 (ca 550 mV vs Ag/AgCl). After a short time (msec to sec), a steady state current will be measurable which is dependent only on the concentration of mediator 2.

Specific Binding Assay with Mixed Mediator Measure-

Specific Assay of HbAlc in a blood sample

- 1. IDA electrodes are provided as in Paragraph A above.
- 2. Conjugates of mediators 1 and 2 and haptens or specific 45 binding members are provided using art-recognized procedures for covalent coupling using either a homo-functional or hetero-functional linker. Specifically, a synthetic peptide corresponding to the N-terminal sequence of the  $\beta$ -chain of HbAlc is conjugated to the osmium complex. Similarly, a 50 synthetic peptide corresponding to the N-terminal sequence of HbA0 is conjugated to a second mediator, for example
- 3. Antibodies for the analytes (HbAlc and HbA0) which react specifically with the N-terminal peptides which have 55 been incorporated into the conjugate are provided by standard methods for producing polyclonal antibodies. In this case, sheep were immunized with carrier proteins to which were conjugated the synthetic peptide sequences for HbAlc and HbA0. Following the appropriate immunization sched- 60 ule, the sheep were bled, and the antibody isolated from the blood via ion exchange chromatography, followed by immunosorbent purification on a column of the same N-terminal peptide with a different linker.
- 4. Appropriate stoichiometry of the reaction was deter- 65 mined for the two reactions independently by methods standard for immunoassay development. A solution contain-

ing a fixed amount of labeled conjugate was mixed with a

solution with varying amounts of antibody, and, following an appropriate incubation period, the amount of free conjugate remaining was measured on the IDA electrode using the procedure described above. The amount of antibody just sufficient to achieve maximum inhibition of the conjugate (ca>80%) was selected.

16

5. Reagent solution 1 was made containing a mixture of the two conjugates in the appropriate concentrations. Reagent solution 2 was made containing a mixture of the two antibodies in the amounts determined above. A blood sample was diluted ca 20-fold in a solution of 25 mM citric acid/0.5% Brij-35. Following a 30 second incubation to allow for lysis and denaturation of the hemoglobin, to 66 uL of this diluted sample was added 33 uL of 1 M phosphate buffer, to adjust the pH back to neutral. 30 uL of antibody solution 2 was added, and the mixture allowed to incubate 30 sec. Then 30 uL of conjugate solution 1 was added, and the mixture measured on the IDA electrode. The concentration of HbAlc in the sample is related to the current measured from Mediator 1, and the concentration of HbA0 is related to the current from Mediator 2. The %HbAlc in the sample is related to the ratio of the measured amounts of Mediator 1 and Mediator 2.

## Application to HbAlc Assay

Hemoglobin Alc is a specific glycohemoglobin in which the glycosylation takes place at the N-terminal of hemoglobin b-chain. The antibody binds specifically to HbAlc has an To facilitate conjugation to other molecules, a nonnative amino acid has been added to the sequence, e.g., Cys, Lys, or Lys-MH, to produce Alc peptides including: 1) Gluc-Val-His-Leu-Thr-Lys-MH (SEQ ID NO:2); 2) Gluc-Val-His-Leu-Tbr-Lys (SEQ ID NO:3); 2) Gluc-Val-His-Leu-Thr-Cys (SEQ ID NO:4).

HbAlc assay requires measuring both Alc concentration ahd total hemoglobin concentration and reports the results as a ratio of these two measurements (%HbAlc). It is advan-40 tageous to assay both Alc and total hemoglobin using same principle because ratioing would minimize biases due to environmental effects. Thus antibody has been raised to bind specifically to hemoglobins with unglycosylated N-terminus, i.e. with an epitope sequence of Val-His-Leu-Tbr (SEQ ID NO:5). Similarly, nonnative amino acid is added to the sequence to facilitate conjugation. The peptides used for total hemoglobin measurement is termed as A0 peptide. A0 peptides that have been used in the preparation of Os mediator-peptide conjugates include Val-His-Leu-Thr-Cys (SEQ ID NO:6) and Val-His-Leu-Thr-Lys (SEQ ID NO:7).

#### Conjugation Chemistry and Conjugates

There are many types of conjugation chemistry that can be employed to link Os mediator to a peptide. The following two conjugation chemistries employed for the preparation of Os mediator-peptide conjugates have also been commonly used for preparing protein conjugates: 1) formation of amide bond by reactive ester with primary amine; 2) formation of thioether bond by maleimide with sulfhydryl group. Amide bond is preferred over thioether bond because amide bond is generally more stable. Based the preferred conjugation chemistry, the ligand on Os mediator can be functionalized with either a primary amine group or a carboxylic acid group. The best location for these functional groups is believed to be the C-4 or C-5 positions on the imidazole ligand of Os mediator, however, functionalization through the non-Os-complexed imidazole ring nitrogen atom can

(b)

17

also be carried out. Two different functionalized Os mediators were synthesized as described above.

Os mediator (a) was formed with histamine while Os mediator (b) was formed with imidazolacetic acid. However,

18

it was found that the imino nitrogen of the imidazole ring interferes with the activation of carboxylic acid group to reactive ester (i.e., N-hydroxysuccinimide ester) using carbodiimide. Thus, use of carboxylic acid functionalized Os mediator in the synthesis of Os mediator-peptide conjugates gave much less favorable results.

The amine group on histamine ligand of Os mediator readily reacts with N-hydroxysuccinimide (NHS) ester to form amide bond. Two types of crosslinkers have been employed to link Os mediator to peptides, (a) heterofunctional crosslinker, having a NHS ester at one end and the other end has a maleimide or a sulfhydryl group; and (b) homofunctional crosslinker, e.g. both ends have NHS esters.

In the case of heterofunctional crosslinker, the crosslinker is first reacted with Os mediator with histamine ligand (Os histamine) at 1:1 molar ratio. One particular point needs to be noted here. Os mediator in oxidized form, i.e. Os(III), can 20 instantly oxidize sulfhydryl group to form disulfide bond. It is important to keep Os center in the reduced form by addition of a small amount of reductant such as sodium dithionite during the conjugation processes. The reaction progress can be monitored by analytical reverse-phase  $^{\rm 25}$   ${\ \ \ }{\ \ \ }{\ \ \ }{\ \ \ }{\ \ \ }{\ \ \ }{\ \ \ }{\ \ \ }{\ \ \ }{\ \ \ }{\ \ \ }{\ \ \ }{\ \ \ }$  HPLC on a C18 column. Then the Os mediator-crosslinker adduct is isolated via preparative HPLC and the collected fraction is subsequently freeze-dried. Finally, the Os mediator-crosslinker adduct is reacted with the appropriate peptide to form Os mediator-peptide conjugate. Again, the product is isolated by collecting appropriate fraction in preparative HPLC and the collected fraction is then freeze-dried.

Two different heterofunctional crosslinkers have been used for the synthesis of Os mediator-peptide conjugates.

SMCC (succinimidyl 4-[N-maleimidomethyl]cyclohexane-1-carboxylate) is used for cystein-containing peptide, while SATA (N-succinimidyl S-acetylthioacetate) is used for maleimide-containing peptide. Three Os mediator-peptide conjugates (two with Ale peptide and one with A0 peptide) have been made using heterofunctional crosslinkers and their structure are shown below: (a) Os-SMMC-Alc; (b) Os-SATA-Alc, and (c) Os-SATA-AO.

-continued

$$\begin{array}{c|c} H & O & H \\ \hline \\ N & O & O \\ \hline \\ N & O$$

stable when they were stored as solutions. Analytical HPLC results indicated that these conjugates degrade. Mass spectroscopy confirmed that the instability is due to splitting of thioether bond present in these conjugates.

In order to avoid thioether bond in the conjugate, homofunctional crosslinker containing two NHS esters was used

However, it has been found that these conjugates were not 60 instead to prepare the conjugates. The crosslinker used was DSG (disuccinimidyl glutarate). In order to prevent the formation of crosslinked Os mediator, i.e. Os-crosslinker-Os, a large excess of homofunctional crosslinker was used in the reaction with Os histamine at 4:1 molar ratio. Under this condition, only the desired product, i.e. Os-crosslinker, was formed. The Os-DSG-Alc conjugate was similarly prepared using the procedure described earlier.

The preparation of analogous Os-DSG-A conjugate requires and extra step since the unglycated N-terminal amine of HbA<sub>0</sub> peptide is also reactive toward NHS ester. In this case, the N-terminal amine of HbAo peptide is first 20 protected by either a base-labile Fmoc<sup>1</sup> or an acid-labile Boc group. After reacting with Os-DSG adduct to form Os-DSG-A conjugate, the protecting group is then cleaved using appropriate deprotection method (adding base for Fmoc or acid for Boc). The peptides prepared by solid-phase 25 peptide synthesis already have N-terminal Fmoc protecting groups. The protecting groups are usually removed prior to cleavage of peptide from the resin beads, but they can also be left on if so desired. The HbA<sub>0</sub> peptide from Zymed has an intact Fmoc protecting group at N-terminal. Using this 30 strategy the Os-DSG-A<sub>0</sub> conjugate was successfully synthesized.

<sup>1</sup>Fmoc=9-flourenylmethyloxycarbonyl

<sup>2</sup>Boc=t-butyloxycarbonyl

Many analytes cannot be assayed using enzyme-based sensors. They require the development of affinity biosensors or immunosensors which are based on the selective binding of antigens to antibodies. The key to the detection of this binding event on electrochemical sensors is the inclusion of antigens labeled with redox labels. Bis(2,2'-bipyridyl) imidazolyl chloroosmium, a.k.a. Os mediator, possesses many properties that make it an excellent redox label for this purpose. In addition, a "handle" for linking it covalently to antigens can be added on without affecting its redox properties.

Several assay schemes can be used in affinity biosensors including, i) competitive binding assay (labeled antigen is competing for a limited number of binding sites); ii) sequential binding assays (labeled antigen is bound to excess binding sites); iii) heterogeneous assay (uses a separation step to separate bound and free labeled antigens); and iv) homogeneous assay (no separation step). The steps involved in a homogeneous sequential binding assay include binding the analyte to an antibody. The labeled antigen (analyte analog) binds to the remaining binding sites on the antibody. Finally the leftover free labeled antigen is detected at electrode surface. The resulting current will be a function of the amount of analyte present.

The detection of free labeled antigens can be achieved 60 using either direct detection or amplified detection methods. Direct detection requires the use of advanced electrochemical techniques such as ac voltammetry, differential pulse voltammetry, square wave voltammetry or ac impedance in order to reach a sensitivity of 5  $\mu$ M or less. Amplified 65 detection methods use dc amperometry with amplification through reaction with enzyme or chemical reductants or by

using interdigital array (IDA) microelectrodes. The preferred detection method is amplified amperometry through cycling of free Os mediator label by using IDA microelectrodes. However, amplified amperometry using Gluc-DOR enzyme can also be used. Fast mediation kinetics of Os mediator is very desirable because the magnitude of amplification is dependent on its mediation kinetic constant with the enzyme.

General Analytical HPLC Method for Osmium Conjugates All HPLC analysis were performed using a Beckman System Gold HPLC system consists of a 126 pump module and a 168 diod array detector module. Stationary phase is a Vydac analytical reverse-phase C18 analytical column. Other parameters are listed below.

Mobil Phase:  $A = 0.1\% \text{ TFA}^3 \text{ in } H_2O$   $B = 0.1\% \text{ TFA in } CH_3CN$ Flow rate: 1 mL/minGradient: 0-5 min: 10% B 5-45 min: 10% B -> 50% B at 1%/min 45-50 min: 100% BDetector: Channel A at 384 nm Channel B at 220 nm.

Synthesis of Bis(2,2'-bipyridyl)dichloroosmium

- 1. Charge a 1 L one-neck RB flask with 19.335 grams K<sub>2</sub>OsCl<sub>6</sub> (0.04019 mole) and 13.295 grams 2,2'-dipyridyl (0.08512 mole). Add 400 mL DMF to dissolve all reactants
- Heat the solution to reflux and then maintain reflux for 1 hour. Then turn off the heat and let solution cool to 30–40° C. at ambient.
- 3. Filter the reaction mixture using a medium grade glass-frit filter. Rinse the flask with additional 20 mL DMF and wash the filter.
- 4. Transfer the filtrate into a 3-L beaker. Charge another 2-L beaker with 22.799 grams of NaS204 and dissolve in 2 L deionized water. Add this solution to the beaker containing Os/DMF filtrate dropwise using a dropping funnel. Keep the solution stirring at all time.
- 5. Then cool the mixture in an ice bath for at least 3 hours. Add ice as necessary.
- 6. Filter the mixture "cold" using a ceramic filter with filter paper. Wash the content on the filter with 50 mL, water twice and 50 mL ether twice.
- 7. Dry the product under high vacuum at 50° C. overnight (at least 15 hours). Weigh the product and transfer into a brown bottle. Store in a desiccator at room temperature

45

Typical yield=16 gram or 70%.

Product is analyzed by UV-Visible spectroscopy and elemental analysis.

	UV-Vis:	
$\epsilon~(M^{-1}cm^{-1})$		Peak $\lambda$ (nm)
10,745		382
9,914		465
11,560		558
3,873		836

	EA:					
	С %	Н%	N %	C1 %	Os %	H <sub>2</sub> O %
Theoretical Actual	41.89 40.74	2.81 2.92	9.77 9.87	12.36 11.91	33.17	0 0.41

Synthesis of Bis(2,2'-bipyridyl)histamine chloroosmium

- Charge a 2 L one-neck RB flask with 11.3959 gram Os(bpy)<sub>2</sub>Cl<sub>2</sub> (0.0198 mole) and 4.9836 gram histamine (0.0448 mole). Add 500 mL ethanol to dissolve the <sub>25</sub> reactants. Then add 250 mL deionized water.
- 2. Heat the solution to reflux and maintain reflux for 6 hours. Let solution cool to RT at ambient.
- Remove all ethanol using rotary evaporation. Then transfer the solution into a 500 mL beaker. Dissolve
   136 gram NH<sub>4</sub>BF<sub>4</sub> in 20 mL water. Add dropwise to Os solution. Precipitate forms. Cool in an ice bath for 30 min. Filter the mixture using a ceramic filter with filter paper. Wash the content on filter with ~20 mL as water twice.
- 4. Dry under high vacuum at  $50^{\circ}$  C. overnight (at least 15 hour).
- 5. Weigh the product and transfer to a brown bottle. Store in a desiccator at room temperature.

Typical yield=7.6 gram or 52%.

Product is analyzed by UV-visible spectroscopy and HPLC.

UV-Vis:	Peak λ (nm) 355 424 514	$\epsilon (M^{-1}cm^{-1})$ 7,538 7,334 7,334	50
HPLC:	722 Elution time Purity by HP	2,775 = 18.0 min LC range from 65–85%	30

Preparation of [Os(bpy)<sub>2</sub>(histamine)Cl]-heterofunctional <sup>55</sup> Crosslinker Adduct

- 1. Weigh 0.1167 g  $[Os(bpy)_2(histamine)Cl]BF_4$  (0.162 mmol) and transfer to a 5 mL Reacti-Vial. Add 1.0 mL DMF to dissolve the reactant. Add 25  $\mu$ L triethylamine.
- Add 0.0508 g SMCC(0.150 mmol)or 0.0390 g SATA (0.168 mmol). Stir the reactants at RT for 2 hours. Inject a sample into HPLC to monitor reaction progress.
- 3. If reaction is complete, dilute the solution with 0.1% 65 TFA buffer to a final volume of 4.5 mL. Inject into preparative HPLC and collect the product peak.

- 4. Freeze dry the collected fraction overnight.
- 5. Weigh the product and transfer to a brown bottle. Store in a desiccated bag at -20° C.
- 5 Typical yield=40 mg or 25%.

Product is analyzed by HPLC and ES/MS.

0		HPLC	ES/MS
	Os-SMCC:	Elution time = 32.1 min	$m^+/e = 434.2$
	Os-SATA:	Elution time = 27.5 min	$m^+/e = 382.8$

Preparation of [Os(bpy)<sub>2</sub>(histamine)Cl]-homofunctional Crosslinker Adduct

- Weigh 0.2042 g DSG (0.626 mmol) ) and transfer to a 5 mL Reacti-Vial. Add 0.75 mL DMF to dissolve the reactant.
- Weigh 0.1023 g [Os(bpy)<sub>2</sub>(histamine)Cl]BF<sub>4</sub> (0.142 mmol) and transfer to a separate 5 mL Reacti-Vial. Add 1.0 mL DMF to dissolve the reactant. Add 25 μL triethylamine. Then add Os/DMF solution dropwise to DSG/DW solution with constant stirring. After reacting for 2 hours at RT, inject a sample into HPLC to monitor reaction progress.
- 3. If reaction is complete, dilute the solution with 0.1% TFA buffer to a final volume of 4.5 mL. Inject into preparative HPLC and collect the product peak.
- 4. Freeze dry the collected fraction overnight.
- 5. Weigh the product and transfer to a brown bottle. Store in a desiccated bag at -20° C.

Typical yield=45 mg or 35%.

Product is analyzed by HPLC and ES/MS.

	HPLC	ES/MS
Os-DSG:	Elution time = 27.1 min	$m^+/e = 429.2$ and 859.6

Preparation of Os-SATA-Alc Conjugate

- Weigh 40.5 mg Os-SATA (0.0529 mmol) and transfer to a 5 mL Reacti-Vial with stir bar. Add 1.0 mL PBS (pH 7.5) to dissolve. Add 20 mg Na<sub>2</sub>S<sub>2</sub>O<sub>4</sub> in order to keep Os in reduced form.
- 2. Add 1.0 mL deacetylation buffer (PBS pH7.5+0.5 M hydroxylamine and 25 mM EDTA) to deprotect the sulfhydryl group. Inject a sample into analytical HPLC to determine whether deprotection is complete by appearance of a new peak at 25.8 min.
- 3. Add 45 mg HbAlc-MH peptide (0.0474 mmol) and let react at RT for 1 hour. Inject a sample into analytical HPLC to monitor reaction progress.
- 4. If reaction is complete, dilute the mixture with 0.1% TFA buffer to a final volume of 4.5 mL. Inject into preparative HPLC to collect product peak.
- 5. Freeze dry the collected fraction overnight (at least 15 hour).
- 6. Weigh the product and transfer to a brown bottle. Store in a desiccated bag at −20° C.

Typical yield=12 mg

Product is analyzed by HPLC and ES/MS.

	HPLC	ES/MS
Os-SATA-Alc:	elution time = 27.6 min	$m^{+}/e = 559.1$ and $838.5$

### Preparation of Os-SMCC-Alc Conjugate

- 1. Weigh 39.0 mg Os-SMCC (0.0452 mmol) and transfer to a 5 mL Reacti-Vial with stir bar. Add 1.0 mL PBS (pH 6.0) to dissolve.
- Add 30.0 mg Hblc-Cys peptide (0.0450 mmol). Let 15 reaction proceed at RT for 2 hours. Inject a sample into analytical HPLC to monitor reaction progress.
- 3. If reaction is complete, dilute the mixture with 0.1% TFA buffer to a final volume of 4.5 mL. Inject into preparative HPLC to collect product peak.
- Freeze dry the collected fraction overnight (at least 15 hour).
- 5. Weigh the product and transfer to a brown bottle. Store in a desiccated bag at  $-20^{\circ}$  C.

Typical yield=12 mg

Product is analyzed by HPLC and ES/MS.

	HPLC	ES/MS
Os-SMCC-Alc:	elution time = 27.6 min	$m^+/e = 480.5$ and 534.4

### Preparation of Os-SMCC-Ao Conjugate

- 1. Weigh 37.0 mg Os-SMCC (0.0426 mmol) and transfer to a 5 mL Reacti-Vial with stir bar. Add 1.0 mL PBS (pH=6.0) to dissolve.
- Add 24.3 mg HbAo-Cys peptide (0.0425 mmol). Let 40 reaction proceed at RT for 2 hours. Inject a sample into analytical HPLC to monitor reaction progress.
- 3. If reaction is complete, dilute the mixture with 0.1% TFA buffer to a final volume of 4.5 mL. Inject into preparative HPLC and collect the product peak.
- Freeze dry the collected fraction overnight (at least 15 hour).
- 5. Weigh the product and transfer to a brown bottle. Store in a desiccated bag at  $-20^{\circ}$  C.

Typical yield=15 mg

Product is analyzed by HPLC and ES/MS.

	HPLC	ES/MS
Os-SMCC-A <sub>o</sub> :	elution time = 27.9 min	m <sup>+</sup> /e = 360.7 and 720.5

## Preparation of Os-DSG-Alc Conjugate

- 1. Weigh 32.0 mg Os-DSG (0.037 mmol) and transfer to a 5 mL Reacti-Vial with stir bar. Add 0.75 mL DMF to dissolve. Add 25  $\mu$ L triethylamine.
- Add 26.5 mg HbAlc-Lys peptide (0.0349 mmol). Let 65 reaction proceed at RT for 2 hours. Inject a sample into analytical BPLC to monitor reaction progress.

26

- 3. If reaction is complete, dilute the mixture with 0.1% TFA buffer to a final volume of 4.5 mL. Inject into preparative HPLC and collect the product peak.
- 4. Freeze dry the collected fraction overnight (at least 15 hour).
- 5. Weigh the product and transfer to a brown bottle. Store in a desiccated bag at -20° C.

Typical yield=16 mg

Product is analyzed by HPLC and ES/MS.

	HPLC	ES/MS
Os-DSG-Alc:	elution time = 23.5 min	m <sup>+</sup> /e = 501.8 and 752.8

Preparation of Os-DSG-Ao Conjugate

- 1. Weigh 52.0 mg Os-DSG (0.0605 mmol) and transfer to a 5 mL Reacti-Vial with stir bar. Add 1.0 mL DMF to dissolve. Add 25  $\mu$ L triethylamine.
- 2. Add 49.1 mg Fmoc-HbA<sub>0</sub> peptide (0.0606 mmol). Let reaction proceed at RT for 2 hours. Inject a sample into analytical HPLC to monitor reaction progress by the appearance of peak at 40.3 min for Os-DSG-A<sub>0</sub>(Fmoc).
- 3. If reaction is complete, inject additional 100 μL triethylamine. After 1 hour, inject sample into analytical HPLC to determine whether all Fmoc protection group is removed by disappearance of the peak at 40.3 min.
- 4. If removal of Fmoc is complete, dilute the mixture with 0.1% TFA buffer to a final volume of 4.5 mL. Inject into preparative HPLC to collect product peak.
- 5. Freeze dry the collected fraction overnight (at least 15 hour)
- 6. Weigh the product and transfer to a brown bottle. Store in a desiccated bag at -20° C.

Typical yield=16 mg

Product is analyzed by HPLC and ES/MS.

15		HPLC	ES/MS
	Os-DSG-A <sub>o</sub> :	elution time = 23.2 min	m <sup>+</sup> /e = 447.4 and 670.3

Synthesis of bis(4,4'-dimethyl-2,2'-bipyridyl) 4-methyl-4'-carboxylpropyl-2,2'-bipyridyl osmium [Os(dm-bpy)2 (mcp-bpy)]Cl2

Potassium hexachloroosmium was reacted with 4,4'-dimethyl-2,2'-dipyridyl at 1:2 molar ratio by refluxing in DMF. The potassium chloride precipitate was filtered and the dimethyl-bipyridyl dichloroosmium complex was reduced from +3 oxidation state to +2 oxidation state using excess sodium dithionite. The product was recrystallized in DMF/water mixture at 0° and recovered by filtration.

4,4'-Dimethyl-2,2'-bipyridyl dichloroosmium was reacted with 4-methyl-4'-carboxylpropyl-2,2'-dipyridyl by refluxing in ethylene glycol. The solvent was removed by rotary evaporation. The product was dissolved in DMF and precipitate in ethyl ether. The product was dried in a vacuum oven overnight.

Analyticals: Product and intermediate product were analyzed by HPLC and mass spectroscopy for purity and identity of the compound.

Os(dm-bpy)2Cl2: Theoretical MW=629.6, MS showed 8 isotope peaks with most abundant peak at 630. HLPC elution time at 29.94 min with a purity of 90%+

Os(dm-bpy)2(mcp-bpy): MS confirmed the MW at 814.5 and HPLC showed a purity greater than 85%.

## Synthesis of biotin-Os Complex Conjugate Biotin-Os(dm-bpy)2(mcp-bpy)Cl2

The carboxyl group was activated by reacting the above Os complex with dicyclohexylcarbodiimide in the presence of N-hydroxysuccinimide. The active ester Os complex was isolated using preparative HPLC method and then reacted with amine-containing biotin to form the final conjugate.

Experiment to Independently Measure the Concentration of Two Electroactive Conjugate Species

Os(bipy)HisCl-DSG-HbAlc was prepared as described above.

Ferrocene-AMCHA-DADOO-biotin was prepared from ferrocene monocarboxylic acid, the crosslinker aminomethylcyclohexylic acid, the chain extender 1,8-diamino-3,6-DiOxoOctane and biotin as described elsewhere.

Mixtures of the two conjugates were prepared to evaluate the ability of the method of the invention to independently measure the concentration of the conjugates, and make <sup>30</sup> corrections for variations in reagent amounts, electrode response, and environmental conditions.

Part 1: Simple Mixed Conjugate Response

The following matrix of solutions was prepared in 10 mM 35 phosphate buffer with 150 mM NaCl and 0.5% Brij-35, a non-ionic surfactant.

Ferrocene	Os-DSG-	Ferrocene-	Os-DSG-
Biotin	HbAlc	Biotin	HbAlc
uM/l	uM/l	uM/l	uM/l
12.5	0	0	0
12.5	6.25	0	6.25
12.5	12.5	0	12.5
12.5	25	0	25
Ferrocene	Os-DSG-	Ferrocene-	Os-DSG-
Biotin	HbAlc	Biotin	HbAlc
uM/l	uM/l	uM/l	uM/l
50	0	25	0
50 50	0 6.25	25 25	0 6.25
	~		

An Interdigitated array (IDA) microelectrode was fabricated according to the procedures described. In addition to the IDA, the chip had a silver/silver chloride electrode on the surface to function as the reference electrode and counter electrode. This electrode was produced with the same lithographic process, and then electroplated with silver and silver chloride according to standard techniques. The IDA was connected to a bipotentiostat capable of controlling the potential relative to the reference and measuring the current at each of the electrodes of the IDA. Aliquots of the solutions were placed onto the surface of the chip, such that the IDA and the reference electrodes were covered.

Measurements were made by first applying –100 mV (vs. Ag/AgCl) to one electrode of the IDA, and 200 mV to the other electrode for a period of 30 seconds. At this time, current was measured at each electrode. Then 200 mV was applied to one electrode, and 550 mV to the other. After 30 seconds, current was again measured. See FIG. 9 for a summary of the results, which clearly demonstrate that the concentrations of the two mediators can be independently measured with this method.

## Part 2. Concentration Co-variance of Dual Mediators on IDA Electrodes

In this experiment, it was demonstrated that by making a mixture of known concentrations of two different mediators, and measuring different dilutions of that mixture by the method of the invention, the ratio of the concentrations of the mediators remains constant. (Internal standard application).

The same two mediator conjugates were used as in Part 1. (Os-DSG-Alc and Fc-Bi)

From a solution containing 40 uM of each conjugate, solutions containing 27 uM, 32 uM, and 36 uM of each conjugate were prepared in the same buffer (PBS/Brij).

The solutions were measured as in the previous example. Each solution was measured on 5 different IDA electrodes. The results are presented as the means, standard deviations, and coefficient of variation for each solution separately, and for all solutions pooled over all electrodes.

Individual concentrations		Os-DSG- Alc	Fc-Bi	Os/FC
28 uM	Mean	156	85	1.84
	S.D.	17.5	13.2	0.08
	% C.V.	11.2	15.5	4.4
32 uM	Mean	165	88	1.88
	S.D.	11	7.2	0.04
	% C.V.	6.7	8.2	2.0
36 uM	Mean	189	102	1.85
	S.D.	12.5	6.9	0.04
	% C.V.	6.6	6.7	2.3
40 uM	Mean	208	110	1.90
	S.D.	9.5	5.5	0.06
	% C.V.	4.6	5.0	3.4
Pooled Concentrations	Mean	182	97	1.87
	S.D.	24.4	13.2	0.06
	% C.V.	13.4	13.5	3.4

This example clearly demonstrates that the internal standard effect of measuring two conjugates or mediators and calculating the ratio gives significantly improved precision of measurement, not only within each solution (compensation for variation between electrodes) but over all solutions (compensation for variation in sample dilution or amount).

## Part 3. Temperature Compensation

It was desired to show the effectiveness of the method in compensating for environmental influences such as Temperature variation on the accuracy or the measurement.

The same two conjugates were prepared in solution at 40 uM as before. They were measured as before on IDA electrodes, either at room temperature or warmed to 35–40 C. on a heated metal plate prior to the measurement. The solutions were also warmed to 37 C. prior to application to the electrodes.

	Room Temperature (23 C.)	Warmed (35–40) C.	Ratio of response Warm/RT
Os-DSG-Alc	261	387	1.45
Fc-Bi	179	268	1.5
Ratio Os/Fc	1.46	1.44	0.99

As demonstrated by the results, the measured values 10 increase by almost 50% in the case of the warmed samples, which would lead to a large measurement error. However the use of the internal standard and ratio calculation effectively eliminates the temperature dependence of the result.

Immunoassay Detection of HbAlc with Osmium Mediator Conjugates

The goal of all diabetic therapy is to maintain a near normal level of glucose in the blood. Home blood glucose kits are available to monitor the current glucose values and are valuable for diabetics to adjust day to day insulin doses and eating habits. Unfortunately, since the tests only measures a point in time result, it does not tell them the overall effectiveness of their actions in maintaining glycemic control. Measurement of glycosylated hemoglobin is now becoming widely accepted as an index of mean blood glucose concentrations over the preceding 6–8 weeks and thus provides a measure of the effectiveness of a diabetic's total therapy during periods of stable control. Since monitoring a diabetic's glycated hemoglobin can lead to improved glycemic control, the ADA recommends routine measurements of four times a year up to once a month for less stable type I diabetics.

Several technologies are available for the measurement of glycated hemoglobin. They include immunoassays for HbAlc (TinaQuant, BMC; DCA2000, Ames; and Unimate, Roche), ion exchange (Variant, BioRad; Eagle Diagnostics), and affinity chromatography (ColumnMate, Helena; GlyHb, Pierce).

One objective of this project is to develop a simple to use disposable strip for electrochemical detection of HbAlc for use in both physician offices and the home.

The most significant parameter for assessing patient condition is ratio of HbAlc to HbA<sub>0</sub>, and thus the measurement of both glycated (HbAlc) and nonglycated (HbA0) values is required to calculate the ratio. This requires two separate measurements. It is preferable to use the same technology to measure both the glycated and nonglycated fractions, thus removing some sample and environmental interferences.

Measurement of HbAlc via electrochemical immunoassay is described below. Electrochemical HbA0 immunoassay measurements are carried out using the same methods as that for HbAlc. The concentrations of HbA<sub>0</sub> are significantly higher. One alternative to  $A_0$  measurements using immunoaffinity would be to measure total hemoglobin directly using biamperometry or differential pulse voltammetry. This can be easily accomplished since hemoglobin is readily oxidized by  $[0s(bpy)_2(im)Cl]^{2+}Cl_2$ .

The N-terminal valine of the  $\beta$ -chain of hemoglobin A is the site of glycosylation in HbAlc, and serves as a recognition site for the antibody. In whole blood the N-terminal valine is not accessible for the antibody to bind. Access is gained by lysing the red cells to release the hemoglobin followed by a conformation change (denaturing or unraveling) to adequately expose the HbAlc epitope. Dilution of the sample may occur as part of the lysing/denaturing process or may be required post denaturing to prepare the sample for the antibody (adjust pH, other) or bring the sample into a range suitable for electrochemical immunoassay. In one embodiment, a fixed amount of antibody is incubated with the prepared sample and it binds to the HbAlc epitopes of the sample. The free antibody and the antibody bound sample is then combined with the osmium peptide conjugate (Alc or  $A_0$ ) to allow the remaining unbound antibody to bind to the mediator label. When the mediator is bound to the antibody (a macromolecule), it can not freely diffuse to interact with the electrode and thus currents generated are significantly reduced. The remaining unbound mediator label is therefore proportional to the concentration of HbAlc in the sample. The unbound mediator can be measured electrochemically either through an enzyme amplification method or directly using an interdigitated array electrode with bipotentiostatic control.

An electrochemical HbAlc immunoassay response was demonstrated on gold electrodes using enzyme amplification in a biamperometric mode. The experimental conditions were not thoroughly optimized and the assay components were premixed in microcentrifuge tubes and then pipette onto the gold 4.95 mm<sup>2</sup> E-cells. The experimental conditions for this assay are shown in Table 1. Table 2 shows the dose response data for the low, medium, and high HbAlc samples. FIG. 4 shows the dose response with two additional points LL and HH which represent a diluted low and a concentrated high sample. The higher currents for LL may possibly be explained by a reduction in blood proteins (due to dilution) leading to a reduction in electrode fouling.

TABLE 1

Dose Response Conditions						
Sample Preparation (denaturing)	Reagents	Electrochemical Measurement				
<ol> <li>20 μL Lysed blood for L, M, H samples (previously frozen whole blood</li> <li>18 μL of L (LL) and 22 μL of H for (HH)</li> <li>480 μL 1.5 M LiSCN with 0.1% Tween</li> <li>Mix and allow to denature for 10 minutes (Vortex)</li> </ol>	<ol> <li>50 μL 12.5 μM PAB     IS<alc>in PBST</alc></li> <li>50 μL denatured Blood</li> <li>20 μL 40 μM Os-DSG-     Alc in DI H<sub>2</sub>O</li> <li>20 μL 1M Glucose in     DI H<sub>2</sub>O</li> <li>20 μL Glucdor/PQQ     (1.7 mg/ml/0.17 mg/ml)</li> </ol>	<ol> <li>VXI Waveform         E-450 mV for 60s</li> <li>Insert Gold Electrodes         WE = 1.5 × 3.3 mm</li> <li>Apply 20 μL Reagent</li> <li>Start biamperometric         measurement mode</li> <li>Extract 60 sec data</li> </ol>				

TABLE 2

	Blood Dose Response Data									
Separate denat					turant	A	ll Data			
g/L	#1	#2	#3	#4	Mean	$^{\mathrm{SD}}$	CV	Mean	SD	CV
Current @ 60 seconds (nA)										
6.49 6.49	76.28 80.30	78.34 82.97	84.79 86.82	78.47 83.48	79.47 83.48	3.69 2.69	4.64 3.22	81.54	4.67	5.73
6.49 6.49	83.25 76.66	85.49 71.72	90.05 78.24	86.67 76.56	86.67 76.55	2.94 1.44	3.40 1.88			
12.34 12.34	95.61 98.59	95.05 106.29	93.06 103.81	94.02 102.08	94.44 102.08	1.13 3.60	1.20 3.53	98.31	4.19	4.26
12.34 12.34	95.80 93.16	103.14 96.2	99.90 103.10	99.32 97.41	99.32 97.41	3.06 4.16	3.08 4.27			
18.20 18.20	100.06 115.43	110.83 116.93	119.08 116.77	112.52 116.26	112.52 116.26	9.29 0.71	8.26 0.61	113.48	5.08	4.48
18.20 18.20	116.12 118.13	109.72 112.16	112.07 109.8	112.21	112.21 112.93	2.78 3.61	2.48 3.20			
	Ca	lculated I	HbAlc (g/o	IL)						
6.49 6.49 6.49 6.49	4.46 5.94 7.02 4.60	5.22 6.91 7.84 3.89	7.58 8.33 9.51 5.18	5.26 7.23 8.72 4.56	5.63 7.10 8.27 4.56	0.99	24.00 13.87 13.05 11.58	6.39	1.71	26.80
12.34 12.34	11.55 12.64	11.34 15.46	10.61 14.56	10.97 13.03	11.12 13.92	0.33 0.41 1.32	.3.72 9.48	12.54	1.54	12.25
12.34 12.34	11.62 10.65	14.31 11.77	13.12 14.29	12.58 12.12	12.91 12.21	1.12 1.53	8.70 12.50	10.10	1.06	10.20
18.20 18.20 18.20	13.18 18.82 19.07	17.13 19.37 16.72	20.15 19.31 17.58	20.54 19.00 17.16	17.75 19.12 17.63	3.41 0.26 1.02	19.19 1.36 5.78	18.10	1.86	10.29
18.20	19.81	17.62	16.75	17.42	147.90	1.32	7.40			

n = 16, 4 denaturation for each HbAlc sample  $\times$  4 replicates each, Y = 2.82  $\times$  + 62.54, See fie 4435051 A.xls

Blood lysis is necessary to release the hemoglobin followed by denaturing to expose the HbAlc epitope. Lysis can easily be accomplished via surfactants, osmotic effects of 40 dilution with water, and directly by many denaturants. Blood lysed through a freeze/thaw cycle was shown not to significantly interfere with the biamperometric measurement ("open rate" with and without lysed blood was almost identical). Conversely, denaturing the lysed blood with a variety of known denaturants to expose the HbAlc epitope has shown significant suppression of the electrochemical response, inhibiting measurement of an HbAlc dose response. Only LiSCN and citric acid from the list of 50 evaluated denaturants shown in Table 3 was able to expose the Alc epitope and minimize protein fouling enough to measure an HbAlc dose response.

Denaturing the sample for antibody recognition without severely fouling the electrode surface is important for successful development of an HbAlc immunoassay. Although LiSCN has been used almost exclusively to show feasibility, it has many limitations that would hinder its use in the disposable. Citric acid, a solid at RT may offer benefits as a denaturant if it could be dried onto a strip followed by a diluent to adjust the pH to neutral. Acid or base blood denaturing followed by a final pH adjustment with a buffered diluent is an area worth further evaluation. One problem that was initially encountered was precipitation in adjusting the pH back to neutral, which can be overcome by using a different buffer or with the addition of surfactants.

TABLE 3

Blood Denaturants				
Method	Comments			
KSCN	Initial work did not show a dose response with KSCN denatured blood.			
	KSCN has a larger negative effect on the electrochemical response than LiSCN.			
	Literature shows that LiSCN is more effective than			
	KSCN (concentrated efforts on LiSCN).			
DCA2000	Denaturing of blood not evident with the higher blood			
Buffer	concentrations required for this assay. Higher			
	concentrations of LiSCN are shown below.			
LiSCN	Method used by Ames DCA2000 HbAlc immunoassay.			
Citric, Sulfuric, Hydrochloric,	Blood HbAlc dose response (high/low) was seen with citric acid and was comparable to the response with			
& Perchloric	Liscn			
Acid	Evidence of blood denaturing was seen by all: "solution			
	turned brown." Citric acid is preferred.			
	Adjustment of pH to neutral after denaturing			
	also saw problems of precipitation. Enzyme mediated			
	responses with Gluc-Dor at pH 5.7 reduces response 50% compared to pH 7–8.			
	Citric acid blood denaturing method is shown in FIG. 5.			
Pepsin/Citric	Roche HbAlc immunoassay uses pepsin/citric acid to			
Acid	hemolyze and proteolytically degrade hemoglobin to glycoproteins accessible by the antibody.			
	Denaturation was apparent by the color change to a			
	brownish red solution.			
	Hemoglobin Alc dose response (high/low) was obtained comparable to LiSCN and citric acid denaturants. The procedure was identical to that of citric acid used			
	above with the exception of pepsin added to the acid.			
	Results were identical to that of citric acid.			

TABLE 3-continued

Blood Denaturants						
Method	Comments					
TTAB (Tetra decyltrimethyl ammonium bromide)	Method of denaturing used in the TinaQuant HbAlc turbidimetric immunoassay.  Evidence of denaturing: "solution turned green" TTAB concentrations 0.0125–0.2% severely suppressed enzyme mediated (Glucdor/PQQ/Glucose)					
	biamperometric measurements. Open rates were 16–50 nA compared to 140 nA without TTAB.					
NaOH	Evidence of denaturing: "solution turned brown."  NaOH does not adversely effect the enzyme mediated electrochemistry. Even at high pH the open rates do not change, although pH adjustment will probably be required to bring it within an optimal range for the antibody.					
	NaOH denatured blood suppresses the open rates probably due to protein fouling.  Lowering the pH to neutral tends to cause some precipitation.					

**34** n the

the severity of denaturing in the sample should be the first approach. Surface conditions that are hydrophobic will favor adhesion of the proteins and thus fouling may be minimized with electrode surfaces of higher surface energies. This explains why gold electrodes shows less fouling with denatured blood than palladium. Reduction of protein fouling may be achieved by changing or protecting the electrode surface. Modifications that make the surface more hydrophilic should reduce the amount of fouling and can be accomplished by argon or oxygen plasma treatment or corona treatment. Selective coatings that could block the proteins from reaching the electrode surface can usually partially circumvent the problem have been used in the field to reduce fouling. Unfortunately, dramatic decreases in 15 responses greater than seen with the denatured blood proteins are normally noted with their use. Hydrophilic coatings such as PEO were also evaluated and showed some improvement, but have similar problems of decreased magnitude and precision caused by forcing reagents to diffuse through the polymers. Reagents dispensed and dried over the electrodes may help reduce the magnitude of protein fouling with less negative effects.

TABLE 4

Effective Blood Denaturing Procedure for 2% Blood						
LiSCN (One Step)	LiSCN (Two Step)	Citric Acid (2 Step)				
40 μL 6M LiSCN	960 μL 1.5M LiSCN	200 μL 0.2M Citric Acid				
20 μL 5% Tween in PBS	20 μL 5% Tween in PBS	20 μL 5% Tween in PBS				
20 μL Blood	20 μL Blood	20 μL Blood				
Mix (vortex) and allow to denature	Mix (vortex) and allow to denature	Mix (vortex) and allow to				
for 10 minutes. Dilute with 920 μL	for 10 minutes.	denature for 10 minutes. Dilute				
DI H <sub>2</sub> O.		with 760 μL 8X PBS (0.1%				
-		Tween)				
Denaturing time was not optimized.	Denaturing time was not optimized.	No optimization studies were				
Limited data supports longer times	Data indicates shorter times may be	performed.				
for better precision using this	adequate.	F				
method.	1					

PBS = 10 mM Phosphate Buffer, 2.7 mM KCl, 137 mM NaCl pH = 7.4 Increased level of surfactant (5% Tween) reduces or eliminates precipitate.

Electrode fouling caused by denatured blood proteins adsorbing to the electrode surface can impede electron transfer and thus decrease electrode sensitivity. Electrode fouling or passivation occurs more or less immediately 45 following sample contact with the surface thus minimizing

Mediator concentration dose response, inhibition with antibody and reversal with a BSA-Alc polyhaptan were evaluated and summarized in Table 5. The Os-DSG-Alc is stable in a lyophilized form and when frozen in solution at  $-20^{\circ}$  C. (40 and 80  $\mu$ M).

TABLE 5

Osmium Mediator Labels						
Mediator Label	Concentration Response	Inhibition with Antibody	Reversal	Comments		
Os-SMCC- Alc	Linear	PAB IS (≦92%) PAB DE (≦97%) MAB (≦50%)	Yes with BSA- Alc polyhaptan	% = Inhibition values ranged from 16% to 97% depending on age of Os-SMCC stock solution. Degrades in solution.		
Os-SATA- Alc	Linear	PAB IS (≦44%)	Yes with BSA- Alc polyhaptan	Stability similar to SMCC.		
Os-DSG-Alc	Linear	PAB IS (≦91%) PAB DE (≦87%) MAB (≦78%)	Yes with BSA- Alc polyhaptan	More stable than conjugate made with SATA and SMCC crosslinker but still degrades in solution.		
Os-SATA-A <sub>0</sub>	Linear	Yes with Sheep $B < HbA_0 > (\le 84\%)$ . No with Zymed rabbit antibodies	No with A <sub>0</sub> HB-peptide#1	${ m A_0}$ conjugate was found to be unstable in solution. Conjugate was not lyophilized.		

Polyclonal DE (ion-exchange) purified sheep antibody is used in the TinaQuant HbAlc assay. IS (immunosorbent) antibody is prepared using standard IS purification methodology. Samples of a monoclonal antibody were also obtained for evaluation. Inhibition curves were performed in solution 5 with all mixing occurring in microcentrifuge tubes. Assays were measured by applying 20 μL onto 6 mm<sup>2</sup> palladium electrodes with the conditions shown in Table 5. Inhibition curves with the three hemoglobin Alc antibodies (PAB IS, PAB DE, and MAB) were generated by fixing OS-DSG-Alc at 5 µM and varying the antibody concentration. Both PAB IS and MAB showed the expected stoichiometric relationship for inhibition with the osmium peptide conjugate indicating efficient and fast binding of the antibody to the Alc peptide. The polyclonal IS and monoclonal both showed 15 steep inhibition curves with maximum change being reached close to 5 μM. Additional antibody above 5 μM showed little effect on increasing the inhibition. The less purified PAB DE antibody had a much smaller slope and as expected required more than 3 times the amount to get close to maximum 20 inhibition. FIG. 6 shows the inhibition curves for each of the HbAlc antibodies tested. From the inhibition curves we were able to select reasonable concentrations of antibody for maximum reversal with Alc samples.

36

Inhibition curves were also performed for the Os-SMCC-Alc (Max=97%) and OS-SATA-Alc (Max=44%) mediator labels. Stability of the mediator labels were also evaluated by monitoring % inhibition values over time. All of the mediator labels showed some degradation when stored in dilute solutions (40  $\mu M$ ) at RT. Samples frozen at  $-20^{\circ}$  C. appear to be stable.

For demonstrating inhibition reversal, antibody concentrations of 4  $\mu$ M for both PAB IS and MAB and 15  $\mu$ M for PAB DE were chosen from the inhibition curves shown above. Reversal curves were then generated using a series of dilutions of BAS-Alc polyhaptan with a ~1:1 Alc:BSA. The BSA-Alc acts as our sample and binds to the antibody. FIG. 10 shows the reversal curves for the three antibodies.

While these feasibility studies for a HbAlc immunoassay used an enzyme mediated amplification method. (Glucdor/PQQ/glucose was used to regenerate reduced mediator after oxidation at the electrode surface providing a higher diffusion controlled current is given by the cottrell equation), they are considered to be indicative of results attainable with the use of IDA electrodes with bipotentiostatic control in accordance with this invention.

#### SEQUENCE LISTING

```
<160> NUMBER OF SEO ID NOS: 7
<210> SEO ID NO 1
<211> LENGTH: 4
<212> TYPE: PRT
<213> ORGANISM: Homo sapiens
<220> FEATURE:
<221> NAME/KEY: CARBOHYD
<222> LOCATION: (1)..(1)
<223> OTHER INFORMATION: Glucose
<400> SEQUENCE: 1
Val His Leu Thr
<210> SEO ID NO 2
<211> LENGTH: 5
<212> TYPE: PRT
<213> ORGANISM: Homo sapiens
<220> FEATURE:
<221> NAME/KEY: CARBOHYD
<222> LOCATION: (1)..(1)
<223> OTHER INFORMATION: Glucose
<220> FEATURE:
<221> NAME/KEY: SITE
<222> LOCATION: (5)..(5)
<223> OTHER INFORMATION: N-terminal 6(N-maleimido)hexanoyl
<400> SEQUENCE: 2
Val His Leu Thr Lys
<210> SEQ ID NO 3
<211> LENGTH: 5
<212> TYPE: PRT
<213> ORGANISM: Homo sapiens
<220> FEATURE:
<221> NAME/KEY: CARBOHYD
<222> LOCATION: (1)..(1)
<223> OTHER INFORMATION: glucose
```


#### -continued

```
<400> SEQUENCE: 3
Val His Leu Thr Lys
<210> SEQ ID NO 4
<211> LENGTH: 5
<212> TYPE: PRT
<213> ORGANISM: Homo sapiens
<220> FEATURE:
<221> NAME/KEY: CARBOHYD
<222> LOCATION: (1)..(1)
<223> OTHER INFORMATION: Glucose
<400> SEQUENCE: 4
Val His Leu Thr Cys
<210> SEQ ID NO 5
<211> LENGTH: 4
<212> TYPE: PRT
<213> ORGANISM: Homo sapiens
<400> SEQUENCE: 5
Val His Leu Thr
<210> SEQ ID NO 6
<211> LENGTH: 5
<212> TYPE: PRT
<213> ORGANISM: Homo sapiens
<400> SEQUENCE: 6
Val His Leu Thr Cys
1 5
<210> SEQ ID NO 7
<211> LENGTH: 5
<212> TYPE: PRT
<213> ORGANISM: Homo sapiens
<400> SEOUENCE: 7
Val His Leu Thr Lys
```

The invention claimed is:

1. A method for measuring the concentration of an analyte in a sample of a liquid, said method comprising contacting said sample with predetermined amounts of

- (1) a specific binding partner for said analyte, and
- (2) a detectable compound of the formula:



wherein

R and R<sub>1</sub> are the same or different and are 2,2'-bipyridyl, 4,4'-disubstituted-2,2'-bipyridyl, 5-5'-disubstituted,-2,

2'-bipyridyl, 1,10-phenanthrolinyl, 4,7-disubstituted-1, 10-phenanthrolinyl, or 5,6-disubstituted-1,10-phenanthrolinyl, wherein each substituent is a methyl, ethyl, or phenyl group,

 $R_5$  is 4-substituted-2,2'-bipyridyl or 4,4'-disubstituted-2, 2'-bipyridyl wherein the 4-substituent is the group  $B-(L)_k-Q(CH_2)_i$ - and the 4'-substituent is a methyl, ethyl or phenyl group;

R,  $R_1$  and  $R_5$  are coordinated to Os through their nitrogen atoms:

Q is O, S, or  $NR_4$  wherein  $R_4$  is hydrogen, methyl or ethyl; —L— is a divalent linker;

k is 1 or 0;

55

60

i is 1, 2, 3, 4, 5 or 6;

B comprises a ligand that binds to the specific binding partner and is selected so that the detectable compound binds competitively with the analyte to said binding partner;

d is +2 or +3;

- X and Y are anions selected from monovalent anions chloride, bromide, iodide, fluoride, tetrafluoroborate, perchlorate, and nitrate and divalent anions sulfate, carbonate or sulfite wherein x and y are independently 0, 1, 2, or 3 so that the net charge of  $X_xY_y$  is -2 or -3; 5 and
- determining electrochemically the concentration of the detectable compound not bound to the specific binding partner, wherein the concentration of the detectable compound not bound to the specific binding partner is proportional to the concentration of analyte present in the sample of fluid.
- 2. The method of claim 1 wherein the liquid sample is diluted blood, the analyte is glycosylated hemoglobin and

40

the group B in the detectable compound comprises a glycosylated peptide of the formula

Gluc-Val-His-Leu-Thr (SEQ. ID NO. 1).

- 3. The method of claim 2 further comprising the step of determining the concentration of total hemoglobin or unglycosylated hemoglobin in the liquid sample, and calculating the ratio of the concentration of glycosylated hemoglobin to unglycosylated hemoglobin.
- **4**. The method of claim **1** wherein the concentration of the unbound detectable compound is determined by dc voltammetry using an interdigitated microarray electrode.

\* \* \* \* \*



专利名称(译)	氧化还原可逆联吡啶 - 锇络合物缀合物					
公开(公告)号	<u>US7045310</u>	公开(公告)日	2006-05-16			
申请号	US09/999110	申请日	2001-11-01			
[标]申请(专利权)人(译)	BUCK HARVEY乙 邓芝DAVID					
申请(专利权)人(译)	BUCK HARVEY B. 邓芝DAVID					
当前申请(专利权)人(译)	罗氏糖尿病护理,INC.					
[标]发明人	BUCK JR HARVEY B DENG ZHI DAVID DIEBOLD ERIC R					
发明人	BUCK, JR., HARVEY B. DENG, ZHI DAVID DIEBOLD, ERIC R.					
IPC分类号	G01N33/53 G01N33/72 C07F15/00 C07K5/103 C07K7/02 C07K7/06 C07K9/00 C07K14/805 G01N27 /49 G01N33/532 G01N33/536 G01N33/58					
CPC分类号	C07F15/0026 C07K7/02 C07K7/06 C07K9/001 C07K14/805 G01N33/532 G01N33/536 G01N33/58 G01N33/723 G01N27/3277 C07K5/101 Y10T436/105831 G01N2333/805 G01N2458/30 Y10S436/805 Y10S436/806					
优先权	60/087576 1998-06-01 US					
其他公开文献	US20020090632A1					
外部链接	Espacenet USPTO					

## 摘要(译)

描述了新的联吡啶-锇络合物缀合物及其在电化学测定中的用途。可以制备氧化还原可逆锇络合物以显示独特的可逆氧化还原电位,因此可以与其他电活性氧化还原可逆物质组合使用,所述其他电活性氧化还原可逆物质在设计用于在其中使用多种电活性物质的电化学测定中具有相差至少50毫伏的氧化还原电位。在两个或更多个氧化还原偶联的缀合物系统之间没有干扰的细胞和相同样品中。

